

Test report No:
NIE: 73396RAN.010

Assessment report

RF EXPOSURE REPORT ACCORDING TO FCC 47 CFR Part 2.1091; FCC 47 CFR Part 2.1093; FCC 47 CFR Part 1.1307; FCC 47 CFR Part 1.1310

(*) Identification of item under evaluation	TETRA portable radio
(*) Trademark	Sepura
(*) Model and /or type reference	SC2024
(*) Other identification of the product	FCC ID: XX6SC2024M IC: 8739A-SC2024M HW version: PLX-2116515-02 (mod state 11) SW version: 1810 002 07367
(*) Features	TETRA, BT, Wi-Fi, GNSS
(*) Manufacturer	Sepura Limited 9000 Cambridge Research Park, Waterbeach, Cambridge CB25 9TL, UK
Test method requested, standard	FCC 47 CFR Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices. FCC 47 CFR Part 2.1093. Radiofrequency radiation exposure evaluation: portable devices. FCC 47 CFR Part 1.1307: Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared. FCC 47 CFR Part 1.1310: Radiofrequency radiation exposure limits.
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Miguel Lacave Antennas Lab Manager
Date of issue	2023-07-13
Report template No	FAN36_02 (*) "Data provided by the client"

Index

Competences and guarantees3

General conditions3

Data provided by the client.....3

Identification of the client.....3

Document history3

Appendix A: FCC RF Exposure assessment result4

 General description of the device under evaluation5

 Evaluation Results.....6

Appendix B: FCC RF Exposure information8

 RF Exposure determination of exemption.....9

 RF Exposure evaluation11

Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification, S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification, S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification, S.A.U. at the time of performance of the test.

DEKRA Testing and Certification, S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Assessment Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification, S.A.U.

General conditions

1. This report is only referred to the item that has undergone the assessment.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification, S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification, S.A.U. and the Accreditation Bodies

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item under evaluation", "Trademark", "Model and/or type reference", "General description of the device", "Other identification of the product").
2. Maximum output power, maximum antenna gains and use distance information
3. The device under evaluation consists of a hand-held portable radio with TETRA, Bluetooth, Wi-Fi and GNSS radios capability.

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

Identification of the client

Sepura Limited

Building 9000, Cambridge Research park, Waterbeach, CB25 9TL, UK

Document history

Report number	Date	Description
73396RAN.010	2023-07-13	First release

Appendix A: FCC RF Exposure assessment result

General description of the device under evaluation

The device under evaluation consists of a hand-held portable radio with TETRA, Bluetooth, Wi-Fi and GNSS radios capability.

According to the manufacturer two different exposure conditions could be possible used depending of the TETRA antennas used during the normal use.

- When TETRA antenna models “310-00006”, “320-00008”, “330-00009”, “330-00010”, “360-00001”, “390-00005” and “390-00006” are used, the separation distance between the radiating structures of the device and nearby users will be greater than 20 cm. In order to perform the assessment a conservative evaluation distance of 20 cm has been used for this exposure condition.
- When TETRA antenna models “300-00499”, “300-00662”, “300-00663”, “300-01031” and “300-01032”, are used, the separation distance between the radiating structures of the device and nearby users will be greater than 0cm. In order to perform the assessment a conservative evaluation distance of 0 cm has been used for this exposure condition.

The equipment specifications declared by the manufacturer for each supported technology and band are stated in type1lv, SC20 BT-WiFi Antenna Data 2v0, CON-REP-00323_SC2021_Operating_Instructions_V2, 310-00006 M8-SPR-09683, 320-00008 M8-SPR-09685, 330-00009 M8-SPR-09687, 330-00010 M8-SPR-09688, 360-00001 AFB-VAR, 390-00005 Manufacturer Spec EBMF-TET-5F, 390-00006 spr-02208-1 and SPR-DOC-03364-6E:

Antenna	Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Maximum Conducted Output Power (Incl. Tune-Up) (dBm)	Duty Cycle (%)	Time Averaged Conducted Power (dBm)	Antenna peak gain (dBi)	Maximum Averaged E.R.P (dBm)	Maximum Averaged E.R.P (mW)	Maximum Averaged E.I.R.P (dBm)	Maximum Averaged E.I.R.P (mW)
Internal	802.11b/g/n	2.4 GHz	2412 - 2484	17.00	100.00	17.00	2.50	17.35	54.33	19.50	89.13
Internal	Bluetooth	2.4 GHz	2400 - 2483.5	9.50	100.00	9.50	2.50	9.85	9.66	12.00	15.85
300-00499	TETRA	403-470 MHz	403 - 470	34.31	22.69	27.87	1.00	26.72	469.72	28.87	770.61
300-00662	TETRA	410-430 MHz	410 - 430	34.31	22.69	27.87	1.00	26.72	469.72	28.87	770.61
300-00663	TETRA	450-470 MHz	450 - 470	34.31	22.69	27.87	1.00	26.72	469.72	28.87	770.61
300-01031	TETRA	410-430 MHz	410 - 430	34.31	22.69	27.87	1.00	26.72	469.72	28.87	770.61
300-01032	TETRA	450-470 MHz	450 - 470	34.31	22.69	27.87	1.00	26.72	469.72	28.87	770.61
310-00006	TETRA	380-430 MHz	380 - 430	34.31	22.69	27.87	2.00	27.72	591.34	29.87	970.14
320-00008	TETRA	400-430 MHz	400 - 430	34.31	22.69	27.87	7.00	32.72	1869.97	34.87	3067.85
330-00009	TETRA	430-472 MHz	430 - 472	34.31	22.69	27.87	2.00	27.72	591.34	29.87	970.14
330-00010	TETRA	430-472 MHz	430 - 472	34.31	22.69	27.87	7.00	32.72	1869.97	34.87	3067.85
360-00001	TETRA	380-430 MHz	380 - 430	34.31	22.69	27.87	2.00	27.72	591.34	29.87	970.14
390-00005	TETRA	380-430 MHz	380 - 430	34.31	22.69	27.87	2.00	27.72	591.34	29.87	970.14
390-00006	TETRA	380-430 MHz	380 - 430	34.31	22.69	27.87	2.00	27.72	591.34	29.87	970.14

Table 1: Equipment specifications

Evaluation Results for portable exposure condition

RF Exposure Exemption evaluation:

Antenna	Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Distance (cm)	Time Averaged Conducted Power (mW)	Maximum Averaged E.R.P (mW)	§ 1.1307(b)(3).i.(B) Exposure Limit (mW)	Verdict for exemption § 1.1307(b)(3).i
Internal	802.11b/g/n	2.4 GHz	2412 - 2484	0.50	N/A	54.33	2.71	*SAR needed
Internal	Bluetooth	2.4 GHz	2400 - 2483.5	0.50	N/A	9.66	2.71	*SAR needed
300-00499	TETRA	403-470 MHz	403 - 470	0.50	612.12	N/A	25.70	*SAR needed
300-00662	TETRA	410-430 MHz	410 - 430	0.50	612.12	N/A	25.08	*SAR needed
300-00663	TETRA	450-470 MHz	450 - 470	0.50	612.12	N/A	22.01	*SAR needed
300-01031	TETRA	410-430 MHz	410 - 430	0.50	612.12	N/A	25.08	*SAR needed
300-01032	TETRA	450-470 MHz	450 - 470	0.50	612.12	N/A	22.01	*SAR needed

Table 2: FCC Exemption Evaluation Results

*SAR measurements and simultaneous transmission evaluation have been performed and are stated into DEKRA Testing and Certification, S.A.U. SAR test report num. 73396RAN.004A1.

Evaluation Results for mobile exposure condition

RF Exposure Exemption evaluation:

Antenna	Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Distance (cm)	Time Averaged Conducted Power (mW)	Maximum Averaged E.R.P (mW)	§ 1.1307(b)(3).i.(B) Exposure Limit (mW)	Verdict for exemption § 1.1307(b)(3).i
Internal	802.11b/g/n	2.4 GHz	2412 - 2484	20.00	54.33	768.00	N/A	Pass
Internal	Bluetooth	2.4 GHz	2400 - 2483.5	20.00	9.66	768.00	N/A	Pass
310-00006	TETRA	380-430 MHz	380 - 430	20.00	612.12	N/A	775.20	Pass
320-00008	TETRA	400-430 MHz	400 - 430	20.00	N/A	1869.97	816.00	MPE required
330-00009	TETRA	430-472 MHz	430 - 472	20.00	612.12	N/A	877.20	Pass
330-00010	TETRA	430-472 MHz	430 - 472	20.00	N/A	1869.97	877.20	MPE required
360-00001	TETRA	380-430 MHz	380 - 430	20.00	612.12	N/A	775.20	Pass
390-00005	TETRA	380-430 MHz	380 - 430	20.00	612.12	N/A	775.20	Pass
390-00006	TETRA	380-430 MHz	380 - 430	20.00	612.12	N/A	775.20	Pass

Table 3: FCC Exemption Evaluation Results

The device fails to comply with applicable §1.1307(b)(3).i. exemption limits, Maximum Permissible Exposure (MPE) evaluation is necessary to demonstrate compliance.

RF Exposure MPE evaluation:

TETRA Antenna	Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Distance (cm)	Power density (mW/cm ²)	FCC Occupational Exposure Limit (mW/cm ²)	Verdict
Internal	802.11b/g/n	2.4 GHz	2412 - 2484	20.00	0.02	5.00	Pass
Internal	Bluetooth	2.4 GHz	2400 - 2483.5	20.00	0.00	5.00	Pass
310-00006	TETRA	380-430 MHz	380 - 430	20.00	0.19	1.27	Pass
320-00008	TETRA	400-430 MHz	400 - 430	20.00	0.61	1.33	Pass
330-00009	TETRA	430-472 MHz	430 - 472	20.00	0.19	1.43	Pass
330-00010	TETRA	430-472 MHz	430 - 472	20.00	0.61	1.43	Pass
360-00001	TETRA	380-430 MHz	380 - 430	20.00	0.19	1.27	Pass
390-00005	TETRA	380-430 MHz	380 - 430	20.00	0.19	1.27	Pass
390-00006	TETRA	380-430 MHz	380 - 430	20.00	0.19	1.27	Pass

Table 4: FCC Evaluation Results

The computed value(s) are below the limit(s), so these modes meet the requirements stated in FCC 47 CFR Part 1.1310.

Simultaneous transmission assessment:

The device under evaluation is able to transmit simultaneously using 802.11 b/g/n, Bluetooth and TETRA transmitters, therefore the most conservative approach for the evaluation of the simultaneous transmission will be:

Simultaneous technologies and modes	Result ($\sum$ of Pout/Pmax ratios)	Verdict ($\sum \leq 1$)
802.11 b/g/n + Bluetooth 2.4 GHz + TETRA 400-430 MHz (320-00008 Antenna)	0.46	Pass

Table 5: Simultaneous Transmission assessment

Appendix B: FCC RF Exposure information

RF Exposure determination of exemption

According to FCC 47 CFR §1.1307 (b)(3) Determination of exemption:

(i) For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2), a single RF source is exempt if:

(A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

(C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

TABLE 1 TO §1.1307(b)(3)(i)(C)—SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

(ii) For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for Pth, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

Pi = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

Pth,i = the exemption threshold power (Pth) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.

ERPj = the ERP of fixed, mobile, or portable RF source j.

ERPth,j = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

Evaluated,k = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limit,k = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from §1.1310 of this chapter.

RF Exposure evaluation

Limits for Maximum Permissible Exposure (MPE) for RF sources are defined in FCC 47 CFR “§1.1310 Radiation Exposure limits, paragraph (e)”:

TABLE 1 TO §1.1310(E)(1)—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

Each supported transmission technology will be evaluated to determine if it is in compliance with limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

In order to perform the assessment, the following equations have been used for the calculations; these equations are accurate in the far-field of an antenna and will over-predict power density in the near field, where they could be used for making a "worst-case" or conservative prediction:

$$\text{Power density: } S[\text{mW} / \text{cm}^2] = \frac{P_{E.I.R.P.}[\text{mW}]}{4\pi R[\text{cm}]^2}$$

Where:

S = power density

$P_{E.I.R.P.}$ = Equivalent isotropically radiated power

R = distance to the center of radiation of the antenna (evaluation distance)

$$P_{E.I.R.P.} = P_T + G_T - L_C$$

Where:

P_T = transmitter time-averaged output power (including Duty Cycle and tune-up tolerance, if applicable)

G_T = gain of the transmitting antenna

L_C = signal attenuation in the connecting cable between the transmitter and the antenna if applicable