FCC ID : XXKWMPN07A1

Refer No. : 70629001

Report No.: 91027304-RP1 Page \_\_\_\_55 \_\_of \_\_\_142\_\_\_

## 8.4 MAXIMUM PERMISSIBLE EXPOSURE

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate theenvironment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time					
(A) Limits for Occupational / Control Exposures									
300-1,500			F/300	6					
1,500-100,000			5	6					
(B) Limits for General Population / Uncontrol Exposures									
300-1,500			F/1500	6					
1,500-100,000			1	30					

## **CALCULATIONS**

Given

$$E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P(mW) = P(W) / 1000$$
 and

$$d(cm) = d(m) / 100$$

Yields


$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

 $S = Power density in mW/cm^2$ 



FCC ID : XXKWMPN07A1

Refer No. : 70629001

Report No.: 91027304-RP1
Page \_\_\_\_56 \_\_\_of \_\_\_142\_\_\_

## **LIMIT**

Power Density Limit, S=1.0mW/cm<sup>2</sup>

## **TEST RESULTS**

Mode	Antenna Gain (dBi)	Minimum separation distance (cm)	Output Power (dBm)	Numeric antenna gain (dB)	Power Density Limit (mW/cm²)	Power Density at 20cm (mW/cm <sup>2</sup> )
IEEE 802.11b	0.69	20.0	22.71	1.17	1.00	0.043523
IEEE 802.11g	0.69	20.0	20.82	1.17	1.00	0.028166
IEEE 802.11n HT20	0.69	20.0	20.61	1.17	1.00	0.026836
IEEE 802.11n HT40	0.69	20.0	20.47	1.17	1.00	0.025985

**Remark:** For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm<sup>2</sup> even if the calculation indicates that the power density would be larger.