

User Manual

The Activity RFID Tag use for mobile resource management and student universal ID, should not take any action, the products automatically transmit a signal 433.96 MHZ every 28 seconds once, hanging belt carrying serious impact and water damage.

The changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

To comply with the FCC RF exposure compliance requirements, this device and its antenna must not be co-located or operating to conjunction with any other antenna or transmitter.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference ☐ received, including interference that may cause undesired operation.

Activity RFID Tag (ID Badge / Asset Tag)

Technical Specification

| Item | Technical Parameter |
|-----------------------|--|
| Frequency | 433.96MHz |
| Data Modulation | ASK |
| Voltage | 3V CR2025 x2 /CR2032 x1 |
| Transmission Range | 30m |
| Power Consumption | Average 50 μ A |
| Operation Temperature | -25 °C ~55°C |
| Storage Temperature | -35 °C ~65°C |
| Humidity | 10~90% |
| Dimension of Tag | 86.5L x 55W x 3.5Hmm/73L x 30W x 12Hmm |
| Weight of Tag | 20/16 Gram |

※The Activity RFID Tag automatically transmit a signal 433.96 MHZ every 28 seconds once .

Feature

ID Badge



Asset Tag

