

Maximum Permissible Exposure (MPE) & Exposure evaluation

Report identification number: 1-0403/20-01-02 MPE (FCC_ISED)


Certification numbers and labeling requirements	
FCC ID	XXZ-INTFB250
ISED number	26236-INTFB250
HVIN (Hardware Version Identification Number)	F4-A250-S, F4-A250-R, F4-A100-S, F4-A100-R
PMN (Product Marketing Name)	FB250, Fleet One
FVIN (Firmware Version Identification Number)	-/-
HMN (Host Marketing Name)	-/-

This report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:



Alexander Hnatovskiy
Lab Manager
Radio Communications & EMC



Marco Scigliano
Testing Manager
Radio Communications & EMC

EUT technologies:

Technologies:	Max. power conducted:	Max. antenna gain:	Max. EIRP
Proprietary 1626.5 to 1660.5 MHz	42.9 dBm	11.3 dBi	54.2 dBm

Prediction of MPE limit at given distance - FCC

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

where: S = Power density
 P = Power input to the antenna
 G = Antenna gain
 R = Distance to the center of radiation of the antenna
 PG = Output Power including antenna gain

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm ²)	Averaging Time (minutes)
300 -1500	f/1500	30
1500 - 100000	1.0	30

where f = Frequency (MHz)

Prediction: worst case

Technologies:	SRR	
Frequency (MHz)	2450	
PG Declared max power (EIRP)	54.2	dBm
R Distance	200	cm
S MPE limit for uncontrolled exposure	1	mW/cm ²
Calculated Power density:	0.5235	mW/cm ²
Calculated percentage of Limit:	52.35%	

The power density levels for FCC at a distance of **2 m** are below the maximum levels allowed by regulations.

Prediction of MPE limit at given distance - ISED

RSS-102, general limitations for E- and H- Field

Reference levels for general public (uncontrolled environment) exposure to time-varying electric and magnetic fields

According to: RSS 102-ISSUE 05		
Frequency Range (MHz)	Power density (W/m ²)	Reference Period (minutes)
0.003-10	--	Instantaneous*
0.1-10	--	6**
1.1-10	--	6**
10-20	2	6
20-48	$8.944 / f^{0.5}$	6
48-300	1.291	6
300-6000	$0.02619 \times f^{0.6834}$	6
6000-15000	10	6
15000-150000	10	$616000 / f^{1.2}$
150000-300000	$6.67 \times 10^{-5} \times f$	$616000 / f^{1.2}$

Note: f is frequency in MHz.
 * Based on nerve stimulation (NS).
 ** Based on specific absorption rate (SAR).

NOTE:

The resulting Limit for 1660.5 MHz is 4.16W/m²

Prediction: worst case

		1626.5 to 1660.5	
	Frequency	1660.5	MHz
R	Distance	230	cm
PG	Maximum EIRP	54.2	dBm
PG	Maximum EIRP	263.0	W
S	Power density	4.0	W/m ²
	Exclusion Limit from above:	4.16	W/m ²
	Calculated percentage of Limit:	95.11%	

The power density levels at a distance of **2.3 m** are below the maximum levels allowed by ISED regulations.