

## RF EXPOSURE INFORMATION

Transmitters operating in the 450 - 470 MHz band is required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

The MPE calculation shown below is for the antenna with a minimum separation distance of 20cm.

In accordance with Section 1.1310, the Maximum Permissible Exposure (MPE) limit for the General Population/Uncontrolled Exposure of 1.0 has been applied, i.e 0.3mW/cm<sup>2</sup>.

Friis transmission formula:  $P_d = (P \cdot G) / (4 \cdot \pi \cdot r^2)$

where:

$P_d$  = power density (mW/cm<sup>2</sup>)

$P$  = power input to the antenna (mW)

$G$  = antenna gain (numeric)

$r$  = distance to the center of radiation of the antenna (cm)

Prediction frequency = 450 – 470 MHz

Maximum peak output power with unity antenna gain = 19.37 dBm = 86.5 mW

Prediction distance = 20 cm

The power density calculated = 0.017 mW/cm<sup>2</sup>

**Results:** Calculations show that the device with described antennas complied with Maximum Permissible Exposure (MPE) limit for the General Population/Uncontrolled Exposure with a separation distance of 20cm.