

TEST REPORT

Application No.: GZCR2111021410AT
Applicant: SKULLCANDY, INC.
Address of Applicant: 6301 N Landmark Dr Park City UT 84098, Utah United States of America
Manufacturer: SKULLCANDY, INC.
Address of Manufacturer: 6301 N Landmark Dr Park City UT 84098, Utah United States of America
Equipment Under Test (EUT):
EUT Name: Mod/Mod XT
Model No.: S2FYW
Trade Mark:




Skullcandy

Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2021-11-11
Date of Test: 2021-11-12 to 2021-11-30
Date of Issue: 2021-12-03

Test Result:

Pass*

* In the configuration tested, the EUT complied with the standards specified above.



Kobe Jian
EMC Laboratory Manager



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2021-12-03		Original

Authorized for issue by				
				
		Curry Wu/Project Engineer		
				
		Ricky Liu/Reviewer		

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.1.3	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions (Below 1GHz)		ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions (Above 1GHz)		ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Duty Cycle		ANSI C63.10 (2013) Section 11.6	KDB 558074 D01 v05r02 section 6	Pass

Note:

E.U.T./EUT means Equipment Under Test.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.

Remark: The EUT with 2 supply prototypes (1st and 2nd source), Only the model 1st source was tested, since according to the declaration from the applicant, the circuitry design, PCB layout, electrical components used, internal wiring and functions were identical for all above models. Only different on some Capacitance, LED, Crystal, MIC and FPC Connector with the second supplier(Consistent parameters), and the 2nd source was performed Maximum Conducted Output Power and Radiated Emissions below 1GHz, Radiated Emissions Above 1GHz for discrepancy.

3 Contents

	Page
1 Cover Page	1
2 Test Summary.....	3
3 Contents	4
4 General Information.....	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units.....	6
4.3 Measurement Uncertainty	7
4.4 Test Location	8
4.5 Test Facility.....	8
4.6 Deviation from Standards.....	9
4.7 Abnormalities from Standard Conditions.....	9
5 Equipment List	10
6 Radio Spectrum Technical Requirement.....	13
6.1 Antenna Requirement	13
6.1.1 Test Requirement:	13
6.1.2 Conclusion	13
7 Radio Spectrum Matter Test Results	14
7.1 Conducted Peak Output Power	14
7.1.1 E.U.T. Operation.....	14
7.1.2 Test Mode Description	14
7.1.3 Test Setup Diagram	15
7.1.4 Measurement Procedure and Data.....	15
7.2 Minimum 6dB Bandwidth.....	16
7.2.1 E.U.T. Operation.....	16
7.2.2 Test Mode Description	16
7.2.3 Test Setup Diagram	16
7.2.4 Measurement Procedure and Data.....	16
7.3 Power Spectrum Density	17
7.3.1 E.U.T. Operation.....	17
7.3.2 Test Mode Description	17
7.3.3 Test Setup Diagram	17
7.3.4 Measurement Procedure and Data.....	17
7.4 Conducted Band Edges Measurement	18
7.4.1 E.U.T. Operation.....	18
7.4.2 Test Mode Description	18
7.4.3 Test Setup Diagram	18
7.4.4 Measurement Procedure and Data.....	19
7.5 Conducted Spurious Emissions.....	20
7.5.1 E.U.T. Operation.....	20
7.5.2 Test Mode Description	20
7.5.3 Test Setup Diagram	20
7.5.4 Measurement Procedure and Data.....	21



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.6	Radiated Emissions which fall in the restricted bands	22
7.6.1	E.U.T. Operation	22
7.6.2	Test Mode Description	22
7.6.3	Test Setup Diagram	23
7.6.4	Measurement Procedure and Data.....	23
7.7	Radiated Spurious Emissions (Below 1GHz)	40
7.7.1	E.U.T. Operation	40
7.7.2	Test Mode Description	40
7.7.3	Test Setup Diagram	41
7.7.4	Measurement Procedure and Data.....	41
7.8	Radiated Spurious Emissions (Above 1GHz).....	58
7.8.1	E.U.T. Operation	58
7.8.2	Test Mode Description	58
7.8.3	Test Setup Diagram	59
7.8.4	Measurement Procedure and Data.....	60
7.9	Duty Cycle	109
7.9.1	E.U.T. Operation	109
7.9.2	Test Setup Diagram	109
7.9.3	Measurement Procedure and Data.....	109
8	Test Setup Photo	110
9	EUT Constructional Details (EUT Photos).....	110
10	Appendix.....	111



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Testing Center EEC Laboratory

No.198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgsgroup.com.cn
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

Power supply:	Left earbuds: Li-Ion Polymer Battery 3.7V 45mAh (Charged by travel case) Right earbuds: Li-Ion Polymer Battery 3.7V 45mAh (Charged by travel case) travel case with backup battery: Li-Ion Polymer Battery 3.7V 500mAh (Charged by Type-c port)
Cable(s):	Type-C cable: 13.5cm unshielded
Operation Frequency:	2402MHz to 2480MHz
Bluetooth Version:	V5.2
Modulation Type:	GFSK
Date Rate:	1Mbps, 2Mbps
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	FPC Antenna
Antenna Gain:	Left Ear: 0.96dBi; Right Ear: 0.78dBi;

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--
The EUT has been tested as an independent unit.			

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Peak Output Power	$\pm 0.75\text{dB}$
Minimum 6dB Bandwidth	$\pm 3\%$
Power Spectrum Density	$\pm 2.84\text{dB}$
Conducted Band Edges Measurement	$\pm 0.75\text{dB}$
Conducted Spurious Emissions	$\pm 0.75\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 5.08\text{dB}$ (1GHz-6GHz); $\pm 5.14\text{dB}$ (above 6GHz)
Radiated Spurious Emissions (Below 1GHz)	$\pm 5.06\text{dB}$ (3m); $\pm 4.46\text{dB}$ (10m)
Radiated Spurious Emissions (Above 1GHz)	$\pm 5.08\text{dB}$ (1GHz-6GHz); $\pm 5.14\text{dB}$ (above 6GHz)
Duty Cycle	$\pm 0.37\%$
Remark: The U_{lab} (lab Uncertainty) is less than U_{CISPR} (CISPR Uncertainty), so the test results – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit; – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.	

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,
198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District,
Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian/New Zealand Regulatory Compliance Mark (RCM).

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **CNAS (Lab Code: L0167)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2018 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2017 General Requirements) for the Competence of Testing Laboratories.

- **FCC Recognized Accredited Test Firm(Registration No.: 486818)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818.

- **ISED (Registration No.: 4620B, CAB identifier: CN0052)**

SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Innovation Science and Economic Development Canada for Wireless Device Testing laboratories to test to Canadian radio equipment requirements. Registration No. 4620B, CAB identifier: CN0052.

- **VCCI (Registration No.: R-12460, C-12584, G-20107 and T-11179)**

The 10m Semi-anechoic chamber, 966 Anechoic Chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-12460, C-12584, G-20107 and T-11179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2017, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-conditions/terms-e-document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None

5 Equipment List

Conducted Peak Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Power Meter (U2021XA_Ch2)	Agilent Technologies	U2021XA_Ch2	SEM009-02	2021-05-19	2022-05-18
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
MI CABLE	SGS-EMC	0.8M	EMC2136	2021-11-01	2023-11-01
Test Software	TST	V2.0	GZE100-78	N/A	N/A

Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2021-09-16	2022-09-15
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
MI CABLE	SGS-EMC	0.8M	EMC2136	2021-11-01	2023-11-01
Test Software	TST	V2.0	GZE100-78	N/A	N/A

Power Spectrum Density					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2021-09-16	2022-09-15
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
MI CABLE	SGS-EMC	0.8M	EMC2136	2021-11-01	2023-11-01
Test Software	TST	V2.0	GZE100-78	N/A	N/A

Conducted Band Edges Measurement					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2021-09-16	2022-09-15
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
MI CABLE	SGS-EMC	0.8M	EMC2136	2021-11-01	2023-11-01
Test Software	TST	V2.0	GZE100-78	N/A	N/A

Conducted Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2021-09-16	2022-09-15
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
MI CABLE	SGS-EMC	0.8M	EMC2136	2021-11-01	2023-11-01
Test Software	TST	V2.0	GZE100-78	N/A	N/A



Radiated Emissions which fall in the restricted bands

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test Receiver(20Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2021-01-08	2022-01-07
Chamber cable(Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2020-09-09	2022-09-08
Horn Antenna(1GHz-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2019-09-25	2022-09-24
1GHz-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2021-01-08	2022-01-07
2.4GHz Filter	Micro-Tronics	BRM 50702	EMC2069	2021-01-08	2022-01-07
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2020-12-20	2023-12-19
MXE EMI Receiver(10Hz-8.4GHz)	Keysight	N9038A	EMC2139	2021-11-12	2022-11-11
EXA Signal Analyzer(10Hz-44GHz)	Keysight	N9010A	EMC2138	2021-09-16	2022-09-15
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
Notch Filter (5150-5880)	Mico-Tronics	BRM50716	EMC2168	2021-07-29	2022-07-28
Horn Antenna(14-40GHz)	SCHWARZBECK	BBHA 9170	EMC2041	2020-06-28	2023-06-27
Microwave Broadband Preamplifier (18-40GHz)	SCHWARZBECK	BBV 9721	EMC2172	2021-08-30	2022-08-29

Radiated Spurious Emissions (Below 1GHz)

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test Receiver(10Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2021-01-08	2022-01-07
Chamber cable	HangTianXing	N/A	EMC0542	2020-09-09	2022-09-08
Trilog Broadband Antenna(25MHz-1GHz)-Lab	SCHWARZBECK MESS-ELEKTRONIK	VULB 9168	SEM003-18	2019-02-22	2022-02-22
Amplifier(9kHz-1.3GHz)	HP	8447F	EMC2065	2021-05-19	2022-05-18
High Pass Filter (915MHz)	FSY MICROWAVE	HM1465-9SS	EMC2079	2021-01-08	2022-01-07
10m Semi-Anechoic Chamber	ETS	N/A	EMC0530	2019-10-20	2022-10-19
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
EMI Test Receiver(1Hz-8GHz)	Rohde & Schwarz	ESW8	EMC2220	2021-05-26	2022-05-25



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. No.198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgsgroup.com.cn
Guangzhou Branch Testing Laboratory, 中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

Radiated Spurious Emissions (Above 1GHz)

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test Receiver(20Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2021-01-08	2022-01-07
Chamber cable(Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2020-09-09	2022-09-08
Horn Antenna(1GHz-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2019-09-25	2022-09-24
1GHz-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2021-01-08	2022-01-07
2.4GHz Filter	Micro-Tronics	BRM 50702	EMC2069	2021-01-08	2022-01-07
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2020-12-20	2023-12-19
MXE EMI Receiver(10Hz-8.4GHz)	Keysight	N9038A	EMC2139	2021-11-12	2022-11-11
EXA Signal Analyzer(10Hz-44GHz)	Keysight	N9010A	EMC2138	2021-09-16	2022-09-15
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
Notch Filter (5150-5880)	Mico-Tronics	BRM50716	EMC2168	2021-07-29	2022-07-28
Horn Antenna(14-40GHz)	SCHWARZBECK	BBHA 9170	EMC2041	2020-06-28	2023-06-27
Microwave Broadband Preamplifier (18-40GHz)	SCHWARZBECK	BBV 9721	EMC2172	2021-08-30	2022-08-29

General used equipment

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DMM	Fluke	73	EMC0006	2021-07-05	2022-07-05
DMM	Fluke	73	EMC0007	2021-07-05	2022-07-05



6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

15.203 Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of 15.211, 15.213, 15.217, 15.219, 15.221, or 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is Left Ear: 0.96dBi; Right Ear: 0.78dBi.

Antenna location: Refer to internal photo.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7 Radio Spectrum Matter Test Results

7.1 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.1.3

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.1.1 E.U.T. Operation


Operating Environment:

Temperature: 21.5 °C Humidity: 53.2 % RH Atmospheric Pressure: 1003 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(1Mbps)(Right Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(2Mbps)(Left Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)(Right Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details

7.2 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)

Test Method: ANSI C63.10 (2013) Section 11.8.1

Limit:

≥500 kHz

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 21.5 °C


Humidity: 53.2 % RH

Atmospheric Pressure: 1003 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(1Mbps)(Right Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(2Mbps)(Left Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)(Right Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgsgroup.com.cn
 中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

7.3 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 21.5 °C


Humidity: 53.2 % RH

Atmospheric Pressure: 1003 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(1Mbps)(Right Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(2Mbps)(Left Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)(Right Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Testing Laboratory

No. 198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgs.com.cn
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

7.4 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 21.5 °C Humidity: 53.2 % RH Atmospheric Pressure: 1003 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(1Mbps)(Right Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(2Mbps)(Left Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)(Right Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details

7.5 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 21.5 °C


Humidity: 53.2 % RH

Atmospheric Pressure: 1003 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(1Mbps)(Right Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(2Mbps)(Left Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)(Right Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.5.3 Test Setup Diagram



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.5.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details

7.6 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 21.5 °C Humidity: 53.2 % RH Atmospheric Pressure: 1003 mbar

7.6.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(1Mbps)(Right Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(2Mbps)(Left Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)(Right Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch
Guangzhou Branch Testing Laboratory

No. 198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgs.com.cn
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com


Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low



Trace: (Discrete)

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2378.747	49.53	27.31	3.46	37.60	42.70	74.00	-31.30	HORIZONTAL	Peak
2	2390.000	47.44	27.33	3.48	37.59	40.66	74.00	-33.34	HORIZONTAL	Peak
3 *	2402.000	105.79	27.35	3.50	37.59	99.05	74.00	25.05	HORIZONTAL	Peak


Test Mode: 04; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



Trace: (Discrete)

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2389.862	50.26	27.33	3.48	37.59	43.48	74.00	-30.52	VERTICAL	Peak
2	2390.000	47.29	27.33	3.48	37.59	40.51	74.00	-33.49	VERTICAL	Peak
3 *	2402.000	100.06	27.35	3.50	37.59	93.32	74.00	19.32	VERTICAL	Peak


Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; ; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	2480.000	107.18	27.47	3.60	37.57	100.68	74.00	26.68	HORIZONTAL Peak
2	2483.500	51.73	27.48	3.53	37.57	45.17	74.00	-28.83	HORIZONTAL Peak
3	2484.296	52.06	27.48	3.53	37.57	45.50	74.00	-28.50	HORIZONTAL Peak


Test Mode: 04; Polarity: Vertical; Modulation:GFSK; ; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2480.000	101.20	27.47	3.60	37.57	94.70	74.00	20.70	VERTICAL	Peak
2	2483.500	48.84	27.48	3.53	37.57	42.28	74.00	-31.72	VERTICAL	Peak
3	2484.695	49.40	27.48	3.53	37.57	42.84	74.00	-31.16	VERTICAL	Peak


Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2387.534	50.32	27.33	3.48	37.59	43.54	74.00	-30.46
2	2390.000	47.36	27.33	3.48	37.59	40.58	74.00	-33.42
3 *	2402.000	105.18	27.35	3.50	37.59	98.44	74.00	24.44


Test Mode: 05; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2366.881	49.12	27.28	3.43	37.60	42.23	74.00	-31.77	VERTICAL	Peak
2	2390.000	47.55	27.33	3.48	37.59	40.77	74.00	-33.23	VERTICAL	Peak
3 *	2402.000	98.85	27.35	3.50	37.59	92.11	74.00	18.11	VERTICAL	Peak


Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; ; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2480.000	107.79	27.47	3.60	37.57	101.29	74.00	27.29	HORIZONTAL	Peak
2	2483.500	52.21	27.48	3.53	37.57	45.65	74.00	-28.35	HORIZONTAL	Peak
3	2484.146	52.05	27.48	3.53	37.57	45.49	74.00	-28.51	HORIZONTAL	Peak


Test Mode: 05; Polarity: Vertical; Modulation: GFSK; ; Channel: High



Trace: (Discrete)

	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2480.000	103.69	27.47	3.60	37.57	97.19	74.00	23.19	VERTICAL	Peak
2	2483.500	49.41	27.48	3.53	37.57	42.85	74.00	-31.15	VERTICAL	Peak
3	2484.820	50.35	27.48	3.53	37.57	43.79	74.00	-30.21	VERTICAL	Peak


Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low



Trace: (Discrete)

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2313.429	49.78	27.15	3.32	37.62	42.63	74.00	-31.37	HORIZONTAL	Peak
2	2390.000	47.85	27.33	3.48	37.59	41.07	74.00	-32.93	HORIZONTAL	Peak
3 *	2402.000	105.61	27.35	3.50	37.59	98.87	74.00	24.87	HORIZONTAL	Peak


Test Mode: 06; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2334.307	49.87	27.20	3.36	37.62	42.81	74.00	-31.19	VERTICAL	Peak
2	2390.000	47.59	27.33	3.48	37.59	40.81	74.00	-33.19	VERTICAL	Peak
3 *	2402.000	99.88	27.35	3.50	37.59	93.14	74.00	19.14	VERTICAL	Peak


Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; ; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2480.000	107.10	27.47	3.60	37.57	100.60	74.00	26.60	HORIZONTAL	Peak
2	2483.500	56.32	27.48	3.53	37.57	49.76	74.00	-24.24	HORIZONTAL	Peak
3	2484.046	53.51	27.48	3.53	37.57	46.95	74.00	-27.05	HORIZONTAL	Peak


Test Mode: 06; Polarity: Vertical; Modulation:GFSK; ; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2480.000	101.14	27.47	3.60	37.57	94.64	74.00	20.64	VERTICAL	Peak
2	2483.500	51.50	27.48	3.53	37.57	44.94	74.00	-29.06	VERTICAL	Peak
3	2483.896	50.32	27.48	3.53	37.57	43.76	74.00	-30.24	VERTICAL	Peak


Test Mode: 07; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low



Trace: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2386.320	49.21	27.33	3.48	37.60	42.42	74.00	-31.58	HORIZONTAL Peak
2	2390.000	46.86	27.33	3.48	37.59	40.08	74.00	-33.92	HORIZONTAL Peak
3 *	2402.000	105.26	27.35	3.50	37.59	98.52	74.00	24.52	HORIZONTAL Peak


Test Mode: 07; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2316.078	50.38	27.17	3.33	37.62	43.26	74.00	-30.74	VERTICAL	Peak
2	2390.000	46.90	27.33	3.48	37.59	40.12	74.00	-33.88	VERTICAL	Peak
3 *	2402.000	99.12	27.35	3.50	37.59	92.38	74.00	18.38	VERTICAL	Peak


Test Mode: 07; Polarity: Horizontal; Modulation:GFSK; ; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2480.000	107.71	27.47	3.60	37.57	101.21	74.00	27.21	HORIZONTAL	Peak
2	2483.500	56.45	27.48	3.53	37.57	49.89	74.00	-24.11	HORIZONTAL	Peak
3	2483.896	55.42	27.48	3.53	37.57	48.86	74.00	-25.14	HORIZONTAL	Peak

Test Mode: 07; Polarity: Vertical; Modulation:GFSK; ; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2480.000	103.66	27.47	3.60	37.57	97.16	74.00	23.16	VERTICAL	Peak
2	2483.500	53.97	27.48	3.53	37.57	47.41	74.00	-26.59	VERTICAL	Peak
3	2483.846	52.43	27.48	3.53	37.57	45.87	74.00	-28.13	VERTICAL	Peak

7.7 Radiated Spurious Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 22.3 °C


Humidity: 55.1 % RH

Atmospheric Pressure: 1003 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(1Mbps)(Right Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(2Mbps)(Left Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)(Right Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data


- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:


- Through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- Scan from 9kHz to 1 GHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

1st Source

Test Mode: 04; Polarity: Horizontal; Modulation: GFSK; ; Channel: Low




Test Mode: 04; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



Site : SGS
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuA/m	dBuA/m	dBuA		
1	49.36	24.03	13.93	1.14	27.17	11.93	29.50	-17.57	VERTICAL	QP
2	67.68	25.25	12.24	1.38	27.14	11.73	29.50	-17.77	VERTICAL	QP
3	298.27	25.52	13.57	3.16	26.55	15.70	35.60	-19.90	VERTICAL	QP
4	582.74	26.95	19.25	5.06	28.19	23.07	35.60	-12.53	VERTICAL	QP
5	774.16	26.59	22.25	6.08	28.05	26.87	35.60	-8.73	VERTICAL	QP
6	989.54	25.96	24.20	7.37	27.67	29.86	43.50	-13.64	VERTICAL	QP


Test Mode: 05; Polarity: Horizontal; Modulation: GFSK; ; Channel: Low



Site : SGS
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuA/m	dBuA/m	dBuA		
1	43.97	24.52	13.80	1.12	27.17	12.27	29.50	-17.23	HORIZONTAL	QP
2	69.11	24.90	12.05	1.40	27.13	11.22	29.50	-18.28	HORIZONTAL	QP
3	292.06	23.93	13.43	3.14	26.56	13.94	35.60	-21.66	HORIZONTAL	QP
4	597.22	25.75	19.80	5.14	28.21	22.48	35.60	-13.12	HORIZONTAL	QP
5	758.04	26.07	22.20	6.01	28.08	26.20	35.60	-9.40	HORIZONTAL	QP
6	996.50	25.84	24.27	7.43	27.66	29.88	43.50	-13.62	HORIZONTAL	QP


Test Mode: 05; Polarity: Vertical; Modulation: GFSK; ; Channel: Low



Site : SGS
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuA/m	dBuA/m	dBuA		
1	47.49	25.30	13.98	1.13	27.17	13.24	29.50	-16.26	VERTICAL	QP
2	68.39	25.32	12.15	1.39	27.14	11.72	29.50	-17.78	VERTICAL	QP
3	283.98	24.98	13.28	3.11	26.56	14.81	35.60	-20.79	VERTICAL	QP
4	547.10	27.63	18.60	4.76	28.09	22.90	35.60	-12.70	VERTICAL	QP
5	771.45	27.09	22.22	6.08	28.06	27.33	35.60	-8.27	VERTICAL	QP
6	965.54	26.22	23.90	7.25	27.71	29.66	43.50	-13.84	VERTICAL	QP


Test Mode: 06; Polarity: Horizontal; Modulation: GFSK; ; Channel: Low



Site : SGS
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dBuV		
1	45.22	24.82	13.86	1.12	27.17	12.63	29.50	-16.87	HORIZONTAL	QP
2	129.47	24.31	12.03	1.96	27.00	11.30	33.10	-21.80	HORIZONTAL	QP
3	285.98	24.82	13.32	3.11	26.56	14.69	35.60	-20.91	HORIZONTAL	QP
4	586.84	27.61	19.35	5.06	28.19	23.83	35.60	-11.77	HORIZONTAL	QP
5	747.48	27.06	22.15	5.97	28.10	27.08	35.60	-8.52	HORIZONTAL	QP
6	1000.00	25.34	24.30	7.43	27.66	29.41	43.50	-14.09	HORIZONTAL	QP


Test Mode: 06; Polarity: Vertical; Modulation: GFSK; ; Channel: Low



Site : SGS
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dBuV		
1	47.16	25.02	13.96	1.13	27.17	12.94	29.50	-16.56	VERTICAL	QP
2	63.98	23.66	12.90	1.32	27.15	10.73	29.50	-18.77	VERTICAL	QP
3	159.23	25.20	13.63	2.33	26.80	14.36	33.10	-18.74	VERTICAL	QP
4	578.67	27.82	19.15	5.02	28.18	23.81	35.60	-11.79	VERTICAL	QP
5	758.04	26.55	22.20	6.01	28.08	26.68	35.60	-8.92	VERTICAL	QP
6	993.01	26.36	24.23	7.37	27.67	30.29	43.50	-13.21	VERTICAL	QP


Test Mode: 07; Polarity: Horizontal; Modulation: GFSK; ; Channel: Low



Site : SGS
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dBuV		
1	49.01	25.00	13.95	1.14	27.17	12.92	29.50	-16.58	HORIZONTAL	QP
2	126.33	24.72	11.63	1.93	27.01	11.27	33.10	-21.83	HORIZONTAL	QP
3	292.06	25.06	13.43	3.14	26.56	15.07	35.60	-20.53	HORIZONTAL	QP
4	599.32	26.45	19.90	5.14	28.21	23.28	35.60	-12.32	HORIZONTAL	QP
5	766.06	27.08	22.20	6.05	28.06	27.27	35.60	-8.33	HORIZONTAL	QP
6	986.07	25.00	24.17	7.37	27.68	28.86	43.50	-14.64	HORIZONTAL	QP

Test Mode: 07; Polarity: Vertical; Modulation: GFSK; ; Channel: Low




Site : SGS
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dBuV		
1	47.49	26.00	13.98	1.13	27.17	13.94	29.50	-15.56	VERTICAL	QP
2	60.92	23.73	13.25	1.27	27.16	11.09	29.50	-18.41	VERTICAL	QP
3	150.01	25.09	13.80	2.24	26.84	14.29	33.10	-18.81	VERTICAL	QP
4	572.61	27.11	18.97	4.98	28.17	22.89	35.60	-12.71	VERTICAL	QP
5	793.40	26.21	22.53	6.14	28.04	26.84	35.60	-8.76	VERTICAL	QP
6	1000.00	25.75	24.30	7.43	27.66	29.82	43.50	-13.68	VERTICAL	QP

2nd Source


Test Mode: 04; Polarity: Horizontal; Modulation: GFSK; ; Channel: Low




Site : SGS
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dBuV		
1	48.50	24.81	13.98	1.14	27.17	12.76	29.50	-16.74	HORIZONTAL	QP
2	69.11	25.49	12.05	1.40	27.13	11.81	29.50	-17.69	HORIZONTAL	QP
3	280.02	25.45	13.20	3.09	26.57	15.17	35.60	-20.43	HORIZONTAL	QP
4	599.32	25.93	19.90	5.14	28.21	22.76	35.60	-12.84	HORIZONTAL	QP
5	760.70	26.73	22.20	6.01	28.07	26.87	35.60	-8.73	HORIZONTAL	QP
6	986.07	25.96	24.17	7.37	27.68	29.82	43.50	-13.68	HORIZONTAL	QP

Test Mode: 04; Polarity: Vertical; Modulation:GFSK; ; Channel:Low




Test Mode: 05; Polarity: Horizontal; Modulation: GFSK; ; Channel: Low



Site : SGS
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dBuV		
1	50.06	24.76	13.90	1.14	27.17	12.63	29.50	-16.87	HORIZONTAL	QP
2	129.01	24.05	11.95	1.96	27.00	10.96	33.10	-22.14	HORIZONTAL	QP
3	276.12	25.49	13.05	3.07	26.57	15.04	35.60	-20.56	HORIZONTAL	QP
4	599.32	27.02	19.90	5.14	28.21	23.85	35.60	-11.75	HORIZONTAL	QP
5	782.35	27.23	22.35	6.11	28.05	27.64	35.60	-7.96	HORIZONTAL	QP
6	989.54	25.36	24.20	7.37	27.67	29.26	43.50	-14.24	HORIZONTAL	QP

Test Mode: 05; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



Site : SGS
Job :
Model :
Power :
Test Mode :


	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dBuV		
1	42.01	24.66	13.70	1.11	27.17	12.30	29.50	-17.20	VERTICAL	QP
2	127.66	25.10	11.75	1.94	27.00	11.79	33.10	-21.31	VERTICAL	QP
3	296.18	24.29	13.52	3.15	26.55	14.41	35.60	-21.19	VERTICAL	QP
4	599.32	26.83	19.90	5.14	28.21	23.66	35.60	-11.94	VERTICAL	QP
5	774.16	27.54	22.25	6.08	28.05	27.82	35.60	-7.78	VERTICAL	QP
6	986.07	25.54	24.17	7.37	27.68	29.40	43.50	-14.10	VERTICAL	QP



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


Test Mode: 06; Polarity: Horizontal; Modulation: GFSK; ; Channel: Low



Site : SGS
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dBuV		
1	45.38	24.79	13.87	1.12	27.17	12.61	29.50	-16.89	HORIZONTAL	QP
2	63.98	24.29	12.90	1.32	27.15	11.36	29.50	-18.14	HORIZONTAL	QP
3	291.04	24.64	13.42	3.14	26.56	14.64	35.60	-20.96	HORIZONTAL	QP
4	588.91	27.48	19.43	5.06	28.20	23.77	35.60	-11.83	HORIZONTAL	QP
5	782.35	27.22	22.35	6.11	28.05	27.63	35.60	-7.97	HORIZONTAL	QP
6	962.16	26.81	23.90	7.25	27.72	30.24	43.50	-13.26	HORIZONTAL	QP


Test Mode: 06; Polarity: Vertical; Modulation: GFSK; ; Channel: Low



Site : SGS
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dBuV		
1	49.01	24.31	13.95	1.14	27.17	12.23	29.50	-17.27	VERTICAL	QP
2	64.43	24.54	12.83	1.34	27.15	11.56	29.50	-17.94	VERTICAL	QP
3	266.61	25.51	12.50	3.02	26.58	14.45	35.60	-21.15	VERTICAL	QP
4	599.32	26.04	19.90	5.14	28.21	22.87	35.60	-12.73	VERTICAL	QP
5	790.62	26.10	22.50	6.14	28.04	26.70	35.60	-8.90	VERTICAL	QP
6	958.79	26.05	23.90	7.18	27.73	29.40	35.60	-6.20	VERTICAL	QP


Test Mode: 07; Polarity: Horizontal; Modulation: GFSK; ; Channel: Low



Site : SGS
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dBuV		
1	47.49	25.42	13.98	1.13	27.17	13.36	29.50	-16.14	HORIZONTAL	QP
2	121.12	25.39	11.00	1.88	27.03	11.24	33.10	-21.86	HORIZONTAL	QP
3	295.15	24.65	13.50	3.15	26.55	14.75	35.60	-20.85	HORIZONTAL	QP
4	588.91	27.03	19.43	5.06	28.20	23.32	35.60	-12.28	HORIZONTAL	QP
5	766.06	26.63	22.20	6.05	28.06	26.82	35.60	-8.78	HORIZONTAL	QP
6	929.01	26.91	23.80	7.06	27.80	29.97	35.60	-5.63	HORIZONTAL	QP

Test Mode: 07; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



Site : SGS
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dBuV		
1	45.69	23.91	13.89	1.12	27.17	11.75	29.50	-17.75	VERTICAL	QP
2	122.40	24.92	11.17	1.89	27.02	10.96	33.10	-22.14	VERTICAL	QP
3	277.09	24.82	13.10	3.09	26.57	14.44	35.60	-21.16	VERTICAL	QP
4	584.79	27.37	19.30	5.06	28.19	23.54	35.60	-12.06	VERTICAL	QP
5	796.18	26.43	22.57	6.14	28.03	27.11	35.60	-8.49	VERTICAL	QP
6	975.75	26.02	24.03	7.31	27.69	29.67	43.50	-13.83	VERTICAL	QP

7.8 Radiated Spurious Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 52.5 °C Humidity: 22.2 % RH Atmospheric Pressure: 1003 mbar

7.8.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(1Mbps)(Right Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(2Mbps)(Left Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)(Right Earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

2) Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

3) The field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


1st Source

Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1592.571	48.98	25.57	2.80	37.98	39.37	74.00	-34.63	HORIZONTAL Peak
2	4193.872	49.48	30.15	4.60	36.81	47.42	74.00	-26.58	HORIZONTAL Peak
3	4804.000	46.89	31.42	5.40	36.83	46.88	74.00	-27.12	HORIZONTAL Peak
4	6432.732	48.20	33.83	5.88	36.99	50.92	74.00	-23.08	HORIZONTAL Peak
5	7206.000	47.67	35.54	5.98	37.38	51.81	74.00	-22.19	HORIZONTAL Peak
6	9608.000	45.34	38.37	7.07	37.42	53.36	74.00	-20.64	HORIZONTAL Peak

Test Mode: 04; Polarity: Vertical; Modulation:GFSK; ; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1677.621	48.73	25.68	2.80	37.91	39.30	74.00	-34.70	VERTICAL	Peak
2	4206.011	49.49	30.18	4.60	36.81	47.46	74.00	-26.54	VERTICAL	Peak
3	4804.000	48.22	31.42	5.40	36.83	48.21	74.00	-25.79	VERTICAL	Peak
4	6995.172	47.55	35.00	5.81	37.25	51.11	74.00	-22.89	VERTICAL	Peak
5	7206.000	46.06	35.54	5.98	37.38	50.20	74.00	-23.80	VERTICAL	Peak
6	9608.000	44.95	38.37	7.07	37.42	52.97	74.00	-21.03	VERTICAL	Peak

Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; ; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1692.231	48.62	25.70	2.80	37.89	39.23	74.00	-34.77	HORIZONTAL Peak
2	4304.400	49.00	30.48	4.65	36.81	47.32	74.00	-26.68	HORIZONTAL Peak
3	4880.000	47.40	31.54	5.50	36.84	47.60	74.00	-26.40	HORIZONTAL Peak
4	6974.982	46.86	34.97	5.81	37.23	50.41	74.00	-23.59	HORIZONTAL Peak
5	7320.000	45.49	36.00	6.13	37.43	50.19	74.00	-23.81	HORIZONTAL Peak
6	9760.000	44.38	38.50	7.02	37.41	52.49	74.00	-21.51	HORIZONTAL Peak


Test Mode: 04; Polarity: Vertical; Modulation:GFSK; ; Channel:middle



race: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1634.543	49.16	25.62	2.80	37.95	39.63	74.00	-34.37	VERTICAL	Peak
2	3587.818	50.47	29.02	4.49	36.91	47.07	74.00	-26.93	VERTICAL	Peak
3	4880.000	47.56	31.54	5.50	36.84	47.76	74.00	-26.24	VERTICAL	Peak
4	6698.373	47.69	34.38	5.83	37.08	50.82	74.00	-23.18	VERTICAL	Peak
5	7320.000	44.83	36.00	6.13	37.43	49.53	74.00	-24.47	VERTICAL	Peak
6	9760.000	44.37	38.50	7.02	37.41	52.48	74.00	-21.52	VERTICAL	Peak


Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; ; Channel:High



Trace: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1667.951	48.14	25.66	2.80	37.91	38.69	74.00	-35.31	HORIZONTAL	Peak
2	4230.396	49.32	30.26	4.61	36.81	47.38	74.00	-26.62	HORIZONTAL	Peak
3	4960.000	47.97	31.65	5.65	36.84	48.43	74.00	-25.57	HORIZONTAL	Peak
4	6995.172	47.24	35.00	5.81	37.25	50.80	74.00	-23.20	HORIZONTAL	Peak
5	7440.000	45.32	36.27	6.22	37.47	50.34	74.00	-23.66	HORIZONTAL	Peak
6	9920.000	44.36	38.65	6.96	37.40	52.57	74.00	-21.43	HORIZONTAL	Peak

Test Mode: 04; Polarity: Vertical; Modulation:GFSK; ; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1574.265	48.01	25.56	2.80	38.00	38.37	74.00	-35.63	VERTICAL	Peak
2	4206.011	48.62	30.18	4.60	36.81	46.59	74.00	-27.41	VERTICAL	Peak
3	4960.000	48.39	31.65	5.65	36.84	48.85	74.00	-25.15	VERTICAL	Peak
4	6340.436	48.33	33.57	5.94	36.97	50.87	74.00	-23.13	VERTICAL	Peak
5	7440.000	45.47	36.27	6.22	37.47	50.49	74.00	-23.51	VERTICAL	Peak
6	9920.000	44.16	38.65	6.96	37.40	52.37	74.00	-21.63	VERTICAL	Peak

Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low



race: (Discrete)

	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1682.477	49.19	25.68	2.80	37.91	39.76	74.00	-34.24	HORIZONTAL	Peak
2	4230.396	49.23	30.26	4.61	36.81	47.29	74.00	-26.71	HORIZONTAL	Peak
3	4804.000	47.26	31.42	5.40	36.83	47.25	74.00	-26.75	HORIZONTAL	Peak
4	6995.172	47.17	35.00	5.81	37.25	50.73	74.00	-23.27	HORIZONTAL	Peak
5	7206.000	46.20	35.54	5.98	37.38	50.34	74.00	-23.66	HORIZONTAL	Peak
6	9608.000	45.55	38.37	7.07	37.42	53.57	74.00	-20.43	HORIZONTAL	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions of Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Testing Center EEC Laboratory.

中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sqs.china@sqs.com


Test Mode: 05; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



Trace: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1677.621	49.35	25.68	2.80	37.91	39.92	74.00	-34.08	VERTICAL	Peak
2	4086.182	50.28	29.92	4.60	36.80	48.00	74.00	-26.00	VERTICAL	Peak
3	4804.000	47.66	31.42	5.40	36.83	47.65	74.00	-26.35	VERTICAL	Peak
4	6088.991	49.47	32.61	6.15	36.92	51.31	74.00	-22.69	VERTICAL	Peak
5	7206.000	46.73	35.54	5.98	37.38	50.87	74.00	-23.13	VERTICAL	Peak
6	9608.000	45.11	38.37	7.07	37.42	53.13	74.00	-20.87	VERTICAL	Peak

Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; ; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1644.019	47.98	25.63	2.80	37.93	38.48	74.00	-35.52	HORIZONTAL	Peak
2	3386.297	51.66	28.83	4.10	36.99	47.60	74.00	-26.40	HORIZONTAL	Peak
3	4880.000	46.72	31.54	5.50	36.84	46.92	74.00	-27.08	HORIZONTAL	Peak
4	6995.172	46.54	35.00	5.81	37.25	50.10	74.00	-23.90	HORIZONTAL	Peak
5	7320.000	45.45	36.00	6.13	37.43	50.15	74.00	-23.85	HORIZONTAL	Peak
6	9760.000	45.37	38.50	7.02	37.41	53.48	74.00	-20.52	HORIZONTAL	Peak

Test Mode: 05; Polarity: Vertical; Modulation:GFSK; ; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1677.621	48.92	25.68	2.80	37.91	39.49	74.00	-34.51	VERTICAL	Peak
2	4015.929	49.06	29.82	4.60	36.80	46.68	74.00	-27.32	VERTICAL	Peak
3	4880.000	47.20	31.54	5.50	36.84	47.40	74.00	-26.60	VERTICAL	Peak
4	6377.195	48.31	33.68	5.91	36.98	50.92	74.00	-23.08	VERTICAL	Peak
5	7320.000	45.59	36.00	6.13	37.43	50.29	74.00	-23.71	VERTICAL	Peak
6	9760.000	45.10	38.50	7.02	37.41	53.21	74.00	-20.79	VERTICAL	Peak

Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; ; Channel:High




	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1658.337	49.46	25.65	2.80	37.93	39.98	74.00	-34.02	HORIZONTAL Peak
2	4133.699	49.86	30.01	4.60	36.80	47.67	74.00	-26.33	HORIZONTAL Peak
3	4960.000	47.82	31.65	5.65	36.84	48.28	74.00	-25.72	HORIZONTAL Peak
4	6679.040	48.39	34.33	5.83	37.07	51.48	74.00	-22.52	HORIZONTAL Peak
5	7440.000	47.15	36.27	6.22	37.47	52.17	74.00	-21.83	HORIZONTAL Peak
6	9920.000	44.59	38.65	6.96	37.40	52.80	74.00	-21.20	HORIZONTAL Peak

Test Mode: 05; Polarity: Vertical; Modulation:GFSK; ; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1677.621	48.92	25.68	2.80	37.91	39.49	74.00	-34.51	VERTICAL	Peak
2	4291.977	49.37	30.45	4.64	36.81	47.65	74.00	-26.35	VERTICAL	Peak
3	4960.000	48.71	31.65	5.65	36.84	49.17	74.00	-24.83	VERTICAL	Peak
4	6974.982	47.88	34.97	5.81	37.23	51.43	74.00	-22.57	VERTICAL	Peak
5	7440.000	46.44	36.27	6.22	37.47	51.46	74.00	-22.54	VERTICAL	Peak
6	9920.000	44.38	38.65	6.96	37.40	52.59	74.00	-21.41	VERTICAL	Peak


Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low



race: (Discrete)


	Freq	ReadAntenna	Cable	Preamp	Limit	Over		
	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1606.441	48.21	25.59	2.80	37.98	38.62	74.00	-35.38 HORIZONTAL Peak
2	4004.339	49.39	29.80	4.60	36.80	46.99	74.00	-27.01 HORIZONTAL Peak
3	4804.000	47.03	31.42	5.40	36.83	47.02	74.00	-26.98 HORIZONTAL Peak
4	6001.626	50.04	32.40	6.20	36.90	51.74	74.00	-22.26 HORIZONTAL Peak
5	7206.000	46.86	35.54	5.98	37.38	51.00	74.00	-23.00 HORIZONTAL Peak
6	9608.000	44.43	38.37	7.07	37.42	52.45	74.00	-21.55 HORIZONTAL Peak

Test Mode: 06; Polarity: Vertical; Modulation:GFSK; ; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1672.779	48.02	25.67	2.80	37.91	38.58	74.00	-35.42	VERTICAL	Peak
2	4133.699	49.65	30.01	4.60	36.80	47.46	74.00	-26.54	VERTICAL	Peak
3	4804.000	47.22	31.42	5.40	36.83	47.21	74.00	-26.79	VERTICAL	Peak
4	6995.172	47.48	35.00	5.81	37.25	51.04	74.00	-22.96	VERTICAL	Peak
5	7206.000	45.81	35.54	5.98	37.38	49.95	74.00	-24.05	VERTICAL	Peak
6	9608.000	44.79	38.37	7.07	37.42	52.81	74.00	-21.19	VERTICAL	Peak

Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; ; Channel:middle




	Freq	ReadAntenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	1672.779	49.26	25.67	2.80	37.91	39.82	74.00	-34.18
2	4133.699	49.79	30.01	4.60	36.80	47.60	74.00	-26.40
3	4880.000	47.49	31.54	5.50	36.84	47.69	74.00	-26.31
4	6954.852	46.52	34.95	5.81	37.21	50.07	74.00	-23.93
5	7320.000	44.60	36.00	6.13	37.43	49.30	74.00	-24.70
6	9760.000	45.28	38.50	7.02	37.41	53.39	74.00	-20.61

Test Mode: 06; Polarity: Vertical; Modulation:GFSK; ; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1331.288	50.47	25.28	2.60	38.29	40.06	74.00	-33.94	VERTICAL	Peak
2	4304.400	50.26	30.48	4.65	36.81	48.58	74.00	-25.42	VERTICAL	Peak
3	4880.000	46.49	31.54	5.50	36.84	46.69	74.00	-27.31	VERTICAL	Peak
4	5967.033	49.18	32.37	6.10	36.90	50.75	74.00	-23.25	VERTICAL	Peak
5	7320.000	44.99	36.00	6.13	37.43	49.69	74.00	-24.31	VERTICAL	Peak
6	9760.000	44.62	38.50	7.02	37.41	52.73	74.00	-21.27	VERTICAL	Peak


Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; ; Channel:High



Trace: (Discrete)


	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1615.754	48.20	25.60	2.80	37.95	38.65	74.00	-35.35	HORIZONTAL Peak
2	4218.186	49.44	30.22	4.60	36.81	47.45	74.00	-26.55	HORIZONTAL Peak
3	4960.000	47.50	31.65	5.65	36.84	47.96	74.00	-26.04	HORIZONTAL Peak
4	5664.525	49.31	31.97	6.37	36.89	50.76	74.00	-23.24	HORIZONTAL Peak
5	7440.000	46.52	36.27	6.22	37.47	51.54	74.00	-22.46	HORIZONTAL Peak
6	9920.000	43.97	38.65	6.96	37.40	52.18	74.00	-21.82	HORIZONTAL Peak

Test Mode: 06; Polarity: Vertical; Modulation:GFSK; ; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1672.779	49.38	25.67	2.80	37.91	39.94	74.00	-34.06	VERTICAL	Peak
2	4218.186	50.42	30.22	4.60	36.81	48.43	74.00	-25.57	VERTICAL	Peak
3	4960.000	47.42	31.65	5.65	36.84	47.88	74.00	-26.12	VERTICAL	Peak
4	5471.422	49.20	31.80	6.31	36.88	50.43	74.00	-23.57	VERTICAL	Peak
5	7440.000	46.26	36.27	6.22	37.47	51.28	74.00	-22.72	VERTICAL	Peak
6	9920.000	44.59	38.65	6.96	37.40	52.80	74.00	-21.20	VERTICAL	Peak


Test Mode: 07; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low



race: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1658.337	49.04	25.65	2.80	37.93	39.56	74.00	-34.44	HORIZONTAL	Peak
2	4206.011	49.16	30.18	4.60	36.81	47.13	74.00	-26.87	HORIZONTAL	Peak
3	4804.000	47.85	31.42	5.40	36.83	47.84	74.00	-26.16	HORIZONTAL	Peak
4	6995.172	46.92	35.00	5.81	37.25	50.48	74.00	-23.52	HORIZONTAL	Peak
5	7206.000	46.12	35.54	5.98	37.38	50.26	74.00	-23.74	HORIZONTAL	Peak
6	9608.000	44.84	38.37	7.07	37.42	52.86	74.00	-21.14	HORIZONTAL	Peak

Test Mode: 07; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1682.477	49.22	25.68	2.80	37.91	39.79	74.00	-34.21	VERTICAL	Peak
2	4133.699	48.74	30.01	4.60	36.80	46.55	74.00	-27.45	VERTICAL	Peak
3	4804.000	46.77	31.42	5.40	36.83	46.76	74.00	-27.24	VERTICAL	Peak
4	5730.396	48.90	32.07	6.25	36.89	50.33	74.00	-23.67	VERTICAL	Peak
5	7206.000	46.97	35.54	5.98	37.38	51.11	74.00	-22.89	VERTICAL	Peak
6	9608.000	45.26	38.37	7.07	37.42	53.28	74.00	-20.72	VERTICAL	Peak


Test Mode: 07; Polarity: Horizontal; Modulation:GFSK; ; Channel:middle



Trace: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	Remark
1	1601.804	48.44	25.58	2.80	37.98	38.84	74.00	-35.16	HORIZONTAL Peak
2	4230.396	48.41	30.26	4.61	36.81	46.47	74.00	-27.53	HORIZONTAL Peak
3	4880.000	46.67	31.54	5.50	36.84	46.87	74.00	-27.13	HORIZONTAL Peak
4	5567.137	48.99	31.86	6.33	36.89	50.29	74.00	-23.71	HORIZONTAL Peak
5	7320.000	45.14	36.00	6.13	37.43	49.84	74.00	-24.16	HORIZONTAL Peak
6	9760.000	44.82	38.50	7.02	37.41	52.93	74.00	-21.07	HORIZONTAL Peak

Test Mode: 07; Polarity: Vertical; Modulation:GFSK; ; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1597.181	48.36	25.58	2.80	37.98	38.76	74.00	-35.24	VERTICAL	Peak
2	4304.400	48.21	30.48	4.65	36.81	46.53	74.00	-27.47	VERTICAL	Peak
3	4880.000	46.39	31.54	5.50	36.84	46.59	74.00	-27.41	VERTICAL	Peak
4	6545.263	48.88	34.06	5.84	37.03	51.75	74.00	-22.25	VERTICAL	Peak
5	7320.000	45.09	36.00	6.13	37.43	49.79	74.00	-24.21	VERTICAL	Peak
6	9760.000	45.17	38.50	7.02	37.41	53.28	74.00	-20.72	VERTICAL	Peak

Test Mode: 07; Polarity: Horizontal; Modulation:GFSK; ; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1682.477	48.54	25.68	2.80	37.91	39.11	74.00	-34.89	HORIZONTAL	Peak
2	4206.011	49.10	30.18	4.60	36.81	47.07	74.00	-26.93	HORIZONTAL	Peak
3	4960.000	48.19	31.65	5.65	36.84	48.65	74.00	-25.35	HORIZONTAL	Peak
4	6974.982	47.51	34.97	5.81	37.23	51.06	74.00	-22.94	HORIZONTAL	Peak
5	7440.000	45.31	36.27	6.22	37.47	50.33	74.00	-23.67	HORIZONTAL	Peak
6	9920.000	44.28	38.65	6.96	37.40	52.49	74.00	-21.51	HORIZONTAL	Peak


Test Mode: 07; Polarity: Vertical; Modulation:GFSK; ; Channel:High



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1672.779	49.05	25.67	2.80	37.91	39.61	74.00	-34.39	VERTICAL	Peak
2	4242.641	49.72	30.30	4.62	36.81	47.83	74.00	-26.17	VERTICAL	Peak
3	4960.000	47.48	31.65	5.65	36.84	47.94	74.00	-26.06	VERTICAL	Peak
4	6195.508	48.52	32.96	6.07	36.94	50.61	74.00	-23.39	VERTICAL	Peak
5	7440.000	45.54	36.27	6.22	37.47	50.56	74.00	-23.44	VERTICAL	Peak
6	9920.000	44.85	38.65	6.96	37.40	53.06	74.00	-20.94	VERTICAL	Peak


2nd Source

Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1248.023	49.81	25.02	2.34	38.35	38.82	74.00	-35.18	HORIZONTAL	Peak
2	4401.242	48.66	30.68	4.70	36.81	47.23	74.00	-26.77	HORIZONTAL	Peak
3	4804.000	46.66	31.42	5.40	36.83	46.65	74.00	-27.35	HORIZONTAL	Peak
4	6050.413	48.82	32.52	6.17	36.91	50.60	74.00	-23.40	HORIZONTAL	Peak
5	7206.000	47.24	35.54	5.98	37.38	51.38	74.00	-22.62	HORIZONTAL	Peak
6	9608.000	45.22	38.37	7.07	37.42	53.24	74.00	-20.76	HORIZONTAL	Peak

Test Mode: 04; Polarity: Vertical; Modulation:GFSK; ; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1629.297	48.25	25.61	2.80	37.95	38.71	74.00	-35.29	VERTICAL	Peak
2	4276.910	49.06	30.42	4.63	36.81	47.30	74.00	-26.70	VERTICAL	Peak
3	4804.000	47.93	31.42	5.40	36.83	47.92	74.00	-26.08	VERTICAL	Peak
4	5318.830	50.04	31.77	6.08	36.88	51.01	74.00	-22.99	VERTICAL	Peak
5	7206.000	45.67	35.54	5.98	37.38	49.81	74.00	-24.19	VERTICAL	Peak
6	9608.000	44.48	38.37	7.07	37.42	52.50	74.00	-21.50	VERTICAL	Peak

Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; ; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1264.042	49.84	25.08	2.42	38.33	39.01	74.00	-34.99	HORIZONTAL Peak
2	3998.083	49.45	29.79	4.60	36.80	47.04	74.00	-26.96	HORIZONTAL Peak
3	4880.000	47.05	31.54	5.50	36.84	47.25	74.00	-26.75	HORIZONTAL Peak
4	5312.329	49.19	31.77	6.08	36.87	50.17	74.00	-23.83	HORIZONTAL Peak
5	7320.000	45.26	36.00	6.13	37.43	49.96	74.00	-24.04	HORIZONTAL Peak
6	9760.000	43.85	38.50	7.02	37.41	51.96	74.00	-22.04	HORIZONTAL Peak

Test Mode: 04; Polarity: Vertical; Modulation:GFSK; ; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1317.986	49.67	25.25	2.60	38.29	39.23	74.00	-34.77	VERTICAL	Peak
2	3329.264	50.67	28.78	4.07	37.02	46.50	74.00	-27.50	VERTICAL	Peak
3	4880.000	47.44	31.54	5.50	36.84	47.64	74.00	-26.36	VERTICAL	Peak
4	5537.109	49.30	31.83	6.37	36.89	50.61	74.00	-23.39	VERTICAL	Peak
5	7320.000	44.72	36.00	6.13	37.43	49.42	74.00	-24.58	VERTICAL	Peak
6	9760.000	43.97	38.50	7.02	37.41	52.08	74.00	-21.92	VERTICAL	Peak

Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; ; Channel:High




	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1537.197	47.97	25.53	2.80	38.07	38.23	74.00	-35.77	HORIZONTAL Peak
2	3503.397	50.92	28.91	4.33	36.94	47.22	74.00	-26.78	HORIZONTAL Peak
3	4960.000	47.68	31.65	5.65	36.84	48.14	74.00	-25.86	HORIZONTAL Peak
4	5563.739	49.38	31.86	6.33	36.89	50.68	74.00	-23.32	HORIZONTAL Peak
5	7440.000	45.03	36.27	6.22	37.47	50.05	74.00	-23.95	HORIZONTAL Peak
6	9920.000	44.00	38.65	6.96	37.40	52.21	74.00	-21.79	HORIZONTAL Peak

Test Mode: 04; Polarity: Vertical; Modulation:GFSK; ; Channel:High




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1297.155	48.46	25.19	2.58	38.31	37.92	74.00	-36.08	VERTICAL	Peak
2	4098.631	48.46	29.94	4.60	36.80	46.20	74.00	-27.80	VERTICAL	Peak
3	4960.000	47.99	31.65	5.65	36.84	48.45	74.00	-25.55	VERTICAL	Peak
4	6751.938	47.34	34.56	5.82	37.10	50.62	74.00	-23.38	VERTICAL	Peak
5	7440.000	45.12	36.27	6.22	37.47	50.14	74.00	-23.86	VERTICAL	Peak
6	9920.000	43.93	38.65	6.96	37.40	52.14	74.00	-21.86	VERTICAL	Peak

Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1665.453	49.05	25.65	2.80	37.91	39.59	74.00	-34.41	HORIZONTAL	Peak
2	4323.463	48.77	30.54	4.67	36.81	47.17	74.00	-26.83	HORIZONTAL	Peak
3	4804.000	47.01	31.42	5.40	36.83	47.00	74.00	-27.00	HORIZONTAL	Peak
4	5532.137	49.17	31.83	6.37	36.89	50.48	74.00	-23.52	HORIZONTAL	Peak
5	7206.000	46.10	35.54	5.98	37.38	50.24	74.00	-23.76	HORIZONTAL	Peak
6	9608.000	45.18	38.37	7.07	37.42	53.20	74.00	-20.80	HORIZONTAL	Peak

Test Mode: 05; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1101.804	51.42	24.37	2.29	38.45	39.63	74.00	-34.37	VERTICAL	Peak
2	3243.069	52.13	28.67	4.02	37.06	47.76	74.00	-26.24	VERTICAL	Peak
3	4804.000	47.48	31.42	5.40	36.83	47.47	74.00	-26.53	VERTICAL	Peak
4	5940.017	49.65	32.34	6.00	36.90	51.09	74.00	-22.91	VERTICAL	Peak
5	7206.000	46.52	35.54	5.98	37.38	50.66	74.00	-23.34	VERTICAL	Peak
6	9608.000	44.77	38.37	7.07	37.42	52.79	74.00	-21.21	VERTICAL	Peak


Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; ; Channel:middle



race: (Discrete)


	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1434.528	48.23	25.44	2.67	38.20	38.14	74.00	-35.86	HORIZONTAL Peak
2	4198.089	49.26	30.15	4.60	36.81	47.20	74.00	-26.80	HORIZONTAL Peak
3	4880.000	46.14	31.54	5.50	36.84	46.34	74.00	-27.66	HORIZONTAL Peak
4	6553.138	46.67	34.06	5.84	37.03	49.54	74.00	-24.46	HORIZONTAL Peak
5	7320.000	45.24	36.00	6.13	37.43	49.94	74.00	-24.06	HORIZONTAL Peak
6	9760.000	44.96	38.50	7.02	37.41	53.07	74.00	-20.93	HORIZONTAL Peak

Test Mode: 05; Polarity: Vertical; Modulation:GFSK; ; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1511.847	48.88	25.51	2.80	38.10	39.09	74.00	-34.91	VERTICAL	Peak
2	4123.464	48.43	29.98	4.60	36.80	46.21	74.00	-27.79	VERTICAL	Peak
3	4880.000	46.93	31.54	5.50	36.84	47.13	74.00	-26.87	VERTICAL	Peak
4	6083.804	48.75	32.61	6.15	36.91	50.60	74.00	-23.40	VERTICAL	Peak
5	7320.000	45.35	36.00	6.13	37.43	50.05	74.00	-23.95	VERTICAL	Peak
6	9760.000	44.84	38.50	7.02	37.41	52.95	74.00	-21.05	VERTICAL	Peak

Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; ; Channel:High




	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1376.854	50.15	25.36	2.60	38.25	39.86	74.00	-34.14	HORIZONTAL Peak
2	3603.963	50.60	29.05	4.50	36.91	47.24	74.00	-26.76	HORIZONTAL Peak
3	4960.000	47.46	31.65	5.65	36.84	47.92	74.00	-26.08	HORIZONTAL Peak
4	6838.869	47.65	34.74	5.82	37.15	51.06	74.00	-22.94	HORIZONTAL Peak
5	7440.000	46.83	36.27	6.22	37.47	51.85	74.00	-22.15	HORIZONTAL Peak
6	9920.000	44.27	38.65	6.96	37.40	52.48	74.00	-21.52	HORIZONTAL Peak

Test Mode: 05; Polarity: Vertical; Modulation:GFSK; ; Channel:High




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1233.810	50.16	24.93	2.30	38.37	39.02	74.00	-34.98	VERTICAL	Peak
2	4326.103	48.92	30.54	4.67	36.81	47.32	74.00	-26.68	VERTICAL	Peak
3	4960.000	48.51	31.65	5.65	36.84	48.97	74.00	-25.03	VERTICAL	Peak
4	5193.698	50.59	31.73	5.60	36.87	51.05	74.00	-22.95	VERTICAL	Peak
5	7440.000	45.86	36.27	6.22	37.47	50.88	74.00	-23.12	VERTICAL	Peak
6	9920.000	44.01	38.65	6.96	37.40	52.22	74.00	-21.78	VERTICAL	Peak

Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1432.433	48.50	25.43	2.66	38.20	38.39	74.00	-35.61	HORIZONTAL Peak
2	3472.428	50.63	28.89	4.25	36.95	46.82	74.00	-27.18	HORIZONTAL Peak
3	4804.000	46.52	31.42	5.40	36.83	46.51	74.00	-27.49	HORIZONTAL Peak
4	6159.608	49.47	32.83	6.10	36.93	51.47	74.00	-22.53	HORIZONTAL Peak
5	7206.000	46.40	35.54	5.98	37.38	50.54	74.00	-23.46	HORIZONTAL Peak
6	9608.000	44.01	38.37	7.07	37.42	52.03	74.00	-21.97	HORIZONTAL Peak

Test Mode: 06; Polarity: Vertical; Modulation:GFSK; ; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1304.123	48.96	25.21	2.60	38.31	38.46	74.00	-35.54	VERTICAL	Peak
2	3940.391	49.43	29.73	4.60	36.81	46.95	74.00	-27.05	VERTICAL	Peak
3	4804.000	46.80	31.42	5.40	36.83	46.79	74.00	-27.21	VERTICAL	Peak
4	5431.863	49.85	31.79	6.13	36.88	50.89	74.00	-23.11	VERTICAL	Peak
5	7206.000	45.23	35.54	5.98	37.38	49.37	74.00	-24.63	VERTICAL	Peak
6	9608.000	44.22	38.37	7.07	37.42	52.24	74.00	-21.76	VERTICAL	Peak

Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; ; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1249.745	50.55	25.02	2.34	38.35	39.56	74.00	-34.44	HORIZONTAL Peak
2	3631.978	50.79	29.09	4.51	36.90	47.49	74.00	-26.51	HORIZONTAL Peak
3	4880.000	47.21	31.54	5.50	36.84	47.41	74.00	-26.59	HORIZONTAL Peak
4	5469.718	48.39	31.80	6.31	36.88	49.62	74.00	-24.38	HORIZONTAL Peak
5	7320.000	44.03	36.00	6.13	37.43	48.73	74.00	-25.27	HORIZONTAL Peak
6	9760.000	45.04	38.50	7.02	37.41	53.15	74.00	-20.85	HORIZONTAL Peak

Test Mode: 06; Polarity: Vertical; Modulation: GFSK; ; Channel: middle




	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1427.685	50.03	25.43	2.65	38.20	39.91	74.00	-34.09	VERTICAL Peak
2	3635.561	51.34	29.11	4.52	36.90	48.07	74.00	-25.93	VERTICAL Peak
3	4880.000	46.02	31.54	5.50	36.84	46.22	74.00	-27.78	VERTICAL Peak
4	6869.942	47.12	34.82	5.82	37.16	50.60	74.00	-23.40	VERTICAL Peak
5	7320.000	44.41	36.00	6.13	37.43	49.11	74.00	-24.89	VERTICAL Peak
6	9760.000	44.32	38.50	7.02	37.41	52.43	74.00	-21.57	VERTICAL Peak

Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; ; Channel:High




	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1306.015	48.73	25.21	2.60	38.31	38.23	74.00	-35.77	HORIZONTAL Peak
2	3977.071	49.38	29.78	4.60	36.81	46.95	74.00	-27.05	HORIZONTAL Peak
3	4960.000	47.28	31.65	5.65	36.84	47.74	74.00	-26.26	HORIZONTAL Peak
4	6281.662	48.16	33.37	5.98	36.95	50.56	74.00	-23.44	HORIZONTAL Peak
5	7440.000	46.02	36.27	6.22	37.47	51.04	74.00	-22.96	HORIZONTAL Peak
6	9920.000	43.45	38.65	6.96	37.40	51.66	74.00	-22.34	HORIZONTAL Peak

Test Mode: 06; Polarity: Vertical; Modulation:GFSK; ; Channel:High




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1132.723	51.51	24.44	2.22	38.43	39.74	74.00	-34.26	VERTICAL	Peak
2	4447.691	49.54	30.73	4.83	36.81	48.29	74.00	-25.71	VERTICAL	Peak
3	4960.000	47.04	31.65	5.65	36.84	47.50	74.00	-26.50	VERTICAL	Peak
4	6056.769	48.47	32.52	6.17	36.91	50.25	74.00	-23.75	VERTICAL	Peak
5	7440.000	45.90	36.27	6.22	37.47	50.92	74.00	-23.08	VERTICAL	Peak
6	9920.000	44.15	38.65	6.96	37.40	52.36	74.00	-21.64	VERTICAL	Peak

Test Mode: 07; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1371.035	49.39	25.35	2.60	38.25	39.09	74.00	-34.91	HORIZONTAL Peak
2	3659.554	50.08	29.15	4.53	36.89	46.87	74.00	-27.13	HORIZONTAL Peak
3	4804.000	47.60	31.42	5.40	36.83	47.59	74.00	-26.41	HORIZONTAL Peak
4	6719.930	46.78	34.44	5.83	37.09	49.96	74.00	-24.04	HORIZONTAL Peak
5	7206.000	45.80	35.54	5.98	37.38	49.94	74.00	-24.06	HORIZONTAL Peak
6	9608.000	44.48	38.37	7.07	37.42	52.50	74.00	-21.50	HORIZONTAL Peak


Test Mode: 07; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



race: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1318.205	50.13	25.25	2.60	38.29	39.69	74.00	-34.31	VERTICAL	Peak
2	4370.557	47.63	30.62	4.68	36.81	46.12	74.00	-27.88	VERTICAL	Peak
3	4804.000	46.64	31.42	5.40	36.83	46.63	74.00	-27.37	VERTICAL	Peak
4	6291.732	47.78	33.37	5.98	36.96	50.17	74.00	-23.83	VERTICAL	Peak
5	7206.000	46.77	35.54	5.98	37.38	50.91	74.00	-23.09	VERTICAL	Peak
6	9608.000	44.90	38.37	7.07	37.42	52.92	74.00	-21.08	VERTICAL	Peak

Test Mode: 07; Polarity: Horizontal; Modulation:GFSK; ; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1207.652	49.83	24.72	2.33	38.39	38.49	74.00	-35.51	HORIZONTAL	Peak
2	3471.132	49.70	28.89	4.25	36.95	45.89	74.00	-28.11	HORIZONTAL	Peak
3	4880.000	46.35	31.54	5.50	36.84	46.55	74.00	-27.45	HORIZONTAL	Peak
4	5594.505	48.70	31.89	6.30	36.89	50.00	74.00	-24.00	HORIZONTAL	Peak
5	7320.000	44.61	36.00	6.13	37.43	49.31	74.00	-24.69	HORIZONTAL	Peak
6	9760.000	44.38	38.50	7.02	37.41	52.49	74.00	-21.51	HORIZONTAL	Peak

Test Mode: 07; Polarity: Vertical; Modulation:GFSK; ; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1293.561	49.15	25.18	2.57	38.31	38.59	74.00	-35.41	VERTICAL	Peak
2	3644.265	49.45	29.11	4.52	36.89	46.19	74.00	-27.81	VERTICAL	Peak
3	4880.000	45.85	31.54	5.50	36.84	46.05	74.00	-27.95	VERTICAL	Peak
4	6062.880	49.35	32.57	6.16	36.91	51.17	74.00	-22.83	VERTICAL	Peak
5	7320.000	44.87	36.00	6.13	37.43	49.57	74.00	-24.43	VERTICAL	Peak
6	9760.000	44.64	38.50	7.02	37.41	52.75	74.00	-21.25	VERTICAL	Peak

Test Mode: 07; Polarity: Horizontal; Modulation:GFSK; ; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1504.195	48.50	25.50	2.80	38.10	38.70	74.00	-35.30	HORIZONTAL	Peak
2	3905.490	49.03	29.69	4.60	36.82	46.50	74.00	-27.50	HORIZONTAL	Peak
3	4960.000	47.92	31.65	5.65	36.84	48.38	74.00	-25.62	HORIZONTAL	Peak
4	6292.010	48.45	33.37	5.98	36.96	50.84	74.00	-23.16	HORIZONTAL	Peak
5	7440.000	44.86	36.27	6.22	37.47	49.88	74.00	-24.12	HORIZONTAL	Peak
6	9920.000	43.72	38.65	6.96	37.40	51.93	74.00	-22.07	HORIZONTAL	Peak

Test Mode: 07; Polarity: Vertical; Modulation:GFSK; ; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1169.509	50.84	24.55	2.39	38.40	39.38	74.00	-34.62	VERTICAL	Peak
2	4320.832	49.15	30.51	4.66	36.81	47.51	74.00	-26.49	VERTICAL	Peak
3	4960.000	47.24	31.65	5.65	36.84	47.70	74.00	-26.30	VERTICAL	Peak
4	5575.689	49.09	31.87	6.32	36.89	50.39	74.00	-23.61	VERTICAL	Peak
5	7440.000	45.38	36.27	6.22	37.47	50.40	74.00	-23.60	VERTICAL	Peak
6	9920.000	44.30	38.65	6.96	37.40	52.51	74.00	-21.49	VERTICAL	Peak