



TEST REPORT

Application No.: SZEM2008007512CR
Applicant: SKULLCANDY, INC.
Address of Applicant: 6301 N Landmark Dr Park City UT 84098, Utah United States of America
Manufacturer: SKULLCANDY, INC.
Address of Manufacturer: 6301 N Landmark Dr Park City UT 84098, Utah United States of America
Equipment Under Test (EUT):
EUT Name: Indy ANC
Model No.: S2IYW
Trade mark: 
Skullcandy
FCC ID: Y22-S2IYW
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2020-08-04
Date of Test: 2020-08-06 to 2020-08-24
Date of Issue: 2020-08-24

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu
EMC Laboratory Manager





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2020-08-24		Original

Authorized for issue by:			
			
		Benson Wang /Project Engineer	
			
		Eric Fu/Reviewer	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass

3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	6
4.1 DETAILS OF E.U.T.	6
4.2 CABLE	6
4.3 DESCRIPTION OF SUPPORT UNITS	6
4.4 MEASUREMENT UNCERTAINTY	7
4.5 TEST LOCATION.....	8
4.6 TEST FACILITY.....	8
4.7 DEVIATION FROM STANDARDS.....	8
4.8 ABNORMALITIES FROM STANDARD CONDITIONS	8
5 EQUIPMENT LIST.....	9
6 RADIO SPECTRUM TECHNICAL REQUIREMENT	11
6.1 ANTENNA REQUIREMENT	11
6.1.1 Test Requirement:	11
7 RADIO SPECTRUM MATTER TEST RESULTS.....	12
7.1 CONDUCTED PEAK OUTPUT POWER.....	12
7.1.1 E.U.T. Operation	12
7.1.2 Test Mode Description	12
7.1.3 Test Setup Diagram.....	13
7.1.4 Measurement Procedure and Data.....	13
7.2 MINIMUM 6dB BANDWIDTH.....	14
7.2.1 E.U.T. Operation	14
7.2.2 Test Mode Description	14
7.2.3 Test Setup Diagram.....	15
7.2.4 Measurement Procedure and Data.....	15
7.3 POWER SPECTRUM DENSITY.....	16
7.3.1 E.U.T. Operation	16
7.3.2 Test Mode Description	16
7.3.3 Test Setup Diagram.....	17
7.3.4 Measurement Procedure and Data.....	17
7.4 CONDUCTED BAND EDGES MEASUREMENT.....	18
7.4.1 E.U.T. Operation	18
7.4.2 Test Mode Description	18
7.4.3 Test Setup Diagram.....	19
7.4.4 Measurement Procedure and Data.....	19
7.5 CONDUCTED SPURIOUS EMISSIONS.....	20
7.5.1 E.U.T. Operation	20
7.5.2 Test Mode Description	20
7.5.3 Test Setup Diagram.....	21
7.5.4 Measurement Procedure and Data.....	21



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.6	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	22
7.6.1	E.U.T. Operation	22
7.6.2	Test Mode Description	22
7.6.3	Test Setup Diagram	23
7.6.4	Measurement Procedure and Data	23
7.7	RADIATED SPURIOUS EMISSIONS	40
7.7.1	E.U.T. Operation	40
7.7.2	Test Mode Description	40
7.7.3	Test Setup Diagram	41
7.7.4	Measurement Procedure and Data	42
8	TEST SETUP PHOTO	75
9	EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)	75
10	APPENDIX	76
10.1	APPENDIX 15.247 FOR RIGHT EARBUDS	76
10.2	APPENDIX 15.247 FOR LEFT EARBUDS	100-123



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
 Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

Battery:	Left earbuds: Li-Ion Polymer Battery 3.7V 55mAh(Charge by travel case) Right earbuds: Li-Ion Polymer Battery 3.7V 55mAh(Charge by travel case) travel case with backup battery: Li-Ion Polymer Battery 3.7V 500mAh(Charged by Type-C port)
Operation Frequency:	2402MHz to 2480MHz
Bluetooth Version:	V5.0 Dual mode
Data Rate:	Support 1M and 2M/bit
Modulation Type:	GFSK
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	Integral Antenna
Antenna Gain:	Left earbuds: 1.32dBi; Right earbuds: 1.37dBi

4.2 Cable

Cable	Length	Shielding	Core
Type-c cable	27cm	Unshielded	Non-Core

4.3 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--

The EUT has been tested as an independent unit.

4.4 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Peak Output Power	$\pm 0.75\text{dB}$
Minimum 6dB Bandwidth	$\pm 3\%$
Power Spectrum Density	$\pm 2.84\text{dB}$
Conducted Band Edges Measurement	$\pm 0.75\text{dB}$
Conducted Spurious Emissions	$\pm 0.75\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 4.5\text{dB}$ (Below 1GHz); $\pm 4.8\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions	$\pm 4.5\text{dB}$ (Below 1GHz); $\pm 4.8\text{dB}$ (Above 1GHz)

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{cisp}}^{\text{r}}$ (CISPR Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch, EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Radiated Emissions and Radiated Emission which fall in the restricted bands					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018-03-13	2021-03-12
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2020-07-09	2021-07-08
EXA Spectrum Analyzer	Agilent Technologies Inc	N9010A	SEM004-12	2020-04-09	2021-04-08
Horn Antenna	Rohde & Schwarz	HF907	SEM003-07	2018-04-13	2021-04-12
Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2019-09-24	2020-09-23
Pre-amplifier	Rohde & Schwarz	CH14-H052	SEM005-17	2020-04-01	2021-03-31
Pre-amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2020-04-01	2021-03-31
DC Power Supply	Zhao Xin	KXN-6020D	SEM011-08	2019-09-24	2020-09-23
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21

Radiated Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
LISN	Schwarzbeck	NNBM8124	SEM007-09	2019-09-24	2020-09-23
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2020-07-19	2023-07-18
MXE EMI Receiver	Agilent Technologies	N9038A	SEM004-15	2019-12-16	2020-12-15
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-02	2019-05-24	2022-05-23
Pre-Amplifier	Agilent Technologies	8447D	SEM005-01	2020-04-01	2021-03-31
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2020-07-10	2021-07-09

RF conducted					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2020-03-24	2021-03-23
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2019-09-24	2020-09-23
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-09	2021-07-08
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2019-09-24	2020-09-23
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2019-09-24	2020-09-23
Electric and Magnetic Field Analyzer	Narda	EHP-50F	SEM022-05	2019-11-28	2020-11-27
Electric Field Probe	WANDEL & GOLTERMANN	EMR-20	EMC0907	2020-05-20	2021-05-19
EMF Tester	Narda	ELT-400	SZE039-4	2020-07-07	2021-07-06

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2019-09-26	2020-09-25
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2019-09-26	2020-09-25
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2019-09-26	2020-09-25
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2019-04-07	2021-04-06
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2020-04-07	2021-04-06



6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

Limit:

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna as below: Left earbuds: 1.32dBi; Right earbuds: 1.37dBi.

Antenna location: Refer to Internal photos.

7 Radio Spectrum Matter Test Results

7.1 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247
Test Method: ANSI C63.10 (2013) Section 11.9.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.1.1 E.U.T. Operation


Operating Environment:

Temperature: 21.9 °C Humidity: 54.5 % RH Atmospheric Pressure: 1000 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(BLE 1M/bit of Left earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(BLE 1M/bit of Right earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	09	TX mode(BLE 2M/bit of Left earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	10	TX mode(BLE 2M/bit of Right earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

Please Refer To Appendix For Details

7.2 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247
 Test Method: ANSI C63.10 (2013) Section 11.8.1

Limit: ≥ 500 kHz

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 21.9 °C Humidity: 54.5 % RH Atmospheric Pressure: 1000 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(BLE 1M/bit of Left earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(BLE 1M/bit of Right earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	09	TX mode(BLE 2M/bit of Left earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	10	TX mode(BLE 2M/bit of Right earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
 Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
 Shenzhen Branch, EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

Please Refer To Appendix For Details

7.3 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247
Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit: $\leq 8\text{dBm}$ in any 3 kHz band during any time interval of continuous transmission


7.3.1 E.U.T. Operation

Operating Environment:
Temperature: 21.9 °C Humidity: 54.5 % RH Atmospheric Pressure: 1000 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(BLE 1M/bit of Left earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(BLE 1M/bit of Right earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	09	TX mode(BLE 2M/bit of Left earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	10	TX mode(BLE 2M/bit of Right earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

Please Refer To Appendix For Details

7.4 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247
Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 21.9 °C Humidity: 54.5 % RH Atmospheric Pressure: 1000 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(BLE 1M/bit of Left earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(BLE 1M/bit of Right earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	09	TX mode(BLE 2M/bit of Left earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	10	TX mode(BLE 2M/bit of Right earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

Please Refer To Appendix For Details

7.5 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.5.1 E.U.T. Operation


Operating Environment:

Temperature: 21.9 °C Humidity: 54.5 % RH Atmospheric Pressure: 1000 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(BLE 1M/bit of Left earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(BLE 1M/bit of Right earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	09	TX mode(BLE 2M/bit of Left earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	10	TX mode(BLE 2M/bit of Right earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Please Refer To Appendix For Details

7.6 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 22.9 °C


Humidity: 47.1 % RH

Atmospheric Pressure: 1000 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(BLE 1M/bit of Left earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(BLE 1M/bit of Right earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	09	TX mode(BLE 2M/bit of Left earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	10	TX mode(BLE 2M/bit of Right earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.6.3 Test Setup Diagram




7.6.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Mode: 02; Polarization: Horizontal; Channel: Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2402 Band edge
Note : BLE1M L


		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.951	4.34	28.52	40.97	57.89	49.78	74.00	-24.22	peak
2	2390.000	4.34	28.52	40.97	56.53	48.42	74.00	-25.58	peak
3 *	2402.000	4.36	28.54	40.98	103.75	95.67	74.00	21.67	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode :02; Polarization: Vertical; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 07512CR/07513CR
Mode : 2402 Band edge
Note : BLE1M L

		Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		
1	2369.692	4.31	28.48	40.96	58.17	50.00	74.00	-24.00	peak
2	2390.000	4.34	28.52	40.97	57.47	49.36	74.00	-24.64	peak
3 *	2402.000	4.36	28.54	40.98	94.23	86.15	74.00	12.15	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode: 02; Polarization: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2480 Band edge
Note : BLE1M L

		Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		
1 * 2480.000	4.49	28.67	41.01	103.07	95.22	74.00	21.22	peak	
2 2483.500	4.49	28.67	41.01	56.00	48.15	74.00	-25.85	peak	
3 2496.134	4.51	28.69	41.02	59.40	51.58	74.00	-22.42	peak	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057
中国·深圳·科技园中区M-10栋一号厂房

t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode :02; Polarization: Vertical; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 07512CR/07513CR
Mode : 2480 Band edge
Note : BLE1M L


		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2480.000	4.49	28.67	41.01	92.89	85.04	74.00	11.04	peak
2	2483.500	4.49	28.67	41.01	56.35	48.50	74.00	-25.50	peak
3	2492.173	4.51	28.69	41.01	58.84	51.03	74.00	-22.97	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode: 07; Polarization: Horizontal; Channel: Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2402 Band edge
Note : BLE1M R

		Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		
1 2367.784	4.31	28.48	40.96	58.45	50.28	74.00	-23.72	peak	
2 2390.000	4.34	28.52	40.97	56.48	48.37	74.00	-25.63	peak	
3 * 2402.000	4.36	28.54	40.98	101.18	93.10	74.00	19.10	peak	




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode :07; Polarization: Vertical; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 07512CR/07513CR
Mode : 2402 Band edge
Note : BLE1M R

		Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		
1 2365.578	4.30	28.48	40.96	58.93	50.75	74.00	-23.25	peak	
2 2390.000	4.34	28.52	40.97	56.96	48.85	74.00	-25.15	peak	
3 * 2402.000	4.36	28.54	40.98	95.19	87.11	74.00	13.11	peak	




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode: 07; Polarization: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2480 Band edge
Note : BLE1M R

		Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark	
MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2480.000	4.49	28.67	41.01	101.18	93.33	74.00	19.33	peak	
2 2483.500	4.49	28.67	41.01	56.35	48.50	74.00	-25.50	peak	
3 2495.180	4.51	28.69	41.02	59.00	51.18	74.00	-22.82	peak	




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode :07; Polarization: Vertical; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 07512CR/07513CR
Mode : 2480 Band edge
Note : BLE1M R

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 * 2480.000	4.49	28.67	41.01	94.77	86.92	74.00	12.92 peak
2 2483.500	4.49	28.67	41.01	57.22	49.37	74.00	-24.63 peak
3 2488.994	4.50	28.68	41.01	59.76	51.93	74.00	-22.07 peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode: 09; Polarization: Horizontal; Channel: Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2402 Band edge
Note : BLE2M L

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2340.151	4.26	28.43	40.95	58.83	50.57	74.00	-23.43	peak
2	2390.000	4.34	28.52	40.97	56.05	47.94	74.00	-26.06	peak
3 *	2402.000	4.36	28.54	40.98	103.63	95.55	74.00	21.55	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode :09; Polarization: Vertical; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 07512CR/07513CR
Mode : 2402 Band edge
Note : BLE2M L

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2342.632	4.27	28.44	40.95	58.53	50.29	74.00	-23.71	peak
2	2390.000	4.34	28.52	40.97	56.28	48.17	74.00	-25.83	peak
3 *	2402.000	4.36	28.54	40.98	94.17	86.09	74.00	12.09	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode: 09; Polarization: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2480 Band edge
Note : BLE2M L

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2480.000	4.49	28.67	41.01	103.05	95.20	74.00	21.20	peak
2	2483.500	4.49	28.67	41.01	56.14	48.29	74.00	-25.71	peak
3	2494.228	4.51	28.69	41.02	58.36	50.54	74.00	-23.46	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode :09; Polarization: Vertical; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 07512CR/07513CR
Mode : 2480 Band edge
Note : BLE2M L

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 * 2480.000	4.49	28.67	41.01	92.82	84.97	74.00	10.97	peak
2 2483.500	4.49	28.67	41.01	56.20	48.35	74.00	-25.65	peak
3 2489.920	4.50	28.68	41.01	58.15	50.32	74.00	-23.68	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode: 10; Polarization: Horizontal; Channel: Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2402 Band edge
Note : BLE2M R

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2361.971	4.30	28.47	40.96	58.09	49.90	74.00	-24.10	peak
2	2390.000	4.34	28.52	40.97	56.31	48.20	74.00	-25.80	peak
3 *	2402.000	4.36	28.54	40.98	101.07	92.99	74.00	18.99	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode :10; Polarization: Vertical; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 07512CR/07513CR
Mode : 2402 Band edge
Note : BLE2M R

		Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark	
MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2333.022	4.25	28.42	40.95	58.22	49.94	74.00	-24.06	peak
2	2390.000	4.34	28.52	40.97	56.26	48.15	74.00	-25.85	peak
3 *	2402.000	4.36	28.54	40.98	95.12	87.04	74.00	13.04	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode: 10; Polarization: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2480 Band edge
Note : BLE2M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2480.000	4.49	28.67	41.01	101.14	93.29	74.00	19.29	peak
2	2483.500	4.49	28.67	41.01	57.15	49.30	74.00	-24.70	peak
3	2498.744	4.52	28.70	41.02	58.98	51.18	74.00	-22.82	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode :10; Polarization: Vertical; Channel: High



Site : chamber

Condition: 3m VERTICAL

Job No : 07512CR/07513CR

Mode : 2480 Band edge

Note : BLE2M R

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 * 2480.000	4.49	28.67	41.01	94.67	86.82	74.00	12.82 peak
2 2483.500	4.49	28.67	41.01	56.56	48.71	74.00	-25.29 peak
3 2491.497	4.51	28.69	41.01	58.83	51.02	74.00	-22.98 peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.7 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.209
Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6
Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.7.1 E.U.T. Operation


Operating Environment:

Temperature: 20 °C Humidity: 53 % RH Atmospheric Pressure: 1000 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(BLE 1M/bit of Left earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(BLE 1M/bit of Right earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	09	TX mode(BLE 2M/bit of Left earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	10	TX mode(BLE 2M/bit of Right earbuds)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

30MHz~1GHz

QP value:

Test Mode: 02; Polarity: Horizontal



Condition: 3m HORIZONTAL

Job No. : 07512CR

Test mode: 02

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	42.75	0.70	16.52	27.70	25.52	15.04	40.00	-24.96	QP
2	104.17	1.11	13.80	27.58	24.17	11.50	43.50	-32.00	QP
3	155.36	1.16	15.10	27.31	25.17	14.12	43.50	-29.38	QP
4	216.02	1.35	17.07	27.09	24.85	16.18	46.00	-29.82	QP
5	386.63	2.26	22.07	27.33	25.34	22.34	46.00	-23.66	QP
6 pp	845.09	3.39	29.11	27.47	25.89	30.92	46.00	-15.08	QP




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 02; Polarity: Vertical



Condition: 3m VERTICAL


Job No. : 07512CR

Test mode: 02

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.11	0.60	22.44	27.74	25.36	20.66	40.00 -19.34 QP
2	97.80	1.14	13.81	27.61	24.92	12.26	43.50 -31.24 QP
3	155.36	1.16	15.10	27.31	25.17	14.12	43.50 -29.38 QP
4	249.43	1.64	18.94	26.99	24.45	18.04	46.00 -27.96 QP
5	462.35	2.43	23.83	27.66	25.23	23.83	46.00 -22.17 QP
6 pp	945.44	3.55	30.03	26.93	24.75	31.40	46.00 -14.60 QP

Above 1GHz


Mode: 02; Polarization: Horizontal; Channel: Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2402 TX SE
Note : BLE1M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1677.621	3.41	26.58	40.62	46.44	35.81	74.00	-38.19	peak
2	4392.376	6.66	33.42	42.47	48.86	46.47	74.00	-27.53	peak
3	4804.000	7.10	33.97	42.77	47.03	45.33	74.00	-28.67	peak
4	6698.373	8.39	35.72	41.84	48.48	50.75	74.00	-23.25	peak
5	7206.000	8.74	36.07	41.58	46.87	50.10	74.00	-23.90	peak
6	9608.000	10.81	37.67	38.57	42.77	52.68	74.00	-21.32	peak


Mode :02; Polarization: Vertical; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 07512CR/07513CR
Mode : 2402 TX SE
Note : BLE1M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1192.811	2.75	24.56	40.28	52.28	39.31	74.00	-34.69	peak
2	4443.453	6.71	33.50	42.51	48.81	46.51	74.00	-27.49	peak
3	4804.000	7.10	33.97	42.77	46.12	44.42	74.00	-29.58	peak
4	6914.763	8.50	35.85	41.73	47.34	49.96	74.00	-24.04	peak
5	7206.000	8.74	36.07	41.58	46.28	49.51	74.00	-24.49	peak
6	9608.000	10.81	37.67	38.57	42.47	52.38	74.00	-21.62	peak


Mode: 02; Polarization: Horizontal; Channel: middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2440 TX SE
Note : BLE1M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1702.042	3.43	26.68	40.63	45.61	35.09	74.00	-38.91	peak
2	4443.453	6.71	33.50	42.51	47.74	45.44	74.00	-28.56	peak
3	4880.000	7.18	34.06	42.82	46.13	44.55	74.00	-29.45	peak
4	6795.879	8.44	35.78	41.79	47.02	49.45	74.00	-24.55	peak
5	7320.000	8.84	36.16	41.52	43.82	47.30	74.00	-26.70	peak
6	9760.000	10.76	37.76	38.35	41.34	51.51	74.00	-22.49	peak


Mode :02; Polarization: Vertical; Channel: middle



Site : chamber
Condition: 3m VERTICAL
Job No : 07512CR/07513CR
Mode : 2440 TX SE
Note : BLE1M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1319.794	2.98	25.11	40.38	48.19	35.90	74.00	-38.10	peak
2	4495.125	6.76	33.59	42.55	48.18	45.98	74.00	-28.02	peak
3	4880.000	7.18	34.06	42.82	45.73	44.15	74.00	-29.85	peak
4	6142.019	8.27	35.25	42.16	47.49	48.85	74.00	-25.15	peak
5	7320.000	8.84	36.16	41.52	45.33	48.81	74.00	-25.19	peak
6	9760.000	10.76	37.76	38.35	41.44	51.61	74.00	-22.39	peak


Mode: 02; Polarization: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2480 TX SE
Note : BLE1M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1615.754	3.36	26.32	40.58	46.77	35.87	74.00	-38.13	peak
2	4367.058	6.64	33.37	42.45	48.29	45.85	74.00	-28.15	peak
3	4960.000	7.26	34.15	42.87	45.50	44.04	74.00	-29.96	peak
4	6621.375	8.34	35.67	41.88	47.87	50.00	74.00	-24.00	peak
5	7440.000	8.96	36.25	41.46	46.06	49.81	74.00	-24.19	peak
6	9920.000	10.71	37.85	38.12	40.12	50.56	74.00	-23.44	peak

Mode :02; Polarization: Vertical; Channel: High




Site : chamber
Condition: 3m VERTICAL
Job No : 07512CR/07513CR
Mode : 2480 TX SE
Note : BLE1M L

		Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		
1	1398.336	3.10	25.42	40.44	49.49	37.57	74.00	-36.43	peak
2	4443.453	6.71	33.50	42.51	48.37	46.07	74.00	-27.93	peak
3	4960.000	7.26	34.15	42.87	47.42	45.96	74.00	-28.04	peak
4	6267.553	8.27	35.37	42.08	48.06	49.62	74.00	-24.38	peak
5	7440.000	8.96	36.25	41.46	45.93	49.68	74.00	-24.32	peak
6	9920.000	10.71	37.85	38.12	40.74	51.18	74.00	-22.82	peak

30MHz~1GHz

QP value:

Test Mode: 07; Polarity: Horizontal




Condition: 3m HORIZONTAL

Job No. : 07512CR

Test mode: 07

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	30.32	0.60	22.32	27.73	24.83	20.02	40.00	-19.98	QP
2	98.14	1.14	13.84	27.61	25.03	12.40	43.50	-31.10	QP
3	169.01	1.18	15.69	27.26	24.48	14.09	43.50	-29.41	QP
4	250.30	1.64	18.96	26.99	24.43	18.04	46.00	-27.96	QP
5	549.02	2.60	25.63	27.97	25.47	25.73	46.00	-20.27	QP
6 pp	945.44	3.55	30.03	26.93	25.53	32.18	46.00	-13.82	QP

Test Mode: 07; Polarity: Vertical



Condition: 3m VERTICAL


Job No. : 07512CR

Test mode: 07

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	30.96	0.61	21.95	27.73	25.03	19.86	40.00	-20.14	QP
2	93.77	1.22	13.45	27.62	24.91	11.96	43.50	-31.54	QP
3	161.47	1.17	15.53	27.29	25.10	14.51	43.50	-28.99	QP
4	300.37	2.00	19.61	26.87	24.03	18.77	46.00	-27.23	QP
5	533.83	2.57	25.32	27.92	25.94	25.91	46.00	-20.09	QP
6 pp	906.48	3.51	29.83	27.13	26.37	32.58	46.00	-13.42	QP

Above 1GHz


Mode: 07; Polarization: Horizontal; Channel: Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2402 TX SE
Note : BLE1M R

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1592.571	3.34	26.22	40.57	45.35	34.34	74.00	-39.66 peak
2	4367.058	6.64	33.37	42.45	47.88	45.44	74.00	-28.56 peak
3	4804.000	7.10	33.97	42.77	46.61	44.91	74.00	-29.09 peak
4	6776.265	8.43	35.77	41.80	47.27	49.67	74.00	-24.33 peak
5	7206.000	8.74	36.07	41.58	45.90	49.13	74.00	-24.87 peak
6	9608.000	10.81	37.67	38.57	41.50	51.41	74.00	-22.59 peak


Mode :07; Polarization: Vertical; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 07512CR/07513CR
Mode : 2402 TX SE
Note : BLE1M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1615.754	3.36	26.32	40.58	46.09	35.19	74.00	-38.81	peak
2	4206.011	6.48	33.08	42.32	48.22	45.46	74.00	-28.54	peak
3	4804.000	7.10	33.97	42.77	46.44	44.74	74.00	-29.26	peak
4	6954.852	8.52	35.87	41.71	47.22	49.90	74.00	-24.10	peak
5	7206.000	8.74	36.07	41.58	45.46	48.69	74.00	-25.31	peak
6	9608.000	10.81	37.67	38.57	41.29	51.20	74.00	-22.80	peak


Mode: 07; Polarization: Horizontal; Channel: middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2440 TX SE
Note : BLE1M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1485.841	3.24	25.75	40.50	46.87	35.36	74.00	-38.64	peak
2	4329.354	6.60	33.30	42.42	47.28	44.76	74.00	-29.24	peak
3	4880.000	7.18	34.06	42.82	46.10	44.52	74.00	-29.48	peak
4	6934.778	8.51	35.86	41.72	46.83	49.48	74.00	-24.52	peak
5	7320.000	8.84	36.16	41.52	45.56	49.04	74.00	-24.96	peak
6	9760.000	10.76	37.76	38.35	40.78	50.95	74.00	-23.05	peak


Mode :07; Polarization: Vertical; Channel: middle



Site : chamber
Condition: 3m VERTICAL
Job No : 07512CR/07513CR
Mode : 2440 TX SE
Note : BLE1M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1658.337	3.40	26.50	40.61	45.62	34.91	74.00	-39.09	peak
2	4495.125	6.76	33.59	42.55	48.26	46.06	74.00	-27.94	peak
3	4880.000	7.18	34.06	42.82	46.74	45.16	74.00	-28.84	peak
4	6756.708	8.42	35.76	41.81	47.67	50.04	74.00	-23.96	peak
5	7320.000	8.84	36.16	41.52	46.01	49.49	74.00	-24.51	peak
6	9760.000	10.76	37.76	38.35	41.64	51.81	74.00	-22.19	peak


Mode: 07; Polarization: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2480 TX SE
Note : BLE1M R

		Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		
1	1481.553	3.23	25.73	40.49	47.18	35.65	74.00	-38.35	peak
2	4304.400	6.58	33.26	42.40	47.40	44.84	74.00	-29.16	peak
3	4960.000	7.26	34.15	42.87	46.44	44.98	74.00	-29.02	peak
4	6914.763	8.50	35.85	41.73	46.79	49.41	74.00	-24.59	peak
5	7440.000	8.96	36.25	41.46	44.97	48.72	74.00	-25.28	peak
6	9920.000	10.71	37.85	38.12	40.80	51.24	74.00	-22.76	peak

Mode :07; Polarization: Vertical; Channel: High




Site : chamber
Condition: 3m VERTICAL
Job No : 07512CR/07513CR
Mode : 2480 TX SE
Note : BLE1M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1477.276	3.23	25.72	40.49	46.61	35.07	74.00	-38.93	peak
2	4469.214	6.73	33.55	42.53	47.74	45.49	74.00	-28.51	peak
3	4960.000	7.26	34.15	42.87	47.17	45.71	74.00	-28.29	peak
4	6451.353	8.28	35.55	41.98	47.70	49.55	74.00	-24.45	peak
5	7440.000	8.96	36.25	41.46	46.16	49.91	74.00	-24.09	peak
6	9920.000	10.71	37.85	38.12	41.22	51.66	74.00	-22.34	peak

30MHz~1GHz

QP value:

Test Mode: 09; Polarity: Horizontal



Condition: 3m HORIZONTAL

Job No. : 07512CR

Test mode: 09

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	31.73	0.62	21.52	27.73	24.40	18.81	40.00	-21.19	QP
2	42.75	0.70	16.52	27.70	27.52	17.04	40.00	-22.96	QP
3	123.70	1.13	13.22	27.47	27.23	14.11	43.50	-29.39	QP
4	327.89	2.09	20.47	27.03	26.62	22.15	46.00	-23.85	QP
5	535.71	2.58	25.36	27.92	26.95	26.97	46.00	-19.03	QP
6 pp	845.09	3.39	29.11	27.47	27.89	32.92	46.00	-13.08	QP




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 09; Polarity: Vertical



Condition: 3m VERTICAL


Job No. : 07512CR

Test mode: 09

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	30.11	0.60	22.44	27.74	26.36	21.66	40.00	-18.34	QP
2	66.03	0.80	12.95	27.65	25.24	11.34	40.00	-28.66	QP
3	107.89	1.11	13.63	27.56	26.51	13.69	43.50	-29.81	QP
4	223.73	1.42	17.51	27.07	25.92	17.78	46.00	-28.22	QP
5	612.06	2.73	26.77	28.10	27.02	28.42	46.00	-17.58	QP
6 pp	906.48	3.51	29.83	27.13	25.72	31.93	46.00	-14.07	QP

Above 1GHz


Mode: 09; Polarization: Horizontal; Channel: Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2402 TX SE
Note : BLE2M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1625.121	3.37	26.36	40.59	46.06	35.20	74.00	-38.80	peak
2	4482.150	6.74	33.57	42.54	48.06	45.83	74.00	-28.17	peak
3	4804.000	7.10	33.97	42.77	45.30	43.60	74.00	-30.40	peak
4	5713.856	8.22	34.82	42.42	48.96	49.58	74.00	-24.42	peak
5	7206.000	8.74	36.07	41.58	45.76	48.99	74.00	-25.01	peak
6	9608.000	10.81	37.67	38.57	40.99	50.90	74.00	-23.10	peak


Mode :09; Polarization: Vertical; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 07512CR/07513CR
Mode : 2402 TX SE
Note : BLE2M L

		Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		
1	1697.129	3.43	26.66	40.63	46.66	36.12	74.00	-37.88	peak
2	4443.453	6.71	33.50	42.51	48.67	46.37	74.00	-27.63	peak
3	4804.000	7.10	33.97	42.77	45.64	43.94	74.00	-30.06	peak
4	6995.172	8.54	35.90	41.69	46.85	49.60	74.00	-24.40	peak
5	7206.000	8.74	36.07	41.58	45.31	48.54	74.00	-25.46	peak
6	9608.000	10.81	37.67	38.57	41.55	51.46	74.00	-22.54	peak


Mode: 09; Polarization: Horizontal; Channel: middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2440 TX SE
Note : BLE2M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1644.019	3.38	26.44	40.60	45.88	35.10	74.00	-38.90	peak
2	4254.921	6.53	33.17	42.36	48.10	45.44	74.00	-28.56	peak
3	4880.000	7.18	34.06	42.82	46.56	44.98	74.00	-29.02	peak
4	6934.778	8.51	35.86	41.72	46.40	49.05	74.00	-24.95	peak
5	7320.000	8.84	36.16	41.52	46.71	50.19	74.00	-23.81	peak
6	9760.000	10.76	37.76	38.35	41.63	51.80	74.00	-22.20	peak


Mode :09; Polarization: Vertical; Channel: middle



Site : chamber
Condition: 3m VERTICAL
Job No : 07512CR/07513CR
Mode : 2440 TX SE
Note : BLE2M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1697.129	3.43	26.66	40.63	45.89	35.35	74.00	-38.65	peak
2	4417.841	6.68	33.46	42.49	47.67	45.32	74.00	-28.68	peak
3	4880.000	7.18	34.06	42.82	47.35	45.77	74.00	-28.23	peak
4	6358.789	8.27	35.46	42.03	47.61	49.31	74.00	-24.69	peak
5	7320.000	8.84	36.16	41.52	45.45	48.93	74.00	-25.07	peak
6	9760.000	10.76	37.76	38.35	41.47	51.64	74.00	-22.36	peak


Mode: 09; Polarization: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2480 TX SE
Note : BLE2M L

		Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		
1	1597.181	3.35	26.24	40.57	45.44	34.46	74.00	-39.54	peak
2	4405.090	6.67	33.44	42.48	48.59	46.22	74.00	-27.78	peak
3	4960.000	7.26	34.15	42.87	47.10	45.64	74.00	-28.36	peak
4	6526.373	8.29	35.62	41.94	48.69	50.66	74.00	-23.34	peak
5	7440.000	8.96	36.25	41.46	45.31	49.06	74.00	-24.94	peak
6	9920.000	10.71	37.85	38.12	40.84	51.28	74.00	-22.72	peak

Mode :09; Polarization: Vertical; Channel: High




Site : chamber
Condition: 3m VERTICAL
Job No : 07512CR/07513CR
Mode : 2480 TX SE
Note : BLE2M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1682.477	3.42	26.60	40.62	46.11	35.51	74.00	-38.49	peak
2	4430.628	6.70	33.48	42.50	47.87	45.55	74.00	-28.45	peak
3	4960.000	7.26	34.15	42.87	46.90	45.44	74.00	-28.56	peak
4	5680.921	8.21	34.79	42.44	49.48	50.04	74.00	-23.96	peak
5	7440.000	8.96	36.25	41.46	46.52	50.27	74.00	-23.73	peak
6	9920.000	10.71	37.85	38.12	40.45	50.89	74.00	-23.11	peak

30MHz~1GHz

QP value:

Test Mode: 10; Polarity: Horizontal




Condition: 3m HORIZONTAL

Job No. : 07512CR

Test mode: 10

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	30.32	0.60	22.32	27.73	26.83	22.02	40.00	-17.98	QP
2	57.59	0.78	13.42	27.67	29.11	15.64	40.00	-24.36	QP
3	98.14	1.14	13.84	27.61	26.03	13.40	43.50	-30.10	QP
4	233.35	1.50	18.28	27.04	25.55	18.29	46.00	-27.71	QP
5	706.70	2.93	27.94	27.90	26.24	29.21	46.00	-16.79	QP
6 pp	945.44	3.55	30.03	26.93	26.53	33.18	46.00	-12.82	QP

Test Mode: 10; Polarity: Vertical



Condition: 3m VERTICAL


Job No. : 07512CR

Test mode: 10

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	30.96	0.61	21.95	27.73	23.03	17.86	40.00	-22.14	QP
2	59.23	0.79	13.27	27.66	26.17	12.57	40.00	-27.43	QP
3	190.41	1.19	16.22	27.18	26.28	16.51	43.50	-26.99	QP
4	394.85	2.29	22.27	27.37	28.55	25.74	46.00	-20.26	QP
5	724.26	3.00	28.05	27.87	25.27	28.45	46.00	-17.55	QP
6 pp	906.48	3.51	29.83	27.13	25.37	31.58	46.00	-14.42	QP

Above 1GHz


Mode: 10; Polarization: Horizontal; Channel: Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2402 TX SE
Note : BLE2M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1565.191	3.32	26.10	40.55	46.68	35.55	74.00	-38.45	peak
2	4329.354	6.60	33.30	42.42	48.34	45.82	74.00	-28.18	peak
3	4804.000	7.10	33.97	42.77	45.70	44.00	74.00	-30.00	peak
4	6640.542	8.36	35.69	41.87	47.10	49.28	74.00	-24.72	peak
5	7206.000	8.74	36.07	41.58	46.53	49.76	74.00	-24.24	peak
6	9608.000	10.81	37.67	38.57	41.91	51.82	74.00	-22.18	peak


Mode :10; Polarization: Vertical; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 07512CR/07513CR
Mode : 2402 TX SE
Note : BLE2M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1516.210	3.27	25.87	40.52	47.04	35.66	74.00	-38.34	peak
2	4469.214	6.73	33.55	42.53	47.41	45.16	74.00	-28.84	peak
3	4804.000	7.10	33.97	42.77	46.20	44.50	74.00	-29.50	peak
4	5915.516	8.25	35.02	42.29	48.52	49.50	74.00	-24.50	peak
5	7206.000	8.74	36.07	41.58	46.06	49.29	74.00	-24.71	peak
6	9608.000	10.81	37.67	38.57	41.37	51.28	74.00	-22.72	peak


Mode: 10; Polarization: Horizontal; Channel: middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2440 TX SE
Note : BLE2M R

		Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		
1	1597.181	3.35	26.24	40.57	46.36	35.38	74.00	-38.62	peak
2	4379.699	6.65	33.39	42.46	47.91	45.49	74.00	-28.51	peak
3	4880.000	7.18	34.06	42.82	46.46	44.88	74.00	-29.12	peak
4	6815.551	8.45	35.79	41.78	46.89	49.35	74.00	-24.65	peak
5	7320.000	8.84	36.16	41.52	45.90	49.38	74.00	-24.62	peak
6	9760.000	10.76	37.76	38.35	41.52	51.69	74.00	-22.31	peak


Mode :10; Polarization: Vertical; Channel: middle



Site : chamber
Condition: 3m VERTICAL
Job No : 07512CR/07513CR
Mode : 2440 TX SE
Note : BLE2M R

		Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark	
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		
1	1398.336	3.10	25.42	40.44	49.92	38.00	74.00	-36.00	peak
2	4495.125	6.76	33.59	42.55	47.67	45.47	74.00	-28.53	peak
3	4880.000	7.18	34.06	42.82	44.75	43.17	74.00	-30.83	peak
4	6914.763	8.50	35.85	41.73	47.43	50.05	74.00	-23.95	peak
5	7320.000	8.84	36.16	41.52	45.90	49.38	74.00	-24.62	peak
6	9760.000	10.76	37.76	38.35	41.42	51.59	74.00	-22.41	peak


Mode: 10; Polarization: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 07512CR/07513CR
Mode : 2480 TX SE
Note : BLE2M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1447.688	3.18	25.61	40.47	46.72	35.04	74.00	-38.96	peak
2	4405.090	6.67	33.44	42.48	47.72	45.35	74.00	-28.65	peak
3	4960.000	7.26	34.15	42.87	46.50	45.04	74.00	-28.96	peak
4	5830.640	8.23	34.94	42.34	48.93	49.76	74.00	-24.24	peak
5	7440.000	8.96	36.25	41.46	46.23	49.98	74.00	-24.02	peak
6	9920.000	10.71	37.85	38.12	40.30	50.74	74.00	-23.26	peak

Mode :10; Polarization: Vertical; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 07512CR/07513CR
Mode : 2480 TX SE
Note : BLE2M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1538.281	3.29	25.98	40.53	46.81	35.55	74.00	-38.45	peak
2	4379.699	6.65	33.39	42.46	48.18	45.76	74.00	-28.24	peak
3	4960.000	7.26	34.15	42.87	45.73	44.27	74.00	-29.73	peak
4	6640.542	8.36	35.69	41.87	47.98	50.16	74.00	-23.84	peak
5	7440.000	8.96	36.25	41.46	45.77	49.52	74.00	-24.48	peak
6	9920.000	10.71	37.85	38.12	39.73	50.17	74.00	-23.83	peak

8 Test Setup Photo

Please refer to setup photos.

9 EUT Constructional Details (EUT Photos)

Please refer to external and internal photos for details.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

10 Appendix


10.1 Appendix 15.247 for Right earbuds



1. Duty Cycle



1.1 Test Result


Test Mode	Channel Frequency(MHz)	TX Type	ANT No.	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)
1M	2402	SISO	1	0.379	0.625	60.64	2.17
	2440	SISO	1	0.380	0.626	60.70	2.17
	2480	SISO	1	0.379	0.625	60.64	2.17
2M	2402	SISO	1	0.195	0.625	31.20	5.06
	2440	SISO	1	0.195	0.625	31.20	5.06
	2480	SISO	1	0.195	0.625	31.20	5.06

1.2 Test Graph











2. Bandwidth



2.1 Test Result



Test Mode	Frequency (MHz)	TX Type	ANT No.	6dB Bandwidth	Verdict
				Test Result (MHz)	
1M	2402	SISO	1	0.714	PASS
	2440	SISO	1	0.714	PASS
	2480	SISO	1	0.715	PASS
2M	2402	SISO	1	1.251	PASS
	2440	SISO	1	1.249	PASS
	2480	SISO	1	1.246	PASS

Test Mode	Frequency (MHz)	TX Type	ANT No.	99% Occupied Bandwidth	
				Test Result (MHz)	
1M	2402	SISO	1	1.034	Only for Report Use
	2440	SISO	1	1.033	Only for Report Use
	2480	SISO	1	1.033	Only for Report Use
2M	2402	SISO	1	2.059	Only for Report Use
	2440	SISO	1	2.059	Only for Report Use
	2480	SISO	1	2.059	Only for Report Use



2.2 Test Graph - 6dB Bandwidth











2.3 Test Graph - 99% Occupied Bandwidth










3. Maximum Conducted Output Power



3.1 Test Result


Test Mode	Frequency (MHz)	Tx Type	Measured Peak Output Power (dBm)	Limits (dBm)	Verdict
			Ant 1		
1M	2402	SISO	-0.23	30	PASS
	2440	SISO	-0.10	30	PASS
	2480	SISO	-0.09	30	PASS
2M	2402	SISO	-0.20	30	PASS
	2440	SISO	-0.08	30	PASS
	2480	SISO	-0.08	30	PASS

3.2 Test Graph











4. Maximum Power Spectral Density (PSD)

4.1 Test Result

Test Mode	Frequency (MHz)	Tx Type	Maximum Power Spectral Density (dBm/3KHz)	Limits (dBm/3kHz)	Verdict
			Ant 1		
1M	2402	SISO	-16.41	≤8	PASS
	2440	SISO	-16.30	≤8	PASS
	2480	SISO	-16.26	≤8	PASS
2M	2402	SISO	-18.73	≤8	PASS
	2440	SISO	-18.61	≤8	PASS
	2480	SISO	-18.63	≤8	PASS

4.2 Test Graph







Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com








5. Unwanted Emissions in Non-restricted Frequency Bands



5.1 Test Result



Test Mode	Frequency (MHz)	TX Type	ANT No.	Spurious Conducted Emission (dBm)	Limits (dBm)	Verdict
1M	2402	SISO	1	Refer to test graph	-21.60	PASS
	2440	SISO	1	Refer to test graph	-21.60	PASS
	2480	SISO	1	Refer to test graph	-21.60	PASS
2M	2402	SISO	1	Refer to test graph	-22.02	PASS
	2440	SISO	1	Refer to test graph	-22.02	PASS
	2480	SISO	1	Refer to test graph	-22.02	PASS



5.2 Test Graph





















10.2 Appendix 15.247 for Left earbuds

1. Duty Cycle

1.1 Test Result

Test Mode	Channel Frequency(MHz)	TX Type	ANT No.	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)
1M	2402	SISO	1	0.380	0.626	60.70	2.17
	2440	SISO	1	0.379	0.625	60.64	2.17
	2480	SISO	1	0.379	0.625	60.64	2.17
2M	2402	SISO	1	0.195	0.626	31.15	5.07
	2440	SISO	1	0.195	0.625	31.20	5.06
	2480	SISO	1	0.195	0.625	31.20	5.06



1.2 Test Graph






Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com









2. Bandwidth



2.1 Test Result



Test Mode	Frequency (MHz)	TX Type	ANT No.	6dB Bandwidth	Verdict
				Test Result (MHz)	
1M	2402	SISO	1	0.715	PASS
	2440	SISO	1	0.717	PASS
	2480	SISO	1	0.715	PASS
2M	2402	SISO	1	1.246	PASS
	2440	SISO	1	1.249	PASS
	2480	SISO	1	1.247	PASS

Test Mode	Frequency (MHz)	TX Type	ANT No.	99% Occupied Bandwidth	
				Test Result (MHz)	
1M	2402	SISO	1	1.034	Only for Report Use
	2440	SISO	1	1.033	Only for Report Use
	2480	SISO	1	1.033	Only for Report Use
2M	2402	SISO	1	2.058	Only for Report Use
	2440	SISO	1	2.059	Only for Report Use
	2480	SISO	1	2.059	Only for Report Use



2.2 Test Graph - 6dB Bandwidth











2.3 Test Graph - 99% Occupied Bandwidth










3. Maximum Conducted Output Power



3.1 Test Result


Test Mode	Frequency (MHz)	Tx Type	Measured Peak Output Power (dBm)	Limits (dBm)	Verdict
			Ant 1		
1M	2402	SISO	-0.25	30	PASS
	2440	SISO	-0.12	30	PASS
	2480	SISO	-0.13	30	PASS
2M	2402	SISO	-0.24	30	PASS
	2440	SISO	-0.12	30	PASS
	2480	SISO	-0.11	30	PASS

3.2 Test Graph













4. Maximum Power Spectral Density (PSD)



4.1 Test Result

Test Mode	Frequency (MHz)	Tx Type	Maximum Power Spectral Density (dBm/3KHz)	Limits (dBm/3kHz)	Verdict
			Ant 1		
1M	2402	SISO	-16.50	≤8	PASS
	2440	SISO	-16.47	≤8	PASS
	2480	SISO	-16.46	≤8	PASS
2M	2402	SISO	-18.86	≤8	PASS
	2440	SISO	-18.77	≤8	PASS
	2480	SISO	-18.70	≤8	PASS

4.2 Test Graph










5. Unwanted Emissions in Non-restricted Frequency Bands



5.1 Test Result



Test Mode	Frequency (MHz)	TX Type	ANT No.	Spurious Conducted Emission (dBm)	Limits (dBm)	Verdict
1M	2402	SISO	1	Refer to test graph	-21.72	PASS
	2440	SISO	1	Refer to test graph	-21.72	PASS
	2480	SISO	1	Refer to test graph	-21.72	PASS
2M	2402	SISO	1	Refer to test graph	-22.16	PASS
	2440	SISO	1	Refer to test graph	-22.16	PASS
	2480	SISO	1	Refer to test graph	-22.16	PASS



5.2 Test Graph


















- End of the Report -