
General RF Exposure Test Report

Report No.: AGC02562150401FH02

FCC ID : Y2L00006
APPLICATION : Original Equipment
PURPOSE : Scouting Camera
PRODUCT : Scouting Camera
DESIGNATION :
BRAND NAME : Boly Guard, Scout Guard
MODEL NAME : MG883G-12mHD(Series model name please see attached list on page 5)
CLIENT : Boly Media Communications (Shenzhen) Co., Ltd
DATE OF ISSUE : May 21,2015
STANDARD(S) : KDB447498 D01/ OET Bulletin 65

Attestation of Global Compliance (Shenzhen) Co., Ltd



CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



REPORT REVISE RECORD

| Report Version | Revise Time | Issued Date | Valid Version | Notes |
|-----------------------|--------------------|--------------------|----------------------|-----------------|
| V1.0 | / | May 21, 2014 | Valid | Original Report |

TABALE OF CONTENTS


| | |
|--|----------|
| TABALE OF CONTENTS | 3 |
| 1. TEST RESULT CERTIFICATION | 4 |
| 2. TECHNICAL INFORMATION | 5 |
| 2.1 EUT DESCRIPTION..... | 5 |
| 3. RF EXPOSURE MEASUREMENT..... | 6 |
| 3.1 INTRODUCTION..... | 6 |
| 3.2 FCC LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE(MPE) | 7 |
| 4. CLASSIFICATION OF THE ASSESSMENT METHODS..... | 8 |
| 5. EUT OPERATION CONDITION | 8 |
| 6. TEST RESULTS | 9 |

1. TEST RESULT CERTIFICATION

| | |
|------------------------|--|
| Applicant Name: | Boly Media Communications (Shenzhen) Co., Ltd. |
| Address: | 2F, Shanshui Building A, B, Yungu Innovation Industrial Park, No. 1183, Liuxian Blvd, Nanshan District, Shenzhen, Guangdong, China |
| Manufacturer Name: | Boly Media Communications (Shenzhen) Co., Ltd. |
| Address: | 2F, Shanshui Building A, B, Yungu Innovation Industrial Park, No. 1183, Liuxian Blvd, Nanshan District, Shenzhen, Guangdong, China |
| Product Designation | Scouting Camera |
| Brand Name | Boly Guard, Scout Guard |
| Test Model | MG883G-12mHD |
| Series Model | Series model name please see attached list on page 6 |
| Difference description | All the same except for the brand name, model name and appearance. |
| Test Standard | KDB447498 D01 General RF Exposure Guidanc v05r02/ OET Bulletin 65 |
| Date of Test: | May 12,2015 to May 20,2015 |

We (AGC), Attestation of Global Compliance Co., Ltd. for compliance with the requirements set forth in the KDB447498 D01 General RF Exposure Guidanc v05r02. The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Prepared By




Bart Xie May 21,2015

Checked By



Kidd Yang May 21,2015

Authorized By



Solger Zhang May 21,2015

2. TECHNICAL INFORMATION

Note: the following data is based on the information by the applicant.

ATTACHED LIST

| | |
|---------------------|--|
| Series model | SG883G-12mHD MG883G-XXXXX ("X" can be replaced by digit "0-9" or letter "A-Z") SG883G-XXXXX ("X" can be replaced by digit "0-9" or letter "A-Z") |
|---------------------|--|

2.1 EUT DESCRIPTION

| | |
|---|--|
| Product Designation: | Scouting Camera |
| Hardware version: | MG883G-V11M_20150228 |
| Software version: | N/A |
| Frequency Bands: | <input checked="" type="checkbox"/> GPRS 850 <input checked="" type="checkbox"/> GPRS 1900 (U.S. Bands) <input checked="" type="checkbox"/> GPRS 900 <input checked="" type="checkbox"/> GPRS 1800 (Non-U.S. Bands) <input checked="" type="checkbox"/> UMTS FDD Band II <input checked="" type="checkbox"/> UMTS FDD Band V (U.S. Bands) <input checked="" type="checkbox"/> UMTS FDD Band I <input checked="" type="checkbox"/> UMTS FDD Band VIII (Non-U.S. Bands) |
| Antenna: | PIFA Antenna |
| Type of Modulation | GPRS : GMSK WCDMA : QPSK |
| Antenna gain(GPRS): | 1.2dBi(GPRS/WCDMA 850), 1.2dBi (GPRS/WCDMA 1900) |
| Power Supply: | DC 6V by Battery |
| Single Card: | WCDMA / GPRS Card Slot |
| GPRS Class | 12 |
| Extreme Vol. Limits: | DC5.1 V to 6.9 V (Normal: DC 6 V) |
| Extreme Temp. Tolerance | -10°C to +50°C |
| *** Note: The High Voltage DC6.9V and Low Voltage DC5.1V were declared by manufacturer, The EUT couldn't be operating normally with higher or lower voltage. Other functions have been performed according to verification procedure except for Bluetooth and MS function. | |

Note:

1. For more details, please refer to the User's manual of the EUT.

3. RF EXPOSURE MEASUREMENT

3.1 INTRODUCTION

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 2.5 cm or more from persons.

The 1992 ANSI/IEEE standard (See Listed limit table) specifies a minimum separation distance of 1cm for performing reliable field measurements to determine adherence to MPE limits.

If the minimum separation distance between a transmitter and nearby persons is more than 2.5 cm under normal operating conditions, compliance with MPE limits may be determined at such distance from the transmitter. When applicable, operation instructions and prominent warning labels may be used to alert the exposed persons to maintain a specified distance from the transmitter or to limit their exposure durations and usage conditions to ensure compliance.

3.2 FCC LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE(MPE)

LIMITS FOR GENERAL POPULATION / CONTROLLED EXPOSURE

| Frequency Range (MHz) | E-field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Time E ² , H ² or S (Minutes) |
|-----------------------|----------------------------|-----------------------------------|---|---|
| 0.3 -- 1.34 | 614 | 1.63 | (100)* | 6 |
| 1.34 -- 30 | 824/f | 4.89/f | (900/f ²)* | 6 |
| 30 -- 300 | 61.4 | 0.163 | 1.0 | 6 |
| 300 -- 1500 | -- | -- | f/300 | 6 |
| 1500 -- 100,000 | -- | -- | 5 | 6 |

*Note:

1. f=Frequency in MHz * Plane-wave Equivalent Power Density.

4. CLASSIFICATION OF THE ASSESSMENT METHODS

According to user manual, The antenna of the product, under normal use condition is at least 0.2m away from the body of the user. Warning statement to the user for keeping at least 2m separation distance and the prohibition of operating to a person has been printed on the user's manual. So, this product under normal use is located on electromagnetic far field between the human body.

$$S = PG/4\pi R^2$$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator R=distance to the center of radiation of the antenna

5. EUT OPERATION CONDITION

Make the EUT to transmit at lowest, middle and highest channel individually.

6. TEST RESULTS

Antenna Gain 1.2dBi (Numeric 1.32), $\pi = 3.1416$

GPRS 900:

| Channel | Frequency | Output Power (peak) | Output Power (peak) | Power Density | Power Density Limit | Result |
|---------|-----------|---------------------|---------------------|--------------------|---------------------|-----------|
| | MHz | dBm | mW | mW/cm ² | mW/cm ² | Pass/Fail |
| L | 824.2 | 32.46 | 1761.98 | 0.463 | 2.75 | Pass |
| M | 836.6 | 32.42 | 1745.82 | 0.458 | 2.79 | Pass |
| H | 848.8 | 32.37 | 1725.84 | 0.453 | 2.83 | Pass |

GPRS 1800:

| Channel | Frequency | Output Power (peak) | Output Power (peak) | Power Density | Power Density Limit | Result |
|---------|-----------|---------------------|---------------------|--------------------|---------------------|-----------|
| | MHz | dBm | mW | mW/cm ² | mW/cm ² | Pass/Fail |
| L | 1850.2 | 29.68 | 928.97 | 0.244 | 5 | Pass |
| M | 1880 | 29.64 | 920.45 | 0.242 | 5 | Pass |
| H | 1909.8 | 29.61 | 914.11 | 0.240 | 5 | Pass |

UMTS BAND II:

| Channel | Frequency | Output Power (peak) | Output Power (peak) | Power Density | Power Density Limit | Result |
|---------|-----------|---------------------|---------------------|--------------------|---------------------|-----------|
| | MHz | dBm | mW | mW/cm ² | mW/cm ² | Pass/Fail |
| L | 1852.4 | 23.67 | 232.81 | 0.061 | 5 | Pass |
| M | 1880 | 23.64 | 231.21 | 0.061 | 5 | Pass |
| H | 1907.6 | 23.61 | 229.21 | 0.060 | 5 | Pass |

UMTS BAND V:

| Channel | Frequency | Output Power (peak) | Output Power (peak) | Power Density | Power Density Limit | Result |
|---------|-----------|---------------------|---------------------|--------------------|---------------------|-----------|
| | MHz | dBm | mW | mW/cm ² | mW/cm ² | Pass/Fail |
| L | 826.4 | 23.71 | 234.96 | 0.062 | 2.75 | Pass |
| M | 836.6 | 23.67 | 232.81 | 0.061 | 2.79 | Pass |
| H | 846.6 | 23.64 | 231.21 | 0.061 | 2.82 | Pass |

Note: The distance between users and EUT is 0.2m.