

Outform Ltd

IVIEW (IMENU) CLASSIC 10.2" DIGITAL DISPLAY

Model: UID0002-X

10 December, 2010

Report No.: 10021087-FCC

(This report supersedes NONE)



EMC Test Report

TO: FCC Part 15 Subpart B Class B: 2010

SIEMIC, INC.
Accessing global markets

Modifications made to the product : None

This Test Report is Issued Under the Authority of:



William Long
Test Engineer



Will Yang
Technical Manager

This test report may be reproduced in full only.
Test result presented in this test report is applicable to the representative sample only.

Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management through out a project. Our extensive experience with China, Asia Pacific, North America, European, and international compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Accreditation Body	Scope
USA	FCC, A2LA	EMC , RF/Wireless , Telecom
Canada	IC, A2LA, NIST	EMC, RF/Wireless , Telecom
Taiwan	BSMI , NCC , NIST	EMC, RF, Telecom , Safety
Hong Kong	OFTA , NIST	RF/Wireless , Telecom
Australia	NATA, NIST	EMC, RF, Telecom , Safety
Korea	KCC/RRA, NIST	EMI, EMS, RF , Telecom, Safety
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom
Mexico	NOM, COFETEL, Caniety	Safety, EMC , RF/Wireless, Telecom
Europe	A2LA, NIST	EMC, RF, Telecom , Safety

Accreditations for Product Certifications

Country	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC , RF , Telecom
Canada	IC FCB , NIST	EMC , RF , Telecom
Singapore	iDA, NIST	EMC , RF , Telecom
EU	NB	EMC & R&TTE Directive



SIEMIC, INC.
Accessing global markets

Title: EMC Test Report for IVIEW (IMENU) CLASSIC 10.2" DIGITAL DISPLAY
Model: UID0002-X
To: FCC Part 15 Subpart B Class B: 2010

Serial#: 10021087-FCC
Issue Date: 10 December, 2010
Page: 3 of 53
www.siemic.com.cn

This page has been left blank intentionally.

CONTENTS

1	EXECUTIVE SUMMARY & EUT INFORMATION	5
2	TECHNICAL DETAILS	6
3	MODIFICATION	7
4	TEST SUMMARY	8
5	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
	ANNEX A. TEST INSTRUMENTATION.....	17
	ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	20
	ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	38
	ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST	42
	ANNEX E. SIEMIC ACCREDITATION CERTIFICATES.....	43

1 Executive Summary & EUT information

The purpose of this test program was to demonstrate compliance of the Outform Ltd IVIEW (IMENU) CLASSIC 10.2" DIGITAL DISPLAY, against the current Stipulated Standards. The IVIEW (IMENU) CLASSIC 10.2" DIGITAL DISPLAY has demonstrated compliance with FCC Part 15 Subpart B Class B: 2010.

EUT Information

EUT Description	IVIEW (IMENU) CLASSIC 10.2" DIGITAL DISPLAY
Model No	UID0002-X (Note)
Serial No	N/A
Input Power	1) Adapter Input: 100-240V AC Output: 12V DC 3A 2) 12V DC 3A Battery
Classification Per Stipulated Test Standard	Class B Emission Product

Note : X can be A-Z (A-Z represent different colors such as: B or W or BL or R (Black/White/Blue/Red)

2 TECHNICAL DETAILS

Purpose	Compliance testing of IVIEW (IMENU) CLASSIC 10.2" DIGITAL DISPLAY with stipulated standards
Applicant / Client	Outform Ltd R405,East,Buliding 203,Tai Ran Industrial Zone,Chengongmiao,Futian,Shenzhen, China
Manufacturer	Outform Ltd R405,East,Buliding 203,Tai Ran Industrial Zone,Chengongmiao,Futian,Shenzhen, China
Laboratory performing the tests	SIEMIC Nanjing (China) Laboratories NO.2-1,Longcang Dadao, Yuhua Economic Development Zone, Nanjing, China Tel:+86(25)86730128/86730129 Fax:+86(25)86730127 Email: info@siemic.com
Test report reference number	10021087-FCC
Date EUT received	5 November, 2010
Standard applied	FCC Part 15 Subpart B Class B: 2010
Dates of test (from – to)	13 November~9 December, 2010
No of Units	#1
Equipment Category	ITE
Trade Name	i Display
Microprocessor (s)	unidentified
RF Operating Frequency (ies)	N/A
Clock/Oscillator Frequency (ies)	32.768KHz,24MHz
Rated Input Power	100V-240V AC 50Hz/60Hz Adapter, 12V DC 3A Battery
Port/Connectors	SD card slot, USB Port

3 MODIFICATION

NONE

4 TEST SUMMARY

The product was tested in accordance with the following specifications.
All testing has been performed according to below product classification:

Class B Emission Product

Test Results Summary

Emissions			
Test Standard	Description	Product Class	Pass / Fail
FCC Part 15 Subpart B Class B: 2010	Radiated Spurious Emission	See Above	Pass
	Conducted Emission	See Above	Pass

All measurement uncertainty is not taken into consideration for all presented test result.

5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

5.1 Radiated Spurious Emission Test Results

Note:


1.	All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.		
2.	A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.		
3.	<u>Radiated Emissions Measurement Uncertainty</u> All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 1GHz (QP only @ 3m & 10m) is +5.6dB/-4.5dB (for EUTs < 0.5m X 0.5m X 0.5m).		
4.	Environmental Conditions	Temperature	15°C
		Relative Humidity	50%
		Atmospheric Pressure	1019mbar
5.	Test date : 13 November~9 December, 2010 Tested By : William long		

5.1.1 Test Result Complying For FCC Part 15 Subpart B Class B: 2010

Below 1GHz test result

Read CD card mode

Peak Detector 
 Quasi Peak Limit 



Test Data

Frequency (MHz)	Quasi Peak (dBuV/m)	Azimuth	Polarity(H /V)	Height (cm)	Factors (dB)	Limit (dBuV/m)	Margin (dB)
650.04	45.28	237.00	V	101.00	-24.69	46.00	-0.72
702.05	44.65	195.00	H	200.00	-22.91	46.00	-1.35
49.99	34.39	54.00	V	120.00	-35.70	40.00	-5.61
950.06	44.43	21.00	V	100.00	-19.66	46.00	-1.57
754.05	42.10	266.00	V	159.00	-21.88	46.00	-3.90
424.22	33.44	360.00	H	311.00	-29.17	46.00	-12.56

Above 1GHz test result


Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading			
GHz	Degree	Meter	H / V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
1.36	5	1.12	v	5.15	55.00	39.5	54.00	-14.5	Ave
1.36	3	1.15	h	5.15	55.00	37.9	54.00	-16.1	Ave
4.85	11	1.07	v	7.23	55.00	42.6	54.00	-11.4	Ave
4.85	0	1.10	h	7.23	55.00	40.6	54.00	-13.4	Ave

Note: Emission was scanned up to 6GHz.

Connect to PC mode

Peak Detector

Quasi Peak Limit



Test Data

Frequency (MHz)	Quasi Peak (dBuV/m)	Azimuth	Polarity(H /V)	Height (cm)	Factors (dB)	Limit (dBuV/m)	Margin (dB)
650.03	45.64	279.00	H	108.00	-24.69	46.00	-0.36
89.02	10.14	179.00	H	154.00	-37.89	43.50	-33.36
450.04	41.99	206.00	V	206.00	-28.94	46.00	-4.01
37.16	15.29	126.00	V	344.00	-28.08	40.00	-24.71
81.41	12.83	60.00	H	155.00	-38.47	40.00	-27.17
750.05	42.05	279.00	V	158.00	-22.59	46.00	-3.95

Above 1GHz test result

Frequency	Direction	Height	Polar	Cable loss	Amplifier	Corrected Reading			
GHz	Degree	Meter	H / V	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
1.36	0	1.12	v	5.15	55.00	37.6	54.00	-16.4	Ave
1.36	15	1.15	h	5.15	55.00	35.2	54.00	-18.8	Ave
4.85	2	1.07	v	7.23	55.00	40.4	54.00	-13.6	Ave
4.85	13	1.10	h	7.23	55.00	42.1	54.00	-11.9	Ave

Note: Emission was scanned up to 6GHz.

5.2 AC Line Conducted Emission Test Results


Note:

1.	All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR and Average detectors, are reported. All other emissions were relatively insignificant.		
2.	A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.		
3.	<u>Conducted Emissions Measurement Uncertainty</u> All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 9kHz – 30MHz (Average & Quasi-peak) is $\pm 3.86\text{dB}$.		
4.	Environmental Conditions	Temperature	15°C
		Relative Humidity	50%
		Atmospheric Pressure	1019mbar
5.	Test Date : 13 November~9 December, 2010 Tested By : William long		

5.2.1 Test Result Complying For FCC Part 15 Subpart B Class B: 2010

Read CD card mode

Peak Detector		Quasi Peak Limit	
Average Detector		Average Limit	




Test Data

Line

Frequency (MHz)	Quasi Peak (dBuV)	Limit (dBuV)	Margin (dB)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Factors (dB)
0.69	33.55	56.00	-22.45	29.83	46.00	-16.17	10.12
0.45	31.05	56.96	-25.92	26.55	46.96	-20.41	10.17
0.77	31.54	56.00	-24.46	26.97	46.00	-19.03	10.15
0.61	29.91	56.00	-26.09	25.13	46.00	-20.87	10.14
22.35	37.18	60.00	-22.82	29.35	50.00	-20.65	10.77
22.46	37.01	60.00	-22.99	29.40	50.00	-20.60	10.77

Read CD card mode




Test Data

Neutral

Frequency (MHz)	Quasi Peak (dBuV)	Limit (dBuV)	Margin (dB)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Factors (dB)
21.34	40.06	60.00	-19.94	33.27	50.00	-16.73	10.70
21.50	38.37	60.00	-21.63	31.45	50.00	-18.55	10.71
21.38	39.94	60.00	-20.06	32.95	50.00	-17.05	10.70
21.06	40.55	60.00	-19.45	33.48	50.00	-16.52	10.68
21.16	40.82	60.00	-19.18	33.87	50.00	-16.13	10.69
21.18	40.54	60.00	-19.46	33.49	50.00	-16.51	10.69

Connect to PC mode

Peak Detector  Quasi Peak Limit 
 Average Detector  Average Limit 




Test Data

Line

Frequency (MHz)	Quasi Peak (dBuV)	Limit (dBuV)	Margin (dB)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Factors (dB)
0.31	42.36	60.04	-17.69	34.19	50.04	-15.86	10.19
4.99	37.61	56.00	-18.39	30.18	46.00	-15.82	10.33
3.64	34.88	56.00	-21.12	26.38	46.00	-19.62	10.40
4.79	34.10	56.00	-21.90	24.55	46.00	-21.45	10.37
5.47	39.10	60.00	-20.90	30.80	50.00	-19.20	10.27
4.90	36.02	56.00	-19.98	27.04	46.00	-18.96	10.35

Connect to PC mode



Test Data

Neutral

Frequency (MHz)	Quasi Peak (dBuV)	Limit (dBuV)	Margin (dB)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Factors (dB)
4.97	37.25	56.00	-18.75	31.43	46.00	-14.57	10.34
0.45	37.52	56.89	-19.37	28.65	46.89	-18.24	10.17
4.92	36.57	56.00	-19.43	31.23	46.00	-14.77	10.34
5.39	39.40	60.00	-20.60	33.57	50.00	-16.43	10.28
5.43	38.90	60.00	-21.10	32.73	50.00	-17.27	10.27
4.80	35.61	56.00	-20.39	28.98	46.00	-17.02	10.37

Annex A. TEST INSTRUMENTATION

Annex A.i. TEST INSTRUMENTATION

Instrument	Model	Serial #	Calibration Due
Radiated Emissions			
R&S Receiver	ESPI 3	101216	05/25/2011
Sunol Sciences, Inc. antenna (30MHz~2GHz)	JB1	A112107	05/25/2011
HP Pre-amplifier	8447F	1937A01160	05/25/2011
Conducted Emissions			
R&S Receiver	ESPI 3	101216	05/25/2011
Com-Power LISN	LI 115	241090	05/25/2011
Com-Power LISN	LI 115	241091	05/25/2011
Com-Power LIMITER	LIT-153	531021	05/25/2011

Annex A. ii. RADIATED EMISSIONS TEST DESCRIPTION

EUT Characterisation

EUT characterisation, over the frequency range from 30MHz to 1GHz (for FCC tests, until the 5th harmonic for operating frequencies \geq 108MHz), was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer /receiver with the appropriate broadband antenna placed 3m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred, clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS).

Test Set-up

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table as shown in [Annex B](#).
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.

Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:
 - a. Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen.
 - b. The EUT was then rotated to the direction that gave the maximum emission.
 - c. Finally, the antenna height was adjusted to the height that gave the maximum emission.
3. A Quasi-peak measurement was then made for that frequency point.
4. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
5. The frequency range covered was from 30MHz to 1GHz (for FCC tests, until the 5th harmonic for operating frequencies \geq 108MHz), using the Biconical antenna for frequencies from 30MHz to 230MHz, Log-periodical antenna for frequencies from 230MHz to 1GHz, and the Horn antenna above 1GHz.

Sample Calculation Example

At 300 MHz	limit = 200 μ V/m = 46.00 dB μ V/m
Log-periodic antenna factor & cable loss at 300 MHz = 18.50 dB	
Q-P reading obtained directly from EMI Receiver = 40.00 dB μ V/m (Calibrated level including antenna factors & cable losses)	
Therefore, Q-P margin = 46.00 – 40.00 = 6.00	i.e. 6 dB below limit

Annex A.iii. CONDUCTED EMISSIONS TEST DESCRIPTION

Test Set-up

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B.
2. The power supply for the EUT was fed through a $50\Omega/50\mu\text{H}$ EUT LISN, connected to filtered mains.
3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.
4. All other supporting equipments were powered separately from another main supply.

Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.
3. High peaks, relative to the limit line, were then selected.
4. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 KHz. For FCC tests, only Quasi-peak measurements were made; while for CISPR/EN tests, both Quasi-peak and Average measurements were made.
5. Steps 2 to 4 were then repeated for the LIVE line (for AC mains) or DC line (for DC power).

Sample Calculation Example

At 20 MHz

limit = $250 \mu\text{V} = 47.96 \text{ dB}\mu\text{V}$

Transducer factor of LISN, pulse limiter & cable loss at 20 MHz = 11.20 dB

Q-P reading obtained directly from EMI Receiver = $40.00 \text{ dB}\mu\text{V}$
 (Calibrated for system losses)

Therefore, Q-P margin = $47.96 - 40.00 = 7.96$ i.e. **7.96 dB below limit**

Annex B. EUT AND TEST SETUP PHOTOGRAPHS

Annex B.i. Photograph 1: EUT External Photo



Front View of EUT



Rear View of EUT



Right View of EUT



Left View of EUT



Top View of EUT



Bottom View of EUT




Front View of lithium battery



Rear View of lithium battery



Front View of Remote Control



Rear View of Remote Control



Front View of Power Adapter



Rear View of Power Adapter

Annex B.ii. Photograph 2: EUT Internal Photo




Front View of LCD Panel




Rear View of LCD Panel




Front View of Main board PCB




Rear View of Main board PCB




Front View of Key Board




Rear View of Key Board



Rear View of Power switch board




Front View of Power switch board




Front View of Speakers




Rear View of Speakers




Front View of Receiver



Rear View of Receiver

Annex B.iii. Photograph 3: Test Setup Photo


Radiated Emission Test Setup Front View Below 1GHz




Radiated Emission Test Setup Rear View Below 1GHz




Radiated Emission Test Setup Front View Above 1GHz




Radiated Emission Test Setup Rear View Above 1GHz




Radiated Emission Test Setup Front View Connected to PC Below 1GHz



Radiated Emission Test Setup Rear View Connected to PC Below 1GHz



Radiated Emission Test Setup Front View Connected to PC Above 1GHz



Radiated Emission Test Setup Rear View Connected to PC Above 1GHz



Conducted Emission Test Setup Front View



Conducted Emission Test Setup Side View



Conducted Emission Test Setup Front View Connected to PC



Conducted Emission Test Setup Side View Connected to PC


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C. i. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Equipment Description (Including Brand Name)	Model & Serial Number	Cable Description (List Length, Type & Purpose)
Gateway Laptop	MS2288 & LXWHF02013951C3CA92200	N/A

Block Configuration Diagram for Conducted Emissions






SIEMIC, INC.
Accessing global markets

Title: EMC Test Report for IVIEW (IMENU) CLASSIC 10.2" DIGITAL DISPLAY
Model: UID0002-X
To: FCC Part 15 Subpart B Class B: 2010

Serial#: 10021087-FCC
Issue Date: 10 December, 2010
Page: 40 of 53
www.siemic.com.cn

Block Configuration Diagram for Radiated Emissions



Annex C.ii. EUT OPERATING CONDITIONS

The following is the description of how the EUT is exercised during testing.

Test	Description Of Operation
Emissions Testing	The EUT was working normally to stimulate the worst case.



SIEMIC, INC.

Accessing global markets

Title: EMC Test Report for IVIEW (IMENU) CLASSIC 10.2" DIGITAL DISPLAY
Model: UID0002-X
To: FCC Part 15 Subpart B Class B: 2010

Serial#: 10021087-FCC
Issue Date: 10 December, 2010
Page: 42 of 53
www.siemic.com.cn

Annex D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST

Please see attachment



Annex E. SIEMIC ACCREDITATION CERTIFICATES

SIEMIC ACCREDITATION DETAILS: A2LA Certificate Number: 2742.01



SIEMIC ACCREDITATION DETAILS: FCC Registration NO:986914

LABORATORY RECOGNITION



SIEMIC, INC.
Accessing global markets

Presented To:

SIEMIC (NANJING) INFOTECH CO. LTD.

Nanjing Laboratories

2-1 Longcang Avenue, Yuhua Economic Development Zone
Nanjing, Jiangsu Province, People's Republic of China

**This is to certify that SIEMIC Nanjing Laboratories has
been assessed per ISO 17025 and listed as
SIEMIC Recognized Laboratory for acceptance of Test
Reports for TCB Certifications for
the following scopes:**

FCC Unlicensed Scope A1, A2, A3, A4
FCC Licensed Scope B1, B2, B3

Leslie Bai
Director of Certification

This certificate of recognition is valid through December 31, 2010

2206 Ringwood Avenue, San Jose, California 95131 U.S.A.

Tel: (408) 526-1100 Fax: (408) 526-1060 www.siemic.com



SIEMIC, INC.

Accessing global markets

Title: EMC Test Report for IVIEW (IMENU) CLASSIC 10.2" DIGITAL DISPLAY
Model: UID0002-X
To: FCC Part 15 Subpart B Class B: 2010

Serial#: 10021087-FCC
Issue Date: 10 December, 2010
Page: 45 of 53
www.siemic.com.cn

SIEMIC ACCREDITATION DETAILS: FCC Listing, Registration NO:986914

FEDERAL COMMUNICATIONS COMMISSION

Laboratory Division
7435 Oakland Mills Road
Columbia, MD 21046

April 25, 2008

Registration Number: 986914

SIEMIC Nanjing (China) Laboratories
2-1 Longcang Avenue,
Yuhua Economic and Technology Development Park,
Nanjing, 210039
China

Attention: Leslie Bai

Re: Measurement facility located at 2-1 Longcang Avenue, Nanjing, China
Anechoic chamber (3 meters) and 3&10 meter OATS
Date of Listing: April 25, 2008

Dear Sir or Madam:

Your request for registration of the subject measurement facility has been reviewed and found to be in compliance with the requirements of Section 2.948 of the FCC rules. The information has, therefore, been placed on file and the name of your organization added to the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website www.fcc.gov under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,

Katie Hawkins
Electronics Engineer

SIEMIC ACCREDITATION DETAILS: Industry of Canada Registration No. 4842

February 19, 2009

OUR FILE: 46405-4842
Submission No: 131645

SIEMIC NANJING (CHINA) LABORATORIES
2-1 Longcang Avenue
Yuhua Economic & Technology Dev. Park
Nanjing
China

Attention: Leslie Bai

Dear Sir/Madame:

The Bureau has received your application for the registration of a 3m/10m alternative test site. Be advised that the information received was satisfactory to Industry Canada. The following number(s) is now associated to the site(s) for which registration / renewal was sought (4842B-1). Please reference the appropriate site number in the body of test reports containing measurements performed on the site. In addition, please keep for your records the following information;

- Your primary code is: 4842
- The company number associated to the site(s) located at the above address is: 4842B

Furthermore, to obtain or renew a unique site number, the applicant shall demonstrate that the site has been accredited to ANSI C63.4-2003 or later. A scope of accreditation indicating the accreditation by a recognized accreditation body to ANSI C63.4-2003 shall be accepted. Please indicate in a letter the previous assigned site number if applicable and the type of site (example: 3 meter OATS or 3 meter chamber). If the test facility is not accredited to ANSI C63.4-2003 or later, the test facility shall submit test data demonstrating full compliance with the ANSI standard. The Bureau will evaluate the filing to determine if recognition shall be granted.

The frequency for re-validation of the test site and the information that is required to be filed or retained by the testing party shall comply with the requirements established by the accrediting organization. However, in all cases, test site re-validation shall occur on an interval not to exceed two years. There is no fee or form associated with an OATS filing. OATS submissions are encouraged to be submitted electronically to the Bureau using the following URL;
http://strategis.ic.gc.ca/epic/internet/inceb-bhst.nsf/en/h_tt00052e.html.

If you have any questions, you may contact the Bureau by e-mail at certification_bureau@ic.gc.ca Please reference our file and submission number above for all correspondence.

Yours sincerely,

Joshua Laviolette
For: Wireless Laboratory Manager
Certification and Engineering Bureau
3701 Carling Ave, Building 94
P.O. Box 11490, Station "H"
Ottawa, Ontario K2H 8S2
Email: joshua.laviolette@ic.gc.ca
Tel. No. (613) 990-2681
Fax. No. (613) 990-4752

SIEMIC ACCREDITATION DETAILS: Korea CAB from NIST: US0160

UNITED STATES DEPARTMENT OF COMMERCE
National Institute of Standards and Technology
Gaithersburg, Maryland 20899

October 1, 2008

Mr. Leslie Bai
SIEMIC, Inc.
2206 Ringwood Avenue
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Radio Research Agency (RRA) Korea Communications Commission (KCC) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131
Identification No.: US0160
Recognized Scope: **EMI:** KCC Notice 2008-39, RRL Notice 2008-3: CA Procedures for EMI
KN22: Test Method for EMI
EMS: KCC Notice 2008-38, RRL Notice 2008-4: CA Procedures for EMS
KN24, KN-61000-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11: Test Method for EMS
Wireless: RRL Notice 2008-26, RRL Notice 2008-2, RRL Notice 2008-10,
RRL Notice 2007-49, RRL Notice 2007-20, RRL Notice 2007-21,
RRL Notice 2007-80, RRL Notice 2004-68
Wired: President Notice 20664, RRL Notice 2007-30,
RRL Notice 2008-7 with attachments 1, 3, 5, 6
President Notice 20664, RRL Notice 2008-7 with attachment 4

You may submit test data to RRA/KCC to verify that the equipment to be imported into Korea satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. If you have any questions please contact Ramona Saar at (301) 975-5521 or ramona.saar@nist.gov.

Sincerely,

David F. Alderman
Group Leader, Standards Coordination and Conformity Group
Standards Services Division

Enclosure

cc: Ramona Saar

SIEMIC ACCREDITATION DETAILS: Taiwan BSMI CAB Accreditation No. SL2-IN-E-1130R



UNITED STATES DEPARTMENT OF COMMERCE
 National Institute of Standards and Technology
 Gaithersburg, Maryland 20899-

May 3, 2006

Mr. Leslie Bai
 SIEMIC Laboratories
 2206 Ringwood Avenue
 San Jose, CA 95131

Dear Mr. Bai:

I am pleased to inform you that your laboratory has been recognized by the Chinese Taipei's Bureau of Standards, Metrology, and Inspection (BSMI) under the Asia Pacific Economic Cooperation (APEC) Mutual Recognition Arrangement (MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. You may submit test data to BSMI to verify that the equipment to be imported into Chinese Taipei satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements. The pertinent designation information is as follows:

- BSMI number: **SL2-IN-E-1130R** (Must be applied to the test reports)
- U.S Identification No: **US0160**
- Scope of Designation: **CNS 13438**
- Authorized signatory: **Mr. Leslie Bai**

The names of all recognized CABs will be posted on the NIST website at <http://ts.nist.gov/mra>. If you have any questions, please contact Mr. Dhillon at 301-975-5521. We appreciate your continued interest in our international conformity assessment activities.

Sincerely,

David F. Alderman
 Group Leader, Standards Coordination and Conformity Group

cc: Jogindar Dhillon

NIST

SIEMIC ACCREDITATION DETAILS: Taiwan NCC CAB ID: US0160

UNITED STATES DEPARTMENT OF COMMERCE
National Institute of Standards and Technology
Gaithersburg, Maryland 20899

March 16, 2009

Mr. LeslieBai
SIEMIC, Inc.
2206 Ringwood Avenue
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the National Communications Commission (NCC) for the requested scope expansion under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131
Identification No.: US0160
Current Scope: LP0002, PSTN01, ADSL01, ID0002, IS6100 and CNS 14336
Additional Scope: PLMN07

You may submit test data to NCC to verify that the equipment to be imported into China satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. If you have any questions please contact Ramona Saar at (301) 975-5521 or ramona.saar@nist.gov.

Sincerely,

David F. Alderman
Group Leader, Standards Coordination and Conformity Group
Standards Services Division

Enclosure

cc: Ramona Saar

SIEMIC ACCREDITATION DETAILS: Mexico NOM Recognition

CAMARA NACIONAL
DE LA INDUSTRIA
ELECTRONICA, DE
TELECOMUNICACIONES
E INFORMATICA

Laboratorio Valentín V. Rivero

México D.F. a 16 de octubre de 2006.

LESLIE BAI
DIRECTOR OF CERTIFICATION
SIEMIC LABORATORIES, INC.
ACCESSING GLOBAL MARKETS
P R E S E N T E

En contestación a su escrito de fecha 5 de septiembre del año en curso, le comento que estamos muy interesados en su intención de firmar un Acuerdo de Reconocimiento Mutuo, para lo cual adjunto a este escrito encontraría el Acuerdo en idioma inglés y español prellenado de los cuales le pido sea revisado y en su caso corregido, para que si está de acuerdo poder firmarlo para mandarlo con las autoridades Mexicanas para su visto bueno y así poder ejercer dicho acuerdo.

Aprovecha este escrito para mencionarte que nuestro intermediario gestor será la empresa Isotel de México, S.A. de C.V., empresa que ha colaborado durante mucho tiempo con nosotros en lo referido a la evaluación de la conformidad y que cuenta con amplia experiencia en la gestoría de la certificación de cumplimiento con Normas Oficiales Mexicanas de producto en México.

Me despido de usted enviándole un cordial saludo y esperando sus comentarios al Acuerdo que nos ocupa.

Atentamente:

Ing. Faustino Gómez González
Gerente Técnico del Laboratorio de
CANIETI



SIEMIC, INC.

Accessing global markets

Title: EMC Test Report for IVIEW (IMENU) CLASSIC 10.2" DIGITAL DISPLAY
Model: UID0002-X
To: FCC Part 15 Subpart B Class B: 2010

Serial#: 10021087-FCC
Issue Date: 10 December, 2010
Page: 51 of 53
www.siemic.com.cn

SIEMIC ACCREDITATION DETAILS: Hong Kong OFTA Recognition No. D23/16V



Your Ref 來函檔號 : D23/16 V
Our Ref 本局檔號 :

Telephone 電話 : (852) 2961 6320
(852) 2838 5004
Fax No 圖文傳真 :
E-mail 電郵地址 : 20 July 2005

Mr. Leslie Bai
Director of Certification,
SIEMIC Laboratories
2206 Ringwood Avenue
San Jose, California 95131
USA

Dear Mr. Bai,

Application of Recognised Testing Agency (RTA)

Referring your submission of 28 June 2005 in relation to the application of RTA, I am pleased to inform you that OFTA has appointed SIEMIC Laboratories (SIEMIC) as a Recognised Testing Agency (RTA) :

Please note that, under the Hong Kong Telecommunications Equipment Evaluation and Certification (HKTEC) Scheme, SIEMIC is authorized to conduct evaluation tests on telecommunications equipment against the following HKTA specifications :

Scope of recognition (HKTA Specifications) :

1001, 1002, 1004, 1006, 1007, 1008
1010, 1015, 1016
1022, 1026, 1027, 1029
1030, 1031, 1032, 1033, 1034, 1035, 1039
1041, 1042, 1043, 1045, 1047, 1048
2001

You are requested to refer to and comply with the code of practice and guidelines for RTA as given in the Information Note OFTA I 411 "Recognised Testing Agency (RTA) for Conducting Evaluation Test of Telecommunications Equipment", which can be downloaded from OFTA's homepage at <http://www.ofta.gov.hk/tec/information-notes.html>.

If you have any queries, please do not hesitate to contact me.

Yours sincerely,

(K K Sin)
for Director-General
of Telecommunications



SIEMIC, INC.

Accessing global markets

Title: EMC Test Report for IVIEW (IMENU) CLASSIC 10.2" DIGITAL DISPLAY
Model: UID0002-X
To: FCC Part 15 Subpart B Class B: 2010

Serial#: 10021087-FCC
Issue Date: 10 December, 2010
Page: 52 of 53
www.siemic.com.cn

SIEMIC ACCREDITATION DETAILS: OFTA CAB from NIST: US0160



UNITED STATES DEPARTMENT OF COMMERCE
National Institute of Standards and Technology
Gaithersburg, Maryland 20899

December 8, 2008

Mr. Leslie Bai
SIEMIC, Inc.
2206 Ringwood Avenue
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Office of the Telecommunications Authority (OFTA) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.
Physical Location: 2206 Ringwood Avenue, San Jose, California 95131 USA
Identification No.: US0160
Recognized Scope: **Radio:** HKTA 1002, 1007, 1008, 1010, 1015, 1016, 1020, 1022, 1026, 1027, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1039, 1041, 1042, 1043, 1044, 1046, 1047, 1048, 1049, 1051
Telecom: HKTA 2011, 2012, 2013, 2014, 2017, 2018, 2022, 2024, 2026, 2027, 2028, 2029, 2030, 2031, 2032, 2033

You may submit test data to OFTA to verify that the equipment to be imported into Hong Kong satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. If you have any questions please contact Ramona Saar at (301) 975-5521 or ramona.saar@nist.gov.

Sincerely,

David F. Alderman

David F. Alderman
Group Leader, Standards Coordination and Conformity Group
Standards Services Division

Enclosure

cc: Ramona Saar

NIST



SIEMIC, INC.

Accessing global markets

Title: EMC Test Report for iVIEW (iMENU) CLASSIC 10.2" DIGITAL DISPLAY
Model: UID0002-X
To: FCC Part 15 Subpart B Class B: 2010

Serial#: 10021087-FCC
Issue Date: 10 December, 2010
Page: 53 of 53
www.siemic.com.cn

SIEMIC ACCREDITATION DETAILS: Australia NATA Recognition



Leslie Bai
SiEMIC, Inc.
2206 Ringwood Avenue
San Jose, CA 95131

November 4, 2008

Under Australian government legislation, the Australian Communications and Media Authority (ACMA) has determined the National Association of Testing Authorities, Australia (NATA) as an accreditation body as per Section 409(1) of the Telecommunications Act 1997 (Cth). Pursuant to Section 409(2) of the Telecommunications Act 1997 (Cth), I am pleased to advise that your laboratory has been determined as a Recognised Testing Authority (RTA).

This determination has been made on the basis of your accreditation by A2LA accreditation no. 2742.01 and the Mutual Recognition Agreement between NATA and A2LA. It is effective from 11 July 2008. RTA status applies only to the following standards and is contingent upon their continued inclusion in your laboratory's scope of accreditation.

AS/ACIF S002, AS/ACIF S003, AS/ACIF S004,
AS/ACIF S006, AS/ACIF S016, AS/ACIF S031,
AS/ACIF S038, AS/ACIF S041 and
AS/ACIF S043.2

As an RTA, your laboratory has the following obligations:

1. the laboratory shall continue to meet all of the accreditation criteria of A2LA;
2. the authorised representative of the laboratory shall notify NATA of changes to the staff or operations of the laboratory which would affect the performance of the tests for which the laboratory has been determined;
3. compliance of equipment shall be reported on test reports bearing the A2LA logo/endorsement.

Current information on the Australian Communications and Media Authority and regulatory requirements for telecommunications products within Australia can be obtained from the ACMA's web-site at "<http://www.acma.gov.au>". Further information about NATA may be gained by visiting "<http://www.nata.asn.au>".

Please note that AS/ACIF S040 and New Zealand standards do not form part of the RTA scheme.

Your RTA listing will appear on the NATA website shortly.

Kind Regards

Chris Norton,
Senior Scientific Officer
Measurement Science and Technology
National Association of Testing Authorities (NATA)
71-73 Flemington Road
North Melbourne Vic 3051
Australia
Ph: +61 3 9329 1633 Fax: +61 3 9326 5148
E-Mail: Christopher.Norton@nata.asn.au
Internet: www.nata.asn.au