



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Applicant: Outform Ltd.

Address: R405, East, Buliding 203, Tai Ran Industrial Zone, Chengongmiao, Futian, Shenzhen, China

Product Name: Retail Tablet

Model Name: UID0350: RETAIL TABLET S, UID0354: RETAIL TABLET M, UID0350-XXX, UID0354-XXX (The first "X" is A-Z which stand for the color, The second "X" is A-Z which stand for the country, the third "X" is 0 or 1(0 is light color, 1 is dark color))

Brand Name: I-DISPLAY

FCC ID: Y34-UID0350

Report No.: MTE/EAH/E11121707

Date of Issue: Jan. 20, 2012

Issued by: Most Technology Service Co., Ltd.

Address: No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China

Tel: 86-755-8617 0306

Fax: 86-755-8617 0310

The report consists 32 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by MOST. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver.

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	3
2. GENERAL INFORMATION	4
2.1 Product Information	4
2.2 OBJECTIVE	5
2.3 TEST STANDARDS AND RESULTS	5
2.4 ENVIRONMENTAL CONDITIONS	5
3. TEST FACILITY	6
3.1 TEST FACILITY	6
3.2 GENERAL TEST PROCEDURES	6
3.3 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS	7
4. SETUP OF EQUIPMENT UNDER TEST	8
4.1 SUPPORT EQUIPMENT	8
4.2 TEST EQUIPMENT LIST	9
5. 47 CFR Part 15C 15.249 Requirements	10
5.1 SPURIOUS EMISSION TEST	10
5.1.1 REQUIREMENT	10
5.1.2 TEST DESCRIPTION	11
5.1.3 TEST DESCRIPTION	12
5.1.4 TEST RESULT	12
5.2 BAND EDGE	21
5.2.1 REQUIREMENT	21
5.2.2 TEST DESCRIPTION	21
5.2.3 TEST RESULT	21
5.3 LINE CONDUCTED EMISSION TEST	24
5.3.1. LIMITS OF LINE CONDUCTED EMISSION TEST	24
5.3.2. BLOCK DIAGRAM OF TEST SETUP	24
5.3.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	25
5.3.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	25
5.3.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	26
APPENDIX 1	30
PHOTOGRAPHS OF TEST SETUP	30

1. VERIFICATION OF CONFORMITY

Equipment Under Test: Retail Tablet

Brand Name: I-DISPLAY

Model Number: UID0350: RETAIL TABLET S, UID0354: RETAIL TABLET M

Series Model Number: UID0350-XXX, UID0354-XXX (The first "X" is A-Z which stand for the color, The second "X" is A-Z which stand for the country, the third "X" is 0 or 1(0 is light color, 1 is dark color))

1. The series models are different in model name and size with the same functions.
2. The size of "S" is 7 inch.
3. The size of "M" is 10 inch.

FCC ID: Y34-UID0350

Applicant: Outform Ltd.

R405, East, Building 203, Tai Ran Industrial Zone, Chengongmiao, Futian, Shenzhen, China

Manufacturer: Outform Ltd.

R405, East, Building 203, Tai Ran Industrial Zone, Chengongmiao, Futian, Shenzhen, China

Technical Standards: 47 CFR Part 15 Subpart C

File Number: MTE/EAH/E11121707

Date of test: Jan. 05-19, 2012

Deviation: None

Condition of Test Sample: Normal

Test Result: PASS

The above equipment was tested by MOST for compliance with the requirements set forth in FCC rules and the Technical Standards mentioned above. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment and the level of the immunity endurance of the equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

Prepared by (+ signature):

Dona Liu

Jan. 19, 2012



Review by (+ signature):

Elva Wong

Jan. 19, 2012

Approved by (+ signature):

Yvette Zhou(Manager)

Jan. 20, 2012

2. GENERAL INFORMATION

2.1 Product Information

Product	Retail Tablet
Trade Name	I-DISPLAY
Model Number	UID0350: RETAIL TABLET S, UID0354: RETAIL TABLET M
Series Number:	UID0350-XXX, UID0354-XXX(The first "X" is A-Z which stand for the color, The second "X" is A-Z which stand for the country, the third "X" is 0 or 1(0 is light color, 1 is dark color))
Description Differences:	<ol style="list-style-type: none"> 1. The series models are different in model name and size with the same functions. 2. The size of "S" is 7 inch. 3. The size of "M" is 10 inch.
Power Supply	DC 9V by AC adapter (100-240V, 50/60Hz)
Frequency Range	2402MHz -2480MHz
Modulation Type	FHSS(GFSK, Pi/4-DOPSK, 8-DPSK)
I/O Ports:	Output Port: Headphone Port, HDMI Port Input Port: SD Port, USB1 Port, USB2 Port, SIM Card, DC Power Port
Antenna Type:	Internal Fixed
Antenna Type:	2.0 dBi
Channel Spacing:	1MHz
Channel Number	79
Temperature Range	-20°C ~ 50°C

NOTE:

1. For a more detailed features description about the EUT, please refer to User's Manual.
2. The USB1 Port was Playing function with USB Stock function, the USB2 Port was connected with the Mouse, Two USB Ports are without data exchange function, The HDMI Port was connected with LCD Monitor through Link Line.

2.2 OBJECTIVE

Perform FCC Part 15 Subpart B tests for FCC Marking.

2.3 TEST STANDARDS AND RESULTS

Test items and the results are as bellow:

No.	Section	Description	Result	Date of Test
1	15.249(a)	Spurious Emission	PASS	Jan. 19, 2012
2	15.249(a)	Band Edge	PASS	Jan. 19, 2012
3	15.207	Power Line Conducted Emission Test	PASS	Jan. 19, 2012

Note: 1. The test result judgment is decided by the limit of measurement standard
2. The information of measurement uncertainty is available upon the customer's request.

2.4 ENVIRONMENTAL CONDITIONS

During the measurement the environmental conditions were within the listed ranges:

- Temperature: 15-35°C
- Humidity: 30-60 %
- Atmospheric pressure: 86-106 kPa

3. TEST FACILITY

3.1 TEST FACILITY

Test Site: Most Technology Service Co.,ltd

Location: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park, Nanshan, Shenzhen, Guangdong ,China

Description: There is one 3m semi-anechoic an area test sites and two line conducted labs for final test. The Open Area Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2009 and CISPR 16 requirements.

The FCC Registration Number is **490827**.

The **IC** Registration Number is **46405-7103**.

The **CNAS** Registration Number is **CNAS L3573**.

Site Filing: The site description is on file with the Federal Communications Commission, 7435 Oakland Mills Road, Columbia, MD 21046.

Instrument Tolerance: All measuring equipment is in accord with ANSI C63.4:2009 and CISPR 16 requirements that meet industry regulatory agency and accreditation agency requirement.

Ground Plane: Two conductive reference ground planes were used during the Line Conducted Emission, one in vertical and the other in horizontal. The dimensions of these ground planes are as below. The vertical ground plane was placed distancing 40 cm to the rear of the wooden test table on where the EUT and the support equipment were placed during test. The horizontal ground plane projected 50 cm beyond the footprint of the EUT system and distanced 80 cm to the wooden test table. For Radiated Emission Test, one horizontal conductive ground plane extended at least 1m beyond the periphery of the EUT and the largest measuring antenna, and covered the entire area between the EUT and the antenna.

3.2 GENERAL TEST PROCEDURES

EUT Function and Test Mode

The EUT has been tested under normal operating (TX) and standby (RX) condition.

All normal using modes of the normal function were tested but only the worst test data of the worst mode is reported by this report under GFSK modulation type.

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4:2009, Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4:2009.

3.3 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 – 0.110	16.42 – 16.423	399.9 – 410	4.5 – 5.15
¹ 0.495 – 0.505	16.69475 – 16.69525	608 – 614	5.35 – 5.46
2.1735 – 2.1905	16.80425 – 16.80475	960 – 1240	7.25 – 7.75
4.125 – 4.128	25.5 – 25.67	1300 – 1427	8.025 – 8.5
4.17725 – 4.17775	37.5 – 38.25	1435 – 1626.5	9.0 – 9.2
4.20725 – 4.20775	73 – 74.6	1645.5 – 1646.5	9.3 – 9.5
6.2125 – 6.2128	74.8 – 75.2	1660 – 1710	10.6 – 12.7
6.26775 – 6.26825	108 – 121.94	1718.8 – 1722.2	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2200 – 2300	14.47 – 14.5
8.291 – 8.294	149.9 – 150.05	2310 – 2390	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2483.5 – 2500	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	2655 – 2900	22.01 – 23.12
8.41425 – 8.41475	162.0125 – 167.17	3260 – 3267	23.6 – 24.0
12.29 – 12.293	167.72 – 173.2	3332 – 3339	31.2 – 31.8
12.51975 – 12.52025	240 – 285	3345.8 – 3358	36.43 – 36.5
12.57675 – 12.57725	322 – 335.4	3600 – 4400	(²)
13.36 – 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

4. SETUP OF EQUIPMENT UNDER TEST**4.1 SUPPORT EQUIPMENT**

Device Type	Brand	Model	Series No.	Data Cable	Power Cord
Headphone	AKG	K450	N/A		1.1M Un-Shielded

Remark:

All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.2 TEST EQUIPMENT LIST

Instrumentation: The following list contains equipment used at Most for testing. The equipment conforms to the CISPR 16-1 / ANSI C63.2 Specifications for Electromagnetic Interference and Field Strength Instrumentation from 10 kHz to 1.0 GHz or above.

No.	Equipment	Manufacturer	Model No.	S/N	Calculator due date
1	Test Receiver	Rohde & Schwarz	ESCI	100492	2012/03/14
2	L.I.S.N.	Rohde & Schwarz	ENV216	100093	2012/03/14
3	Coaxial Switch	Anritsu Corp	MP59B	6200283933	2012/03/14
4	Terminator	Hubersuhner	50Ω	No.1	2012/03/14
5	RF Cable	SchwarzBeck	N/A	No.1	2012/03/14
6	Test Receiver	Rohde & Schwarz	ESPI	101202	2012/03/14
7	Bilog Antenna	SCHWARZBECK	BBHA9120D	D69250	2012/03/14
8	Cable	Resenberger	N/A	NO.1	2012/03/14
9	Cable	SchwarzBeck	N/A	NO.2	2012/03/14
10	Cable	SchwarzBeck	N/A	NO.3	2012/03/14
11	DC Power Filter	DuoJi	DL2×30B	N/A	2012/03/14
12	Single Phase Power Line Filter	DuoJi	FNF 202B30	N/A	2012/03/14
13	3 Phase Power Line Filter	DuoJi	FNF 402B30	N/A	2012/03/14
14	Test Receiver	Rohde & Schwarz	ESCI	100492	2012/03/14
15	Absorbing Clamp	Luthi	MDS21	3635	2012/03/14
16	Coaxial Switch	Anritsu Corp	MP59B	6200283933	2012/03/14
17	AC Power Source	Kikusui	AC40MA	LM003232	2012/03/14
18	Test Analyzer	Kikusui	KHA1000	LM003720	2012/03/14
19	Line Impedance Network	Kikusui	LIN40MA-PCR-L	LM002352	2012/03/14
20	ESD Tester	Kikusui	KES4021	LM003537	2012/03/14
21	EMCPRO System	EM Test	UCS-500-M4	V0648102026	2012/03/14
22	Signal Generator	IFR	2032	203002/100	2012/03/14
23	Amplifier	A&R	150W1000	301584	2012/03/14
24	CDN	FCC	FCC-801-M2-25	47	2012/03/14
25	CDN	FCC	FCC-801-M3-25	107	2012/03/14
26	EM Injection Clamp	FCC	F-203I-23mm	403	2012/03/14
27	RF Cable	MIYAZAKI	N/A	No.1/No.2	2012/03/14
28	Universal Radio Communication Tester	ROHDE&SCHWARZ	CMU200	0304789	2012/03/14
29	Telecommunication Antenna	European Antennas	PSA 75301R/170	0304213	2012/03/14
30	Telecommunication Test Equipment	R&S	CMU200	N/A	2012/03/14
31	8 Loop Antenna	ARA	PLA-1030/B	1029	2012/02/19

NOTE: Equipments listed above have been calibrated and are in the period of validation.

5. 47 CFR Part 15C 15.249 Requirements

5.1 SPURIOUS EMISSION TEST

5.1.1 REQUIREMENT

According to FCC section 15.249(a):

Except as provided in paragraph (a) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (mV/m)	Field Strength of Harmonics (μV/m)
902-928	50	500
2400-2483.5	50	500
5725-5875	50	500
24000-24250	250	2500

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.


In the above emission table, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3


5.1.2 TEST DESCRIPTION


Test Setup:

From 9KHz to 30MHz:



Below 1GHz:



Above 1GHz:**5.1.3 TEST DESCRIPTION**

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:
 - Below 1GHz: RBW=100 kHz / VBW=300 kHz / Sweep=AUTO
 - Above 1GHz : (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
(b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.

5.1.4 TEST RESULT

The Bluetooth model was carried out for GFSK, Pi/4-DOPSK and 8-DPSK modulation types, GFSK Low channel modulation type was the worst case condition, The test data was shown on the summary data page.

Form 9 KHz to 30MHz:

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
N/A	H								>20
N/A	V								>20


-Note: No test data was detected in below 30MHz.

Below 1GHz



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement



Site: Site MOST 3M
Polarization: **Horizontal**
Temperature: 26
Limit: FCC Part 15 B 3M Radiation
Power: DC 9V Adapter AC 120V/60Hz
Humidity: 61 %
EUT: Retail Tablet
Distance:
M/N: UID0350: RETAIL TABLET S
Mode: Bluetooth Mode
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm		Table Degree	Comment
								Detector	degree		
1		201.6899	15.11	17.32	32.43	43.50	-11.07	QP			
2	!	258.9200	24.08	17.56	41.64	46.00	-4.36	QP			
3	!	345.2500	24.96	17.42	42.38	46.00	-3.62	QP			
4	*	374.3500	24.26	18.24	42.50	46.00	-3.50	QP			
5	!	431.5800	20.61	20.32	40.93	46.00	-5.07	QP			
6	!	605.2100	17.35	23.20	40.55	46.00	-5.45	QP			

*:Maximum data x:Over limit !:over margin

Engineer Signature: Allen



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement


File : UID0350: RETAIL TABLET S

Data : #21

Date: 2012-1-5

Time: 15:39:19

70.0 dBuV/m



Site site MOST 3M

Polarization: **Vertical**

Temperature: 26

Limit: FCC Part 15 B 3M Radiation

Power: DC 9V Adapter AC 120V/60Hz

Humidity: 61 %

EUT: Retail Tablet

Distance:

M/N: UID0350: RETAIL TABLET S

Mode: Bluetooth Mode

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	Antenna Table		
								Height	Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		258.9200	20.96	17.56	38.52	46.00	-7.48	QP		
2	!	288.0200	21.04	19.42	40.46	46.00	-5.54	QP		
3		316.1500	23.15	16.85	40.00	46.00	-6.00	QP		
4		345.2500	22.26	17.42	39.68	46.00	-6.32	QP		
5	!	403.4500	22.57	18.77	41.34	46.00	-4.66	QP		
6	*	431.5800	21.34	20.32	41.66	46.00	-4.34	QP		

*:Maximum data x:Over limit !:over margin

Engineer Signature: Allen



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement


File : UID0354: RETAIL TABLET M

Data #: 19

Date: 2012-1-5

Time: 7:58:11

70.0 dBuV/m



Site: site MOST 3M

Polarization: **Horizontal**

Temperature: 26

Limit: FCC Part 15 B 3M Radiation

Power: DC 9V Adapter AC 120V/60Hz

Humidity: 61 %

EUT: Retail Tablet

Distance:

M/N: UID0354: RETAIL TABLET M

Mode: Bluetooth Mode

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Table		
								Height	Degree	Comment
MHz		dBuV		dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	I	258.9200	25.08	17.56	42.64	46.00	-3.36	QP		
2	*	345.2500	25.46	17.42	42.88	46.00	-3.12	QP		
3	I	431.5800	21.11	20.32	41.43	46.00	-4.57	QP		
4	I	605.2100	18.85	23.20	42.05	46.00	-3.95	QP		
5		806.9699	12.96	25.90	38.86	46.00	-7.14	QP		
6		864.2000	11.20	27.04	38.24	46.00	-7.76	QP		

*:Maximum data x:Over limit !:over margin

Engineer Signature: Allen



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
 Guangdong, China
 Tel: 0755-86170306 Fax: 0755-86170310


Radiated Emission Measurement

File : UID0354: RETAIL TABLET M

Data #20

Date: 2012-1-5

Time: 8:03:29

70.0 dB_{uV/m}

Site site MOST 3M

Polarization: **Vertical**

Temperature: 26

Limit: FCC Part 15 B 3M Radiation

Power: DC 9V Adapter AC 120V/60Hz

Humidity: 61 %

EUT: Retail Tablet

Distance:

M/N: UID0354: RETAIL TABLET M

Mode: Bluetooth Mode

Note:

No.	Mk.	Freq. MHz	Reading Level dB _{uV}	Correct Factor dB	Measure- ment dB _{uV/m}	Limit dB _{uV/m}	Over dB	Antenna Height cm		Table Degree
								Detector	Comment	
1		86.2600	20.15	11.33	31.48	40.00	-8.52	QP		
2		208.4800	20.24	16.28	36.52	43.50	-6.98	QP		
3	!	258.9200	22.46	17.56	40.02	46.00	-5.98	QP		
4	*	288.0200	23.54	19.42	42.96	46.00	-3.04	QP		
5	!	345.2500	23.76	17.42	41.18	46.00	-4.82	QP		
6	!	547.0099	17.80	22.38	40.18	46.00	-5.82	QP		

*:Maximum data x:Over limit !:over margin

Engineer Signature: Allen

Above 1 GHz

Operation Mode: GFSK Mode/CH Low **Test Date:** Jan. 19, 2012
Temperature: 20°C **Tested by:** Habby Guo
Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak (dBuV)	AV (dBuV)	Ant. / CL CF	Actual Fs		Peak	AV	AV
							Limit	Limit	Margin
2402.0	H	94.36	70.51	9.07	103.43	79.58	114.00	94.00	-14.42
1612.5	H	54.29	33.58	6.05	60.34	39.63	74.00	54.00	-14.37
4815.0	H	47.98	25.06	17.05	65.04	42.11	74.00	54.00	-11.89
N/A									>20
2402.0	V	93.27	68.49	9.07	102.34	77.56	114.00	94.00	-16.44
1612.5	V	52.41	31.08	6.05	58.46	38.13	74.00	54.00	-15.87
4815.0	V	46.86	26.15	17.05	64.91	49.20	74.00	54.00	-10.80
N/A	V								

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = auto.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = auto

Operation Mode: GFSK Mode/CH Mid **Test Date:** Jan. 19, 2012
Temperature: 20°C **Tested by:** Habby Guo
Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak (dBuV/m)	AV (dBuV/m)	AV
					Peak (dBuV/m)	AV (dBuV/m)			
2441.0	H	92.64	71.45	9.07	101.71	80.52	114.00	94.00	-13.48
1612.5	H	52.78	30.49	6.05	58.83	36.54	74.00	54.00	-17.46
4815.0	H	45.62	24.02	17.05	62.67	41.07	74.00	54.00	-12.93
N/A									>20
2441.0	V	91.82	69.27	9.07	100.89	78.34	114.00	94.00	-15.66
1612.5	V	50.10	32.95	6.05	56.15	39.00	74.00	54.00	-15.00
4815.0	V	43.35	27.84	17.05	60.40	44.89	74.00	54.00	-9.11
N/A	V								>20

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = *auto*.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = *auto*.

Operation Mode: GFSK Mode/CH High **Test Date:** Jan. 19, 2012
Temperature: 20°C **Tested by:** Habby Guo
Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak (dBuV)	AV (dBuV)	Ant. / CL CF	Actual Fs		Peak	AV	AV
							Limit	Limit	Margin
				(dB)	Peak (dBuV/m)	AV (dBuV/m)			
2480.0	H	90.04	68.72	9.07	99.11	77.79	114.00	94.00	-16.21
1612.5	H	49.62	28.16	6.05	55.67	34.21	74.00	54.00	-19.79
4815.0	H	41.34	19.46	17.05	61.39	37.51	74.00	54.00	-16.49
N/A									>20
2480.0	V	89.58	67.82	9.07	98.65	76.89	114.00	94.00	-17.11
1612.5	V	48.27	27.51	6.05	54.32	33.56	74.00	54.00	-20.44
4815.0	V	47.82	26.81	17.05	64.87	43.86	74.00	54.00	-10.14
N/A	V								>20

Notes:


1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = *auto*.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = *auto*.

5.2 BAND EDGE

5.2.1 REQUIREMENT

According to FCC section 15.249(a), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.


5.2.2 TEST DESCRIPTION




5.2.3 TEST RESULT

The EUT operates at hopping-off test mode. The lowest and highest channels are tested to verify the band edge emissions.


Test Mode		Channel Marked Frequency	Limit (dBuv/m)	Test Result Highest Emission (dBuv/m)			
				Vertical		Horizontal	
				Peak	Average	Peak	Average
Bluetooth	Low Channel	2390MHz	74(Peak) 54(Average)	59.02	36.25	68.16	47.45
		2400MHz		66.86	46.38	73.36	53.78
	High Channel	2483.5MHz		69.77	48.75	60.56	40.69
		2500MHz		60.29	39.08	67.69	45.47

Test Plot:


(CH Low, Horizontal)



(CH Low, Vertical)



(CH High, Horizontal)



(CH High, Vertical)

5.3 LINE CONDUCTED EMISSION TEST


5.3.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P. (dBuV)	Average(dBuV)
150kHz-500kHz	66-56	56-46
500kHz-5MHz	56	46
5MHz-30MHz	60	50

****Note:** 1. the lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

5.3.2. BLOCK DIAGRAM OF TEST SETUP



5.3.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per FCC Part 15 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per FCC Part 15.
- 3) All I/O cables were positioned to simulate typical actual usage as per FCC Part 15.
- 4) The EUT through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5) All support equipments received power from a second LISN supplying power of AC 120V/60Hz, if any.
- 6) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7) Analyzer / Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.
- 8) During the above scans, the emissions were maximized by cable manipulation.

5.3.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

EUT and support equipment was set up on the test bench as per step 9 of the preliminary test.

A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.


The Bluetooth model was carried out for GFSK, Pi/4-DOPSK and 8-DPSK modulation types, GFSK Low channel modulation type was the worst case condition, The test data was shown on the summary data page.

5.3.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Conducted Emission Measurement



Site: site MOST 3M Phase: **L1** Temperature: 26

Limit: FCC Part15 B Class B QP Power: DC 9V Adapter AC 120V/60Hz Humidity: 60 %

EUT: Retail Tablet

M/N: UID0350: RETAIL TABLET S

Mode: Bluetooth Mode

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1	*	0.1700	44.43	10.20	54.63	64.96	-10.33	QP
2		0.2060	39.97	11.96	51.93	63.36	-11.43	QP
3		0.5780	30.12	10.00	40.12	56.00	-15.88	QP
4		1.4100	25.62	9.59	35.21	56.00	-20.79	QP
5		2.4380	21.01	9.44	30.45	56.00	-25.55	QP
6		6.9298	18.47	10.84	29.31	60.00	-30.69	QP


*:Maximum data x:Over limit !:over margin

Engineer Signature: Rex



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Conducted Emission Measurement



Site: site MOST 3M

Phase: N

Temperature: 26

Limit: FCC Part15 B Class B QP

Power: DC 9V Adapter AC 120V/60Hz

Humidity: 60 %

EUT: Retail Tablet

M/N: UID0350: RETAIL TABLET S

Mode: Bluetooth Mode

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dB	Over Detector	Over
								Comment
1	*	0.1700	44.93	10.20	55.13	64.96	-9.83	QP
2		0.2140	41.16	11.91	53.07	63.04	-9.97	QP
3		0.4900	31.54	10.07	41.61	56.17	-14.56	QP
4		1.4460	28.26	9.55	37.81	56.00	-18.19	QP
5		4.8939	20.34	11.89	32.23	56.00	-23.77	QP
6		23.7660	18.56	9.00	27.56	60.00	-32.44	QP


*:Maximum data x:Over limit !:over margin

Engineer Signature: Rex



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
 Guangdong, China
 Tel: 0755-86170306 Fax: 0755-86170310

Conducted Emission Measurement



Site: site MOST 3M

Phase: L1

Temperature: 26

Limit: FCC Part15 B Class B QP

Power: DC 9V Adapter AC 120V/60Hz

Humidity: 60 %

EUT: Retail Tablet

M/N: UID0354: RETAIL TABLET M

Mode: Bluetooth Mode

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dB	Over Detector	Over	
								Comment	
1	*	0.1620	44.25	9.72	53.97	65.36	-11.39	QP	
2		0.2140	39.04	11.91	50.95	63.04	-12.09	QP	
3		0.4220	32.49	10.52	43.01	57.41	-14.40	QP	
4		1.0420	27.47	9.96	37.43	56.00	-18.57	QP	
5		1.5580	26.35	9.44	35.79	56.00	-20.21	QP	
6		4.8939	18.52	11.89	30.41	56.00	-25.59	QP	


*:Maximum data x:Over limit !:over margin

Engineer Signature: Allen



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Conducted Emission Measurement



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dB	Over	
							Detector	Comment
1	*	0.1580	45.47	9.49	54.96	65.56	-10.60	QP
2		0.4500	31.18	10.33	41.51	56.87	-15.36	QP
3		1.1060	29.16	9.89	39.05	56.00	-16.95	QP
4		2.8460	20.92	9.85	30.77	56.00	-25.23	QP
5		4.5379	18.31	11.54	29.85	56.00	-26.15	QP
6		9.2379	12.19	9.46	21.65	60.00	-38.35	QP

*:Maximum data x:Over limit !:over margin


Engineer Signature: Allen


APPENDIX 1
PHOTOGRAPHS OF TEST SETUP

CE TEST SETUP



RE TEST SETUP





SPURIOUS EMISSION TEST SETUP



-----END OF REPORT-----