



---

# SAR Test Report

---

Report No.: AGC00946130901FH01

**FCC ID** : Y3GGALAPAD6

**APPLICATION PURPOSE** : Original Equipment

**PRODUCT DESIGNATION** : Smart Phone

**BRAND NAME** : Galapad, Sosmart

**MODEL NAME** : Galapad 6

**CLIENT** : Galaxy Microsystems Ltd.

**DATE OF ISSUE** : Sep.13, 2013

**STANDARD(S)** : IEEE Std. 1528:2003  
47CFR § 2.1093  
IEEE/ANSI C95.1

**REPORT VERSION** : V1.0

Attestation of Global Compliance(Shenzhen) Co., Ltd.



**CAUTION:**

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

### Report Revise Record

| Report Version | Revise Time | Issued Date  | Valid Version | Notes           |
|----------------|-------------|--------------|---------------|-----------------|
| V1.0           | /           | Sep.13, 2013 | Valid         | Original Report |

| Test Report Certification |                                                                                                                                                                                                                                        |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Applicant Name            | : Galaxy Microsystems Ltd.                                                                                                                                                                                                             |
| Applicant Address         | : Room1101-1103, 11/F, Enterprise Square Tow, 3 Sheung, Yuet Road, Kowloon Bay, Kowloon, Hong Kong                                                                                                                                     |
| Manufacturer Name         | : Shen Zhen Project Enterprise Co., LTD.                                                                                                                                                                                               |
| Manufacturer Address      | : R106, 30 Building, Zhiheng Industrial Park, Nantou Checkpoint, Nanshan District, Shenzhen                                                                                                                                            |
| Product Designation       | : Smart Phone                                                                                                                                                                                                                          |
| Brand Name                | : Galapad, Sosmart                                                                                                                                                                                                                     |
| Model Name                | : Galapad 6                                                                                                                                                                                                                            |
| Different Description     | N/A                                                                                                                                                                                                                                    |
| EUT Voltage               | : DC3.7V by battery                                                                                                                                                                                                                    |
| Applicable Standard       | : IEEE Std. 1528:2003<br>47CFR § 2.1093<br>IEEE/ANSI C95.1                                                                                                                                                                             |
| Test Date                 | : Sep.12, 2013                                                                                                                                                                                                                         |
| Test Results              | : MAX SAR MEASUREMENT(1g)<br>Head: <b>0.406</b> W/Kg Body: <b>0.266</b> W/Kg (2G)<br>Head: <b>0.933</b> W/Kg Body: <b>0.697</b> W/Kg (3G)<br>(Maximum Scaling SAR = <b>1.018</b> W/Kg)<br>simultaneous transmission: <b>1.129</b> W/Kg |
| Performed Location        | : Attestation of Global Compliance(Shenzhen) Co., Ltd.<br>2 F, Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang Street, Bao'an District, Shenzhen, China                                                  |
| Report Template           | : AGCRT-US-3G/SAR (2013-03-01)                                                                                                                                                                                                         |

Tested By

*Sun YIN*

Sun Yin

Sep.13, 2013

Checked By

*Angela Li*

Angela Li

Sep.13, 2013

Authorized By

*Solger Zhang*

Solger Zhang

Sep.13, 2013

**TABLE OF CONTENTS**

**1. GENERAL INFORMATION..... 5**

1.1. EUT DESCRIPTION..... 5

1.2. TEST PROCEDURE ..... 7

1.3. TEST ENVIRONMENT..... 7

**2. SAR MEASUREMENT SYSTEM ..... 8**

2.1. COMOSAR SYSTEM DESCRIPTION..... 8

2.2. COMOSAR E-FIELD PROBE ..... 10

2.3. ROBOT..... 10

2.4. VIDEO POSITIONING SYSTEM ..... 11

2.5. DEVICE HOLDER ..... 11

2.6. SAM TWIN PHANTOM..... 12

**3. TISSUE SIMULATING LIQUID..... 13**

3.1. THE COMPOSITION OF THE TISSUE SIMULATING LIQUID..... 13

3.2. TISSUE CALIBRATION RESULT ..... 14

3.3. TISSUE DIELECTRIC PARAMETERS FOR HEAD AND BODY PHANTOMS..... 15

**4. SAR MEASUREMENT PROCEDURE ..... 16**

4.1. SAR SYSTEM VALIDATION..... 16

4.2. SAR MEASUREMENT PROCEDURE ..... 18

**5. SAR EXPOSURE LIMITS ..... 19**

**6. TEST EQUIPMENT LIST ..... 20**

**7. MEASUREMENT UNCERTAINTY ..... 21**

**8. CONDUCTED POWER MEASUREMENT ..... 22**

**9. TEST RESULTS ..... 27**

9.1. SAR TEST RESULTS SUMMARY ..... 27

**APPENDIX A. SAR SYSTEM VALIDATION DATA ..... 42**

**APPENDIX B. SAR MEASUREMENT DATA..... 48**

**APPENDIX C. TEST SETUP PHOTOGRAPHS &EUT PHOTOGRAPHS ..... 128**

**APPENDIX D. PROBE CALIBRATION DATA ..... 140**

**APPENDIX E. DIPOLE CALIBRATION DATA..... 150**

## 1. General Information

### 1.1. EUT Description

| General Information                     |                                                                                                                                                                                                                                                                                       |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Designation                     | Smart Phone                                                                                                                                                                                                                                                                           |
| Test Model                              | Galapad 6                                                                                                                                                                                                                                                                             |
| Hardware Version                        | TJ63-MB-V1.0                                                                                                                                                                                                                                                                          |
| Software Version                        | N/A                                                                                                                                                                                                                                                                                   |
| Device Category                         | Portable                                                                                                                                                                                                                                                                              |
| RF Exposure Environment                 | Uncontrolled                                                                                                                                                                                                                                                                          |
| Antenna Type                            | Internal                                                                                                                                                                                                                                                                              |
| GSM and GPRS                            |                                                                                                                                                                                                                                                                                       |
| Support Band                            | <input checked="" type="checkbox"/> GSM 850 <input checked="" type="checkbox"/> PCS 1900 (U.S. Bands)<br><input checked="" type="checkbox"/> GSM 900 <input checked="" type="checkbox"/> DCS 1800 (Non-U.S. Bands)                                                                    |
| GPRS Type                               | Class B                                                                                                                                                                                                                                                                               |
| GPRS Class                              | Class 8,10 ,12(1Tx+4Rx, 2Tx+3Rx, 3Tx+2Rx, 4Tx+1Rx)                                                                                                                                                                                                                                    |
| TX Frequency Range                      | GSM 850 : 824.2~848.8MHz;<br>PCS 1900: 1850.2~1909.8MHz;                                                                                                                                                                                                                              |
| RX Frequency Range                      | GSM 850 : 869~894MHz<br>PCS 1900: 1930~1990MHz                                                                                                                                                                                                                                        |
| Release Version                         | R99                                                                                                                                                                                                                                                                                   |
| Type of modulation                      | GMSK for GSM/GPRS                                                                                                                                                                                                                                                                     |
| Antenna Gain                            | 1.0dBi                                                                                                                                                                                                                                                                                |
| Avg. Burst Power<br>(Max. Output Power) | GSM835: 31.56dBm(32.47dBm- Peak Power)<br>PCS1900: 28.71dBm(29.64dBm-Peak Power)                                                                                                                                                                                                      |
| WCDMA                                   |                                                                                                                                                                                                                                                                                       |
| Support Band                            | U.S. Bands: <input checked="" type="checkbox"/> UMTS FDD Band II <input checked="" type="checkbox"/> UMTS FDD Band V<br>Non-U.S. Bands:<br><input checked="" type="checkbox"/> UMTS FDD Band I <input type="checkbox"/> UMTS FDD Band III <input type="checkbox"/> UMTS FDD Band VIII |
| HS Type                                 | HSPA(HSUPA/HSDPA)                                                                                                                                                                                                                                                                     |
| TX Frequency Range                      | WCDMA FDD Band II: 1852.4 -1907.6MHz<br>WCDMA FDD Band V: 826.4-846.6MHz                                                                                                                                                                                                              |

|                                         |                                                                                                                                                                                                                          |
|-----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RX Frequency Range                      | WCDMA FDD Band II: 1930-1990MHz<br>WCDMA FDD Band V: 869-894MHz                                                                                                                                                          |
| Release Version                         | Rel-6                                                                                                                                                                                                                    |
| Type of modulation                      | QPSK                                                                                                                                                                                                                     |
| Antenna Gain                            | 0.8dBi                                                                                                                                                                                                                   |
| Avg. Burst Power<br>(Max. Output Power) | Band II: 22.62dBm (23.60dBm- Peak Power)<br>Band V: 23.06dBm (23.33dBm- Peak Power)                                                                                                                                      |
| <b>Bluetooth</b>                        |                                                                                                                                                                                                                          |
| Bluetooth Version                       | <input type="checkbox"/> V2.0 <input type="checkbox"/> V2.1 <input checked="" type="checkbox"/> V2.1+EDR <input type="checkbox"/> V3.0 <input type="checkbox"/> V3.0+EDR <input type="checkbox"/> V4.0                   |
| Operation Frequency                     | 2402~2480MHz                                                                                                                                                                                                             |
| Type of modulation                      | <input checked="" type="checkbox"/> GFSK <input checked="" type="checkbox"/> π/4-DQPSK <input checked="" type="checkbox"/> 8-DPSK                                                                                        |
| Avg. Burst Power                        | 2.31dBm                                                                                                                                                                                                                  |
| Antenna Gain                            | 1.2dBi                                                                                                                                                                                                                   |
| <b>WIFI</b>                             |                                                                                                                                                                                                                          |
| WIFI Specification                      | <input type="checkbox"/> 802.11a <input checked="" type="checkbox"/> 802.11b <input checked="" type="checkbox"/> 802.11g <input checked="" type="checkbox"/> 802.11n(20) <input checked="" type="checkbox"/> 802.11n(40) |
| Operation Frequency                     | 2412~2462MHz                                                                                                                                                                                                             |
| Avg. Burst Power                        | 11b: 10.03 dBm,11g: 9.02dBm,11n(20): 8.43dBm,11n(40): 5.66dBm                                                                                                                                                            |
| Antenna Gain                            | 1.2dBi                                                                                                                                                                                                                   |
| <b>Accessories</b>                      |                                                                                                                                                                                                                          |
| Battery                                 | Brand name: Galapad, Sosmart<br>Model No. : ADFSZ-013-TJ63<br>Voltage and Capacitance: 3.7 V & 3000mAh                                                                                                                   |
| Adapter                                 | Brand name: Galapad, Sosmart<br>Model No. : JT-M05100<br>Input: AC 100-240V, 50-60Hz,150mA   Output: DC5.0V, 1A                                                                                                          |
| Earphone                                | Brand name: N/A<br>Model No. : N/A                                                                                                                                                                                       |

Note:

1. The EUT is a model of GSM Portable Mobile Station (MS). It supports GSM/GPRS, BT, WIFI, and support hot spot mode.
2. The sample used for testing is end product.

### 1.2. Test Procedure

|   |                                                                     |
|---|---------------------------------------------------------------------|
| 1 | Setup the EUT and simulators as shown on above.                     |
| 2 | Turn on the power of all equipment.                                 |
| 3 | EUT Communicate with 8960, and test them respectively at U.S. bands |


### 1.3. Test Environment

Ambient conditions in the laboratory:

| Items            | Required | Actual |
|------------------|----------|--------|
| Temperature (°C) | 18-25    | 21± 2  |
| Humidity (%RH)   | 30-70    | 55±2   |

## 2. SAR Measurement System

### 2.1. COMOSAR System Description



The COMOSAR system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot with controller, teach pendant and software.

- An arm extension for accommodating the data acquisition electronics (DAE).

- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital Communicate to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.

- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.

- A computer running WinXP and the Opensar software.

- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.

- The phantom, the device holder and other accessories according to the targeted measurement.

#### 2.1.1. Applications

Predefined procedures and evaluations for automated compliance testing with all worldwide standards, e.g., IEEE 1528, OET 65, IEC 62209-1, IEC 62209-2, EN 50360, EN 50383 and others.

### 2.1.2. Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 10mm<sup>2</sup> step integral, with 1mm interpolation used to locate the peak SAR area used for zoom scan assessments.

When an Area Scan has measured all reachable points, it computes the field maxima found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE 1528-2003, EN 50361 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan).

### 2.1.3. Zoom Scan (Cube Scan Averaging)

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. A density of 1000 kg/m<sup>3</sup> is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1 g cube is 10mm, with the side length of the 10 g cube 21,5mm.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications utilize a physical step of 7x7x7 (5mmx5mmx5mm) providing a volume of 30mm in the X & Y axis, and 30mm in the Z axis.

### 2.1.4. Uncertainty of Inter-/Extrapolation and Averaging

In order to evaluate the uncertainty of the interpolation, extrapolation and averaged SAR calculation algorithms of the Post processor, COMOSAR allows the generation of measurement grids which are artificially predefined by analytically based test functions. Therefore, the grids of area scans and zoom scans can be filled with uncertainty test data, according to the SAR benchmark functions of IEEE 1528. The three analytical functions shown in equations as below are used to describe the possible range of the expected SAR distributions for the tested handsets. The field gradients are covered by the spatially flat distribution f1, the spatially steep distribution f3 and f2 accounts for H-field cancellation on the phantom/tissue surface.

$$f_1(x, y, z) = A e^{-\frac{z}{2a}} \cos^2 \left( \frac{\pi}{2} \frac{\sqrt{x'^2 + y'^2}}{5a} \right)$$

$$f_2(x, y, z) = A e^{-\frac{z}{a}} \frac{a^2}{a^2 + x'^2} \left( 3 - e^{-\frac{2z}{a}} \right) \cos^2 \left( \frac{\pi}{2} \frac{y'}{3a} \right)$$

$$f_3(x, y, z) = A \frac{a^2}{\frac{a^2}{4} + x'^2 + y'^2} \left( e^{-\frac{2z}{a}} + \frac{a^2}{2(a + 2z)^2} \right)$$


## 2.2. COMOSAR E-Field Probe

The SAR measurement is conducted with the dissymmetric probe manufactured by SATIMO.

The probe is specially designed and calibrated for use in liquid with high permittivity. The dissymmetric probe has special calibration in liquid at different frequency.

SATIMO conducts the probe calibration in compliance with international and national standards (e.g. IEEE 1528, EN62209-1, IEC 62209, etc.) Under ISO17025. The calibration data are in Appendix D.

### 2.2.1. Isotropic E-Field Probe Specification

|               |                                                                                                                                                                                                            |                                                                                     |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Model         | EP165                                                                                                                                                                                                      |                                                                                     |
| Manufacture   | SATIMO                                                                                                                                                                                                     |                                                                                     |
| Frequency     | 0.03GHz-3 GHz<br>Linearity:±0.2dB(30 MHz-3 GHz)                                                                                                                                                            |  |
| Dynamic Range | 0.01W/Kg-100W/Kg<br>Linearity:±0.2dB                                                                                                                                                                       |                                                                                     |
| Dimensions    | Overall length:330mm<br>Length of individual dipoles:4.5mm<br>Maximum external diameter:8mm<br>Probe Tip external diameter:5mm<br>Distance between dipoles/ probe extremity:2.7mm                          |                                                                                     |
| Application   | High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 3 GHz with precision of better 30%. |                                                                                     |

## 2.3. Robot

The COMOSAR system uses the KUKA robot from SATIMO SA (France).For the 6-axis controller COMOSAR system, the KUKA robot controller version from SATIMO is used.

The XL robot series have many features that are important for our application:

- High precision (repeatability 0.02 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)
- 6-axis controller




## 2.4. Video Positioning System

The video positioning system is used in OpenSAR to check the probe. Which is composed of a camera, LED, mirror and mechanical parts. The camera is piloted by the main computer with firewire link.

During the process, the actual position of the probe tip with respect to the robot arm is measured, as well as the probe length and the horizontal probe offset. The software then corrects all movements, such that the robot coordinates are valid for the probe tip.

The repeatability of this process is better than 0.1 mm. If a position has been taught with an aligned probe, the same position will be reached with another aligned probe within 0.1 mm, even if the other probe has different dimensions. During probe rotations, the probe tip will keep its actual position.




## 2.5. Device Holder

The COMOSAR device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR).

Thus the device needs no repositioning when changing the angles.

The COMOSAR device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon_r \approx 3$  and loss tangent  $\delta = 0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



## 2.6. SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region where shell thickness increases to 6mm). It has three measurement areas:

- Left head
- Right head
- Flat phantom



The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

### 3. Tissue Simulating Liquid

#### 3.1. The composition of the tissue simulating liquid

| Ingredient       | 835MHz | 835MHz | 1900MHz | 1900MHz | 2450MHz | 2450MHz |
|------------------|--------|--------|---------|---------|---------|---------|
| (% Weight)       | Head   | Body   | Head    | Body    | Head    | Body    |
| <b>Water</b>     | 40.45  | 52.4   | 54.90   | 40.5    | 46.7    | 73.2    |
| <b>Salt</b>      | 1.42   | 1.40   | 0.18    | 0.50    | 0.00    | 0.04    |
| <b>Sugar</b>     | 57.6   | 45.0   | 0.00    | 58.0    | 0.00    | 0.00    |
| <b>HEC</b>       | 0.40   | 1.00   | 0.00    | 0.50    | 0.00    | 0.00    |
| <b>Preventol</b> | 0.10   | 0.20   | 0.00    | 0.50    | 0.00    | 0.00    |
| <b>DGBE</b>      | 0.00   | 0.00   | 44.92   | 0.00    | 53.3    | 26.7    |
| <b>TWEEN</b>     | 0.00   | 0.00   | 0.00    | 0.00    | 0.00    | 0.00    |

### 3.2. Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using COMOSAR Dielectric Probe Kit and R&S Network Analyzer ZVL6 .

| Tissue Stimulant Measurement for GSM 835 |       |                                |                                        |                                        |                  |
|------------------------------------------|-------|--------------------------------|----------------------------------------|----------------------------------------|------------------|
| Frequency (MHz)                          | Parts | Description                    | Dielectric Parameters                  |                                        | Tissue Temp [°C] |
| 835MHz                                   | Head  | Reference result<br>±5% window | $\epsilon_r$<br>41.50<br>39.425-43.575 | $\delta[s/m]$<br>0.90<br>0.855-0.945   | N/A              |
|                                          |       | Sep.12, 2013                   | 39.97                                  | 0.91                                   | 21               |
| 835MHz                                   | Body  | Reference result<br>±5% window | $\epsilon_r$<br>55.20<br>52.44-57.96   | $\delta[s/m]$<br>0.97<br>0.9215-1.0185 | N/A              |
|                                          |       | Sep.12, 2013                   | 53.26                                  | 0.95                                   | 21               |

| Tissue Stimulant Measurement for PCS 1900 |       |                                |                                        |                                      |                  |
|-------------------------------------------|-------|--------------------------------|----------------------------------------|--------------------------------------|------------------|
| Frequency (MHz)                           | Parts | Description                    | Dielectric Parameters                  |                                      | Tissue Temp [°C] |
| 1900MHz                                   | Head  | Reference result<br>±5% window | $\epsilon_r$<br>40.00<br>38.00-42.00   | $\delta[s/m]$<br>1.40<br>1.33-1.47   | N/A              |
|                                           |       | Sep.12, 2013                   | 40.33                                  | 1.38                                 | 21               |
| 1900MHz                                   | Body  | Reference result<br>±5% window | $\epsilon_r$<br>53.30<br>50.635-55.965 | $\delta[s/m]$<br>1.52<br>1.444-1.596 | N/A              |
|                                           |       | Sep.12, 2013                   | 54.12                                  | 1.53                                 | 21               |

| Tissue Stimulant Measurement for 2450 |       |                                |                                       |                                        |                  |
|---------------------------------------|-------|--------------------------------|---------------------------------------|----------------------------------------|------------------|
| Frequency (MHz)                       | Parts | Description                    | Dielectric Parameters                 |                                        | Tissue Temp [°C] |
| 2450MHz                               | Head  | Reference result<br>±5% window | $\epsilon_r$<br>39.2<br>37.24-41.16   | $\delta[s/m]$<br>1.80<br>1.71-1.89     | N/A              |
|                                       |       | Sep.12, 2013                   | 40.57                                 | 1.78                                   | 21               |
|                                       | Body  | Reference result<br>±5% window | $\epsilon_r$<br>52.7<br>50.065-55.335 | $\delta[s/m]$<br>1.95<br>1.8525-2.0475 | N/A              |
|                                       |       | Sep.12, 2013                   | 53.46                                 | 1.89                                   | 21               |

### 3.3. Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.


| Target Frequency<br>(MHz) | head         |                | body         |                |
|---------------------------|--------------|----------------|--------------|----------------|
|                           | $\epsilon_r$ | $\sigma$ (S/m) | $\epsilon_r$ | $\sigma$ (S/m) |
| 300                       | 45.3         | 0.87           | 58.2         | 0.92           |
| 450                       | 43.5         | 0.87           | 56.7         | 0.94           |
| <b>835</b>                | <b>41.5</b>  | <b>0.90</b>    | <b>55.2</b>  | <b>0.97</b>    |
| 900                       | 41.5         | 0.97           | 55.0         | 1.05           |
| 915                       | 41.5         | 1.01           | 55.0         | 1.06           |
| 1450                      | 40.5         | 1.20           | 54.0         | 1.30           |
| 1610                      | 40.3         | 1.29           | 53.8         | 1.40           |
| <b>1800 – 2000</b>        | <b>40.0</b>  | <b>1.40</b>    | <b>53.3</b>  | <b>1.52</b>    |
| <b>2450</b>               | <b>39.2</b>  | <b>1.80</b>    | <b>52.7</b>  | <b>1.95</b>    |
| 3000                      | 38.5         | 2.40           | 52.0         | 2.73           |
| 5800                      | 35.3         | 5.27           | 48.2         | 6.00           |

( $\epsilon_r$  = relative permittivity,  $\sigma$  = conductivity and  $\rho$  = 1000 kg/m<sup>3</sup>)

## 4. SAR Measurement Procedure

### 4.1. SAR System Validation

#### 4.1.1. Validation Dipoles



The dipoles used is based on the IEEE-1528 standard, and is complied with mechanical and electrical specifications in line with the requirements of both IEEE and FCC Supplement C. the table below provides details for the mechanical and electrical Specifications for the dipoles.

| Frequency | L (mm) | h (mm) | d (mm) |
|-----------|--------|--------|--------|
| 900 MHz   | 149    | 83.3   | 3.6    |
| 1900MHz   | 68     | 39.5   | 3.6    |
| 2450MHz   | 51.5   | 30.4   | 3.6    |

#### 4.1.2. Validation Result

| System Performance Check at 835 MHz &1900MHz for Head    |                               |                        |                        |                  |
|----------------------------------------------------------|-------------------------------|------------------------|------------------------|------------------|
| Validation Kit: SN 46/11DIP 0G900-185                    |                               |                        |                        |                  |
| Frequency [MHz]                                          | Description                   | SAR [w/kg] 1g          | SAR [w/kg] 10g         | Tissue Temp.[°C] |
| 835MHz                                                   | Reference result ± 10% window | 10.9<br>9.81 to 11.99  | 6.99<br>6.29 to 7.69   | N/A              |
|                                                          | Sep.12, 2013                  | 10.73                  | 6.46                   | 21.0             |
| Validation Kit: SN 46/11DIP 1G900-187                    |                               |                        |                        |                  |
| Frequency [MHz]                                          | Description                   | SAR [w/kg] 1g          | SAR [w/kg] 10g         | Tissue Temp.[°C] |
| 1900 MHz                                                 | Reference result ± 10% window | 39.7<br>35.73 to 43.67 | 20.5<br>18.45 to 22.55 | N/A              |
|                                                          | Sep.12, 2013                  | 42.65                  | 22.43                  | 21.0             |
| Validation Kit: SN 46/11DIP 2G450-189                    |                               |                        |                        |                  |
| Frequency [MHz]                                          | Description                   | SAR [w/kg] 1g          | SAR [w/kg] 10g         | Tissue Temp.[°C] |
| 2450 MHz                                                 | Reference result ± 10% window | 52.4<br>47.16 to 57.64 | 24.0<br>21.6 to 26.4   | N/A              |
|                                                          | Sep.12, 2013                  | 49.74                  | 24.36                  | 21               |
| Note: All SAR values are normalized to 1W forward power. |                               |                        |                        |                  |

## 4.2. SAR Measurement Procedure

The COMOSAR calculates SAR using the following equation,

$$SAR = \frac{\sigma |E|^2}{\rho}$$

$\sigma$ : represents the simulated tissue conductivity

$\rho$ : represents the tissue density

The EUT is set to transmit at the required power in line with product specification, at each frequency relating to the LOW, MID, and HIGH channel settings.

Pre-scans are made on the device to establish the location for the transmitting antenna, using a large area scan in either air or tissue simulation fluid.

The EUT is placed against the Universal Phantom where the maximum area scan dimensions are larger than the physical size of the resonating antenna. When the scan size is not large enough to cover the peak SAR distribution, it is modified by either extending the area scan size in both the X and Y directions, or the device is shifted within the predefined area.

The area scan is then run to establish the peak SAR location (interpolated resolution set at 1mm<sup>2</sup>) which is then used to orient the center of the zoom scan. The zoom scan is then executed and the 1g and 10g averages are derived from the zoom scan volume (interpolated resolution set at 1mm<sup>3</sup>).

When multiple peak SAR location were found during the same configuration or test mode, Zoom scan shall performed on each peak SAR location, only the peak point with maximum SAR value will be reported for the configuration or test mode.

## 5. SAR Exposure Limits

SAR assessments have been made in line with the requirements of IEEE-1528, FCC Supplement C, and comply with ANSI/IEEE C95.1-1992 “Uncontrolled Environments” limits. These limits apply to a location which is deemed as “Uncontrolled Environment” which can be described as a situation where the general public may be exposed to an RF source with no prior knowledge or control over their exposure.

### Limits for General Population/Uncontrolled Exposure (W/kg)

| Type Exposure                                       | Uncontrolled Environment Limit |
|-----------------------------------------------------|--------------------------------|
| Spatial Peak SAR (1g cube tissue for brain or body) | 1.60 W/kg                      |

## 6. Test Equipment List

| Equipment description | Manufacturer/ Model | Identification No.    | Current calibration date    | Next calibration date       |
|-----------------------|---------------------|-----------------------|-----------------------------|-----------------------------|
| SAR Probe             | SATIMO              | SN 04/13 EP165        | 01/31/2013                  | 01/30/2014                  |
| Phantom               | SATIMO              | SN_4511_SAM90         | Validated. No cal required. | Validated. No cal required. |
| Liquid                | SATIMO              | -                     | Validated. No cal required. | Validated. No cal required. |
| Comm Tester           | R&S - CMU200        | 069Y7-158-13-712      | 02/28/2013                  | 02/27/2014                  |
| Comm Tester           | Agilent-8960        | GB46310822            | 10/22/2012                  | 10/21/2013                  |
| Multimeter            | Keithley 2000       | 1188656               | 02/28/2013                  | 02/27/2014                  |
| Dipole                | SATIMO SID900       | SN46/11 DIP 0G900-185 | 12/09/2011                  | 12/08/2013                  |
| Dipole                | SATIMO SID1900      | SN46/11 DIP 1G900-187 | 12/09/2011                  | 12/08/2013                  |
| Dipole                | SATIMO SID2450      | SN46/11 DIP 2G450-189 | 12/09/2011                  | 12/08/2013                  |
| Amplifier             | Aethercomm          | SN 046                | 12/08/2012                  | 12/07/2013                  |
| Signal Generator      | Agilent-E4421B      | MY43351603            | 05/13/2013                  | 05/12/2014                  |
| Power Probe           | NRP-Z23             | US38261498            | 02/28/2013                  | 02/27/2014                  |
| SPECTRUM ANALYZER     | Agilent/E4440A      | MY44303916            | 10/22/2012                  | 10/21/2013                  |
| Power Attenuator      | BED                 | DLA-5W                | 07/30/2013                  | 07/29/2014                  |
| Network Analyzer      | Rhode & Schwarz ZVA | SN100132              | 02/28/2013                  | 02/27/2014                  |

Note: Per KDB 50824 Dipole SAR Validation Verification, AGC Lab has adopted 3 years calibration intervals. On annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole;
2. System validation with specific dipole is within 10% of calibrated value;
3. Return-loss is within 20% of calibrated measurement;
4. Impedance is within 5Ω of calibrated measurement.

## 7. Measurement Uncertainty

| SATIMO Uncertainty                                                             |         |             |                |            |                 |                 |                           |                           |                  |
|--------------------------------------------------------------------------------|---------|-------------|----------------|------------|-----------------|-----------------|---------------------------|---------------------------|------------------|
| Measurement uncertainty for 30 MHz to 3 GHz averaged over 1 gram / 10 gram.    |         |             |                |            |                 |                 |                           |                           |                  |
| Error Description                                                              | Sec     | Tol<br>(±%) | Prob.<br>Dist. | Div.       | (Ci)<br>1g      | (Ci)<br>10g     | Std.<br>Unc.<br>(1g) (±%) | Std.<br>Unc.<br>(10g)(±%) | (Vi)<br>Ve<br>ff |
| Measurement System                                                             |         |             |                |            |                 |                 |                           |                           |                  |
| Probe Calibration                                                              | E.2.1   | 6           | N              | 1          | 1               | 1               | 6                         | 6                         | ∞                |
| Axial Isotropy                                                                 | E.2.2   | 3           | R              | $\sqrt{3}$ | $(1-C_p)^{1/2}$ | $(1-C_p)^{1/2}$ | 1.22474                   | 1.22474                   | ∞                |
| Hemispherical Isotropy                                                         | E.2.2   | 5           | R              | $\sqrt{3}$ | $\sqrt{C_p}$    | $\sqrt{C_p}$    | 2.04124                   | 2.04124                   | ∞                |
| Boundary Effects                                                               | E.2.3   | 1           | R              | $\sqrt{3}$ | 1               | 1               | 0.57735                   | 0.57735                   | ∞                |
| Linearity                                                                      | E.2.4   | 5           | R              | $\sqrt{3}$ | 1               | 1               | 2.88675                   | 2.88675                   | ∞                |
| System Detection Limits                                                        | E.2.5   | 1           | R              | $\sqrt{3}$ | 1               | 1               | 0.57735                   | 0.57735                   | ∞                |
| Readout Electronics                                                            | E.2.6   | 0.5         | N              | 1          | 1               | 1               | 0.5                       | 0.5                       | ∞                |
| Response Time                                                                  | E.2.7   | 0.2         | R              | $\sqrt{3}$ | 1               | 1               | 0.11547                   | 0.11547                   | ∞                |
| Integration Time                                                               | E.2.8   | 2           | R              | $\sqrt{3}$ | 1               | 1               | 1.1547                    | 1.1547                    | ∞                |
| RF Ambient Noise                                                               | E.6.1   | 3           | R              | $\sqrt{3}$ | 1               | 1               | 1.73205                   | 1.73205                   | ∞                |
| Probe Positioner Mechanical Tolerance                                          | E.6.2   | 2           | R              | $\sqrt{3}$ | 1               | 1               | 1.1547                    | 1.1547                    | ∞                |
| Probe Positioning with Respect to Phantom Shell                                | E.6..3  | 1           | R              | $\sqrt{3}$ | 1               | 1               | 0.57735                   | 0.57735                   | ∞                |
| Extrapolation,interpolation and Integration Algorithms for Max. SAR Evaluation | E.5.2   | 1.5         | R              | $\sqrt{3}$ | 1               | 1               | 0.86603                   | 0.86603                   | ∞                |
| Dipole                                                                         |         |             |                |            |                 |                 |                           |                           |                  |
| Device Positioning                                                             | 8,E.4.2 | 1           | N              | $\sqrt{3}$ | 1               | 1               | 0.57735                   | 0.57735                   | N-1              |
| Power Drift                                                                    | 8.6.6.2 | 2           | R              | $\sqrt{3}$ | 1               | 1               | 1.1547                    | 1.1547                    | ∞                |
| Phantom and Tissue Parameters                                                  |         |             |                |            |                 |                 |                           |                           |                  |
| Phantom Uncertainty                                                            | E.3.1   | 4           | R              | $\sqrt{3}$ | 1               | 1               | 2.3094                    | 2.3094                    | ∞                |
| Liquid Conductivity (target)                                                   | E.3.2   | 5           | R              | $\sqrt{3}$ | 0.64            | 0.43            | 1.84752                   | 1.2413                    | ∞                |
| Liquid Conductivity (meas.)                                                    | E.3.3   | 2.5         | N              | 1          | 0.64            | 0.43            | 1.6                       | 1.075                     | ∞                |
| Liquid Permittivity (target)                                                   | E.3.2   | 3           | R              | $\sqrt{3}$ | 0.6             | 0.49            | 1.03923                   | 0.8487                    | ∞                |
| Liquid Permittivity (meas.)                                                    | E.3.3   | 2.5         | N              | 1          | 0.6             | 0.49            | 1.5                       | 1.225                     | M                |
| Combined Standard Uncertainty                                                  |         |             | RSS            |            |                 |                 | 8.09272                   | 7.9296                    |                  |
| Expanded Uncertainty (95%CONFIDENCE INTERVAL)                                  |         |             | k              |            |                 |                 | 16.18544                  | 15.8592                   |                  |

## 8. Conducted Power Measurement

### GSM BAND

| Mode                 | Frequency(MHz) | Avg. Burst Power(dBm) | Duty cycle Factor(dBm) | Frame Power(dBm) |
|----------------------|----------------|-----------------------|------------------------|------------------|
| Maximum Power <1>    |                |                       |                        |                  |
| GSM 835              | 824.2          | <b>31.56</b>          | -9                     | 22.56            |
|                      | 836.6          | 31.49                 | -9                     | 22.49            |
|                      | 848.8          | 31.45                 | -9                     | 22.45            |
| GPRS 835<br>(1 Slot) | 824.2          | 31.47                 | -9                     | 22.47            |
|                      | 836.6          | 31.42                 | -9                     | 22.42            |
|                      | 848.8          | 31.31                 | -9                     | 22.31            |
| GPRS 835<br>(2 Slot) | 824.2          | 28.52                 | -6                     | 22.52            |
|                      | 836.6          | 28.46                 | -6                     | 22.46            |
|                      | 848.8          | 28.41                 | -6                     | 22.41            |
| GPRS 835<br>(3 Slot) | 824.2          | 26.37                 | -4.26                  | 22.11            |
|                      | 836.6          | 26.44                 | -4.26                  | 22.18            |
|                      | 848.8          | 26.63                 | -4.26                  | 22.37            |
| GPRS 835<br>(4 Slot) | 824.2          | 25.68                 | -3                     | 22.68            |
|                      | 836.6          | 25.56                 | -3                     | 22.56            |
|                      | 848.8          | 25.51                 | -3                     | 22.51            |
| PCS1900              | 1850.2         | <b>28.71</b>          | -9                     | 19.71            |
|                      | 1880           | 28.66                 | -9                     | 19.66            |
|                      | 1909.8         | 28.52                 | -9                     | 19.52            |
| GPRS1900<br>(1 Slot) | 1850.2         | 28.62                 | -9                     | 19.62            |
|                      | 1880           | 28.52                 | -9                     | 19.52            |
|                      | 1909.8         | 28.48                 | -9                     | 19.48            |
| GPRS1900<br>(2 Slot) | 1850.2         | 25.73                 | -6                     | 19.73            |
|                      | 1880           | 25.65                 | -6                     | 19.65            |
|                      | 1909.8         | 25.61                 | -6                     | 19.61            |
| GPRS1900<br>(3 Slot) | 1850.2         | 24.72                 | -4.26                  | 20.46            |
|                      | 1880           | 24.63                 | -4.26                  | 20.37            |
|                      | 1909.8         | 24.55                 | -4.26                  | 20.29            |
| GPRS1900<br>(4 Slot) | 1850.2         | 22.64                 | -3                     | 19.64            |
|                      | 1880           | 22.72                 | -3                     | 19.72            |
|                      | 1909.8         | 22.63                 | -3                     | 19.63            |
| Maximum Power <2>    |                |                       |                        |                  |
| GSM 835              | 824.2          | 31.49                 | -9                     | 22.49            |
| PCS1900              | 1850.2         | 28.66                 | -9                     | 19.66            |

Note 1:

The Frame Power (Source-based time-averaged Power) is scaled the maximum burst average power based on time slots. The calculated methods are show as following:

Frame Power = Max burst power (1 Up Slot) – 9 dB

Frame Power = Max burst power (2 Up Slot) – 6 dB

Frame Power = Max burst power (3 Up Slot) – 4.26 dB

Frame Power = Max burst power (4 Up Slot) – 3 dB

**UMTS BAND II**

| <b>Mode</b>        | <b>Frequency<br/>(MHz)</b> | <b>Avg.Burst Power</b> |
|--------------------|----------------------------|------------------------|
| WCDMA 1900<br>RMC  | 1852.4                     | 22.53                  |
|                    | 1880                       | <b>22.62</b>           |
|                    | 1907.6                     | 22.58                  |
| WCDMA 1900<br>AMR  | 1852.4                     | 22.19                  |
|                    | 1880                       | 22.27                  |
|                    | 1907.6                     | 22.07                  |
| HSDPA<br>Subtest 1 | 1852.4                     | 22.17                  |
|                    | 1880                       | 22.07                  |
|                    | 1907.6                     | 22.31                  |
| HSDPA<br>Subtest 2 | 1852.4                     | 22.36                  |
|                    | 1880                       | 22.32                  |
|                    | 1907.6                     | 22.35                  |
| HSDPA<br>Subtest 3 | 1852.4                     | 22.31                  |
|                    | 1880                       | 22.35                  |
|                    | 1907.6                     | 22.47                  |
| HSDPA<br>Subtest 4 | 1852.4                     | 22.36                  |
|                    | 1880                       | 22.28                  |
|                    | 1907.6                     | 22.3                   |
| HSUPA<br>Subtest 1 | 1852.4                     | 22.29                  |
|                    | 1880                       | 22.21                  |
|                    | 1907.6                     | 22.18                  |
| HSUPA<br>Subtest 2 | 1852.4                     | 22.22                  |
|                    | 1880                       | 22.12                  |
|                    | 1907.6                     | 22.27                  |
| HSUPA<br>Subtest 3 | 1852.4                     | 22.25                  |
|                    | 1880                       | 22.33                  |
|                    | 1907.6                     | 22.31                  |
| HSUPA<br>Subtest 4 | 1852.4                     | 22.38                  |
|                    | 1880                       | 22.21                  |
|                    | 1907.6                     | 22.19                  |
| HSUPA<br>Subtest 5 | 1852.4                     | 22.63                  |
|                    | 1880                       | 22.49                  |
|                    | 1907.6                     | 22.32                  |

**UMTS BAND V**

| <b>Mode</b>        | <b>Frequency<br/>(MHz)</b> | <b>Avg.Burst Power</b> |
|--------------------|----------------------------|------------------------|
| WCDMA 850<br>RMC   | 826.4                      | <b>23.06</b>           |
|                    | 835.0                      | 22.99                  |
|                    | 846.6                      | 23.04                  |
| WCDMA 850<br>AMR   | 826.4                      | 22.99                  |
|                    | 835.0                      | 21.95                  |
|                    | 846.6                      | 21.91                  |
| HSDPA<br>Subtest 1 | 826.4                      | 21.95                  |
|                    | 835.0                      | 22.05                  |
|                    | 846.6                      | 22.32                  |
| HSDPA<br>Subtest 2 | 826.4                      | 22.26                  |
|                    | 835.0                      | 22.30                  |
|                    | 846.6                      | 22.26                  |
| HSDPA<br>Subtest 3 | 826.4                      | 22.22                  |
|                    | 835.0                      | 22.16                  |
|                    | 846.6                      | 22.37                  |
| HSDPA<br>Subtest 4 | 826.4                      | 22.34                  |
|                    | 835.0                      | 22.12                  |
|                    | 846.6                      | 22.21                  |
| HSUPA<br>Subtest 1 | 826.4                      | 22.14                  |
|                    | 835.0                      | 22.03                  |
|                    | 846.6                      | 22.06                  |
| HSUPA<br>Subtest 2 | 826.4                      | 22.04                  |
|                    | 835.0                      | 21.99                  |
|                    | 846.6                      | 22.04                  |
| HSUPA<br>Subtest 3 | 826.4                      | 21.94                  |
|                    | 835.0                      | 21.92                  |
|                    | 846.6                      | 21.9                   |
| HSUPA<br>Subtest 4 | 826.4                      | 21.95                  |
|                    | 835.0                      | 21.98                  |
|                    | 846.6                      | 22.00                  |
| HSUPA<br>Subtest 5 | 826.4                      | 22.12                  |
|                    | 835.0                      | 22.21                  |
|                    | 846.6                      | 22.27                  |

**WIFI**

| Mode        | Data Rate (Mbps) | Channel | Frequency(MHz) | Avg. Burst Power(dBm) |
|-------------|------------------|---------|----------------|-----------------------|
| 802.11b     | 1                | 01      | 2412           | 9.85                  |
|             |                  | 06      | 2437           | 9.95                  |
|             |                  | 11      | 2462           | <b>10.03</b>          |
| 802.11g     | 6                | 01      | 2412           | 8.88                  |
|             |                  | 06      | 2437           | 8.96                  |
|             |                  | 11      | 2462           | 9.02                  |
| 802.11n(20) | 6.5              | 01      | 2412           | 8.25                  |
|             |                  | 06      | 2437           | 8.35                  |
|             |                  | 11      | 2462           | 8.43                  |
| 802.11n(40) | 13.5             | 03      | 2422           | 5.57                  |
|             |                  | 06      | 2437           | 5.53                  |
|             |                  | 09      | 2452           | 5.66                  |

According to 3GPP 25.101 sub-clause 6.2.2 , the maximum output power is allowed to be reduced by following the table.

Table 6.1aA: UE maximum output power with HS-DPCCH and E-DCH

| UE Transmit Channel Configuration                                                                                                                                                              | CM(db)               | MPR(db)       |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|---------------|
| For all combinations of ,DPDCH,DPCCH<br>HS-DPDCH,E-DPDCH and E-DPCCH                                                                                                                           | $0 \leq CM \leq 3.5$ | $MAX(CM-1,0)$ |
| Note: CM=1 for $\beta_d/\beta_d=12/15$ , $\beta_{hs}/\beta_c=24/15$ .For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference. |                      |               |

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensation for the power back-off by increasing the gain of TX\_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.

## 9. Test Results

### 9.1. SAR Test Results Summary

#### 9.1.1. Test position and configuration

Head SAR was performed with the device configured in the positions according to IEEE1528, and Body SAR was performed with the device 5mm from the phantom; the overall device length and width(16.7cm×8.8cm) are >9cm×5cm, Hotspot mode with a test separation distance of 10mm.

#### 9.1.2. Operation Mode

- According to KDB 447498 D01 v05r01 ,for each exposure position, if the highest 1-g SAR is  $\leq 0.8$  W/kg, testing for low and high channel is optional.
- Per KDB 865664 D01 v01r01,for each frequency band, if the measured SAR is  $\geq 0.8$ W/Kg, testing for repeated SAR measurement is required , that the highest measured SAR is only to be tested .
- Body-worn exposure conditions are intended to voice call operations, therefore GSM voice call mode is selected to be test.
- According to KDB 648474 D04 v01r01,when the reported SAR for a body-worn accessory measured without a headset connected to the handset is  $\leq 1.2$ W/Kg, SAR testing with a headset connected is not required.
- According to 941225 D06, when the overall device length and width are >9cm×5cm, Hotspot mode with a test separation distance of 10mm. For device with form factors smaller than 9cm×5cm, Hotspot mode with a test separation distance of 5mm. Body SAR was also performed with the headset attached and without.
- According to 248227 D01, SAR is not required for 802.11g channels when the maximum average output power is less than 1/4dB higher than measured on the corresponding 802.11b channels.
- Maximum Scaling SAR in order to calculate the Maximum SAR values to test under the standard Peak Power, Calculation method is as follows:  
Maximum Scaling SAR =tested SAR (Max.)  $\times$  (GSM standard Peak Power (mw)/ tested Max. Peak Power (mw))

### 9.1.3. SAR Test Results Summary

| SAR MEASUREMENT                                                                                          |            |        |                  |           |       |                           |                 |              |
|----------------------------------------------------------------------------------------------------------|------------|--------|------------------|-----------|-------|---------------------------|-----------------|--------------|
| Ambient Temperature (°C) : 21 ± 2                                                                        |            |        |                  |           |       | Relative Humidity (%): 55 |                 |              |
| Liquid Temperature (°C) : 21 ± 2                                                                         |            |        |                  |           |       | Depth of Liquid (cm):>15  |                 |              |
| Product: Smart Phone                                                                                     |            |        |                  |           |       |                           |                 |              |
| Test Mode: GSM835 with GMSK modulation                                                                   |            |        |                  |           |       |                           |                 |              |
| Configuration                                                                                            |            |        | Antenna Position | Frequency |       | Power Drift (<±5%)        | SAR (1g) (W/kg) | Limit (W/kg) |
| SIM                                                                                                      | Position   | Status |                  | channel   | MHz   |                           |                 |              |
| <1>                                                                                                      | Left Head  | Cheek  | Fixed            | 128       | 824.2 | --                        | --              | --           |
|                                                                                                          |            |        |                  | 190       | 836.6 | -0.14                     | 0.178           | 1.6          |
|                                                                                                          |            |        |                  | 251       | 848.8 | --                        | --              | --           |
|                                                                                                          |            | Tilted | Fixed            | 128       | 824.2 | --                        | --              | --           |
|                                                                                                          |            |        |                  | 190       | 836.6 | -0.63                     | 0.099           | 1.6          |
|                                                                                                          |            |        |                  | 251       | 848.8 | --                        | --              | --           |
|                                                                                                          | Right Head | Cheek  | Fixed            | 128       | 824.2 | --                        | --              | --           |
|                                                                                                          |            |        |                  | 190       | 836.6 | -0.77                     | <b>0.212</b>    | 1.6          |
|                                                                                                          |            |        |                  | 251       | 848.8 | --                        | --              | --           |
|                                                                                                          |            | Tilted | Fixed            | 128       | 824.2 | --                        | --              | --           |
|                                                                                                          |            |        |                  | 190       | 836.6 | -0.46                     | 0.109           | 1.6          |
|                                                                                                          |            |        |                  | 251       | 848.8 | --                        | --              | --           |
| <2>                                                                                                      | Right      | Cheek  | Fixed            | 190       | 836.6 | 0.28                      | 0.202           | 1.6          |
| Note: when the 1-g SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. refer to KDB 941225. |            |        |                  |           |       |                           |                 |              |

| SAR MEASUREMENT                                                                                          |            |        |                  |           |       |                           |                 |              |
|----------------------------------------------------------------------------------------------------------|------------|--------|------------------|-----------|-------|---------------------------|-----------------|--------------|
| Ambient Temperature (°C) : 21 ± 2                                                                        |            |        |                  |           |       | Relative Humidity (%): 55 |                 |              |
| Liquid Temperature (°C) : 21 ± 2                                                                         |            |        |                  |           |       | Depth of Liquid (cm):>15  |                 |              |
| Product: Smart Phone                                                                                     |            |        |                  |           |       |                           |                 |              |
| Test Mode: GSM835 with GMSK modulation                                                                   |            |        |                  |           |       |                           |                 |              |
| Configuration                                                                                            |            |        | Antenna Position | Frequency |       | Power Drift (<±5%)        | SAR (1g) (W/kg) | Limit (W/kg) |
| SIM                                                                                                      | Position   | Status |                  | channel   | MHz   |                           |                 |              |
| <1>                                                                                                      | Body back  | MS     | Fixed            | 128       | 824.2 | --                        | --              | --           |
|                                                                                                          |            |        |                  | 190       | 836.6 | -0.17                     | <b>0.225</b>    | 1.6          |
|                                                                                                          |            |        |                  | 251       | 848.8 | --                        | --              | --           |
|                                                                                                          | Body Front | MS     | Fixed            | 128       | 824.2 | --                        | --              | --           |
|                                                                                                          |            |        |                  | 190       | 836.6 | -0.63                     | 0.133           | 1.6          |
|                                                                                                          |            |        |                  | 251       | 848.8 | --                        | --              | --           |
| Note: when the 1-g SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. refer to KDB 941225. |            |        |                  |           |       |                           |                 |              |

| SAR MEASUREMENT                         |            |        |                  |           |        |                           |                 |              |
|-----------------------------------------|------------|--------|------------------|-----------|--------|---------------------------|-----------------|--------------|
| Ambient Temperature (°C) : 21 ± 2       |            |        |                  |           |        | Relative Humidity (%): 55 |                 |              |
| Liquid Temperature (°C) : 21 ± 2        |            |        |                  |           |        | Depth of Liquid (cm):>15  |                 |              |
| Product: Smart Phone                    |            |        |                  |           |        |                           |                 |              |
| Test Mode: PCS1900 with GMSK modulation |            |        |                  |           |        |                           |                 |              |
| Configuration                           |            |        | Antenna Position | Frequency |        | Power Drift (<±5%)        | SAR (1g) (W/kg) | Limit (W/kg) |
| SIM                                     | Position   | Status |                  | channel   | MHz    |                           |                 |              |
| <1>                                     | Left Head  | Cheek  | Fixed            | 512       | 1850.2 | --                        | --              | --           |
|                                         |            |        |                  | 661       | 1880.0 | -0.15                     | 0.264           | 1.6          |
|                                         |            |        |                  | 810       | 1909.8 | --                        | --              | --           |
|                                         |            | Tilted | Fixed            | 512       | 1850.2 | --                        | --              | --           |
|                                         |            |        |                  | 661       | 1880.0 | -0.42                     | 0.205           | 1.6          |
|                                         |            |        |                  | 810       | 1909.8 | --                        | --              | --           |
|                                         | Right Head | Cheek  | Fixed            | 512       | 1850.2 | --                        | --              | --           |
|                                         |            |        |                  | 661       | 1880.0 | -0.33                     | <b>0.406</b>    | 1.6          |
|                                         |            |        |                  | 810       | 1909.8 | --                        | --              | --           |
|                                         |            | Tilted | Fixed            | 512       | 1850.2 | --                        | --              | --           |
|                                         |            |        |                  | 661       | 1880.0 | 0.15                      | 0.295           | 1.6          |
|                                         |            |        |                  | 810       | 1909.8 | --                        | --              | --           |
| <2>                                     | Right      | Cheek  | Fixed            | 661       | 1880.0 | 0.27                      | 0.406           | 1.6          |

Note: when the 1-g SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. refer to KDB 941225.

## SAR MEASUREMENT

| Ambient Temperature (°C) : 21 ± 2        |            |        |                  |           |        | Relative Humidity (%): 55 |                 |              |
|------------------------------------------|------------|--------|------------------|-----------|--------|---------------------------|-----------------|--------------|
| Liquid Temperature (°C) : 21 ± 2         |            |        |                  |           |        | Depth of Liquid (cm):>15  |                 |              |
| Product: Smart Phone                     |            |        |                  |           |        |                           |                 |              |
| Test Mode: PCS 1900 with GMSK modulation |            |        |                  |           |        |                           |                 |              |
| Configuration                            |            |        | Antenna Position | Frequency |        | Power Drift (<±5%)        | SAR (1g) (W/kg) | Limit (W/kg) |
| SIM                                      | Position   | Status |                  | channel   | MHz    |                           |                 |              |
| <1>                                      | Body Back  | MS     | Fixed            | 512       | 1850.2 | --                        | --              | --           |
|                                          |            |        |                  | 661       | 1880.0 | 0.74                      | <b>0.266</b>    | 1.6          |
|                                          |            |        |                  | 810       | 1909.8 | --                        | --              | --           |
|                                          | Body front | MS     | Fixed            | 512       | 1850.2 | --                        | --              | --           |
|                                          |            |        |                  | 661       | 1880.0 | -0.15                     | 0.214           | 1.6          |
|                                          |            |        |                  | 810       | 1909.8 | --                        | --              | --           |

Note: when the 1-g SAR is  $\leq 0.8$  W/kg, testing for low and high channel is optional. refer to KDB 941225.

| SAR MEASUREMENT                                                                                          |            |        |                  |           |        |                           |                 |              |
|----------------------------------------------------------------------------------------------------------|------------|--------|------------------|-----------|--------|---------------------------|-----------------|--------------|
| Ambient Temperature (°C) : 21 ± 2                                                                        |            |        |                  |           |        | Relative Humidity (%): 55 |                 |              |
| Liquid Temperature (°C) : 21 ± 2                                                                         |            |        |                  |           |        | Depth of Liquid (cm):>15  |                 |              |
| Product: Smart Phone                                                                                     |            |        |                  |           |        |                           |                 |              |
| Test Mode: WCDMA Band II with QPSK modulation                                                            |            |        |                  |           |        |                           |                 |              |
| Configuration                                                                                            |            |        | Antenna Position | Frequency |        | Power Drift (<±5%)        | SAR (1g) (W/kg) | Limit (W/kg) |
| SIM                                                                                                      | Position   | Status |                  | channel   | MHz    |                           |                 |              |
| <1>                                                                                                      | Left Head  | Cheek  | Fixed            | 9262      | 1852.4 | --                        | --              | --           |
|                                                                                                          |            |        |                  | 9400      | 1880   | -0.14                     | 0.654           | 1.6          |
|                                                                                                          |            |        |                  | 9538      | 1907.6 | --                        | --              | --           |
|                                                                                                          |            | Tilted | Fixed            | 9262      | 1852.4 | --                        | --              | --           |
|                                                                                                          |            |        |                  | 9400      | 1880   | -0.06                     | 0.216           | 1.6          |
|                                                                                                          |            |        |                  | 9538      | 1907.6 | --                        | --              | --           |
|                                                                                                          | Right Head | Cheek  | Fixed            | 9262      | 1852.4 | 1.25                      | 0.864           | 1.6          |
|                                                                                                          |            |        |                  | 9400      | 1880   | 0.63                      | <b>0.933</b>    | 1.6          |
|                                                                                                          |            |        |                  | 9538      | 1907.6 | 0.77                      | 0.882           | 1.6          |
|                                                                                                          |            | Tilted | Fixed            | 9262      | 1852.4 | --                        | --              | --           |
|                                                                                                          |            |        |                  | 9400      | 1880   | -0.45                     | 0.203           | 1.6          |
|                                                                                                          |            |        |                  | 9538      | 1907.6 | --                        | --              | --           |
| Note: when the 1-g SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. refer to KDB 941225. |            |        |                  |           |        |                           |                 |              |

|                                                                                                          |          |                       |                  |           |        |                           |                 |              |
|----------------------------------------------------------------------------------------------------------|----------|-----------------------|------------------|-----------|--------|---------------------------|-----------------|--------------|
| SAR MEASUREMENT                                                                                          |          |                       |                  |           |        |                           |                 |              |
| Ambient Temperature (°C) : 21 ± 2                                                                        |          |                       |                  |           |        | Relative Humidity (%): 55 |                 |              |
| Liquid Temperature (°C) : 21 ± 2                                                                         |          |                       |                  |           |        | Depth of Liquid (cm):>15  |                 |              |
| Product: Smart Phone                                                                                     |          |                       |                  |           |        |                           |                 |              |
| Test Mode: WCDMA Band II with QPSK modulation                                                            |          |                       |                  |           |        |                           |                 |              |
| Configuration                                                                                            |          |                       | Antenna Position | Frequency |        | Power Drift (<±5%)        | SAR (1g) (W/kg) | Limit (W/kg) |
| SIM                                                                                                      | Position | Status                |                  | channel   | MHz    |                           |                 |              |
| <1>                                                                                                      | Body     | RMC (towards grounds) | Fixed            | 9262      | 1852.4 | --                        | --              | --           |
|                                                                                                          |          |                       |                  | 9400      | 1880   | -0.74                     | <b>0.614</b>    | 1.6          |
|                                                                                                          |          |                       |                  | 9538      | 1907.6 | --                        | --              | --           |
|                                                                                                          |          | RMC (towards phantom) | Fixed            | 9262      | 1852.4 | --                        | --              | --           |
|                                                                                                          |          |                       |                  | 9400      | 1880   | -0.41                     | 0.479           | 1.6          |
|                                                                                                          |          |                       |                  | 9538      | 1907.6 | --                        | --              | --           |
| Note: when the 1-g SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. refer to KDB 941225. |          |                       |                  |           |        |                           |                 |              |

| SAR MEASUREMENT                              |            |        |                  |           |       |                           |                 |              |
|----------------------------------------------|------------|--------|------------------|-----------|-------|---------------------------|-----------------|--------------|
| Ambient Temperature (°C) : 21 ± 2            |            |        |                  |           |       | Relative Humidity (%): 55 |                 |              |
| Liquid Temperature (°C) : 21 ± 2             |            |        |                  |           |       | Depth of Liquid (cm):>15  |                 |              |
| Product: Smart Phone                         |            |        |                  |           |       |                           |                 |              |
| Test Mode: WCDMA Band V with QPSK modulation |            |        |                  |           |       |                           |                 |              |
| Configuration                                |            |        | Antenna Position | Frequency |       | Power Drift (<±5%)        | SAR (1g) (W/kg) | Limit (W/kg) |
| SIM                                          | Position   | Status |                  | channel   | MHz   |                           |                 |              |
| <1>                                          | Left Head  | Cheek  | Fixed            | 4132      | 826.4 | --                        | --              | --           |
|                                              |            |        |                  | 4182      | 835.0 | -0.01                     | 0.344           | 1.6          |
|                                              |            |        |                  | 4233      | 846.6 | --                        | --              | --           |
|                                              |            | Tilted | Fixed            | 4132      | 826.4 | --                        | --              | --           |
|                                              |            |        |                  | 4182      | 835.0 | -0.63                     | 0.322           | 1.6          |
|                                              |            |        |                  | 4233      | 846.6 | --                        | --              | --           |
|                                              | Right Head | Cheek  | Fixed            | 4132      | 826.4 | --                        | --              | --           |
|                                              |            |        |                  | 4182      | 835.0 | -0.45                     | <b>0.428</b>    | 1.6          |
|                                              |            |        |                  | 4233      | 846.6 | --                        | --              | --           |
|                                              |            | Tilted | Fixed            | 4132      | 826.4 | --                        | --              | --           |
|                                              |            |        |                  | 4182      | 835.0 | 0.28                      | 0.365           | 1.6          |
|                                              |            |        |                  | 4233      | 846.6 | --                        | --              | --           |

Note: when the 1-g SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. refer to KDB 941225.

|                                                                                                          |          |                       |                  |           |       |                           |                 |              |
|----------------------------------------------------------------------------------------------------------|----------|-----------------------|------------------|-----------|-------|---------------------------|-----------------|--------------|
| SAR MEASUREMENT                                                                                          |          |                       |                  |           |       |                           |                 |              |
| Ambient Temperature (°C) : 21 ± 2                                                                        |          |                       |                  |           |       | Relative Humidity (%): 55 |                 |              |
| Liquid Temperature (°C) : 21 ± 2                                                                         |          |                       |                  |           |       | Depth of Liquid (cm):>15  |                 |              |
| Product: Smart Phone                                                                                     |          |                       |                  |           |       |                           |                 |              |
| Test Mode: WCDMA Band V with QPSK modulation                                                             |          |                       |                  |           |       |                           |                 |              |
| Configuration                                                                                            |          |                       | Antenna Position | Frequency |       | Power Drift (<±5%)        | SAR (1g) (W/kg) | Limit (W/kg) |
| SIM                                                                                                      | Position | Status                |                  | channel   | MHz   |                           |                 |              |
| <1>                                                                                                      | Body     | RMC (towards grounds) | Fixed            | 4132      | 826.4 | --                        | --              | --           |
|                                                                                                          |          |                       |                  | 4182      | 835.0 | -0.14                     | <b>0.697</b>    | 1.6          |
|                                                                                                          |          |                       |                  | 4233      | 846.6 | --                        | --              | --           |
|                                                                                                          |          | RMC (towards phantom) | Fixed            | 4132      | 826.4 | --                        | --              | --           |
|                                                                                                          |          |                       |                  | 4182      | 835.0 | -0.49                     | 0.440           | 1.6          |
|                                                                                                          |          |                       |                  | 4233      | 846.6 | --                        | --              | --           |
| Note: when the 1-g SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. refer to KDB 941225. |          |                       |                  |           |       |                           |                 |              |

| SAR MEASUREMENT                   |            |        |                  |           |      |                           |                 |              |
|-----------------------------------|------------|--------|------------------|-----------|------|---------------------------|-----------------|--------------|
| Ambient Temperature (°C) : 21 ± 2 |            |        |                  |           |      | Relative Humidity (%): 55 |                 |              |
| Liquid Temperature (°C) : 21 ± 2  |            |        |                  |           |      | Depth of Liquid (cm):>15  |                 |              |
| Product: Smart Phone              |            |        |                  |           |      |                           |                 |              |
| Test Mode: 802.11b                |            |        |                  |           |      |                           |                 |              |
| Configuration                     |            |        | Antenna Position | Frequency |      | Power Drift (<±5%)        | SAR (1g) (W/kg) | Limit (W/kg) |
| Test Mode                         | Position   | Status |                  | channel   | MHz  |                           |                 |              |
| 802.11b                           | Left Head  | Cheek  | Fixed            | 1         | 2412 | --                        | --              | --           |
|                                   |            |        |                  | 6         | 2437 | -0.05                     | <b>0.153</b>    | 1.6          |
|                                   |            |        |                  | 11        | 2462 | --                        | --              | --           |
|                                   |            | Tilted | Fixed            | 1         | 2412 | --                        | --              | --           |
|                                   |            |        |                  | 6         | 2437 | -0.45                     | 0.073           | 1.6          |
|                                   |            |        |                  | 11        | 2462 | --                        | --              | --           |
|                                   | Right Head | Cheek  | Fixed            | 1         | 2412 | --                        | --              | --           |
|                                   |            |        |                  | 6         | 2437 | -0.63                     | 0.147           | 1.6          |
|                                   |            |        |                  | 11        | 2462 | --                        | --              | --           |
|                                   |            | Tilted | Fixed            | 1         | 2412 | --                        | --              | --           |
|                                   |            |        |                  | 6         | 2437 | 0.27                      | 0.124           | 1.6          |
|                                   |            |        |                  | 11        | 2462 | --                        | --              | --           |

Note1: when the 1-g SAR is ≤ 0.8 W/kg, testing for low and high channel is optional.  
Note2: IEEE802.11b support DBPSK, DQPSK, CCK modulation mode, IEEE802.11g/n support OFDM, 16-QAM, 64-QAM modulation mode.

Note2: IEEE802.11b support DBPSK, DQPSK, CCK modulation mode, IEEE802.11g/n support OFDM, 16-QAM, 64-QAM modulation mode.

| SAR MEASUREMENT                   |            |        |                  |           |      |                           |                 |              |
|-----------------------------------|------------|--------|------------------|-----------|------|---------------------------|-----------------|--------------|
| Ambient Temperature (°C) : 21 ± 2 |            |        |                  |           |      | Relative Humidity (%): 55 |                 |              |
| Liquid Temperature (°C) : 21 ± 2  |            |        |                  |           |      | Depth of Liquid (cm):>15  |                 |              |
| Product: Smart Phone              |            |        |                  |           |      |                           |                 |              |
| Test Mode: Hotspot                |            |        |                  |           |      |                           |                 |              |
| Configuration                     |            |        | Antenna Position | Frequency |      | Power Drift (<±5%)        | SAR (1g) (W/kg) | Limit (W/kg) |
| Test Mode                         | Position   | Status |                  | channel   | MHz  |                           |                 |              |
| Hotspot                           | Left Head  | Cheek  | Fixed            | 1         | 2412 | --                        | --              | --           |
|                                   |            |        |                  | 6         | 2437 | -0.05                     | 0.127           | 1.6          |
|                                   |            |        |                  | 11        | 2462 | --                        | --              | --           |
|                                   |            | Tilted | Fixed            | 1         | 2412 | --                        | --              | --           |
|                                   |            |        |                  | 6         | 2437 | 0.13                      | 0.113           | 1.6          |
|                                   |            |        |                  | 11        | 2462 | --                        | --              | --           |
|                                   | Right Head | Cheek  | Fixed            | 1         | 2412 | --                        | --              | --           |
|                                   |            |        |                  | 6         | 2437 | -0.37                     | <b>0.196</b>    | 1.6          |
|                                   |            |        |                  | 11        | 2462 | --                        | --              | --           |
|                                   |            | Tilted | Fixed            | 1         | 2412 | --                        | --              | --           |
|                                   |            |        |                  | 6         | 2437 | 0.46                      | 0.099           | 1.6          |
|                                   |            |        |                  | 11        | 2462 | --                        | --              | --           |

Note: when the 1-g SAR is ≤ 0.8 W/kg, testing for low and high channel is optional.

| SAR MEASUREMENT                                                                     |            |        |                  |           |      |                           |                 |              |
|-------------------------------------------------------------------------------------|------------|--------|------------------|-----------|------|---------------------------|-----------------|--------------|
| Ambient Temperature (°C) : 21 ± 2                                                   |            |        |                  |           |      | Relative Humidity (%): 55 |                 |              |
| Liquid Temperature (°C) : 21 ± 2                                                    |            |        |                  |           |      | Depth of Liquid (cm):>15  |                 |              |
| Product: Smart Phone                                                                |            |        |                  |           |      |                           |                 |              |
| Test Mode: Hotspot                                                                  |            |        |                  |           |      |                           |                 |              |
| Configuration                                                                       |            |        | Antenna Position | Frequency |      | Power Drift (<±5%)        | SAR (1g) (W/kg) | Limit (W/kg) |
| Test Mode                                                                           | Position   | Status |                  | channel   | MHz  |                           |                 |              |
| Hotspot                                                                             | Body Back  | MS     | Fixed            | 1         | 2412 | --                        | --              | --           |
|                                                                                     |            |        |                  | 6         | 2437 | 0.02                      | <b>0.244</b>    | 1.6          |
|                                                                                     |            |        |                  | 11        | 2462 | --                        | --              | --           |
|                                                                                     | Body front | MS     | Fixed            | 1         | 2412 | --                        | --              | --           |
|                                                                                     |            |        |                  | 6         | 2437 | -1.13                     | 0.164           | 1.6          |
|                                                                                     |            |        |                  | 11        | 2462 | --                        | --              | --           |
| Note: when the 1-g SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. |            |        |                  |           |      |                           |                 |              |

## Simultaneous Multi-band Transmission Evaluation:

| Position | Simultaneous state                 |
|----------|------------------------------------|
| Head     | 1.WWAN(voice)+WLAN 2.4GHz band     |
|          | 2.WWAN(voice)+Bluetooth            |
|          | 3.WWAN(voice)+ HOTSPOT 2.4GHz band |
| Body     | 4. WWAN(voice)+WLAN 2.4GHz band    |
|          | 5. WWAN(voice)+Bluetooth           |
|          | 6.WWAN(voice)+ HOTSPOT 2.4GHz band |

### NOTE:

1. WLAN and BT share the same antenna, and cannot transmit simultaneously.
2. Simultaneous with every transmitter must be the same test position.
3. Based upon KDB 447498 D01 v05, BT SAR is excluded as below table.
4. Based upon KDB 447498 D01 v05, for handsets the test separation distance is determined by the smallest distance between the outer surface of the device and the user; which is 0mm for head SAR AND 5mm for body-worn SAR.
5. If the test separation distance is <5mm, 5mm is used for excluded SAR calculation.
6. For minimum test separation distance  $\leq 50\text{mm}$ , Bluetooth standalone SAR is excluded according to  $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot \sqrt{f \text{ (GHz)}} / x] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR
7. KDB 447498 / 4.3.2 (2) when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:
  - a)  $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot \sqrt{f \text{ (GHz)}} / x$  W/kg for test separation distances  $\leq 50 \text{ mm}$ ; Where  $x = 7.5$  for 1-g SAR, and  $x = 18.75$  for 10-g SAR.
  - b)  $0.4\text{W/Kg}$  for 1-g SAR and  $1.0\text{W/Kg}$  for 10-g SAR, when the separation distance is  $>50\text{mm}$ .

|    |      | Maximum Average Power |       | Antenna to user (mm) | SAR exclusion threshold (mW) | SAR testing required (Yes/No) | Head (0mm gap) | Body (5mm gap) |
|----|------|-----------------------|-------|----------------------|------------------------------|-------------------------------|----------------|----------------|
|    |      | dBm                   | mW    |                      |                              |                               |                |                |
| BT | Head | 2.31                  | 1.702 | 5                    | 10                           | NO                            | 0.0710 W/kg    | 0.0710 W/kg    |
|    | Body |                       |       | 5                    | 10                           | NO                            |                |                |

### Maximum test results (WWAN) with BT and WIFI/ HOTSPOT Simultaneous Transmission SAR:

**BT:** Head (0 cm gap): 0.0710 W/kg and Body (0.5 cm gap): 0.0710 W/kg

Head (WWAN (voice) +BT):  $0.933 \text{ W/kg} + 0.0710 \text{ W/kg} = 1.004 \text{ W/kg}$

Body (WWAN (voice) +BT):  $0.697 \text{ W/kg} + 0.0710 \text{ W/kg} = 0.768 \text{ W/kg}$

## HOTSPOT

| Head                                           |                             |              |              |                  |                 |
|------------------------------------------------|-----------------------------|--------------|--------------|------------------|-----------------|
| Conditions<br>(SAR1+SAR2)                      | Position                    | Max.<br>SAR1 | Max.<br>SAR2 | SAR<br>Summation | Limit<br>(W/kg) |
| <b>GSM835<br/>+ Hotspot<br/>(voice)</b>        | Right Cheek                 | 0.212        | 0.196        | 0.408            | 1.6             |
| <b>PCS1900<br/>+ Hotspot<br/>(voice)</b>       | Right Cheek                 | 0.406        | 0.196        | 0.602            | 1.6             |
| <b>WCDMA Band II<br/>+ Hotspot<br/>(voice)</b> | Right Cheek                 | 0.933        | 0.196        | <b>1.129</b>     | 1.6             |
| <b>WCDMA Band V<br/>+ Hotspot<br/>(voice)</b>  | Right Cheek                 | 0.428        | 0.196        | 0.624            | 1.6             |
| Body                                           |                             |              |              |                  |                 |
| Conditions<br>(SAR1+SAR2)                      | Position                    | Max.<br>SAR1 | Max.<br>SAR2 | SAR<br>Summation | Limit<br>(W/kg) |
| <b>GSM835<br/>+ Hotspot<br/>(voice)</b>        | Body Back<br>(MS)           | 0.225        | 0.244        | 0.469            | 1.6             |
| <b>PCS1900<br/>+ Hotspot<br/>(voice)</b>       | Body Back<br>(MS)           | 0.266        | 0.244        | 0.510            | 1.6             |
| <b>WCDMA Band II<br/>+ Hotspot<br/>(voice)</b> | RMC<br>(towards<br>grounds) | 0.614        | 0.244        | 0.858            | 1.6             |
| <b>WCDMA Band V<br/>+ Hotspot<br/>(voice)</b>  | RMC<br>(towards<br>grounds) | 0.697        | 0.244        | <b>0.941</b>     | 1.6             |

## Appendix A. SAR System Validation Data

Test Laboratory: AGC Lab

Date: Sep.12, 2013

System Check Head 835 MHz

DUT: Dipole 900 MHz Type: SID 900

Communication System CW; Communication System Band: D835 (835.0 MHz); Duty Cycle: 1:1; Conv.F=5.30

Frequency: 835 MHz; Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.91$  mho/m;  $\epsilon_r = 39.97$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;

Phantom section: Flat Section ; Input Power=10dBm

Ambient temperature (°C): 21, Liquid temperature (°C): 21


SATIMO Configuration:

Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01



Configuration/System Check GSM 835 Head/Area Scan: Measurement grid: dx=8mm,dy=8mm

Configuration/System Check GSM 835 Head/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm



Maximum location: X=0.00, Y=0.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.064627 |
| SAR 1g (W/Kg)  | 0.107315 |



**Test Laboratory: AGC Lab**  
**System Check Head 1900MHz**  
**DUT: Dipole 1900 MHz; Type: SID 1900**

**Date: Sep.12, 2013**


Communication System: CW; Communication System Band: D1900 (1900.0 MHz); Duty Cycle:1:1; Conv.F=4.72  
Frequency: 1900 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 40.33$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section ; Input Power=10dBm  
Ambient temperature (°C): 21, Liquid temperature (°C): 21

SATIMO Configuration:

Probe: EP165; Calibrated: 01/31/2013



- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

**Configuration/System Check PCS1900 Head/Area Scan: Measurement grid: dx=8mm,dy=8mm**  
**Configuration/System Check PCS1900 Head/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm**



**Maximum location: X=0.00, Y=0.00**

|                       |          |
|-----------------------|----------|
| <b>SAR 10g (W/Kg)</b> | 0.224312 |
| <b>SAR 1g (W/Kg)</b>  | 0.426457 |



**Test Laboratory: AGC Lab**  
**System Check Head 2450 MHz**  
**DUT: Dipole 2450 MHz Type: SID 2450**

**Date: Sep.12, 2013**


Communication System: CW; Communication System Band: D2450 (2450.0 MHz); Duty Cycle: 1:1; Conv.F=4.19  
Frequency: 2450 MHz; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.78$  mho/m;  $\epsilon_r = 40.57$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section; Input Power=10dBm  
Ambient temperature (°C): 21, Liquid temperature (°C): 21

SATIMO Configuration:

Probe: EP165; Calibrated: 01/31/2013



- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

**Configuration/System Check 2450 MHz Head/Area Scan: Measurement grid: dx=8mm,dy=8mm**  
**Configuration/System Check 2450 MHz Head/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm**



**Maximum location: X=0.00, Y=0.00**

|                       |          |
|-----------------------|----------|
| <b>SAR 10g (W/Kg)</b> | 0.243648 |
| <b>SAR 1g (W/Kg)</b>  | 0.497412 |



## Appendix B. SAR measurement Data

Test Laboratory: AGC Lab

Date: Sep.12, 2013

GSM 835 Mid-Touch-Left <SIM 1>

DUT: Smart Phone; Type: Galapad 6

Communication System: Generic GSM; Communication System Band: GSM 835; Duty Cycle: 1:8.3; Conv.F=5.30  
Frequency: 836.6 MHz; Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.91$  mho/m;  $\epsilon_r = 39.97$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section  
Ambient temperature (°C): 21.0, Liquid temperature (°C): 21.0


SATIMO Configuration:

Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01



Configuration/GSM 835 Mid-Touch-Left/Area Scan (6x8x1): Measurement grid: dx=8mm, dy=8mm  
Configuration/GSM 835 Mid-Touch-Left/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | sam_direct_droit2_surf8mm.txt        |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Left head                            |
| Device Position | Cheek                                |
| Band            | GSM 835                              |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 8.0)             |



Maximum location: X=-45.00, Y=-25.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.121275 |
| SAR 1g (W/Kg)  | 0.178437 |



Test Laboratory: AGC Lab  
GSM 835 Mid-Tilt-Left <SIM 1>  
DUT: Smart Phone; Type: Galapad 6

Date: Sep.12, 2013

Communication System: Generic GSM; Communication System Band: GSM 835; Duty Cycle: 1:8.3; Conv.F=5.30;  
Frequency: 836.6 MHz; Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.91$  mho/m;  $\epsilon_r = 39.97$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section  
Ambient temperature (°C): 21.0, Liquid temperature(°C): 21.0


SATIMO Configuration:

Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01



Configuration/GSM 835 Mid-Tilt-Left/Area Scan (6x8x1): Measurement grid: dx=8mm, dy=8mm  
Configuration/GSM 835 Mid-Tilt-Left/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm,dz=5mm;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | sam_direct_droit2_surf8mm.txt        |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Left head                            |
| Device Position | Tilt                                 |
| Band            | GSM 835                              |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 8.0)             |



Maximum location: X=-25.00, Y=-8.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.067143 |
| SAR 1g (W/Kg)  | 0.098854 |



Test Laboratory: AGC Lab  
GSM 835 Mid-Touch-Right <SIM 1>  
DUT: Smart Phone; Type: Galapad 6

Date: Sep.12, 2013

Communication System: Generic GSM; Communication System Band: GSM 835; Duty Cycle: 1:8.3; Conv.F=5.30;  
Frequency: 836.6 MHz; Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.91$  mho/m;  $\epsilon_r = 39.97$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 21.0, Liquid temperature (°C): 21.0

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

Configuration/GSM 835 Mid-Touch-Right/Area Scan: Measurement grid: dx=8mm, dy=8mm



Configuration/GSM 835 Mid-Touch-Right/Zoom Scan: Measurement grid: dx=8mm,  
dy=8mm, dz=5mm;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | sam_direct_droit2_surf8mm.txt        |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Right head                           |
| Device Position | Cheek                                |
| Band            | GSM 835                              |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 8.0)             |



Maximum location: X=-53.00, Y=-30.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.141035 |
| SAR 1g (W/Kg)  | 0.212247 |



Test Laboratory: AGC Lab  
GSM 835 Mid-Tilt-Right <SIM 1>  
DUT: Smart Phone; Type: Galapad 6

Date: Sep.12, 2013

Communication System: Generic GSM; Communication System Band: GSM 835; Duty Cycle: 1:8.3; Conv.F=5.30;  
Frequency: 836.6 MHz; Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.91$  mho/m;  $\epsilon_r = 39.97$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 21.0, Liquid temperature (°C): 21.0

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

Configuration/GSM 835 Mid-Tilt-Right/Area Scan: Measurement grid: dx=8mm, dy=8mm



Configuration/GSM 835 Mid-Tilt-Right/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | sam_direct_droit2_surf8mm.txt        |
| Zoom Scan       | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Right head                           |
| Device Position | Tilt                                 |
| Band            | GSM 835                              |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 8.0)             |



Maximum location: X=-41.00, Y=-24.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.072471 |
| SAR 1g (W/Kg)  | 0.108528 |



Test Laboratory: AGC Lab  
GSM 835 Mid-Touch-Right <SIM 2>  
DUT: Smart Phone; Type: Galapad 6

Date: Sep.12, 2013

Communication System: Generic GSM; Communication System Band: GSM 835; Duty Cycle: 1:8.3; Conv.F=5.30  
Frequency: 836.6 MHz; Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.91$  mho/m;  $\epsilon_r = 39.97$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 21.0, Liquid temperature (°C): 21.0


SATIMO Configuration:

Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01



Configuration/GSM 835 Mid-Touch-Right/Area Scan (6x8x1): Measurement grid: dx=8mm, dy=8mm  
Configuration/GSM 835 Mid-Touch-Right/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | sam_direct_droit2_surf8mm.txt        |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Right head                           |
| Device Position | Cheek                                |
| Band            | GSM 835                              |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 8.0)             |



Maximum location: X=-48.00, Y=-24.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.134275 |
| SAR 1g (W/Kg)  | 0.202217 |



Test Laboratory: AGC Lab  
GSM 835 Mid- Body- Back <SIM 1>  
DUT: Smart Phone; Type: Galapad 6

Date: Sep.12, 2013

Communication System: Generic GSM; Communication System Band: GSM 835; Duty Cycle: 1:8.3; Conv.F=5.46;  
Frequency: 836.6 MHz; Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.95$  mho/m;  $\epsilon_r = 53.26$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C): 21.0, Liquid temperature (°C): 21.0


SATIMO Configuration:

Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01



Configuration/GSM 835 Mid-Body-Back/Area Scan (6x8x1): Measurement grid: dx=8mm, dy=8mm  
Configuration/GSM 835 Mid-Body-Back/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | surf_sam_plan.txt                    |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Validation plane                     |
| Device Position | Body Back                            |
| Band            | GSM 835                              |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 8.0)             |



Maximum location: X=8.00, Y=-2.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.151357 |
| SAR 1g (W/Kg)  | 0.224682 |



Test Laboratory: AGC Lab  
GSM 835 Mid- Body- Front (MS) <SIM 1>  
DUT: Smart Phone; Type: Galapad 6

Date: Sep.12, 2013

Communication System: Generic GSM; Communication System Band: GSM 835; Duty Cycle: 1:8.3; Conv.F=5.46;  
Frequency: 836.6 MHz; Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.95$  mho/m;  $\epsilon_r = 53.26$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C): 21.0, Liquid temperature (°C): 21.0


SATIMO Configuration:

Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01



Configuration/GSM 835 Mid-Body- Front /Area Scan (6x8x1): Measurement grid: dx=8mm, dy=8mm  
Configuration/GSM 835 Mid-Body- Front Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | surf_sam_plan.txt                    |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Validation plane                     |
| Device Position | Body Front                           |
| Band            | GSM 835                              |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 8.0)             |



Maximum location: X=-2.00, Y=-22.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.093574 |
| SAR 1g (W/Kg)  | 0.132761 |



Test Laboratory: AGC Lab  
PCS 1900 Mid-Touch-Left <SIM 1>  
DUT: Smart Phone; Type: Galapad 6

Date: Sep.12, 2013

Communication System: Generic GSM; Communication System Band: PCS 1900; Duty Cycle: 1:8.3; Conv.F=4.72;  
Frequency: 1880 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 40.33$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section  
Ambient temperature (°C): 21.0, Liquid temperature (°C): 21.0

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

Configuration/PCS1900 Mid-Touch-Left/Area Scan: Measurement grid: dx=8mm, dy=8mm



Configuration/PCS1900 Mid-Touch-Left/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | sam_direct_droit2_surf8mm.txt        |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Left head                            |
| Device Position | Cheek                                |
| Band            | PCS 1900                             |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 8.0)             |



Maximum location: X=-55.00, Y=-57.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.165274 |
| SAR 1g (W/Kg)  | 0.263846 |



Test Laboratory: AGC Lab  
PCS 1900 Mid-Tilt-Left <SIM 1>  
DUT: Smart Phone; Type: Galapad 6

Date: Sep.12, 2013

Communication System: Generic GSM; Communication System Band: PCS 1900; Duty Cycle: 1:8.3; Conv.F=4.72;  
Frequency: 1880 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 40.33$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section  
Ambient temperature (°C): 21.0, Liquid temperature (°C): 21.0

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

Configuration/PCS1900 Mid-Tilt-Left/Area Scan: Measurement grid: dx=8mm, dy=8mm



Configuration/PCS1900 Mid-Tilt-Left/Zoom Scan: Measurement grid: dx=8mm, dy=8mm,dz=5mm;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | sam_direct_droit2_surf8mm.txt        |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Left head                            |
| Device Position | Tilt                                 |
| Band            | PCS 1900                             |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 8.0)             |



Maximum location: X=-16.00, Y=-8.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.157548 |
| SAR 1g (W/Kg)  | 0.205372 |



Test Laboratory: AGC Lab  
PCS 1900 Mid-Touch-Right <SIM 1>  
DUT: Smart Phone; Type: Galapad 6

Date: Sep.12, 2013

Communication System: Generic GSM; Communication System Band: PCS 1900; Duty Cycle: 1:8.3; Conv.F=4.72;  
Frequency: 1880 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 40.33$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 21.0, Liquid temperature (°C): 21.0

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

Configuration/PCS1900 Mid-Touch-Right/Area Scan: Measurement grid: dx=8mm, dy=8mm



Configuration/PCS1900 Mid-Touch-Right/Zoom Scan: Measurement grid: dx=8mm,  
dy=8mm, dz=5mm;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | sam_direct_droit2_surf8mm.txt        |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Right head                           |
| Device Position | Cheek                                |
| Band            | PCS 1900                             |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 8.0)             |



Maximum location: X=-55.00, Y=-57.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.237124 |
| SAR 1g (W/Kg)  | 0.406258 |



Test Laboratory: AGC Lab  
PCS 1900 Mid-Tilt-Right <SIM 1>  
DUT: Smart Phone; Type: Galapad 6

Date: Sep.12, 2013

Communication System: Generic GSM; Communication System Band: PCS 1900; Duty Cycle: 1:8.3; Conv.F=4.72;  
Frequency: 1880 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 40.33$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 21.0, Liquid temperature (°C): 21.0

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

Configuration/PCS1900 Mid-Tilt-Right/Area Scan: Measurement grid: dx=8mm, dy=8mm



Configuration/PCS1900 Mid-Tilt-Right/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | sam_direct_droit2_surf8mm.txt        |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Right head                           |
| Device Position | Tilt                                 |
| Band            | PCS 1900                             |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 8.0)             |



Maximum location: X=-30.00, Y=0.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.195721 |
| SAR 1g (W/Kg)  | 0.294628 |



Test Laboratory: AGC Lab  
PCS 1900 Mid-Touch-Right <SIM 2>  
DUT: Smart Phone; Type: Galapad 6

Date: Sep.12, 2013

Communication System: Generic GSM; Communication System Band: PCS 1900; Duty Cycle: 1:8.3; Conv.F=4.72;  
Frequency: 1880 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 40.33$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 21.0, Liquid temperature (°C): 21.0

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

Configuration/PCS1900 Mid-Touch-Right/Area Scan: Measurement grid: dx=8mm, dy=8mm



Configuration/PCS1900 Mid-Touch-Right/Zoom Scan: Measurement grid: dx=8mm,  
dy=8mm, dz=5mm;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | sam_direct_droit2_surf8mm.txt        |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Right head                           |
| Device Position | Cheek                                |
| Band            | PCS 1900                             |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 8.0)             |



Maximum location: X=-52.00, Y=-55.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.243907 |
| SAR 1g (W/Kg)  | 0.405539 |



Test Laboratory: AGC Lab  
PCS 1900 Mid-Body- Back <SIM 1>  
DUT: Smart Phone; Type: Galapad 6

Date: Sep.12, 2013

Communication System: Generic GSM; Communication System Band: PCS 1900; Duty Cycle: 1:8.3; Conv.F=4.84;  
Frequency: 1880 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.53$  mho/m;  $\epsilon_r = 54.12$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C): 21.0, Liquid temperature (°C): 21.0

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

Configuration/PCS1900 Mid-Body-Back/Area Scan: Measurement grid: dx=8mm, dy=8mm



Configuration/PCS1900 Mid-Body-Back/Zoom Scan: Measurement grid: dx=8mm,  
dy=8mm, dz=5mm;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | surf_sam_plan.txt                    |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Validation plane                     |
| Device Position | Body Back                            |
| Band            | PCS 1900                             |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 8.0)             |



Maximum location: X=-10.00, Y=25.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.164284 |
| SAR 1g (W/Kg)  | 0.265724 |



Test Laboratory: AGC Lab  
PCS 1900 Mid-Body -Front (MS) <SIM 1>  
DUT: Smart Phone; Type: Galapad 6

Date: Sep.12, 2013

Communication System: Generic GSM; Communication System Band: PCS 1900; Duty Cycle: 1:8.3; Conv.F=4.84;  
Frequency: 1880 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.53$  mho/m;  $\epsilon_r = 54.12$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C): 21.0, Liquid temperature (°C): 21.0


SATIMO Configuration:

Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01



Configuration/PCS1900 Mid-Body- Front /Area Scan: Measurement grid: dx=8mm, dy=8mm  
Configuration/PCS1900 Mid-Body- Front /Zoom Scan: Measurement grid: dx=8mm,  
dy=8mm, dz=5mm;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | surf_sam_plan.txt                    |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Validation plane                     |
| Device Position | Body Front                           |
| Band            | PCS 1900                             |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 8.0)             |



Maximum location: X=0.00, Y=-8.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.123128 |
| SAR 1g (W/Kg)  | 0.214273 |



**Test Laboratory:** AGC Lab  
**WCDMA Band II Mid-Touch-Left (RMC)**  
**DUT: Smart Phone; Type: Galapad 6**

**Date: Sep.12, 2013**

Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty Cycle:1:1;Conv.F=4.72  
Frequency: 1880 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 40.33$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section  
Ambient temperature (°C):21, Liquid temperature (°C):21


**SATIMO Configuration:**

Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01



**Configuration/ WCDMA Band II Mid-Touch-Left/Area Scan: Measurement grid: dx=8mm, dy=8mm**  
**Configuration/ WCDMA Band II Mid-Touch-Left/Zoom Scan: Measurement grid:**  
**dx=8mm,dy=8mm,dz=5mm;**

|                        |                                      |
|------------------------|--------------------------------------|
| <b>Area Scan</b>       | sam_direct_droit2_surf8mm.txt        |
| <b>ZoomScan</b>        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| <b>Phantom</b>         | Left head                            |
| <b>Device Position</b> | Cheek                                |
| <b>Band</b>            | WCDMA Band II                        |
| <b>Channels</b>        | Middle                               |
| <b>Signal</b>          | TDMA (Crest factor: 1.0)             |



**Maximum location: X=-57.00, Y=-16.00**

|                       |          |
|-----------------------|----------|
| <b>SAR 10g (W/Kg)</b> | 0.395837 |
| <b>SAR 1g (W/Kg)</b>  | 0.654217 |



**Test Laboratory:** AGC Lab  
**WCDMA Band** II Mid-Tilt-Left (RMC)  
**DUT:** Smart Phone; **Type:** Galapad 6

**Date:** Sep.12, 2013

Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty Cycle:1:1; Conv.F=4.72  
Frequency: 1880 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 40.33$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section  
Ambient temperature (°C):21, Liquid temperature (°C):21


SATIMO Configuration:

Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01



**Configuration/ WCDMA Band II Mid-Tilt-Left/Area Scan: Measurement grid: dx=8mm, dy=8mm**  
**Configuration/ WCDMA Band II Mid-Tilt-Left/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm;**

|                        |                                      |
|------------------------|--------------------------------------|
| <b>Area Scan</b>       | sam_direct_droit2_surf8mm.txt        |
| <b>ZoomScan</b>        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| <b>Phantom</b>         | Left head                            |
| <b>Device Position</b> | Tilt                                 |
| <b>Band</b>            | WCDMA Band II                        |
| <b>Channels</b>        | Middle                               |
| <b>Signal</b>          | TDMA (Crest factor: 1.0)             |



**Maximum location: X=6.00, Y=15.00**

|                       |          |
|-----------------------|----------|
| <b>SAR 10g (W/Kg)</b> | 0.126274 |
| <b>SAR 1g (W/Kg)</b>  | 0.215843 |



**Test Laboratory:** AGC Lab  
**WCDMA Band** II Low-Touch-Right (RMC)  
**DUT:** Smart Phone; **Type:** Galapad 6

**Date:** Sep.12, 2013

Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty Cycle:1:1; Conv.F=4.72  
Frequency: 1852.4 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 40.33$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C):21, Liquid temperature (°C):21


SATIMO Configuration:

Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01



**Configuration/ WCDMA band II Low-Touch-Right/Area Scan:** Measurement grid: dx=8mm, dy=8mm  
**Configuration/ WCDMA band II Low-Touch-Right/Zoom Scan:** Measurement grid: dx=8mm, dy=8mm, dz=5mm;

|                        |                                      |
|------------------------|--------------------------------------|
| <b>Area Scan</b>       | sam_direct_droit2_surf8mm.txt        |
| <b>ZoomScan</b>        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| <b>Phantom</b>         | Right head                           |
| <b>Device Position</b> | Cheek                                |
| <b>Band</b>            | WCDMA band II                        |
| <b>Channels</b>        | Low                                  |
| <b>Signal</b>          | TDMA (Crest factor: 1.0)             |



**Maximum location: X=-55.00, Y=-53.00**

|                       |          |
|-----------------------|----------|
| <b>SAR 10g (W/Kg)</b> | 0.452307 |
| <b>SAR 1g (W/Kg)</b>  | 0.864271 |



**Test Laboratory:** AGC Lab  
**WCDMA Band** II Mid-Touch-Right (RMC)  
**DUT:** Smart Phone; Type: Galapad 6

**Date:** Sep.12, 2013

Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty Cycle:1:1; Conv.F=4.72  
Frequency: 1880 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 40.33$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C):21, Liquid temperature (°C):21


SATIMO Configuration:

Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01



**Configuration/ WCDMA band II Mid-Touch-Right/Area Scan: Measurement grid: dx=8mm, dy=8mm**  
**Configuration/ WCDMA band II Mid-Touch-Right/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm;**

|                        |                                      |
|------------------------|--------------------------------------|
| <b>Area Scan</b>       | sam_direct_droit2_surf8mm.txt        |
| <b>ZoomScan</b>        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| <b>Phantom</b>         | Right head                           |
| <b>Device Position</b> | Cheek                                |
| <b>Band</b>            | WCDMA band II                        |
| <b>Channels</b>        | Middle                               |
| <b>Signal</b>          | TDMA (Crest factor: 1.0)             |



**Maximum location: X=-55.00, Y=-50.00**

|                       |          |
|-----------------------|----------|
| <b>SAR 10g (W/Kg)</b> | 0.496271 |
| <b>SAR 1g (W/Kg)</b>  | 0.932846 |



**Test Laboratory:** AGC Lab  
**WCDMA Band** II High-Touch-Right (RMC)  
**DUT:** Smart Phone; Type: Galapad 6

**Date:** Sep.12, 2013

Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty Cycle:1:1; Conv.F=4.72  
Frequency: 1907.6 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 40.33$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C):21, Liquid temperature (°C):21


SATIMO Configuration:

Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01



**Configuration/ WCDMA band II High-Touch-Right/Area Scan: Measurement grid: dx=8mm, dy=8mm**  
**Configuration/ WCDMA band II High-Touch-Right/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm;**

|                        |                                      |
|------------------------|--------------------------------------|
| <b>Area Scan</b>       | sam_direct_droit2_surf8mm.txt        |
| <b>ZoomScan</b>        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| <b>Phantom</b>         | Right head                           |
| <b>Device Position</b> | Cheek                                |
| <b>Band</b>            | WCDMA band II                        |
| <b>Channels</b>        | High                                 |
| <b>Signal</b>          | TDMA (Crest factor: 1.0)             |



**Maximum location: X=-50.00, Y=-48.00**

|                       |          |
|-----------------------|----------|
| <b>SAR 10g (W/Kg)</b> | 0.456271 |
| <b>SAR 1g (W/Kg)</b>  | 0.882248 |



Test Laboratory: AGC Lab  
WCDMA Band II Mid-Tilt-Right <RMC>  
DUT: Smart Phone; Type: Galapad 6

Date: Sep.12, 2013

Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty Cycle:1:1; Conv.F=4.72  
Frequency: 1880 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 40.33$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C):21, Liquid temperature (°C):21

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

Configuration/PCS1900 Mid-Tilt-Right/Area Scan: Measurement grid: dx=8mm, dy=8mm



Configuration/PCS1900 Mid-Tilt-Right/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | sam_direct_droit2_surf8mm.txt        |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Right head                           |
| Device Position | Tilt                                 |
| Band            | WCDMA band II                        |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 1.0)             |



Maximum location: X=-40.00, Y=-40.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.124281 |
| SAR 1g (W/Kg)  | 0.202846 |



**Test Laboratory:** AGC Lab  
**WCDMA Band II Mid-Body-Towards Grounds (RMC)**  
**DUT: Smart Phone; Type: Galapad 6**

**Date: Sep.12, 2013**

Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty Cycle:1:1; ConvF=4.84  
Frequency: 1880 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.53$  mho/m;  $\epsilon_r = 54.12$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C):21, Liquid temperature (°C):21


**SATIMO Configuration:**

Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01



**Configuration/ WCDMA band II Mid-Body-back/Area Scan: Measurement grid: dx=8mm, dy=8mm**  
**Configuration/ WCDMA band II Mid-Body-back/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm;**

|                        |                                      |
|------------------------|--------------------------------------|
| <b>Area Scan</b>       | surf_sam_plan.txt                    |
| <b>ZoomScan</b>        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| <b>Phantom</b>         | Validation plane                     |
| <b>Device Position</b> | Body Back                            |
| <b>Band</b>            | WCDMA band II                        |
| <b>Channels</b>        | Middle                               |
| <b>Signal</b>          | TDMA (Crest factor: 1.0)             |



**Maximum location: X=-20.00, Y=8.00**

|                       |          |
|-----------------------|----------|
| <b>SAR 10g (W/Kg)</b> | 0.354627 |
| <b>SAR 1g (W/Kg)</b>  | 0.613854 |



**Test Laboratory:** AGC Lab  
**WCDMA Band II Mid-Body-Towards Phantom (RMC)**  
**DUT: Smart Phone; Type: Galapad 6**

**Date: Sep.12, 2013**

Communication System: UMTS; Communication System Band: Band II UTRA/FDD ;Duty Cycle:1:1; ConvF=4.84  
Frequency: 1880 MHz; Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.53$  mho/m;  $\epsilon_r = 54.12$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C):21, Liquid temperature (°C):21


**SATIMO Configuration:**

Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01



**Configuration/ WCDMA band II Mid-Body-Front/Area Scan: Measurement grid: dx=8mm, dy=8mm**  
**Configuration/ WCDMA band II Mid-Body-Front/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm;**

|                        |                                      |
|------------------------|--------------------------------------|
| <b>Area Scan</b>       | surf_sam_plan.txt                    |
| <b>ZoomScan</b>        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| <b>Phantom</b>         | Validation plane                     |
| <b>Device Position</b> | Body Front                           |
| <b>Band</b>            | WCDMA band II                        |
| <b>Channels</b>        | Middle                               |
| <b>Signal</b>          | TDMA (Crest factor: 1.0)             |



**Maximum location: X=22.00, Y=18.00**

|                       |          |
|-----------------------|----------|
| <b>SAR 10g (W/Kg)</b> | 0.292024 |
| <b>SAR 1g (W/Kg)</b>  | 0.478948 |



Test Laboratory: AGC Lab

Date: Sep.12, 2013

WCDMA Band V Mid-Touch-Left (RMC )

DUT: Smart Phone; Type: Galapad 6

Communication System: UMTS; Communication System Band: BAND V UTRA/FDD ; Duty Cycle:1: 1; Conv.F=5.30  
Frequency: 835 MHz; Medium parameters used:  $f = 850$  MHz;  $\sigma=0.91$  mho/m;  $\epsilon_r=39.97$ ;  $\rho= 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section  
Ambient temperature (°C): 21, Liquid temperature (°C): 21


SATIMO Configuration:

Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01



Configuration/ WCDMA Band V Mid-Touch-Left/Area Scan (6x8x1): Measurement grid: dx=8mm, dy=8mm  
Configuration/ WCDMA Band V Mid-Touch-Left/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | sam direct droit2_surf8mm.txt        |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Left head                            |
| Device Position | Cheek                                |
| Band            | WCDMA Band V                         |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 1.0)             |



Maximum location: X=-49.00, Y=-39.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.245284 |
| SAR 1g (W/Kg)  | 0.344276 |



Test Laboratory: AGC Lab

Date: Sep.12, 2013

WCDMA Band V Mid-Tilt-Left (RMC)

DUT: Smart Phone; Type: Galapad 6

Communication System: UMTS; Communication System Band: BAND V UTRA/FDD ; Duty Cycle:1: 1; Conv.F=5.30  
Frequency: 835 MHz; Medium parameters used:  $f = 850$  MHz;  $\sigma=0.91$  mho/m;  $\epsilon_r=39.97$ ;  $\rho= 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section  
Ambient temperature (°C): 21, Liquid temperature (°C): 21


SATIMO Configuration:

Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01



Configuration/ WCDMA Band V Mid-Tilt-Left/Area Scan (6x8x1): Measurement grid: dx=8mm, dy=8mm  
Configuration/ WCDMA Band V Mid-Tilt-Left/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | sam direct droit2_surf8mm.txt        |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Left head                            |
| Device Position | Tilt                                 |
| Band            | WCDMA Band V                         |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 1.0)             |



Maximum location: X=-25.00, Y=-15.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.237246 |
| SAR 1g (W/Kg)  | 0.322257 |



Test Laboratory: AGC Lab

Date: Sep.12, 2013

WCDMA Band V Mid- Touch-Right (RMC)

DUT: Smart Phone; Type: Galapad 6

Communication System: UMTS; Communication System Band: BAND V UTRA/FDD ; Duty Cycle:1: 1; Conv.F=5.30  
Frequency: 835 MHz; Medium parameters used:  $f = 850$  MHz;  $\sigma=0.91$  mho/m;  $\epsilon_r=39.97$ ;  $\rho= 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 21, Liquid temperature (°C): 21

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

Configuration/ WCDMA Band V Mid-Touch-Right/Area Scan: Measurement grid: dx=8mm, dy=8mm



Configuration/ WCDMA Band V Mid-Touch-Right/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | sam_direct_droit2_surf8mm.txt        |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Right head                           |
| Device Position | Cheek                                |
| Band            | WCDMA Band V                         |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 1.0)             |



Maximum location: X=-49.00, Y=-42.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.272576 |
| SAR 1g (W/Kg)  | 0.427721 |



Test Laboratory: AGC Lab

Date: Sep.12, 2013

WCDMA Band V Mid-Tilt-Right (RMC)

DUT: Smart Phone; Type: Galapad 6

Communication System: UMTS; Communication System Band: BAND V UTRA/FDD ; Duty Cycle:1: 1; Conv.F=5.30  
Frequency: 835 MHz; Medium parameters used:  $f = 850$  MHz;  $\sigma=0.91$  mho/m;  $\epsilon_r=39.97$ ;  $\rho= 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 21, Liquid temperature (°C): 21

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

Configuration/ WCDMA Band V Mid-Tilt-Right/Area Scan: Measurement grid: dx=8mm, dy=8mm



Configuration/ WCDMA Band V Mid-Tilt-Right/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | sam direct droit2_surf8mm.txt        |
| Zoom Scan       | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Right head                           |
| Device Position | Tilt                                 |
| Band            | WCDMA Band V                         |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 1.0)             |



Maximum location: X=-16.00, Y=0.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.264127 |
| SAR 1g (W/Kg)  | 0.365274 |



Test Laboratory: AGC Lab

Date: Sep.12, 2013

WCDMA Band V Mid-Body-Towards Grounds (RMC)

DUT: Smart Phone; Type: Galapad 6

Communication System: UMTS; Communication System Band: BAND V UTRA/FDD; Duty Cycle:1: 1; Conv.F=5.46  
Frequency: 835 MHz; Medium parameters used:  $f = 850$  MHz;  $\sigma=0.95$  mho/m;  $\epsilon_r=53.26$ ;  $\rho= 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C):21, Liquid temperature (°C):21

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

Configuration/ WCDMA Band V Mid-Body-Front/Area Scan (6x8x1): Measurement grid: dx=8mm, dy=8mm



Configuration/ WCDMA Band V Mid-Body-Front/Zoom Scan (5x5x7)/Cube 0: Measurement grid:  
dx=8mm,dy=8mm, dz=5mm;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | surf_sam_plan.txt                    |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Validation plane                     |
| Device Position | Body Back                            |
| Band            | WCDMA Band V                         |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 1.0)             |



Maximum location: X=10.00, Y=-30.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.481024 |
| SAR 1g (W/Kg)  | 0.697328 |



Test Laboratory: AGC Lab

Date: Sep.12, 2013

WCDMA Band V Mid- Body - Towards Phantom (RMC)

DUT: Smart Phone; Type: Galapad 6

Communication System: UMTS; Communication System Band: BAND V UTRA/FDD ; Duty Cycle:1: 1; Conv.F=5.46  
Frequency: 835 MHz; Medium parameters used:  $f = 850$  MHz;  $\sigma=0.95$  mho/m;  $\epsilon_r=53.26$ ;  $\rho= 1000\text{kg/m}^3$  ;  
Phantom section: Flat Section  
Ambient temperature ( $^{\circ}\text{C}$ ):21, Liquid temperature ( $^{\circ}\text{C}$ ):21


SATIMO Configuration:

Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01



Configuration/ WCDMA Band V Mid-Body- Back /Area Scan (6x8x1): Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$   
Configuration/ WCDMA Band V Mid-Body- Back /Zoom Scan (5x5x7)/Cube 0: Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ ;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | surf_sam_plan.txt                    |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Validation plane                     |
| Device Position | Body Front                           |
| Band            | WCDMA Band V                         |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 1.0)             |



Maximum location: X=0.00, Y=-24.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.306425 |
| SAR 1g (W/Kg)  | 0.440286 |



## WIFI MODE

Test Laboratory: AGC Lab  
802.11b Mid-Touch-Left

Date: Sep.12, 2013

DUT: Smart Phone; Type: Galapad 6

Communication System: Wi-Fi; Communication System Band: 802.11b; Duty Cycle: 1:1; Conv.F=4.19;  
Frequency: 2437 MHz; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.78$  mho/m;  $\epsilon_r = 40.57$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section  
Ambient temperature (°C): 21, Liquid temperature (°C): 21


SATIMO Configuration:

Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01



Configuration/802.11b Mid- Touch-Left/Area Scan (6x8x1): Measurement grid: dx=8mm, dy=8mm  
Configuration/802.11b Mid- Touch-Left/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | sam_direct_droit2_surf8mm.txt        |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Left head                            |
| Device Position | Cheek                                |
| Band            | 2450MHz                              |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 8.0)             |



Maximum location: X=-17.00, Y=-2.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.094127 |
| SAR 1g (W/Kg)  | 0.152831 |



Test Laboratory: AGC Lab  
802.11b Mid -Tilt-Left

Date: Sep.12, 2013

DUT: Smart Phone; Type: Galapad 6

Communication System: Wi-Fi; Communication System Band: 802.11b; Duty Cycle: 1:1; Conv.F=4.19;  
Frequency: 2437 MHz; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.78$  mho/m;  $\epsilon_r = 40.57$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section  
Ambient temperature (°C): 21, Liquid temperature (°C): 21

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

Configuration/802.11b Mid- Tilt-Left/Area Scan (6x8x1): Measurement grid: dx=8mm, dy=8mm



Configuration/802.11b Mid- Tilt-Left/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm,dz=5mm;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | sam_direct_droit2_surf8mm.txt        |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Left head                            |
| Device Position | Tilt                                 |
| Band            | 2450MHz                              |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 8.0)             |



Maximum location: X=-8.00, Y=8.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.046127 |
| SAR 1g (W/Kg)  | 0.072846 |



Test Laboratory: AGC Lab  
802.11b Mid- Touch-Right  
**DUT: Smart Phone; Type: Galapad 6**

**Date: Sep.12, 2013**

Communication System: Wi-Fi; Communication System Band: 802.11b; Duty Cycle: 1:1; Conv.F=4.19;  
Frequency: 2437 MHz; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.78$  mho/m;  $\epsilon_r = 40.57$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 21, Liquid temperature (°C): 21

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

**Configuration/802.11b Mid- Touch-Right /Area Scan:** Measurement grid: dx=8mm, dy=8mm



**Configuration/802.11b Mid- Touch-Right /Zoom Scan:** Measurement grid: dx=8mm, dy=8mm, dz=5mm;

|                        |                                      |
|------------------------|--------------------------------------|
| <b>Area Scan</b>       | sam_direct_droit2_surf8mm.txt        |
| <b>ZoomScan</b>        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| <b>Phantom</b>         | Right head                           |
| <b>Device Position</b> | Cheek                                |
| <b>Band</b>            | 2450MHz                              |
| <b>Channels</b>        | Middle                               |
| <b>Signal</b>          | TDMA (Crest factor: 8.0)             |



**Maximum location: X=-18.00, Y=-7.00**

|                       |          |
|-----------------------|----------|
| <b>SAR 10g (W/Kg)</b> | 0.084305 |
| <b>SAR 1g (W/Kg)</b>  | 0.146817 |



Test Laboratory: AGC Lab  
802.11b Mid-Tilt-Right  
**DUT: Smart Phone; Type: Galapad 6**

**Date: Sep.12, 2013**

Communication System: Wi-Fi; Communication System Band: 802.11b; Duty Cycle: 1:1; Conv.F=4.19;  
Frequency: 2437 MHz; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.78$  mho/m;  $\epsilon_r = 40.57$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 21, Liquid temperature (°C): 21

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

**Configuration/802.11b Mid- Tilt-Right/Area Scan:** Measurement grid: dx=8mm, dy=8mm



**Configuration/802.11b Mid- Tilt-Right/Zoom Scan:** Measurement grid: dx=8mm, dy=8mm, dz=5mm;

|                        |                                      |
|------------------------|--------------------------------------|
| <b>Area Scan</b>       | sam_direct droit2_surf8mm.txt        |
| <b>Zoom Scan</b>       | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| <b>Phantom</b>         | Right head                           |
| <b>Device Position</b> | Tilt                                 |
| <b>Band</b>            | 2450MHz                              |
| <b>Channels</b>        | Middle                               |
| <b>Signal</b>          | TDMA (Crest factor: 8.0)             |



**Maximum location: X=8.00, Y=2.00**

|                       |          |
|-----------------------|----------|
| <b>SAR 10g (W/Kg)</b> | 0.067218 |
| <b>SAR 1g (W/Kg)</b>  | 0.124128 |



Test Laboratory: AGC Lab  
802.11b Mid-Body-Worn- Back  
**DUT: Smart Phone; Type: Galapad 6**

**Date: Sep.12, 2013**

Communication System: Wi-Fi; Communication System Band: 802.11b; Duty Cycle: 1:1; Conv.F=4.32;  
Frequency: 2437 MHz; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.89$  mho/m;  $\epsilon_r = 53.46$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C):21, Liquid temperature (°C):21

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

**Configuration/802.11b Mid- Body- Back /Area Scan (6x8x1):** Measurement grid: dx=8mm, dy=8mm



**Configuration/802.11b Mid- Body- Back /Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm;

|                        |                                      |
|------------------------|--------------------------------------|
| <b>Area Scan</b>       | surf_sam_plan.txt                    |
| <b>ZoomScan</b>        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| <b>Phantom</b>         | Validation plane                     |
| <b>Device Position</b> | Body Back                            |
| <b>Band</b>            | 2450MHz                              |
| <b>Channels</b>        | Middle                               |
| <b>Signal</b>          | TDMA (Crest factor: 8.0)             |



**Maximum location: X=-2.00, Y=-13.00**

|                       |          |
|-----------------------|----------|
| <b>SAR 10g (W/Kg)</b> | 0.116218 |
| <b>SAR 1g (W/Kg)</b>  | 0.207215 |



Test Laboratory: AGC Lab  
802.11b Mid-Body -Front  
**DUT: Smart Phone; Type: Galapad 6**

**Date: Sep.12, 2013**

Communication System: Wi-Fi; Communication System Band: 802.11b; Duty Cycle: 1:1; Conv.F=4.32;  
Frequency: 2437 MHz; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.89$  mho/m;  $\epsilon_r = 53.46$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C):21, Liquid temperature (°C):21

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

**Configuration/802.11b Mid-Body- Front /Area Scan:** Measurement grid: dx=8mm, dy=8mm



**Configuration/802.11b Mid-Body- Front /Zoom Scan:** Measurement grid: dx=8mm, dy=8mm, dz=5mm;

|                        |                                      |
|------------------------|--------------------------------------|
| <b>Area Scan</b>       | surf_sam_plan.txt                    |
| <b>ZoomScan</b>        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| <b>Phantom</b>         | Validation plane                     |
| <b>Device Position</b> | Body Front                           |
| <b>Band</b>            | 2450MHz                              |
| <b>Channels</b>        | Middle                               |
| <b>Signal</b>          | TDMA (Crest factor: 8.0)             |



**Maximum location: X=0.00, Y=-22.00**

|                       |          |
|-----------------------|----------|
| <b>SAR 10g (W/Kg)</b> | 0.057208 |
| <b>SAR 1g (W/Kg)</b>  | 0.095237 |



## HOTSPOT MODE

Test Laboratory: AGC Lab

Hotspot Mid-Touch-Left

DUT: Smart Phone; Type: Galapad 6

Date: Sep.12, 2013

Communication System: Wi-Fi; Communication System Band: Hotspot; Duty Cycle: 1:1; Conv.F=4.19;  
Frequency: 2437 MHz; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.78$  mho/m;  $\epsilon_r = 40.57$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section  
Ambient temperature (°C): 21, Liquid temperature (°C): 21

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

Configuration/Hotspot Mid- Touch-Left/Area Scan (6x8x1): Measurement grid: dx=8mm, dy=8mm



Configuration/Hotspot Mid- Touch-Left/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | sam_direct droit2_surf8mm.txt        |
| ZoomScan        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Left head                            |
| Device Position | Cheek                                |
| Band            | 2450MHz                              |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 8.0)             |



Maximum location: X=-31.00, Y=-15.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.079208 |
| SAR 1g (W/Kg)  | 0.127108 |



Test Laboratory: AGC Lab  
Hotspot Mid -Tilt-Left  
**DUT: Smart Phone; Type: Galapad 6**

**Date: Sep.12, 2013**

Communication System: Wi-Fi; Communication System Band: Hotspot; Duty Cycle: 1:1; Conv.F=4.19;  
Frequency: 2437 MHz; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.78$  mho/m;  $\epsilon_r = 40.57$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section  
Ambient temperature (°C): 21, Liquid temperature (°C): 21

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

**Configuration/Hotspot Mid- Tilt-Left/Area Scan (6x8x1):** Measurement grid: dx=8mm, dy=8mm



**Configuration/Hotspot Mid- Tilt-Left/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm,dz=5mm;

|                        |                                      |
|------------------------|--------------------------------------|
| <b>Area Scan</b>       | sam_direct_droit2_surf8mm.txt        |
| <b>ZoomScan</b>        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| <b>Phantom</b>         | Left head                            |
| <b>Device Position</b> | Tilt                                 |
| <b>Band</b>            | 2450MHz                              |
| <b>Channels</b>        | Middle                               |
| <b>Signal</b>          | TDMA (Crest factor: 8.0)             |



**Maximum location: X=-22.00, Y=-8.00**

|                       |          |
|-----------------------|----------|
| <b>SAR 10g (W/Kg)</b> | 0.077218 |
| <b>SAR 1g (W/Kg)</b>  | 0.112840 |



Test Laboratory: AGC Lab  
Hotspot Mid- Touch-Right  
**DUT: Smart Phone; Type: Galapad 6**

**Date: Sep.12, 2013**

Communication System: Wi-Fi; Communication System Band: Hotspot; Duty Cycle: 1:1; Conv.F=4.19;  
Frequency: 2437 MHz; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.78$  mho/m;  $\epsilon_r = 40.57$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 21, Liquid temperature (°C): 21

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

**Configuration/Hotspot Mid- Touch-Right /Area Scan:** Measurement grid: dx=8mm, dy=8mm



**Configuration/Hotspot Mid- Touch-Right /Zoom Scan:** Measurement grid: dx=8mm, dy=8mm, dz=5mm;

|                        |                                      |
|------------------------|--------------------------------------|
| <b>Area Scan</b>       | sam_direct_droit2_surf8mm.txt        |
| <b>ZoomScan</b>        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| <b>Phantom</b>         | Right head                           |
| <b>Device Position</b> | Cheek                                |
| <b>Band</b>            | 2450MHz                              |
| <b>Channels</b>        | Middle                               |
| <b>Signal</b>          | TDMA (Crest factor: 8.0)             |



**Maximum location: X=-10.00, Y=-6.00**

|                       |          |
|-----------------------|----------|
| <b>SAR 10g (W/Kg)</b> | 0.134281 |
| <b>SAR 1g (W/Kg)</b>  | 0.196128 |



Test Laboratory: AGC Lab  
Hotspot Mid-Tilt-Right

Date: Sep.12, 2013

DUT: Smart Phone; Type: Galapad 6

Communication System: Wi-Fi; Communication System Band: Hotspot; Duty Cycle: 1:1; Conv.F=4.19;  
Frequency: 2437 MHz; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.78$  mho/m;  $\epsilon_r = 40.57$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section  
Ambient temperature (°C): 21, Liquid temperature (°C): 21

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

Configuration/Hotspot Mid- Tilt-Right/Area Scan: Measurement grid: dx=8mm, dy=8mm



Configuration/Hotspot Mid- Tilt-Right/Zoom Scan: Measurement grid: dx=8mm, dy=8mm, dz=5mm;

|                 |                                      |
|-----------------|--------------------------------------|
| Area Scan       | sam_direct_droit2_surf8mm.txt        |
| Zoom Scan       | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| Phantom         | Right head                           |
| Device Position | Tilt                                 |
| Band            | 2450MHz                              |
| Channels        | Middle                               |
| Signal          | TDMA (Crest factor: 8.0)             |



Maximum location: X=-2.00, Y=-8.00

|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.053128 |
| SAR 1g (W/Kg)  | 0.098514 |



Test Laboratory: AGC Lab  
Hotspot Mid-Body-Worn- Back  
**DUT: Smart Phone; Type: Galapad 6**

**Date: Sep.12, 2013**

Communication System: Wi-Fi; Communication System Band: Hotspot; Duty Cycle: 1:1; Conv.F=4.32;  
Frequency: 2437 MHz; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.89$  mho/m;  $\epsilon_r = 53.46$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C):21, Liquid temperature (°C):21

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

**Configuration/Hotspot Mid- Body- Back /Area Scan (6x8x1):** Measurement grid: dx=8mm, dy=8mm



**Configuration/Hotspot Mid- Body- Back /Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm;

|                        |                                      |
|------------------------|--------------------------------------|
| <b>Area Scan</b>       | surf_sam_plan.txt                    |
| <b>ZoomScan</b>        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| <b>Phantom</b>         | Validation plane                     |
| <b>Device Position</b> | Body Back                            |
| <b>Band</b>            | 2450MHz                              |
| <b>Channels</b>        | Middle                               |
| <b>Signal</b>          | TDMA (Crest factor: 8.0)             |



**Maximum location: X=10.00, Y=-25.00**

|                       |          |
|-----------------------|----------|
| <b>SAR 10g (W/Kg)</b> | 0.147501 |
| <b>SAR 1g (W/Kg)</b>  | 0.244205 |



Test Laboratory: AGC Lab  
Hotspot Mid-Body -Front  
**DUT: Smart Phone; Type: Galapad 6**

**Date: Sep.12, 2013**

Communication System: Wi-Fi; Communication System Band: Hotspot; Duty Cycle: 1:1; Conv.F=4.32;  
Frequency: 2437 MHz; Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.89$  mho/m;  $\epsilon_r = 53.46$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section  
Ambient temperature (°C):21, Liquid temperature (°C):21

SATIMO Configuration:


Probe: EP165; Calibrated: 01/31/2013

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: Flat Phantom; Type: Elliptical Phantom
- Measurement SW: OpenSAR V4\_02\_01

**Configuration/Hotspot Mid-Body- Front /Area Scan:** Measurement grid: dx=8mm, dy=8mm

**Configuration/Hotspot Mid-Body- Front /Zoom Scan:** Measurement grid: dx=8mm, dy=8mm, dz=5mm;

|                        |                                      |
|------------------------|--------------------------------------|
| <b>Area Scan</b>       | surf_sam_plan.txt                    |
| <b>ZoomScan</b>        | 5x5x7,dx=8mm dy=8mm dz=5mm,Very fast |
| <b>Phantom</b>         | Validation plane                     |
| <b>Device Position</b> | Body Front                           |
| <b>Band</b>            | 2450MHz                              |
| <b>Channels</b>        | Middle                               |
| <b>Signal</b>          | TDMA (Crest factor: 8.0)             |



**Maximum location: X=-10.00, Y=-22.00**

|                       |          |
|-----------------------|----------|
| <b>SAR 10g (W/Kg)</b> | 0.097124 |
| <b>SAR 1g (W/Kg)</b>  | 0.164208 |

