



FCC PART 15.407 TEST REPORT

For

Shenzhen Crystal Video Technology Co.,LTD.

F13, F518 Idea Land, Baoyuan Road, Baoan Central Area, Shenzhen, China

FCC ID: Y3HCB662020120206

Report Type: Product Type: WHDI Device Original Report **Test Engineer:** Ares Liu **Report Number:** R1DG120210005-00 **Report Date:** 2012-03-02 Merry Zhao **Reviewed By:** EMC Engineer Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building. ShiHua Road, FuTian Free Trade Zone **Test Laboratory:** Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk "★" (Rev.2)

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
TEST FACILITY	
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT Exercise Software	
EQUIPMENT MODIFICATIONS	6
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	7
FCC §15.407 (f), §2.1093, §1.1307(b) (1) – RF EXPOSURE EVALUATIO	
APPLICABLE STANDARD	8
FCC §15.203 – ANTENNA REQUIREMENT	9
APPLICABLE STANDARD	
ANTENNA CONNECTOR CONSTRUCTION	
FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS	10
APPLICABLE STANDARD	10
MEASUREMENT UNCERTAINTY	
EUT SETUP	
EMI TEST RECEIVER SETUP	
TEST EQUIPMENT LIST AND DETAILS	
TEST PROCEDURE TEST RESULTS SUMMARY	
TEST DATA	
FCC §15.209, §15.205 & §15.407(b) (1) (6) (7) – UNDESIRABLE EMIS	
APPLICABLE STANDARD	
MEASUREMENT UNCERTAINTY	
EUT Setup.	
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	15
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS	
TEST RESULTS SUMMARY	
TEST DATA	
FCC §15.407(a) (1) – 26 dB OCCUPIED BANDWIDTH	
APPLICABLE STANDARD	
TEST EQUIPMENT LIST AND DETAILS	
TEST PROCEDURE	
Test Data	
FCC §15.407(a) (1) – CONDUCTED TRANSMITTER OUTPUT POW	ER24
APPLICABLE STANDARD	
TEST EQUIPMENT LIST AND DETAILS	24

TEST PROCEDURE	24
Test Data	25
FCC §15.407(a) (1) (5) - POWER SPECTRAL DENSITY	27
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST EQUIPMENT LIST AND DETAILS.	27
Test Data	28
FCC §15.407(a) (6) – PEAK EXCURSION RATIO	30
APPLICABLE STANDARD	30
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	30
TEST DATA	
FCC §407(g) - FREQUENCY STABILITY	33
APPLICABLE STANDARDS	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
Test Data	
DECLARATION LETTER	35

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Shenzhen Crystal Video Technology Co.,LTD.'s product, model number: CB6620,CV6620,CV6620,CV6620-IL,CB6620-IL,CB6628,5002R,5003R, (FCC ID: Y3HCB662020120206) ("EUT") in this report is a transmitter of wireless high-definition receiver, which was measured approximately: 14.7 cm (L) x 9.7cm (W) x 2.1 cm (H), rated input voltage: DC 5V from AC/DC adapter.

Report No.: R1DG120210005-00

Adapter information: Trade Name: GOSPELL Model:GP005U-050-200 Input:100-240V,50/60Hz,0.5A Output:5VDC,2A

Note: The series product, model CB6620,CV6620,CV6620-IL,CB6620-IL,CB6628,5002R and 5003R are electrically identical, the difference between them is just the model name, we selected CB6620 for fully testing, the details was explained in the attached declaration letter.

* All measurement and test data in this report was gathered from production sample serial number: 1202105 (Assigned by Shenzhen BACL). The EUT was received on 2012-02-20.

Objective

This type approval report is prepared on behalf of *Shenzhen Crystal Video Technology Co.,LTD.* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and E of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

Related Submittal(s)/Grant(s)

No related submittal.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

FCC Part 15.407 Page 4 of 35

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Report No.: R1DG120210005-00

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at http://ts.nist.gov/Standards/scopes/2007070.htm

FCC Part 15.407 Page 5 of 35

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which is provided by manufacture.

Report No.: R1DG120210005-00

The operating frequency band is 5150-5250 MHz; the test frequency is 5190 MHz and 5230 MHz.


EUT Exercise Software

The test was performed under "AppCom_3.0.3.16".

Equipment Modifications

No modification was made to the unit tested.

Block Diagram of Test Setup



FCC Part 15.407 Page 6 of 35

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.407 (f), §2.1093, §1.1307(b)(1)	RF Exposure Evaluation	Compliance
§15.203	Antenna Requirement	Compliance
§15.407(b)(6)& §15.207(a)	Conducted Emissions	Compliance
§15.205& §15.209 &§15.407(b) (1),(6),(7)	Undesirable Emission& Restricted Bands	Compliance
§15.407(a) (1)	26 dB Bandwidth	Compliance
§15.407(a)(1),	Conducted Transmitter Output Power	Compliance
§15.407 (a)(1),(5)	Power Spectral Density	Compliance
§15.407(a)(6)	Peak Excursion Ratio	Compliance
§15.407(g)	Frequency Stability	Compliance

Report No.: R1DG120210005-00

FCC Part 15.407 Page 7 of 35

FCC §15.407 (f), §2.1093, §1.1307(b) (1) – RF EXPOSURE EVALUATION

Applicable Standard

According to subpart 15.247(i)and subpart §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Report No.: R1DG120210005-00

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure						
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)		
0.3–1.34	614	1.63	*(100)	30		
1.34–30	824/f	2.19/f	*(180/f²)	30		
30–300	27.5	0.073	0.2	30		
300–1500	/	/	f/1500	30		
1500-100,000	/	/	1.0	30		

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

 $S = PG/4\pi R^2 = power density (in appropriate units, e.g. mW/cm^2);$

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Frequency	Ante	Antenna Gain		ucted wer	Evaluation Distance	Power Density	MPE Limit
(MHz)	(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm^2)	(mW/cm ²)
5190	2.90	1.95	19.02	79.80	20	0.0309	1.0

Result: The device meet FCC MPE at 20 cm distance

FCC Part 15.407 Page 8 of 35

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

Report No.: R1DG120210005-00

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.407 (a), if the transmitting antennas of directional gain greater than 6dBi are used, the transmit power and power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has five printed antennas on the PCB, only one for transmitting, and the rest for receiving, which in accordance to section 15.203, the maximum gain is 2.9 dBi; please refer to the internal photos.

Result: Compliance.

FCC Part 15.407 Page 9 of 35

FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207, §15.407(b) (6)


Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Report No.: R1DG120210005-00

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratory Corp. (Shenzhen) is +2.4 dB.

EUT Setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

FCC Part 15.407 Page 10 of 35

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Report No.: R1DG120210005-00

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	830245	2011-05-03	2012-05-02
Rohde & Schwarz	L.I.S.N.	ESH2-Z5	892107/021	2011-11-17	2012-11-16

^{*}Statement of Traceability: Bay Area Compliance Laboratory Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

During the conducted emission test, the adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Part 15.207</u>, with the worst margin reading of:

11.15 dB at 0.780 MHz in the Neutral conducted mode

Test Data

Environmental Conditions


Temperature:	25 ° C
Relative Humidity:	48 %
ATM Pressure:	100.0 kPa

The testing was performed by Ares Liu on 2012-02-29.

Test Mode: Transmitting

FCC Part 15.407 Page 11 of 35

120 V, 60 Hz, Line:




Report No.: R1DG120210005-00

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/QP/Ave.)
0.170	45.90	1.10	65.43	19.53	QP
0.170	34.42	1.10	55.43	21.01	Ave.
0.230	39.84	1.10	63.71	23.87	QP
0.230	29.11	1.10	53.71	24.60	Ave.
0.780	38.12	1.10	56.00	17.88	QP
0.780	34.58	1.10	46.00	11.42	Ave.
3.190	29.94	1.10	56.00	26.06	QP
3.180	19.59	1.10	46.00	26.41	Ave.
11.420	29.10	1.10	60.00	30.90	QP
11.410	23.82	1.10	50.00	26.18	Ave.
0.310	36.77	1.10	61.43	24.66	QP
0.310	26.09	1.10	51.43	25.34	Ave.

FCC Part 15.407 Page 12 of 35

120V, 60 Hz, Neutral:



Report No.: R1DG120210005-00

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/QP/Ave.)
0.170	46.64	1.10	65.43	18.79	QP
0.170	34.06	1.10	55.43	21.37	Ave.
0.780	37.92	1.10	56.00	18.08	QP
0.780	34.85	1.10	46.00	11.15	Ave.
3.170	28.32	1.10	56.00	27.68	QP
3.160	19.81	1.10	46.00	26.19	Ave.
8.270	30.38	1.10	60.00	29.62	QP
8.250	24.84	1.10	50.00	25.16	Ave.
0.180	46.96	1.10	65.14	18.18	QP
0.180	34.16	1.10	55.14	20.98	Ave.
0.950	35.45	1.10	56.00	20.55	QP
0.950	30.27	1.10	46.00	15.73	Ave.

FCC Part 15.407 Page 13 of 35

FCC §15.209, §15.205 & §15.407(b) (1) (6) (7) – UNDESIRABLE EMISSION & RESTRICTED BANDS

Report No.: R1DG120210005-00

Applicable Standard

FCC §15.407 (b) (1), (6), (7); §15.209; §15.205;

For transmitters operating in the 5.15–5.25 GHz band: all emissions outside of the 5.15–5.35 GHz band shall not exceed an EIRP of –27 dBm/MHz.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209.


Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.


Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is $\pm 4.0 \text{ dB}$.

EUT Setup

Below 1GHz:



Above 1GHz:



FCC Part 15.407 Page 14 of 35

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source,

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	QP
1000 MHz – 40 GHz	1 MHz	3 MHz	PK
1000 MHz – 40 GHz	1 MHz	10 Hz	Ave.

Test Procedure

During the radiated emission test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz, peak and Average detection modes for frequencies above 1GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15.407 Page 15 of 35

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447D	2944A09795	2011-11-24	2012-11-23
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2011-11-17	2012-11-16
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2012-11-27
DUCOMMUN Technologies	Pre-amp	ALN- 09173030-01	991396-01	2011-11-24	2012-12-23
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-01	2012-11-30
HP	Spectrum Analyzer	8593A	2919A00242	2011-04-09	2012-04-08
Rohde & Schwarz	Signal Analyzer	FSIQ 26	8386001028	2011-11-24	2012-11-23

Report No.: R1DG120210005-00

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47, Part 15, Subpart C, Section 15.205, 15.209 and Subpart E, Section 15.407</u>, with the worst margin reading of:

3.02 dB at 10460 MHz in the Vertical polarization

Test Data

Environmental Conditions

Temperature:	25 ° C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Ares Liu on 2012-02-29.

FCC Part 15.407 Page 16 of 35

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Mode: Transmitting

30MHz~40GHz:

Frequency	Reading	Detector	Polar	Corrected	Correction	Limit	Margin	
(MHz)	(dBmV)	(PK/QP /Ave.)	(H/V)	Amplitude (dB/m)	Data (dBmV/m)	(dBmV/m)	(dB)	Comment
			L	ow Channel (5	5190MHz)			
35.69	36.21	QP	V	0.09	36.3	40	3.7*	spurious
33.42	45.52	QP	Н	-4.22	41.3	46	4.7	spurious
5150	25.05	PK	Н	29.03	54.08	68.3	14.22	restrict band
5150	18.36	AV	Н	29.03	47.39	54	6.61	restrict band
5150	26.25	PK	V	29.03	55.28	68.3	13.02	restrict band
5150	18.53	AV	V	29.03	47.56	54	6.44	restrict band
5190	85.32	PK	Н	29.03	114.35			Fundamental
5190	74.36	AV	Н	29.03	103.39			Fundamental
5190	87.63	PK	V	29.03	116.66			Fundamental
5190	78.96	AV	V	29.03	107.99			Fundamental
10380	35.26	PK	Н	27.48	62.74	68.3	5.56	harmanic
10380	36.85	PK	V	27.48	64.33	68.3	3.97*	harmanic
			Н	igh Channel (5230MHz)			
533.43	47.78	QP	V	-7.9	39.88	43.5	3.62*	spurious
535.21	41.59	QP	Н	-0.15	41.44	46	4.56	spurious
5230	82.54	PK	Н	29.03	111.57			Fundamental
5230	70.65	AV	Н	29.03	99.68			Fundamental
5230	83.54	PK	V	29.03	112.57			Fundamental
5230	71.26	AV	V	29.03	100.29			Fundamental
5350	24.16	PK	Н	29.18	53.34	68.3	14.96	restrict band
5350	18.01	AV	Н	29.18	47.19	54	6.81	restrict band
5350	25.64	PK	V	29.18	54.82	68.3	13.48	restrict band
5350	19.21	AV	V	29.18	48.39	54	5.61	restrict band
10460	34.48	PK	Н	28.45	62.93	68.3	5.37	harmanic
10460	35.82	PK	V	28.45	64.27	68.3	4.03	harmanic

Report No.: R1DG120210005-00

There is no noise above 18GHz

FCC Part 15.407 Page 17 of 35

^{*}Within measurement uncertainty!

Conducted Spurious Emission at Antenna Port


Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. The single test point connect to the spectrum analyzer. The Resolution bandwidth is set to 1MHz, The Video bandwidth is set to 1MHz, report the peak value out of the oprating band.

Report No.: R1DG120210005-00

3. Repeat above procedures until all frequencies measured were complete.

Offset value =attenuation+combiner loss +cable loss




Please refer to the following plots.


FCC Part 15.407 Page 18 of 35

5190 MHz Below 1G

Report No.: R1DG120210005-00




5190 MHz Above 1G




FCC Part 15.407 Page 19 of 35

5230 MHz Below 1G

Report No.: R1DG120210005-00



5230 MHz Above 1G



FCC Part 15.407 Page 20 of 35

FCC $\S15.407(a)$ (1) – 26 dB OCCUPIED BANDWIDTH

Applicable Standard

For the band 5.15–5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW or 4 dBm + 10 log B, where B is the 26–dB emission bandwidth in MHz. In addition, the peak power spectral density shall not exceed 4 dBm in any 1–MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Report No.: R1DG120210005-00


Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2011-07-08	2012-07-07

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Use a RBW = approximately 1% of the emission bandwidth. Set the VBW > RBW. Use a peak detector. Do not use the Max Hold function. Rather, use the viewbutton to capture the emission. Measure maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat, measurement as needed until the RBW/EBW ratio is approximately 1%.
- 4. Repeat above procedures until all frequencies measured were complete.



FCC Part 15.407 Page 21 of 35

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56%
ATM Pressure:	100.0kPa

The testing was performed by Ares Liu on 2012-03-07.

Test Result: Pass.

Please refer to the following tables and plots.


Channel Frequency (MHz)	26dB Bandwidth (MHz)
5190	38.87
5230	45.37

Report No.: R1DG120210005-00


FCC Part 15.407 Page 22 of 35

26 dB Bandwidth-5190 MHz

Report No.: R1DG120210005-00



26 dB Bandwidth-5230 MHz



FCC Part 15.407 Page 23 of 35

FCC §15.407(a) (1) - CONDUCTED TRANSMITTER OUTPUT POWER

Report No.: R1DG120210005-00

Applicable Standard

For the band 5.15–5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW or 4 dBm + 10 log B, where B is the 26–dB emission bandwidth in MHz. In addition, the peak power spectral density shall not exceed 4 dBm in any 1–MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2011-07-08	2012-07-07

^{*} Statement of Traceability: Bay Area Compliance Lab Corp. (ShenZhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set span = 80MHz (to encompass the entire emission bandwidth (EBW) of the signal). Set RBW = 1 MHz.Set VBW ≥ 3 MHz. Use sample detector mode Use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at full control power for entire sweep of every sweep. If the device transmits continuously, with no off intervals or reduced power intervals, the trigger may be set to "free run". Trace average 100 traces in power averaging mode. Compute power by integrating the spectrum across the 26 dB EBW of the signal. The integration can be performed using the spectrum analyzer's band power measurement function with band limits set equal to the EBW band edges or by summing power levels in each 1 MHz band in linear power terms. The 1 MHz band power levels to be summed can be obtained by averaging, in linear power terms, power levels in each frequency bin across the 1 MHz.
- 4. Repeat above procedures until all frequencies measured were complete.

FCC Part 15.407 Page 24 of 35

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56%
ATM Pressure:	100.0kPa

The testing was performed by Ares Liu on 2012-03-07.

Test Mode: Transmitting

Test Result: Pass

Please refer to the following tables and plots.


Channel Frequency (MHz)	Output Power (dBm)	Limit (dBm)
5190	15.41	17
5230	15.04	17

Report No.: R1DG120210005-00


FCC Part 15.407 Page 25 of 35

Output Power-5190 MHz

Report No.: R1DG120210005-00



Output Power-5230 MHz



FCC Part 15.407 Page 26 of 35

FCC §15.407(a) (1) (5) - POWER SPECTRAL DENSITY

Applicable Standard

For the band 5.15–5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW or 4 dBm + 10 log B, where B is the 26–dB emission bandwidth in MHz. In addition, the peak power spectral density shall not exceed 4 dBm in any 1–MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Report No.: R1DG120210005-00

The peak power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A resolution bandwidth less than the measurement bandwidth can be used, provided that the measured power is integrated to show total power over the measurement bandwidth. If the resolution bandwidth is approximately equal to the measurement bandwidth, and much less than the emission bandwidth of the equipment under test, the measured results shall be corrected to account for any difference between the resolution bandwidth of the test instrument and its actual noise bandwidth.

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Position the EUT was set without connection to measurement instrument. Turn on the EUT and
 connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one
 measured frequency within its operating range, and make sure the instrument is operated in its linear
 range.
- 3. Use sample detector and power averaging (not video averaging) mode. Set RBW= 1 MHz*, VBW > 1 MHz. The PPSD is the highest level found across the emission in any 1-MHz band after 100 sweeps of averaging. This method is permitted only if the transmission pulse or sequence of pulses remains at maximum transmits power throughout each of the 100 sweeps of averaging and that the interval between pulses is not included in any of the sweeps.
- 4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2011-07-08	2012-07-07

^{*} Statement of Traceability: Bay Area Compliance Lab Corp. (ShenZhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

FCC Part 15.407 Page 27 of 35

Test Data

Environmental Conditions

Temperature:	25 ° C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Ares Liu on 2012-03-07.

Test Mode: Transmitting

Test Result: Pass


Channel Frequency (MHz)	Power Spectral Density (dBm/MHz)	Limit (dBm/MHz)
5190	2.86	4
5230	3.53	4

Report No.: R1DG120210005-00

FCC Part 15.407 Page 28 of 35

Power Spectral Density-5190 MHz

Report No.: R1DG120210005-00



Power Spectral Density -5230 MHz



FCC Part 15.407 Page 29 of 35

FCC §15.407(a) (6) – PEAK EXCURSION RATIO

Applicable Standard

According to §15.407(a) (6), the ratio of the peak excursion of the modulation envelope (measured using a peak hold function) to the maximum conducted output power (measured as specified above) shall not exceed 13 dB across any 1 MHz bandwidth or the emission bandwidth whichever is less.

Report No.: R1DG120210005-00

Test Procedure

Set the spectrum analyzer span to view the entire emission bandwidth.

The largest difference between the following two traces must be ≤ 13 dB for all frequencies across the emission bandwidth. Submit a plot.

1st Trace:

• Set RBW = 1 MHz, VBW \geq 3 MHz with peak detector and maxhold settings.

2nd Trace:

 \bullet create the 2nd trace using the settings described in the setion "FCC §15.407(a)(1)(2) – CONDUCTED TRANSMITTER OUTPUT POWER".

EUT Spectrum Analyzer

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2011-07-08	2012-07-07

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 ° C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Ares Liu on 2012-03-07.

Test Mode: Transmitting


FCC Part 15.407 Page 30 of 35

Channel Frequency (MHz)	Peak Excursion Ratio (dB)	Limit (dB)
5190	1.08	13
5230	0.78	13


FCC Part 15.407 Page 31 of 35

Peak Excursion Radio-5190 MHz

Report No.: R1DG120210005-00



Peak Excursion Radio-5230 MHz



FCC Part 15.407 Page 32 of 35

FCC §407(g) - FREQUENCY STABILITY

Applicable Standards

FCC§407(g), manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.


Report No.: R1DG120210005-00

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external AC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The AC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: An external variable AC power supply was connected to the adaptor terminals of the equipment under test. The voltage was set to 80% and 115% of the nominal value and was then decreased until the transmitter light no longer illuminated. The output frequency was recorded for each voltage.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
WUHUAN	Temperature & Humidity Chamber	HTP205	20021115	2011-06-04	2012-06-03
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2011-07-08	2012-07-07

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

FCC Part 15.407 Page 33 of 35

Test Data

Environmental Conditions

Temperature:	25 ° C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Ares Liu on 2012-02-21.

Test Mode: Transmitting

Channel Frequency (MHz)	Power supply (V _{AC})	Temperature (°C)	Measurement Frequency (MHz)
5190	120	-30	5190.014
		-20	5190.011
		-10	5190.010
		+0	5190.011
		+10	5190.016
		+20	5190.018
		+30	5190.021
		+40	5190.024
		+50	5190.021
	138	+20	5190.017
	102	+20	5190.019

Report No.: R1DG120210005-00

FCC Part 15.407 Page 34 of 35

DECLARATION LETTER



Shenzhen Crystal Video Technology Co., LTD F13, F518 Idea Land, Baoyuan Road, Baoan Central Area, Shenzhen, China Tel: 0755-26716030, Fax: 0755-23496331

Product Similarity Declaration

Report No.: R1DG120210005-00

To Whom It May Concern,

We, Shenzhen Crystal Video Technology Co., LTD, hereby declare that our product wireless high-definition receiver, Model Number: CB6620、CV6620、CV6620-IL、 CB6620-IL, CB6628, 5002R, 5003R are electrically identical with the Model Number: CB6620 that was certified by BACL. Their only difference is model name.

The rest are the same.

Please contact me if you have any question.

Signature:

Date:2012-02-10

Xiaojun / Quality Manager 2012 03.10

Xiowjun

***** END OF REPORT *****

FCC Part 15.407 Page 35 of 35