

Report: EMC_SL16122101-SPC-006_FCC

EMC TEST REPORT

Report: EMC_SL16122101-SPC-006_FCC

Supersedes: None

Applicant Name:			Spi	derCloud Wireless
Pı	roduct Name:		Spide	erCloud Radio Node
N	Model Name:		SCRN-320-0	0446 and SCRN320-0446E
To	est Standard:	FCC 15 Subpart B (Class A)		
1	Test Method:		A	NSI C63.4: 2014
Date of Test:			Jan 2	6 th to Feb 6 th - 2017
Report Issue Date:		2/15/2017		
Test Result: Equipment complied w Equipment did not com This test report is issued	ith the specifications:			
	and of the datherny on			
Mush Kumuy			A	lik sales
Full Name:	Anish Kumar		Full Name:	Michael R. Gates
Title: Compliance Test Engineer			Title:	Quality Engineer

This test report may be reproduced in full only.

Test result presented in this test report is applicable to the tested sample only.

ISSUED BY:

SIEMIC Laboratories
775 Montague Expressway, Milpitas, CA 95035 USA





Report: EMC_SL16122101-SPC-006_FCC

Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for conformity assessment

Country/Region	Accreditation Body	Scope
USA	FCC, A2LA	EMC, RF/Wireless, Telecom
Canada	IC, A2LA, NIST	EMC, RF/Wireless, Telecom
Taiwan	BSMI, NCC, NIST	EMC, RF, Telecom, Safety
Hong Kong	OFTA, NIST	RF/Wireless, Telecom
Australia	NATA, NIST	EMC, RF, Telecom, Safety
Korea	KCC/RRA, NIST	EMI, EMS, RF, Telecom, Safety
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom
Mexico	NOM, COFETEL, Caniety	Safety, EMC, RF/Wireless, Telecom
Europe	A2LA, NIST	EMC, RF, Telecom, Safety
Israel	MOC, NIST	EMC, RF, Telecom, Safety

Accreditations for conformity assessment

Country/Region	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC, RF, Telecom
Canada	IC FCB, NIST	EMC, RF, Telecom
Singapore	iDA, NIST	EMC, RF, Telecom
EU	NB	EMC & R&TTE Directive
Japan	MIC (RCB 208)	RF, Telecom
Hong Kong	OFTA (US002)	RF, Telecom



Report: EMC_SL16122101-SPC-006_FCC

Table of Contents

1. Report revision history	
2. Executive summary	
3. Customer information	
4. Test site information	
5. Modification	
6. Test software version	
7. EUT Information	
7.1. EUT Description	
7.2. EUT Test modes / Configuration description	
7.2.1. EUT Test modes: Pre-test mode	
7.2.2. EUT Test modes: Final test mode	
7.3. EUT Photos External	
7.4. EUT Photos Internal	
7.5. EUT Photos Test setup	12
8. Supporting equipment / Software / Cabling information	14
8.1. Support equipment	14
8.2. I/O Ports	15
8.3. Test software description	16
8.4. System setup block diagram	17
9. Test summary	18
10. Measurement uncertainty	18
11. Frequency Range of Radiated Measurements	19
12. Guideline for interference allowed	20
12.1. AC Conducted emissions (Class A)	20
12.2. Radiated Spurious Emissions Below 1GHz (Class A)	30
13. Annex A Test instruments and method	45
14. Annex B SIEMIC Accreditation	46



Report: EMC_SL16122101-SPC-006_FCC

1. Report revision history

Report No.	Version No.	Description	Issue Date
EMC_SL16122101-SPC-006_FCC	Original Report	FCC 15 Subpart B (Class A)	2/15/2017

2. Executive summary

The purpose of this test program was to demonstrate compliance of following product:

Company: SpiderCloud Wireless
Product: SpiderCloud Radio Node

Model: SCRN-320-0446 and SCRN 320-0446E

against the current Stipulated Standards. The specified model product stated above has demonstrated compliance with the Stipulated Standard listed on 1st page.

3. Customer information

Applicant Name:	Spider Cloud Wireless
Applicant Address:	475 Sycamore Drive, Milpitas, CA 95035 US
Manufacturer Name:	Flextronics International USA, Inc
Manufacturer Address:	927 Gibaraltar Dr., Bldg. 6, Milpitas, CA95035 US

4. Test site information

Lab Performing Tests:		SIEMIC Laboratories
Lab Address:		775 Montague Expressway, Milpitas, CA 95035
FCC Test Site No:		881796
IC Test Site No:		4842D-2



Report: EMC_SL16122101-SPC-006_FCC

5. Modification

Item	Description	Note
1	External Antenna- LTE_B4_B252	Larsen Antennas
2	External Antenna- LTE_BR_B255	Larsen Antennas
3	Internal Antenna- LTE_B4_B252	SpiderCloud Antenna
4	Internal Antenna- LTE_B4_B255	SpiderCloud Antenna

6. Test software version

Test Item	Vendor	Software	Version
Radiated Emission	EMISoft	EMISoft Vasona	V6.0
Conducted Emission	EMISoft	EMISoft Vasona	V5.0



Report: EMC_SL16122101-SPC-006_FCC

7. EUT Information 7.1. EUT Description

Product Name:	SpiderCloud Radio Node	
Model No.:	SCRN-320-0446 and SCRN 320-0446E	
Trade Name:	SpiderCloud Wireless	
Serial No.:	16298X25439	
Input Power:	56V, .6 A	
PoE Input Voltage	100-240V~1.0A	
Power Adapter Manu/Model:	PoE P832000567A1/ Phihong Switching Power Supply	
Hardware version:	02650-06-001	
Software version:	6.1.0	
Date of EUT received:	Jan 25th, 2017	
Equipment Class/ Category:	Class A/ ITE	
Highest frequency generated or used in the device or on which the device operates or tunes:	5.8GHz	
Port/Connectors:	RJ45	
Remark:	The EUT was powered by PoE which was connected to the input port of the PoE port and the other port PoE's was connected to the laptop which was used to make the EUT function as well as to change the modes. The PoE comes along the EUT	
AC Power Cord Type:	IEC Type B (PoE)	
DC Power Cable Type:	N/A	



Report: EMC_SL16122101-SPC-006_FCC

7.2. EUT Test modes / Configuration description 7.2.1.EUT Test modes: Pre-test mode

Pre-Sca	n Test Mode	Notes
Pre-test Mode 1	LTE B4 B255	Both External and Internal antennas were tested with this configuration The operating frequencies are:
		2100MHz and 5GHz
Pre-test Mode 2	LTE_B4_B252	Both External and Internal antennas were tested with this configuration The operating frequencies are: 2100MHz and 5GHz
Remark:	The above mentioned operating frequencies were tested all together.	

7.2.2.EUT Test modes: Final test mode

Final	Test Mode	Notes
Pre-test Mode 1	LTE_B4_B255	Both External and Internal antennas were tested with this configuration The operating frequencies are: 2100MHz and 5GHz
Pre-test Mode 2	LTE_B4_B255	Both External and Internal antennas were tested with this configuration The operating frequencies are: 2100MHz and 5GHz
Remark:	The above mentioned operating frequencies were tested all together.	



Report: EMC_SL16122101-SPC-006_FCC

7.3. EUT Photos | External



Picture 1: Top View- External Antenna



Picture 3: Left View- External Antenna



Picture 5: Right View- External Antenna



Picture 2: Front View- External Antenna



Picture 4: Rear View- External Antenna



Picture 6: Back View- External Antenna






Picture 1: Front View- Internal Antenna



Picture 2: Top View- Internal Antenna



Picture 3: Right View- Internal Antenna



Picture 4: Rear View- Internal Antenna



Picture 5: Left View- Internal Antenna




Picture 6: Back View- Internal Antenna



Report: EMC_SL16122101-SPC-006_FCC

7.4. EUT Photos | Internal



Picture 1: Main Board- Back View



Picture 3: Main Board- Front View



Picture 5: Main Board- Rear View



Picture 2: Main Board- Top View




Picture 4: Main Board- Left View



Picture 6: Main Board- Right View







Picture 7: 5GHz PCB Board- Front View




Picture 7: Serail Number of the 5GHz PCB Board



Picture 7: 2.4GHz PCB Board- Rear View



Picture 8: 5GHz PCB Board- Rear View



Picture 7: 2.4GHz PCB Board- Front View



Picture 8: Serial Number of 2.4GHz PCB Board




Report: EMC_SL16122101-SPC-006_FCC

7.5. EUT Photos | Test setup



Picture 1: AC Conducted Emissions- Front View




Picture 3: Radiated Emissions B 1GHz - Front View



Picture 5: Radiated Emissions 1-18GHz- Front View



Picture 2: AC Conducted Emissions- Rear View




Picture 4: Radiated Emissions B 1GHz- Rear View




Picture 6: Radiated Emissions 1-18GHz- Rear View





Picture 7: Radiated Emissions 18-29GHz- Front View



Picture 8: Radiated Emissions 18-29GHz- Rear View



Report: EMC_SL16122101-SPC-006_FCC

8. Supporting equipment / Software / Cabling information

8.1. Support equipment

Item	Supporting Equipment Description	ent Model Serial Number		Manufacturer	Note
1	Laptop	Latitute E6400	CBMXRK1	Dell	N/A
2	PoE	POE36U-1AT-R	N/A	Phihong	N/A
3	AC/DC power Adapter	PA-1900-02D	9T215	Dell	N/A
4	10MHz signal reference source	DSA-12R-12 AUS 120120	332-10006-01	NetGear	Provide power to 10MHz signal source



Report: EMC_SL16122101-SPC-006_FCC

8.2. I/O Ports

Item	Connection Start			Connection Stop		Length / shielding Info		
	From	I/O Port	То	I/O Port	Length (m)	Shielding	Note	
1	Laptop	RJ45	PoE	RJ45 (Output Port)	3.5m	Unshielded	-	
2	EUT	RJ45	PoE	RJ45 (Input Port)	4.3m	Unshielded	-	
3	10MHz reference Source	SMA male	EUT (Antenna Port)	SMA female	2m	Unshielded	Connected to the 10MHz reference port of the EUT	





Report: EMC_SL16122101-SPC-006_FCC

8.3. Test software description


Test Item	Software	Description
1	Small Cell DVT test Client	This is laptop software used for configuring the EUT.





Report: EMC_SL16122101-SPC-006_FCC

8.4. System setup block diagram





Report: EMC_SL16122101-SPC-006_FCC

9. Test summary

Emissions							
Test Item	Test Standard	Test Method / Procedure	Pass / Fail				
AC Conducted Emissions	FCC 15 Subpart B (Class A)	ANSI C63.4:2014	X Pass Fail N/A				
Radiated Spurious Emissions Below 1GHz	FCC 15 Subpart B (Class A)	ANSI C63.4:2014	X Pass Fail N/A				
Radiated Spurious Emissions Above 1GHz	FCC 15 Subpart B (Class A)	ANSI C63.4:2014	X Pass Fail N/A				

10. Measurement uncertainty

	Emissions						
Test Item	Test Item Frequency Range Description						
AC Conducted Emissions	150KHz – 30MHz	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2	±3.5dB				
Radiated Spurious Emissions	30MHz – 1GHz	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/- 4.5dB				
Radiated Spurious Emissions	>1GHz	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+4.3dB/- 4.1dB				



Report: EMC_SL16122101-SPC-006_FCC

11. Frequency Range of Radiated Measurements

(b) For unintentional radiators:

- (1) Except as otherwise indicated in paragraphs (b)(2) or (b)(3) of this section, for an unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a radiated emission limit is specified, up to the frequency shown in the following table:
- (2) A unintentional radiator, excluding a digital device, in which the highest frequency generated in the device, the highest frequency used in

highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)				
Below 1.705	30.				
1.705-108	1000.				
108-500	2000.				
500-1000	5000.				
Above 1000	5th harmonic of the highest frequency or 40 GHz,				
	whichever is lower.				

the device and the highest frequency on which the device operates or tunes are less than 30 MHz and which, in accordance with §15.109, is required to comply with standards on the level of radiated emissions within the frequency range 9 kHz to 30 MHz, such as a CB receiver or a device designed to conduct its radio frequency emissions via connecting wires or cables, e.g., a carrier current system not intended to radiate, shall be investigated from the lowest radio frequency generated or used in the device, without going below 9 kHz (25 MHz for CB receivers), up to the frequency shown in the following table. If the unintentional radiator contains a digital device, the upper frequency to be investigated shall be that shown in the table below or in the table in paragraph (b)(1) of this section, as based on both the highest frequency generated and the highest frequency used in the digital device, whichever range is higher.

Highest frequency generated or used in the device tunes (MHz)	Upper frequency of measurement range (MHz)	
Below 1.705		30
1.705-10		400
10-30		500

⁽³⁾ Except for a CB receiver, a receiver employing superheterodyne techniques shall be investigated from 30 MHz up to at least the second harmonic of the highest local oscillator frequency generated in the device. If such receiver is controlled by a digital device, the frequency range shall be investigated up to the higher of the second harmonic of the highest local oscillator frequency generated in the device or the upper frequency of the measurement range specified for the digital device in paragraph (b)(1) of this section.

Example:

If the EUT has a transceiver operating or tunes at 2.4GHz, then both the Receiver, and the Transmitter needs to be tested separately to the Fifth Harmonic (e.g. Upper Frequency range would be 12GHz). A Transceiver consists of both a transmitter and a receiver, the receiver portion of which is always subject to the part 15 Subpart B Unintentional Radiator rules.



Report: EMC_SL16122101-SPC-006_FCC

12. Guideline for interference allowed

12.1. AC Conducted emissions (Class A)

Spec	Item	Requirement				Applicable	
	a)	radio frequency voltage the frequencies within the band 15 n	t is designed to be connected to at is conducted back onto the AC 0 kHz to 30 MHz shall not exceen neasured using a 50 µH/50 ohms Conducted Emissions at the A	power line on any the the limits set in factorial the limits set in factorial to the limits set in factorial the l	frequency or	Yes	
§ 15.107			Frequency ranges	Limit	(dBuV)		
3 10.101		Section	(MHz)	QP	Average		
		Class A devices	0.15 ~ 0.5	79	66		
			0.5 ~ 30 pply at the transition frequencies	73	60		
		NOTE I THE lower littlit stidil a	ppry at the transition frequencies				
Test Setup		2. Both and c	of LISNs (AMN) are 80 cm from EUT and at other metal planes	least 80 cm from other			
Procedure	2. Th 3. Th 4. All 5. Th 6. As tes 7. Hi 8. Th ba Qu 9. All	x 0.8m high, non-metallic table. The power supply for the EUT was fed through a 50\[/]50\[]H EUT LISN, connected to filtered mains. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable. All other supporting equipment was powered separately from another main supply. The EUT was switched on and allowed to warm up to its normal operating condition. A scan was made on the Neutral/Phase line (for AC mains) or Earth line over the required frequency range using test receiver. High peaks, relative to the limit line, were then selected. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a bandwidth setting of 10 kHz. For FCC tests, only Quasi-peak measurements were made; while for CISPR/EN test Quasi-peak and Average measurements were made					



Report: EMC_SL16122101-SPC-006_FCC

Description of the Conducted Emission Program	This EMC Measurement software, EMI Soft Vasona offers a common user interface for electromagnetic interference (EMI) measurements. This software is a modern and powerful tool for controlling and monitoring EMI test receivers and EMC test systems. It guarantees reliable collection, evaluation, and documentation of measurement results. Basically, this program will run a pre-scan measurement before it proceeds with the final measurement. The pre-scan routine will run the common scan range from 15 kHz to 30 MHz; the program will first start a peak and average scan on selectable measurement time and step size. After the program complete the pre-scan, this program will perform the Quasi Peak and Average measurement, based on the pre-scan peak data reduction result.
Sample Calculation Example	At 20 MHz
Remarks	Configurations tested are LTE_B4_B255 and LTE_B4_B252. The operating frequencies are: 2100MHz and 5GHz. Both the frequencies were operated at the same time.

Test Data: X Yes N/A


Test Plot: X Yes (See below) N/A



Report: EMC_SL16122101-SPC-006_FCC

Conducted Emission Test Results per FCC 15 Subpart B (Class A)

Temp(°C): 25.0 X Pass	Test specification:	AC Condu	cted Emissions (Class A	ı)			
Atmospheric(mbar): 1016.7 Mains Power: 120Vac, 60Hz Tested by: Anish Kumar Test Date: 25th Jan, 2017 Remarks: Neutral Line- Internal Antenna-LTE_B4_B255 Mode. The operating frequencies are: 2100MHz and		Temp(°C): 25.0					
Mains Power: Tested by: Anish Kumar Fail Test Date: Semarks: Neutral Line- Internal Antenna-LTE_B4_ B255 Mode. The operating frequencies are: 2100MHz and	Environmental Conditions:	Humidity (%):	53.17		X Pass		
Tested by: Anish Kumar Fail Test Date: 25th Jan, 2017 Neutral Line- Internal Antenna-LTE_B4_ B255 Mode. The operating frequencies are: 2100MHz and		Atmospheric(mbar):	1016.7	Result:			
Test Date: 25th Jan, 2017 Neutral Line- Internal Antenna-LTE_B4_ B255 Mode. The operating frequencies are: 2100MHz and	Mains Power:	120Vac, 60Hz					
Remarks: Neutral Line- Internal Antenna-LTE_B4_ B255 Mode. The operating frequencies are: 2100MHz and	Tested by:	Anish Kumar	-	Fail			
	Test Date:	25 th Jan, 2017					
	Remarks:	Neutral Line- Internal Antenna-LTE_B4_ B255 Mode. The operating frequencies are: 2100MHz and 5GHz. Both the frequencies were operated at the same time.					




Tower Bile Conducted Billipsions	remplate. Ac cond Emis-clas
Filename: o:\program files\emisoft - vasona\resu	ts\SPC-006-Band 4- NII-1-Neutral.emi

Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	Factors (dB)	Level (dBuV)	Measurement Type	Line/ Neutral	Limit (dBuV)	Margin (dB)	Pass /Fail
0.15	42.18	10.00	1.74	53.93	Quasi Peak	Neutral	79.00	-25.07	Pass
12.43	37.17	10.05	0.54	47.76	Quasi Peak	Neutral	73.00	-25.24	Pass
11.75	33.65	10.05	0.53	44.23	Quasi Peak	Neutral	73.00	-28.77	Pass
13.11	26.95	10.06	0.54	37.55	Quasi Peak	Neutral	73.00	-35.45	Pass
11.07	25.39	10.05	0.52	35.96	Quasi Peak	Neutral	73.00	-37.04	Pass
9.69	29.23	10.05	0.51	39.79	Quasi Peak	Neutral	73.00	-33.21	Pass
0.15	22.65	10.00	1.74	34.40	Average	Neutral	66.00	-31.60	Pass
12.43	27.22	10.05	0.54	37.81	Average	Neutral	60.00	-22.19	Pass
11.75	18.63	10.05	0.53	29.21	Average	Neutral	60.00	-30.79	Pass
13.11	18.69	10.06	0.54	29.29	Average	Neutral	60.00	-30.71	Pass
11.07	17.39	10.05	0.52	27.97	Average	Neutral	60.00	-32.03	Pass
9.69	25.09	10.05	0.51	35.65	Average	Neutral	60.00	-24.35	Pass



Test specification:	AC Condu	cted Emissions (Class B)				
	Temp(°C):	25.0					
Environmental Conditions:	Humidity (%):	53.17		X Pass			
	Atmospheric(mbar):	1016.7	Result:				
Mains Power:	120Vac, 60Hz						
Tested by:	Anish Kumar			Fail			
Test Date:	25th Jan, 2017	25th Jan, 2017					
Remarks:	Phase Line. Internal Antenna-LTE_B4_B255 the frequencies were operated at the same ti		s are: 2100MHz a	nd 5GHz. Both			



Filename: o:\program	m files\emisoft - vasona	avresults\SPC-006-Band 4- NII-1-	· Live.emi
Frequency	Raw	Cable Loss	Facto

Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	Factors (dB)	Level (dBuV)	Measurement Type	Line/ Neutral	Limit (dBuV)	Margin (dB)	Pass /Fail
11.80	38.92	10.05	0.53	49.51	Quasi Peak	Live	73.00	-23.49	Pass
0.20	44.03	10.00	1.25	55.28	Quasi Peak	Live	79.00	-23.72	Pass
11.13	38.65	10.05	0.52	49.22	Quasi Peak	Live	73.00	-23.78	Pass
12.49	38.36	10.05	0.54	48.95	Quasi Peak	Live	73.00	-24.05	Pass
10.45	38.32	10.05	0.52	48.89	Quasi Peak	Live	73.00	-24.11	Pass
13.17	37.01	10.06	0.54	47.61	Quasi Peak	Live	73.00	-25.39	Pass
11.80	36.44	10.05	0.53	47.03	Average	Live	60.00	-12.97	Pass
0.20	37.37	10.00	1.25	48.62	Average	Live	66.00	-17.38	Pass
11.13	36.56	10.05	0.52	47.13	Average	Live	60.00	-12.87	Pass
12.49	35.06	10.05	0.54	45.65	Average	Live	60.00	-14.35	Pass
10.45	36.85	10.05	0.52	47.42	Average	Live	60.00	-12.58	Pass
13.17	25.19	10.06	0.54	35.79	Average	Live	60.00	-24.21	Pass




Filename: o:\program files\emisoft - vasona\results\SPC-006-Band 4-NII-3- Neutral.emi

Applicant: SpiderCloud Wireless

Report: EMC_SL16122101-SPC-006_FCC


Test specification:	AC Cond	AC Conducted Emissions (Class A)								
	Temp(°C):	25.0								
Environmental Conditions:	Humidity (%):	53.17		X Pass						
	Atmospheric(mbar):	Result:								
Mains Power:	120Vac, 60Hz	120Vac, 60Hz								
Tested by:	Anish Kumar			Fail						
Test Date:	25 th Jan, 2017	25 th Jan, 2017								
Remarks:	Neutral Line- Internal Antenna- LTE_B4_B2	Neutral Line- Internal Antenna- LTE_B4_B252. The operating frequencies are: 2100MHz and 5GHz. Bot								
	the frequencies were operated at the same	time								



Frequency Cable Loss **Factors** Level Measurement Line/ Limit Margin **Pass** Raw (dBuV) (MHz) (dBuV) (dB) (dB) (dBuV) Type Neutral (dB) /Fail 0.19 10.00 79.00 40.83 1.31 52.14 Quasi Peak Neutral -26.86 Pass 49.27 Quasi Peak 73.00 -23.73 12.52 38.68 10.05 0.54 Pass Neutral 11.84 38.41 10.05 0.53 49.00 Quasi Peak 73.00 -24.00 Neutral **Pass** 73.00 13.21 38.16 10.06 0.54 48.76 Quasi Peak -24.24 Pass Neutral 49.10 -23.90 11.16 38.52 10.05 0.52 Quasi Peak 73.00 Neutral **Pass** 46.99 Pass 9.11 36.43 10.05 0.51 Quasi Peak 73.00 -26.01 Neutral 0.19 37.55 10.00 1.31 48.86 66.00 -17.14 Pass Average Neutral 12.52 35.74 10.05 0.54 46.34 60.00 -13.66 Pass Average Neutral -13.43 11.84 35.99 10.05 0.53 46.57 60.00 Pass Average Neutral 13.21 36.03 10.06 0.54 46.63 Average Neutral 60.00 -13.37 Pass 11.16 37.19 10.05 0.52 47.76 60.00 -12.24 Average Neutral **Pass** 32.77 10.05 43.33 Pass 9.11 0.51 60.00 -16.67 Average Neutral



Test specification:	AC Conduc	ted Emissions (Class B)			
	Temp(°C):	25.0				
Environmental Conditions:	Humidity (%):	53.17		X Pass		
	Atmospheric(mbar):	1016.7	Result:			
Mains Power:	120Vac, 60Hz	120Vac, 60Hz				
Tested by:	Anish Kumar			Fail		
Test Date:	25th Jan, 2017	25th Jan, 2017				
Remarks:	Phase Line. Internal Antenna-LTE_B4_ B252		es are: 2100MHz	and 5GHz. Both		
	the frequencies were operated at the same time	ne.				




Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	Factors (dB)	Level (dBuV)	Measurement Type	Line/ Neutral	Limit (dBuV)	Margin (dB)	Pass /Fail
0.20	41.89	10.00	1.23	53.12	Quasi Peak	Live	79.00	-25.88	Pass
11.85	39.15	10.05	0.53	49.74	Quasi Peak	Live	73.00	-23.26	Pass
12.54	38.81	10.05	0.54	49.41	Quasi Peak	Live	73.00	-23.59	Pass
13.22	38.35	10.06	0.54	48.95	Quasi Peak	Live	73.00	-24.05	Pass
11.17	38.84	10.05	0.52	49.41	Quasi Peak	Live	73.00	-23.59	Pass
10.48	37.35	10.05	0.52	47.92	Quasi Peak	Live	73.00	-25.08	Pass
0.20	30.77	10.00	1.23	42.01	Average	Live	66.00	-23.99	Pass
11.85	37.17	10.05	0.53	47.75	Average	Live	60.00	-12.25	Pass
12.54	36.99	10.05	0.54	47.59	Average	Live	60.00	-12.41	Pass
13.22	35.99	10.06	0.54	46.59	Average	Live	60.00	-13.41	Pass
11.17	37.10	10.05	0.52	47.67	Average	Live	60.00	-12.33	Pass
10.48	31.78	10.05	0.52	42.34	Average	Live	60.00	-17.66	Pass



Report: EMC_SL16122101-SPC-006_FCC

Test specification:	AC Cond	AC Conducted Emissions (Class B)								
	Temp(°C):	25.0								
Environmental Conditions:	Humidity (%):	53.17		X Pass						
	Atmospheric(mbar):	1016.7	Result:							
Mains Power:	120Vac, 60Hz									
Tested by:	Anish Kumar			Fail						
Test Date:	25th Jan, 2017	25th Jan, 2017								
Remarks:	Neutral Line. External Antenna-LTE_B4_ B	255. The operating frequ	encies are: 2100MHz	and 5GHz.						
	Both the frequencies were operated at the s	same time								



Filename: o:\program files\emisoft - vasona\results\SPC-006-FCC-EA-Neutral.emi

Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	Factors (dB)	Level (dBuV)	Measurement Type	Line/ Neutral	Limit (dBuV)	Margin (dB)	Pass /Fail
13.14	43.84	10.06	0.54	54.44	Quasi Peak	Neutral	73.00	-18.56	Pass
12.91	33.14	10.06	0.54	43.74	Quasi Peak	Neutral	73.00	-29.26	Pass
12.42	35.15	10.05	0.54	45.74	Quasi Peak	Neutral	73.00	-27.26	Pass
13.79	36.52	10.06	0.55	47.13	Quasi Peak	Neutral	73.00	-25.87	Pass
13.57	36.45	10.06	0.55	47.05	Quasi Peak	Neutral	73.00	-25.95	Pass
14.48	35.43	10.06	0.56	46.05	Quasi Peak	Neutral	73.00	-26.95	Pass
13.14	36.05	10.06	0.54	46.65	Average	Neutral	60.00	-13.35	Pass
12.91	24.46	10.06	0.54	35.06	Average	Neutral	60.00	-24.94	Pass
12.42	32.81	10.05	0.54	43.4	Average	Neutral	60.00	-16.60	Pass
13.79	32.46	10.06	0.55	43.07	Average	Neutral	60.00	-16.93	Pass
13.57	32.24	10.06	0.55	42.84	Average	Neutral	60.00	-17.16	Pass
14.48	29.58	10.06	0.56	40.19	Average	Neutral	60.00	-19.81	Pass




Filename: c:\program files\emisoft - vasona\results\SPC-006-FCC-EA-Live.emi

Applicant: SpiderCloud Wireless

Report: EMC_SL16122101-SPC-006_FCC


Test specification:	AC Cond	AC Conducted Emissions (Class B)								
	Temp(°C):	25.0								
Environmental Conditions:	Humidity (%):	53.17		X Pass						
	Atmospheric(mbar):	1016.70	Result:							
Mains Power:	120Vac, 60Hz									
Tested by:	Anish Kumar			Fail						
Test Date:	25th Jan, 2017	25th Jan, 2017								
Remarks:	Phase Line. External Antenna- LTE_B4_B2	55. The operating frequen	cies are: 2100MHz	and 5GHz. Both						
	the frequencies were enerated at the same	timo								



Frequency Cable Loss **Factors** Level Measurement Line/ Limit Margin **Pass** Raw (dBuV) (MHz) (dBuV) (dB) (dB) (dBuV) Type Neutral (dB) /Fail 12.51 10.05 73.00 -16.38 46.03 0.54 56.62 Quasi Peak Live Pass 46.18 Quasi Peak 73.00 -16.22 13.19 10.06 0.54 56.78 Live Pass 12.97 45.68 10.06 0.54 56.28 Quasi Peak Live 73.00 -16.72 **Pass** 73.00 13.65 44.33 10.06 0.55 54.94 Quasi Peak Live -18.06 Pass 45.82 56.43 Quasi Peak 13.89 10.06 0.55 Live 73.00 -16.57 Pass 73.00 Pass 12.29 44.33 10.05 0.54 54.92 Quasi Peak Live -18.08 12.51 42.96 10.05 0.54 53.56 Live 60.00 -6.44 Pass Average 13.19 43.47 10.06 0.54 54.07 Live 60.00 -5.93 Pass Average 12.97 43.84 10.06 0.54 54.43 Live 60.00 -5.57 Pass Average 13.65 41.45 10.06 0.55 52.06 Average Live 60.00 -7.94 Pass -5.34 13.89 44.05 10.06 0.55 54.66 60.00 Average Live **Pass** 12.29 41.38 10.05 0.54 51.97 Pass Live 60.00 -8.03 Average




Test specification:	AC Condu	icted Emissions (Class	B)		
	Temp(°C):	25.0			
Environmental Conditions:	Humidity (%):	53.17		X Pass	
	Atmospheric(mbar):	1016.70	Result:		
Mains Power:	120Vac, 60Hz	120Vac, 60Hz			
Tested by:	Anish Kumar			Fail	
Test Date:	25th Jan, 2017	25th Jan, 2017			
Remarks:	Neutral Line. External Antenna- LTE_B4_B2		ncies are: 2100MHz	and 5GHz.	
	Both the frequencies were operated at the sa	ame time.			



Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	Factors (dB)	Level (dBuV)	Measurement Type	Line/ Neutral	Limit (dBuV)	Margin (dB)	Pass /Fail
12.52	46.76	10.05	0.54	57.35	Quasi Peak	Neutral	73.00	-15.65	Pass
13.21	46.91	10.06	0.54	57.51	Quasi Peak	Neutral	73.00	-15.49	Pass
13.89	46.23	10.06	0.55	56.84	Quasi Peak	Neutral	73.00	-16.16	Pass
11.84	45.10	10.05	0.53	55.68	Quasi Peak	Neutral	73.00	-17.32	Pass
12.98	44.98	10.06	0.54	55.58	Quasi Peak	Neutral	73.00	-17.42	Pass
14.57	44.24	10.06	0.56	54.86	Quasi Peak	Neutral	73.00	-18.14	Pass
12.52	44.75	10.05	0.54	55.34	Average	Neutral	60.00	-4.66	Pass
13.21	45.19	10.06	0.54	55.79	Average	Neutral	60.00	-4.21	Pass
13.89	44.47	10.06	0.55	55.07	Average	Neutral	60.00	-4.93	Pass
11.84	43.22	10.05	0.53	53.80	Average	Neutral	60.00	-6.20	Pass
12.98	42.87	10.06	0.54	53.46	Average	Neutral	60.00	-6.54	Pass
14.57	41.57	10.06	0.56	52.18	Average	Neutral	60.00	-7.82	Pass



Test specification:	AC Cond	AC Conducted Emissions (Class B)									
	Temp(°C):	25.0									
Environmental Conditions:	Humidity (%):	53.17		X Pass							
	Atmospheric(mbar):	1016.70	Result:								
Mains Power:	120Vac, 60Hz	120Vac, 60Hz									
Tested by:	Anish Kumar			Fail							
Test Date:	25th Jan, 2017										
Remarks:	Phase Line. External Antenna- B252. The of frequencies were operated at the same time		100MHz and 5GHz	z. Both the							



Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	Factors (dB)	Level (dBuV)	Measurement Type	Line/ Neutral	Limit (dBuV)	Margin (dB)	Pass /Fail
13.21	47.12	10.06	0.54	57.73	Quasi Peak	Live	73.00	-15.27	Pass
12.53	46.86	10.05	0.54	57.45	Quasi Peak	Live	73.00	-15.55	Pass
13.90	46.35	10.06	0.55	56.95	Quasi Peak	Live	73.00	-16.05	Pass
11.85	45.25	10.05	0.53	55.84	Quasi Peak	Live	73.00	-17.16	Pass
14.58	44.83	10.06	0.56	55.44	Quasi Peak	Live	73.00	-17.56	Pass
12.99	44.82	10.06	0.54	55.41	Quasi Peak	Live	73.00	-17.59	Pass
13.21	45.53	10.06	0.54	56.13	Average	Live	60.00	-3.87	Pass
12.53	44.73	10.05	0.54	55.32	Average	Live	60.00	-4.68	Pass
13.90	44.67	10.06	0.55	55.28	Average	Live	60.00	-4.72	Pass
11.85	43.36	10.05	0.53	53.95	Average	Live	60.00	-6.05	Pass
14.58	42.39	10.06	0.56	53.01	Average	Live	60.00	-6.99	Pass
12.99	42.86	10.06	0.54	53.46	Average	Live	60.00	-6.54	Pass



Item

Applicant: SpiderCloud Wireless

Report: EMC_SL16122101-SPC-006_FCC

Applicable

12.2. Radiated Spurious Emissions Below 1GHz (Class A)

Requirement

Requirement(s):

Spec

Spec	iteiii	Requirement	Applicable
\$ 45 400	a)	The field strength of radiated emissions from a Class A digital device, as determined at a distance of 10 meters, shall not exceed the following:	Yes
§ 15.109		Frequency range (MHz) Field Strength (uV/m)	
		30 – 88 100	
		88 – 216 216 960 210	
		Above 960 300	
Test Setup		Radio Absorbing Material The state of the s	
Procedure	X 0 2. The 3. The em folk a. b. c. 4. A C	EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a .8m high, non-metallic table EUT was switched on and allowed to warm up to its normal operating condition. The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization ssions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna he owing manner: Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT The EUT was then rotated to the direction that gave the maximum emission. Finally, the antenna height was adjusted to the height that gave the maximum emission. The substitution of the set of the standard on top of a substitution of the EUT that substitution is a substitution of the standard on top of a substitution. Finally, the antenna height was adjusted to the height that gave the maximum emission. The substitution of the substitution of the substitution of the substitution of the EUT that substitution of the substitution of the substitution of the EUT that substitution of the	of the ight in the
Description of the Radiated Emissions Program	measu system a pre-s antenn scan; ti hold sv	MC Measurement software, EMI Soft Vasona offers a common user interface for electromagnetic interference. This software is a modern and powerful tool for controlling and monitoring EMI test receivers is. It guarantees reliable collection, evaluation, and documentation of measurement results. Basically, this pecan measurement before it proceeds with the final measurement. The pre-scan routine will run the scan of a heights, 2 antenna polarity, and 360 degrees table rotation. For example, the program was set to run 30 me program will first start from a meter antenna height and divide the 30 MHz to 1 GHz into 10 separate particles. Each parts of maximum hold sweep, the program will collect the data from 0 degree to 360 degrees the program complete the 1m scan, the antenna continues to rise to 2m and continue the scan. The step we	and EMC test rogram will runt four differer MHz to 1 GH ts of maximures table rotation

process and pre-scan routine. The final measurement will be based on the pre-scan data reduction result.

all specified antenna height and polarity. This program will perform the Quasi Peak measurement after the signal maximization



Report: EMC_SL16122101-SPC-006_FCC

Sample	At 300 MHz limit = 200 μ V/m = 46.00 dB μ V/m Log-periodic antenna factor & cable loss at 300 MHz = 18.50 dB								
Calculation	Q-P reading obtained directly from EMI Receiver = 40.00 dBµV/m								
Example	(Calibrated level including antenna factors & cable losses								
	Therefore, Q-P margin = 46.00 – 40.00 = 6.00 i.e. 6 dB below limit								
Remarks	The configurations tested: LTE_B4_B255 and LTE_B4_B252. The operating frequencies are: 2100MHz and 5GHz. Both the frequencies were operated at the same time.								


Test Data: X Yes (See below) N/A
Test Data: X Yes (See below) N/A



Report: EMC_SL16122101-SPC-006_FCC

Radiated Emission Test Results (Below 1GHz, Class A)


Test specification:	Radiated Emissions (Below 1GHz)							
	Temp(°C):	23.60						
Environmental Conditions:	Humidity (%):	37.12	-	X Pass				
	Atmospheric(mbar):	1016.70	Result:					
Mains Power:	120Vac, 60Hz							
Tested by:	Anish Kumar		-	Fail				
Test Date:	27th Jan 2017	-						
Remarks:	30 – 1000 MHz- Internal Antenna Configurati and 5GHz. Testing was done at 10m chambe		erating frequencie	s are: 2100MHz				



Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Po I	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
51.61	45.60	1.34	-13.38	33.56	Quasi Max	V	223	264	39.08	-5.52	Pass
30.00	31.44	0.99	0.06	32.49	Quasi Max	V	150	200	39.08	-6.59	Pass
109.94	40.51	1.75	-9.98	32.27	Quasi Max	٧	99	239	43.52	-11.25	Pass
63.23	35.62	1.44	-14.44	22.62	Quasi Max	٧	119	289	39.08	-16.46	Pass
169.99	41.92	2.11	-10.73	33.3	Quasi Max	V	102	297	43.52	-10.22	Pass
179.92	33.89	2.18	-11.14	24.93	Quasi Max	V	100	266	43.52	-18.59	Pass



Test specification:	Radiated	Emissions (Below 1GHz)					
	Temp(°C):	23.60					
Environmental Conditions:	Humidity (%):	37.12	-	X Pass			
	Atmospheric(mbar):	Result:					
Mains Power:	120Vac, 60Hz						
Tested by:	Anish Kumar			Fail			
Test Date:	27th Jan 2017						
Remarks:	30 – 1000 MHz- Internal Antenna Configuration. LTE_B4_ B252. The operating frequencies are: 2100MHz and 5GHz. Testing was done at 10m chamber						




Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Po I	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
51.61	45.60	1.34	-13.38	33.56	Quasi Max	V	223	264	39.08	-5.52	Pass
30.00	31.44	0.99	0.06	32.49	Quasi Max	٧	150	200	39.08	-6.59	Pass
109.94	40.51	1.75	-9.98	32.27	Quasi Max	٧	99	239	43.52	-11.25	Pass
63.23	35.62	1.44	-14.44	22.62	Quasi Max	٧	119	289	39.08	-16.46	Pass
169.99	41.92	2.11	-10.73	33.3	Quasi Max	٧	102	297	43.52	-10.22	Pass
179.92	33.89	2.18	-11.14	24.93	Quasi Max	٧	100	266	43.52	-18.59	Pass



Filename: c:\program files\emisoft - vasona\SPC-008- EA-FCC.emi

Applicant: SpiderCloud Wireless


Test specification:	Radiated Emissions (Below 1GHz)							
	Temp(°C):	23.60						
Environmental Conditions:	Humidity (%):	37.12	-	X Pass				
	Atmospheric(mbar):	Result:						
Mains Power:	120Vac, 60Hz							
Tested by:	Anish Kumar			Fail				
Test Date:	27th Jan 2017	1						
Remarks:	30 – 1000 MHz- External Antenna Configuration.LTE_B4_ B255. The operating frequencies are: 2100MHz and 5GHz. Testing was done at 10m chamber							



Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Po I	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
399.16	33.88	3.25	-20.64	16.49	Quasi Max	Н	384	59	46.44	-29.95	Pass
389.86	44.93	3.19	-21.07	27.04	Quasi Max	Н	198	140	46.44	-19.40	Pass
68.81	50.34	1.47	-28.07	23.74	Quasi Max	٧	277	182	39.08	-15.34	Pass
45.31	54.31	1.25	-25.21	30.35	Quasi Max	٧	194	27	39.08	-8.73	Pass
280.99	34.60	2.84	-23.05	14.39	Quasi Max	٧	142	339	46.44	-32.05	Pass
379.98	61.72	3.13	-21.17	43.68	Quasi Max	Н	262	132	46.44	-2.76	Pass



Test specification:	Radiated Emissions (Below 1GHz)							
	Temp(°C):	23.60						
Environmental Conditions:	Humidity (%):	37.12		X Pass				
	Atmospheric(mbar):	1016.70	Result:					
Mains Power:	120Vac, 60Hz	120Vac, 60Hz						
Tested by:	Anish Kumar			Fail				
Test Date:	27th Jan 2017	27th Jan 2017						
Remarks:	30 – 1000 MHz- External Antenna Configuration, LTE, R4, R255. The operating frequencies							



Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Po I	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
399.28	33.91	3.25	-20.63	16.53	Quasi Max	Н	162	49	46.44	-29.91	Pass
389.86	45.17	3.19	-21.07	27.29	Quasi Max	Н	216	146	46.44	-19.15	Pass
68.72	50.24	1.47	-28.10	23.61	Quasi Max	٧	227	224	39.08	-15.47	Pass
280.63	34.80	2.84	-23.05	14.60	Quasi Max	٧	380	345	46.44	-31.84	Pass
45.45	55.54	1.25	-25.29	31.51	Quasi Max	٧	164	22	39.08	-7.57	Pass
379.99	62.00	3.13	-21.17	43.95	Quasi Max	Н	243	146	46.44	-2.49	Pass



Report: EMC_SL16122101-SPC-006_FCC

12.3. Radiated Spurious Emissions above 1GHz (Class A)

Requirement(s):

pec	Item	Requirement	Applicable
	a)	The field strength of radiated emissions from a Class A digital device, as determined distance of 3 meters, shall not exceed the following:	ed at a Yes
§ 15.109		Frequency range (GHz) Average limit Peak limit dB(uV/m) Average limit dB(uV/m)	
		Above 1 60 80	
Test Setup		Semi Anechoic Chamber Radio Absorbing Material 3m / 10m Antenna 1-4m	Spectrum Analyzer
Procedure	1.00 2. The 3. The em folk a. b. c. 4. A P 5. Ste 6. The	EUT and supporting equipment were set up in accordance with the requirements of the X 0.8m high, non-metallic table at EUT was switched on and allowed to warm up to its normal operating condition. The test was carried out at the selected frequency points obtained from the EUT character issions, was carried out by rotating the EUT, changing the antenna polarization, and adjoining manner: Vertical or horizontal polarisation (whichever gave the higher emission level over a full chosen. The EUT was then rotated to the direction that gave the maximum emission. Finally, the antenna height was adjusted to the height that gave the maximum emission leak and Average measurement was then made for that frequency point. The sum of the su	isation. Maximization of the justing the antenna height in the Irotation of the EUT) was on.
Remarks		urations were tested: LTE_B4_B255 and LTE_B4_B252. erating frequencies are: 2100MHz and 5GHz. Both the frequencies were operated at	the same time.

Test Data: X Yes (See below) N/A


Test Data: X Yes (See below) N/A



Report: EMC_SL16122101-SPC-006_FCC

Radiated Emission Test Results (Above 1GHz, Class A)


Test specification:	Radiated	Emissions (Above 1GH	<u>z)</u>				
	Temp(°C):	23.10					
Environmental Conditions:	Humidity (%):	37.19		X Pass			
	Atmospheric(mbar):	1017.70	Result:				
Mains Power:	120Vac, 60Hz	120Vac, 60Hz					
Tested by:	Anish Kumar			Fail			
Test Date:	2nd Feb 2017						
Remarks:	1-18Ghz. Internal Antenna Configuration- B	3255 Mode. The operating	frequencies are: 21	00MHz and			
	5GHz. Testing was done at 10m chamber						



Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Po I	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
2127.17	66.28	3.34	-11.77	57.84	Peak Max	Н	159	12	80.00	-22.16	Pass
5776.66	59.87	5.56	-3.48	61.94	Peak Max	٧	222	357	80.00	-18.06	Pass
17931.63	37.40	9.14	8.44	54.98	Peak Max	٧	240	304	80.00	-25.02	Pass
6930.38	39.61	5.73	-0.49	44.86	Peak Max	٧	184	260	80.00	-35.14	Pass
7711.53	39.43	5.93	-0.12	45.23	Peak Max	٧	102	50	80.00	-34.77	Pass
12231.21	38.95	7.34	2.37	48.66	Peak Max	٧	249	39	80.00	-31.34	Pass
2127.17	54.33	3.34	-11.77	45.90	Average Max	Н	159	12	60.00	-14.10	Pass
5776.66	49.11	5.56	-3.48	51.18	Average Max	٧	222	357	60.00	-8.82	Pass
17931.63	25.14	9.14	8.44	42.72	Average Max	V	240	304	60.00	-17.28	Pass
6930.38	26.83	5.73	-0.49	32.08	Average Max	V	184	260	60.00	-27.92	Pass
7711.53	27.29	5.93	-0.12	33.10	Average Max	V	102	50	60.00	-26.90	Pass
12231.21	26.81	7.34	2.37	36.52	Average Max	V	249	39	60.00	-23.48	Pass




Test specification:	Radiated	Emissions (Above 1GHz	:)				
	Temp(°C):	23.1					
Environmental Conditions:	Humidity (%):	37.19		X Pass			
	Atmospheric(mbar):	1017.7	Result:				
Mains Power:	120Vac, 60Hz	120Vac, 60Hz					
Tested by:	Anish Kumar			Fail			
Test Date:	2nd Feb 2017						
Remarks:	1-18Ghz. Internal Antenna Configuration-LTE	E_B4_ B252. The operating	g frequencies are:	2100MHz and			
	5GHz. Testing was done at 10m chamber						



Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Po I	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
17674.88	37.50	9.07	8.39	54.95	Peak Max	٧	308	104	80.00	-25.05	Pass
16779.01	37.37	8.87	5.74	51.97	Peak Max	Н	194	113	80.00	-28.03	Pass
11413.21	39.45	7.67	2.29	49.41	Peak Max	٧	203	218	80.00	-30.59	Pass
2132.62	53.71	3.34	-11.8	45.25	Peak Max	Н	144	276	80.00	-34.75	Pass
8354.67	39.39	6.45	-0.10	45.74	Peak Max	Н	197	4	80.00	-34.26	Pass
5200.04	42.46	4.88	-4.50	42.83	Peak Max	Н	200	25	80.00	-37.17	Pass
17674.88	25.45	9.07	8.39	42.91	Average Max	٧	308	104	60.00	-17.09	Pass
16779.01	25.40	8.87	5.74	40.01	Average Max	Н	194	113	60.00	-20.00	Pass
11413.21	27.69	7.67	2.29	37.65	Average Max	٧	203	218	60.00	-22.35	Pass
2132.62	51.00	3.34	-11.8	42.53	Average Max	Н	144	276	60.00	-17.47	Pass
8354.67	27.62	6.45	-0.10	33.98	Average Max	Н	197	4	60.00	-26.02	Pass
5200.04	35.75	4.88	-4.5	36.12	Average Max	Н	200	25	60.00	-23.88	Pass



Test specification:	Radiated	l Emissions (Above 1GHz)				
	Temp(°C):	23.1					
Environmental Conditions:	Humidity (%):	37.19	-	X Pass			
	Atmospheric(mbar):	1017.7	Result:				
Mains Power:	120Vac, 60Hz	120Vac, 60Hz					
Tested by:	Anish Kumar		-	Fail			
Test Date:	2nd Feb 2017		-				
Remarks:	1-18Ghz. External Antenna Configuration-L	TE_B4_ B252. The operating	ng frequencies are	2100MHz and			
	5GHz. Testing was done at 10m chamber						




Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Po I	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
2135.95	67.24	3.34	-11.82	58.76	Peak Max	٧	396	189	80.00	-21.24	Pass
5208.04	58.55	4.89	-4.48	58.97	Peak Max	Н	155	49	80.00	-21.04	Pass
4265.12	57.87	4.88	-5.76	56.99	Peak Max	٧	194	305	80.00	-23.01	Pass
17566.67	38.16	9.04	7.77	54.97	Peak Max	Н	341	311	80.00	-25.03	Pass
6933.24	46.49	5.73	-0.47	51.75	Peak Max	Н	132	45	80.00	-28.25	Pass
10405.20	45.23	7.24	0.15	52.61	Peak Max	Н	107	18	80.00	-27.39	Pass
2135.95	56.81	3.34	-11.82	48.33	Average Max	٧	396	189	60.00	-11.67	Pass
5208.04	47.36	4.89	-4.48	47.78	Average Max	Н	155	49	60.00	-12.22	Pass
4265.12	47.73	4.88	-5.76	46.85	Average Max	٧	194	305	60.00	-13.15	Pass
17566.67	25.94	9.04	7.77	42.75	Average Max	Н	341	311	60.00	-17.25	Pass
6933.24	42.51	5.73	-0.47	47.77	Average Max	Н	132	45	60.00	-12.23	Pass
10405.20	30.93	7.24	0.15	38.31	Average Max	Н	107	18	60.00	-21.69	Pass



Report: EMC_SL16122101-SPC-006_FCC

Test specification:	Radiated	Emissions (Above 1GH	lz)			
	Temp(°C):	23.10				
Environmental Conditions:	Humidity (%):	37.19		X Pass		
	Atmospheric(mbar):	1017.7 0	Result:			
Mains Power:	120Vac, 60Hz	120Vac, 60Hz				
Tested by:	Anish Kumar			Fail		
Test Date:	6 th Feb 2017					
Remarks:	Above 1-18Ghz. External Antenna Configura and 5GHz. Testing was done at 10m chambe		perating frequencies	are: 2100MHz		




Filename: o:\program files\emisoft - vasona\SPC-006-FCC-B255.emi

Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Po I	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
17948.92	38.75	9.14	8.35	56.25	Peak Max	٧	143	216	80	-23.76	Pass
17292.14	37.86	9.00	6.77	53.63	Peak Max	Н	166	308	80	-26.37	Pass
12944.80	38.72	7.53	3.48	49.73	Peak Max	٧	158	12	80	-30.27	Pass
7713.52	42.82	5.93	-0.13	48.62	Peak Max	Н	102	304	80	-31.38	Pass
5233.57	39.17	4.94	-4.41	39.70	Peak Max	٧	198	133	80	-40.3	Pass
2944.96	42.76	3.86	-9.93	36.70	Peak Max	٧	260	131	80	-43.3	Pass
17948.92	25.99	9.14	8.35	43.49	Average Max	٧	143	216	60	-16.51	Pass
17292.14	25.99	9.00	6.77	41.76	Average Max	Н	166	308	60	-18.24	Pass
12944.80	26.80	7.53	3.48	37.81	Average Max	٧	158	12	60	-22.19	Pass
7713.52	34.37	5.93	-0.13	40.17	Average Max	Н	102	304	60	-19.83	Pass
5233.57	27.54	4.94	-4.41	28.07	Average Max	٧	198	133	60	-31.93	Pass
2944.96	30.62	3.86	-9.93	24.56	Average Max	٧	260	131	60	-35.44	Pass




Test specification:	Radiated	Emissions (Above 1GHz	:)	
	Temp(°C):	21.50		
Environmental Conditions:	Humidity (%):	35.50		X Pass
	Atmospheric(mbar):	1015.60	Result:	
Mains Power:	120Vac, 60Hz			
Tested by:	Anish Kumar			Fail
Test Date:	6 th Feb 2017			
Remarks:	Above 18-29Ghz. Internal Antenna Configura and 5GHz. Testing was done at 10m chambe		erating frequencies	s are: 2100MHz



Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Po I	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
23142.20	39.59	10.33	4.78	54.70	Peak Max	Н	99	12	80.00	-25.30	Pass
26770.67	38.51	11.52	7.04	57.07	Peak Max	Н	241	87	80.00	-22.93	Pass
28384.28	38.37	11.51	5.49	55.37	Peak Max	Н	212	290	80.00	-24.63	Pass
25216.82	39.18	10.97	3.56	53.71	Peak Max	Н	180	4	80.00	-26.29	Pass
21051.68	37.36	10.00	2.65	50.02	Peak Max	٧	202	132	80.00	-29.98	Pass
20295.03	38.20	9.80	0.30	48.31	Peak Max	٧	364	336	80.00	-31.69	Pass
23142.20	26.99	10.33	4.78	42.10	Average Max	Н	99	12	60.00	-17.90	Pass
26770.67	26.73	11.52	7.04	45.29	Average Max	Н	241	87	60.00	-14.72	Pass
28384.28	25.72	11.51	5.49	42.73	Average Max	Н	212	290	60.00	-17.28	Pass
25216.82	25.76	10.97	3.56	40.29	Average Max	Н	180	4	60.00	-19.71	Pass
21051.68	25.00	10.00	2.65	37.65	Average Max	V	202	132	60.00	-22.35	Pass
20295.03	25.89	9.80	0.30	36.00	Average Max	V	364	336	60.00	-24.00	Pass




Test specification:	Radiated	d Emissions (Above 1G	Hz)	
	Temp(°C):	21.50		
Environmental Conditions:	Humidity (%):	35.50		X Pass
	Atmospheric(mbar):	1015.60	Result:	
Mains Power:	120Vac, 60Hz	-		
Tested by:	Anish Kumar			Fail
Test Date:	6 th Feb 2017			
Remarks:	Above 18-29Ghz. Internal Antenna Configurand 5GHz. Testing was done at 10m cham		operating frequencies	are: 2100MHz



Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Po I	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
28999.88	38.93	11.71	6.90	57.54	Peak Max	٧	144	219	80.00	-22.46	Pass
27711.45	37.60	11.44	6.43	55.47	Peak Max	٧	225	169	80.00	-24.53	Pass
22702.14	38.28	10.17	4.71	53.17	Peak Max	Н	356	108	80.00	-26.83	Pass
25940.87	39.43	11.07	3.84	54.33	Peak Max	Н	218	301	80.00	-25.67	Pass
20888.08	37.04	9.94	2.04	49.02	Peak Max	Н	259	80	80.00	-30.98	Pass
24550.51	39.11	10.60	1.78	51.49	Peak Max	٧	233	71	80.00	-28.51	Pass
28999.88	26.08	11.71	6.90	44.70	Average Max	٧	144	219	60.00	-15.30	Pass
27711.45	25.65	11.44	6.43	43.52	Average Max	٧	225	169	60.00	-16.48	Pass
22702.14	25.84	10.17	4.71	40.72	Average Max	Н	356	108	60.00	-19.28	Pass
25940.87	26.44	11.07	3.84	41.35	Average Max	Н	218	301	60.00	-18.65	Pass
20888.08	25.06	9.94	2.04	37.04	Average Max	Н	259	80	60.00	-22.96	Pass
24550.51	25.71	10.60	1.78	38.09	Average Max	٧	233	71	60.00	-21.91	Pass




Test specification:	Radiated Emissions (Above 1GHz)				
	Temp(°C):	Temp(°C): 21.5			
Environmental Conditions:	Humidity (%): 35.50			X Pass	
	Atmospheric(mbar):	Result:			
Mains Power:	120Vac, 60Hz				
Tested by:	Anish Kumar		Fail		
Test Date:	6 th Feb 2017				
Remarks:	Above 18-29Ghz. External Antenna Configuration- B252 Mode. The operating frequencies are: 2100Ml and 5GHz. Testing was done at 10m chamber				



Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Po I	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
26712.67	38.70	11.52	7.06	57.28	Peak Max	Н	313	115	80.00	-22.73	Pass
22936.11	37.88	10.27	4.95	53.10	Peak Max	Н	225	253	80.00	-26.90	Pass
28661.03	37.15	11.58	5.87	54.60	Peak Max	Н	263	347	80.00	-25.40	Pass
25952.62	38.71	11.07	3.83	53.60	Peak Max	٧	163	302	80.00	-26.40	Pass
20323.49	37.83	9.80	0.34	47.97	Peak Max	٧	389	216	80.00	-32.03	Pass
24512.44	37.56	10.58	1.68	49.82	Peak Max	Н	381	303	80.00	-30.18	Pass
26712.67	27.00	11.52	7.06	45.57	Average Max	Н	313	115	60.00	-14.43	Pass
22936.11	25.75	10.27	4.95	40.98	Average Max	Н	225	253	60.00	-19.02	Pass
28661.03	25.23	11.58	5.87	42.68	Average Max	Н	263	347	60.00	-17.32	Pass
25952.62	26.41	11.07	3.83	41.31	Average Max	٧	163	302	60.00	-18.69	Pass
20323.49	25.82	9.80	0.34	35.96	Average Max	٧	389	216	60.00	-24.04	Pass
24512.44	25.74	10.58	1.68	38.00	Average Max	Н	381	303	60.00	-22.00	Pass



Test specification:	Radiated Emissions (Above 1GHz)				
	Temp(°C): 21.5				
Environmental Conditions:	Humidity (%): 35.50			X Pass	
	Atmospheric(mbar):	Result:			
Mains Power:	120Vac, 60Hz				
Tested by:	Anish Kumar		Fail		
Test Date:	6 th Feb 2017				
Remarks:	Above 18-29Ghz. External Antenna Configuration- B255 Mode. The operating frequencies are: 2100MHz and 5GHz. Testing was done at 10m chamber				



Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Po I	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
23141.37	42.15	10.33	4.78	57.26	Peak Max	Н	99	293	80.00	-22.74	Pass
26568.18	38.50	11.52	7.06	57.07	Peak Max	٧	103	183	80.00	-22.93	Pass
27951.68	37.15	11.50	5.63	54.28	Peak Max	٧	299	11	80.00	-25.72	Pass
21238.29	38.36	10.08	3.30	51.74	Peak Max	Н	262	99	80.00	-28.26	Pass
20626.72	37.45	9.84	1.04	48.33	Peak Max	Н	314	35	80.00	-31.67	Pass
24857.67	37.86	10.78	2.52	51.16	Peak Max	٧	272	85	80.00	-28.84	Pass
23141.37	29.16	10.33	4.78	44.27	Average Max	Н	99	293	60.00	-15.73	Pass
26568.18	26.55	11.52	7.06	45.13	Average Max	٧	103	183	60.00	-14.87	Pass
27951.68	25.31	11.50	5.63	42.43	Average Max	٧	299	11	60.00	-17.57	Pass
21238.29	25.59	10.08	3.30	38.98	Average Max	Н	262	99	60.00	-21.03	Pass
20626.72	25.80	9.84	1.04	36.68	Average Max	Н	314	35	60.00	-23.32	Pass
24857.67	25.74	10.78	2.52	39.05	Average Max	٧	272	85	60.00	-20.95	Pass



Report: EMC_SL16122101-SPC-006_FCC

13. Annex A | Test instruments and method

Instrument	Model	Serial #	Cal Cycle	Cal Due	In use
	Cor	nducted Emissions			
EMI Test Receiver (9kHz - 6GHz)	ESL6	100178	1 Year	8/17/2017	YES
Transient Limiter (9kHz - 100MHz)	EM-7600	287	1 Year	4/7/2017	YES
V-LISN (150 kHz - 30 MHz)	NNLK 8129	8129-190	1 Year	8/4/2017	YES
LISN (9kHz - 30MHz)	MN2050B	1018	1 Year	8/16/2017	YES
	Ra	diated Emissions			
EMI Test Receiver	ESIB 40	100179	1 Year	6/8/2017	YES
Keysight EXA 44 GHz Spectrum Analyzer	N9010A	MY51440112	1 Year	8/2/2017	YES
Antenna - Biconlog (30MHz - 2GHz)	JB1	A030702	1 Year	7/8/2017	YES
Double Ridged Waveguide Horn Antenna (1 - 18 GHz)	3115	10SL0059	1 Year	8/11/2017	YES
Horn Antenna (18-40GHz)	AH-840	101013	1 Year	7/15/2017	YES
Horn Antenna (700MHz - 18GHz)	SAS-571	411	1 Year	4/4/2017	NO
RF Pre-Amplifier (9kHz - 6.5GHz)	LPA-6-30	11140711	1 Year	2/10/2017	YES
1-40GHz Preamp	RLNA00M45GA	1611210047	N/A	N/A	YES
High Pass Filter	HFCN-3100+	N/A	N/A	N/A	YES
Pre-Amplifier (1 - 26.5GHz)	8449B	3008A00715	1 Year	3/30/2017	NO
2.4GHz Notch Filter	BRM50702	G242	1 Year	4/14/2017	YES
5.7GHz Notch Filter	BRC50705	G093	1 Year	4/14/2017	YES
10 Meters SAC	10M	N/A	1 Year	7/6/2017	YES



Report: EMC_SL16122101-SPC-006_FCC

14. Annex B | SIEMIC Accreditation

Accreditations	Document	Scope / Remark				
ISO 17025 (A2LA)		Please see the documents for the detailed scope				
ISO Guide 65 (A2LA)	7	Please see the documents for the detailed scope				
TCB Designation		A1, A2, A3, A4, B1, B2, B3, B4, C				
FCC DoC Accreditation	₽	FCC Declaration of Conformity Accreditation				
FCC Site Registration	7	3 meter site				
FCC Site Registration	₽	10 meter site				
IC Site Registration	7	3 meter site				
IC Site Registration	艮	10 meter site				
	73	Radio & Telecommunications Terminal Equipment: EN45001 – EN ISO/IEC 17025				
EU NB	₺	Electromagnetic Compatibility: EN45001 – EN ISO/IEC 17025				
Singapore iDA CB(Certification Body)	因因	Phase I, Phase II				
Vietnam MIC CAB Accreditation	73	Please see the document for the detailed scope				
Hong Kong OFCA		(Phase II) OFCA Foreign Certification Body for Radio and Telecom				
	7	(Phase I) Conformity Assessment Body for Radio and Telecom				
Industry Canada CAB	7	Radio: Scope A – All Radio Standard Specification in Category I				
	D	Telecom: CS-03 Part I, II, V, VI, VII, VIII				
Japan Recognized Certification Body Designation	起因	Radio: A1. Terminal equipment for purpose of calling Telecom: B1. Specified radio equipment specified in Article 38-2, Paragraph 1, Item 1 of the Radio Law				
Korea CAB Accreditation	B	EMI: KCC Notice 2008-39, RRL Notice 2008-3: CA Procedures for EMI KN22: Test Method for EMI EMS: KCC Notice 2008-38, RRL Notice 2008-4: CA Procedures for EM, KN24, KN61000-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11: Test Method for EMS				



		Radio: RRL Notice 2008-26, RRL Notice 2008-2, RRL Notice 2008-10,				
		RRL Notice 2007-49, RRL Notice 2007-20, RRL Notice 2007-21, RRL Notice 2007-80,				
		RRL Notice 2004-68				
		Telecom: President Notice 20664, RRL Notice 2007-30, RRL Notice 2008-7 with				
		attachments 1, 3, 5, 6; President Notice 20664, RRL Notice 2008-7 with attachment 4				
Taiwan NCC CAB Recognition	7	LP0002, PSTN01, ADSL01, ID0002, IS6100, CNS14336, PLMN07, PLMN01, PLMN08				
Taiwan BSMI CAB Recognition		CNS 13438				
Japan VCCI		R-3083: Radiation 3 meter site				
	Z	C-3421: Main Ports Conducted Interference Measurement				
		T-1597: Telecommunication Ports Conducted Interference Measurement				
		EMC: AS/NZS CISPR 11, AS/NZS CISPR 14.1, AS/NZS CISPR22, AS/NZS 61000.6.3,				
		AS/NZS 61000.6.4				
		Radio communications: AS/NZS 4281, AS/NZS 4268, AS/NZS 4280.1,				
Australia CAD Decembion	=	AS/NZS 4280.2, AS/NZS 4295, AS/NZS 4582, AS/NZS 4583, AS/NZS 4769.1, AS/NZS				
Australia CAB Recognition	<i>></i> -	4769.2, AS/NZS 4770, AS/NZS 4771				
		Telecommunications: AS/ACIF S002:05, AS/ACIF S003:06, AS/ACIF S004:06, AS/ACIF				
		S006:01, AS/ACIF S016:01, AS/ACIF S031:01, AS/ACIF S038:01, AS/ACIF S040:01,				
		AS/ACIF S041:05, AS/ACIF S043.2:06, AS/ACIF S60950.1				
Australia NATA Recognition	-	AS/ACIF S002, AS/ACIF S003, AS/ACIF S004, AS/ACIF S006, AS/ACIF S016,AS/ACIF				
	<u> </u>	S031, AS/ACIF S038, AS/ACIF S040, AS/ACIF S041, AS/ACIF S043.2				