



Project No.: TM-2308000407P
Report No.: TMTN2308001128NR

FCC ID: Y4O-ACVR



Page: 1 / 155
Rev.: 00

FCC 47 CFR PART 15 SUBPART C AND ANSI C63.10: 2013

TEST REPORT

For

Audio Device

Model: ACVR

Brand: AKAI PROFESSIONAL



Issued for

inMusic Brands, Inc.

200 Scenic View Drive, Cumberland, RI 02864, U.S.A.

Issued by

Compliance Certification Services Inc.

Tainan Lab.

No. 168, Ln. 523, Sec. 3, Zhongzheng Rd., Rende
Dist., Tainan City, 717017, Taiwan
Issued Date: October 31, 2023

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. Ltd. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

REVISION HISTORY

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	October 31, 2023	Initial Issue	ALL	Gina Lin

TABLE OF CONTENTS

1. TEST REPORT CERTIFICATION	4
2. EUT DESCRIPTION	5
3. DESCRIPTION OF TEST MODES	7
4. TEST METHODOLOGY	8
5. FACILITIES AND ACCREDITATIONS.....	8
5.1 FACILITIES.....	8
5.2 EQUIPMENT.....	8
5.3 LABORATORY ACCREDITATIONS LISTINGS	8
5.4 TABLE OF ACCREDITATIONS AND LISTINGS	9
6. CALIBRATION AND UNCERTAINTY.....	10
6.1 MEASURING INSTRUMENT CALIBRATION.....	10
6.2 MEASUREMENT UNCERTAINTY	10
7. SETUP OF EQUIPMENT UNDER TEST.....	11
7.1 SETUP CONFIGURATION OF EUT.....	11
7.2 SUPPORT EQUIPMENT	12
7.3 EUT OPERATING CONDITION	14
8. APPLICABLE LIMITS AND TEST RESULTS.....	17
8.1 6dB BANDWIDTH.....	17
8.2 MAXIMUM PEAK OUTPUT POWER.....	31
8.3 DUTY CYCLE	46
8.4 POWER SPECTRAL DENSITY	60
8.5 CONDUCTED SPURIOUS EMISSION.....	76
8.6 RADIATED EMISSIONS	98
8.6.1 TRANSMITTER RADIATED SUPURIOUS EMISSIONS.....	98
8.6.2 WORST-CASE RADIATED EMISSION BELOW 1 GHZ	103
8.6.3 TRANSMITTER RADIATED EMISSION ABOVE 1 GHZ	105
8.6.4 RESTRICTED BAND EDGES.....	135
8.7 POWERLINE CONDUCTED EMISSIONS	145
9. ANTENNA REQUIREMENT.....	149
9.1 STANDARD APPLICABLE	149
9.2 ANTENNA CONNECTED CONSTRUCTION	149
APPENDIX I SETUP PHOTOS	150

1. TEST REPORT CERTIFICATION

Applicant

: **inMusic Brands, Inc.**
200 Scenic View Drive, Cumberland, RI 02864, U.S.A.

Manufacturer

: **inMusic Brands, Inc.**
200 Scenic View Drive, Cumberland, RI 02864, U.S.A.

Equipment Under Test

: Audio Device

Model

: ACVR

Brand

: AKAI PROFESSIONAL

**Date of Test**

: August 28, 2023 ~ August 30, 2023

APPLICABLE STANDARD

STANDARD	TEST RESULT
FCC Part 15 Subpart C AND ANSI C63.10: 2013	No non-compliance noted

Statements of Conformity

Determining compliance shall be based on the results of the compliance measurement,
not taking into account measurement instrumentation uncertainty.

Approved by:

A handwritten signature in black ink that reads "John Chen".

John Chen
Supervisor

2. EUT DESCRIPTION

Product Name	Audio Device
Model	ACVR
Brand	AKAI PROFESSIONAL 
Received Date	August 23, 2023
Frequency Range	IEEE 802.11b/g, 802.11n HT20: 2412MHz~2462MHz Bluetooth 5.0: 2402MHz~2480MHz
Transmit Power	IEEE 802.11b Mode: 19.37dBm (86.497mW) IEEE 802.11g Mode: 22.26dBm (168.267mW) IEEE 802.11n HT20 Mode: 22.05dBm (160.325mW) Bluetooth 4.0 Mode: 5.85dBm (3.849mW) Bluetooth 5.0 Mode: 5.99dBm (3.967mW)
Channel Spacing	IEEE 802.11b/g, 802.11n HT20: 5MHz Bluetooth 5.0: 2MHz
Channel Number	IEEE 802.11b/g, 802.11n HT20: 11 Channels Bluetooth 5.0 : 40 Channels
Transmit Data Rate	IEEE 802.11b : 11, 5.5, 2, 1 Mbps IEEE 802.11g : 54, 48 ,36, 24, 18, 12, 9, 6 Mbps IEEE 802.11n HT20 : 130, 117 ,104, 78, 65, 58.5, 52, 39, 26, 19.5,13, 6.5 Mbps Bluetooth 5.0: 2 Mbps
Type of Modulation	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK) Bluetooth 5.0: GFSK
Antenna Type	Type: WLAN EMBEDDED ANTENNA Model: WLA-EM-1707-0064-B Manufacturer: BRITO Gain: 4.63 dBi
Power Rating	AC 100-240V
Hardware Version	IINM-PCB-ACVR-RearPanel-RevE
Software Version	N/A
Firmware Version	ACVR-2.12.1.1031-2023-07-21-17-33-os_c836be0-acvs_v2.12.1.1031-full
Temperature Range	0°C ~ +40°C
Reported Date	September 11, 2023

Power Adapter :

No.	Manufacturer	Model No.	Power Input	Power Output
1	FSP	FSP036-RHBN3	AC 100-240V~,1.8A, 50-60Hz	DC 12.0V, 3.0A, 36.0W

Report No.: TMTN2308001128NR**REMARK:**

1. The sample (**ACVR**) selected for test was engineering sample that approximated to production product and was provided by manufacturer.
2. This submittal(s) (test report) is intended for FCC ID: **Y4O-ACVR** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.
3. For more details, please refer to the User's manual of the EUT.

3. DESCRIPTION OF TEST MODES

The EUT is a Audio Device. It has one transmitter chains and one receive chains (1x1 configurations) and BT5.0. The 1x1 configuration is implemented with one outside chains (Chain 0).

The RF chipset is manufactured by Synaptics.

The antenna peak gain 4.63dBi (highest gain) were chosen for full testing.

IEEE 802.11 b ,802.11g ,802.11n HT20 mode (DTS Band)

The EUT had been tested under operating condition.

There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2412
Middle	2437
High	2462

IEEE 802.11b mode: 1Mbps long data rate (worst case) were chosen for full testing.

IEEE 802.11g mode: 6Mbps data rate (worst case) were chosen for full testing.

IEEE 802.11n HT20 mode: 6.5Mbps data rate (worst case) were chosen for full testing.

GFSK mode

The EUT had been tested under operating condition.

There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2402
Middle	2442
High	2480

Bluetooth 5.0 (GFSK) mode: 2Mbps data rate (worst case) were chosen for full testing.

4. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10 and FCC CFR 47 15.207, 15.209 and 15.247.

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

- No.8, Jiucengling, Xinhua Dist., Tainan City 712, Taiwan (R.O.C.)
- No. 168, Ln. 523, Sec. 3, Zhongzheng Rd., Rende Dist., Tainan City 717017, Taiwan (R.O.C.)

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 LABORATORY ACCREDITATIONS LISTINGS

The test facilities used to perform radiated and conducted emissions tests are accredited by Taiwan Accreditation Foundation for the specific scope of accreditation under Lab Code: 1109 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by TAF or any agency of the Government. In addition, the test facilities are listed with Federal Communications Commission (registration no: TW1109).

5.4 TABLE OF ACCREDITATIONS AND LISTINGS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

Taiwan	TAF
---------------	-----

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada	Industry Canada (TW1109)
---------------	--------------------------

6. CALIBRATION AND UNCERTAINTY

6.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

6.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:


PARAMETER	UNCERTAINTY
Radiated Emission, 9kHz~30MHz Test Site : CB1166	±2.7dB
Radiated Emission, 30 MHz ~1GHz Test Site : CB1166	±3.76dB
Radiated Emission, 1GHz ~18GHz Test Site : CB1166	±4.43dB
Radiated Emission, 18GHz~26.5GHz Test Site : CB1166	±4.79dB
Radiated Emission, 26.5GHz~40GHz Test Site : CB1166	±4.72dB
Power Line Conducted Emission, 9kHz~30MHz	±1.83dB
Band Width	0.025%
Peak Output Power MU	±1.9dB
Band Edge MU	±0.264dBuV
Channel Separation MU	±361.69Hz
Duty Cycle MU	±0.2%
Frequency Stability MU	±0.493Hz
Temperature	±0.5
Humidity	±3%

Uncertainty figures are valid to a confidence level of 95%, K=2


7. SETUP OF EQUIPMENT UNDER TEST

7.1 SETUP CONFIGURATION OF EUT

FOR RF TEST



FOR EMI TEST



7.2 SUPPORT EQUIPMENT

RF test

No.	Product	Manufacturer	Model No.	Certify No.	Signal cable
1	SD Card	TOSHIBA	2GB	DOC	N/A
2	Flash Disk	Transcend	Jet Flash700	DOC	N/A
3	Note Book	ACER	MS2229	DOC	Non-shd, 1.8m, 1core

No.	Signal cable description	
A	AC Power	Unshielded, 1.0m, 1pcs.
B	DC Power	Unshielded, 2.0m, 1pcs with one core.
C	USB	Shielded, 2.0m, 1pcs with one core.
D	USB	Shielded, 1.8m, 1pcs with one core.
E	Audio	Shielded, 1.0m, 13pcs.

EMI test

No.	Product	Manufacturer	Model No.	Certify No.	Signal cable
1	iPad mini	Apple	A2567	DOC	N/A
2	Speaker System	infotec	SP-102	DOC	N/A
3	Flash Disk	Transcend	Jet Flash700	DOC	N/A
4	SD Card	Transcend	N/A	DOC	N/A
5	keyboard	AKAI	LPK25	DOC	N/A

No.	Signal cable description	
A	AC Power cable	Unshielded, 1.0m, 1pcs.
B	DC Power cable	Unshielded, 2.0m, 1pcs with one core.
C	Audio cable	Shielded, 2.0m, 1pcs.
D	Audio cable	Shielded, 2.0m, 1pcs.
E	USB cable	Shielded, 1.8m, 1pcs with one core.
F	Audio cable	Shielded, 1.0m, 12pcs.

REMARK:

1. All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

7.3 EUT OPERATING CONDITION

RF Setup

RF Setup

1. Set up a whole system as the setup diagram.
2. The “Tera Term” software was used for testing
3. Key in “root” , “connmanctl enable wifi”.

TX Mode Key in:

B Mode :

```
wl down
wl mpc 0
wl country ALL
wl band b
wl up
wl 2g_rate -r 01 -b 20
wl channel 01 (01,06,11)
wl phy_watchdog 0
wl scansuppress 1
wl phy_forcecal 1
wl phy_txpwrctrl 1
wl txpwr1 -o -d 15
wl pkteng_start 00:90:4c:14:43:19 tx 100 1000 0
```

G Mode :

```
wl down
wl mpc 0
wl country ALL
wl band b
wl up
wl 2g_rate -r 06 -b 20
wl channel 01 (01,06,11)
wl phy_watchdog 0
wl scansuppress 1
wl phy_forcecal 1
wl phy_txpwrctrl 1
wl txpwr1 -o -d 13
wl pkteng_start 00:90:4c:14:43:19 tx 100 1000 0
```

HT20 Mode :

```
wl down
wl mpc 0
wl country ALL
wl band b
wl up
wl 2g_rate -h 0 -b 20
wl channel 01 (01,06,11)
wl phy_watchdog 0
wl scansuppress 1
wl phy_forcecal 1
wl phy_txpwrctrl 1
wl txpwr1 -o -d 13 (12,11)
wl pkteng_start 00:90:4c:14:43:19 tx 100 1000 0
```

RX Mode Key in:

```
wl down
wl band auto
wl mpc 0
wl country ALL
wl channel 01 (01,06,11)
wl bi 65535
wl up
wl phy_watchdog 0
wl scansuppress 1
wl phy_forcecal 1
```

4. All of the function are under run.
5. Start test.

Bluetooth:

1. Set up a whole system as the setup diagram.
2. The “Tera Term” software was used for testing.

3. Key in :

```
root
cd /sys/class/bluetooth/hci0
ls -al
cd rfkill2/
echo 1 >state
echo 0 > /sys/class/rfkill/rfkill1/soft
bluetoothctl
power on
```

4. Press "Ctrl + z"

TX Mode

BLE 1M Key in:

```
hciconfig hci0 up
hcitool cmd 0x03 0x0003
hcitool cmd 0x08 0X0001e 00(00,14,27) 25 00
```

BLE 2M

BLE 2M Key in:

```
hciconfig hci0 up
hcitool cmd 0x03 0x0003
hcitool cmd 0x08 0x0034 00(00,14,27) 25 00 02
```

RX Mode

BLE1M Key in:

```
hciconfig hci0 up
hcitool cmd 0x03 0x0003
hcitool cmd 0x3f 0x0052 EE FF C0 88 00 00 E8 03 00(00,27,4E) 04 00 01 FF FF
```

BLE2M Key in:

```
hciconfig hci0 up
hcitool cmd 0x03 0x0003
hcitool cmd 0x08 0x0033 00(00,14,27) 02 00
```

5. All of the function are under run.
6. Start test.

8. APPLICABLE LIMITS AND TEST RESULTS

8.1 6dB BANDWIDTH

LIMIT

§ 15.247(a) (2) For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

TEST EQUIPMENTS

Chamber Room #1166					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	07/25/2023	07/24/2024
SMA Cable+10dB Attenuator	CCS	SMA+10dB ATT	SMA/10dB	01/19/2023	01/18/2024
Software	Excel(ccs-o6-2020 v1.1)				

TEST SETUP



TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 1-5 % of the emission bandwidth (EBW).
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. Compare the resultant bandwidth with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is 1-5 %.

TEST RESULTS

No non-compliance noted.

Model Name	ACVR	Test By	Peter Chu
Temp & Humidity	24.5°C, 44%	Test Date	2023/08/28

IEEE 802.11b mode

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (kHz)	Pass / Fail
Low	2412	8.05	500	PASS
Middle	2437	8.07	500	PASS
High	2462	8.08	500	PASS

NOTE :

1. At final test to get the worst-case emission at 1Mbps long.
2. The cable assembly insertion loss of 11.4dB was entered as an offset in the spectrum analyzer to allow for direct reading of power.

IEEE 802.11g mode

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (kHz)	Pass / Fail
Low	2412	15.36	500	PASS
Middle	2437	15.22	500	PASS
High	2462	15.21	500	PASS

NOTE :

1. At final test to get the worst-case emission at 6Mbps.
2. The cable assembly insertion loss of 11.4dB was entered as an offset in the spectrum analyzer to allow for direct reading of power.

IEEE 802.11n HT20 mode

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (kHz)	Pass / Fail
Low	2412	15.22	500	PASS
Middle	2437	15.22	500	PASS
High	2462	15.21	500	PASS

NOTE :

1. At final test to get the worst-case emission at 6.5Mbps.
2. The cable assembly insertion loss of 11.4dB was entered as an offset in the spectrum analyzer to allow for direct reading of power.

Model Name	ACVR	Test By	Peter Chu
Temp & Humidity	24.4°C, 45%	Test Date	2023/08/28

Bluetooth 4.0 (GFSK) mode

Channel	Channel Frequency (MHz)	6dB Bandwidth (kHz)	Minimum Limit (kHz)	Pass / Fail
Low	2402	715	500	PASS
Middle	2442	720	500	PASS
High	2480	718	500	PASS

NOTE :

1. At final test to get the worst-case emission at 1Mbps.
2. The cable assembly insertion loss of 11.4dB was entered as an offset in the spectrum analyzer to allow for direct reading of power.

Model Name	ACVR	Test By	Peter Chu
Temp & Humidity	24.4°C, 45%	Test Date	2023/08/28


Bluetooth 5.0 (GFSK) mode


Channel	Channel Frequency (MHz)	6dB Bandwidth (kHz)	Minimum Limit (kHz)	Pass / Fail
Low	2402	1150	500	PASS
Middle	2442	1160	500	PASS
High	2480	1150	500	PASS

NOTE :


1. At final test to get the worst-case emission at 2Mbps.
2. The cable assembly insertion loss of 11.4dB was entered as an offset in the spectrum analyzer to allow for direct reading of power.


6dB BANDWIDTH (802.11b MODE)







Report No.: TMTN2308001128NR

6dB BANDWIDTH (802.11g MODE)




Report No.: TMTN2308001128NR


6dB BANDWIDTH (802.11n HT20 MODE)




Report No.: TMTN2308001128NR


6dB BANDWIDTH (GFSK(4.0) MODE)





Report No.: TMTN2308001128NR

6dB BANDWIDTH (GFSK(5.0) MODE)



8.2 MAXIMUM PEAK OUTPUT POWER

LIMIT

§ 15.247(b) The maximum peak output power of the intentional radiator shall not exceed the following :


§ 15.247(b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands : 1 watt.

§ 15.247(b) (4) Except as shown in paragraphs (c) of this section , if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2), and (b)(3) of this section , as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST EQUIPMENTS

Chamber Room #1166					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	07/25/2023	07/24/2024
SMA Cable+10dB Attenuator	CCS	SMA+10dB ATT	SMA/10dB	01/19/2023	01/18/2024
Software	Excel(ccs-o6-2020 v1.1)				

TEST SETUP



TEST PROCEDURE

The tests were performed in accordance with KDB 558074 8.3.1.1.

11.9.1.1 RBW \geq DTS bandwidth

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than

the DTS bandwidth is available to perform the measurement:

- a) Set the RBW \geq DTS bandwidth.
- b) Set VBW \geq [3 \times RBW].
- c) Set span \geq [3 \times RBW].
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

TEST RESULTS

No non-compliance noted

Model Name	ACVR			Test By	Peter Chu	
Temp & Humidity	24.5°C, 44%			Test Date	2023/08/28	

IEEE 802.11b mode

Channel	Frequency (MHz)	Data Rate	Power Set	Output Power (dBm)	Output Power Total		Limit (dBm)	Result
				ChainA	(dBm)	(W)		
Low	2412	1	15	17.38	17.38	0.0547	30.00	PASS
Middle	2437	1	15	19.25	19.25	0.0841		PASS
High	2462	1	15	19.37	19.37	0.0865		PASS

NOTE :

1. At final test to get the worst-case emission at 1Mbps long.
2. The cable assembly insertion loss of 11.4dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.

IEEE 802.11g mode

Channel	Frequency (MHz)	Data Rate	Power Set	Output Power (dBm)	Output Power Total		Limit (dBm)	Result
				ChainA	(dBm)	(W)		
Low	2412	6	13	21.65	21.65	0.1462	30.00	PASS
Middle	2437	6	13	22.26	22.26	0.1683		PASS
High	2462	6	13	22.21	22.21	0.1663		PASS

NOTE :

1. At final test to get the worst-case emission at 6Mbps.
2. The cable assembly insertion loss of 11.4dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.

IEEE 802.11n HT20 mode

Channel	Frequency (MHz)	Data Rate	Power Set	Output Power (dBm)	Output Power Total		Limit (dBm)	Result
				ChainA	(dBm)	(W)		
Low	2412	MCS1	13	21.11	21.11	0.1291	30.00	PASS
Middle	2437	MCS1	13	21.67	21.67	0.1469		PASS
High	2462	MCS1	13	22.05	22.05	0.1603		PASS

NOTE :

1. At final test to get the worst-case emission at 6.5Mbps.
2. The cable assembly insertion loss of 11.4dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.

Model Name	ACVR	Test By	Peter Chu
Temp & Humidity	24.4°C, 45%	Test Date	2023/08/28

Bluetooth 4.0 (GFSK) mode

Channel	Channel Frequency (MHz)	Peak Power (dBm)	Peak Power Limit (dBm)	Pass / Fail
Low	2402	5.85	30.00	PASS
Middle	2442	5.73	30.00	PASS
High	2480	5.39	30.00	PASS

NOTE :

1. At final test to get the worst-case emission at 1Mbps.
2. The cable assembly insertion loss of 11.4dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.

Bluetooth 5.0 (GFSK) mode

Channel	Channel Frequency (MHz)	Peak Power (dBm)	Peak Power Limit (dBm)	Pass / Fail
Low	2402	5.99	30.00	PASS
Middle	2442	5.96	30.00	PASS
High	2480	5.31	30.00	PASS

NOTE :

1. At final test to get the worst-case emission at 2Mbps.
2. The cable assembly insertion loss of 11.4dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.

**Average Power Data
IEEE 802.11b mode**

Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2412	14.44
Middle	2437	16.39
High	2462	16.47

IEEE 802.11g mode

Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2412	13.46
Middle	2437	14.01
High	2462	14.00

IEEE 802.11n HT20 mode

Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2412	12.79
Middle	2437	13.33
High	2462	13.70


Bluetooth 4.0 (GFSK) mode


Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2402	5.51
Middle	2442	5.44
High	2480	4.96

Bluetooth 5.0 (GFSK) mode


Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2402	5.29
Middle	2442	5.39
High	2480	4.74


MAXIMUM PEAK OUTPUT POWER (802.11b MODE)







MAXIMUM PEAK OUTPUT POWER (802.11g MODE)






MAXIMUM PEAK OUTPUT POWER (802.11n HT20 MODE)







Report No.: TMTN2308001128NR


MAXIMUM PEAK OUTPUT POWER (GFSK(4.0) MODE)





MAXIMUM PEAK OUTPUT POWER (GFSK(5.0) MODE)





8.3 DUTY CYCLE


LIMIT

Nil (No dedicated limit specified in the Rules)

TEST EQUIPMENTS

Chamber Room #1166					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	07/25/2023	07/24/2024
SMA Cable+10dB Attenuator	CCS	SMA+10dB ATT	SMA/10dB	01/19/2023	01/18/2024
Software	Excel(ccs-o6-2020 v1.1)				

TEST SETUP



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW \geq OBW if possible; otherwise, set RBW to the largest available value. Set VBW \geq RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

TEST RESULTS

No non-compliance noted.

TEST DATA**WIFI**

Duty Cycle				
Configuration	Duty Cycle(%)	Duty Factor(dB)	1/T(kHz)	VBW Setting(kHz)
B	0.00	0.00	0.01	0.01
G	0.00	0.00	0.01	0.01
n HT20	0.00	0.00	0.01	0.01

Model Name	ACVR	Test By	Peter Chu
Temp & Humidity	24.5°C, 44%	Test Date	2023/08/28

IEEE 802.11b Mode:

	us	Times	Ton	Total Ton time(ms)
Ton1	100000.000	1	100000	
Ton2		0	0	
Ton3			0	100
Tp				100

Ton	100
Tp(Ton+Toff)	100
Duty Cycle	1
10 * log (1/x) =	0

IEEE 802.11g Mode:



	us	Times	Ton	Total Ton time(ms)
Ton1	100000.000	1	100000	
Ton2		0	0	
Ton3			0	100
Tp				100


Ton	100
Tp(Ton+Toff)	100
Duty Cycle	1
10 * log (1/x) =	0



IEEE 802.11n HT20 Mode:


	us	Times	Ton	Total Ton time(ms)
Ton1	100000.000	1	100000	
Ton2		0	0	
Ton3			0	100
Tp				100



Ton	100
Tp(Ton+Toff)	100
Duty Cycle	1
10 * log (1/x) =	0


TEST PLOT











Duty Cycle				
Configuration	Duty Cycle(%)	Duty Factor(dB)	1/T(kHz)	VBW Setting(kHz)
BLE 1M	64	-1.94	2.50	3.0
BLE 2M	33.6	-4.74	4.76	5.1

Bluetooth 4.0:

Model Name	ACVR	Test By	Peter Chu
Temp & Humidity	24.4°C, 45%	Test Date	2023/08/28

	us	Times	Ton	Total Ton time(ms)
Ton1	400	1	400	
Ton2		0	0	
Ton3			0	0.4
Tp				0.625

Ton	0.4
Tp(Ton+Toff)	0.625
Duty Cycle	0.64
10 * log (1/x) =	1.94

Bluetooth 5.0:

Model Name	ACVR	Test By	Peter Chu
Temp & Humidity	24.4°C, 45%	Test Date	2023/08/28


	us	Times	Ton	Total Ton time(ms)
Ton1	210	1	210	
Ton2		0	0	
Ton3			0	0.21
Tp				0.625

Ton	0.21
Tp(Ton+Toff)	0.625
Duty Cycle	0.336
10 * log (1/x) =	4.74


Plot


Bluetooth 4.0

CH Low






CH Mid





Bluetooth 5.0





8.4 POWER SPECTRAL DENSITY

LIMIT

§ 15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST EQUIPMENTS

Chamber Room #1166					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	07/25/2023	07/24/2024
SMA Cable+10dB Attenuator	CCS	SMA+10dB ATT	SMA/10dB	01/19/2023	01/18/2024
Software	Excel(ccs-o6-2020 v1.1)				

TEST SETUP



TEST PROCEDURE

The tests were performed in accordance with KDB 558074 5.3.1.

5.3.1 Measurement Procedure PKPSD:

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the *DTS bandwidth*.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \text{ RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST RESULTS

Model Name	ACVR	Test By	Peter Chu
Temp & Humidity	24.5°C, 44%	Test Date	2023/08/28

IEEE 802.11b mode

Channel	Frequency (MHz)	PPSD/3kHz (dBm)	Limit (dBm)	Margin (dB)	Pass / Fail
Low	2412	-5.64	8.00	-13.64	PASS
Middle	2437	-5.96	8.00	-13.96	PASS
High	2462	-5.31	8.00	-13.31	PASS

NOTE : 1. At final test to get the worst-case emission at 1long Mbps long.
2. The cable assembly insertion loss of 11.4dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.

IEEE 802.11g mode

Channel	Frequency (MHz)	PPSD/3kHz (dBm)	Limit (dBm)	Margin (dB)	Pass / Fail
Low	2412	-9.07	8.00	-17.07	PASS
Middle	2437	-8.58	8.00	-16.58	PASS
High	2462	-8.43	8.00	-16.43	PASS

NOTE : 1. At final test to get the worst-case emission at 6long Mbps long.
2. The cable assembly insertion loss of 11.4dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.

IEEE 802.11n HT20 mode

Channel	Frequency (MHz)	PPSD/3kHz (dBm)	Limit (dBm)	Margin (dB)	Pass / Fail
Low	2412	-10.16	8.00	-18.16	PASS
Middle	2437	-9.43	8.00	-17.43	PASS
High	2462	-8.12	8.00	-16.12	PASS

NOTE : 1. At final test to get the worst-case emission at 6.5long Mbps long.
2. The cable assembly insertion loss of 11.4dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.

Model Name	ACVR	Test By	Peter Chu
Temp & Humidity	24.4°C, 45%	Test Date	2023/08/28

Bluetooth 4.0 (GFSK) mode

Channel	Frequency (MHz)	PPSD/3kHz (dBm)	Limit (dBm)	Margin (dB)	Pass / Fail
Low	2402	-8.32	8.00	-16.32	PASS
Middle	2442	-8.43	8.00	-16.43	PASS
High	2480	-8.90	8.00	-16.90	PASS

NOTE :


1. At final test to get the worst-case emission at 1long Mbps long.
2. The cable assembly insertion loss of 11.45dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.


Bluetooth 5.0 (GFSK) mode

Channel	Frequency (MHz)	PPSD/3kHz (dBm)	Limit (dBm)	Margin (dB)	Pass / Fail
Low	2402	-11.15	8.00	-19.15	PASS
Middle	2442	-11.34	8.00	-19.34	PASS
High	2480	-11.52	8.00	-19.52	PASS


NOTE :


1. At final test to get the worst-case emission at 2long Mbps long.
2. The cable assembly insertion loss of 11.4dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.

POWER SPECTRAL DENSITY (IEEE 802.11b MODE)



POWER SPECTRAL DENSITY (IEEE 802.11g MODE)





POWER SPECTRAL DENSITY (802.11n HT20 MODE)

