



Project No.: TM-2112000126P
Report No.: TMTN2112000722NR

FCC ID: Y4O-HG06

Page: 1 / 161
Rev.: 00

FCC 47 CFR PART 15 SUBPART C AND ANSI C63.10: 2013

TEST REPORT

For

Audio Device

Model: HG06

Brand: Headrush

Issued for

inMusic Brands, Inc.

200 Scenic View Drive, Cumberland, RI 02864 United States

Issued by

Compliance Certification Services Inc.

Tainan Lab.

No.8, Jiucengling, Xinhua Dist.,

Tainan City, Taiwan

Issued Date: April 30, 2022

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. Ltd. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: TMTN2112000722NR

Page: 2 / 161

Rev.: 00

REVISION HISTORY

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	April 30, 2022	Initial Issue	ALL	Gina Lin



Report No.: TMTN2112000722NR

Page: 3 / 161

Rev.: 00

TABLE OF CONTENTS

1. TEST REPORT CERTIFICATION	4
2. EUT DESCRIPTION	5
3. DESCRIPTION OF TEST MODES	6
4. TEST METHODOLOGY	7
5. FACILITIES AND ACCREDITATIONS.....	7
5.1 FACILITIES.....	7
5.2 EQUIPMENT.....	7
5.3 LABORATORY ACCREDITATIONS LISTINGS	7
5.4 TABLE OF ACCREDITATIONS AND LISTINGS	8
6. CALIBRATION AND UNCERTAINTY.....	9
6.1 MEASURING INSTRUMENT CALIBRATION.....	9
6.2 MEASUREMENT UNCERTAINTY	9
7. SETUP OF EQUIPMENT UNDER TEST.....	10
7.1 SETUP CONFIGURATION OF EUT.....	10
7.2 SUPPORT EQUIPMENT	11
7.3 EUT OPERATING CONDITION	12
8. APPLICABLE LIMITS AND TEST RESULTS.....	15
8.1 6dB BANDWIDTH.....	15
8.2 MAXIMUM PEAK OUTPUT POWER.....	29
8.3 DUTY CYCLE	55
8.4 POWER SPECTRAL DENSITY	68
8.5 CONDUCTED SPURIOUS EMISSION.....	82
8.6 RADIATED EMISSIONS.....	104
8.6.1 TRANSMITTER RADIATED SUPURIOUS EMSSIONS.....	104
8.6.2 WORST-CASE RADIATED EMISSION BELOW 1 GHZ	109
8.6.3 TRANSMITTER RADIATED EMISSION ABOVE 1 GHZ	111
8.6.4 RESTRICTED BAND EDGES.....	126
8.7 POWERLINE CONDUCTED EMISSIONS	151
9. ANTENNA REQUIREMENT	155
9.1 STANDARD APPLICABLE	155
9.2 ANTENNA CONNECTED CONSTRUCTION	155
APPENDIX I SETUP PHOTOS	156

Report No.: TMTN2112000722NR

1. TEST REPORT CERTIFICATION

Applicant : **inMusic Brands, Inc.**
200 Scenic View Drive, Cumberland, RI 02864 United States

Manufacturer : **inMusic Brands, Inc.**
200 Scenic View Drive, Cumberland, RI 02864 United States

Equipment Under Test : Audio Device

Model : HG06

Brand : Headrush

Date of Test : December 08, 2021 ~ March 03, 2022

APPLICABLE STANDARD	
STANDARD	TEST RESULT
FCC Part 15 Subpart C AND ANSI C63.10: 2013	No non-compliance noted

Statements of Conformity
Determining compliance shall be based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Approved by:

John Chen

John Chen
Supervisor

2. EUT DESCRIPTION

Product Name	Audio Device
Model	HG06
Brand	Headrush
Received Date	December 07, 2021
Frequency Range	IEEE 802.11b/g, 802.11n HT20: 2412MHz~2462MHz Bluetooth 5.0: 2402MHz~2480MHz
Transmit Power	IEEE 802.11b Mode: 18.57dBm (71.945mW) IEEE 802.11g Mode: 20.00dBm (100.000mW) IEEE 802.11n HT20 Mode: 19.26dBm (84.333mW) Bluetooth 4.0 Mode: 4.21dBm (2.636mW) Bluetooth 5.0 Mode: 4.43dBm (2.773mW)
Channel Spacing	IEEE 802.11b/g, 802.11n HT20: 5MHz Bluetooth 5.0: 2MHz
Channel Number	IEEE 802.11b/g, 802.11n HT20: 11 Channels Bluetooth 5.0 : 40 Channels
Transmit Data Rate	IEEE 802.11b : 11, 5.5, 2, 1 Mbps IEEE 802.11g : 54, 48, 36, 24, 18, 12, 9, 6 Mbps IEEE 802.11n HT20 : 130, 117, 104, 78, 65, 58.5, 52, 39, 26, 19.5, 13, 6.5 Mbps Bluetooth 5.0: 2 Mbps
Type of Modulation	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK) Bluetooth 5.0: GFSK
Antenna Type	Type: WLAN ANTENNA Model: DB1EM60-I0300-S Manufacturer: BRITO Gain: 4.6 dBi
Power Rating	AC 100-240V
Hardware Version	INM-AZ05-Carrier Board
Software Version	N/A
Firmware Version	hg06-2021-09-08-03-13-unified-1c43f5c-AZ01-master-863f253
Temperature Range	0°C ~ +35°C
Reported Date	April 22, 2022

REMARK:

- The sample (**HG06**) selected for test was engineering sample that approximated to production product and was provided by manufacturer.
- This submittal(s) (test report) is intended for FCC ID: **Y40-HG06** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.
- For more details, please refer to the User's manual of the EUT.

3. DESCRIPTION OF TEST MODES

The EUT is a Audio Device. It has one transmitter chains and one receive chains (1x1 configurations) and BT5.0. The 1x1 configuration is implemented with one outside chains (Chain 0).

The RF chipset is manufactured by Broadcom.

The antenna peak gain 4.6dBi (highest gain) were chosen for full testing.

IEEE 802.11 b ,802.11g ,802.11n HT20 mode (DTS Band)

The EUT had been tested under operating condition.

There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2412
Middle	2437
High	2462

IEEE 802.11b mode: 1Mbps long data rate (worst case) were chosen for full testing.

IEEE 802.11g mode: 6Mbps data rate (worst case) were chosen for full testing.

IEEE 802.11n HT20 mode: 6.5Mbps data rate (worst case) were chosen for full testing.

GFSK mode

The EUT had been tested under operating condition.

There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2402
Middle	2442
High	2480

Bluetooth 5.0 (GFSK) mode: 1Mbps data rate (worst case) were chosen for full testing.

4. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10 and FCC CFR 47 15.207, 15.209 and 15.247.

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at No.8, Jiucengling, Xinhua Dist., Tainan City 712, Taiwan (R.O.C.)

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 LABORATORY ACCREDITATIONS LISTINGS

The test facilities used to perform radiated and conducted emissions tests are accredited by Taiwan Accreditation Foundation for the specific scope of accreditation under Lab Code: 1109 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by TAF or any agency of the Government. In addition, the test facilities are listed with Federal Communications Commission (registration no: TW1109).



Report No.: TMTN2112000722NR

Page: 8 / 161

Rev.: 00

5.4 TABLE OF ACCREDITATIONS AND LISTINGS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

Taiwan	TAF
---------------	-----

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada	Industry Canada (TW1109)
Germany	TUV NORD
Taiwan	BSMI
USA	FCC

6. CALIBRATION AND UNCERTAINTY

6.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

6.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:


PARAMETER	UNCERTAINTY
Radiated Emission, 30 to 200 MHz Test Site : OATS-6	$\pm 3.3456\text{dB}$
Radiated Emission, 200 to 1000 MHz Test Site : OATS-6	$\pm 2.6828\text{dB}$
Radiated Emission, 1 to 8 GHz	$\pm 2.6485\text{dB}$
Radiated Emission, 8 to 18 GHz	$\pm 2.6852\text{dB}$
Radiated Emission, 18 to 26.5 GHz	$\pm 2.6485\text{dB}$
Radiated Emission, 26 to 40 GHz	$\pm 3.0295\text{dB}$
Power Line Conducted Emission	$\pm 1.91\text{dB}$
Band Width	136.49kHz
Peak Output Power MU	$\pm 1.904\text{dB}$
Band Edge MU	$\pm 0.302\text{dBuV}$
Channel Separation MU	361.69Hz
Duty Cycle MU	0.064ms
Frequency Stability MU	0.223kHz

Uncertainty figures are valid to a confidence level of 95%, K=2


7. SETUP OF EQUIPMENT UNDER TEST

7.1 SETUP CONFIGURATION OF EUT

FOR RF TEST



FOR EMI TEST



7.2 SUPPORT EQUIPMENT

RF test

No.	Product	Manufacturer	Model No.	Certify No.	Signal cable
1	Flash Disk	Transcend	Jet Flash700	DOC	N/A
2	Notebook	Acer	MS2229	DOC	Unshielded, 1.4m Unshielded, 1.6m with one core

No.	Signal cable description	
A	AC Power cable	Unshielded, 1.8m, 1pcs.
B	USB	Shielded, 1.4m, 1pcs. with one core
C	MIC	Shielded, 1.0m, 2pcs.
D	Audio 6.4m	Shielded, 0.5m, 9pcs.
E	Audio 3.5m	Shielded, 1.0m, 2pcs.
F	USB	Unshielded, 2.0m, 1pcs.
G	MIC	Shielded, 0.5m, 2pcs.

EMI test

No.	Product	Manufacturer	Model No.	Certify No.	Signal cable
1	Speaker System	T.C.SATR	TCS2285	DOC	N/A
2	Flash Disk	Transcend	Jet Flash700	DOC	N/A

No.	Signal cable description	
A	AC Power cable	Unshielded, 1.7m, 1pcs.
B	Audio	Shielded, 1.0m, 13pcs.
C	USB	Shielded, 2.0m, 1pcs.
D	Audio	Shielded, 1.0m, 1pcs.

REMARK:

- All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.
- Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

7.3 EUT OPERATING CONDITION

RF Setup

1. Set up a whole system as the setup diagram.
2. The "Tera Term" software was used for testing
3. Key in "root" , "connmanctl enable wifi".

TX Mode Key in:

B Mode :

```
wl down
wl mpc 0
wl country ALL
wl band b
wl up
wl 2g_rate -r 01 -b 20
wl channel 01 (01,06,11)
wl phy_watchdog 0
wl scansuppress 1
wl phy_forcecal 1
wl phy_txpwrctrl 1
wl txpwr1 -o -d 15
wl pkteng_start 00:90:4c:14:43:19 tx 100 1000 0
```

G Mode :

```
wl down
wl mpc 0
wl country ALL
wl band b
wl up
wl 2g_rate -r 06 -b 20
wl channel 01 (01,06,11)
wl phy_watchdog 0
wl scansuppress 1
wl phy_forcecal 1
wl phy_txpwrctrl 1
wl txpwr1 -o -d 13 (13,12,11)
wl pkteng_start 00:90:4c:14:43:19 tx 100 1000 0
```



Report No.: TMTN2112000722NR

Page: 13 / 161
Rev.: 00

HT20 Mode :

```
wl down
wl mpc 0
wl country ALL
wl band b
wl up
wl 2g_rate -h 0 -b 20
wl channel 01 (01,06,11)
wl phy_watchdog 0
wl scansuppress 1
wl phy_forcecal 1
wl phy_txpwrctrl 1
wl txpwr1 -o -d 12 (12,11)
wl pkteng_start 00:90:4c:14:43:19 tx 100 1000 0
```

RX Mode Key in:

```
wl down
wl band auto
wl mpc 0
wl country ALL
wl channel 01 (01,06,11)
wl bi 65535
wl up
wl phy_watchdog 0
wl scansuppress 1
wl phy_forcecal 1
```

4. All of the function are under run.

5. Start test.

Report No.: TMTN2112000722NR

Bluetooth:

1. Set up a whole system as the setup diagram.
2. The "Tera Term" software was used for testing.
3. Key in :
root
cd /sys/class/bluetooth/hci0
ls -al
cd rfkill2/
echo 1 >state
echo 0 > /sys/class/rfkill/rfkill1/soft
bluetoothctl
power on
4. Press "Ctrl + z"

TX Mode**BLE 1M Key in:**

```
hciconfig hci0 up  
hcidtool cmd 0x03 0x0003  
hcidtool cmd 0x08 0x0001e 00(00,14,27) 25 00
```

BLE 2M**BLE 2M Key in:**

```
hciconfig hci0 up  
hcidtool cmd 0x03 0x0003  
hcidtool cmd 0x08 0x00034 00(00,14,27) 25 00 02
```

RX Mode**BLE1M Key in:**

```
hciconfig hci0 up  
hcidtool cmd 0x03 0x0003  
hcidtool cmd 0x3f 0x0052 EE FF C0 88 00 00 E8 03 00(00,27,4E) 04 00 01 FF FF
```

BLE2M Key in:

```
hciconfig hci0 up  
hcidtool cmd 0x03 0x0003  
hcidtool cmd 0x08 0x00033 00(00,14,27) 02 00
```

5. All of the function are under run.
6. Start test.

8. APPLICABLE LIMITS AND TEST RESULTS

8.1 6dB BANDWIDTH

LIMIT

§ 15.247(a) (2) For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

TEST EQUIPMENTS

Chamber Room #966					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	07/22/2021	07/21/2022
Power Meter	Anritsu	ML2487A	6K00003888	05/18/2021	05/17/2022
Power Sensor	Anritsu	MA2491A	033265	05/18/2021	05/17/2022
SMA Cable+10dB Attenuator	CCS	SMA+10dB ATT	SMA/10dB	01/28/2022	01/27/2023
Software	Excel(ccs-o6-2020 v1.1)				

TEST SETUP



TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 1-5 % of the emission bandwidth (EBW).
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. Compare the resultant bandwidth with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is 1-5 %.

TEST RESULTS

No non-compliance noted.

Model Name	HG06	Test By	Ted Huang
Temp & Humidity	23.4°C, 65%	Test Date	2022/03/03

IEEE 802.11b mode

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (kHz)	Pass / Fail
Low	2412	8.06	500	PASS
Middle	2437	7.59	500	PASS
High	2462	8.04	500	PASS

NOTE :

1. At final test to get the worst-case emission at 1Mbps long.
2. The cable assembly insertion loss of 11.45dB was entered as an offset in the spectrum analyzer to allow for direct reading of power.

IEEE 802.11g mode

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (kHz)	Pass / Fail
Low	2412	15.51	500	PASS
Middle	2437	15.53	500	PASS
High	2462	15.20	500	PASS

NOTE :

1. At final test to get the worst-case emission at 6Mbps.
2. The cable assembly insertion loss of 11.45dB was entered as an offset in the spectrum analyzer to allow for direct reading of power.

IEEE 802.11n HT20 mode

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (kHz)	Pass / Fail
Low	2412	15.22	500	PASS
Middle	2437	15.39	500	PASS
High	2462	15.21	500	PASS

NOTE :

1. At final test to get the worst-case emission at 6.5Mbps.
2. The cable assembly insertion loss of 11.45dB was entered as an offset in the spectrum analyzer to allow for direct reading of power.

Model Name	HG06	Test By	Ted Huang
Temp & Humidity	23.4°C, 65%	Test Date	2022/03/03

Bluetooth 4.0 (GFSK) mode

Channel	Channel Frequency (MHz)	6dB Bandwidth (kHz)	Minimum Limit (kHz)	Pass / Fail
Low	2402	714	500	PASS
Middle	2442	714	500	PASS
High	2480	715	500	PASS

NOTE :

1. At final test to get the worst-case emission at 1Mbps.
2. The cable assembly insertion loss of 11.45dB was entered as an offset in the spectrum analyzer to allow for direct reading of power.

Model Name	HG06	Test By	Ted Huang
Temp & Humidity	23.4°C, 65%	Test Date	2022/03/03


Bluetooth 5.0 (GFSK) mode


Channel	Channel Frequency (MHz)	6dB Bandwidth (kHz)	Minimum Limit (kHz)	Pass / Fail
Low	2402	1160	500	PASS
Middle	2442	1160	500	PASS
High	2480	1130	500	PASS

NOTE :


1. At final test to get the worst-case emission at 2Mbps.
2. The cable assembly insertion loss of 11.45dB was entered as an offset in the spectrum analyzer to allow for direct reading of power.


6dB BANDWIDTH (802.11b MODE)







6dB BANDWIDTH (802.11g MODE)







6dB BANDWIDTH (802.11n HT20 MODE)







6dB BANDWIDTH (GFSK(4.0) MODE)





6dB BANDWIDTH (GFSK(5.0) MODE)





8.2 MAXIMUM PEAK OUTPUT POWER

LIMIT


§ 15.247(b) The maximum peak output power of the intentional radiator shall not exceed the following :

§ 15.247(b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands : 1 watt.

§ 15.247(b) (4) Except as shown in paragraphs (c) of this section , if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2), and (b)(3) of this section , as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST EQUIPMENTS

Chamber Room #966					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	07/22/2021	07/21/2022
Power Meter	Anritsu	ML2487A	6K00003888	05/18/2021	05/17/2022
Power Sensor	Anritsu	MA2491A	033265	05/18/2021	05/17/2022
SMA Cable+10dB Attenuator	CCS	SMA+10dB ATT	SMA/10dB	01/28/2022	01/27/2023
Software	Excel(ccs-o6-2020 v1.1)				

TEST SETUP**TEST PROCEDURE**

The tests were performed in accordance with KDB 558074 8.3.1.1.

11.9.1.1 RBW $\geq$ DTS bandwidth

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than

the DTS bandwidth is available to perform the measurement:

- a) Set the RBW $\geq$ DTS bandwidth.
- b) Set VBW $\geq [3 \times \text{RBW}]$.
- c) Set span $\geq [3 \times \text{RBW}]$.
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

Average Power

TEST PROCEDURE

1. Set span to at least 1.5 times the OBW.
2. Set RBW = 1% to 5% of the OBW, not to exceed 1 MHz.
3. Set VBW $\geq [3 \times \text{RBW}]$.
4. Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
5. Manually set sweep time $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission symbol period})]$,
but not less than the automatic default sweep time.
6. Set detector = RMS (power averaging).
7. The EUT shall be operated at $\geq 98\%$ duty cycle or sweep triggering/signal gating shall be employed such that the sweep time is less than or equal to the transmission duration T.
8. Perform a single sweep.
9. Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, then sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

TEST RESULTS

No non-compliance noted

Model Name	HG06	Test By	Ted Huang
Temp & Humidity	23.4°C, 65%	Test Date	2022/03/03

IEEE 802.11b mode

Channel	Frequency (MHz)	Data Rate	Power Set	Output Power (dBm)	Output Power Total		Limit (dBm)	Result
				ChainA	(dBm)	(W)		
Low	2412	1	15	17.43	17.43	0.0553	30.00	PASS
Middle	2437	1	15	17.62	17.62	0.0578		PASS
High	2462	1	15	18.57	18.57	0.0719		PASS

NOTE : 1. At final test to get the worst-case emission at 1Mbps long.
2. The cable assembly insertion loss of 11.45dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.

IEEE 802.11g mode

Channel	Frequency (MHz)	Data Rate	Power Set	Output Power (dBm)	Output Power Total		Limit (dBm)	Result
				ChainA	(dBm)	(W)		
Low	2412	6	13	20.00	20.00	0.1000	30.00	PASS
Middle	2437	6	12	19.83	19.83	0.0962		PASS
High	2462	6	11	19.63	19.63	0.0918		PASS

NOTE : 1. At final test to get the worst-case emission at 6Mbps.
2. The cable assembly insertion loss of 11.45dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.

IEEE 802.11n HT20 mode

Channel	Frequency (MHz)	Data Rate	Power Set	Output Power (dBm)	Output Power Total		Limit (dBm)	Result
				ChainA	(dBm)	(W)		
Low	2412	MCS1	12	18.39	18.39	0.0690	30.00	PASS
Middle	2437	MCS1	12	19.15	19.15	0.0822		PASS
High	2462	MCS1	11	19.26	19.26	0.0843		PASS

NOTE : 1. At final test to get the worst-case emission at 6.5Mbps.
2. The cable assembly insertion loss of 11.45dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.

Model Name	HG06	Test By	Ted Huang
Temp & Humidity	23.4°C , 65%	Test Date	2022/03/03

Bluetooth 4.0 (GFSK) mode

Channel	Channel Frequency (MHz)	Peak Power (dBm)	Peak Power Limit (dBm)	Pass / Fail
Low	2402	0.42	30.00	PASS
Middle	2442	2.61	30.00	PASS
High	2480	4.21	30.00	PASS

NOTE : 1. At final test to get the worst-case emission at 1Mbps.
2. The cable assembly insertion loss of 11.45dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.

Bluetooth 5.0 (GFSK) mode

Channel	Channel Frequency (MHz)	Peak Power (dBm)	Peak Power Limit (dBm)	Pass / Fail
Low	2402	0.58	30.00	PASS
Middle	2442	2.76	30.00	PASS
High	2480	4.43	30.00	PASS

NOTE : 1. At final test to get the worst-case emission at 2Mbps.
2. The cable assembly insertion loss of 11.45dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.

Report No.: TMTN2112000722NR

Average Power Data

IEEE 802.11b mode

Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2412	14.51
Middle	2437	14.71
High	2462	15.69

IEEE 802.11g mode

Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2412	11.74
Middle	2437	11.57
High	2462	11.36

IEEE 802.11n HT20 mode

Channel	Channel Frequency (MHz)	Average Power (dBm)
		Chain 0
Low	2412	9.82
Middle	2437	10.82
High	2462	10.67


Bluetooth 4.0 (GFSK) mode

Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2402	0.07
Middle	2442	2.29
High	2480	3.78

Bluetooth 5.0 (GFSK) mode

Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2402	0.19
Middle	2442	2.35
High	2480	3.96

MAXIMUM PEAK OUTPUT POWER (802.11b MODE)







Report No.: TMTN2112000722NR


Page: 36 / 161

Rev.: 00





MAXIMUM PEAK OUTPUT POWER (802.11g MODE)







MAXIMUM PEAK OUTPUT POWER (802.11n HT20 MODE)







MAXIMUM PEAK OUTPUT POWER (GFSK(4.0) MODE)








MAXIMUM PEAK OUTPUT POWER (GFSK(5.0) MODE)






MAXIMUM AVERAGE POWER (802.11b MODE)





MAXIMUM AVERAGE POWER (802.11g MODE)







Report No.: TMTN2112000722NR


Page: 48 / 161

Rev.: 00





MAXIMUM AVERAGE POWER (802.11n HT20 MODE)







MAXIMUM AVERAGE POWER (GFSK(4.0) MODE)





MAXIMUM AVERAGE POWER (GFSK(5.0) MODE)





8.3 DUTY CYCLE

LIMIT

Nil (No dedicated limit specified in the Rules)

TEST EQUIPMENTS

Chamber Room #966					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	07/22/2021	07/21/2022
Power Meter	Anritsu	ML2487A	6K00003888	05/18/2021	05/17/2022
Power Sensor	Anritsu	MA2491A	033265	05/18/2021	05/17/2022
SMA Cable+10dB Attenuator	CCS	SMA+10dB ATT	SMA/10dB	01/28/2022	01/27/2023
Software	Excel(ccs-o6-2020 v1.1)				

TEST SETUP



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW $\geq$ OBW if possible; otherwise, set RBW to the largest available value. Set VBW $\geq$ RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)



Report No.: TMTN2112000722NR

Page: 56 / 161

Rev.: 00

TEST RESULTS

No non-compliance noted.

TEST DATA

WIFI



Model Name	HG06	Test By	Ted Huang
Temp & Humidity	23.4°C, 65%	Test Date	2022/03/03

	us	Times	Ton	Total Ton time(ms)
Ton1	100000.000	1	100000	
Ton2		0	0	
Ton3			0	100
Tp				100

Ton	100
Tp(Ton+Toff)	100
Duty Cycle	1
$10 * \log (1/x) =$	0

TEST PLOT

Plot








Report No.: TMTN2112000722NR

Page: 58 / 161

Rev.: 00











Report No.: TMTN2112000722NR

Page: 60 / 161

Rev.: 00







Bluetooth 4.0:

Model Name	HG06	Test By	Ted Huang
Temp & Humidity	23.4°C, 65%	Test Date	2022/03/03

	us	Times	Ton	Total Ton time(ms)
Ton1	400	1	400	
Ton2		0	0	
Ton3			0	0.4
Tp				0.625

Ton	0.4
Tp(Ton+Toff)	0.625
Duty Cycle	0.64
10 * log (1/x) =	1.94



Bluetooth 5.0:


Model Name	HG06	Test By	Ted Huang
Temp & Humidity	23.4°C, 65%	Test Date	2022/03/03

	us	Times	Ton	Total Ton time(ms)
Ton1	200	1	200	
Ton2		0	0	
Ton3			0	0.2
Tp				0.625

Ton	0.2
Tp(Ton+Toff)	0.625
Duty Cycle	0.32
10 * log (1/x) =	4.95


Plot







Bluetooth 5.0

CH Low



CH Mid





8.4 POWER SPECTRAL DENSITY

LIMIT

§ 15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST EQUIPMENTS

Chamber Room #966					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	07/22/2021	07/21/2022
Power Meter	Anritsu	ML2487A	6K00003888	05/18/2021	05/17/2022
Power Sensor	Anritsu	MA2491A	033265	05/18/2021	05/17/2022
SMA Cable+10dB Attenuator	CCS	SMA+10dB ATT	SMA/10dB	01/28/2022	01/27/2023
Software	Excel(ccs-o6-2020 v1.1)				

TEST SETUP



TEST PROCEDURE

The tests were performed in accordance with KDB 558074 5.3.1.

5.3.1 Measurement Procedure PKPSD:

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the *DTS bandwidth*.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST RESULTS

Model Name	HG06	Test By	Ted Huang
Temp & Humidity	23.4°C, 65%	Test Date	2022/03/03

IEEE 802.11b mode

Channel	Frequency (MHz)	PPSD/3kHz (dBm)	Limit (dBm)	Margin (dB)	Pass / Fail
Low	2412	-6.96	8.00	-14.96	PASS
Middle	2437	-7.51	8.00	-15.51	PASS
High	2462	-5.51	8.00	-13.51	PASS

NOTE : 1. At final test to get the worst-case emission at 1long Mbps long.
2. The cable assembly insertion loss of 11.45dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.

IEEE 802.11g mode

Channel	Frequency (MHz)	PPSD/3kHz (dBm)	Limit (dBm)	Margin (dB)	Pass / Fail
Low	2412	-10.81	8.00	-18.81	PASS
Middle	2437	-10.82	8.00	-18.82	PASS
High	2462	-10.96	8.00	-18.96	PASS

NOTE : 1. At final test to get the worst-case emission at 6long Mbps long.
2. The cable assembly insertion loss of 11.45dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.

IEEE 802.11n HT20 mode

Channel	Frequency (MHz)	PPSD/3kHz (dBm)	Limit (dBm)	Margin (dB)	Pass / Fail
Low	2412	-13.18	8.00	-21.18	PASS
Middle	2437	-12.08	8.00	-20.08	PASS
High	2462	-11.35	8.00	-19.35	PASS

NOTE : 1. At final test to get the worst-case emission at 6.5long Mbps long.
2. The cable assembly insertion loss of 11.45dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.

Model Name	HG06	Test By	Ted Huang
Temp & Humidity	23.4°C, 65%	Test Date	2022/03/03

Bluetooth 4.0 (GFSK) mode

Channel	Frequency (MHz)	PPSD/3kHz (dBm)	Limit (dBm)	Margin (dB)	Pass / Fail
Low	2402	-13.92	8.00	-21.92	PASS
Middle	2442	-11.55	8.00	-19.55	PASS
High	2480	-9.98	8.00	-17.98	PASS


NOTE : 1. At final test to get the worst-case emission at 1long Mbps long.
2. The cable assembly insertion loss of 11.45dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.


Bluetooth 5.0 (GFSK) mode

Channel	Frequency (MHz)	PPSD/3kHz (dBm)	Limit (dBm)	Margin (dB)	Pass / Fail
Low	2402	-16.72	8.00	-24.72	PASS
Middle	2442	-14.20	8.00	-22.20	PASS
High	2480	-12.73	8.00	-20.73	PASS


NOTE : 1. At final test to get the worst-case emission at 2long Mbps long.
2. The cable assembly insertion loss of 11.45dB was entered as an offset in the spectrum analyzer to allow for direct reading of power, it was not displayed on the plot due to the instrument.


POWER SPECTRAL DENSITY (IEEE 802.11b MODE)







POWER SPECTRAL DENSITY (IEEE 802.11g MODE)







POWER SPECTRAL DENSITY (802.11n HT20 MODE)





POWER SPECTRAL DENSITY (Bluetooth 4.0 (GFSK) MODE)





POWER SPECTRAL DENSITY (Bluetooth 5.0 (GFSK) MODE)

