

FCC ID: Y4O-LGAF

FCC PART 15C TEST REPORT FOR CERTIFICATION  
On Behalf of

INMUSIC BRANDS INC

Portable Powered Bluetooth Speaker System

Model Number: TRANSACTIVE WIRELESS 2

FCC ID: Y4O-LGAF

Prepared for : INMUSIC BRANDS INC  
200 SCENIC VIEW DRIVE, SUITE 201, CUMBERLAND, RI  
02864, U.S.A.

Prepared By :EST Technology Co., Ltd.  
San Tun Management Zone, Houjie District, Dongguan, China

Tel: 86-769-83081888-808

Report Number: ESTE-R1608022  
Date of Test : July 16 ~ August 01, 2016  
Date of Report: August 04, 2016

## 1. EXPOSURE EVALUATION OF PORTABLE OR MOBILE DEVICES

Human exposure to RF emissions from portable devices (47 CFR §2.1093), as defined by the FCC, must be evaluated with respect to the FCC-adopted limits for SAR. Evaluation of mobile devices, as defined by the FCC, may also be performed with respect to SAR limits, but in such cases it is usually simpler and more cost-effective to evaluate compliance with respect to field strength or power density limits. For certain devices that are designed to be used in both mobile and portable configurations similar to those described in 47 CFR §2.1091(d)(4), such as certain desktop phones and wireless modem modules, compliance for mobile configurations is also satisfied when the same device is evaluated for SAR compliance in portable configurations.

## 2. SAR TEST EXCLUSION THRESHOLD FOR 100MHz to 6GHz and $\leq 50\text{mm}$

| MHz  | 5  | 10 | 15  | 20  | 25  | mm                                      |
|------|----|----|-----|-----|-----|---|
| 150  | 39 | 77 | 116 | 155 | 194 | SAR Test<br>Exclusion<br>Threshold (mW) |
| 300  | 27 | 55 | 82  | 110 | 137 |   |
| 450  | 22 | 45 | 67  | 89  | 112 |   |
| 835  | 16 | 33 | 49  | 66  | 82  |   |
| 900  | 16 | 32 | 47  | 63  | 79  |   |
| 1500 | 12 | 24 | 37  | 49  | 61  |   |
| 1900 | 11 | 22 | 33  | 44  | 54  |   |
| 2450 | 10 | 19 | 29  | 38  | 48  |   |
| 3600 | 8  | 16 | 24  | 32  | 40  |   |
| 5200 | 7  | 13 | 20  | 26  | 33  |   |
| 5400 | 6  | 13 | 19  | 26  | 32  |   |
| 5800 | 6  | 12 | 19  | 25  | 31  |   |

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

### 3. EVALUATION RESULTS

Maximum measured transmitter power.

| Mode   | CH   | Peak output Power (dBm) | Peak output Power (mW) | Target power (dBm) | Results |
|--------|------|-------------------------|------------------------|--------------------|---------|
| GFSK   | 2402 | -4.490                  | 0.356                  | -5±2.0             | 0.155   |
|        | 2441 | -4.641                  | 0.343                  | -5±2.0             | 0.157   |
|        | 2480 | -4.647                  | 0.343                  | -5±2.0             | 0.158   |
| 8-DPSK | 2402 | -5.725                  | 0.268                  | -6±2.0             | 0.123   |
|        | 2441 | -5.526                  | 0.280                  | -6±2.0             | 0.124   |
|        | 2480 | -5.712                  | 0.268                  | -6±2.0             | 0.125   |

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \* [ √ f(GHz) ] < 3.0

SAR Test Exclusion Thresholds is 3.0 for separation distance 5mm. Therefore, SAR test is not required.

=====END=====