



FCC RF Test Report

APPLICANT : INMUSIC BRANDS INC
EQUIPMENT : 6" Active Studio Monitor w DSP, BT, App
8" Active Studio Monitor w DSP, BT, App
BRAND NAME : M-Audio
MODEL NAME : MA51, MA51*****, FORTY SIXTY, Forty Sixty,
FORTY SIXTY*****, Forty Sixty*****,
(“*” can be “0-9”, “A-Z”, “a-z”, blank, “-”, “+” or
any character, symbol, alphanumeric.)
MA52, MA52*****, FORTY EIGHTY, Forty Eighty,
FORTY EIGHTY*****, Forty Eighty*****,
(“*” can be “0-9”, “A-Z”, “a-z”, blank, “-”, “+” or
any character, symbol, alphanumeric.)
FCC ID : Y4O-MA52
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : Jan. 18, 2024 ~ May 30, 2024

We, Sporton International Inc. (Shenzhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Testing Location	6
1.7 Test Software.....	7
1.8 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	8
2.1 Carrier Frequency Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example.....	11
3 TEST RESULT	12
3.1 6dB and 99% Bandwidth Measurement	12
3.2 Output Power Measurement.....	17
3.3 Power Spectral Density Measurement	18
3.4 Conducted Band Edges and Spurious Emission Measurement	23
3.5 Radiated Band Edges and Spurious Emission Measurement	28
3.6 AC Conducted Emission Measurement.....	32
3.7 Antenna Requirements.....	34
4 LIST OF MEASURING EQUIPMENT.....	35
5 MEASUREMENT UNCERTAINTY.....	36
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR3D1820B	Rev. 01	Initial issue of report	May 15, 2024
FR3D1820B	Rev. 02	Added conducted power and RSE test data for CH37/38	May 30, 2024



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Report only	-
3.2	15.247(b)(3)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 0.51 dB at 7320.00 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 6.65 dB at 0.41 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

INMUSIC BRANDS INC

200 Scenic View Drive,Suite 201,Cumberland,Rhode Island 02864,United States

1.2 Manufacturer

INMUSIC BRANDS INC

200 Scenic View Drive,Suite 201,Cumberland,Rhode Island 02864,United States

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	6" Active Studio Monitor w DSP, BT, App 8" Active Studio Monitor w DSP, BT, App
Brand Name	M-Audio
Model Name	MA51, MA51*****, FORTY SIXTY, Forty Sixty, FORTY SIXTY*****, Forty Sixty*****. ("*" can be "0-9", "A-Z", "a-z", blank, "-", "+" or any character, symbol, alphanumeric.) MA52, MA52*****, FORTY EIGHTY, Forty Eighty, FORTY EIGHTY*****, Forty Eighty*****. ("*" can be "0-9", "A-Z", "a-z", blank, "-", "+" or any character, symbol, alphanumeric.)
FCC ID	Y4O-MA52
SN Code	Conducted: A42308263400001 for sample 1 Conduction: A42308263400001 for Sample 1 A42308263300001 for sample 2 Radiation: A42308263400001 for Sample 1 A42308263300001 for sample 2
HW Version	N/A
SW Version	N/A
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two samples under test: sample 1 (MA52) and sample2 (MA51) with different size and some of parts. According to the difference, we choose sample 1 to perform full test and sample 2 to verify the worst case.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	5.54 dBm (0.0036 W)
99% Occupied Bandwidth	1.015MHz
Antenna Type / Gain	FPC Antenna type with gain 2.4 dBi
Type of Modulation	Bluetooth LE : GFSK

Note: BLE support 1Mbps data rate only

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-SZ TH01-SZ	CN1256	421272

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH01-SZ	CN1256	421272

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH01-SZ	AUDIX	E3	6.2009-8-24
2.	CO01-SZ	AUDIX	E3	6.120613b

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE
	Mode 2: Bluetooth Tx CH19_2440 MHz_BLE
	Mode 3: Bluetooth Tx CH39_2480 MHz_BLE
	Mode 4: Bluetooth Tx CH37_2476 MHz_BLE
	Mode 5: Bluetooth Tx CH38_2478 MHz_BLE
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE
	Mode 2: Bluetooth Tx CH19_2440 MHz_BLE
	Mode 3: Bluetooth Tx CH39_2480 MHz_BLE
	Mode 4: Bluetooth Tx CH37_2476 MHz_BLE
	Mode 5: Bluetooth Tx CH38_2478 MHz_BLE
AC Conducted Emission	Mode 1: BT Link with Mobile Phone(Play music) + Power Cable 4 for Sample 1
	Mode 2: BT Link with Mobile Phone(Play music) + Power Cable 4 for Sample 2
Remark: - The worst case of conducted emission is mode 1; only the test data of it was reported. - For Radiated Test Cases, the tests were performance with power cable 5.	

2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Mobile phone	Huawei	MATA9	QISEVA-L09	N/A	N/A

2.5 EUT Operation Test Setup

For BLE function, the engineering test program was provided and enabled to make EUT continuous transmit.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 2.30 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 2.30 + 10 = 12.30 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1% to 5% of the 99% OBW and the VBW is set to 3 times of the RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth


Please refer to Appendix A.

6 dB Bandwidth Plot on Channel 00



Date: 31.JAN.2024 12:49:36


6 dB Bandwidth Plot on Channel 19



Date: 31.JAN.2024 12:54:01



6 dB Bandwidth Plot on Channel 39




Date: 31.JAN.2024 12:55:46



3.1.6 Test Result of 99% Occupied Bandwidth


Please refer to Appendix A.

99% Occupied Bandwidth Plot on Channel 00



Date: 31.JAN.2024 12:49:07


99% Occupied Bandwidth Plot on Channel 19



Date: 31.JAN.2024 12:53:50



99% Occupied Bandwidth Plot on Channel 39



Date: 31.JAN.2024 12:55:35

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



Spectrum

Ref Level 20.00 dBm Offset 12.30 dB RBW 100 kHz
Att 20 dB SWT 1 ms VBW 300 kHz Mode Sweep

1Pk Max

M1[1] 5.34 dBm
2.40224720 GHz

10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm

CF 2.402 GHz 1001 pts Span 1.002 MHz

Spectrum

Ref Level 20.00 dBm Offset 12.30 dB RBW 100 kHz
Att 20 dB SWT 1 ms VBW 300 kHz Mode Sweep

1Pk Max


M1[1] 3.33 dBm
2.44024220 GHz

CF 2.44 GHz 1001 pts Span 1.002 MHz

Date: 5.FEB.2024 23:24:10



PSD 100kHz Plot on Channel 39




Date: 5.FEB.2024 23:25:55




3.3.7 Test Result of Power Spectral Density Plots (3kHz)

PSD 3kHz Plot on Channel 00



Date: 5.FEB.2024 23:18:59


PSD 3kHz Plot on Channel 19



Date: 5.FEB.2024 23:23:52



PSD 3kHz Plot on Channel 39



Date: 5.FEB.2024 23:25:39

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges Plots

Low Band Edge Plot on Channel 00



Date: 6.FEB.2024 00:12:29

High Band Edge Plot on Channel 39




Date: 6.FEB.2024 00:16:52




3.4.6 Test Result of Conducted Spurious Emission Plots

Conducted Spurious Emission Plot on Bluetooth LE GFSK Channel 00



Date: 6.FEB.2024 00:11:40

Conducted Spurious Emission Plot on Bluetooth LE GFSK Channel 00




Date: 6.FEB.2024 00:11:56



Conducted Spurious Emission Plot on Bluetooth LE


GFSK Channel 19



Date: 6.FEB.2024 00:13:15

Conducted Spurious Emission Plot on Bluetooth LE

GFSK Channel 19




Date: 6.FEB.2024 00:13:33



Conducted Spurious Emission Plot on Bluetooth LE


GFSK Channel 39



Date: 6.FEB.2024 00:14:21

Conducted Spurious Emission Plot on Bluetooth LE

GFSK Channel 39



Date: 6.FEB.2024 00:15:56

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver&SA	Agilent	N9038A	MY52260185	20Hz~26.5GHz	Dec. 27, 2023	Jan. 18, 2024~May 29, 2024	Dec. 26, 2024	Radiation (03CH01-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 07, 2023	Jan. 18, 2024~May 29, 2024	Jul. 06, 2024	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jul. 28, 2022	Jan. 18, 2024~May 29, 2024	Jul. 27, 2024	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	Oct. 24, 2023	Jan. 18, 2024~May 29, 2024	Oct. 23, 2025	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 08, 2023	Jan. 18, 2024~May 29, 2024	Jul. 07, 2024	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Apr. 08, 2023	Jan. 18, 2024~May 29, 2024	Apr. 07, 2024	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Apr. 07, 2024		Apr. 06, 2025	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 04, 2023	Jan. 18, 2024~May 29, 2024	Apr. 03, 2024	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 03, 2024		Apr. 02, 2025	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-00101800-30-10P-R	1943528	1GHz~18GHz	Oct. 18, 2023	Jan. 18, 2024~May 29, 2024	Oct. 17, 2024	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5Ghz	Oct. 18, 2023	Jan. 18, 2024~May 29, 2024	Oct. 17, 2024	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 07, 2023	Jan. 18, 2024~May 29, 2024	Jul. 06, 2024	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	Oct. 18, 2023	Jan. 18, 2024~May 29, 2024	Oct. 17, 2024	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jan. 18, 2024~May 29, 2024	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jan. 18, 2024~May 29, 2024	NCR	Radiation (03CH01-SZ)
laser range finder	Dingxin Yi	D-40	#01	NA	Oct. 19, 2023	Jan. 18, 2024~May 29, 2024	Oct. 18, 2024	Radiation (03CH01-SZ)
Thermo meter	Anymetre	JR593	#2	- 10℃ ~ 50℃ 10%RH ~ 99%RH	Apr. 12, 2023	Jan. 18, 2024~May 29, 2024	Apr. 11, 2024	Radiation (03CH01-SZ)
Thermo meter	Anymetre	JR593	#2	- 10℃ ~ 50℃ 10%RH ~ 99%RH	Apr. 11, 2024		Apr. 10, 2025	Radiation (03CH01-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Jul. 06, 2023	Jan. 31, 2024	Jul. 05, 2024	Conduction (CO01-SZ)
AC LISN	R&S	ENV216	100063	9kHz~30MHz	Aug. 21, 2023	Jan. 31, 2024	Aug. 20, 2024	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Oct. 16, 2023	Jan. 31, 2024	Oct. 15, 2024	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 07, 2023	Jan. 31, 2024	Jul. 06, 2024	Conduction (CO01-SZ)
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 06, 2023	Jan. 31, 2024~May 30, 2024	Apr. 05, 2024	Conducted (TH01-SZ)
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 05, 2024		Apr. 04, 2025	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1339473	30MHz~40GHz	Dec. 29, 2023	Jan. 31, 2024~May 30, 2024	Dec. 28, 2024	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Aug. 21, 2023	Jan. 31, 2024~May 30, 2024	Aug. 20, 2024	Conducted (TH01-SZ)
Thermo meter	Anymetre	JR593	#7	- 10℃ ~ 50℃ 10%RH~99%RH	Apr. 08, 2023	Jan. 31, 2024~May 30, 2024	Apr. 07, 2024	Conducted (TH01-SZ)
Thermo meter	Anymetre	JR593	#7	- 10℃ ~ 50℃ 10%RH~99%RH	Apr. 07, 2024		Apr. 06, 2025	Conducted (TH01-SZ)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±1.34 dB
Occupied Channel Bandwidth	±0.1 MHz
Conducted Power	±1.34 dB
Conducted Power Spectral Density	±1.32 dB
Frequency	±1.3 Hz

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.7 dB
---	--------

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.8 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.2 dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0 dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.3 dB
---	--------

----- THE END -----



Appendix A. Conducted Test Results

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Chen Ran	Temperature:	21~25	°C
Test Date:	2024/1/31~2024/5/30	Relative Humidity:	51~54	%

<u>TEST RESULTS DATA</u> <u>6dB and 99% Occupied Bandwidth</u>								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.015	0.668	0.50	Pass
BLE	1Mbps	1	19	2440	1.013	0.668	0.50	Pass
BLE	1Mbps	1	39	2480	1.015	0.670	0.50	Pass

<u>TEST RESULTS DATA</u> <u>Peak Power Table</u>										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	5.54	30.00	2.40	7.94	36.00	Pass
BLE	1Mbps	1	19	2440	3.64	30.00	2.40	6.04	36.00	Pass
BLE	1Mbps	1	37	2478	3.36	30.00	2.40	5.76	36.00	Pass
BLE	1Mbps	1	38	2479	1.28	30.00	2.40	3.68	36.00	Pass
BLE	1Mbps	1	39	2480	1.57	30.00	2.40	3.97	36.00	Pass

<u>TEST RESULTS DATA</u> <u>Average Power Table</u> <u>(Reporting Only)</u>						
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	0.65	5.30
BLE	1Mbps	1	19	2440	0.65	3.30
BLE	1Mbps	1	37	2478	0.65	3.00
BLE	1Mbps	1	38	2479	0.65	1.00
BLE	1Mbps	1	39	2480	0.65	1.20


Remark: Power setting is CH00: 4, CH19:2, CH37:4, CH38:2, CH39:4 .

<u>TEST RESULTS DATA</u> <u>Peak Power Density</u>									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	5.34	-10.87	2.40	8.00	Pass
BLE	1Mbps	1	19	2440	3.33	-13.12	2.40	8.00	Pass
BLE	1Mbps	1	39	2480	1.22	-15.21	2.40	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.




Appendix B. AC Conducted Emission Test Results





Test Engineer :	Liang FangMing	Temperature :	22~24°C
		Relative Humidity :	44~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : C001-SZ
Condition: FCC 15C_QP AC LISN 100063_N NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.15	26.83	-28.99	55.82	6.51	10.19	10.13	Average
2 *	0.15	44.23	-21.59	65.82	23.91	10.19	10.13	QP
3	0.21	19.40	-33.87	53.27	-1.00	10.25	10.15	Average
4	0.21	41.10	-22.17	63.27	20.70	10.25	10.15	QP
5	0.30	20.21	-30.16	50.37	-0.39	10.45	10.15	Average
6	0.30	34.31	-26.06	60.37	13.71	10.45	10.15	QP
7	0.34	18.13	-31.18	49.31	-2.40	10.37	10.16	Average
8	0.34	35.83	-23.48	59.31	15.30	10.37	10.16	QP
9	1.12	18.68	-27.32	46.00	-1.70	10.21	10.17	Average
10	1.12	31.48	-24.52	56.00	11.10	10.21	10.17	QP
11	4.07	15.49	-30.51	46.00	-5.30	10.47	10.32	Average
12	4.07	18.19	-37.81	56.00	-2.60	10.47	10.32	QP

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



Appendix C Radiated Spurious Emission Test Data

Test Engineer :	Zhaohui Liang	Relative Humidity :	48~49%
		Temperature :	24-25℃





Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Sample	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	1	Bluetooth-LE	00	2402	1Mbps	-	-
Mode 2	2400-2483.5	1	Bluetooth-LE	19	2440	1Mbps	-	-
Mode 3	2400-2483.5	1	Bluetooth-LE	39	2480	1Mbps	-	-
Mode 4	2400-2483.5	1	Bluetooth-LE	19	2440	1Mbps	-	LF
Mode 5	2400-2483.5	2	Bluetooth-LE	19	2440	1Mbps	-	-
Mode 6	2400-2483.5	1	Bluetooth-LE	38	2478	1Mbps	-	-
Mode 7	2400-2483.5	1	Bluetooth-LE	37	2476	1Mbps	-	-





Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	Bluetooth-LE	00	2385.92	38.88	54.00	-15.12	V	AVERAGE	Pass	Band Edge
1	Bluetooth-LE	00	4804.00	53.21	54.00	-0.79	H	Average	Pass	Harmonic
2	Bluetooth-LE	19	-	-	-	-	-	-	-	Band Edge
2	Bluetooth-LE	19	7320.00	53.49	54.00	-0.51	H	Average	Pass	Harmonic
3	Bluetooth-LE	39	2489.78	39.32	54.00	-14.68	H	AVERAGE	Pass	Band Edge
3	Bluetooth-LE	39	4960.00	51.26	54.00	-2.74	V	Average	Pass	Harmonic
4	Bluetooth-LE	19	527.61	35.85	46.00	-10.15	H	Peak	Pass	LF
5	Bluetooth-LE	19	2344.02	50.73	54.00	-3.27	V	AVERAGE	Pass	Band Edge
5	Bluetooth-LE	19	3252.52	51.15	54.00	-2.85	V	Average	Pass	Harmonic
6	Bluetooth-LE	38	2487.90	47.73	54.00	-6.27	V	AVERAGE	Pass	Band Edge
6	Bluetooth-LE	38	4956.00	52.35	54.00	-1.65	V	Average	Pass	Harmonic
7	Bluetooth-LE	37	-	-	-	-	-	-	-	Band Edge
7	Bluetooth-LE	37	4952.00	53.35	54.00	-0.65	V	Average	Pass	Harmonic



Mode	1																																																																																								
	Band Edge																																																																																								
	2400-2483.5_Bluetooth-LE_CH00_2402MHz																																																																																								
ANT	SISO																																																																																								
Pol.	Horizontal						Fundamental																																																																																		
Peak																																																																																									
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2378.88</td><td>49.12</td><td>74.00</td><td>-24.88</td><td>41.24</td><td>32.23</td><td>7.73</td><td>32.08</td><td>225</td><td>83</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2378.88	49.12	74.00	-24.88	41.24	32.23	7.73	32.08	225	83	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>78.74</td><td>-----</td><td>-----</td><td>70.75</td><td>32.28</td><td>7.79</td><td>32.08</td><td>225</td><td>83</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2402.00	78.74	-----	-----	70.75	32.28	7.79	32.08	225	83
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																		
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																	
1	2378.88	49.12	74.00	-24.88	41.24	32.23	7.73	32.08	225	83	PEAK																																																																														
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																		
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																	
1	2402.00	78.74	-----	-----	70.75	32.28	7.79	32.08	225	83	PEAK																																																																														
Avg																																																																																									
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2371.85</td><td>38.74</td><td>54.00</td><td>-15.26</td><td>30.88</td><td>32.22</td><td>7.71</td><td>32.07</td><td>225</td><td>83</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2371.85	38.74	54.00	-15.26	30.88	32.22	7.71	32.07	225	83	AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>77.53</td><td>-----</td><td>-----</td><td>69.54</td><td>32.28</td><td>7.79</td><td>32.08</td><td>225</td><td>83</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2402.00	77.53	-----	-----	69.54	32.28	7.79	32.08	225	83
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																		
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																	
1	2371.85	38.74	54.00	-15.26	30.88	32.22	7.71	32.07	225	83	AVERAGE																																																																														
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																		
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																	
1	2402.00	77.53	-----	-----	69.54	32.28	7.79	32.08	225	83	AVERAGE																																																																														





Mode	1																																																	
	Band Edge																																																	
	2400-2483.5_Bluetooth-LE_CH00_2402MHz																																																	
ANT	SISO																																																	
Pol.	Vertical																																																	
Peak	Fundamental																																																	
	Date: 2024-02-21																																																	
																																																		
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2378.99</td><td>49.35</td><td>74.00</td><td>-24.65</td><td>41.47</td><td>32.23</td><td>7.73</td><td>32.08</td><td>278</td><td>327</td><td>PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2378.99	49.35	74.00	-24.65	41.47	32.23	7.73	32.08	278	327	PEAK
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																									
1	2378.99	49.35	74.00	-24.65	41.47	32.23	7.73	32.08	278	327	PEAK																																							
Avg	Date: 2024-02-21																																																	
																																																		
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2378.99</td><td>49.35</td><td>74.00</td><td>-24.65</td><td>41.47</td><td>32.23</td><td>7.73</td><td>32.08</td><td>278</td><td>327</td><td>PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2378.99	49.35	74.00	-24.65	41.47	32.23	7.73	32.08	278	327
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																									
1	2378.99	49.35	74.00	-24.65	41.47	32.23	7.73	32.08	278	327	PEAK																																							
Peak	Date: 2024-02-21																																																	
																																																		
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>79.70</td><td>-----</td><td>-----</td><td>71.71</td><td>32.28</td><td>7.79</td><td>32.08</td><td>278</td><td>327</td><td>PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2402.00	79.70	-----	-----	71.71	32.28	7.79	32.08	278	327
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																									
1	2402.00	79.70	-----	-----	71.71	32.28	7.79	32.08	278	327	PEAK																																							
Avg	Date: 2024-02-21																																																	
																																																		
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>77.80</td><td>-----</td><td>-----</td><td>69.81</td><td>32.28</td><td>7.79</td><td>32.08</td><td>278</td><td>327</td><td>AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2402.00	77.80	-----	-----	69.81	32.28	7.79	32.08	278	327
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																									
1	2402.00	77.80	-----	-----	69.81	32.28	7.79	32.08	278	327	AVERAGE																																							







Mode	1																																																																										
	Harmonic																																																																										
	2400-2483.5_Bluetooth-LE_CH00_2402MHz																																																																										
ANT	SISO																																																																										
Pol.	Horizontal																																																																										
Peak Avg	Data: 1 Level (dBuV/m) Date: 2024-02-20 <table><thead><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4804.000</td><td>57.24</td><td>-16.76</td><td>74.00</td><td>62.92</td><td>34.82</td><td>11.08</td><td>51.58</td><td>341</td><td>304</td><td>Peak</td></tr><tr><td>2</td><td>4804.000</td><td>53.21</td><td>-0.79</td><td>54.00</td><td>58.89</td><td>34.82</td><td>11.08</td><td>51.58</td><td>341</td><td>304</td><td>Average</td></tr><tr><td>3</td><td>7206.000</td><td>57.78</td><td>-16.22</td><td>74.00</td><td>59.64</td><td>36.28</td><td>13.00</td><td>51.14</td><td>---</td><td>---</td><td>Peak</td></tr></tbody></table>												Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos		Freq	Level	Limit	Line	Level	Factor	Loss	Factor	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	4804.000	57.24	-16.76	74.00	62.92	34.82	11.08	51.58	341	304	Peak	2	4804.000	53.21	-0.79	54.00	58.89	34.82	11.08	51.58	341	304	Average	3	7206.000	57.78	-16.22	74.00	59.64	36.28	13.00	51.14	---	---	Peak
		Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos																																																																			
	Freq	Level	Limit	Line	Level	Factor	Loss	Factor	Remark																																																																		
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																	
	1	4804.000	57.24	-16.76	74.00	62.92	34.82	11.08	51.58	341	304	Peak																																																															
2	4804.000	53.21	-0.79	54.00	58.89	34.82	11.08	51.58	341	304	Average																																																																
3	7206.000	57.78	-16.22	74.00	59.64	36.28	13.00	51.14	---	---	Peak																																																																
Peak Avg	Data: 2 Level (dBuV/m) Date: 2024-02-20 <table><thead><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4804.000</td><td>55.88</td><td>-18.12</td><td>74.00</td><td>61.56</td><td>34.82</td><td>11.08</td><td>51.58</td><td>400</td><td>100</td><td>Peak</td></tr><tr><td>2</td><td>4804.000</td><td>52.29</td><td>-1.71</td><td>54.00</td><td>57.97</td><td>34.82</td><td>11.08</td><td>51.58</td><td>400</td><td>100</td><td>Average</td></tr><tr><td>3</td><td>7206.000</td><td>57.58</td><td>-16.42</td><td>74.00</td><td>59.44</td><td>36.28</td><td>13.00</td><td>51.14</td><td>---</td><td>---</td><td>Peak</td></tr></tbody></table>												Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos		Freq	Level	Limit	Line	Level	Factor	Loss	Factor	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	4804.000	55.88	-18.12	74.00	61.56	34.82	11.08	51.58	400	100	Peak	2	4804.000	52.29	-1.71	54.00	57.97	34.82	11.08	51.58	400	100	Average	3	7206.000	57.58	-16.42	74.00	59.44	36.28	13.00	51.14	---	---	Peak
		Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos																																																																			
	Freq	Level	Limit	Line	Level	Factor	Loss	Factor	Remark																																																																		
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																	
	1	4804.000	55.88	-18.12	74.00	61.56	34.82	11.08	51.58	400	100	Peak																																																															
2	4804.000	52.29	-1.71	54.00	57.97	34.82	11.08	51.58	400	100	Average																																																																
3	7206.000	57.58	-16.42	74.00	59.44	36.28	13.00	51.14	---	---	Peak																																																																

Remark: 7206MHz is harmonics emission which fall in the non-restricted bands, the limit is 20 dB below the highest emission level within the authorized band, test result is PASS.







Mode	2																																																																																																																																									
	Harmonic																																																																																																																																									
	2400-2483.5_Bluetooth-LE_CH19_2440MHz																																																																																																																																									
ANT	SISO																																																																																																																																									
Pol.	Horizontal					Vertical																																																																																																																																				
Peak Avg																																																																																																																																										
	<table><thead><tr><th></th><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4880.00</td><td>54.31</td><td>74.00</td><td>-19.69</td><td>59.91</td><td>34.85</td><td>11.10</td><td>51.55</td><td>262</td><td>77 Peak</td></tr><tr><td>2</td><td>4880.00</td><td>49.75</td><td>54.00</td><td>-4.25</td><td>55.35</td><td>34.85</td><td>11.10</td><td>51.55</td><td>262</td><td>77 Average</td></tr><tr><td>3</td><td>7320.00</td><td>58.38</td><td>74.00</td><td>-15.62</td><td>60.12</td><td>36.33</td><td>13.09</td><td>51.16</td><td>100</td><td>45 Peak</td></tr><tr><td>4</td><td>7320.00</td><td>53.49</td><td>54.00</td><td>-0.51</td><td>55.23</td><td>36.33</td><td>13.09</td><td>51.16</td><td>100</td><td>45 Average</td></tr></tbody></table>						Freq	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	4880.00	54.31	74.00	-19.69	59.91	34.85	11.10	51.55	262	77 Peak	2	4880.00	49.75	54.00	-4.25	55.35	34.85	11.10	51.55	262	77 Average	3	7320.00	58.38	74.00	-15.62	60.12	36.33	13.09	51.16	100	45 Peak	4	7320.00	53.49	54.00	-0.51	55.23	36.33	13.09	51.16	100	45 Average	<table><thead><tr><th></th><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4880.00</td><td>54.86</td><td>74.00</td><td>-19.14</td><td>60.46</td><td>34.85</td><td>11.10</td><td>51.55</td><td>131</td><td>77 Peak</td></tr><tr><td>2</td><td>4880.00</td><td>50.04</td><td>54.00</td><td>-3.96</td><td>55.64</td><td>34.85</td><td>11.10</td><td>51.55</td><td>131</td><td>77 Average</td></tr><tr><td>3</td><td>7320.00</td><td>56.83</td><td>74.00</td><td>-17.17</td><td>58.57</td><td>36.33</td><td>13.09</td><td>51.16</td><td>349</td><td>51 Peak</td></tr><tr><td>4</td><td>7320.00</td><td>52.60</td><td>54.00</td><td>-1.40</td><td>54.34</td><td>36.33</td><td>13.09</td><td>51.16</td><td>349</td><td>51 Average</td></tr></tbody></table>						Freq	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	4880.00	54.86	74.00	-19.14	60.46	34.85	11.10	51.55	131	77 Peak	2	4880.00	50.04	54.00	-3.96	55.64	34.85	11.10	51.55	131	77 Average	3	7320.00	56.83	74.00	-17.17	58.57	36.33	13.09	51.16	349	51 Peak	4	7320.00	52.60	54.00	-1.40	54.34	36.33	13.09	51.16	349	51 Average
		Freq	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																																																																
	1	4880.00	54.31	74.00	-19.69	59.91	34.85	11.10	51.55	262	77 Peak																																																																																																																															
2	4880.00	49.75	54.00	-4.25	55.35	34.85	11.10	51.55	262	77 Average																																																																																																																																
3	7320.00	58.38	74.00	-15.62	60.12	36.33	13.09	51.16	100	45 Peak																																																																																																																																
4	7320.00	53.49	54.00	-0.51	55.23	36.33	13.09	51.16	100	45 Average																																																																																																																																
	Freq	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																																																																	
1	4880.00	54.86	74.00	-19.14	60.46	34.85	11.10	51.55	131	77 Peak																																																																																																																																
2	4880.00	50.04	54.00	-3.96	55.64	34.85	11.10	51.55	131	77 Average																																																																																																																																
3	7320.00	56.83	74.00	-17.17	58.57	36.33	13.09	51.16	349	51 Peak																																																																																																																																
4	7320.00	52.60	54.00	-1.40	54.34	36.33	13.09	51.16	349	51 Average																																																																																																																																



Mode	3																																																																																	
	Band Edge																																																																																	
	2400-2483.5_Bluetooth-LE_CH39_2480MHz																																																																																	
ANT	SISO																																																																																	
Pol.	Horizontal	Fundamental																																																																																
Peak	Level (dBuV/m) Date: 2024-02-04  <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2493.96</td><td>49.74</td><td>74.00</td><td>-24.26</td><td>41.46</td><td>32.49</td><td>7.89</td><td>32.10</td><td>387</td><td>348</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2493.96	49.74	74.00	-24.26	41.46	32.49	7.89	32.10	387	348	PEAK	Level (dBuV/m) Date: 2024-02-04  <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>80.01</td><td>-----</td><td>-----</td><td>71.78</td><td>32.46</td><td>7.87</td><td>32.10</td><td>387</td><td>348</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2480.00	80.01	-----	-----	71.78	32.46	7.87	32.10	387	348	PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																									
1	2493.96	49.74	74.00	-24.26	41.46	32.49	7.89	32.10	387	348	PEAK																																																																							
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																									
1	2480.00	80.01	-----	-----	71.78	32.46	7.87	32.10	387	348	PEAK																																																																							
Avg	Level (dBuV/m) Date: 2024-02-04  <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2489.78</td><td>39.32</td><td>54.00</td><td>-14.68</td><td>31.06</td><td>32.48</td><td>7.88</td><td>32.10</td><td>387</td><td>348</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2489.78	39.32	54.00	-14.68	31.06	32.48	7.88	32.10	387	348	AVERAGE	Level (dBuV/m) Date: 2024-02-04  <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>78.91</td><td>-----</td><td>-----</td><td>70.68</td><td>32.46</td><td>7.87</td><td>32.10</td><td>387</td><td>348</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2480.00	78.91	-----	-----	70.68	32.46	7.87	32.10	387	348	AVERAGE
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																									
1	2489.78	39.32	54.00	-14.68	31.06	32.48	7.88	32.10	387	348	AVERAGE																																																																							
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																									
1	2480.00	78.91	-----	-----	70.68	32.46	7.87	32.10	387	348	AVERAGE																																																																							



Mode	3																																																																																									
	Band Edge																																																																																									
	2400-2483.5_Bluetooth-LE_CH39_2480MHz																																																																																									
ANT	SISO																																																																																									
Pol.	Vertical						Fundamental																																																																																			
Peak																																																																																										
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2489.08</td><td>49.98</td><td>74.00</td><td>-24.02</td><td>41.72</td><td>32.48</td><td>7.88</td><td>32.10</td><td>368</td><td>295</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2489.08	49.98	74.00	-24.02	41.72	32.48	7.88	32.10	368	295	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>81.36</td><td>-----</td><td>-----</td><td>73.13</td><td>32.46</td><td>7.87</td><td>32.10</td><td>368</td><td>295</td><td>PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2480.00	81.36	-----	-----	73.13	32.46	7.87	32.10	368	295
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																	
1	2489.08	49.98	74.00	-24.02	41.72	32.48	7.88	32.10	368	295	PEAK																																																																															
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																	
1	2480.00	81.36	-----	-----	73.13	32.46	7.87	32.10	368	295	PEAK																																																																															
Avg																																																																																										
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2490.10</td><td>39.23</td><td>54.00</td><td>-14.77</td><td>30.97</td><td>32.48</td><td>7.88</td><td>32.10</td><td>368</td><td>295</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2490.10	39.23	54.00	-14.77	30.97	32.48	7.88	32.10	368	295	AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>80.17</td><td>-----</td><td>-----</td><td>71.94</td><td>32.46</td><td>7.87</td><td>32.10</td><td>368</td><td>295</td><td>AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2480.00	80.17	-----	-----	71.94	32.46	7.87	32.10	368	295
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																	
1	2490.10	39.23	54.00	-14.77	30.97	32.48	7.88	32.10	368	295	AVERAGE																																																																															
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																	
1	2480.00	80.17	-----	-----	71.94	32.46	7.87	32.10	368	295	AVERAGE																																																																															



Mode	3																																																																																																																																																							
	Harmonic																																																																																																																																																							
	2400-2483.5_Bluetooth-LE_CH39_2480MHz																																																																																																																																																							
ANT	SISO																																																																																																																																																							
Pol.	Horizontal						Vertical																																																																																																																																																	
Peak Avg	Level (dBuV/m) Date: 2024-02-04 <table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4960.00</td><td>54.51</td><td>74.00</td><td>-19.49</td><td>60.00</td><td>34.88</td><td>11.14</td><td>51.51</td><td>167</td><td>324</td><td>Peak</td></tr><tr><td>2</td><td>4960.00</td><td>50.03</td><td>54.00</td><td>-3.97</td><td>55.52</td><td>34.88</td><td>11.14</td><td>51.51</td><td>167</td><td>324</td><td>Average</td></tr><tr><td>3</td><td>7440.00</td><td>49.15</td><td>74.00</td><td>-24.85</td><td>50.99</td><td>36.38</td><td>12.97</td><td>51.19</td><td>--</td><td>--</td><td>Peak</td></tr></table>								Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4960.00	54.51	74.00	-19.49	60.00	34.88	11.14	51.51	167	324	Peak	2	4960.00	50.03	54.00	-3.97	55.52	34.88	11.14	51.51	167	324	Average	3	7440.00	49.15	74.00	-24.85	50.99	36.38	12.97	51.19	--	--	Peak	Level (dBuV/m) Date: 2024-02-04 <table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4960.00</td><td>55.70</td><td>74.00</td><td>-18.30</td><td>61.19</td><td>34.88</td><td>11.14</td><td>51.51</td><td>135</td><td>77</td><td>Peak</td></tr><tr><td>2</td><td>4960.00</td><td>51.26</td><td>54.00</td><td>-2.74</td><td>56.75</td><td>34.88</td><td>11.14</td><td>51.51</td><td>135</td><td>77</td><td>Average</td></tr><tr><td>3</td><td>7440.00</td><td>49.48</td><td>74.00</td><td>-24.52</td><td>51.32</td><td>36.38</td><td>12.97</td><td>51.19</td><td>--</td><td>--</td><td>Peak</td></tr></table>								Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4960.00	55.70	74.00	-18.30	61.19	34.88	11.14	51.51	135	77	Peak	2	4960.00	51.26	54.00	-2.74	56.75	34.88	11.14	51.51	135	77	Average	3	7440.00	49.48	74.00	-24.52	51.32	36.38	12.97	51.19	--	--	Peak
			Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																												
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																																																
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																													
1	4960.00	54.51	74.00	-19.49	60.00	34.88	11.14	51.51	167	324	Peak																																																																																																																																													
2	4960.00	50.03	54.00	-3.97	55.52	34.88	11.14	51.51	167	324	Average																																																																																																																																													
3	7440.00	49.15	74.00	-24.85	50.99	36.38	12.97	51.19	--	--	Peak																																																																																																																																													
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																														
1	4960.00	55.70	74.00	-18.30	61.19	34.88	11.14	51.51	135	77	Peak																																																																																																																																													
2	4960.00	51.26	54.00	-2.74	56.75	34.88	11.14	51.51	135	77	Average																																																																																																																																													
3	7440.00	49.48	74.00	-24.52	51.32	36.38	12.97	51.19	--	--	Peak																																																																																																																																													



Mode	4																																																																																																																																																																																																											
	LF																																																																																																																																																																																																											
	2400-2483.5_Bluetooth-LE_CH19_2440MHz																																																																																																																																																																																																											
ANT	SISO																																																																																																																																																																																																											
Pol.	Horizontal						Vertical																																																																																																																																																																																																					
QP/ Peak	Level (dBuV/m) Date: 2024-02-05 Frequency (MHz) <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>56.19</td><td>19.86</td><td>40.00</td><td>-20.14</td><td>36.34</td><td>13.22</td><td>1.54</td><td>31.24</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>129.91</td><td>28.54</td><td>43.50</td><td>-14.96</td><td>39.59</td><td>18.00</td><td>2.09</td><td>31.14</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>301.60</td><td>31.48</td><td>46.00</td><td>-14.52</td><td>40.21</td><td>19.44</td><td>2.73</td><td>30.90</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>395.69</td><td>33.15</td><td>46.00</td><td>-12.85</td><td>38.99</td><td>21.79</td><td>3.08</td><td>30.71</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>527.61</td><td>35.85</td><td>46.00</td><td>-10.15</td><td>38.76</td><td>24.41</td><td>3.55</td><td>30.87</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>561.56</td><td>31.53</td><td>46.00</td><td>-14.47</td><td>33.91</td><td>24.98</td><td>3.64</td><td>31.00</td><td>--</td><td>--</td><td>Peak</td></tr></tbody></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	cm	deg		1	56.19	19.86	40.00	-20.14	36.34	13.22	1.54	31.24	--	--	Peak	2	129.91	28.54	43.50	-14.96	39.59	18.00	2.09	31.14	--	--	Peak	3	301.60	31.48	46.00	-14.52	40.21	19.44	2.73	30.90	--	--	Peak	4	395.69	33.15	46.00	-12.85	38.99	21.79	3.08	30.71	--	--	Peak	5	527.61	35.85	46.00	-10.15	38.76	24.41	3.55	30.87	--	--	Peak	6	561.56	31.53	46.00	-14.47	33.91	24.98	3.64	31.00	--	--	Peak	Level (dBuV/m) Date: 2024-02-05 Frequency (MHz) <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>45.52</td><td>27.36</td><td>40.00</td><td>-12.64</td><td>41.04</td><td>16.13</td><td>1.39</td><td>31.20</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>95.96</td><td>24.97</td><td>43.50</td><td>-18.53</td><td>38.21</td><td>16.18</td><td>1.82</td><td>31.24</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>191.99</td><td>23.99</td><td>43.50</td><td>-19.51</td><td>37.35</td><td>15.26</td><td>2.31</td><td>30.93</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>288.02</td><td>30.35</td><td>46.00</td><td>-15.65</td><td>39.30</td><td>19.28</td><td>2.67</td><td>30.90</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>395.69</td><td>29.00</td><td>46.00</td><td>-17.00</td><td>34.84</td><td>21.79</td><td>3.08</td><td>30.71</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>527.61</td><td>32.48</td><td>46.00</td><td>-13.52</td><td>35.39</td><td>24.41</td><td>3.55</td><td>30.87</td><td>--</td><td>--</td><td>Peak</td></tr></tbody></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	cm	deg		1	45.52	27.36	40.00	-12.64	41.04	16.13	1.39	31.20	--	--	Peak	2	95.96	24.97	43.50	-18.53	38.21	16.18	1.82	31.24	--	--	Peak	3	191.99	23.99	43.50	-19.51	37.35	15.26	2.31	30.93	--	--	Peak	4	288.02	30.35	46.00	-15.65	39.30	19.28	2.67	30.90	--	--	Peak	5	395.69	29.00	46.00	-17.00	34.84	21.79	3.08	30.71	--	--	Peak	6	527.61	32.48	46.00	-13.52	35.39	24.41	3.55	30.87	--	--	Peak
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																	
1	56.19	19.86	40.00	-20.14	36.34	13.22	1.54	31.24	--	--	Peak																																																																																																																																																																																																	
2	129.91	28.54	43.50	-14.96	39.59	18.00	2.09	31.14	--	--	Peak																																																																																																																																																																																																	
3	301.60	31.48	46.00	-14.52	40.21	19.44	2.73	30.90	--	--	Peak																																																																																																																																																																																																	
4	395.69	33.15	46.00	-12.85	38.99	21.79	3.08	30.71	--	--	Peak																																																																																																																																																																																																	
5	527.61	35.85	46.00	-10.15	38.76	24.41	3.55	30.87	--	--	Peak																																																																																																																																																																																																	
6	561.56	31.53	46.00	-14.47	33.91	24.98	3.64	31.00	--	--	Peak																																																																																																																																																																																																	
Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																																																																	
MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																		
1	45.52	27.36	40.00	-12.64	41.04	16.13	1.39	31.20	--	--	Peak																																																																																																																																																																																																	
2	95.96	24.97	43.50	-18.53	38.21	16.18	1.82	31.24	--	--	Peak																																																																																																																																																																																																	
3	191.99	23.99	43.50	-19.51	37.35	15.26	2.31	30.93	--	--	Peak																																																																																																																																																																																																	
4	288.02	30.35	46.00	-15.65	39.30	19.28	2.67	30.90	--	--	Peak																																																																																																																																																																																																	
5	395.69	29.00	46.00	-17.00	34.84	21.79	3.08	30.71	--	--	Peak																																																																																																																																																																																																	
6	527.61	32.48	46.00	-13.52	35.39	24.41	3.55	30.87	--	--	Peak																																																																																																																																																																																																	



Mode	5																																																																																	
	Band Edge - L																																																																																	
	2400-2483.5_Bluetooth-LE_CH19_2440MHz																																																																																	
ANT	SISO																																																																																	
Pol.	Horizontal	Fundamental																																																																																
Peak	Level (dBuV/m) Date: 2024-02-05 Frequency (MHz) <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2343.88</td><td>51.53</td><td>74.00</td><td>-22.47</td><td>43.81</td><td>32.16</td><td>7.63</td><td>32.07</td><td>121</td><td>86</td><td>PEAK</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2343.88	51.53	74.00	-22.47	43.81	32.16	7.63	32.07	121	86	PEAK	Level (dBuV/m) Date: 2024-02-05 Frequency (MHz) <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>92.12</td><td>-----</td><td>-----</td><td>84.00</td><td>32.37</td><td>7.84</td><td>32.09</td><td>121</td><td>86</td><td>PEAK</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2440.00	92.12	-----	-----	84.00	32.37	7.84	32.09	121	86	PEAK
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																									
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2343.88	51.53	74.00	-22.47	43.81	32.16	7.63	32.07	121	86	PEAK																																																																							
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2440.00	92.12	-----	-----	84.00	32.37	7.84	32.09	121	86	PEAK																																																																							
Avg	Level (dBuV/m) Date: 2024-02-05 Frequency (MHz) <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2343.88</td><td>42.33</td><td>54.00</td><td>-11.67</td><td>34.61</td><td>32.16</td><td>7.63</td><td>32.07</td><td>121</td><td>86</td><td>AVERAGE</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2343.88	42.33	54.00	-11.67	34.61	32.16	7.63	32.07	121	86	AVERAGE	Level (dBuV/m) Date: 2024-02-05 Frequency (MHz) <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>90.97</td><td>-----</td><td>-----</td><td>82.85</td><td>32.37</td><td>7.84</td><td>32.09</td><td>121</td><td>86</td><td>AVERAGE</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2440.00	90.97	-----	-----	82.85	32.37	7.84	32.09	121	86	AVERAGE
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2343.88	42.33	54.00	-11.67	34.61	32.16	7.63	32.07	121	86	AVERAGE																																																																							
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2440.00	90.97	-----	-----	82.85	32.37	7.84	32.09	121	86	AVERAGE																																																																							



Mode	5									
	Band Edge - R									
	2400-2483.5_Bluetooth-LE_CH19_2440MHz									
ANT	SISO									
Pol.	Horizontal					Fundamental				
Peak	Level (dBuV/m) <									



Mode	5	
	Band Edge - L	
	2400-2483.5_Bluetooth-LE_CH19_2440MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak		



Mode	5																																											
	Band Edge - R																																											
	2400-2483.5_Bluetooth-LE_CH19_2440MHz																																											
ANT	SISO																																											
Pol.	Vertical	Fundamental																																										
Peak	Date: 2024-02-05 PEAK_BE_74 <table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2487.96</td><td>54.48</td><td>74.00</td><td>-19.52</td><td>46.23</td><td>32.47</td><td>7.88</td><td>32.10</td><td>209</td><td>65</td><td>PEAK</td></tr></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2487.96	54.48	74.00	-19.52	46.23	32.47	7.88	32.10	209	65	PEAK	Blank
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																				
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark																																			
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																			
1	2487.96	54.48	74.00	-19.52	46.23	32.47	7.88	32.10	209	65	PEAK																																	
Avg	Date: 2024-02-05 AVG_BE_54 <table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2487.89</td><td>47.82</td><td>54.00</td><td>-6.18</td><td>39.57</td><td>32.47</td><td>7.88</td><td>32.10</td><td>209</td><td>65</td><td>AVERAGE</td></tr></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2487.89	47.82	54.00	-6.18	39.57	32.47	7.88	32.10	209	65	AVERAGE	Blank
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																				
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark																																			
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																			
1	2487.89	47.82	54.00	-6.18	39.57	32.47	7.88	32.10	209	65	AVERAGE																																	







Mode	5																																																																																																																																																																			
	Harmonic																																																																																																																																																																			
	2400-2483.5_Bluetooth-LE_CH19_2440MHz																																																																																																																																																																			
ANT	SISO																																																																																																																																																																			
Pol.	Horizontal						Vertical																																																																																																																																																													
Peak Avg	Level (dBuV/m) Date: 2024-02-05 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>51.05</td><td>74.00</td><td>-22.95</td><td>56.65</td><td>34.85</td><td>11.10</td><td>51.55</td><td>400</td><td>324</td><td>Peak</td></tr><tr><td>2</td><td>4880.00</td><td>44.65</td><td>54.00</td><td>-9.35</td><td>50.25</td><td>34.85</td><td>11.10</td><td>51.55</td><td>400</td><td>324</td><td>Average</td></tr><tr><td>3</td><td>7320.00</td><td>47.88</td><td>74.00</td><td>-26.12</td><td>49.62</td><td>36.33</td><td>13.09</td><td>51.16</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4880.00	51.05	74.00	-22.95	56.65	34.85	11.10	51.55	400	324	Peak	2	4880.00	44.65	54.00	-9.35	50.25	34.85	11.10	51.55	400	324	Average	3	7320.00	47.88	74.00	-26.12	49.62	36.33	13.09	51.16	--	--	Peak	Level (dBuV/m) Date: 2024-02-05 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>3252.52</td><td>53.64</td><td>74.00</td><td>-20.36</td><td>61.98</td><td>34.55</td><td>9.01</td><td>51.90</td><td>291</td><td>91</td><td>Peak</td></tr><tr><td>2</td><td>3252.52</td><td>51.15</td><td>54.00</td><td>-2.85</td><td>59.49</td><td>34.55</td><td>9.01</td><td>51.90</td><td>291</td><td>91</td><td>Average</td></tr><tr><td>3</td><td>4880.00</td><td>52.65</td><td>74.00</td><td>-21.35</td><td>58.25</td><td>34.85</td><td>11.10</td><td>51.55</td><td>143</td><td>39</td><td>Peak</td></tr><tr><td>4</td><td>4880.00</td><td>48.07</td><td>54.00</td><td>-5.93</td><td>53.67</td><td>34.85</td><td>11.10</td><td>51.55</td><td>143</td><td>39</td><td>Average</td></tr><tr><td>5</td><td>7320.00</td><td>49.97</td><td>74.00</td><td>-24.03</td><td>51.71</td><td>36.33</td><td>13.09</td><td>51.16</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	3252.52	53.64	74.00	-20.36	61.98	34.55	9.01	51.90	291	91	Peak	2	3252.52	51.15	54.00	-2.85	59.49	34.55	9.01	51.90	291	91	Average	3	4880.00	52.65	74.00	-21.35	58.25	34.85	11.10	51.55	143	39	Peak	4	4880.00	48.07	54.00	-5.93	53.67	34.85	11.10	51.55	143	39	Average	5	7320.00	49.97	74.00	-24.03	51.71	36.33	13.09	51.16	--	--	Peak
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																																																												
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																										
1	4880.00	51.05	74.00	-22.95	56.65	34.85	11.10	51.55	400	324	Peak																																																																																																																																																									
2	4880.00	44.65	54.00	-9.35	50.25	34.85	11.10	51.55	400	324	Average																																																																																																																																																									
3	7320.00	47.88	74.00	-26.12	49.62	36.33	13.09	51.16	--	--	Peak																																																																																																																																																									
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																																																																												
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																											
1	3252.52	53.64	74.00	-20.36	61.98	34.55	9.01	51.90	291	91	Peak																																																																																																																																																									
2	3252.52	51.15	54.00	-2.85	59.49	34.55	9.01	51.90	291	91	Average																																																																																																																																																									
3	4880.00	52.65	74.00	-21.35	58.25	34.85	11.10	51.55	143	39	Peak																																																																																																																																																									
4	4880.00	48.07	54.00	-5.93	53.67	34.85	11.10	51.55	143	39	Average																																																																																																																																																									
5	7320.00	49.97	74.00	-24.03	51.71	36.33	13.09	51.16	--	--	Peak																																																																																																																																																									



Mode	6																																																																																										
	Band Edge																																																																																										
	2400-2483.5_Bluetooth-LE_CH38_2478MHz																																																																																										
ANT	SISO																																																																																										
Pol.	Horizontal						Fundamental																																																																																				
Peak	Level (dBuV/m) Date: 2024-05-29 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2488.19</td><td>52.25</td><td>74.00</td><td>-21.75</td><td>44.00</td><td>32.47</td><td>7.88</td><td>32.10</td><td>300</td><td>333</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2488.19	52.25	74.00	-21.75	44.00	32.47	7.88	32.10	300	333	PEAK	Level (dBuV/m) Date: 2024-05-29 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2478.00</td><td>91.01</td><td>-----</td><td>-----</td><td>82.78</td><td>32.45</td><td>7.87</td><td>32.09</td><td>300</td><td>333</td><td>PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2478.00	91.01	-----	-----	82.78	32.45	7.87	32.09	300	333	PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																		
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2488.19	52.25	74.00	-21.75	44.00	32.47	7.88	32.10	300	333	PEAK																																																																																
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2478.00	91.01	-----	-----	82.78	32.45	7.87	32.09	300	333	PEAK																																																																																
Avg	Level (dBuV/m) Date: 2024-05-29 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2488.01</td><td>43.91</td><td>54.00</td><td>-10.09</td><td>35.66</td><td>32.47</td><td>7.88</td><td>32.10</td><td>300</td><td>333</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2488.01	43.91	54.00	-10.09	35.66	32.47	7.88	32.10	300	333	AVERAGE	Level (dBuV/m) Date: 2024-05-29 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2478.00</td><td>89.90</td><td>-----</td><td>-----</td><td>81.67</td><td>32.45</td><td>7.87</td><td>32.09</td><td>300</td><td>333</td><td>AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2478.00	89.90	-----	-----	81.67	32.45	7.87	32.09	300	333	AVERAGE
		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																		
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2488.01	43.91	54.00	-10.09	35.66	32.47	7.88	32.10	300	333	AVERAGE																																																																																
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2478.00	89.90	-----	-----	81.67	32.45	7.87	32.09	300	333	AVERAGE																																																																																



Mode	6																																																																																													
	Band Edge																																																																																													
	2400-2483.5_Bluetooth-LE_CH38_2478MHz																																																																																													
ANT	SISO																																																																																													
Pol.	Vertical						Fundamental																																																																																							
Peak																																																																																														
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2487.64</td><td>54.62</td><td>74.00</td><td>-19.38</td><td>46.37</td><td>32.47</td><td>7.88</td><td>32.10</td><td>300</td><td>8</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2487.64	54.62	74.00	-19.38	46.37	32.47	7.88	32.10	300	8	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2478.00</td><td>95.04</td><td>-----</td><td>-----</td><td>86.81</td><td>32.45</td><td>7.87</td><td>32.09</td><td>300</td><td>8</td><td>PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2478.00	95.04	-----	-----	86.81	32.45	7.87	32.09	300	8
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																				
1	2487.64	54.62	74.00	-19.38	46.37	32.47	7.88	32.10	300	8	PEAK																																																																																			
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																				
1	2478.00	95.04	-----	-----	86.81	32.45	7.87	32.09	300	8	PEAK																																																																																			
Avg																																																																																														
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2487.90</td><td>47.73</td><td>54.00</td><td>-6.27</td><td>39.48</td><td>32.47</td><td>7.88</td><td>32.10</td><td>300</td><td>8</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2487.90	47.73	54.00	-6.27	39.48	32.47	7.88	32.10	300	8	AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2478.00</td><td>94.04</td><td>-----</td><td>-----</td><td>85.81</td><td>32.45</td><td>7.87</td><td>32.09</td><td>300</td><td>8</td><td>AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2478.00	94.04	-----	-----	85.81	32.45	7.87	32.09	300	8
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																				
1	2487.90	47.73	54.00	-6.27	39.48	32.47	7.88	32.10	300	8	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																				
1	2478.00	94.04	-----	-----	85.81	32.45	7.87	32.09	300	8	AVERAGE																																																																																			



Mode	6																																																																																																																																																																																
	Harmonic																																																																																																																																																																																
	2400-2483.5_Bluetooth-LE_CH38_2478MHz																																																																																																																																																																																
ANT	SISO																																																																																																																																																																																
Pol.	Horizontal						Vertical																																																																																																																																																																										
Peak Avg	Level (dBuV/m) Date: 2024-05-29 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 3000 6000 9000 12000 15000 18000 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>3304.00</td><td>49.09</td><td>74.00</td><td>-24.91</td><td>57.38</td><td>34.58</td><td>9.03</td><td>51.90</td><td>363</td><td>310 Peak</td></tr><tr><td>2</td><td>3304.00</td><td>45.07</td><td>54.00</td><td>-8.93</td><td>53.36</td><td>34.58</td><td>9.03</td><td>51.90</td><td>363</td><td>310 Average</td></tr><tr><td>3</td><td>4956.00</td><td>52.34</td><td>74.00</td><td>-21.66</td><td>57.85</td><td>34.88</td><td>11.13</td><td>51.52</td><td>345</td><td>25 Peak</td></tr><tr><td>4</td><td>4956.00</td><td>48.13</td><td>54.00</td><td>-5.87</td><td>53.64</td><td>34.88</td><td>11.13</td><td>51.52</td><td>345</td><td>25 Average</td></tr><tr><td>5</td><td>7434.00</td><td>47.20</td><td>74.00</td><td>-26.80</td><td>49.03</td><td>36.37</td><td>12.99</td><td>51.19</td><td>--</td><td>-- Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	3304.00	49.09	74.00	-24.91	57.38	34.58	9.03	51.90	363	310 Peak	2	3304.00	45.07	54.00	-8.93	53.36	34.58	9.03	51.90	363	310 Average	3	4956.00	52.34	74.00	-21.66	57.85	34.88	11.13	51.52	345	25 Peak	4	4956.00	48.13	54.00	-5.87	53.64	34.88	11.13	51.52	345	25 Average	5	7434.00	47.20	74.00	-26.80	49.03	36.37	12.99	51.19	--	-- Peak	Level (dBuV/m) Date: 2024-05-29 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 3000 6000 9000 12000 15000 18000 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>3304.00</td><td>51.37</td><td>74.00</td><td>-22.63</td><td>59.66</td><td>34.58</td><td>9.03</td><td>51.90</td><td>382</td><td>90 Peak</td></tr><tr><td>2</td><td>3304.00</td><td>49.02</td><td>54.00</td><td>-4.98</td><td>57.31</td><td>34.58</td><td>9.03</td><td>51.90</td><td>382</td><td>90 Average</td></tr><tr><td>3</td><td>4956.00</td><td>56.41</td><td>74.00</td><td>-17.59</td><td>61.92</td><td>34.88</td><td>11.13</td><td>51.52</td><td>233</td><td>66 Peak</td></tr><tr><td>4</td><td>4956.00</td><td>52.35</td><td>54.00</td><td>-1.65</td><td>57.86</td><td>34.88</td><td>11.13</td><td>51.52</td><td>233</td><td>66 Average</td></tr><tr><td>5</td><td>7434.00</td><td>47.51</td><td>74.00</td><td>-26.49</td><td>49.34</td><td>36.37</td><td>12.99</td><td>51.19</td><td>--</td><td>-- Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	3304.00	51.37	74.00	-22.63	59.66	34.58	9.03	51.90	382	90 Peak	2	3304.00	49.02	54.00	-4.98	57.31	34.58	9.03	51.90	382	90 Average	3	4956.00	56.41	74.00	-17.59	61.92	34.88	11.13	51.52	233	66 Peak	4	4956.00	52.35	54.00	-1.65	57.86	34.88	11.13	51.52	233	66 Average	5	7434.00	47.51	74.00	-26.49	49.34	36.37	12.99	51.19	--	-- Peak
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																								
1	3304.00	49.09	74.00	-24.91	57.38	34.58	9.03	51.90	363	310 Peak																																																																																																																																																																							
2	3304.00	45.07	54.00	-8.93	53.36	34.58	9.03	51.90	363	310 Average																																																																																																																																																																							
3	4956.00	52.34	74.00	-21.66	57.85	34.88	11.13	51.52	345	25 Peak																																																																																																																																																																							
4	4956.00	48.13	54.00	-5.87	53.64	34.88	11.13	51.52	345	25 Average																																																																																																																																																																							
5	7434.00	47.20	74.00	-26.80	49.03	36.37	12.99	51.19	--	-- Peak																																																																																																																																																																							
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																								
1	3304.00	51.37	74.00	-22.63	59.66	34.58	9.03	51.90	382	90 Peak																																																																																																																																																																							
2	3304.00	49.02	54.00	-4.98	57.31	34.58	9.03	51.90	382	90 Average																																																																																																																																																																							
3	4956.00	56.41	74.00	-17.59	61.92	34.88	11.13	51.52	233	66 Peak																																																																																																																																																																							
4	4956.00	52.35	54.00	-1.65	57.86	34.88	11.13	51.52	233	66 Average																																																																																																																																																																							
5	7434.00	47.51	74.00	-26.49	49.34	36.37	12.99	51.19	--	-- Peak																																																																																																																																																																							



Mode	7																																																																																																																																																																																																								
	Harmonic																																																																																																																																																																																																								
	2400-2483.5_Bluetooth-LE_CH37_2476MHz																																																																																																																																																																																																								
ANT	SISO																																																																																																																																																																																																								
Pol.	Horizontal						Vertical																																																																																																																																																																																																		
Peak Avg	Level (dBuV/m) Date: 2024-05-29 <table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>3300.00</td><td>52.49</td><td>74.00</td><td>-21.51</td><td>60.79</td><td>34.58</td><td>9.02</td><td>51.90</td><td>185</td><td>75</td><td>Peak</td></tr><tr><td>2</td><td>3300.00</td><td>48.35</td><td>54.00</td><td>-5.65</td><td>56.65</td><td>34.58</td><td>9.02</td><td>51.90</td><td>185</td><td>75</td><td>Average</td></tr><tr><td>3</td><td>4952.00</td><td>54.05</td><td>74.00</td><td>-19.95</td><td>59.56</td><td>34.88</td><td>11.13</td><td>51.52</td><td>395</td><td>318</td><td>Peak</td></tr><tr><td>4</td><td>4952.00</td><td>48.64</td><td>54.00</td><td>-5.36</td><td>54.15</td><td>34.88</td><td>11.13</td><td>51.52</td><td>395</td><td>318</td><td>Average</td></tr><tr><td>5</td><td>7428.00</td><td>49.39</td><td>74.00</td><td>-24.61</td><td>51.20</td><td>36.37</td><td>13.01</td><td>51.19</td><td>--</td><td>--</td><td>Peak</td></tr></table>								Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	3300.00	52.49	74.00	-21.51	60.79	34.58	9.02	51.90	185	75	Peak	2	3300.00	48.35	54.00	-5.65	56.65	34.58	9.02	51.90	185	75	Average	3	4952.00	54.05	74.00	-19.95	59.56	34.88	11.13	51.52	395	318	Peak	4	4952.00	48.64	54.00	-5.36	54.15	34.88	11.13	51.52	395	318	Average	5	7428.00	49.39	74.00	-24.61	51.20	36.37	13.01	51.19	--	--	Peak	Level (dBuV/m) Date: 2024-05-29 <table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>3300.00</td><td>55.96</td><td>74.00</td><td>-18.04</td><td>64.26</td><td>34.58</td><td>9.02</td><td>51.90</td><td>178</td><td>77</td><td>Peak</td></tr><tr><td>2</td><td>3300.00</td><td>53.20</td><td>54.00</td><td>-0.80</td><td>61.50</td><td>34.58</td><td>9.02</td><td>51.90</td><td>178</td><td>77</td><td>Average</td></tr><tr><td>3</td><td>4952.00</td><td>57.55</td><td>74.00</td><td>-16.45</td><td>63.06</td><td>34.88</td><td>11.13</td><td>51.52</td><td>173</td><td>78</td><td>Peak</td></tr><tr><td>4</td><td>4952.00</td><td>53.35</td><td>54.00</td><td>-0.65</td><td>58.86</td><td>34.88</td><td>11.13</td><td>51.52</td><td>173</td><td>78</td><td>Average</td></tr><tr><td>5</td><td>7428.00</td><td>48.65</td><td>74.00</td><td>-25.35</td><td>50.46</td><td>36.37</td><td>13.01</td><td>51.19</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	3300.00	55.96	74.00	-18.04	64.26	34.58	9.02	51.90	178	77	Peak	2	3300.00	53.20	54.00	-0.80	61.50	34.58	9.02	51.90	178	77	Average	3	4952.00	57.55	74.00	-16.45	63.06	34.88	11.13	51.52	173	78	Peak	4	4952.00	53.35	54.00	-0.65	58.86	34.88	11.13	51.52	173	78	Average	5	7428.00	48.65	74.00	-25.35	50.46	36.37	13.01	51.19	--	--	Peak
			Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																
1	3300.00	52.49	74.00	-21.51	60.79	34.58	9.02	51.90	185	75	Peak																																																																																																																																																																																														
2	3300.00	48.35	54.00	-5.65	56.65	34.58	9.02	51.90	185	75	Average																																																																																																																																																																																														
3	4952.00	54.05	74.00	-19.95	59.56	34.88	11.13	51.52	395	318	Peak																																																																																																																																																																																														
4	4952.00	48.64	54.00	-5.36	54.15	34.88	11.13	51.52	395	318	Average																																																																																																																																																																																														
5	7428.00	49.39	74.00	-24.61	51.20	36.37	13.01	51.19	--	--	Peak																																																																																																																																																																																														
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																
1	3300.00	55.96	74.00	-18.04	64.26	34.58	9.02	51.90	178	77	Peak																																																																																																																																																																																														
2	3300.00	53.20	54.00	-0.80	61.50	34.58	9.02	51.90	178	77	Average																																																																																																																																																																																														
3	4952.00	57.55	74.00	-16.45	63.06	34.88	11.13	51.52	173	78	Peak																																																																																																																																																																																														
4	4952.00	53.35	54.00	-0.65	58.86	34.88	11.13	51.52	173	78	Average																																																																																																																																																																																														
5	7428.00	48.65	74.00	-25.35	50.46	36.37	13.01	51.19	--	--	Peak																																																																																																																																																																																														




Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
Bluetooth LE 1Mbps for Sample 1	86.13	2.159	0.463	1KHz
Bluetooth LE 1Mbps for Sample 2	86.4	2.16	0.463	1KHz

For Sample 1:

Bluetooth LE 1Mbps



For Sample 2:

Bluetooth LE 1Mbps

