

**KDB 447498 D03**  
**47 C.F.R. Part 1, Subpart I, Section 1.1310**  
**47 C.F.R. Part 2, Subpart J, Section 2.1091**

**RF EXPOSURE REPORT**

For

**Stand-Alone Media player**

**Model: MIXSTREAM PRO**

**Trade Name: Numark**

*Issued to*

**inMusic Brands, Inc.**  
**200 Scenic View Drive, Suite 201, Cumberland, RI 02864, U.S.A.**

Issued By

**Compliance Certification Services Inc.**  
**No.11, Wugong 6th Rd., Wugu Dist.,**  
**New Taipei City 24891, Taiwan. (R.O.C.)**

**Issued Date: May 20, 2021**

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## REVISION HISTORY

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	May 20, 2021	Initial Issue	ALL	Angel Cheng

**TABLE OF CONTENTS**

<b>1. LIMIT.....</b>	<b>4</b>
<b>2. EUT SPECIFICATION .....</b>	<b>5</b>
<b>3. TEST RESULTS.....</b>	<b>6</b>
<b>4. MAXIMUM PERMISSIBLE EXPOSURE.....</b>	<b>7</b>

## 1. TEST RESULT CERTIFICATION

### We hereby certify that:

The equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirement of the applicable standards. The test record, data evaluation and Equipment under Test (EUT) configurations represented herein are true and accurate accounts of the measurement of the sample's RF characteristics under the conditions specified in this report.

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
KDB 447498 D03 47 C.F.R. Part 1, Subpart I, Section 1.1310 47 C.F.R. Part 2, Subpart J, Section 2.1091	No non-compliance noted
Statements of Conformity	
Determining compliance shall be based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.	

Approved by:



---

Kevin Tsai  
Deputy Manager  
Compliance Certification Services Inc.

## 2. LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

## 3. EUT SPECIFICATION

<b>EUT</b>	Stand-Alone Media player		
<b>Model</b>	MIXSTREAM PRO		
<b>Brand</b>	<b>Numark</b>		
<b>RF Module</b>	Broadcom	<b>Model:</b>	AP6256
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> IEEE 802.11b/g, 802.11n HT20: 2412MHz~2462MHz <input checked="" type="checkbox"/> Bluetooth 4.0: 2402MHz~2480MHz		
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others		
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure ( $S = 5\text{mW/cm}^2$ ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ( $S=1\text{mW/cm}^2$ )		
<b>Antenna Specification</b>	WLAN EMBEDDEN ANTENNA / Gain: <b>4.6 dBi</b> (Numeric gain: 2.88)		
<b>Maximum Average output power</b>	IEEE 802.11b Mode : IEEE 802.11g Mode : IEEE 802.11n HT20 Mode : Bluetooth 4.0 Mode :	12.88 dBm 9.41 dBm 9.54 dBm 4.80 dBm	(19.409 mW) (8.730 mW) (8.995 mW) (3.020 mW)
<b>Maximum Tune up Power</b>	IEEE 802.11b Mode : IEEE 802.11g Mode : IEEE 802.11n HT20 Mode : Bluetooth 4.0 Mode :	13.50 dBm 10.00 dBm 10.00 dBm 5.50 dBm	(22.387 mW) (10.000 mW) (10.000 mW) (3.548 mW)
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A		
<b>Received Date</b>	February 01, 2021		
<b>Reported Date</b>	March 08, 2021		

### Remark:

1. RF power data reference report (T210201N03-RP1)
2. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.

## 4. TEST RESULTS

**No non-compliance noted.**

### Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{377}$$

Where  $E$  = Field strength in Volts / meter

$P$  = Power in Watts

$G$  = Numeric antenna gain

$d$  = Distance in meters

$S$  = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$P$  (mW) =  $P$  (W) / 1000 and

$d$  (cm) =  $d$  (m) / 100

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where  $d$  = Distance in cm

$P$  = Power in mW

$G$  = Numeric antenna gain

$S$  = Power density in mW / cm<sup>2</sup>

## 5. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using  $d = 20$  cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where  $P$  = Power in mW

$G$  = Numeric antenna gain

$S$  = Power density in mW / cm<sup>2</sup>

IEEE 802.11b Mode :

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )	Result
High	2462	22.387	2.88	20	0.0128	1	Pass

IEEE 802.11g Mode :

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )	Result
Mid	2437	10.000	2.88	20	0.0057	1	Pass

IEEE 802.11n HT 20 Mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )	Result
High	2462	10.000	2.88	20	0.0057	1	Pass

Bluetooth 4.0 Mode :

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )	Result
Low	2402	3.548	2.88	20	0.0020	1	Pass