



FCC PART 15.249

MEASUREMENT AND TEST REPORT

For

Shenzhen Bondidea Technology Co., Ltd.

10th Building, Honghualing Industrial Park, Qingshui Road,
Longgang, Shenzhen, Guangdong, China

FCC ID: Y4PBONDID11

Report Type: Original Report	Product Type: 2.4GHz Wireless Mouse
Test Engineer: Kvass Yang	<i>Kvass. Yang</i>
Report Number: RDG11050302	
Report Date: 2011-05-26	
Reviewed By: EMC Engineer	<i>Merry Zhao</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Shenzhen). This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk “★” (Rev.2)

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
TEST FACILITY	3
SYSTEM TEST CONFIGURATION.....	5
JUSTIFICATION	5
EQUIPMENT MODIFICATIONS	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS.....	6
FCC §15.203 - ANTENNA REQUIREMENT.....	7
APPLICABLE STANDARD	7
ANTENNA CONNECTOR CONSTRUCTION	7
FCC §15.205, §15.209 & §15.249 - RADIATED EMISSIONS	8
APPLICABLE STANDARDS.....	8
MEASUREMENT UNCERTAINTY	8
TEST EQUIPMENT SETUP	8
EUT SETUP	9
TEST EQUIPMENT LIST AND DETAILS.....	9
TEST PROCEDURE	10
CORRECTED AMPLITUDE & MARGIN CALCULATION	10
TEST RESULTS SUMMARY.....	10
TEST DATA	10
FCC §15.215(C) – 20 DB EMISSION BANDWIDTH.....	14
APPLICABLE STANDARD	14
TEST EQUIPMENT LIST AND DETAILS.....	14
TEST PROCEDURE	14
TEST DATA	14

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Shenzhen Bondidea Technology Co., Ltd.* 's product, model *BD-8508G (FCC ID: Y4PBONDID11)*, or the "EUT" as referred to in this report is a *2.4 GHz wireless mouse*, which measures approximately: 9.85 cm (L) x 6.20 cm (W) x 3.4 cm (H), rated input voltage: DC 2 * 1.5 V AAA battery

** All measurement and test data in this report was gathered from production sample serial number: 1105002 (Assigned by BACL, Shenzhen). The EUT was received on 2011-05-03.*

Objective

This Type approval report is prepared on behalf of *Shenzhen Bondidea Technology Co., LTD* in accordance with Part 2, Subpart J, and Part 15, Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.249 rules.

Related Submittal(s)/Grant(s)

FCC Part 15C and 15B submissions with FCC ID: Y4PBONDID8

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 guide accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION


Justification

The system was configured for testing in a engineering mode which was provided by the manufacturer.

Equipment Modifications

No modifications were made to the EUT tested.

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conduction Emissions	N/A
§15.205, §15.209 & §15.249	Radiated Emissions	Compliance
§15.215(c)	20 dB Emission Bandwidth	Compliance

Note: N/A: EUT is battery operation.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

Antenna Connector Construction

The EUT has a printed antenna on PCB, the antenna gain is 2.0 dBi, which in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.

Result: Compliant.

Please refer to the EUT photos.

FCC §15.205, §15.209 & §15.249 - RADIATED EMISSIONS**Applicable Standards**

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is ± 4.0 dB.

Test Equipment Setup

The spectrum analyzer or receiver is set as:

Below 1000 MHz:


RBW = 100 kHz / VBW = 300 kHz / Sweep = Auto

Above 1000 MHz:

Peak: RBW = 1MHz / VBW = 1MHz / Sweep = Auto

Average: RBW = 1MHz / VBW = 10 Hz / Sweep = Auto

EUT Setup



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209 and FCC 15.249 limits.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	8447E	1937A01046	2010-08-02	2011-08-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100224	2010-11-11	2011-11-10
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2010-07-05	2011-07-04
Mini-Circuits	Amplifier	ZVA-213+	T-E27H	2011-03-08	2012-03-07
Sunol Sciences	Horn Antenna	DRH-118	A052604	2011-05-05	2012-05-04
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2010-07-08	2011-07-07

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

For the radiated emissions test, maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 meter, and the EUT is placed on a turntable, which is 0.8 meter above ground plane, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209 & 15.249, with the worst margin reading of:

2.36 dB at 4810 MHz in the **Vertical** polarization for low channel


Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.2 kPa

The testing was performed by Kvass Yang on 2011-05-17

Test Mode: Transmitting

1) 30-1000 MHz (worst case):

Frequency (MHz)	Corrected Amplitude (dB μ V/m)	Antenna Height (cm)	Antenna Polarity (H/V)	Turntable Position (deg)	Correction Factor (dB)	Limit (dB μ V/m)	Margin (dB)
30.914000	27.8	173.0	V	115.0	-6.0	40.0	12.2
904.647250	26.2	373.0	V	74.0	-0.7	46.0	19.8
755.447000	25.6	217.0	V	62.0	-2.4	46.0	20.4
702.453000	25.2	357.0	V	230.0	-3.0	46.0	20.8

2) Above 1 GHz:

Freq. (MHz)	S.A. Reading (dB μ V)	Detector QP/PK/Ave.	Direction Degree	Test Antenna			Cable Loss (dB)	Amp. Gain (dB)	Cod. Amp. (dB μ V/m)	FCC Part 15.249/15.209		
				Height (m)	Polar (H/V)	Factor (dB/m)				Limit (dB μ V/m)	Margin (dB)	Comment
Low Channel (2405 MHz)												
4810	39.24	Ave.	139	2.0	V	34.9	4.30	26.80	51.64	54	2.36*	Harmonic
4810	34.98	Ave	245	1.0	H	36.2	4.30	26.80	48.68	54	5.32	Harmonic
2405	80.57	Ave	80	2.0	V	30.3	3.03	26.83	87.07	94	6.93	Fund.
2405	76.13	Ave	187	1.0	H	30.2	3.03	26.83	82.53	94	11.47	Fund.
4810	40.05	PK	139	2.0	V	34.9	4.30	26.80	52.45	74	21.55	Harmonic
4810	35.64	PK	245	1.0	H	36.2	4.30	26.80	49.34	74	24.66	Harmonic
2405	81.24	PK	80	2.0	V	30.3	3.03	26.83	87.74	114	26.26	Fund.
2405	76.54	PK	187	1.0	H	30.2	3.03	26.83	82.94	114	31.06	Fund.
Middle Channel (2448 MHz)												
4896	37.01	Ave	258	1.37	V	35.1	4.36	26.78	49.69	54	4.31	Harmonic
4896	34.24	Ave	144	1.75	H	35.3	4.36	26.78	47.12	54	6.88	Harmonic
2448	80.34	Ave	145	1.70	V	30.4	3.08	26.84	86.98	94	7.02	Fund.
2448	76.04	Ave	85	1.50	H	30.3	3.08	26.84	82.58	94	11.42	Fund.
4896	37.84	PK	258	1.37	V	35.1	4.36	26.78	50.52	74	23.48	Harmonic
4896	35.12	PK	144	1.75	H	35.3	4.36	26.78	48.00	74	26.00	Harmonic
2448	81.15	PK	145	1.70	V	30.4	3.08	26.84	87.79	114	26.21	Fund.
2448	76.98	PK	85	1.50	H	30.3	3.08	26.84	83.52	114	30.48	Fund.
High Channel (2472 MHz)												
4944	33.67	Ave	178	1.5	H	36.6	4.30	26.76	47.81	54	6.19	Harmonic
2472	80.21	Ave	80	1.0	V	30.5	3.12	26.85	86.98	94	7.02	Fund.
4944	34.01	Ave	139	1.0	V	35.4	4.30	26.76	46.95	54	7.05	Harmonic
2472	76.02	Ave	25	1.5	H	30.6	3.12	26.85	82.89	94	11.11	Fund.
4944	34.26	PK	178	1.5	H	36.6	4.30	26.76	48.40	74	25.60	Harmonic
2472	81.04	PK	80	1.0	V	30.5	3.12	26.85	87.81	114	26.19	Fund.
4944	34.67	PK	139	1.0	V	35.4	4.30	26.76	47.61	74	26.39	Harmonic
2472	76.88	PK	25	1.5	H	30.6	3.12	26.85	83.75	114	30.25	Fund.

Note: *Within measurement uncertainty.

3) Spurious Emissions in Restricted Bands

Freq. (MHz)	S.A. Reading (dB μ V)	Detector QP/PK/Ave.	Direction Degree	Test Antenna			Cable Loss (dB)	Amp. Gain (dB)	Cod. Amp. (dB μ V/m)	FCC Part 15.249/15.209		
				Height (m)	Polar (H/V)	Factor (dB/m)				Limit (dB μ V/m)	Margin (dB)	Comment
2374.6	29.19	Ave.	187	1.0	H	30.1	2.98	26.83	35.44	54	18.56	Spurious
2374.6	29.02	Ave.	80	2.0	V	30.2	2.98	26.83	35.37	54	18.63	Spurious
2492.66	28.31	Ave.	245	1.0	H	30.6	3.25	26.86	35.30	54	18.70	Spurious
2492.66	27.59	Ave.	139	2.0	V	30.6	3.25	26.86	34.58	54	19.42	Spurious
2374.61	39.74	PK	360	2.0	H	30.1	2.98	26.83	45.99	74	28.01	Spurious
2492.66	38.92	PK	245	1.0	H	30.6	3.25	26.86	45.91	74	28.09	Spurious
2374.61	39.35	PK	80	2.0	V	30.2	2.98	26.83	45.70	74	28.30	Spurious
2492.66	38.39	PK	139	2.0	V	30.6	3.25	26.86	45.38	74	28.62	Spurious

FCC §15.215(c) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100224	2010-11-11	2011-11-10
Mini-Circuits	Amplifier	ZVA-213+	T-E27H	2011-03-08	2012-03-07
Sunol Sciences	Horn Antenna	DRH-118	A052604	2011-05-05	2012-05-04

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that indicated 20dB bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.2 kPa

**The testing was performed by Kvass Yang on 2011-05-19*


Test Mode: Transmitting

Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
Low	2405	2.360
Middle	2448	2.400
High	2472	2.380


Low Channel



Date: 19.MAY.2011 10:24:56

Middle Channel

Date: 19.MAY.2011 10:18:52

High Channel

Date: 19.MAY.2011 10:20:23

******* END OF REPORT *******