FCC 47 CFR PART 15 SUBPART C

Report No.: C130726Z06-RP1

TEST REPORT

For

Outdoor Bluetooth Speaker Model: DC-932-A Brand: N/A

Test Report Number: C130726Z06-RP1

Prepared for

SHENZHEN QI SHENGLONG INDUSTRIALIST CO.,LTD.

5F.,Blk 6A, Jing Nan Industry, Bai Ge long, Buji, Shenzhen, China

Prepared by

COMPLIANCE CERTIFICATION SERVICES (SHENZHEN) INC. No.10-1, Mingkeda Logistics Park, No.18, Huanguan South Rd., Guan Lan Town, Baoan District, Shenzhen China

TEL: 86-755-28055000 FAX: 86-755-28055221 Issued Date: August 19, 2013



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST or any government agencies. The test result of this report relate only to the tested sample identified in this report.

FCC ID: Y56QSLDC932A Page 1 / 59

Revision History

Report No.: C130726Z06-RP1

Rev.	Issue No.	Revisions	Effect Page	Revised By
00	C130726Z06-RP1	Initial Issue	ALL	Sinphy Xie

FCC ID: Y56QSLDC932A Page 2 of 59

TABLE OF CONTENTS

1.	TEST RESULT CERTIFICATION	4
2.	EUT DESCRIPTION	5
3.	. TEST METHODOLOGY	6
	3.1 DESCRIPTION OF TEST MODES	6
4.	FACILITIES AND ACCREDITATIONS	7
	4.1 FACILITIES	7
	4.2 ACCREDITATIONS	
5.	SETUP OF EQUIPMENT UNDER TEST	8
	5.1 SETUP CONFIGURATION OF EUT	8 8
	. FCC PART 15.247 REQUIREMENTS	
	6.1 20dB BANDWIDTH	
	6.2 PEAK POWER	13
	6.3 PEAK POWER SPECTRAL DENSITY	
	6.4 BAND EDGES MEASUREMENT	
	6.5 FREQUENCY SEPARATION	∠b
	6.7 TIME OF OCCUPANCY (DWELL TIME)	
	6.8 SPURIOUS EMISSIONS	
	6.9 POWERLINE CONDUCTED EMISSIONS	

Report No.: C130726Z06-RP1

1. TEST RESULT CERTIFICATION

Product:	Outdoor Bluetooth Speaker
Model:	DC-932-A
Brand:	N/A
Tested:	July 26~August 16, 2013
Applicant:	SHENZHEN QI SHENGLONG INDUSTRIALIST CO.,LTD. 5F.,Blk 6A, Jing Nan Industry, Bai Ge long,Buji, Shenzhen, China
Manufacturer:	DONGGUAN FEIHAO INDUSTRIALIST CO.,LTD No.8,Fengyi Road, Dakan Village, Huangjiang, DongGuan, China

Report No.: C130726Z06-RP1

APPLICABLE STANDARDS				
STANDARD TEST RESULT				
FCC 47 CFR Part 15 Subpart C	No non-compliance noted			

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4:2009 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.207, 15.209 and 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Reviewed by:

Tom Gan

Supervisor of EMC Dept.

Compliance Certification Service Inc.

Ruby Zhang

Supervisor of Report Dept.

Compliance Certification Service Inc.

2. EUT DESCRIPTION

Product	Outdoor Bluetooth Speaker
Model Number	DC-932-A
Brand	N/A
Model Discrepancy	N/A
Identify Number	C130726Z06-RP1
Power Supply	DC5V supplied by the notebook or DC3.7V supplied by the battery
Received Date	July 26, 2013
Frequency Range	2402 ~ 2480 MHz
Transmit Power	GFSK: 1.26dBm 8DPSK: -0.20dBm
Modulation Technique	FHSS (GFSK for 1Mbps, π /4-DQPSK for 2Mbps, 8DPSK for 3Mbps)
Number of Channels	79 Channels
Antenna Specification	Integral Antenna with 0dBi gain(Max)
Temperature Range	-10°C ~ +45°C

Report No.: C130726Z06-RP1

Note: This submittal(s) (test report) is intended for FCC ID: <u>Y56QSLDC932A</u> filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.

FCC ID: Y56QSLDC932A Page 5 of 59

3. TEST METHODOLOGY

3.1 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Report No.: C130726Z06-RP1

The following test mode(s) were scanned during the preliminary test below 1G:

Test Item	Test mode	Worse mode
	Mode 1: Charging	
Conducted Emission	Mode 2: Charging and bluetooth play music	
Lillioololi	Mode 3: Charging and AUX play music	\boxtimes
Radiated Emission	Mode 1: TX	\boxtimes

Above 1G, Channel Low (2402MHz) · Mid (2441MHz) and High (2480MHz) were chosen for full testing for GFSK and 8DPSK.

FCC ID: Y56QSLDC932A Page 6 of 59

4. FACILITIES AND ACCREDITATIONS

4.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

No.10-1, Mingkeda Logistics Park, No.18, Huanguan South Rd., Guan Lan Town, Baoan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.4:2009, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

Report No.: C130726Z06-RP1

4.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

USA A2LA China CNAS

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

USA FCC
Japan VCCI(C-3478, R-3135, T-652, G-624)
Canada INDUSTRY CANADA
Taiwan BSMI
Norway Nemko

Copies of granted accreditation certificates are available for downloading from our web site, http://www.ccsrf.com

4.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Uncertainty
Radiated Emission, 30 to 200 MHz Test Site : 966(2)	+/-3.6880dB
Radiated Emission, 200 to 1000 MHz Test Site : 966(2)	+/-3.6695dB
Radiated Emission, 1 to 8 GHz	+/-5.1782dB
Radiated Emission, 8 to 18 GHz	+/-5.2173dB
Conducted Emissions	+/-3.6836dB
Band Width	178kHz
Peak Output Power MU	+/-1.906dB
Band Edge MU	+/-0.182dB
Channel Separation MU	416.178Hz
Duty Cycle MU	0.054ms
Frequency Stability MU	226Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

The measured result is above (below) the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance (non-compliance) is more probable than non-compliance) with the specification limit.

FCC ID: Y56QSLDC932A Page 7 of 59

5. SETUP OF EQUIPMENT UNDER TEST

5.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

Report No.: C130726Z06-RP1

5.2 SUPPORT EQUIPMENT

No.	Equipment	Model No.	Serial No.	FCC ID	Brand	Data Cable	Power Cord
1	Notebook	5310m	N/A	N/A	HP	N/A	Unshielded 1.80m
2	IPOD	A1238	JQ807LBYMV	N/A	APPLE	Unshielded 0.80m	N/A

Notes:

Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

FCC ID: Y56QSLDC932A Page 8 of 59

6. FCC PART 15.247 REQUIREMENTS

6.1 20dB BANDWIDTH

None; for reporting purpose only.


MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2013	03/08/2014

Report No.: C130726Z06-RP1

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST CONFIGURATION



TEST PROCEDURE

- 1. Place the EUT on the table and set it in the transmitting mode.
- 2. Remove the antenna from the EUT, then connect a low loss RF cable from antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as RBW=30kHz, VBW=100kHz, Span=3MHz, Sweep = auto.
- 4. Mark the peak frequency and 20dB (upper and lower) frequency.
- 5. Repeat until all the test channels are investigated.


TEST RESULTS

No non-compliance noted

FCC ID: Y56QSLDC932A Page 9 of 59




20dB Bandwidth(CH Low)



Transmit Freq Error -27.334 kHz x dB Bandwidth 860.125 kHz

20dB Bandwidth (CH Mid)




Transmit Freq Error -28.315 kHz x dB Bandwidth 862.457 kHz

FCC ID: Y56QSLDC932A Page 10 of 59




20dB Bandwidth (CH High)



Transmit Freq Error -29.603 kHz 847.605 kHz x dB Bandwidth

8DPSK


20dB Bandwidth (CH Low)



Transmit Freq Error -15.601 kHz x dB Bandwidth 1.215 MHz




20dB Bandwidth (CH Mid)



-17.469 kHz Transmit Freq Error x dB Bandwidth 1.213 MHz

20dB Bandwidth (CH High)



Transmit Freq Error -19.151 kHz x dB Bandwidth 1.214 MHz

FCC ID: Y56QSLDC932A Page 12 of 59

6.2 PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

Report No.: C130726Z06-RP1


- 1. For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
- 2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6dBi.
- 3. The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Power Meter	Anritsu	ML2495A	1204003	03/09/2013	03/08/2014
Power Sensor	Anritsu	MA2411B	1126150	03/09/2013	03/08/2014
Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2013	03/08/2014

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the RF Power Meter. The RF Power Meter is set to the peak power detection.

FCC ID: Y56QSLDC932A Page 13 of 59

TEST RESULTS

No non-compliance noted

Test Data

GFSK

Channel	Frequency (MHz)	Reading Power (dBm)	Factor (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2402	-2.24	3.50	1.26	0.00134		PASS
Mid	2441	-2.53	3.50	0.97	0.00125	1	PASS
High	2480	-3.23	3.50	0.27	0.00106		PASS

Report No.: C130726Z06-RP1

8DPSK

Channel	Frequency (MHz)	Reading Power (dBm)	Factor (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2402	-3.70	3.50	-0.20	0.00095		PASS
Mid	2441	-3.85	3.50	-0.35	0.00092	1	PASS
High	2480	-4.63	3.50	-1.13	0.00077		PASS

FCC ID: Y56QSLDC932A Page 14 of 59

6.3 PEAK POWER SPECTRAL DENSITY

LIMIT

1. For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

Report No.: C130726Z06-RP1


2. The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2013	03/08/2014

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 300kHz, Sweep=100s
- 4. Record the max. reading.
- 5. Repeat the above procedure until the measurements for all frequencies are completed.

TEST RESULTS

Not applicable. Since EUT is the Bluetooth device.

FCC ID: Y56QSLDC932A Page 15 of 59

6.4 BAND EDGES MEASUREMENT

LIMIT


According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in15.209(a).

Report No.: C130726Z06-RP1

MEASUREMENT EQUIPMENT USED

Radiated Emission Test Site 966 (2)								
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration			
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2013	03/08/2014			
EMI TEST RECEIVER.ESCI	ROHDE&SCHWARZ	ESCI	100783	03/09/2013	03/08/2014			
Amplifier	MITEQ	AM-1604-3000	1123808	03/18/2013	03/18/2014			
High Noise Amplifier	Agilent	8449B	3008A01838	03/18/2013	03/18/2014			
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	06/21/2013	06/21/2014			
Bilog Antenna	SCHAFFNER	CBL6143	5082	03/02/2013	03/01/2014			
Horn Antenna	SCHWARZBECK	BBHA9120	D286	03/02/2013	03/01/2014			
Loop Antenna	A、R、A	PLA-1030/B	1029	03/19/2013	03/18/2014			
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R			
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R			
Controller	СТ	N/A	N/A	N.C.R	N.C.R			
Temp. / Humidity Meter	Anymetre	JR913	N/A	03/04/2013	03/03/2014			
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R			
Test S/W	FARAD		LZ-RF / CCS	S-SZ-3A2				

Test Configuration



FCC ID: Y56QSLDC932A Page 16 of 59

TEST PROCEDURE

- 1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.

Report No.: C130726Z06-RP1

- 4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
- 5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.


TEST RESULTS


Refer to attach spectrum analyzer data chart.

FCC ID: Y56QSLDC932A Page 17 of 59


Test Data (GFSK)

Band Edges (CH-Low)







FCC ID: Y56QSLDC932A Page 18 of 59





Detector mode: Average Polarity: Horizontal * Agilent Mkr1 2.402 0 GHz Ref 107 dBpV 75.87 dB**µ**V #Atten 10 dB #Peak Log 10 dB/ LgAv M1 S2 Start 2.310 0 GHz Stop 2.410 0 GHz #Res BW 1 MHz #VBW 10 Hz Sweep 7.797 s (601 pts) Trace (1) (1) X fixis 2.402 0 GHz 2.390 0 GHz Amplitude 75.87 dBµV 27.84 dBµV Type Freq Freq Marker

Band Edges (CH-High)












8DPSK


Band Edges (CH-Low)















Band Edges (CH-High)









6.5 FREQUENCY SEPARATION

LIMIT


According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2013	03/08/2014

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set center frequency of spectrum analyzer = middle of hopping channel.
- 4. Set the spectrum analyzer as RBW=30kHz, VBW=30kHz, Adjust Span to 4 MHz, Sweep = auto.
- 5. Max hold. Mark 3 Peaks of hopping channel and record the 3 peaks frequency.

TEST RESULTS

No non-compliance noted

Test Data

GFSK

Channel Separation (MHz) Two-thirds of the 20 dB Bandwidth (kHz)		Channel Separation Limit	Result
1.000	574.971	> Two-thirds of the 20 dB Bandwidth	Pass

8DPSK


Channel Separation (MHz)	Two-thirds of the 20 dB Bandwidth (kHz)	Channel Separation Limit	Result
1.000	810.000	> Two-thirds of the 20 dB Bandwidth	Pass

Report No.: C130726Z06-RP1


GFSK

Test Plot

Measurement of Channel Separation



20 dB bandwidth(CH Mid)



Transmit Freq Error

x dB Bandwidth


-28.315 kHz

862.457 kHz


8DPSK

Test Plot

Measurement of Channel Separation



20 dB bandwidth(CH Low)



Transmit Freq Error -15.601 kHz x dB Bandwidth 1.215 MHz

6.6 NUMBER OF HOPPING FREQUENCY

LIMIT


According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 15 hopping frequencies.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model Serial Number		Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2013	03/08/2014

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set spectrum analyzer Start=2400MHz, Stop = 2441.5MHz, Sweep = 1ms and Start=2441.5MHz, Stop = 2483.5MHz, Sweep = 1ms.
- 4. Set the spectrum analyzer as RBW, VBW=300kHz,
- 5. Max hold, view and count how many channel in the band.

TEST RESULTS

No non-compliance noted

Test Data


Result (No. of CH)	Limit (No. of CH)	Result
79	>15	PASS

Report No.: C130726Z06-RP1


Test Plot (GFSK)

Channel Number

2.400 GHz - 2.4415 GHz




2.4415 GHz -2.4835 GHz




Test Plot (8DPSK)

Channel Number

2.400 GHz - 2.4415 GHz



2.4415 GHz -2.4835 GHz



6.7 TIME OF OCCUPANCY (DWELL TIME)

LIMIT


According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model Serial Number		Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2013	03/08/2014

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set center frequency of spectrum analyzer = operating frequency.
- 4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
- 5. Repeat above procedures until all frequency measured were complete.

Report No.: C130726Z06-RP1

TEST RESULTS

No non-compliance noted

Test Data

GFSK

DH 1

CH Mid: 0.398* (1600/2)/79*31.6 = 127.360 (ms)

СН	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	0.398	127.360	31.60	400.00	PASS

DH 3

CH Mid: 1.655* (1600/4)/79* 31.6 = 264.800 (ms)

СН	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	1.655	264.800	31.60	400.00	PASS

<u>DH 5</u>

CH Mid: 2.900* (1600/6)/79 * 31.6 = 309.333(ms)

СН	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	2.900	309.333	31.60	400.00	PASS

Test Data

8DPSK

DH 1

CH Mid: $0.410^* (1600/2)/79 * 31.6 = 131.200 (ms)$

СН	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	0.410	131.200	31.60	400.00	PASS

DH 3

CH Mid: $1.660^* (1600/4)/79 * 31.6 = 265.600 (ms)$

СН	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	1.660	265.600	31.60	400.00	PASS

<u>DH 5</u>

CH Mid: 2.900* (1600/6)/79 * 31.6 = 309.333(ms)


СН	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	2.900	309.333	31.60	400.00	PASS

Test Plot

GFSK


DH 1

(CH Mid)




DH 3

(CH Mid)




<u>DH 5</u>



Test Plot 8DPSK


<u>DH 1</u>

(CH Mid)




DH 3

(CH Mid)



DH 5 (CH Mid)



6.8 SPURIOUS EMISSIONS

6.8.1. CONDUCTED MEASUREMENT

LIMIT


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2013	03/08/2014

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.

Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.


TEST RESULTS

No non-compliance noted


Report No.: C130726Z06-RP1

Test Plot (GFSK)


CH Low (30MHz ~26.5GHz)




CH Low (2.31GHz ~2.41GHz)




CH Mid (30MHz ~ 26.5GHz)



CH High (30MHz ~ 26.5GHz)




CH High (2.475GHz ~ 2.5GHz)




Test Plot (8DPSK)


CH Low (30MHz ~26.5GHz)




CH Low (2.31GHz ~2.41GHz)




CH Mid (30MHz ~ 26.5GHz)



CH High (30MHz ~ 26.5GHz)



CH High (2.475GHz ~ 2.5GHz)



6.8.2. RADIATED EMISSIONS

LIMIT

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Report No.: C130726Z06-RP1

Note: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength (μV/m at 3-meter)	Field Strength (dBµV/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

FCC ID: Y56QSLDC932A Page 46/59

MEASUREMENT EQUIPMENT USED

	Radiated Emission Test Site 966 (2)								
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration				
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2013	03/08/2014				
EMI TEST RECEIVER.ESCI	ROHDE&SCHWARZ	ESCI	100783	03/09/2013	03/08/2014				
Amplifier	MITEQ	AM-1604-3000	1123808	03/18/2013	03/18/2014				
High Noise Amplifier	Agilent	8449B	3008A01838	03/18/2013	03/18/2014				
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	06/21/2013	06/21/2014				
Bilog Antenna	SCHAFFNER	CBL6143	5082	03/02/2013	03/01/2014				
Horn Antenna	SCHWARZBECK	BBHA9120	D286	03/02/2013	03/01/2014				
Loop Antenna	A、R、A	PLA-1030/B	1029	03/19/2013	03/18/2014				
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R				
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R				
Controller	СТ	N/A	N/A	N.C.R	N.C.R				
Temp. / Humidity Meter	Anymetre	JR913	N/A	03/04/2013	03/03/2014				
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R				
Test S/W	FARAD		LZ-RF / CC	S-SZ-3A2					


Report No.: C130726Z06-RP1

Remark: Each piece of equipment is scheduled for calibration once a year.


FCC ID: Y56QSLDC932A Page 47/59

TEST CONFIGURATION


Below 30MHz



Below 1 GHz



Above 1 GHz



TEST PROCEDURE

- 1. The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until the measurements for all frequencies are complete.

TEST RESULTS

Below 1 GHz

Operation Mode: TX Test Date: August 5, 2013

Temperature: 24°C **Tested by:** Sunday Hu

Humidity: 52% RH **Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
145.4300	39.76	-19.08	20.68	43.50	-22.82	V	QP
226.9100	34.09	-18.03	16.06	46.00	-29.94	V	QP
280.2600	34.91	-18.57	16.34	46.00	-29.66	V	QP
596.4800	31.45	-12.84	18.61	46.00	-27.39	V	QP
734.2200	31.22	-10.72	20.50	46.00	-25.50	V	QP
951.5000	32.12	-8.19	23.93	46.00	-22.07	V	QP
						•	
159.9800	39.67	-18.85	20.82	43.50	-22.68	Н	QP
279.2900	44.21	-18.55	25.66	46.00	-20.34	Н	QP
327.7900	44.39	-17.49	26.90	46.00	-19.10	Н	QP
704.1500	36.11	-10.67	25.44	46.00	-20.56	Н	QP
736.1600	36.09	-10.75	25.34	46.00	-20.66	Н	QP
936.9500	33.30	-8.38	24.92	46.00	-21.08	Н	QP

^{**}Remark: No emission found between lowest internal used/generated frequency to 30MHz. **Notes:**

- 1. Measuring frequencies from 9kHz to the 1GHz.
- 2. Radiated emissions measured in frequency range from 30MHz to 1GHz were made with an instrument using Peak/Quasi-peak detector mode.
- 3. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4. The IF bandwidth of SPA between 30MHz to 1GHz was 120kHz.

5. Frequency (MHz). = Emission frequency in MHz

Reading (dBuV) = Receiver reading

Correction Factor(dB/m) = Antenna factor + Cable loss – Amplifier gain Actual FS (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)

Limit (dBuV/m) = Limit stated in standard

Margin(dB) = Measured (dBuV/m) - Limits (dBuV/m)

Antenna Pole(V/H) = Current carrying line of reading

Above 1 GHz **GFSK**

Operation Mode: TX(CH Low) Test Date: August 3, 2013 Temperature: 24°C Tested by: Sunday Hu **Humidity:** 52% RH Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1240.0000	51.70	-8.55	43.15	74.00	-30.85	V	peak
1465.0000	52.12	-8.11	44.01	74.00	-29.99	V	peak
1795.0000	52.09	-9.42	42.67	74.00	-31.33	V	peak
3865.0000	46.44	-2.50	43.94	74.00	-30.06	V	peak
4810.0000	47.17	0.46	47.63	74.00	-26.37	V	peak
6115.0000	45.11	3.43	48.54	74.00	-25.46	V	peak
1465.0000	49.33	-8.11	41.22	74.00	-32.78	Н	peak
2995.0000	46.62	-4.26	42.36	74.00	-31.64	Н	peak
3775.0000	46.52	-2.55	43.97	74.00	-30.03	Н	peak
4540.0000	45.53	-0.57	44.96	74.00	-29.04	Н	peak
4810.0000	48.94	0.46	49.40	74.00	-24.60	Н	peak
6085.0000	45.00	3.34	48.34	74.00	-25.66	Н	peak

Notes:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms. b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.
- 5. Frequency (MHz) = Emission frequency in MHz

Reading (dBµV/m) =Uncorrected Analyzer / Receiver Reading Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain

Limit (dBµV/m) = Limit stated in standard

Margin (dB) = Result ($dB\mu V/m$)- Limit ($dB\mu V/m$)

Pk = Peak Reading AV. = Average Reading

Operation Mode: TX(CH Mid) Test Date: August 3, 2013

24°C Tested by: Sunday Hu Temperature:

Ver. / Hor. **Humidity:** 52% RH Polarity:

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1240.0000	54.00	-8.55	45.45	74.00	-28.55	V	peak
1465.0000	53.00	-8.11	44.89	74.00	-29.11	V	peak
3685.0000	46.77	-2.79	43.98	74.00	-30.02	V	peak
4885.0000	45.64	0.80	46.44	74.00	-27.56	V	peak
6130.0000	44.99	3.48	48.47	74.00	-25.53	V	peak
6940.0000	45.08	6.04	51.12	74.00	-22.88	V	peak
1465.0000	48.47	-8.11	40.36	74.00	-33.64	Н	peak
3220.0000	46.33	-4.08	42.25	74.00	-31.75	Н	peak
3865.0000	46.70	-2.50	44.20	74.00	-29.80	Н	peak
4885.0000	46.58	0.80	47.38	74.00	-26.62	Н	peak
5740.0000	44.55	2.52	47.07	74.00	-26.93	Н	peak
6895.0000	45.57	5.82	51.39	74.00	-22.61	Н	peak

Notes:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.
- 5. Frequency (MHz) = Emission frequency in MHz

Reading (dBµV/m) =Uncorrected Analyzer / Receiver Reading Correction Factor (dB) = Antenna factor + Cable loss - Amplifier gain

Limit (dBµV/m) = Limit stated in standard

Margin (dB) = Result ($dB\mu V/m$)- Limit ($dB\mu V/m$)

Pk = Peak Reading AV. = Average Reading

Operation Mode: TX(CH High) Test Date: August 3, 2013

Temperature: 24 °C **Tested by:** Sunday Hu

Humidity: 52% RH **Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1240.0000	53.40	-8.55	44.85	74.00	-29.15	V	peak
1465.0000	53.47	-8.11	45.36	74.00	-28.64	V	peak
2395.0000	52.47	-6.57	45.90	74.00	-28.10	V	peak
3640.0000	46.67	-2.91	43.76	74.00	-30.24	V	peak
4960.0000	47.15	1.14	48.29	74.00	-25.71	V	peak
6250.0000	45.02	3.83	48.85	74.00	-25.15	V	peak
1375.0000	49.00	-7.94	41.06	74.00	-32.94	Н	peak
3235.0000	46.79	-4.07	42.72	74.00	-31.28	Н	peak
4285.0000	45.61	-1.26	44.35	74.00	-29.65	Н	peak
4960.0000	46.86	1.14	48.00	74.00	-26.00	Н	peak
6115.0000	44.56	3.43	47.99	74.00	-26.01	Н	peak
6385.0000	45.26	4.22	49.48	74.00	-24.52	Н	peak

Notes:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms. b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.
- 5. Frequency (MHz) = Emission frequency in MHz

Reading $(dB\mu V/m)$ = Uncorrected Analyzer / Receiver Reading Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain

 $Limit (dB\mu V/m) = Limit stated in standard$

Margin (dB) = Result (dB μ V/m)- Limit (dB μ V/m)

Pk = Peak Reading AV. = Average Reading

8DPSK

Operation Mode: TX(CH Low) Test Date: August 3, 2013

Temperature: 24°C **Tested by:** Sunday Hu

Humidity: 52% RH **Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1240.0000	53.88	-8.55	45.33	74.00	-28.67	V	peak
1465.0000	52.54	-8.11	44.43	74.00	-29.57	V	peak
1735.0000	56.63	-9.19	47.44	74.00	-26.56	V	peak
4285.0000	45.11	-1.26	43.85	74.00	-30.15	V	peak
5350.0000	44.60	1.53	46.13	74.00	-27.87	V	peak
5830.0000	44.32	2.83	47.15	74.00	-26.85	V	peak
1240.0000	49.46	-8.55	40.91	74.00	-33.09	Н	peak
1795.0000	50.04	-9.42	40.62	74.00	-33.38	Н	peak
3010.0000	47.07	-4.23	42.84	74.00	-31.16	Н	peak
3880.0000	45.91	-2.51	43.40	74.00	-30.60	Н	peak
5095.0000	44.70	1.43	46.13	74.00	-27.87	Н	peak
6325.0000	44.61	4.05	48.66	74.00	-25.34	Н	peak

Notes:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.
- 5. Frequency (MHz) = Emission frequency in MHz

Reading $(dB\mu V/m)$ = Uncorrected Analyzer / Receiver Reading Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain

 $Limit (dB\mu V/m) = Limit stated in standard$

Margin (dB) = Result (dB μ V/m)- Limit (dB μ V/m)

Pk = Peak Reading
AV. = Average Reading

Operation Mode: TX(CH Mid) Test Date: August 3, 2013

Temperature: 24°C **Tested by:** Sunday Hu

Humidity: 52% RH **Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1240.0000	52.72	-8.55	44.17	74.00	-29.83	V	peak
1465.0000	53.45	-8.11	45.34	74.00	-28.66	V	peak
3040.0000	47.09	-4.21	42.88	74.00	-31.12	V	peak
4135.0000	45.85	-1.89	43.96	74.00	-30.04	V	peak
4930.0000	45.88	1.00	46.88	74.00	-27.12	V	peak
5995.0000	44.87	3.08	47.95	74.00	-26.05	V	peak
1465.0000	49.38	-8.11	41.27	74.00	-32.73	Н	peak
2950.0000	46.61	-4.44	42.17	74.00	-31.83	Н	peak
3775.0000	46.22	-2.55	43.67	74.00	-30.33	Н	peak
4690.0000	45.79	-0.07	45.72	74.00	-28.28	Н	peak
6130.0000	45.07	3.48	48.55	74.00	-25.45	Н	peak
7030.0000	44.37	6.50	50.87	74.00	-23.13	Н	peak

Notes:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.
- 5. Frequency (MHz) = Emission frequency in MHz

Reading (dBµV/m) = Uncorrected Analyzer / Receiver Reading Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain

 $Limit (dB\mu V/m) = Limit stated in standard$

Margin (dB) = Result (dB μ V/m)- Limit (dB μ V/m)

Pk = Peak Reading
AV. = Average Reading

Operation Mode: TX(CH High) Test Date: August 3, 2013

Temperature:24 °CTested by:Sunday HuHumidity:52% RHPolarity:Ver. / Hor.

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1240.0000	54.30	-8.55	45.75	74.00	-28.25	V	peak
1465.0000	52.71	-8.11	44.60	74.00	-29.40	V	peak
1795.0000	51.60	-9.42	42.18	74.00	-31.82	V	peak
2395.0000	50.55	-6.57	43.98	74.00	-30.02	V	peak
4210.0000	46.09	-1.54	44.55	74.00	-29.45	V	peak
5230.0000	45.85	1.55	47.40	74.00	-26.60	V	peak
		•					
1525.0000	49.42	-8.36	41.06	74.00	-32.94	Н	peak
3460.0000	47.30	-3.70	43.60	74.00	-30.40	Н	peak
4225.0000	45.84	-1.48	44.36	74.00	-29.64	Н	peak
4975.0000	44.64	1.21	45.85	74.00	-28.15	Н	peak
5755.0000	44.69	2.59	47.28	74.00	-26.72	Н	peak
6580.0000	45.18	4.76	49.94	74.00	-24.06	Н	peak

Notes:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.
- 5. Frequency (MHz) = Emission frequency in MHz

Reading $(dB\mu V/m)$ = Uncorrected Analyzer / Receiver Reading Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain

 $Limit (dB\mu V/m) = Limit stated in standard$

Margin (dB) = Result (dB μ V/m)- Limit (dB μ V/m)

Pk = Peak Reading
AV. = Average Reading

6.9 POWERLINE CONDUCTED EMISSIONS

LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Fraguency Pango (MUz)	Limits (dBμV)				
Frequency Range (MHz)	Quasi-peak	Average			
0.15 to 0.50	66 to 56	56 to 46			
0.50 to 5	56	46			
5 to 30	60	50			

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.


MEASUREMENT EQUIPMENT USED

Conducted Emission Test Site											
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration						
EMI TEST RECEIVER.ESCI	ROHDE&SCHWARZ	ESCI	100783	03/09/2013	03/08/2014						
LISN(EUT)	ROHDE&SCHWARZ	ENV216	101543-WX	04/20/2013	04/19/2014						
LISN	EMCO	3825/2	8901-1459	03/09/2013	03/08/2014						
Temp. / Humidity Meter	VICTOR	HTC-1	N/A	03/04/2013	03/03/2014						
Test S/W	FARAD	EZ-EMC/ CCS-3A1-CE									

Remark: Each piece of equipment is scheduled for calibration once a year.

Report No.: C130726Z06-RP1

TEST CONFIGURATION



See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

- 1. The EUT was placed on a table, which is 0.8m above ground plane.
- 2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3. Repeat above procedures until all frequency measured were complete.

TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Test Data

Operation Mode: Mode 3 Test Date: August 7, 2013

Temperature: 22°C Humidity: 45% RH

Tested by: Sunday Hu

Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Line (L1/L2)
0.1547	39.82	19.47	9.59	49.41	29.06	65.74	55.74	-16.33	-26.68	L1
0.6500	28.61	15.45	9.76	38.37	25.21	56.00	46.00	-17.63	-20.79	L1
2.2740	31.84	15.86	9.72	41.56	25.58	56.00	46.00	-14.44	-20.42	L1
2.7420	31.23	17.09	9.72	40.95	26.81	56.00	46.00	-15.05	-19.19	L1
16.2979	36.72	20.88	9.89	46.61	30.77	60.00	50.00	-13.39	-19.23	L1
27.6260	31.91	20.53	9.95	41.86	30.48	60.00	50.00	-18.14	-19.52	L1
0.1539	37.70	8.84	9.78	47.48	18.62	65.78	55.79	-18.30	-37.17	L2
0.2100	32.75	11.45	9.79	42.54	21.24	63.20	53.21	-20.66	-31.97	L2
0.6500	27.77	13.74	9.69	37.46	23.43	56.00	46.00	-18.54	-22.57	L2
2.5460	31.59	16.50	9.74	41.33	26.24	56.00	46.00	-14.67	-19.76	L2
16.7460	37.84	22.10	9.72	47.56	31.82	60.00	50.00	-12.44	-18.18	L2
27.1660	34.45	25.88	9.83	44.28	35.71	60.00	50.00	-15.72	-14.29	L2

Note:

- 1. Measuring frequencies from 0.15 MHz to 30MHz.
- 2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Peak detector, Quasi-peak detector and average detector.
- 3. "---" denotes the emission level was or more than 2dB below the Average limit.
- 4. The IF bandwidth of SPA between 0.15MHz to 30MHz was 10kHz; the IF bandwidth of Test Receiver between 0.15MHz to 30MHz was 9kHz;
- 5. L1= Line One (Live Line)/ L2= Line Two (Neutral Line)

Report No.: C130726Z06-RP1