

# RF TEST REPORT



Report No.: 17070286-FCC-R2

Supersede Report No.: N/A

Applicant	SHENZHEN QISHENGLONG INDUSTRIALIST CO.,LTD	
Product Name	Microphone Bluetooth Speaker	
Model No.	DC-K0069	
Serial No.	N/A	
Test Standard	FCC Part 15.247: 2016, ANSI C63.10: 2013	
Test Date	April 19 to May 09, 2017	
Issue Date	May 10, 2017	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification <input checked="" type="checkbox"/>		
Equipment did not comply with the specification <input type="checkbox"/>		
Loren Luo	David Huang	
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only		
Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

---

This page has been left blank intentionally.

## CONTENTS

1. REPORT REVISION HISTORY .....	5
2. CUSTOMER INFORMATION.....	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	6
5. TEST SUMMARY .....	7
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS.....	8
6.1 ANTENNA REQUIREMENT .....	8
6.2 CHANNEL SEPARATION.....	9
6.3 20DB BANDWIDTH.....	13
6.4 PEAK OUTPUT POWER .....	17
6.5 NUMBER OF HOPPING CHANNEL .....	21
6.6 TIME OF OCCUPANCY (DWELL TIME).....	23
6.7 BAND EDGE & RESTRICTED BAND .....	27
6.8 AC POWER LINE CONDUCTED EMISSIONS.....	35
6.9 RADIATED EMISSIONS & RESTRICTED BAND.....	41
ANNEX A. TEST INSTRUMENT.....	47
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	48
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	56
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST.....	60
ANNEX E. DECLARATION OF SIMILARITY .....	61

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070286-FCC-R2	NONE	Original	May 10, 2017

## 2. Customer information

Applicant Name	SHENZHEN QISHENGLONG INDUSTRIALIST CO.,LTD
Applicant Add	5/F.,BLK 6A,JINNAN INDUSTRY,BAIGELONG,BUJI,SHENZHEN,CHINA
Manufacturer	SHENZHEN KINGSUN ENTERPRISES Co.,Ltd.
Manufacturer Add	25F,CEC information Building,Xinwen Road,Futian District,Shenzhen, Guangdong, P.R.China

## 3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software of Radiated Emission	Radiated Emission Program-To Shenzhen v2.0
Test Software of Conducted Emission	EZ-EMC(ver.lcp-03A1)

## 4. Equipment under Test (EUT) Information

Description of EUT: Microphone Bluetooth Speaker

Main Model: DC-K0069

Serial Model: N/A

Date EUT received: April 18, 2017

Test Date(s): April 19 to May 09, 2017

Equipment Category : DSS

Antenna Gain: 0.944dBi

Antenna Type: PCB antenna

Type of Modulation: Bluetooth: GFSK,  $\pi/4$ DQPSK, 8DPSK

RF Operating Frequency (ies): Bluetooth: 2402-2480 MHz

Max. Output Power: 1.076dBm

Number of Channels: Bluetooth: 79CH

Port: USB Port, SD Card Port

Input Power: Battery:  
Spec: 3.7V, 1200mAh, 4.44Wh  
USB: DC5V

Trade Name : N/A

FCC ID: Y56QLHD326

## 5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)	20 dB Bandwidth	Compliance
§15.247(b)(1)	Peak Output Power	Compliance
§15.247(a)(1)(iii)	Number of Hopping Channel	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(d)	Band Edge& Restricted Band	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions& Restricted Band	Compliance

### Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge& Restricted Band and Radiated Emissions& Restricted Band	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

## **6. Measurements, Examination And Derived Results**

### **6.1 Antenna Requirement**

#### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited.

The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Antenna Connector Construction**

The EUT has 1 antenna:

A permanently attached PCB antenna for Bluetooth, the gain is 0.944dBi for Bluetooth.


**The antenna meets up with the ANTENNA REQUIREMENT.**

**Result:** Compliance.

## 6.2 Channel Separation

Temperature	24 °C
Relative Humidity	56%
Atmospheric Pressure	1004mbar
Test date :	May 04, 2016
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(a)(1)	a)	Channel Separation < 20dB BW and 20dB BW < 25KHz ; Channel Separation Limit=25KHz Chanel Separation < 20dB BW and 20dB BW > 25kHz ; Channel Separation Limit=2/3 20dB BW	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;"><b>Spectrum Analyzer</b>                                    <b>EUT</b></p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.</p> <p><u>Use the following spectrum analyzer settings:</u></p> <ul style="list-style-type: none"> <li>- The EUT must have its hopping function enabled</li> <li>- Span = wide enough to capture the peaks of two adjacent channels</li> <li>- Resolution (or IF) Bandwidth (RBW) <math>\geq</math> 1% of the span</li> <li>- Video (or Average) Bandwidth (VBW) <math>\geq</math> RBW</li> <li>- Sweep = auto</li> <li>- Detector function = peak</li> <li>- Trace = max hold</li> <li>- Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.</li> </ul>		


Remark		
Result	<input checked="" type="checkbox"/> Pass	<input type="checkbox"/> Fail
Test Data	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> N/A
Test Plot	<input checked="" type="checkbox"/> Yes (See below)	<input type="checkbox"/> N/A


### Channel Separation measurement result

Type/ Modulation	CH	CH Frequency (MHz)	CH Separation (MHz)	Limit (MHz)	Result
CH Separation GFSK	Low Channel	2402	1.005	0.688	Pass
	Adjacency Channel	2403			
	Mid Channel	2440			
	Adjacency Channel	2441	1.005	0.676	Pass
	High Channel	2480			
	Adjacency Channel	2479			
CH Separation $\pi/4$ DQPSK	Low Channel	2402	1.005	0.751	Pass
	Adjacency Channel	2403			
	Mid Channel	2440			
	Adjacency Channel	2441	1.005	0.755	Pass
	High Channel	2480			
	Adjacency Channel	2479			
CH Separation 8DPSK	Low Channel	2402	1.005	0.691	Pass
	Adjacency Channel	2403			
	Mid Channel	2440			
	Adjacency Channel	2441	1.005	0.685	Pass
	High Channel	2480			
	Adjacency Channel	2479			

## Test Plots

### Channel Separation measurement result






## 6.3 20dB Bandwidth

Temperature	24 °C
Relative Humidity	56%
Atmospheric Pressure	1004mbar
Test date :	May 04, 2016
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)	a)	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;"><b>Spectrum Analyzer</b>                                    <b>EUT</b></p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.</p> <p><u>Use the following spectrum analyzer settings:</u></p> <ul style="list-style-type: none"> <li>- Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel</li> <li>- RBW <math>\geq</math> 1% of the 20 dB bandwidth</li> <li>- VBW <math>\geq</math> RBW</li> <li>- Sweep = auto</li> <li>- Detector function = peak</li> <li>- Trace = max hold.</li> <li>- The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference</li> </ul>		

	marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A


Test Plot  Yes (See below)  N/A


#### Measurement result

Modulation	CH	CH Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GFSK	Low	2402	1.032	0.9668
	Mid	2441	1.014	0.9294
	High	2480	1.029	0.9514
$\pi/4$ DQPSK	Low	2402	1.126	1.1369
	Mid	2441	1.133	1.1327
	High	2480	1.114	1.1299
8-DPSK	Low	2402	1.036	1.1054
	Mid	2441	1.027	1.0982
	High	2480	1.035	1.0999

## Test Plots

### 20dB Bandwidth measurement result





## 6.4 Peak Output Power

Temperature	24 °C
Relative Humidity	56%
Atmospheric Pressure	1004mbar
Test date :	May 04, 2016
Tested By :	Loren Luo

### Requirement(s):

	<ul style="list-style-type: none"> <li>- Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (see the note above regarding external attenuation and cable loss). The limit is specified in one of the subparagraphs of this Section. Submit this plot. A peak responding power meter may be used instead of a spectrum analyzer.</li> </ul>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A


Test Plot  Yes (See below)  N/A


#### Peak Output Power measurement result

Type	Modulation	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (mW)	Result
Output power	GFSK	Low	2402	-0.151	125	Pass
		Mid	2441	-0.581	125	Pass
		High	2480	-0.733	125	Pass
	$\pi/4$ DQPSK	Low	2402	1.034	125	Pass
		Mid	2441	0.600	125	Pass
		High	2480	0.582	125	Pass
	8-DPSK	Low	2402	<b>1.076</b>	125	Pass
		Mid	2441	0.725	125	Pass
		High	2480	0.530	125	Pass

## Test Plots

### Output Power measurement result





## 6.5 Number of Hopping Channel

Temperature	24 °C
Relative Humidity	56%
Atmospheric Pressure	1004mbar
Test date :	May 04, 2016
Tested By :	Loren Luo


### Requirement(s):

### Number of Hopping Channel measurement result

Type	Modulation	Frequency Range	Number of Hopping Channel	Limit
Number of Hopping Channel	GFSK	2400-2483.5	79	15
	$\pi/4$ DQPSK	2400-2483.5	79	15
	8-DPSK	2400-2483.5	79	15

### Test Plots


#### Number of Hopping Channels measurement result



## 6.6 Time of Occupancy (Dwell Time)

Temperature	24 °C
Relative Humidity	56%
Atmospheric Pressure	1004mbar
Test date :	May 04, 2016
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable	
§15.247(a) (1)(iii)	a)	Dwell Time < 0.4s	<input checked="" type="checkbox"/>	
Test Setup	 <b>Spectrum Analyzer</b> <b>EUT</b>			
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.</p> <p><u>Use the following spectrum analyzer</u></p> <ul style="list-style-type: none"> <li>- Span = zero span, centered on a hopping channel</li> <li>- RBW = 1 MHz</li> <li>- VBW <math>\geq</math> RBW</li> <li>- Sweep = as necessary to capture the entire dwell time per hopping channel</li> <li>- Detector function = peak</li> <li>- Trace = max hold</li> <li>- use the marker-delta function to determine the dwell time</li> </ul>			
Remark				
Result	<input checked="" type="checkbox"/>	Pass	<input type="checkbox"/>	Fail

Test Data  Yes  N/A

Test Plot  Yes (See below)  N/A


Dwell Time measurement result


Type	Modulation	CH	Pulse Width (ms)	Dwell Time (ms)	Limit (ms)	Result
Dwell Time	GFSK	Low	3.02	322.133	400	Pass
		Mid	3.03	323.200	400	Pass
		High	3.04	324.267	400	Pass
	$\pi/4$ DQPSK	Low	3.04	324.267	400	Pass
		Mid	3.06	326.400	400	Pass
		High	3.07	327.467	400	Pass
	8-DPSK	Low	3.02	322.133	400	Pass
		Mid	3.02	322.133	400	Pass
		High	3.03	323.200	400	Pass

Note: Dwell time=Pulse Time (ms)  $\times (1600 \div 6 \div 79) \times 31.6$

## Test Plots

### Dwell Time measurement result






## 6.7 Band Edge & Restricted Band

Temperature	22 °C
Relative Humidity	51%
Atmospheric Pressure	1009mbar
Test date :	May 09, 2017
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.□	<input checked="" type="checkbox"/>
Test Setup	 <p>The diagram illustrates the test setup. A Turn Table is positioned on a Ground Plane. An EUT &amp; Support Units is placed on the turn table. A vertical Ant. Tower is connected to the EUT. The distance between the EUT and the Ant. Tower is 3m. The height of the EUT is 0.8/1.5m. The height of the Ant. Tower is 1-4m Variable. A Test Receiver is connected to the Ant. Tower to measure the signal.</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Radiated Method Only</p> <ul style="list-style-type: none"> <li>- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.</li> <li>- 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range,</li> </ul>		

	<p>and make sure the instrument is operated in its linear range.</p> <ul style="list-style-type: none"> <li>- 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below:           <ul style="list-style-type: none"> <li>a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</li> <li>b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</li> <li>c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</li> </ul> </li> <li>- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.</li> <li>- 5. Repeat above procedures until all measured frequencies were complete.</li> </ul>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail


Test Data     Yes       N/A

Test Plot     Yes (See below)       N/A


## Test Plots

### GFSK Mode:





Date: 9.MAY.2017 11:59:28



Date: 9.MAY.2017 13:32:40

#### GFSK-Left Side-PK

**Note: F1 is frequency 2400MHz**

#### GFSK-Right Side-PK

**Note: F1 is frequency 2483.5MHz**


Note: (no need if PK value less than the AV limit)


Note: (no need if PK value less than the AV limit)

GFSK-Left Side-AV


GFSK-Right Side-AV

$\pi/4$  DQPSK Mode:





Date: 9.MAY.2017 12:01:09



Date: 9.MAY.2017 13:29:37

$\pi/4$  DQPSK-Left Side-PK

**Note: F1 is frequency 2400MHz**

$\pi/4$  DQPSK-Right Side-PK

**Note: F1 is frequency 2483.5MHz**



Note: (no need if PK value less than the AV limit)


Note: (no need if PK value less than the AV limit)

$\pi/4$  DQPSK-Left Side-AV

$\pi/4$  DQPSK-Right Side-AV

### 8-DPSK Mode:


 <p>* RBW 1 MHz * Att 5 dB Ref 102.0 dB<math>\mu</math>V VBW 3 MHz SWT 2.5ms <b>M1[1]</b> 49.43 dB<math>\mu</math>V 2.390920000 GHz</p> <p>1Pk Max 90 dB<math>\mu</math>V Line Limit-L 74 Limit-L 74 Tdf 50 dB<math>\mu</math>V M2 M1 F1</p> <p>Start 2.31 GHz Stop 2.44 GHz</p> <p>Date: 9.MAY.2017 13:43:12</p>	 <p>* RBW 1 MHz * Att 5 dB Ref 102.0 dB<math>\mu</math>V VBW 3 MHz SWT 2.5ms <b>M1[1]</b> 51.94 dB<math>\mu</math>V 2.494790000 GHz</p> <p>1Pk Max 90 dB<math>\mu</math>V Line Limit-R 74 Limit-R 74 Tdf 50 dB<math>\mu</math>V M1 F1</p> <p>Start 2.44 GHz Stop 2.5 GHz</p> <p>Date: 9.MAY.2017 13:54:06</p>
<p>8DPSK-Hopping Left Side-PK</p> <p><b>Note: F1 is frequency 2400MHz</b></p>	<p>8DPSK-Hopping Right Side-PK</p> <p><b>Note: F1 is frequency 2483.5MHz</b></p>
<p>Note: (no need if PK value less than the AV limit)</p>	<p>Note: (no need if PK value less than the AV limit)</p>
<p>8DPSK-Hopping Left-AV</p>	<p>8DPSK-Hopping Right-AV</p>



## 6.8 AC Power Line Conducted Emissions

Temperature	25 °C
Relative Humidity	53%
Atmospheric Pressure	1020mbar
Test date :	April 20, 2017
Tested By :	Loren Luo

### Requirement(s):


Spec	Item	Requirement	Applicable														
47CFR§15.207, RSS210 (A8.1)	a)	<p>For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.</p> <table border="1"> <thead> <tr> <th rowspan="2">Frequency ranges (MHz)</th> <th colspan="2">Limit (dB<math>\mu</math>V)</th> </tr> <tr> <th>QP</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15 ~ 0.5</td> <td>66 – 56</td> <td>56 – 46</td> </tr> <tr> <td>0.5 ~ 5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5 ~ 30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency ranges (MHz)	Limit (dB $\mu$ V)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50	<input checked="" type="checkbox"/>
Frequency ranges (MHz)	Limit (dB $\mu$ V)																
	QP	Average															
0.15 ~ 0.5	66 – 56	56 – 46															
0.5 ~ 5	56	46															
5 ~ 30	60	50															
Test Setup	 <p><b>Note:</b> 1. Support units were connected to second LISN. 2. Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>																
Procedure	<ol style="list-style-type: none"> <li>The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.</li> <li>The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains.</li> <li>The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss</li> </ol>																

	<p>coaxial cable.</p> <ol style="list-style-type: none"> <li>4. All other supporting equipment were powered separately from another main supply.</li> <li>5. The EUT was switched on and allowed to warm up to its normal operating condition.</li> <li>6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.</li> <li>7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz.</li> <li>8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).</li> </ol>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data       Yes       N/A

Test Plot       Yes (See below)       N/A

Test Mode: Bluetooth Mode




**Test Data**

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBuV)	Detector	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)
1	L1	0.4932	29.68	QP	10.03	39.71	56.11	-16.40
2	L1	0.4932	19.55	AVG	10.03	29.58	46.11	-16.53
3	L1	0.5790	30.32	QP	10.03	40.35	56.00	-15.65
4	L1	0.5790	19.61	AVG	10.03	29.64	46.00	-16.36
5	L1	1.1445	31.04	QP	10.03	41.07	56.00	-14.93
6	L1	1.1445	26.16	AVG	10.03	36.19	46.00	-9.81
7	L1	1.9050	31.03	QP	10.04	41.07	56.00	-14.93
8	L1	1.9050	25.83	AVG	10.04	35.87	46.00	-10.13
9	L1	2.6694	30.42	QP	10.05	40.47	56.00	-15.53
10	L1	2.6694	25.35	AVG	10.05	35.40	46.00	-10.60
11	L1	4.1934	29.77	QP	10.07	39.84	56.00	-16.16
12	L1	4.1934	24.52	AVG	10.07	34.59	46.00	-11.41


**Test Mode:** Bluetooth Mode



Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBuV)	Detector	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)
1	N	0.1773	34.64	QP	10.02	44.66	64.61	-19.95
2	N	0.1773	20.96	AVG	10.02	30.98	54.61	-23.63
3	N	0.2202	28.13	QP	10.02	38.15	62.81	-24.66
4	N	0.2202	15.04	AVG	10.02	25.06	52.81	-27.75
5	N	0.5712	25.64	QP	10.02	35.66	56.00	-20.34
6	N	0.5712	17.80	AVG	10.02	27.82	46.00	-18.18
7	N	0.8013	24.76	QP	10.03	34.79	56.00	-21.21
8	N	0.8013	15.39	AVG	10.03	25.42	46.00	-20.58
9	N	1.1445	26.72	QP	10.03	36.75	56.00	-19.25
10	N	1.1445	22.88	AVG	10.03	32.91	46.00	-13.09
11	N	3.4290	25.43	QP	10.05	35.48	56.00	-20.52
12	N	3.4290	21.20	AVG	10.05	31.25	46.00	-14.75

**Test Mode:** Bluetooth Mode




### Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBuV)	Detector	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)
1	L1	0.2280	41.77	QP	10.03	51.80	62.52	-10.72
2	L1	0.2280	33.21	AVG	10.03	43.24	52.52	-9.28
3	L1	0.2904	36.13	QP	10.03	46.16	60.51	-14.35
4	L1	0.2904	29.18	AVG	10.03	39.21	50.51	-11.30
5	L1	0.3216	43.90	QP	10.03	53.93	59.67	-5.74
6	L1	0.3216	36.49	AVG	10.03	46.52	49.67	-3.15
7	L1	1.1445	28.43	QP	10.03	38.46	56.00	-17.54
8	L1	1.1445	21.49	AVG	10.03	31.52	46.00	-14.48
9	L1	1.9050	28.74	QP	10.04	38.78	56.00	-17.22
10	L1	1.9050	21.93	AVG	10.04	31.97	46.00	-14.03
11	L1	4.1934	26.05	QP	10.07	36.12	56.00	-19.88
12	L1	4.1934	18.98	AVG	10.07	29.05	46.00	-16.95

**Test Mode:** Bluetooth Mode



### Test Data


Phase Neutral Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBuV)	Detector	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)
1	N	0.2280	42.82	QP	10.02	52.84	62.52	-9.68
2	N	0.2280	33.61	AVG	10.02	43.63	52.52	-8.89
3	N	0.3255	42.43	QP	10.02	52.45	59.57	-7.12
4	N	0.3255	34.42	AVG	10.02	44.44	49.57	-5.13
5	N	1.1406	30.60	QP	10.03	40.63	56.00	-15.37
6	N	1.1406	25.69	AVG	10.03	35.72	46.00	-10.28
7	N	1.8972	30.35	QP	10.04	40.39	56.00	-15.61
8	N	1.8972	25.15	AVG	10.04	35.19	46.00	-10.81
9	N	3.4173	29.42	QP	10.05	39.47	56.00	-16.53
10	N	3.4173	20.18	AVG	10.05	30.23	46.00	-15.77
11	N	9.1230	30.12	QP	10.13	40.25	60.00	-19.75
12	N	9.1230	21.43	AVG	10.13	31.56	50.00	-18.44

## 6.9 Radiated Emissions & Restricted Band

Temperature	25 °C
Relative Humidity	53%
Atmospheric Pressure	1020mbar
Test date :	April 20, 2017
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable										
47CFR§15. 205, §15.209, §15.247(d)	a)	<p>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</p> <table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th>Field Strength (µV/m)</th> </tr> </thead> <tbody> <tr> <td>30 – 88</td> <td>100</td> </tr> <tr> <td>88 – 216</td> <td>150</td> </tr> <tr> <td>216 - 960</td> <td>200</td> </tr> <tr> <td>Above 960</td> <td>500</td> </tr> </tbody> </table>	Frequency range (MHz)	Field Strength (µV/m)	30 – 88	100	88 – 216	150	216 - 960	200	Above 960	500	<input checked="" type="checkbox"/>
Frequency range (MHz)	Field Strength (µV/m)												
30 – 88	100												
88 – 216	150												
216 - 960	200												
Above 960	500												
Test Setup		 <p>The diagram illustrates the test setup. A 'Turn Table' is positioned on a 'Ground Plane'. A 'EUT &amp; Support Units' is mounted on the turn table. A 'Ant. Tower' is connected to the EUT and is height-adjustable, with a '1-4m Variable' height indicator. A 'Test Receiver' is connected to the tower and is shown with a display screen and control buttons.</p>											
Procedure		<ol style="list-style-type: none"> <li>The EUT was switched on and allowed to warm up to its normal operating condition.</li> <li>The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:</li> </ol>											


	<p>a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen.</p> <p>b. The EUT was then rotated to the direction that gave the maximum emission.</p> <p>c. Finally, the antenna height was adjusted to the height that gave the maximum emission.</p> <p>3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</p> <p>4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</p> <p>The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</p> <p>5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A

Test Plot  Yes (See below)  N/A

**Test Mode:** Bluetooth Mode

**Below 1GHz**




**Test Data**

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detect or	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degr ee
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	( )
1	H	366.8231	46.39	QP	15.00	22.10	2.03	41.32	46.00	-4.68	100	221
2	H	252.0627	38.74	peak	11.49	22.29	1.70	29.64	46.00	-16.36	100	46
3	H	181.2834	36.23	peak	11.07	22.26	1.38	26.42	43.50	-17.08	200	9
4	H	47.8260	37.94	peak	9.36	22.34	0.78	25.74	40.00	-14.26	100	331
5	H	30.5306	26.95	peak	20.99	22.28	0.63	26.29	40.00	-13.71	100	52
6	H	74.3955	32.79	peak	7.71	22.40	0.96	19.06	40.00	-20.94	200	41

### Below 1GHz



### Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency (MHz)	Reading (dB <sub>u</sub> V/m)	Detect or	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dB <sub>u</sub> V/m)	Limit (dB <sub>u</sub> V/m)	Margin (dB)	Height (cm)	Degr ee
1	V	173.8135	38.64	peak	11.49	22.26	1.36	29.23	43.50	-14.27	100	15
2	V	404.6665	34.27	peak	15.79	22.00	2.02	30.08	46.00	-15.92	100	197
3	V	89.5900	39.66	peak	7.98	22.32	0.96	26.28	43.50	-17.22	100	129
4	V	46.8303	48.50	QP	9.79	22.32	0.77	36.74	40.00	-3.26	100	0
5	V	51.6616	47.67	QP	8.22	22.38	0.79	34.30	40.00	-5.70	100	143
6	V	30.4238	33.09	peak	21.07	22.28	0.63	32.51	40.00	-7.49	100	191

## Above 1GHz

Test Mode:	Transmitting Mode
------------	-------------------

Low Channel: 8-DPSK Mode (Worst Case) (2402 MHz)

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4804	38.89	AV	V	33.67	6.86	32.66	46.76	54	-7.24
4804	39.44	AV	H	33.67	6.86	32.66	47.31	54	-6.69
4804	48.48	PK	V	33.67	6.86	32.66	56.35	74	-17.65
4804	46.22	PK	H	33.67	6.86	32.66	54.09	74	-19.91
17808	23.74	AV	V	45.03	11.21	32.38	47.6	54	-6.4
17808	25.34	AV	H	45.03	11.21	32.38	49.2	54	-4.8
17808	40.75	PK	V	45.03	11.21	32.38	64.61	74	-9.39
17808	42.24	PK	H	45.03	11.21	32.38	66.1	74	-7.9

Middle Channel: 8-DPSK (Worst Case) (2441 MHz)

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4882	38.73	AV	V	33.71	6.95	32.74	46.65	54	-7.35
4882	39.19	AV	H	33.71	6.95	32.74	47.11	54	-6.89
4882	49.41	PK	V	33.71	6.95	32.74	57.33	74	-16.67
4882	47	PK	H	33.71	6.95	32.74	54.92	74	-19.08
17808	25.58	AV	V	45.15	11.18	32.41	49.5	54	-4.5
17808	23.08	AV	H	45.15	11.18	32.41	47	54	-7
17808	40.91	PK	V	45.15	11.18	32.41	64.83	74	-9.17
17808	40.73	PK	H	45.15	11.18	32.41	64.65	74	-9.35

High Channel:  $\pi/4$  DQPSK Mode (Worst Case) (2480 MHz)

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4960	37.91	AV	V	33.9	6.76	32.74	45.83	54	-8.17
4960	38.45	AV	H	33.9	6.76	32.74	46.37	54	-7.63
4960	48.27	PK	V	33.9	6.76	32.74	56.19	74	-17.81
4960	47.03	PK	H	33.9	6.76	32.74	54.95	74	-19.05
17820	23.11	AV	V	45.22	11.35	32.38	47.3	54	-6.7
17820	24.27	AV	H	45.22	11.35	32.38	48.46	54	-5.54
17820	42.09	PK	V	45.22	11.35	32.38	66.28	74	-7.72
17820	41.33	PK	H	45.22	11.35	32.38	65.52	74	-8.48

**Note:**

1, The testing has been conformed to  $10*2480\text{MHz}=24,800\text{MHz}$

2, All other emissions more than 30 dB below the limit

3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

## Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
<b>AC Line Conducted</b>					
EMI test receiver	ESCS30	8471241027	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191106	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191107	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
LISN	ISN T800	34373	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Transient Limiter	LIT-153	531118	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
<b>RF conducted test</b>					
Agilent ESA-E SERIES	E4407B	MY45108319	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
<b>Radiated Emissions</b>					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Positioning Controller	UC3000	MF780208282	11/18/2016	11/17/2017	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>

## Annex B. EUT And Test Setup Photographs

### Annex B.i. Photograph: EUT External Photo


EUT - Front View




EUT - Rear View



EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View



**Annex B.ii. Photograph: EUT Internal Photo**


Cover Off - Top View 1



Cover Off - Top View 2




Battery - Front View




Battery - Rear View




Mainboard – Front View




Mainboard - Rear View



BT - Antenna View




**Annex B.iii. Photograph: Test Setup Photo**




## Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

### Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions ( Below 1GHz ) .



Block Configuration Diagram for Radiated Emissions ( Above 1GHz ) .



## Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

### Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Lenovo	Laptop	E40	LR-1EHRX
SAMSUNG	Adapter	P6200	SA5230
SAMSUNG	Phone	,W899	BR630

### Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	SA5230

## Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

## Annex E. DECLARATION OF SIMILARITY

N/A