



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

BLUETOOTH HEADPHONE

Model: MA-876, MA-876A

Brand: N/A

Test Report Number:

C140305Z01-RP1

Prepared for

SHENZHEN QI SHENGLONG INDUSTRIALIST CO.,LTD.

5F., Blk 6A, Jing Nan Industry, Bai Ge long, Buji, Shenzhen, China

Prepared by

COMPLIANCE CERTIFICATION SERVICES (SHENZHEN) INC.

**No.10-1, Mingkeda Logistics Park, No.18, Huanguan South Rd.,
Guan Lan Town, Baoan District, Shenzhen China**

TEL: 86-755-28055000

FAX: 86-755-28055221

Issued Date: March 25, 2014



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST or any government agencies. The test result of this report relate only to the tested sample identified in this report.



Revision History

Rev.	Issue No.	Revisions	Effect Page	Revised By
00	C140305Z01-RP1	Initial Issue	ALL	Nancy Fu

**TABLE OF CONTENTS**

1. TEST RESULT CERTIFICATION	4
2. EUT DESCRIPTION.....	5
3. TEST METHODOLOGY.....	6
3.1 DESCRIPTION OF TEST MODES	6
4. FACILITIES AND ACCREDITATIONS	7
4.1 FACILITIES.....	7
4.2 ACCREDITATIONS	7
4.3 MEASUREMENT UNCERTAINTY	7
5. SETUP OF EQUIPMENT UNDER TEST	8
5.1 SETUP CONFIGURATION OF EUT	8
5.2 SUPPORT EQUIPMENT	8
6. FCC PART 15.247 REQUIREMENTS	9
6.1 20dB BANDWIDTH.....	9
6.2 PEAK POWER.....	13
6.3 PEAK POWER SPECTRAL DENSITY	14
6.4 BAND EDGES MEASUREMENT	16
6.5 FREQUENCY SEPARATION	26
6.6 NUMBER OF HOPPING FREQUENCY	29
6.7 TIME OF OCCUPANCY (DWELL TIME).....	32
6.8 SPURIOUS EMISSIONS	39
6.9 POWERLINE CONDUCTED EMISSIONS	57



1. TEST RESULT CERTIFICATION

Product	BLUETOOTH HEADPHONE
Model	MA-876, MA-876A
Brand	N/A
Tested	March 5~ March 24, 2014
Applicant	SHENZHEN QI SHENGLONG INDUSTRIALIST CO.,LTD. 5F.,Blk 6A, Jing Nan Industry, Bai Ge long,Buji, Shenzhen, China
Manufacturer	DONGGUAN FEIHAO INDUSTRIALIST CO.,LTD No.8,Fengyi Road, Dakan Village, Huangjiang, DongGuan, China

APPLICABLE STANDARDS

STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4:2009 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.207, 15.209 and 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Sunday Hu
Supervisor of EMC Dept.
Compliance Certification Service Inc.

Reviewed by:

Ruby Zhang
Supervisor of Report Dept.
Compliance Certification Service Inc.



2. EUT DESCRIPTION

Product	BLUETOOTH HEADPHONE
Model Number	MA-876, MA-876A
Brand	N/A
Model Discrepancy	The models are identical except different appearance.
Identify Number	C140305Z01-RP1
Power Supply	DC5V supplied by the PC or DC3.7V supplied by the battery
Received Date	March 5, 2014
Frequency Range	2402 ~ 2480 MHz
Transmit Power	GFSK : 3.12dBm 8DPSK : 3.43dBm
Modulation Technique	FHSS (GFSK for 1Mbps, $\pi/4$ -DQPSK for 2Mbps, 8DPSK for 3Mbps)
Number of Channels	79 Channels
Antenna Specification	Built-in Antenna with 0 dBi gain(Max)
Temperature Range	0°C ~ +40°C
USB Cable	Shielded, 0.50m

Note: This submittal(s) (test report) is intended for FCC ID: Y56QSLMA876X filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



3. TEST METHODOLOGY

3.1 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

The following test mode(s) were scanned during the preliminary test below 1G:

Test Item	Test mode	Worse mode
Conducted Emission	Mode 1: Charge by PC and BT play	<input checked="" type="checkbox"/>
Radiated Emission	Mode 1: TX	<input checked="" type="checkbox"/>

Above 1G, Channel Low (2402MHz)、Mid (2441MHz) and High (2480MHz) were chosen for full testing for GFSK and 8DPSK.



4. FACILITIES AND ACCREDITATIONS

4.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

No.10-1, Mingkeda Logistics Park, No.18, Huanguan South Rd., Guan Lan Town, Baoan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.4:2009, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

4.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

USA	A2LA
China	CNAS

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

USA	FCC
Japan	VCCI(C-3478, R-3135, T-652, G-624)
Canada	INDUSTRY CANADA
Taiwan	BSMI
Norway	Nemko

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsrf.com>

4.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Uncertainty
Radiated Emission, 30 to 200 MHz Test Site : 966(2)	+/-3.6880dB
Radiated Emission, 200 to 1000 MHz Test Site : 966(2)	+/-3.6695dB
Radiated Emission, 1 to 8 GHz	+/-5.1782dB
Radiated Emission, 8 to 18 GHz	+/-5.2173dB
Conducted Emissions	+/-3.6836dB
Band Width	178kHz
Peak Output Power MU	+/-1.906dB
Band Edge MU	+/-0.182dB
Channel Separation MU	416.178Hz
Duty Cycle MU	0.054ms
Frequency Stability MU	226Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

The measured result is above (below) the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance (non-compliance) is more probable than non-compliance) with the specification limit.



5. SETUP OF EQUIPMENT UNDER TEST

5.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

5.2 SUPPORT EQUIPMENT

No.	Equipment	Model No.	Serial No.	FCC ID	Brand	Data Cable	Power Cord
1	PC	DCSM1F	B8AC6F2474CE	N/A	DELL	N/A	Unshielded 1.50m
2	Printer	D1668	CN9CKCB2RG	N/A	HP	Unshielded 1.20m	Unshielded 2.00m
3	Modem	E17OSC	CN-DOV539-64180 -DAP-3E1S	N/A	DELL	Unshielded 1.20m	Unshielded 1.50M
4	Monitor	Compaq LA2405wg	CN401602SL	N/A	DELL	Shielded 1.50m	Unshielded 1.50m
5	Keyboard	SK8115	CNODJ3B7161608 A014	N/A	DELL	Unshielded 1.45m	N/A
6	Mouse	KB212-B	CN09RRC4475116 80996	N/A	DELL	Unshielded 1.45m	N/A

Notes:

Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.



6. FCC PART 15.247 REQUIREMENTS

6.1 20dB BANDWIDTH


None; for reporting purpose only.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2014	03/08/2015

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST CONFIGURATION



TEST PROCEDURE

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT, then connect a low loss RF cable from antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW=30kHz, VBW=100kHz, Span=3MHz, Sweep = auto.
4. Mark the peak frequency and 20dB (upper and lower) frequency.
5. Repeat until all the test channels are investigated.


TEST RESULTS

No non-compliance noted




Test plot
GFSK

20dB Bandwidth(CH Low)



Transmit Freq Error -152.892 kHz
x dB Bandwidth 994.405 kHz

20dB Bandwidth (CH Mid)




Transmit Freq Error -23.890 kHz
x dB Bandwidth 986.427 kHz

**20dB Bandwidth (CH High)**

Agilent

R T




Transmit Freq Error -23.002 kHz
x dB Bandwidth 957.563 kHz



8DPSK**20dB Bandwidth (CH Low)**

Agilent

R T



Transmit Freq Error -21.185 kHz
x dB Bandwidth 1.271 MHz

**20dB Bandwidth (CH Mid)****20dB Bandwidth (CH High)**



6.2 PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:


1. For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6dBi.
3. The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Power Meter	Anritsu	ML2495A	1204003	03/09/2014	03/08/2015
Power Sensor	Anritsu	MA2411B	1126150	03/09/2014	03/08/2015
Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2014	03/08/2015

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the RF Power Meter. The RF Power Meter is set to the peak power detection.



TEST RESULTS

No non-compliance noted

Test Data

GFSK

Channel	Frequency (MHz)	Reading Power (dBm)	Factor (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2402	-0.41	3.50	3.09	0.00204	1	PASS
Mid	2441	-0.45	3.50	3.05	0.00202		PASS
High	2480	-0.38	3.50	3.12	0.00205		PASS

8DPSK

Channel	Frequency (MHz)	Reading Power (dBm)	Factor (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2402	-0.57	3.50	2.93	0.00196	1	PASS
Mid	2441	-0.07	3.50	3.43	0.00220		PASS
High	2480	-0.57	3.50	2.93	0.00196		PASS



6.3 PEAK POWER SPECTRAL DENSITY

LIMIT


1. For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
2. The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2014	03/08/2015

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 300kHz, Sweep=100s
4. Record the max. reading.
5. Repeat the above procedure until the measurements for all frequencies are completed.

TEST RESULTS

Not applicable. Since EUT is the Bluetooth device.

6.4 BAND EDGES MEASUREMENT


LIMIT

According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

MEASUREMENT EQUIPMENT USED

Radiated Emission Test Site 966(2)					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2014	03/08/2015
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	03/09/2014	03/08/2015
Amplifier	MITEQ	AM-1604-3000	1123808	03/18/2014	03/18/2015
High Noise Amplifier	Agilent	8449B	3008A01838	03/18/2014	03/18/2015
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	06/21/2013	06/21/2014
Bilog Antenna	SCHAFFNER	CBL6143	5082	03/02/2014	03/01/2015
Horn Antenna	SCHWARZBECK	BBHA9120	D286	03/02/2014	03/01/2015
Loop Antenna	A, R, A	PLA-1030/B	1029	03/19/2014	03/18/2015
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller	CT	N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	03/04/2014	03/03/2015
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Test S/W	FARAD		LZ-RF / CCS-SZ-3A2		

Test Configuration





TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=2.4kHz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

TEST RESULTS

Refer to attach spectrum analyzer data chart.




Test Data (GFSK)

Band Edges (CH-Low)


Detector mode: Peak



Polarity: Vertical



Detector mode: Average

Polarity: Vertical



**Detector mode: Peak****Polarity: Horizontal****Detector mode: Average****Polarity: Horizontal**



Band Edges (CH-High)


Detector mode: Peak

Polarity: Vertical

Agilent

R T

Mkr1 2.479 96 GHz
70.50 dB μ V/m




Detector mode: Average

Polarity: Vertical

Agilent

R T

Mkr1 2.479 96 GHz
70.23 dB μ V/m






Detector mode: Peak

Polarity: Horizontal


Agilent





Detector mode: Average

Polarity: Horizontal

Agilent



**8DPSK****Band Edges (CH-Low)****Detector mode: Peak****Polarity: Vertical****Detector mode: Average****Polarity: Vertical**



Detector mode: Peak

Agilent

Ref 96.99 dB μ V/m

#Atten 20 dB

Polarity: Horizontal

R T

Mkr2 2.390 0 GHz

42.32 dB μ V/m

#Peak

Log

10

dB/

Offst

10

dB

LgAv

M1 S2

Start 2.310 0 GHz

Stop 2.410 0 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 1 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.402 0 GHz	81.57 dB μ V/m
2	(1)	Freq	2.390 0 GHz	42.32 dB μ V/m

Detector mode: Average

Agilent

Ref 96.99 dB μ V/m

#Atten 20 dB

Polarity: Horizontal

R T

Mkr2 2.390 0 GHz

32.28 dB μ V/m

#Peak

Log

10

dB/

Offst

10

dB

LgAv

M1 S2

Start 2.310 0 GHz

Stop 2.410 0 GHz

#Res BW 1 MHz

#VBW 2.4 kHz

Sweep 32.52 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.402 0 GHz	81.42 dB μ V/m
2	(1)	Freq	2.390 0 GHz	32.28 dB μ V/m




Band Edges (CH-High)

Detector mode: Peak

Polarity: Vertical


Agilent



Detector mode: Average

Polarity: Vertical

Agilent



**Detector mode: Peak**

* Agilent

Ref 96.99 dB μ V/m

#Atten 20 dB

Polarity: Horizontal

R T

Mkr1 2.479 96 GHz
81.88 dB μ V/m

#Peak

Log
10
dB/
Offst
10
dB

LgAv

M1 S2

Start 2.475 00 GHz

#Res BW 1 MHz

Stop 2.500 00 GHz

Sweep 1 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.479 96 GHz	81.88 dB μ V/m
2	(1)	Freq	2.483 50 GHz	43.12 dB μ V/m

Detector mode: Average

* Agilent

Ref 96.99 dB μ V/m

#Atten 20 dB

Polarity: Horizontal

R T

Mkr1 2.479 96 GHz
81.75 dB μ V/m

#Peak

Log
10
dB/
Offst
10
dB

LgAv

M1 S2

Start 2.475 00 GHz

#Res BW 2.4 kHz

Stop 2.500 00 GHz

Sweep 8.16 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.479 96 GHz	81.75 dB μ V/m
2	(1)	Freq	2.483 50 GHz	32.54 dB μ V/m



6.5 FREQUENCY SEPARATION

LIMIT


According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2014	03/08/2015

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = middle of hopping channel.
4. Set the spectrum analyzer as RBW=30kHz, VBW=30kHz, Adjust Span to 4 MHz, Sweep = auto.
5. Max hold. Mark 3 Peaks of hopping channel and record the 3 peaks frequency.

TEST RESULTS

No non-compliance noted



Test Data

GFSK

Channel Separation (MHz)	Two-thirds of the 20 dB Bandwidth (kHz)	Channel Separation Limit	Result
1.000	662.937	> Two-thirds of the 20 dB Bandwidth	Pass

8DPSK

Channel Separation (MHz)	Two-thirds of the 20 dB Bandwidth (kHz)	Channel Separation Limit	Result
1.000	811.333	> Two-thirds of the 20 dB Bandwidth	Pass

**GFSK****Test Plot****Measurement of Channel Separation****20 dB bandwidth(CH Low)**


Transmit Freq Error -152.892 kHz
x dB Bandwidth 994.405 kHz




8DPSK

Test Plot

Measurement of Channel Separation



20 dB bandwidth(CH Low)



Transmit Freq Error -21.185 kHz
x dB Bandwidth 1.271 MHz



6.6 NUMBER OF HOPPING FREQUENCY

LIMIT


According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 15 hopping frequencies.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2014	03/08/2015

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set spectrum analyzer Start=2400MHz, Stop = 2441.5MHz, Sweep = 1ms and Start=2441.5MHz, Stop = 2483.5MHz, Sweep = 1ms.
4. Set the spectrum analyzer as RBW, VBW=300kHz,
5. Max hold, view and count how many channel in the band.

TEST RESULTS

No non-compliance noted


Test Data

Result (No. of CH)	Limit (No. of CH)	Result
79	>15	PASS


Test Plot (GFSK)



Channel Number

2.400 GHz – 2.4415 GHz



2.4415 GHz – 2.4835 GHz



Test Plot (8DPSK)Channel Number**2.400 GHz – 2.4415 GHz****2.4415 GHz – 2.4835 GHz**



6.7 TIME OF OCCUPANCY (DWELL TIME)

LIMIT


According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2014	03/08/2015

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
5. Repeat above procedures until all frequency measured were complete.



TEST RESULTS

No non-compliance noted

Test Data

GFSK

DH 1

CH Mid: $0.411 * (1600/2)/79 * 31.6 = 131.520$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	0.411	131.520	31.60	400.00	PASS

DH 3

CH Mid: $1.668 * (1600/4)/79 * 31.6 = 266.880$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	1.668	266.880	31.60	400.00	PASS

DH 5

CH Mid: $2.924 * (1600/6)/79 * 31.6 = 311.893$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	2.924	311.893	31.60	400.00	PASS



Test Data

8DPSK

DH 1

CH Mid: $0.420^* (1600/2)/79 * 31.6 = 134.400$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	0.420	134.400	31.60	400.00	PASS

DH 3



CH Mid: $1.672^* (1600/4)/79 * 31.6 = 267.520$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	1.672	267.520	31.60	400.00	PASS

DH 5

CH Mid: $2.936^* (1600/6)/79 * 31.6 = 313.173$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	2.936	313.173	31.60	400.00	PASS


Test Plot**GFSK****DH 1****(CH Mid)****DH 3****(CH Mid)**



DH 5


(CH Mid)

Agilent




**Test Plot**
8DPSK**DH 1****(CH Mid)**

Agilent

**DH 3****(CH Mid)**

Agilent






DH 5

(CH Mid)

 Agilent





6.8 SPURIOUS EMISSIONS

6.8.1. CONDUCTED MEASUREMENT

LIMIT


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2014	03/08/2015

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE



Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.

Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.


TEST RESULTS

No non-compliance noted


Test Plot (GFSK)**CH Low (30MHz ~26.5GHz)****CH Low (2.31GHz ~2.41GHz)**



CH Mid (30MHz ~ 26.5GHz)






CH High (30MHz ~ 26.5GHz)






CH High (2.475GHz ~ 2.5GHz)




**Test Plot (8DPSK)****CH Low (30MHz ~26.5GHz)****CH Low (2.31GHz ~2.41GHz)**



CH Mid (30MHz ~ 26.5GHz)




CH High (30MHz ~ 26.5GHz)





CH High (2.475GHz ~ 2.5GHz)





6.8.2. RADIATED EMISSIONS

LIMIT

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Note: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength (μ V/m at 3-meter)	Field Strength (dB μ V/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54


**MEASUREMENT EQUIPMENT USED**

Radiated Emission Test Site 966(2)					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	03/09/2014	03/08/2015
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	03/09/2014	03/08/2015
Amplifier	MITEQ	AM-1604-3000	1123808	03/18/2014	03/18/2015
High Noise Amplifier	Agilent	8449B	3008A01838	03/18/2014	03/18/2015
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	06/21/2013	06/21/2014
Bilog Antenna	SCHAFFNER	CBL6143	5082	03/02/2014	03/01/2015
Horn Antenna	SCHWARZBECK	BBHA9120	D286	03/02/2014	03/01/2015
Loop Antenna	A、R、A	PLA-1030/B	1029	03/19/2014	03/18/2015
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller	CT	N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	03/04/2014	03/03/2015
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Test S/W	FARAD	LZ-RF / CCS-SZ-3A2			


Remark: Each piece of equipment is scheduled for calibration once a year.


TEST CONFIGURATION

Below 30MHz



Below 1 GHz



Above 1 GHz**TEST PROCEDURE**

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.



TEST RESULTS

Below 1 GHz

Operation Mode: TX

Test Date: March 24, 2014

Temperature: 24°C

Tested by: Jimmy Zheng

Humidity: 52% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dB μ V)	Correction Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Antenna Pole (V/H)	Remark
96.9300	61.92	-22.52	39.40	43.50	-4.10	V	QP
121.1800	58.53	-20.18	38.35	43.50	-5.15	V	QP
146.4000	60.18	-18.98	41.20	43.50	-2.30	V	QP
219.1500	58.33	-18.10	40.23	46.00	-5.77	V	QP
243.4000	55.38	-17.50	37.88	46.00	-8.12	V	QP
267.6500	59.46	-18.45	41.01	46.00	-4.99	V	QP
<hr/>							
96.9300	62.10	-22.52	39.58	43.50	-3.92	H	QP
109.5400	60.02	-20.93	39.09	43.50	-4.41	H	QP
121.1800	60.04	-20.18	39.86	43.50	-3.64	H	QP
146.4000	59.68	-18.98	40.70	43.50	-2.80	H	QP
219.1500	59.49	-18.10	41.39	46.00	-4.61	H	QP
316.1500	60.24	-17.81	42.43	46.00	-3.57	H	QP

****Remark:** No emission found between lowest internal used/generated frequency to 30MHz.

Notes:

1. Measuring frequencies from 9kHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30MHz to 1GHz were made with an instrument using Peak/Quasi-peak detector mode.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 120kHz.
5. Frequency (MHz). = Emission frequency in MHz
Reading (dB μ V) = Receiver reading
Correction Factor(dB/m) = Antenna factor + Cable loss – Amplifier gain
Actual FS (dB μ V/m) = Reading (dB μ V) + Corr. Factor (dB/m)
Limit (dB μ V/m) = Limit stated in standard
Margin(dB) = Measured (dB μ V/m) – Limits (dB μ V/m)
Antenna Pole(V/H) = Current carrying line of reading

**Above 1 GHz****GFSK**

Operation Mode: TX(CH Low)
Temperature: 24°C
Humidity: 52% RH

Test Date: March 24, 2014
Tested by: Jimmy Zheng
Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dB μ V)	Correction Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1279.000	64.72	-19.04	45.68	74.00	-28.32	V	peak
1999.000	66.29	-18.86	47.43	74.00	-26.57	V	peak
2467.000	62.80	-17.31	45.49	74.00	-28.51	V	peak
2773.000	62.14	-15.99	46.15	74.00	-27.85	V	peak
3034.000	61.39	-14.88	46.51	74.00	-27.49	V	peak
3196.000	61.55	-14.37	47.18	74.00	-26.82	V	peak
1099.000	64.13	-18.88	45.25	74.00	-28.75	H	peak
1567.000	63.92	-19.33	44.59	74.00	-29.41	H	peak
1999.000	63.39	-18.86	44.53	74.00	-29.47	H	peak
2503.000	62.65	-17.19	45.46	74.00	-28.54	H	peak
2845.000	62.38	-15.68	46.70	74.00	-27.30	H	peak
3502.000	60.94	-13.40	47.54	74.00	-26.46	H	peak

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

5. Frequency (MHz) = Emission frequency in MHz

Reading (dB μ V/m) = Uncorrected Analyzer / Receiver Reading

Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain

Limit (dB μ V/m) = Limit stated in standard

Margin (dB) = Result (dB μ V/m) - Limit (dB μ V/m)

Pk = Peak Reading

AV. = Average Reading

Remark = Mark Peak Reading or Average Reading

**Operation Mode:** TX(CH Mid)**Test Date:** March 24, 2014**Temperature:** 24°C**Tested by:** Jimmy Zheng**Humidity:** 52% RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dB μ V)	Correction Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1180.000	64.02	-19.01	45.01	74.00	-28.99	V	peak
1999.000	65.38	-18.86	46.52	74.00	-27.48	V	peak
2125.000	63.48	-18.44	45.04	74.00	-28.96	V	peak
2485.000	63.59	-17.25	46.34	74.00	-27.66	V	peak
2998.000	61.21	-15.00	46.21	74.00	-27.79	V	peak
3466.000	60.63	-13.51	47.12	74.00	-26.88	V	peak
<hr/>							
1108.000	63.95	-18.90	45.05	74.00	-28.95	H	peak
1396.000	63.21	-19.03	44.18	74.00	-29.82	H	peak
2125.000	62.79	-18.44	44.35	74.00	-29.65	H	peak
2422.000	62.67	-17.46	45.21	74.00	-28.79	H	peak
2791.000	62.17	-15.91	46.26	74.00	-27.74	H	peak
3610.000	61.33	-13.38	47.95	74.00	-26.05	H	peak

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.
5. Frequency (MHz) = Emission frequency in MHz
Reading (dB μ V/m) = Uncorrected Analyzer / Receiver Reading
Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain
Limit (dB μ V/m) = Limit stated in standard
Margin (dB) = Result (dB μ V/m) - Limit (dB μ V/m)
Pk = Peak Reading
AV. = Average Reading
Remark = Mark Peak Reading or Average Reading

**Operation Mode:** TX(CH High)**Test Date:**

March 24, 2014

Temperature: 24 °C**Tested by:**

Jimmy Zheng

Humidity: 52% RH**Polarity:**

Ver. / Hor.

Frequency (MHz)	Reading (dB μ V)	Correction Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1270.000	64.07	-19.04	45.03	74.00	-28.97	V	peak
1999.000	64.42	-18.86	45.56	74.00	-28.44	V	peak
2080.000	63.44	-18.59	44.85	74.00	-29.15	V	peak
2476.000	63.34	-17.28	46.06	74.00	-27.94	V	peak
2773.000	61.75	-15.99	45.76	74.00	-28.24	V	peak
3331.000	61.06	-13.94	47.12	74.00	-26.88	V	peak
<hr/>							
1099.000	64.16	-18.88	45.28	74.00	-28.72	H	peak
1999.000	63.17	-18.86	44.31	74.00	-29.69	H	peak
2530.000	62.69	-17.07	45.62	74.00	-28.38	H	peak
2800.000	63.14	-15.87	47.27	74.00	-26.73	H	peak
3502.000	60.50	-13.40	47.10	74.00	-26.90	H	peak
4402.000	61.00	-11.36	49.64	74.00	-24.36	H	peak

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.
5. Frequency (MHz) = Emission frequency in MHz
Reading (dB μ V/m) = Uncorrected Analyzer / Receiver Reading
Correction Factor (dB) = Antenna factor + Cable loss - Amplifier gain
Limit (dB μ V/m) = Limit stated in standard
Margin (dB) = Result (dB μ V/m) - Limit (dB μ V/m)
Pk = Peak Reading
AV. = Average Reading
Remark = Mark Peak Reading or Average Reading

**8DPSK****Operation Mode:** TX(CH Low)**Test Date:** March 24, 2014**Temperature:** 24°C**Tested by:** Jimmy Zheng**Humidity:** 52% RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dB μ V)	Correction Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1144.000	63.50	-18.95	44.55	74.00	-29.45	V	peak
1495.000	63.98	-19.20	44.78	74.00	-29.22	V	peak
1990.000	66.27	-18.91	47.36	74.00	-26.64	V	peak
2575.000	62.17	-16.87	45.30	74.00	-28.70	V	peak
2782.000	61.66	-15.95	45.71	74.00	-28.29	V	peak
2971.000	60.78	-15.12	45.66	74.00	-28.34	V	peak
<hr/>							
1567.000	63.62	-19.33	44.29	74.00	-29.71	H	peak
1999.000	63.58	-18.86	44.72	74.00	-29.28	H	peak
2791.000	62.19	-15.91	46.28	74.00	-27.72	H	peak
3016.000	61.32	-14.94	46.38	74.00	-27.62	H	peak
3538.000	59.97	-13.39	46.58	74.00	-27.42	H	peak
3727.000	60.80	-13.35	47.45	74.00	-26.55	H	peak

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.
5. Frequency (MHz) = Emission frequency in MHz
 Reading (dB μ V/m) = Uncorrected Analyzer / Receiver Reading
 Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain
 Limit (dB μ V/m) = Limit stated in standard
 Margin (dB) = Result (dB μ V/m) - Limit (dB μ V/m)
 Pk = Peak Reading
 AV. = Average Reading
 Remark = Mark Peak Reading or Average Reading

**Operation Mode:** TX(CH Mid)**Test Date:** March 24, 2014**Temperature:** 24°C**Tested by:** Jimmy Zheng**Humidity:** 52% RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dB μ V)	Correction Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1135.000	64.84	-18.94	45.90	74.00	-28.10	V	peak
1999.000	65.23	-18.86	46.37	74.00	-27.63	V	peak
2467.000	63.21	-17.31	45.90	74.00	-28.10	V	peak
2971.000	61.18	-15.12	46.06	74.00	-27.94	V	peak
3457.000	61.26	-13.54	47.72	74.00	-26.28	V	peak
3772.000	61.16	-13.35	47.81	74.00	-26.19	V	peak
<hr/>							
1099.000	63.98	-18.88	45.10	74.00	-28.90	H	peak
1963.000	63.31	-19.07	44.24	74.00	-29.76	H	peak
2503.000	62.57	-17.19	45.38	74.00	-28.62	H	peak
2935.000	61.32	-15.28	46.04	74.00	-27.96	H	peak
3286.000	60.51	-14.08	46.43	74.00	-27.57	H	peak
4141.000	61.25	-12.62	48.63	74.00	-25.37	H	peak

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.
5. Frequency (MHz) = Emission frequency in MHz
Reading (dB μ V/m) = Uncorrected Analyzer / Receiver Reading
Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain
Limit (dB μ V/m) = Limit stated in standard
Margin (dB) = Result (dB μ V/m) - Limit (dB μ V/m)
Pk = Peak Reading
AV. = Average Reading
Remark = Mark Peak Reading or Average Reading

**Operation Mode:** TX(CH High)**Test Date:** March 24, 2014**Temperature:** 24 °C**Tested by:** Jimmy Zheng**Humidity:** 52% RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dB μ V)	Correction Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1999.000	65.21	-18.86	46.35	74.00	-27.65	V	peak
2485.000	62.88	-17.25	45.63	74.00	-28.37	V	peak
2800.000	61.43	-15.87	45.56	74.00	-28.44	V	peak
3169.000	60.10	-14.45	45.65	74.00	-28.35	V	peak
3781.000	59.82	-13.34	46.48	74.00	-27.52	V	peak
3925.000	60.76	-13.32	47.44	74.00	-26.56	V	peak
1054.000	64.62	-18.81	45.81	74.00	-28.19	H	peak
2098.000	62.43	-18.53	43.90	74.00	-30.10	H	peak
2512.000	62.93	-17.15	45.78	74.00	-28.22	H	peak
2791.000	62.33	-15.91	46.42	74.00	-27.58	H	peak
4240.000	61.02	-12.14	48.88	74.00	-25.12	H	peak
4636.000	60.06	-10.41	49.65	74.00	-24.35	H	peak

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.
5. Frequency (MHz) = Emission frequency in MHz
Reading (dB μ V/m) = Uncorrected Analyzer / Receiver Reading
Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain
Limit (dB μ V/m) = Limit stated in standard
Margin (dB) = Result (dB μ V/m) - Limit (dB μ V/m)
Pk = Peak Reading
AV. = Average Reading
Remark = Mark Peak Reading or Average Reading



6.9 POWERLINE CONDUCTED EMISSIONS

LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50


Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

MEASUREMENT EQUIPMENT USED

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	03/09/2014	03/08/2015
LISN(EUT)	ROHDE&SCHWARZ	ENV216	101543-WX	04/20/2013	04/19/2014
LISN	EMCO	3825/2	8901-1459	03/09/2014	03/08/2015
Temp. / Humidity Meter	VICTOR	HTC-1	N/A	03/04/2014	03/03/2015
Test S/W	FARAD		EZ-EMC/ CCS-3A1-CE		

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST CONFIGURATION



See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

**Test Data****Operation Mode:** Mode 1 **Test Date:** March 6, 2014**Temperature:** 26°C **Humidity:** 60% RH**Tested by:** Jimmy Zheng

Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Line (L1/L2)
0.1500	47.94	30.24	9.58	57.52	39.82	65.99	56.00	-8.47	-16.18	L1
0.5340	24.96	14.15	9.70	34.66	23.85	56.00	46.00	-21.34	-22.15	L1
3.0180	33.90	20.69	9.72	43.62	30.41	56.00	46.00	-12.38	-15.59	L1
7.2300	25.42	6.63	9.79	35.21	16.42	60.00	50.00	-24.79	-33.58	L1
10.7140	28.62	12.36	9.88	38.50	22.24	60.00	50.00	-21.50	-27.76	L1
21.6420	25.93	16.95	9.85	35.78	26.80	60.00	50.00	-24.22	-23.20	L1
<hr/>										
0.1500	45.44	31.50	9.78	55.22	41.28	65.99	56.00	-10.77	-14.72	L2
0.2180	24.95	18.31	9.78	34.73	28.09	62.89	52.89	-28.16	-24.80	L2
0.2660	23.74	12.83	9.77	33.51	22.60	61.24	51.24	-27.73	-28.64	L2
0.5380	26.35	11.41	9.68	36.03	21.09	56.00	46.00	-19.97	-24.91	L2
2.9860	33.88	19.47	9.75	43.63	29.22	56.00	46.00	-12.37	-16.78	L2
6.9460	24.42	11.28	9.78	34.20	21.06	60.00	50.00	-25.80	-28.94	L2

Note:

1. Measuring frequencies from 0.15 MHz to 30MHz.
2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Peak detector, Quasi-peak detector and average detector.
3. “--” denotes the emission level was or more than 2dB below the Average limit.
4. The IF bandwidth of SPA between 0.15MHz to 30MHz was 10kHz; the IF bandwidth of Test Receiver between 0.15MHz to 30MHz was 9kHz;
5. L1= Line One (Live Line)/ L2= Line Two (Neutral Line)