

TEST REPORT

Report Number: HK11051691-2

Application
for
Original Grant
of
47 CFR Part 15: 2009 Certification

1.9GHz Digital Modulation Cordless Phone with Caller ID, Speakerphone and Bluetooth - Base Unit Bluetooth Portion

FCC ID: Y5PIRBD10US001

| Prepared and Checked by: | Approved by: |
|-----------------------------|---|
| Signed on File | |
| Koo Wai Ip Lead Engineer | Nip Ming Fung, Melvin Senior Supervisor August 15, 2011 |

The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

GENERAL INFORMATION

| Applicant Name: | Cypress Electronics Ltd. |
|----------------------------------|--|
| Applicant Address: | 11/F, Block G, East Sun Industrial Centre, |
| | 16 Shing Yip Street, Kwun Tong, |
| | Kowloon, Hong Kong. |
| FCC Specification Standard: | FCC Part 15, October 1, 2009 Edition |
| FCC ID: | Y5PIRBD10US001 |
| FCC Model(s): | 50541241, 50541247, 50541248 |
| Type of EUT: | Transceiver |
| Description of EUT: | 1.9GHz Digital Modulation Cordless |
| | Phone with Caller ID, Speakerphone and |
| | Bluetooth - Base Unit Bluetooth Portion |
| Serial Number: | N/A |
| Sample Receipt Date: | May 26, 2011 |
| Date of Test: | June 16-24, 2011 |
| Report Date: | August 15, 2011 |
| Environmental Conditions: | Temperature: +10 to 40°C |
| | Humidity: 10 to 90% |

Test Report Number: HK11051691-2 Page 1 of 25

Table of Contents

| 1.0 Test Results Summary & Statement of Compliance | 4 |
|---|----|
| 1.1 Summary of Test Results | 4 |
| 1.2 Statement of Compliance | |
| 2.0 General Description | 6 |
| 2.1 Product Description | 6 |
| 2.2 Test Methodology | 6 |
| 2.3 Test Facility | |
| 3.0 System Test Configuration | |
| 3.1 Justification | 8 |
| 3.2 EUT Exercising Software | 9 |
| 3.3 Details of EUT and Description of Accessories | 10 |
| 3.4 Measurement Uncertainty | 10 |
| 4.0 Test Results | 12 |
| 4.1 Field Strength Calculation | |
| 4.2 Radiated Emissions | 13 |
| 4.2.1 Radiated Emission Configuration Photograph | 13 |
| 4.2.2 Radiated Emission Data | |
| 4.2.3 Transmitter Duty Cycle Calculation | |
| 4.3 Radiated Emission on the Bandedge | |
| 4.4 AC Power Line Conducted Emission | |
| 4.4.1 AC Power Line Conducted Emission Configuration Photograph | |
| 4.4.2 AC Power Line Conducted Emission Data | |
| 5.0 Equipment List | 25 |

Test Report Number: HK11051691-2 Page 2 of 25 FCC ID: Y5PIRBD10US001

EXHIBIT 1 TEST RESULTS SUMMARY & STATEMENT OF COMPLIANCE

Test Report Number: HK11051691-2 Page 3 of 25

1.0 Test Results Summary & Statement of Compliance

1.1 Summary of Test Results

| Test Items | FCC Part 15 Section | Results | Details see section |
|--|------------------------------------|--------------|---------------------------|
| Antenna Requirement | 15.203 | Pass | 2.1 |
| Radiated Emission Radiated Emission on the Bandedge | 15.249(a), 209, & 109 15.249(d) | Pass Pass | 4.2 4.4 |
| Radiated Emission in Restricted Bands | 15.205 | Pass | 4.2 |
| Radiated Emission from Receiver | N/A | Pass | 4.3 |
| AC Power Line Conducted Emission | 15.207 & 15.107 | Pass | 4.5 |

Note: Pursuant to FCC Part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

1.2 Statement of Compliance

The equipment under test is found to be complying with the following standard:

FCC Part 15, October 1, 2009 Edition

Test Report Number: HK11051691-2 Page 4 of 25

EXHIBIT 2 GENERAL DESCRIPTION

Test Report Number: HK11051691-2 Page 5 of 25

2.0 **General Description**

2.1 Product Description

The 50541241 is a 1.9GHz Digital Modulation Cordless Phone with Caller ID, Speakerphone and Bluetooth - Base Unit Bluetooth Portion. It operates at frequency range of 2402MHz to 2480MHz with 79 channels. The Base Unit is powered by an adaptor 100-240VAC to 6.5VDC, 1500mA (Model: SW-065150A). With Bluetooth and 1.9GHz wireless communications enabled, the Base Unit allows user to uses a cordless handset to dial out or receive Bluetooth-equipped cellular phone calls via the cellular network. Only one cellular phone can be on a call at a time.

The Bluetooth antennas used in base unit is integral, and the test sample is a prototype.

The Model(s): 50541247 and 50541248 are the same as the Model: 50541241 in electronics/electrical designs including software & firmware, PCB layout and construction design/physical design/enclosure. The only differences between these models are model number and cosmetic details to be sold for marketing purpose.

The circuit description is attached in the Appendix and saved with filename: descri.pdf.

Connection between the device and the telephone network is accomplished through the use of USOC RJ11C in the 2-wire loop calling central office line.

2.2 Test Methodology

Both AC power line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2003). Preliminary radiated scans and all radiated measurements were performed in Open Area Test Sites. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application.

2.3 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data and conducted data are at Roof Top and 2nd Floor respectively of Intertek Testing Services Hong Kong Ltd., which is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC.

Test Report Number: HK11051691-2 Page 6 of 25

EXHIBIT 3 SYSTEM TEST CONFIGURATION

Test Report Number: HK11051691-2 Page 7 of 25

3.0 **System Test Configuration**

3.1 Justification

For radiated emissions testing, the equipment under test (EUT) was setup to transmit continuously / receive continuously / normal mode to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables (if any) were manipulated to produce worst case emissions.

The Base Unit was powered by an adaptor 100-240VAC to 6.5VDC, 1500mA (Model: SW-065150A).

For the measurements, the EUT was attached to a plastic stand if necessary and placed on the wooden turntable. If the base unit attached to peripherals, they were connected and operational to simulate typical use. The handset was remotely located as far from the antenna and the base as possible to ensure full power transmission from the base. Else, the base was wired to transmit full power.

The signal was maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization were varied during the search for maximum signal level. The antenna height was varied from 1 to 4 meters. Radiated emissions were taken at three meters unless the signal level was too low for measurement at that distance. If necessary, a pre-amplifier was used and/or the test was conducted at a closer distance.

For any intentional radiator powered by AC power line, measurements of the radiated signal level of the fundamental frequency component of the emission was performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.

For transmitter radiated measurement, the spectrum analyzer resolution bandwidth was 100 kHz for frequencies below 1000 MHz. The resolution bandwidth was 1 MHz for frequencies above 1000 MHz.

For receiver radiated measurement, the spectrum analyzer resolution bandwidth was 1MHz for measurement above 1GHz while 100kHz for measurement from 30MHz to 1GHz.

Radiated emission measurement for transmitter was performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower. Receiver was performed from 30MHz the fifth harmonic of the highest frequency or 40GHz, whichever is lower.

Emission that are directly caused by digital circuits in the transmit path and transmitter portion were measured, and the limit are according to FCC Part 15 Section 15.109.

Test Report Number: HK11051691-2 Page 8 of 25

3.1 Justification - Cont'd

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in section 4.2.3.

Determination of pulse desensitization was made according to *Hewlett Packard Application Note 150-2, Spectrum Analysis... Pulsed RF.* The effective period (Teff) was 625µs. With the resolution bandwidth 1MHz and spectrum analyzer IF bandwidth 3dB, the pulse desensitization factor was 0dB.

For AC line conducted emission test, the EUT along with its peripherals were placed on a 1.0m(W)x1.5m(L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN), which provided 50ohm coupling impedance for measuring instrument. The LISN housing, measuring instrument case, reference ground plane, and vertical ground plane were bounded together. The excess power cable between the EUT and the LISN was bundled.

All connecting cables of EUT and peripherals were manipulated to find the maximum emission.

All relevant operation modes have been tested, and the worst case data is included in this report.

Bluetooth portion and DECT portion of Base unit were in active during radiated emission testing and conducted emission testing. The simultaneous transmission of both Bluetooth and DECT portions on Base Unit was checked. No new emission was observed during the simultaneous transmission.

3.2 EUT Exercising Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use.

Test Report Number: HK11051691-2 Page 9 of 25

3.3 Details of EUT and Description of Accessories

Details of EUT:

An AC adaptor (provided with the unit) was used to power the device. Their description are listed below.

(1) Base Unit: An AC adaptor (100-240VAC to 6.5VDC, 1500mA, Model: SW-065150A) (Supplied by Client)

Description of Peripherals:

- (1) Telecommunication cable with RJ11C connectors (1m, unshielded), terminated (Supplied by Intertek)
- (2) Telephone Line Simulator, Model: TLS-5D-01, S/N: 151101 (Supplied by Intertek)
- (3) Cordless Handset, Model: 50541241, FCC ID: Y5PIRBD10US001 (Supplied by Client)
- (4) iPod nano, Model: A1320, Serial No.: YM9374AG72F, DoC Product (Supplied by Client)
- (5) Nokia Cell Phone, Model: 5300, FCC ID: PPIRM-146 (Supplied by Intertek)
- (6) 3m Telephone Line (Supplied by Intertek)

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Test Report Number: HK11051691-2 Page 10 of 25

EXHIBIT 4 TEST RESULTS

Test Report Number: HK11051691-2 Page 11 of 25

4.0 Test Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

4.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

FS = RA + AF + CF - AG + PD + AV

where FS = Field Strength in $dB_{\mu}V/m$

RA = Receiver Amplitude (including preamplifier) in $dB\mu V$

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflects the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

FS = RA + AF + CF - AG + PD +AV

Example

Assume a receiver reading of 62.0 dB $_{\mu}V$ is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB $_{\mu}V/m$. This value in dB $_{\mu}V/m$ was converted to its corresponding level in $_{\mu}V/m$.

RA = 62.0 dBuV

AF = 7.4 dB

CF = 1.6 dB

AG = 29 dB

PD = 0 dB

AV = -10 dB

 $FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 dB\mu V/m$

Level in μ V/m = Common Antilogarithm [(32 dB μ V/m)/20] = 39.8 μ V/m

4.2 Radiated Emissions

4.2.1 Radiated Emission Configuration Photograph

Worst Case Radiated Emission at

Base Unit: 63.542 MHz

The worst case radiated emission configuration photographs are attached in the Appendix and saved with filename: config photos.pdf

4.2.2 Radiated Emission Data

The data in tables 1-4 list the significant emission frequencies, the limit and the margin of compliance.

Judgement -

Base Unit: Passed by 5.4 dB margin

Test Report Number: HK11051691-2 Page 13 of 25

4.2.3 Transmitter Duty Cycle Calculation

Based on the Bluetooth Specification Version 2.0 / 2.1 + EDR, the transmitter ON time for each timeslot of Bluetooth is $625\mu s$. DH5 has the maximum duty cycle, which consists of 5 continuous Tx slots and 1 Rx slot. Therefore one hopset take (5+1) x $625\mu s = 3.75ms$. For one period for a pseudo-random hopping through all 79 RF channels, it take: $79 \times 3.75ms = 296.25ms$.

The dwell time for DH5 is $5 \times 625 \mu s = 3.125 ms$.

Therefore,

Duty Cycle (DC) = Maximum On time in 100ms/100ms = 3.125ms/100ms = 0.03125

Average Factor (AF) of Bluetooth in dB = $20 \log_{10} (0.03125)$ = -30.1dB

Test Report Number: HK11051691-2 Page 14 of 25

Mode: TX-Channel 00

Table 1, Base Unit

Radiated Emission Data

| | | | Pre-Amp | Antenna | Average | Calculated | Average | |
|---------|-----------|---------|---------|---------|---------|------------|-------------|--------|
| Dolori | Frogueno. | Dooding | | | • | | | Morgin |
| Polari- | Frequency | Reading | Gain | Factor | Factor | at 3m | Limit at 3m | Margin |
| zation | (MHz) | (dBµV) | (dB) | (dB) | (dB) | (dBµV/m) | (dBµV/m) | (dB) |
| V | 2402.000 | 95.0 | 33 | 29.4 | 30.1 | 61.3 | 94.0 | -32.7 |
| V | 4804.000 | 60.5 | 33 | 34.9 | 30.1 | 32.3 | 54.0 | -21.7 |
| Н | 7206.000 | 49.7 | 33 | 37.9 | 30.1 | 24.5 | 54.0 | -29.5 |
| Н | 9608.000 | 45.0 | 33 | 40.4 | 30.1 | 22.3 | 54.0 | -31.7 |
| Н | 12010.000 | 43.4 | 33 | 40.5 | 30.1 | 20.8 | 54.0 | -33.2 |
| Н | 14412.000 | 43.2 | 33 | 40.0 | 30.1 | 20.1 | 54.0 | -33.9 |

| Polari- zation | Frequency (MHz) | Reading (dBµV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Peak (dBµV/m) | Peak Limit at 3m (dBµV/m) | Margin (dB) |
|-------------------|--------------------|-------------------|-------------------------|---------------------------|---------------------------------|---------------------------------|----------------|
| V | 2402.000 | 95.0 | 33 | 29.4 | 91.4 | 114.0 | -22.6 |
| V | 4804.000 | 60.5 | 33 | 34.9 | 62.4 | 74.0 | -11.6 |
| Н | 7206.000 | 49.7 | 33 | 37.9 | 54.6 | 74.0 | -19.4 |
| Н | 9608.000 | 45.0 | 33 | 40.4 | 52.4 | 74.0 | -21.6 |
| Н | 12010.000 | 43.4 | 33 | 40.5 | 50.9 | 74.0 | -23.1 |
| Н | 14412.000 | 43.2 | 33 | 40.0 | 50.2 | 74.0 | -23.8 |

NOTES: 1. Peak detector is used for the emission measurement.

- 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.

Test Report Number: HK11051691-2 Page 15 of 25

Mode: TX-Channel 39

Table 2, Base Unit

Radiated Emission Data

| | | | Pre-Amp | Antenna | Average | Calculated | Average | |
|---------|-----------|---------|---------|---------|---------|------------|-------------|--------|
| Polari- | Frequency | Reading | Gain | Factor | Factor | at 3m | Limit at 3m | Margin |
| zation | (MHz) | (dBµV) | (dB) | (dB) | (dB) | (dBµV/m) | (dBµV/m) | (dB) |
| V | 2441.000 | 95.2 | 33 | 29.4 | 30.1 | 61.5 | 94.0 | -32.5 |
| V | 4882.000 | 60.4 | 33 | 34.9 | 30.1 | 32.2 | 54.0 | -21.8 |
| Н | 7323.000 | 49.9 | 33 | 37.9 | 30.1 | 24.7 | 54.0 | -29.3 |
| Н | 9764.000 | 45.2 | 33 | 40.4 | 30.1 | 22.5 | 54.0 | -31.5 |
| Н | 12205.000 | 43.3 | 33 | 40.5 | 30.1 | 20.7 | 54.0 | -33.3 |
| Н | 14646.000 | 44.8 | 33 | 38.4 | 30.1 | 20.1 | 54.0 | -33.9 |

| Polari- | Frequency | Reading | Pre-Amp Gain | Antenna Factor | Net at 3m - Peak | Peak Limit at 3m | Margin |
|---------|-----------|---------|-----------------|-------------------|---------------------|---------------------|--------|
| zation | (MHz) | (dBµV) | (dB) | (dB) | (dBµV/m) | (dBµV/m) | (dB) |
| V | 2441.000 | 95.2 | 33 | 29.4 | 91.6 | 114.0 | -22.4 |
| V | 4882.000 | 60.4 | 33 | 34.9 | 62.3 | 74.0 | -11.7 |
| Н | 7323.000 | 49.9 | 33 | 37.9 | 54.8 | 74.0 | -19.2 |
| Н | 9764.000 | 45.2 | 33 | 40.4 | 52.6 | 74.0 | -21.4 |
| Н | 12205.000 | 43.3 | 33 | 40.5 | 50.8 | 74.0 | -23.2 |
| Н | 14646.000 | 44.8 | 33 | 38.4 | 50.2 | 74.0 | -23.8 |

NOTES: 1. Peak detector is used for the emission measurement.

- 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.

Test Report Number: HK11051691-2 Page 16 of 25

Mode: TX-Channel 78

Table 3, Base Unit

Radiated Emission Data

| | | | Pre-Amp | Antenna | Average | Calculated | Average | |
|---------|-----------|---------|---------|---------|---------|------------|-------------|--------|
| Polari- | Frequency | Reading | Gain | Factor | Factor | at 3m | Limit at 3m | Margin |
| zation | (MHz) | (dBµV) | (dB) | (dB) | (dB) | (dBµV/m) | (dBµV/m) | (dB) |
| V | 2480.000 | 96.1 | 33 | 29.4 | 30.1 | 62.4 | 94.0 | -31.6 |
| V | 4960.000 | 60.5 | 33 | 34.9 | 30.1 | 32.3 | 54.0 | -21.7 |
| Н | 7440.000 | 49.7 | 33 | 37.9 | 30.1 | 24.5 | 54.0 | -29.5 |
| Н | 9920.000 | 44.9 | 33 | 40.4 | 30.1 | 22.2 | 54.0 | -31.8 |
| Н | 12400.000 | 43.4 | 33 | 40.5 | 30.1 | 20.8 | 54.0 | -33.2 |
| Н | 14880.000 | 44.7 | 33 | 38.4 | 30.1 | 20.0 | 54.0 | -34.0 |

| | | | Pre-Amp | Antenna | Netat | Peak Limit | |
|---------|-----------|---------|---------|---------|-----------|---------------|--------|
| Polari- | Frequency | Reading | Gain | Factor | 3m - Peak | at 3 m | Margin |
| zation | (MHz) | (dBµV) | (dB) | (dB) | (dBµV/m) | $(dB\mu V/m)$ | (dB) |
| V | 2480.000 | 96.1 | 33 | 29.4 | 92.5 | 114.0 | -21.5 |
| V | 4960.000 | 60.5 | 33 | 34.9 | 62.4 | 74.0 | -11.6 |
| Н | 7440.000 | 49.7 | 33 | 37.9 | 54.6 | 74.0 | -19.4 |
| Н | 9920.000 | 44.9 | 33 | 40.4 | 52.3 | 74.0 | -21.7 |
| Н | 12400.000 | 43.4 | 33 | 40.5 | 50.9 | 74.0 | -23.1 |
| Н | 14880.000 | 44.7 | 33 | 38.4 | 50.1 | 74.0 | -23.9 |

NOTES: 1. Peak detector is used for the emission measurement.

- 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.

Test Report Number: HK11051691-2 Page 17 of 25

Mode: Talk

Table 4, Base unit

Radiated Emission Data

| | | | Pre- | Antenna | Net | Limit | |
|--------------|-----------|---------|------|---------|----------|----------|--------|
| | Frequency | Reading | amp | Factor | at 3m | at 3m | Margin |
| Polarization | (MHz) | (dBµV) | (dB) | (dB) | (dBµV/m) | (dBµV/m) | (dB) |
| V | 38.476 | 39.8 | 16 | 10.0 | 33.8 | 40.0 | -6.2 |
| V | 54.575 | 39.5 | 16 | 11.0 | 34.5 | 40.0 | -5.5 |
| Н | 63.542 | 41.6 | 16 | 9.0 | 34.6 | 40.0 | -5.4 |
| Н | 108.371 | 35.8 | 16 | 14.0 | 33.8 | 43.5 | -9.7 |
| Н | 132.428 | 34.8 | 16 | 14.0 | 32.8 | 43.5 | -10.7 |
| Н | 169.374 | 30.2 | 16 | 18.0 | 32.2 | 43.5 | -11.3 |

NOTES: 1. Peak detector is used for the emission measurement.

- 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.

Test Report Number: HK11051691-2 Page 18 of 25

4.3 Radiated Emission on the Bandedge

From the following plots, they show that the fundamental emissions are confined in the specified band (902MHz and 928MHz) / (2400MHz and 2483.5MHz) / (5725MHz and 5875MHz). In case of emissions up to two standard bandwidths away from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.4 (2003) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in FCC Part 15 Section 15.209, whichever is the lesser attenuation, which meet the requirement of FCC Part 15 Section 15.249(d).

Radiated Emission on bandedge plots are attached in the Appendix and saved with filename: be.pdf

Bandedge compliance is determined by applying marker-delta method, i.e.

Resultant Field Strength = Fundamental Emissions - Delta from the plot

Resultant field strength for the lowest and/or highest channel(s), with corresponding average values are calculated as follows:

| | | | | Resultant | | |
|------|---------|-------------|------------|-----------|----------|--------|
| | | Fundamental | Delta from | Field | Average | |
| | | Emission | the Plot | Strength | Limit | Margin |
| | Channel | (dBµV/m) | (dB) | (dBµV/m) | (dBµV/m) | (dB) |
| | Lowest | 61.3 | 43.49 | 17.81 | 54 | -36.19 |
| Base | Highest | 62.4 | 45.71 | 16.69 | 54 | -37.31 |

| | | | | Resultant | | |
|------|---------|-------------|------------|-----------|------------|--------|
| | | Fundamental | Delta from | Field | | |
| | | Emission | the Plot | Strength | Peak Limit | Margin |
| | Channel | (dBµV/m) | (dB) | (dBµV/m) | (dBµV/m) | (dB) |
| | Lowest | 91.4 | 43.49 | 47.91 | 74 | -26.09 |
| Base | Highest | 92.5 | 45.71 | 46.79 | 74 | -27.21 |

The resultant field strength meets the general radiated emission limit in FCC Part 15 Section 15.209, which does not exceed $74dB\mu V/m$ for peak limit and also $54dB\mu V/m$ for average limit.

Test Report Number: HK11051691-2 Page 19 of 25

4.4 AC Power Line Conducted Emission

- Not applicable EUT is only powered by battery for operation.
- [x] EUT connects to AC power line. Emission Data is listed in following pages.
- [] Base Unit connects to AC power line and has transmission. Handset connects to AC power line but has no transmission. Emission Data of Base Unit is listed in following pages.

4.4.1 AC Power Line Conducted Emission Configuration Photograph

Worst Case Line-Conducted Configuration at

0.312 MHz

The worst case line conducted configuration photographs are attached in the Appendix and saved with filename: config photos.pdf


4.4.2 AC Power Line Conducted Emission Data

The plot(s) and data in the following pages list the significant emission frequencies, the limit and the margin of compliance

Passed by 4.7 dB margin compare with average limit

Test Report Number: HK11051691-2 Page 20 of 25

Worst Case: Talk and Charging (IPod)



Date: 16.JUN.2011 19:25:14

Test Report Number: HK11051691-2 Page 21 of 25

Worst Case: Talk and Charging (IPod)

| | TD.T. | - DENI T.C. (D.: | . 7. 24 | | D 11) |
|-----|--------------|-------------------|-------------|-----|----------------|
| | | T PEAK LIST (Fina | al Measurem | ent | Results) |
| | cel: | CF15MQP | | | |
| Tra | ce2: | CF15MAV | | | |
| Tra | ce3: | | | | |
| | TRACE | FREQUENCY | LEVEL de | βμV | DELTA LIMIT dB |
| 1 | Quasi Peak | 172.5 kHz | 40.21 | L1 | -24.62 |
| 2 | CISPR Averag | €289.5 kHz | 40.51 | L1 | -10.02 |
| 1 | Quasi Peak | 289.5 kHz | 48.13 | L1 | -12.40 |
| 2 | CISPR Averag | e312 kHz | 45.20 | L1 | -4.70 |
| 1 | Quasi Peak | 312 kHz | 52.65 | L1 | -7.26 |
| 1 | Quasi Peak | 501 kHz | 41.30 | L1 | -14.69 |
| 2 | CISPR Averag | r∈564 kHz | 33.99 | L1 | -12.00 |
| 1 | Quasi Peak | 568.5 kHz | 40.71 | L1 | -15.29 |
| 2 | CISPR Averag | r∈685.5 kHz | 34.76 | L1 | -11.23 |
| 1 | Quasi Peak | 847.5 kHz | 40.86 | L1 | -15.13 |
| 2 | CISPR Averag | e1.059 MHz | 34.47 | L1 | -11.52 |
| 2 | CISPR Averag | e1.1265 MHz | 34.61 | L1 | -11.38 |
| 1 | Quasi Peak | 1.149 MHz | 40.52 | L1 | -15.47 |
| 1 | Quasi Peak | 1.851 MHz | 39.77 | L1 | -16.22 |
| 2 | CISPR Averag | r∈2.031 MHz | 34.06 | L1 | -11.93 |
| 2 | CISPR Averag | €2.3775 MHz | 33.44 | L1 | -12.55 |
| 1 | Quasi Peak | 2.436 MHz | 40.47 | L1 | -15.52 |
| 2 | CISPR Averag | e3.066 MHz | 32.35 | L1 | -13.64 |
| 1 | Quasi Peak | 3.309 MHz | 38.99 | L1 | -17.00 |
| 2 | CISPR Averag | r∈4.767 MHz | 31.83 | L1 | -14.16 |

Date: 16.JUN.2011 19:24:56

Test Report Number: HK11051691-2 Page 22 of 25

Worst Case: Talk and Charging (IPod)

| | EDIT PEAK LIST (Fi | inal Measurement | Results) |
|------------|--------------------|------------------|----------------|
| Trace1: | CF15MQP | | |
| Trace2: | CF15MAV | | |
| Trace3: | | | |
| TRACE | FREQUENCY | LEVEL dBµV | DELTA LIMIT dB |
| 1 Quasi Pe | eak 4.8345 MHz | 38.67 L1 | -17.32 |
| 2 CISPR Av | rerage6.927 MHz | 39.66 L1 | -10.33 |
| 1 Quasi Pe | ak 7.0395 MHz | 46.50 L1 | -13.49 |

Date: 16.JUN.2011 19:25:06

Test Report Number: HK11051691-2 Page 23 of 25 FCC ID: Y5PIRBD10US001

EXHIBIT 5 EQUIPMENT LIST

Test Report Number: HK11051691-2 Page 24 of 25

5.0 **Equipment List**

1) Radiated Emissions Test

| Equipment | Biconical Antenna | Spectrum Analyzer | EMI Test Receiver |
|----------------------|-------------------|-------------------|-------------------|
| Registration No. | EW-0954 | EW-2188 | EW-2500 |
| Manufacturer | EMCO | AGILENTTECH | R&S |
| Model No. | 3104C | E4407B | ESCI |
| Calibration Date | Apr. 14, 2010 | Dec. 27, 2010 | Jan. 25, 2011 |
| Calibration Due Date | Oct. 14, 2011 | Dec. 31, 2011 | Jan. 25, 2012 |

| Equipment | Broad-Band Horn | Double Ridged | Log Periodic |
|----------------------|-----------------|---------------|---------------|
| | Antenna | Guide Antenna | Antenna |
| Registration No. | EW-1679 | EW-1015 | EW-0446 |
| Manufacturer | SCHWARZBECK | EMCO | EMCO |
| Model No. | BBHA9170 | 3115 | 3146 |
| Calibration Date | Mar. 03, 2011 | Feb. 09, 2010 | Apr. 26, 2010 |
| Calibration Due Date | Sep. 03, 2012 | Aug. 09, 2011 | Oct. 26, 2011 |

2) Conducted Emissions Test

| Equipment | Artificial Mains | EMI Test Receiver | Pulse Limiter |
|----------------------|------------------|-------------------|---------------|
| | Network | | |
| Registration No. | EW-2501 | EW-2666 | EW-0699 |
| Manufacturer | R&S | R&S | R&S |
| Model No. | ENV-216 | ESCI7 | ESH3-Z2 |
| Calibration Date | Mar. 30, 2011 | Oct. 12, 2010 | Dec. 24, 2009 |
| Calibration Due Date | Mar. 30, 2012 | Oct. 12, 2011 | Jun. 24, 2011 |

END OF TEST REPORT

Test Report Number: HK11051691-2 Page 25 of 25