

FCC ID : Y5VMW0922

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB 447498 (2)(a)(i)

Frequency Range		Center frequency (MHz)	60/f SAR Limitation (mw)
Low Frequency (MHz)	High Frequency(MHz)		
2412	2462	2437	25

Maximum measured transmitter power for **802.11b Mode**

Conducted Power (dBm)	Max Antenna Gain (dBi)	EIRP (mw)
11.96	0	15.70
11.14	0	13.00
12.10	0	14.06

Maximum measured transmitter power **802.11g Mode**

Conducted Power (dBm)	Max Antenna Gain (dBi)	EIRP (mw)
12.24	0	16.75
11.43	0	13.90
12.10	0	16.22

Maximum measured transmitter power **802.11n Mode**

Conducted Power (dBm)	Max Antenna Gain (dBi)	EIRP (mw)
12.23	0	16.71
11.44	0	13.93
12.11	0	16.26

Threshold at which no SAR required is 25 mw.

Maximum Tx power is **16.75mW** EIRP.

Conclusion: No SAR is required.

SIMULTANEOUS TRANSMISSION EVALUATION

N/A