

STS

LAB



## RADIO TEST REPORT

Report No:STS1807043W01

Issued for

Canon Electronic Business Machines (H.K.) Co., Ltd.

17/F, Tower One, Ever Gain Plaza, 82-100 Container Port  
Road, Kwai Chung, New Territories, Hong Kong

|                       |                                    |
|-----------------------|------------------------------------|
| <b>Product Name:</b>  | Wireless Receiver                  |
| <b>Brand Name:</b>    | Canon                              |
| <b>Model Name:</b>    | D20D                               |
| <b>Series Model:</b>  | N/A                                |
| <b>FCC ID:</b>        | Y7J-D20D                           |
| <b>IC:</b>            | 9472A-D20D                         |
| <b>Test Standard:</b> | FCC Part 15.249<br>RSS 210 Issue 9 |

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS. All Test Data Presented in this report is only applicable to presented Test sample.

Shenzhen STS Test Services Co., Ltd.  
1/F., Building B, Zhuoke Science Park, No.190, Chongqing Road,  
Fuyong Street, Bao'an District, Shenzhen, Guangdong, China  
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com





## TEST RESULT CERTIFICATION

Applicant's name .....: Canon Electronic Business Machines (H.K.) Co., Ltd.  
Address .....: 17/F, Tower One, Ever Gain Plaza, 82-100 Container Port Road,  
Kwai Chung, New Territories, Hong Kong  
Manufacture's Name .....: Canon Electronic Business Machines (H.K.) Co., Ltd.  
Address .....: 17/F, Tower One, Ever Gain Plaza, 82-100 Container Port Road,  
Kwai Chung, New Territories, Hong Kong

### Product description

Product Name .....: Wireless Receiver  
Brand Name .....: Canon  
Model Name .....: D20D  
Series Model .....: N/A

**Test Standards** .....: FCC Part15.249  
RSS 210 Issue 9

Test procedure .....: ANSI C63.10-2013

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC&IC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test .....:

Date of performance of tests ...: 29 Nov. 2018 ~24 Dec. 2018

Date of Issue .....: 25 Dec. 2018

Test Result .....: **Pass**

Testing Engineer : 

( Chris Chen )

Technical Manager : 

( Sunday Hu )

Authorized Signatory : 

(Vita Li)





| Table of Contents   | Page      |
|---|-----------|
| <b>1. SUMMARY OF TEST RESULTS</b>                           | <b>5</b>  |
| 1.1 TEST FACTORY  | 6         |
| 1.2 MEASUREMENT UNCERTAINTY                                 | 6         |
| <b>2. GENERAL INFORMATION</b>                               | <b>7</b>  |
| 2.1 GENERAL DESCRIPTION OF THE EUT                          | 7         |
| 2.2 DESCRIPTION OF TEST MODES                               | 9         |
| 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED | 10        |
| 2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS  | 11        |
| 2.5 EQUIPMENTS LISTS  | 12        |
| <b>3. EMC EMISSION TEST</b>                                 | <b>13</b> |
| 3.1 CONDUCTED EMISSION MEASUREMENT                          | 13        |
| 3.2 RADIATED EMISSION MEASUREMENT                           | 17        |
| <b>4. BANDWIDTH TEST</b>                                    | <b>30</b> |
| 4.2 TEST SETUP  | 30        |
| 4.3 EUT OPERATION CONDITIONS                                | 30        |
| 4.4 TEST RESULTS  | 31        |
| <b>5. ANTENNA REQUIREMENT</b>                               | <b>33</b> |
| 5.1 STANDARD REQUIREMENT                                    | 33        |
| 5.2 EUT ANTENNA   | 33        |
| <b>6. FREQUENCY STABILITY</b>                               | <b>34</b> |
| 6.1 LIMITS  | 34        |
| 6.2 TEST PROCEDURE  | 34        |
| 6.3 TEST RESULT   | 34        |
| <b>APPENDIX- PHOTOS OF TEST SETUP</b>                       | <b>35</b> |

**Revision History**

| Rev. | Issue Date   | Report NO.    | Effect Page | Contents      |
|------|--------------|---------------|-------------|---------------|
| 00   | 25 Dec. 2018 | STS1807043W01 | ALL         | Initial Issue |
|      |              |               |             |               |





## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

| <b>FCC Part 15.249 , Subpart C<br/>RSS 210 Issue 9</b> |                             |          |        |
|--|-----------------------------|----------|--------|
| Standard Section                                       | Test Item                   | Judgment | Remark |
| 15.207<br>RSS-Gen Issue 5 April 2018                   | Conducted Emission          | Pass     | --     |
| 15.203<br>RSS-Gen Issue 5 April 2018                   | Antenna Requirement         | Pass     | --     |
| 15.249<br>RSS 210 Issue 9 (B.10)                       | Radiated Spurious Emission  | Pass     | --     |
| 15.205   | Radiated Band Edge Emission | Pass     | --     |
| 15.249<br>RSS-Gen Issue 5 April 2018                   | Occupied Bandwidth          | Pass     | --     |
| RSS-Gen Issue 5 April 2018                             | Frequency Stability         | PASS     | --     |

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

(2)All tests are according to ANSI C63.10-2013



## 1.1 TEST FACTORY

Shenzhen STS Test Services Co., Ltd.

Add. : 1/F., Building B, Zhuoke Science Park, No.190, Chongqing Road,  
Fuyong Street, Bao'an District, Shenzhen, Guangdong, China

FCC Registration No.: 625569

IC Registration No.: 12108A; A2LA Certificate No.: 4338.01;

## 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$  · where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$  · providing a level of confidence of approximately **95 %** .

| No. | Item                               | Uncertainty         |
|-----|------------------------------------|---------------------|
| 1   | RF output power,conducted          | $\pm 0.71\text{dB}$ |
| 2   | Unwanted Emissions,conducted       | $\pm 0.63\text{dB}$ |
| 3   | All emissions,radiated 30-200MHz   | $\pm 3.43\text{dB}$ |
| 4   | All emissions,radiated 200MHz-1GHz | $\pm 3.57\text{dB}$ |
| 5   | All emissions,radiated>1G          | $\pm 4.13\text{dB}$ |
| 6   | Conducted Emission(9KHz-150KHz)    | $\pm 3.18\text{dB}$ |
| 7   | Conducted Emission(150KHz-30MHz)   | $\pm 2.70\text{dB}$ |



## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF THE EUT

|                         |   |                      |               |                  |      |                      |             |                     |          |
|-------------------------|---|----------------------|---------------|------------------|------|----------------------|-------------|---------------------|----------|
| Product Name            | Wireless Receiver   |                      |               |                  |      |                      |             |                     |          |
| Trade Name              | Canon   |                      |               |                  |      |                      |             |                     |          |
| Model Name              | D20D  |                      |               |                  |      |                      |             |                     |          |
| Series Model            | N/A   |                      |               |                  |      |                      |             |                     |          |
| Model Difference        | N/A   |                      |               |                  |      |                      |             |                     |          |
| Product Description     | <p>The EUT is a Wireless Receiver</p> <table border="1"><tr><td>Operation Frequency:</td><td>2405~2460 MHz</td></tr><tr><td>Modulation Type:</td><td>GFSK</td></tr><tr><td>Antenna Designation:</td><td>PCB Antenna</td></tr><tr><td>Antenna Gain(Peak):</td><td>-2.5 dBi</td></tr></table> <p>Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.</p> | Operation Frequency: | 2405~2460 MHz | Modulation Type: | GFSK | Antenna Designation: | PCB Antenna | Antenna Gain(Peak): | -2.5 dBi |
| Operation Frequency:    | 2405~2460 MHz   |                      |               |                  |      |                      |             |                     |          |
| Modulation Type:        | GFSK  |                      |               |                  |      |                      |             |                     |          |
| Antenna Designation:    | PCB Antenna   |                      |               |                  |      |                      |             |                     |          |
| Antenna Gain(Peak):     | -2.5 dBi  |                      |               |                  |      |                      |             |                     |          |
| Channel List            | Please refer to the Note 2.   |                      |               |                  |      |                      |             |                     |          |
| Power Rating            | DC 5V   |                      |               |                  |      |                      |             |                     |          |
| Hardware version number | R000  |                      |               |                  |      |                      |             |                     |          |
| Software version number | V02   |                      |               |                  |      |                      |             |                     |          |

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.

| Channel List |                 |         |                 |
|--------------|-----------------|---------|-----------------|
| Channel      | Frequency (MHz) | Channel | Frequency (MHz) |
| 01           | 2405            | 06      | 2430            |
| 02           | 2410            | 07      | 2435            |
| 03           | 2415            | 08      | 2440            |
| 04           | 2450            | 09      | 2445            |
| 05           | 2425            | 10      | 2460            |

3. Table for Filed Antenna

| Ant | Brand | Model Name | Antenna Type | Connector | Gain (dBi) | NOTE    |
|-----|-------|------------|--------------|-----------|------------|---------|
| 1   | Canon | D20D       | PCB Antenna  | N/A       | -2.5       | Antenna |



## 2.2 DESCRIPTION OF TEST MODES

For conducted test items and radiated spurious emissions

Each of these EUT operation mode(s) or test configuration mode(s) mentioned below was evaluated respectively..

| Pretest Mode | Description | Data/Modulation |
|--------------|-------------|-----------------|
| Mode 1       | TX CH01     | GFSK            |
| Mode 2       | TX CH06     | GFSK            |
| Mode 3       | TX CH10     | GFSK            |

Note:

- (1) All above mode have been measurement, only worst data was reported.
- (2) We have been tested for all available U.S. voltage and frequencies(For 120V,50/60Hz and 240V, 50/60Hz) for which the device is capable of operation, and the worst case of 120V,50/60Hz is shown in the report
- (3) We tested two power states of when the EUT working is by USB charging and a separate lithium battery to powers. the EUT working by USB charging power is higher, so all the test data is tested by USB charging mode.
- (4) Controlled using a bespoke application on the laptop PC supplied by the customer. The application was used to enable a continuous transmission mode and to select the test channels, data rates and modulation schemes as required.


For AC Conducted Emission

| Test Case             |                     |
|-----------------------|---------------------|
| AC Conducted Emission | Mode 4 : Keeping TX |


### 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters

#### Radiated Spurious Emission Test



#### Conduction Test Set





#### 2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

##### Necessary accessories

| Item | Equipment | Mfr/Brand | Model/Type No. | Serial No. | Note |
|------|-----------|-----------|----------------|------------|------|
| N/A  | N/A       | N/A       | N/A            | N/A        | N/A  |
|      |           |           |                |            |      |
|      |           |           |                |            |      |
|      |           |           |                |            |      |
|      |           |           |                |            |      |

##### Support units

| Item | Equipment        | Mfr/Brand | Model/Type No. | Serial No. | Note |
|------|------------------|-----------|----------------|------------|------|
| E-2  | Notebook         | HP        | 500-320cx      | N/A        | N/A  |
| E-3  | Notebook Adapter | HP        | HSTNN-CA15     | N/A        | N/A  |
| C-1  | DC Cable         | NO        | 100cm          | N/A        | N/A  |
|      |                  |           |                |            |      |

##### Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in «Length» column.



## 2.5 EQUIPMENTS LISTS

### Radiation Test equipment

| Kind of Equipment                | Manufacturer | Type No.            | Serial No.   | Last calibration | Calibrated until |
|----------------------------------|--------------|---------------------|--------------|------------------|------------------|
| Test Receiver                    | R&S          | ESCI                | 101427       | 2018.10.13       | 2019.10.12       |
| Signal Analyzer                  | Agilent      | N9020A              | MY51110105   | 2018.03.08       | 2019.03.07       |
| Active loop Antenna              | ZHINAN       | ZN30900C            | 16035        | 2017.03.11       | 2020.03.10       |
| Bilog Antenna                    | TESEQ        | CBL6111D            | 34678        | 2017.11.02       | 2020.11.01       |
| Horn Antenna                     | Schwarzbeck  | BBHA<br>9120D(1201) | 9120D-1343   | 2017.10.27       | 2020.10.26       |
| SHF-EHF Horn Antenna (15G-40GHz) | A-INFO       | LB-180400-KF        | J211020657   | 2018.03.11       | 2019.03.10       |
| Pre-mplifier (0.1M-3GHz)         | EM           | EM330               | 060665       | 2018.03.09       | 2019.03.08       |
| PreAmplifier (1G-18GHz)          | SKET         | LNPA-01018G-4<br>5  | SK2018080901 | 2018.10.13       | 2019.10.12       |
| Temperature & Humidity           | HH660        | Mieo                | N/A          | 2018.10.11       | 2019.10.10       |
| turn table                       | EM           | SC100_1             | 60531        | N/A              | N/A              |
| Antenna mast                     | EM           | SC100               | N/A          | N/A              | N/A              |

### Conduction Test equipment

| Kind of Equipment      | Manufacturer | Type No. | Serial No. | Last calibration | Calibrated until |
|------------------------|--------------|----------|------------|------------------|------------------|
| Test Receiver          | R&S          | ESCI     | 101427     | 2018.10.13       | 2019.10.12       |
| LISN                   | R&S          | ENV216   | 101242     | 2018.10.13       | 2019.10.12       |
| LISN                   | EMCO         | 3810/2NM | 23625      | 2018.10.13       | 2019.10.12       |
| Temperature & Humidity | HH660        | Mieo     | N/A        | 2018.10.11       | 2019.10.10       |

### RF Connected Test

| Kind of Equipment      | Manufacturer | Type No. | Serial No.    | Last calibration | Calibrated until |
|------------------------|--------------|----------|---------------|------------------|------------------|
| USB RF power sensor    | DARE         | RPR3006W | 15I00041SNO03 | 2018.10.13       | 2019.10.12       |
| Signal Analyzer        | Agilent      | N9020A   | MY49100060    | 2018.10.13       | 2019.10.12       |
| Temperature & Humidity | HH660        | Mieo     | N/A           | 2018.10.11       | 2019.10.10       |



### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

Operating frequency band. In case the emission fall within the restricted band specified on Part 15.249& RSS-Gen Issue 5 limit in the table below has to be followed.

| FREQUENCY (MHz) | Class B (dBuV) |           | Standard |
|-----------------|----------------|-----------|----------|
|                 | Quasi-peak     | Average   |          |
| 0.15 -0.5       | 66 - 56 *      | 56 - 46 * | CISPR    |
| 0.50 -5.0       | 56.00          | 46.00     | CISPR    |
| 5.0 -30.0       | 60.00          | 50.00     | CISPR    |

|           |           |           |     |
|-----------|-----------|-----------|-----|
| 0.15 -0.5 | 66 - 56 * | 56 - 46 * | FCC |
| 0.50 -5.0 | 56.00     | 46.00     | FCC |
| 5.0 -30.0 | 60.00     | 50.00     | FCC |

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

| Receiver Parameters | Setting  |
|---------------------|----------|
| Attenuation         | 10 dB    |
| Start Frequency     | 0.15 MHz |
| Stop Frequency      | 30 MHz   |
| IF Bandwidth        | 9 kHz    |

### 3.1.2 TEST PROCEDURE

- a. The EUT was 0.8 meters from the horizontal ground plane and 0.4 meters from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.1.3 TEST SETUP



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

### 3.1.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


### 3.1.5 TEST RESULTS

|               |              |                    |       |
|---------------|--------------|--------------------|-------|
| Temperature:  | 27 °C        | Relative Humidity: | 62.5% |
| Test Voltage: | AC 120V/60Hz | Phase:             | L     |
| Test Mode:    | Mode 4       |                    |       |

| Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>Factor(dB) | Result<br>(dBuV) | Limit<br>(dBuV) | Margin<br>(dB) | Remark |
|--------------------|-------------------|-----------------------|------------------|-----------------|----------------|--------|
|                    |                   |                       |                  |                 |                |        |
| 0.1740             | 48.59             | 9.79                  | 58.38            | 64.77           | -6.39          | QP     |
| 0.1740             | 30.72             | 9.79                  | 40.51            | 54.77           | -14.26         | AVG    |
| 0.2341             | 43.47             | 9.93                  | 53.40            | 62.30           | -8.90          | QP     |
| 0.2341             | 24.46             | 9.93                  | 34.39            | 52.30           | -17.91         | AVG    |
| 0.3340             | 38.30             | 10.16                 | 48.46            | 59.35           | -10.89         | QP     |
| 0.3340             | 19.27             | 10.16                 | 29.43            | 49.35           | -19.92         | AVG    |
| 0.5140             | 29.45             | 10.02                 | 39.47            | 56.00           | -16.53         | QP     |
| 0.5140             | 8.09              | 10.02                 | 18.11            | 46.00           | -27.89         | AVG    |
| 3.3220             | 34.45             | 9.82                  | 44.27            | 56.00           | -11.73         | QP     |
| 3.3220             | 12.81             | 9.82                  | 22.63            | 46.00           | -23.37         | AVG    |
| 10.3980            | 36.65             | 10.21                 | 46.86            | 60.00           | -13.14         | QP     |
| 10.3980            | 22.86             | 10.21                 | 33.07            | 50.00           | -16.93         | AVG    |

#### Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result =Reading + Factor )–Limit




|               |              |                    |       |
|---------------|--------------|--------------------|-------|
| Temperature:  | 27°C         | Relative Humidity: | 62.5% |
| Test Voltage: | AC 120V/60Hz | Phase:             | N     |
| Test Mode:    | Mode 4       |                    |       |

| Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>Factor(dB) | Result<br>(dBuV) | Limit<br>(dBuV) | Margin<br>(dB) | Remark |
|--------------------|-------------------|-----------------------|------------------|-----------------|----------------|--------|
| 0.1500             | 51.10             | 9.79                  | 60.89            | 66.00           | -5.11          | QP     |
| 0.1500             | 34.58             | 9.79                  | 44.37            | 56.00           | -11.63         | AVG    |
| 0.1980             | 45.38             | 9.78                  | 55.16            | 63.69           | -8.53          | QP     |
| 0.1980             | 26.42             | 9.78                  | 36.20            | 53.69           | -17.49         | AVG    |
| 0.2420             | 43.65             | 9.97                  | 53.62            | 62.03           | -8.41          | QP     |
| 0.2420             | 25.47             | 9.97                  | 35.44            | 52.03           | -16.59         | AVG    |
| 0.5420             | 30.11             | 9.99                  | 40.10            | 56.00           | -15.90         | QP     |
| 0.5420             | 14.86             | 9.99                  | 24.85            | 46.00           | -21.15         | AVG    |
| 3.4580             | 30.79             | 9.82                  | 40.61            | 56.00           | -15.39         | QP     |
| 3.4580             | 13.95             | 9.82                  | 23.77            | 46.00           | -22.23         | AVG    |
| 10.2460            | 36.49             | 10.21                 | 46.70            | 60.00           | -13.30         | QP     |
| 10.2460            | 23.51             | 10.21                 | 33.72            | 50.00           | -16.28         | AVG    |

**Remark:**

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result =Reading + Factor )–Limit

100.0 dBuV





## 3.2 RADIATED EMISSION MEASUREMENT

### 3.2.1 RADIATED EMISSION LIMITS

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on Part 15.249 and the Part 15.209(a) limit in the table below has to be followed.

Standard FCC 15.209

| Frequencies<br>(MHz) | Field Strength<br>(micorvolts/meter)                              | Measurement Distance<br>(meters) |
|----------------------|---|----------------------------------|
| 0.009~0.490          | 2400/F(KHz)   | 300                              |
| 0.490~1.705          | 24000/F(KHz)  | 30                               |
| 1.705~30.0           | 30  | 30                               |
| 30~88                | 100   | 3                                |
| 88~216               | 150   | 3                                |
| 216~960              | 200   | 3                                |
| 960~1000             | 500   | 3                                |
| Above 1000           | Other:74.0 dB( $\mu$ V)/m (Peak)<br>54.0 dB( $\mu$ V)/m (Average) | 3                                |

Standard FCC 15.249

| Frequency of Emission<br>(MHz) | Field Strength of<br>fundamental<br>(millivolts /meter) | Field Strength of<br>Harmonics<br>(microvolts/meter) |
|--------------------------------|---|--|
| 900~928                        | 50  | 500  |
| 2400~2483.5                    | 50  | 500  |
| 5725~5875                      | 50  | 500  |
| 24000~242500                   | 250   | 2500   |

Notes:

- (1) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.



In case the emission fall within the restricted band specified on RSS-Gen Issue 4 limit in the followed

. In measuring unwanted emissions, the spectrum shall be investigated from 30 MHz or the lowest radio frequency signal generated in the equipment, whichever is lower, without going below 9 kHz, up to at least the frequency given below:

(a) If the equipment operates below 10 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

(b) If the equipment operates at or above 10 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.

Particular attention should be paid to harmonics and sub-harmonics of the carrier frequency, as well as to those frequencies removed from the carrier by multiples of the oscillator frequency. Radiation at the frequencies of multiplier stages should also be checked.

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value need not be reported.

When limits are expressed in absolute terms, compliance with the emission limits below 1000 MHz shall be demonstrated using a CISPR quasi-peak detector and the related measurement bandwidth. As an alternative to CISPR quasi-peak measurement, compliance with the emission limits can be demonstrated using measuring equipment employing a peak detector function properly adjusted for factors such as pulse desensitization as required, with an equal or greater measurement bandwidth relative to the applicable CISPR quasi-peak bandwidth.

Above 1000 MHz, compliance with the emission limits shall be demonstrated using an average detector with a minimum resolution bandwidth of 1 MHz.

In case the emission fall within the restricted band specified on RSS 210 Issue 9 (B.10) limit in the followed

1. The field strength of fundamental and harmonic emissions, measured at 3 m, shall not exceed 50 mV/m and 0.5 mV/m respectively.

The field strength limits shall be measured using an average detector, except for the fundamental emission in the frequency band 902-928 MHz, which is based on measurements using an International Special Committee on Radio Interference (CISPR) quasi-peak detector.

2. Emissions radiated outside of the specified frequency bands, except for harmonic emissions, shall be attenuated by at least 50 dB below the level of the fundamental emissions or to the general field strength limits listed in RSS-Gen, whichever is less stringent.

**NOTE:**

(1)The limit for radiated test was performed according to RSS 210 Issue 9

(2)Emission level (dBuV/m)=20log Emission level (uV/m).



| Spectrum Parameter               | Setting               |
|----------------------------------|-----------------------|
| Detector                         | Peak/AV               |
| Attenuation                      | Auto                  |
| Start Frequency                  | 1000 MHz              |
| Stop Frequency                   | 10th carrier harmonic |
| RB (emission in restricted band) | >20BW                 |
| VB (emission in restricted band) | =3xRB                 |

| Receiver Parameter     | Setting                              |
|------------------------|--------------------------------------|
| Attenuation            | Auto                                 |
| Start ~ Stop Frequency | 9kHz~90kHz / RB 200Hz for PK & AV    |
|                        | 90kHz~110kHz / RB 200Hz for QP       |
|                        | 110kHz~490kHz / RB 200Hz for PK & AV |
|                        | 490kHz~30MHz / RB 9kHz for QP        |
|                        | 30MHz~1000MHz / RB 120kHz for QP     |

### 3.2.2 TEST PROCEDURE

- a. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Below 1GHz)
- b. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Above 1GHz)
- c. The height of the test antenna shall vary between 1m to 4m. Both horizontal and vertical polarization of the antenna are set to make the measurement.
- d. The initial step in collecting radiated emission data is a receive peak detector mode. Pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. All readings are peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP limits and then QP Mode measurement didn't perform (Below 1GHz)
- f. All readings are Peak mode value unless otherwise stated AVG in column of Note. If the Peak mode measured value compliance with the Peak limits and lower than AVG Limits, the EUT shall be deemed to meet Peak & AVG limits and then only Peak mode was measured, but AVG mode didn't perform.(Above 1GHz)
- g. For the actual test configuration, please refer to the related Item –EUT Test Photos.


Note: Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

### 3.2.3 DEVIATION FROM TEST STANDARD


No deviation

### 3.2.4 TEST SETUP


#### (A) Radiated Emission Test-Up Frequency Below 30MHz



#### (B) Radiated Emission Test-Up Frequency 30MHz~1GHz



#### (C) Radiated Emission Test-Up Frequency Above 1GHz





### 3.2.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

| Frequency | FS             | RA             | AF   | CL   | AG   | Factor |
|-----------|----------------|----------------|------|------|------|--------|
| (MHz)     | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB) | (dB) | (dB) | (dB)   |
| 300       | 40             | 58.1           | 12.2 | 1.6  | 31.9 | -18.1  |

$$\text{Factor} = AF + CL - AG$$

### 3.2.6 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

Below 30 MHz

|               |                |                    |     |
|---------------|----------------|--------------------|-----|
| Temperature:  | 27.1°C         | Relative Humidity: | 59% |
| Test Voltage: | DC 5V from USB | Polarization:      | --  |
| Test Mode:    | TX Mode        |                    |     |

| Freq. | Reading        | Limit          | Margin | State |
|-------|----------------|----------------|--------|-------|
| (MHz) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   | P/F   |
| --    | --             | --             | --     | PASS  |
| --    | --             | --             | --     | PASS  |

#### NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log(\text{specific distance}/\text{test distance})$  (dB);

Limit line = specific limits(dB $\mu$ V) + distance extrapolation factor.


## Between 30MHz – 1000 MHz Radiation Spurious

|               |                           |                    |            |
|---------------|---------------------------|--------------------|------------|
| Temperature:  | 27.1 °C                   | Relative Humidity: | 59%        |
| Test Voltage: | DC 5V from USB            | Phase:             | Horizontal |
| Test Mode:    | Mode 1/2/3(Model 1 worst) |                    |            |

| Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>Factor(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|--------------------|-------------------|-------------------------|--------------------|-------------------|----------------|--------|
| 47.4917            | 40.15             | -20.19                  | 19.96              | 40.00             | -20.04         | QP     |
| 99.8777            | 42.70             | -19.20                  | 23.50              | 43.50             | -20.00         | QP     |
| 199.2855           | 50.96             | -20.17                  | 30.79              | 43.50             | -12.71         | QP     |
| 266.6090           | 49.25             | -15.33                  | 33.92              | 46.00             | -12.08         | QP     |
| 492.4685           | 41.81             | -9.09                   | 32.72              | 46.00             | -13.28         | QP     |
| 1000.0000          | 38.04             | -0.07                   | 37.97              | 54.00             | -16.03         | QP     |

## Remark:

1. All readings are Quasi-Peak .
2. Margin = Result (Result =Reading + Factor )–Limit






|               |                           |                    |          |
|---------------|---------------------------|--------------------|----------|
| Temperature:  | 27.1 °C                   | Relative Humidity: | 59%      |
| Test Voltage: | DC 5V from USB            | Phase:             | Vertical |
| Test Mode:    | Mode 1/2/3(Model 1 worst) |                    |          |

| Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>Factor(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|--------------------|-------------------|-------------------------|--------------------|-------------------|----------------|--------|
| 44.9004            | 42.30             | -18.86                  | 23.44              | 40.00             | -16.56         | QP     |
| 99.8777            | 42.98             | -19.20                  | 23.78              | 43.50             | -19.72         | QP     |
| 260.1444           | 44.23             | -15.07                  | 29.16              | 46.00             | -16.84         | QP     |
| 467.2348           | 44.27             | -9.87                   | 34.40              | 46.00             | -11.60         | QP     |
| 701.7610           | 38.74             | -5.29                   | 33.45              | 46.00             | -12.55         | QP     |
| 932.2712           | 33.50             | -1.05                   | 32.45              | 46.00             | -13.55         | QP     |

**Remark:**

1. All readings are Quasi-Peak.
2. Margin = Result (Result =Reading + Factor )–Limit





Fundamental frequency:

PK

| Frequency<br>(MHz) | Reading<br>(dB $\mu$ V/m) | Amplifier | Loss | Antenna<br>Factor | Factor(dB)<br>Corr. | Result | Limit | Margin(dB) | Polarization |
|--------------------|---------------------------|-----------|------|-------------------|---------------------|--------|-------|------------|--------------|
|                    |                           |           |      |                   |                     | (dB)   | (dB)  | (dB/m)     |              |
| 2405               | 90.548                    | 44.40     | 6.03 | 27.60             | -10.77              | 79.78  | 114   | -34.22     | Vertical     |
| 2405               | 91.360                    | 44.40     | 6.03 | 27.60             | -10.77              | 80.59  | 114   | -33.41     | Horizontal   |
| 2430               | 90.601                    | 44.40     | 6.04 | 27.63             | -10.73              | 79.87  | 114   | -34.13     | Vertical     |
| 2430               | 91.166                    | 44.40     | 6.04 | 27.63             | -10.73              | 80.44  | 114   | -33.56     | Horizontal   |
| 2460               | 90.620                    | 44.40     | 6.06 | 27.66             | -10.68              | 79.94  | 114   | -34.06     | Vertical     |
| 2460               | 91.269                    | 44.40     | 6.06 | 27.66             | -10.68              | 80.59  | 114   | -33.41     | Horizontal   |

AV

| Frequency<br>(MHz) | Reading<br>(dB $\mu$ V/m) | Amplifier | Loss | Antenna<br>Factor | Factor(dB)<br>Corr. | Result | Limit | Margin(dB) | Polarization |
|--------------------|---------------------------|-----------|------|-------------------|---------------------|--------|-------|------------|--------------|
|                    |                           |           |      |                   |                     | (dB)   | (dB)  | (dB/m)     |              |
| 2405               | 76.446                    | 44.40     | 6.03 | 27.60             | -10.77              | 65.68  | 94    | -28.32     | Vertical     |
| 2405               | 75.360                    | 44.40     | 6.03 | 27.60             | -10.77              | 64.59  | 94    | -29.41     | Horizontal   |
| 2430               | 76.059                    | 44.40     | 6.04 | 27.63             | -10.73              | 65.33  | 94    | -28.67     | Vertical     |
| 2430               | 74.625                    | 44.40     | 6.04 | 27.63             | -10.73              | 63.90  | 94    | -30.10     | Horizontal   |
| 2460               | 75.053                    | 44.40     | 6.06 | 27.66             | -10.68              | 64.38  | 94    | -29.62     | Vertical     |
| 2460               | 73.600                    | 44.40     | 6.06 | 27.66             | -10.68              | 62.92  | 94    | -31.08     | Horizontal   |

Note: RBW>20BW; VBW=3xRBW



## Above 1G Radiation Spurious

| Frequency<br>(MHz)     | Reading<br>(dB $\mu$ V) | Amplifier<br>(dB) | Loss<br>(dB) | Antenna<br>Factor<br>(dB/m) | Corrected<br>Factor<br>(dB) | Emission<br>Level<br>(dB $\mu$ V/m) | Limits<br>(dB $\mu$ V/m) | Margin<br>(dB) | Detector<br>Type | Comment    |
|------------------------|-------------------------|-------------------|--------------|-----------------------------|-----------------------------|-------------------------------------|--------------------------|----------------|------------------|------------|
| Low Channel (2405 MHz) |                         |                   |              |                             |                             |                                     |                          |                |                  |            |
| 3264.73                | 48.21                   | 44.70             | 6.70         | 28.20                       | -9.80                       | 38.41                               | 74.00                    | -35.59         | PK               | Vertical   |
| 3264.73                | 38.70                   | 44.70             | 6.70         | 28.20                       | -9.80                       | 28.90                               | 54.00                    | -25.10         | AV               | Vertical   |
| 3264.83                | 48.09                   | 44.70             | 6.70         | 28.20                       | -9.80                       | 38.29                               | 74.00                    | -35.71         | PK               | Horizontal |
| 3264.83                | 38.31                   | 44.70             | 6.70         | 28.20                       | -9.80                       | 28.51                               | 54.00                    | -25.49         | AV               | Horizontal |
| 4810.51                | 59.32                   | 44.20             | 9.04         | 31.60                       | -3.56                       | 55.76                               | 74.00                    | -18.24         | PK               | Vertical   |
| 4810.51                | 38.25                   | 44.20             | 9.04         | 31.60                       | -3.56                       | 34.69                               | 54.00                    | -19.31         | AV               | Vertical   |
| 4810.54                | 59.25                   | 44.20             | 9.04         | 31.60                       | -3.56                       | 55.69                               | 74.00                    | -18.31         | PK               | Horizontal |
| 4810.54                | 38.76                   | 44.20             | 9.04         | 31.60                       | -3.56                       | 35.20                               | 54.00                    | -18.80         | AV               | Horizontal |
| 5359.71                | 46.38                   | 44.20             | 9.86         | 32.00                       | -2.34                       | 44.04                               | 74.00                    | -29.96         | PK               | Vertical   |
| 5359.71                | 38.35                   | 44.20             | 9.86         | 32.00                       | -2.34                       | 36.01                               | 54.00                    | -17.99         | AV               | Vertical   |
| 5359.83                | 46.39                   | 44.20             | 9.86         | 32.00                       | -2.34                       | 44.05                               | 74.00                    | -29.95         | PK               | Horizontal |
| 5359.83                | 38.11                   | 44.20             | 9.86         | 32.00                       | -2.34                       | 35.77                               | 54.00                    | -18.23         | AV               | Horizontal |
| 7215.93                | 51.48                   | 43.50             | 11.40        | 35.50                       | 3.40                        | 54.88                               | 74.00                    | -19.12         | PK               | Vertical   |
| 7215.93                | 33.22                   | 43.50             | 11.40        | 35.50                       | 3.40                        | 36.62                               | 54.00                    | -17.38         | AV               | Vertical   |
| 7215.90                | 51.12                   | 43.50             | 11.40        | 35.50                       | 3.40                        | 54.52                               | 74.00                    | -19.48         | PK               | Horizontal |
| 7215.90                | 32.99                   | 43.50             | 11.40        | 35.50                       | 3.40                        | 36.39                               | 54.00                    | -17.61         | AV               | Horizontal |



| Frequency<br>(MHz)        | Reading<br>(dB $\mu$ V) | Amplifier<br>(dB) | Loss<br>(dB) | Antenna<br>Factor<br>(dB/m) | Corrected<br>Factor<br>(dB) | Emission<br>Level<br>(dB $\mu$ V/m) | Limits<br>(dB $\mu$ V/m) | Margin<br>(dB) | Detector<br>Type | Comment    |
|---------------------------|-------------------------|-------------------|--------------|-----------------------------|-----------------------------|-------------------------------------|--------------------------|----------------|------------------|------------|
| Middle Channel (2430 MHz) |                         |                   |              |                             |                             |                                     |                          |                |                  |            |
| 3264.75                   | 49.13                   | 44.70             | 6.70         | 28.20                       | -9.80                       | 39.33                               | 74.00                    | -34.67         | PK               | Vertical   |
| 3264.75                   | 39.11                   | 44.70             | 6.70         | 28.20                       | -9.80                       | 29.31                               | 54.00                    | -24.69         | AV               | Vertical   |
| 3264.61                   | 48.45                   | 44.70             | 6.70         | 28.20                       | -9.80                       | 38.65                               | 74.00                    | -35.35         | PK               | Horizontal |
| 3264.61                   | 38.13                   | 44.70             | 6.70         | 28.20                       | -9.80                       | 28.33                               | 54.00                    | -25.67         | AV               | Horizontal |
| 4860.40                   | 58.48                   | 44.20             | 9.04         | 31.60                       | -3.56                       | 54.92                               | 74.00                    | -19.08         | PK               | Vertical   |
| 4860.40                   | 39.34                   | 44.20             | 9.04         | 31.60                       | -3.56                       | 35.78                               | 54.00                    | -18.22         | AV               | Vertical   |
| 4860.37                   | 59.25                   | 44.20             | 9.04         | 31.60                       | -3.56                       | 55.69                               | 74.00                    | -18.31         | PK               | Horizontal |
| 4860.37                   | 39.57                   | 44.20             | 9.04         | 31.60                       | -3.56                       | 36.01                               | 54.00                    | -17.99         | AV               | Horizontal |
| 5359.59                   | 45.30                   | 44.20             | 9.86         | 32.00                       | -2.34                       | 42.96                               | 74.00                    | -31.04         | PK               | Vertical   |
| 5359.59                   | 38.20                   | 44.20             | 9.86         | 32.00                       | -2.34                       | 35.86                               | 54.00                    | -18.14         | AV               | Vertical   |
| 5359.60                   | 45.60                   | 44.20             | 9.86         | 32.00                       | -2.34                       | 43.26                               | 74.00                    | -30.74         | PK               | Horizontal |
| 5359.60                   | 37.94                   | 44.20             | 9.86         | 32.00                       | -2.34                       | 35.60                               | 54.00                    | -18.40         | AV               | Horizontal |
| 7290.72                   | 51.46                   | 43.50             | 11.40        | 35.50                       | 3.40                        | 54.86                               | 74.00                    | -19.14         | PK               | Vertical   |
| 7290.72                   | 33.16                   | 43.50             | 11.40        | 35.50                       | 3.40                        | 36.56                               | 54.00                    | -17.44         | AV               | Vertical   |
| 7290.88                   | 50.62                   | 43.50             | 11.40        | 35.50                       | 3.40                        | 54.02                               | 74.00                    | -19.98         | PK               | Horizontal |
| 7290.88                   | 33.18                   | 43.50             | 11.40        | 35.50                       | 3.40                        | 36.58                               | 54.00                    | -17.42         | AV               | Horizontal |



| Frequency<br>(MHz)      | Reading<br>(dB $\mu$ V) | Amplifier<br>(dB) | Loss<br>(dB) | Antenna<br>Factor<br>(dB/m) | Corrected<br>Factor<br>(dB) | Emission<br>Level<br>(dB $\mu$ V/m) | Limits<br>(dB $\mu$ V/m) | Margin<br>(dB) | Detector<br>Type | Comment    |
|-------------------------|-------------------------|-------------------|--------------|-----------------------------|-----------------------------|-------------------------------------|--------------------------|----------------|------------------|------------|
| High Channel (2460 MHz) |                         |                   |              |                             |                             |                                     |                          |                |                  |            |
| 3264.77                 | 48.17                   | 44.70             | 6.70         | 28.20                       | -9.80                       | 38.37                               | 74.00                    | -35.63         | PK               | Vertical   |
| 3264.77                 | 38.36                   | 44.70             | 6.70         | 28.20                       | -9.80                       | 28.56                               | 54.00                    | -25.44         | AV               | Vertical   |
| 3264.71                 | 48.00                   | 44.70             | 6.70         | 28.20                       | -9.80                       | 38.20                               | 74.00                    | -35.80         | PK               | Horizontal |
| 3264.71                 | 38.31                   | 44.70             | 6.70         | 28.20                       | -9.80                       | 28.51                               | 54.00                    | -25.49         | AV               | Horizontal |
| 4920.43                 | 58.47                   | 44.20             | 9.04         | 31.60                       | -3.56                       | 54.91                               | 74.00                    | -19.09         | PK               | Vertical   |
| 4920.43                 | 39.25                   | 44.20             | 9.04         | 31.60                       | -3.56                       | 35.69                               | 54.00                    | -18.31         | AV               | Vertical   |
| 4920.37                 | 59.13                   | 44.20             | 9.04         | 31.60                       | -3.56                       | 55.57                               | 74.00                    | -18.43         | PK               | Horizontal |
| 4920.37                 | 38.89                   | 44.20             | 9.04         | 31.60                       | -3.56                       | 35.33                               | 54.00                    | -18.67         | AV               | Horizontal |
| 5359.81                 | 45.92                   | 44.20             | 9.86         | 32.00                       | -2.34                       | 43.58                               | 74.00                    | -30.42         | PK               | Vertical   |
| 5359.81                 | 37.52                   | 44.20             | 9.86         | 32.00                       | -2.34                       | 35.18                               | 54.00                    | -18.82         | AV               | Vertical   |
| 5359.62                 | 46.48                   | 44.20             | 9.86         | 32.00                       | -2.34                       | 44.14                               | 74.00                    | -29.86         | PK               | Horizontal |
| 5359.62                 | 38.21                   | 44.20             | 9.86         | 32.00                       | -2.34                       | 35.87                               | 54.00                    | -18.13         | AV               | Horizontal |
| 7380.72                 | 51.74                   | 43.50             | 11.40        | 35.50                       | 3.40                        | 55.14                               | 74.00                    | -18.86         | PK               | Vertical   |
| 7380.72                 | 32.58                   | 43.50             | 11.40        | 35.50                       | 3.40                        | 35.98                               | 54.00                    | -18.02         | AV               | Vertical   |
| 7380.79                 | 51.50                   | 43.50             | 11.40        | 35.50                       | 3.40                        | 54.90                               | 74.00                    | -19.10         | PK               | Horizontal |
| 7380.79                 | 33.62                   | 43.50             | 11.40        | 35.50                       | 3.40                        | 37.02                               | 54.00                    | -16.98         | AV               | Horizontal |

Note:


1) Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Reading + Factor

2) The frequency emission of peak points that did not show above the forms are below the limit, the frequency emission is mainly from the environment noise.




(Restricted Bands)


**GFSK-Low**  
Horizontal

| No. | Frequency | Reading | Correct      | Result   | Limit    | Margin | Remark |
|-----|-----------|---------|--------------|----------|----------|--------|--------|
|     | (MHz)     | (dBuV)  | Factor(dB/m) | (dBuV/m) | (dBuV/m) | (dB)   |        |
| 1   | 2317.600  | 59.33   | -11.22       | 48.11    | 74.00    | -25.89 | peak   |
| 2   | 2390.000  | 56.57   | -10.75       | 45.82    | 74.00    | -28.18 | peak   |

## Vertical




| No. | Frequency | Reading | Correct      | Result   | Limit    | Margin | Remark |
|-----|-----------|---------|--------------|----------|----------|--------|--------|
|     | (MHz)     | (dBuV)  | Factor(dB/m) | (dBuV/m) | (dBuV/m) | (dB)   |        |
| 1   | 2326.400  | 58.82   | -11.17       | 47.65    | 74.00    | -26.35 | peak   |
| 2   | 2390.000  | 56.91   | -10.75       | 46.16    | 74.00    | -27.84 | peak   |

**GFSK-High**  
Horizontal

| No. | Frequency | Reading | Correct      | Result   | Limit    | Margin | Remark |
|-----|-----------|---------|--------------|----------|----------|--------|--------|
|     | (MHz)     | (dBuV)  | Factor(dB/m) | (dBuV/m) | (dBuV/m) | (dB)   |        |
| 1   | 2483.500  | 55.36   | -10.29       | 45.07    | 74.00    | -28.93 | peak   |
| 2   | 2546.872  | 59.84   | -10.08       | 49.76    | 74.00    | -24.24 | peak   |

## Vertical



| No. | Frequency | Reading | Correct      | Result   | Limit    | Margin | Remark |
|-----|-----------|---------|--------------|----------|----------|--------|--------|
|     | (MHz)     | (dBuV)  | Factor(dB/m) | (dBuV/m) | (dBuV/m) | (dB)   |        |
| 1   | 2483.500  | 55.74   | -10.29       | 45.45    | 74.00    | -28.55 | peak   |
| 2   | 2523.872  | 59.26   | -10.14       | 49.12    | 74.00    | -24.88 | peak   |

## 4. BANDWIDTH TEST

### 4.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW= 30KHz, VBW $\geq$ RBW, Sweep time = Auto.

### 4.2 TEST SETUP



### 4.3 EUT OPERATION CONDITIONS

TX mode.




#### 4.4 TEST RESULTS

|               |             |                    |     |
|---------------|-------------|--------------------|-----|
| Temperature:  | 25 °C       | Relative Humidity: | 50% |
| Test Voltage: | AC120V/60Hz |                    |     |


| Test Channel | Frequency (MHz) | 20 dBc Bandwidth (MHz) | 99% Bandwidth (MHz) |
|--------------|-----------------|------------------------|---------------------|
| CH01         | 2405            | 1.457                  | 1.6262              |
| CH06         | 2430            | 1.393                  | 1.6452              |
| CH10         | 2460            | 1.402                  | 1.6493              |

#### The Lowest Channel:2405MHz






### The Middle Channel: 2430MHz



### The High Channel: 2460MHz





## 5. ANTENNA REQUIREMENT

### 5.1 STANDARD REQUIREMENT

According to the FCC Part 15 Paragraph 15.203& RSS-Gen Issue 5, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 5.2 EUT ANTENNA

The EUT antenna is PCB Antenna. It conforms to the standard requirements.





## 6.FREQUENCY STABILITY

### 6.1 LIMITS

The frequency tolerance of the carrier signal shall be maintained within +/-0.02% of the operating frequency over a temperature variation of -30 degrees to 50 degrees C at normal supply voltage, and for a variation in primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees.

### 6.2 TEST PROCEDURE

- 1.The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
- 2.Turn the EUT on and couple its output to spectrum analyzer.
- 3.Turn the EUT off and set the chamber to the highest temperature specified.
- 4.Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2,5, and 10 minutes.
- 5.Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
- 6.The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

### 6.3 TEST RESULT

Channel 06 (2430MHz)

#### Voltage vs. Frequency Stability

| Voltage vs. Frequency<br>Stability Voltage(V) | Measurement<br>Frequency(MHz) |
|---|-------------------------------|
| 5.75  | 2430.0025                     |
| 5   | 2430.0022                     |
| 4.25  | 2430.0017                     |
| Max.Deviation(MHz)                            | 0.0025                        |
| Max.Deviation(ppm)                            | 1.03                          |

Rated working voltage:DC 5V

#### Temperature vs. Frequency Stability

| Temperature(°C)    | Measurement<br>Frequency(MHz) |
|--------------------|-------------------------------|
| -30                | 2430.0031                     |
| -20                | 2430.0021                     |
| -10                | 2430.0024                     |
| 0                  | 2430.0030                     |
| 10                 | 2430.0030                     |
| 20                 | 2430.0028                     |
| 30                 | 2430.0026                     |
| 40                 | 2430.0029                     |
| 50                 | 2430.0021                     |
| Max.Deviation(MHz) | 0.0031                        |
| Max.Deviation(ppm) | 1.28                          |



## APPENDIX- PHOTOS OF TEST SETUP

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

※※※※※END OF THE REPORT※※※※

