

TEST REPORT**Report No.: HK11010872-1****Canon Electronic Business Machines (H.K.) Co., Ltd.**

Application
For
Certification
(Original Grant)
(FCC ID: Y7J5093B01)

Transceiver

Prepared and Checked by:

Signed On File
Wong Kwok Yeung, Kenneth
Engineer

Approved by:

Chan Chi Hung, Terry
Assistant Supervisor
Date: June 15, 2011

- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

INTERTEK TESTING SERVICES

GENERAL INFORMATION

Canon Electronic Business Machines (H.K.) Co., Ltd.
BRAND NAME: Canon, MODEL: X Mark I Keypad BT

FCC ID: Y7J5093B01

Grantee:	Canon Electronic Business Machines (H.K.) Co., Ltd.
Grantee Address:	17/F., Tower One, Ever Gain Plaza, 82-100 Container Port Road, Kwai Chung, N.T., Hong Kong.
Contact Person:	Mr. Ronald Chan
Tel:	852-2305 8400
Fax:	852-2318 1719
e-mail:	Ronald_Chan@cebm.canon.com.hk
Manufacturer:	Canon Electronic Business Machines (H.K.) Co., Ltd.
Manufacturer Address:	17/F., Tower One, Ever Gain Plaza, 82-100 Container Port Road, Kwai Chung, N.T., Hong Kong.
Brand Name:	Canon
Model:	X Mark I Keypad BT
Type of EUT:	Transceiver
Description of EUT:	Bluetooth Keypad
Serial Number:	N/A
FCC ID:	Y7J5093B01
Date of Sample Submitted:	January 20, 2011
Date of Test:	February 01, 2011 to February 09, 2011
Report No.:	HK11010872-1
Report Date:	June 15, 2011
Environmental Conditions:	Temperature: +10 to 40°C Humidity: 10 to 90%

INTERTEK TESTING SERVICES

SUMMARY OF TEST RESULT

Canon Electronic Business Machines (H.K.) Co., Ltd.
BRAND NAME: Canon, MODEL: X Mark I Keypad BT

FCC ID: Y7J5093B01

TEST SPECIFICATION	REFERENCE	RESULTS
Maximum Peak Output Power	15.247(b), (c) / RSS-210 A8.4	N/A
Hopping Channel Carrier Frequencies Separation	15.247(e) / RSS-210 A8.1	N/A
20dB Bandwidth of the Hopping Channel	15.247(a) / RSS-210 A8.1	N/A
Number of Hopping Frequencies	15.247(e) / RSS-210 A8.1	N/A
Average Time of Occupancy of Hopping Frequency	15.247(e) / RSS-210 A8.1	N/A
Antenna Conducted Spurious Emissions	15.247(d) / RSS-210 A8.5	N/A
Radiated Spurious Emissions	15.247(d) / RSS-210 A8.5	N/A
RF Exposure Compliance	15.247(i) / RSS-Gen 5.5	N/A
Transmitter Power Line Conducted Emissions	15.207 / RSS-Gen 7.2.2	N/A
Transmitter Field Strength	15.227 / RSS-310 3.8	N/A
Transmitter Field Strength	15.229 / RSS-210 A2.7	N/A
Transmitter Field Strength, Bandwidth and Timing Requirement	15.231(a) / RSS-210 A1.1.1	N/A
Transmitter Field Strength, Bandwidth and Timing Requirement	15.231(e) / RSS-210 A1.1.5	N/A
Transmitter Field Strength and Bandwidth Requirement	15.239 / RSS-210 A2.8	N/A
Transmitter Field Strength and Bandwidth Requirement	15.249 / RSS-210 A2.9	Pass
Transmitter Field Strength and Bandwidth Requirement	15.235 / RSS-310 3.9	N/A
Digital Device Radiated Emissions	15.109 / ICES-003	Pass
Digital Device Conducted Emissions	15.107 / ICES-003	N/A

Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.

2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

INTERTEK TESTING SERVICES

Table of Contents

1.0	<u>General Description</u>	1
1.1	Product Description	1
1.2	Related Submittal(s) Grants	1
1.3	Test Methodology	1
1.4	Test Facility	1
2.0	<u>System Test Configuration</u>	2
2.1	Justification	2
2.2	EUT Exercising Software	3
2.3	Special Accessories	3
2.4	Equipment Modification	3
2.5	Measurement Uncertainty	3
2.6	Support Equipment List and Description	3
3.0	<u>Emission Results</u>	4
3.1	Field Strength Calculation	4
3.2	Radiated Emission Configuration Photograph	5
3.3	Radiated Emission Data	5
4.0	<u>Equipment Photographs</u>	10
5.0	<u>Product Labelling</u>	10
6.0	<u>Technical Specifications</u>	10
7.0	<u>Instruction Manual</u>	10
8.0	<u>Miscellaneous Information</u>	10
8.1	Measured Bandwidth	11
8.2	Discussion of Pulse Desensitization	11
8.3	Calculation of Average Factor	12
8.4	Emissions Test Procedures	13
9.0	<u>Confidentiality Request</u>	13
10.0	<u>Equipment List</u>	15

INTERTEK TESTING SERVICES

1.0 General Description

1.1 Product Description

The equipment under test (EUT) is a Bluetooth wireless calculator or numeric keypad device, which is operate at 2402MHz to 2480MHz with 1MHz channel spacing. The EUT is energized by either two AAA size batteries or solar energy. The EUT can be connected with both “PC” and Macintosh hardware for use across various different computer models via Bluetooth protocol; it can be used as a wireless numeric keypad for data entry.

Antenna Type : Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Related Submittal(s) Grants

This is a single application for certification of a transceiver.

1.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.4 (2003). All radiated measurements were performed in an Open Area Test Site. Preliminary scans were performed in the Open Area Test Site only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

INTERTEK TESTING SERVICES

2.0 System Test Configuration

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2003).

The device was powered by two new AAA size batteries.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

INTERTEK TESTING SERVICES

2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

2.4 Equipment Modification

Any modifications installed previous to testing by Canon Electronic Business Machines (H.K.) Co., Ltd. will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Intertek Testing Services Hong Kong Ltd.

2.5 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

2.6 Support Equipment List and Description

For test mode setting;

1. Bluetooth Control Module Testing Kit (Provided by Applicant)
2. Software: Mocha Test – Bluepacket Mocha Test Tool 2.1.0b (Provided by Applicant)

INTERTEK TESTING SERVICES

3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + CF - AG - AV$$

where FS = Field Strength in $dB\mu V/m$

RA = Receiver Amplitude (including preamplifier) in $dB\mu V$

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where FS = Field Strength in $dB\mu V/m$

RR = $RA - AG - AV$ in $dB\mu V$

LF = $CF + AF$ in dB

Assume a receiver reading of 52.0 $dB\mu V$ is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 $dB\mu V/m$. This value in $dB\mu V/m$ was converted to its corresponding level in $\mu V/m$.

$$RA = 52.0 \text{ } dB\mu V/m$$

$$AF = 7.4 \text{ dB}$$

$$RR = 18.0 \text{ } dB\mu V$$

$$CF = 1.6 \text{ dB}$$

$$LF = 9.0 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$AV = 5.0 \text{ dB}$$

$$FS = RR + LF$$

$$FS = 18 + 9 = 27 \text{ } dB\mu V/m$$

$$\text{Level in } \mu V/m = \text{Common Antilogarithm } [(27 \text{ } dB\mu V/m)/20] = 22.4 \text{ } \mu V/m$$

INTERTEK TESTING SERVICES

3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 7206.000 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 15.0 dB

INTERTEK TESTING SERVICES

Applicant: Canon Electronic Business Machines (H.K.) Co., Ltd.

Model: X Mark I Keypad BT Date of Test: February 01, 2011 to February 09, 2011

Worst-Case Operating Mode: Transmitting

Table 1

Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Lowest Channel

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
V	2402.000	90.1	33	29.4	86.5	30.1	56.4	94.0	-37.6
V	4804.000	46.7	33	34.9	48.6	30.1	18.5	54.0	-35.5
V	7206.000	54.1	33	37.9	59.0	30.1	28.9	54.0	-25.1
H	9608.000	43.7	33	40.4	51.1	30.1	21.0	54.0	-33.0
H	12010.000	45.3	33	40.5	52.8	30.1	22.7	54.0	-31.3
H	14412.000	48.0	33	40.0	55.0	30.1	24.9	54.0	-29.1

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Calculated at 3m (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
V	2402.000	90.1	33	29.4	86.5	86.5	114.0	-27.5
V	4804.000	46.7	33	34.9	48.6	48.6	74.0	-25.4
V	7206.000	54.1	33	37.9	59.0	59.0	74.0	-15.0
H	9608.000	43.7	33	40.4	51.1	51.1	74.0	-22.9
H	12010.000	45.3	33	40.5	52.8	52.8	74.0	-21.2
H	14412.000	48.0	33	40.0	55.0	55.0	74.0	-19.0

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: Canon Electronic Business Machines (H.K.) Co., Ltd.

Model: X Mark I Keypad BT Date of Test: February 01, 2011 to February 09, 2011

Worst-Case Operating Mode: Transmitting

Table 2

Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Middle Channel

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
V	2441.000	88.6	33	29.4	85.0	30.1	54.9	94.0	-39.1
V	4882.000	47.4	33	34.9	49.3	30.1	19.2	54.0	-34.8
V	7323.000	53.5	33	37.9	58.4	30.1	28.3	54.0	-25.7
H	9764.000	44.3	33	40.4	51.7	30.1	21.6	54.0	-32.4
H	12205.000	45.9	33	40.5	53.4	30.1	23.3	54.0	-30.7
H	14646.000	50.0	33	38.4	55.4	30.1	25.3	54.0	-28.7

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Calculated at 3m (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
V	2441.000	88.6	33	29.4	85.0	85.0	114.0	-29.0
V	4882.000	47.4	33	34.9	49.3	49.3	74.0	-24.7
V	7323.000	53.5	33	37.9	58.4	58.4	74.0	-15.6
H	9764.000	44.3	33	40.4	51.7	51.7	74.0	-22.3
H	12205.000	45.9	33	40.5	53.4	53.4	74.0	-20.6
H	14646.000	50.0	33	38.4	55.4	55.4	74.0	-18.6

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: Canon Electronic Business Machines (H.K.) Co., Ltd.

Model: X Mark I Keypad BT Date of Test: February 01, 2011 to February 09, 2011

Worst-Case Operating Mode: Transmitting

Table 3

Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Highest Channel

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
V	2480.000	89.6	33	29.4	86.0	30.1	55.9	94.0	-38.1
V	4960.000	48.1	33	34.9	50.0	30.1	19.9	54.0	-34.1
V	7440.000	53.9	33	37.9	58.8	30.1	28.7	54.0	-25.3
H	9920.000	44.0	33	40.4	51.4	30.1	21.3	54.0	-32.7
H	12400.000	46.1	33	40.5	53.6	30.1	23.5	54.0	-30.5
H	14880.000	49.9	33	38.4	55.3	30.1	25.2	54.0	-28.8

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Calculated at 3m (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
V	2480.000	89.6	33	29.4	86.0	86.0	114.0	-28.0
V	4960.000	48.1	33	34.9	50.0	50.0	74.0	-24.0
V	7440.000	53.9	33	37.9	58.8	58.8	74.0	-15.2
H	9920.000	44.0	33	40.4	51.4	51.4	74.0	-22.6
H	12400.000	46.1	33	40.5	53.6	53.6	74.0	-20.4
H	14880.000	49.9	33	38.4	55.3	55.3	74.0	-18.7

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: Canon Electronic Business Machines (H.K.) Co., Ltd.

Model: X Mark I Keypad BT Date of Test: February 01, 2011 to February 09, 2011

Worst-Case Operating Mode: Power On

Table 4

Radiated Emissions Pursuant to FCC Part 15 Section 15.109 Requirement

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	33.850	38.8	16	10.0	32.8	40.0	-7.2
V	38.410	39.1	16	10.0	33.1	40.0	-6.9
V	43.750	37.4	16	10.0	31.4	40.0	-8.6
V	48.400	36.6	16	11.0	31.6	40.0	-8.4
V	53.105	35.3	16	11.0	30.3	40.0	-9.7
V	58.400	35.6	16	11.0	30.6	40.0	-9.4

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

4.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

5.0 Product Labelling

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

6.0 Technical Specifications

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

8.0 Miscellaneous Information

The miscellaneous information includes details of the test procedure and measured bandwidth.

INTERTEK TESTING SERVICES

8.1 Measured Bandwidth

From the following plots, they show that the fundamental emissions are confined in the specified band (2400MHz to 2483.5MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.4 (2003) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).

Peak Measurement

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

Lower bandedge

Resultant field strength = Fundamental emissions (peak value) – delta from the plot
= 86.5 dB μ V/m – 49.48 dB μ V/m
= 37.02 dB μ V/m

Upper bandedge

Resultant field strength = Fundamental emissions (peak value) – delta from the plot
= 86.0 dB μ V/m – 53.0 dB μ V/m
= 33.0 dB μ V/m

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 54 dB μ V/m (Average limit).

8.2 Discussion Pulse Desensitity

Pulse desensitity is not applicable for this device. The effective period (Teff) is approximately 625 μ s for a digital “1” bit which illustrated on technical specification, with a resolution bandwidth (3dB) of 100kHz, so the pulse desensitity factor is 0dB.

INTERTEK TESTING SERVICES

8.3 Calculation of Average Factor

Based on the Bluetooth Specification Version 2.0 / 2.1 + EDR, the transmitter ON time for each times lot of Bluetooth is 625 μ s. DH5 has the maximum duty cycle, which consists of 5 continuous Tx slots and 1 Rx slot. Therefore one hopset take $(5+1) \times 625\mu\text{s} = 3.75\text{ms}$. For one period for a pseudo-random hopping through all 79 RF channels, it takes: $79 \times 3.75\text{ms} = 296.25\text{ms}$.

The dwell time for DH5 is $5 \times 625\mu\text{s} = 3.125\text{ms}$

Therefore,

$$\begin{aligned}\text{Duty Cycle (DC)} &= \text{Maximum On time in 100ms/100ms} \\ &= 3.125\text{ms}/100\text{ms} \\ &= 0.03125\end{aligned}$$

$$\begin{aligned}\text{Average Factor (AF) of Bluetooth in dB} &= 20 \log_{10} (0.03125) \\ &= -30.1 \text{ dB}\end{aligned}$$

INTERTEK TESTING SERVICES

8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 2003. A typical or an unmodulated CW signal at the operating frequency of the EUT has been supplied to the EUT for all measurements. Such a signal is supplied by a signal generator and an antenna in close proximity to the EUT. The signal level is sufficient to stabilize the local oscillator of the EUT.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

INTERTEK TESTING SERVICES

8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.4 - 2003.

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.

9.0 Confidentiality Request

For electronic filing, a preliminary copy of the confidentiality request is saved with filename: request.pdf.

INTERTEK TESTING SERVICES

10.0 Equipment List

1) Radiated Emissions Test

Equipment	EMI Test Receiver	Biconical Antenna	Log Periodic Antenna
Registration No.	EW-2251	EW-0954	EW-0446
Manufacturer	R&S	EMCO	EMCO
Model No.	ESCI	3104C	3146
Calibration Date	Oct 22, 2009	Apr 14, 2010	Apr 26, 2010
Calibration Due Date	Apr 22, 2011	Oct 14, 2011	Oct 26, 2011

Equipment	Spectrum Analyzer	Double Ridged Guide Antenna
Registration No.	EW-2188	EW-1015
Manufacturer	AGILENTTECH	EMCO
Model No.	E4407B	3115
Calibration Date	Dec 27, 2010	Feb 09, 2010
Calibration Due Date	Dec 31, 2011	Aug 09, 2011

2) Bandedge Measurement

Equipment	Spectrum Analyzer
Registration No.	EW-2249
Manufacturer	R&S
Model No.	FSP30
Calibration Date	Oct 22, 2010
Calibration Due Date	Oct 22, 2011