

Report No.: AGC00529130604 FE03 Page 1 of 51

FCC Test Report

Report No.: AGC00529130604FE03

FCC ID : Y7WPLUMD100

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION: Pizazz Mobile Phone

BRAND NAME : plum

MODEL NAME : D100

CLIENT : CLC Hong Kong Limited

DATE OF ISSUE : July 08,2013

STANDARD(S) : FCC Part 15 Rules

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

Page 2 of 51

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	July 08,2013	Valid	Original Report

TABLE OF CONTENTS

1. VE	ERIFICATION OF CONFORMITY	5
2. G	ENERAL INFORMATION	6
2.	.1. PRODUCT DESCRIPTION	.6
	.2. TABLE OF CARRIER FREQUENCYS	
	.3. RECEIVER INPUT BANDWIDTH	
2.	.4. EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE	. 7
	.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR	
	.6. RELATED SUBMITTAL(S) / GRANT (S)	
2.	.7. TEST METHODOLOGY	.8
2.	.8. SPECIAL ACCESSORIES	.8
	.9. EQUIPMENT MODIFICATIONS	
	EASUREMENT UNCERTAINTY	
	ESCRIPTION OF TEST MODES	
	YSTEM TEST CONFIGURATION 1	
	.1. CONFIGURATION OF EUT SYSTEM	
	.2. EQUIPMENT USED IN EUT SYSTEM	
	.3. SUMMARY OF TEST RESULTS	
	EST FACILITY1	
	EAK OUTPUT POWER1	
	.1. MEASUREMENT PROCEDURE	
	.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
	.3. LIMITS AND MEASUREMENT RESULT	
	DDB BANDWIDTH1	
	.1. MEASUREMENT PROCEDURE	
	.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
	.3. LIMITS AND MEASUREMENT RESULTS	
	ONDUCTED SPURIOUS EMISSION 1	
	.1. MEASUREMENT PROCEDURE	
	.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
	.3. MEASUREMENT EQUIPMENT USED	
	.4. LIMITS AND MEASUREMENT RESULT	
	RADIATED EMISSION 2	
	0.1. MEASUREMENT PROCEDURE	
10	0.2. TEST SETUP	23

10.3. TEST RESULT	24
11. BAND EDGE EMISSION	28
11.1. MEASUREMENT PROCEDURE	28
11.2. TEST SET-UP	28
11.3. TEST RESULT	29
12. NUMBER OF HOPPING FREQUENCY	33
12.1. MEASUREMENT PROCEDURE	33
12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	33
12.3. MEASUREMENT EQUIPMENT USED	33
12.4. LIMITS AND MEASUREMENT RESULT	33
13. TIME OF OCCUPANCY (DWELL TIME)	34
13.1. MEASUREMENT PROCEDURE	34
13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	34
13.3. MEASUREMENT EQUIPMENT USED	34
13.4. LIMITS AND MEASUREMENT RESULT	34
14. FREQUENCY SEPARATION	37
14.1. MEASUREMENT PROCEDURE	37
14.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	37
14.3. MEASUREMENT EQUIPMENT USED	37
14.4. LIMITS AND MEASUREMENT RESULT	37
15. FCC LINE CONDUCTED EMISSION TEST	38
15.1. LIMITS OF LINE CONDUCTED EMISSION TEST	38
15.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	38
15.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	39
15.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	39
15.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	40
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	42
APPENDIX B: PHOTOGRAPHS OF EUT	43

Page 5 of 51

1. VERIFICATION OF CONFORMITY

Applicant	CLC Hong Kong Limited		
Address 2209, Concordia Plaza, North Tower, No.1 Science Museum Road, Tsui East, Kowloon, Hong Kong			
Manufacturer	CLC Technology Co., Ltd.		
Address Room 6G, Block C, NEO Building, Chegongmiao, Futian District, Shenz P.R.China			
Product Designation	Pizazz Mobile Phone		
Brand Name	plum		
Test Model	D100		
Date of test	June 27, 2013 to July 02, 2013		
Deviation	None		
Condition of Test Sample	Normal		
Report Template	AGCRT-US-BR/RF (2013-03-01)		

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.247.

Wall Huang July 08,2013

Checked By

Forrest Lei July 08,2013

Authorized By

Solger Zhang July 08,2013

Page 6 of 51

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

The EUT is "Pizazz Mobile Phone" designed as a "Communication Device". It is designed by way of utilizing the FHSS technology to achieve the system operation.

A major technical description of EUT is described as following

7			
Operation Frequency	2.402 GHz to 2.480GHz		
RF Output Power	3.88dBm(Max)		
Bluetooth Version	V 2.0		
Modulation	GFSK		
Number of channels	79		
Hardware Version	A300_KT12_V3.0		
Software Version	N/A		
Antenna Designation	Integrated Antenna		
Antenna Gain	0.8dBi		
Power Supply	DC3.7V by Battery		

2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency	
	0	2402MHZ	
	1	2403MHZ	
	÷	:	
	38	2440 MHZ	
2400~2483.5MHZ	39	2441 MHZ	
	40	2442 MHZ	
	••	:	
	77	2479 MHZ	
	78	2480 MHZ	

Page 7 of 51

2.3. RECEIVER INPUT BANDWIDTH

The input bandwidth of the receiver is 1.0MHZ,In every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally the type of connection(e.g. single of multislot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings.

Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

2.4. EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE

Example of a 79 hopping sequence in data mode: 40,21,44,23,42,53,46,55,48,33,52,35,50,65,54,67 56,37,60,39,58,69,62,71,64,25,68,27,66,57,70,59 72,29,76,31,74,61,78,63,01,41,05,43,03,73,07,75 09,45,13,47,11,77,15,00,64,49,66,53,68,02,70,06 01, 51, 03, 55, 05, 04

2.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR

The generation of the hopping sequence in connection mode depends essentially on two input values:

- 1. LAP/UAP of the master of the connection.
- 2. Internal master clock

The LAP(lower address part) are the 24 LSB's of the 48 BD_ADDRESS. The BD_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP(upper address part) are the 24MSB's of the 48BD ADDRESS

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For ehavior zation with other units only offset are used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about one day(23h30). In most case it is implemented as 28 bit counter. For the deriving of the hopping sequence the entire. LAP(24 bits), 4LSB's (4bits) (Input 1) and the 27MSB's of the clock (Input 2) are used. With this input values different mathematical procedures (permutations, additions, XOR-operations) are performed to generate te Sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following ehavior:

The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended. The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer(and it Cannot be shorter) than the minimum resolution of the clock(312.5us). The hopping sequence will always Differ from the first one.

Page 8 of 51

2.6. RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: Y7WPLUMD100** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.7. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.4 (2003). Radiated testing was performed at an antenna to EUT distance 3 meters.

2.8. SPECIAL ACCESSORIES

Refer to section 5.2.

2.9. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

Page 9 of 51

3. MEASUREMENT UNCERTAINTY

Conducted measurement: +/- 2.75dB Radiated measurement: +/- 3.2dB

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel TX
2	Middle channel TX
3	High channel TX
4	Normal Hopping

Note:

2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.


^{1.} All the test modes can be supply by battery and adapter, only the result of the worst case was recorded in the report, if no other cases.

Page 10 of 51

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configuration:



5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark		
1	Pizazz Mobile Phone	D100	FCC ID: Y7WPLUMD100	EUT		
2	Adapter	PMC03	DC5.0V /500mA	Accessory		
3	Battery	PMB31	DC3.7V/ 800 mAh	Accessory		
4	Earphone	D100	N/A	Accessory		
5	USB Cable	D100	N/A	Accessory		

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.247	Peak Output Power	Compliant
§15.247	20 dB Bandwidth	Compliant
§15.247	Spurious Emission	Compliant
§15.209	Radiated Emission	Compliant
§15.247	Band Edges	Compliant
§15.207	Conduction Emission	Compliant
§15.247	Number of Hopping Frequency	Compliant
§15.247	Time of Occupancy	Compliant
§15.247	Frequency Separation	Compliant

Page 11 of 51

6. TEST FACILITY

Site	Attestation of Global Compliance (Shenzhen) Co., Ltd		
Location	2/F., Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China		
Description	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2003.		

ALL TEST EQUIPMENT LIST

Description	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Power Probe	R&S	NRP-Z23	100323	07/18/2012	07/17/2013
RF attenuator	N/A	RFA20db	68	N/A	N/A
Spectrum Analyzer	Agilent	E4440A	US41421290	07/18/2012	07/17/2013
Amplifier	EM	EM30180	0607030	02/28/2013	02/27/2014
Horn Antenna	EM	EM-AH-10180	67	04/21/2013	04/20/2014
Horn Antenna	A.H. Systems Inc.	SAS-574		06/08/2013	06/07/2014
EMI Test Receiver	Rohde & Schwarz	ESCI	100694	07/18/2012	07/17/2013
Bilogical Antenna	A.H. Systems Inc.	SAS-521-4	26	06/08/2013	06/07/2014
Loop Antenna	Daze	ZN30900N	SEL0097	07/18/2012	07/17/2013
Isolation Transformer	LETEAC	LTBK		07/18/2012	07/17/2013

Page 12 of 51

7. PEAK OUTPUT POWER

7.1. MEASUREMENT PROCEDURE

For peak power test:

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 3. Set the EUT Work on the top, middle and the bottom operation frequency individually.
- 4. Set the RBW greater than 6DB bandwidth of emission.
- 5. Record the maximum power from the Spectrum Analyzer.


For average power test:

- 1. The EUT was placed on a table which is 0.8m above ground plane.
- 2. Connect EUT RF output port to power probe through an RF attenuator.
- 3. Connect the power probe to the PC.
- 4. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 5. Record the maximum power from the software.
- 6. The maximum peak power shall be less 1 Watt (30dBm).


Note: The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

PEAK POWER TEST SETUP



AVERAGE POWER SETUP



Page 13 of 51

7.3. LIMITS AND MEASUREMENT RESULT

PEAK OUTPUT POWER MEASUREMENT RESULT FOR GFSK MOUDULATION						
Frequency (GHz)	Dace or Fail					
2.402	1.87	3.83	30	Pass		
2.441	1.82	3.77	30	Pass		
2.480	1.93	3.88	30	Pass		


Page 14 of 51

8. 20DB BANDWIDTH

8.1. MEASUREMENT PROCEDURE

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 3, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 4. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ RBW; Sweep = auto; Detector function = peak
- 5. Set SPA Trace 1 Max hold, then View.

8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)



8.3. LIMITS AND MEASUREMENT RESULTS


BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESUL								
Amplicable Limite		Measurement Result						
Applicable Limits	Test Da	Criteria						
	Low Channel	0.742	PASS					
N/A	Middle Channel	0.731	PASS					
	High Channel	0.741	PASS					

Page 15 of 51

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



Report No.: AGC00529130604 FE03 Page 16 of 51

TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



Page 17 of 51

9. CONDUCTED SPURIOUS EMISSION

9.1. MEASUREMENT PROCEDURE

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 3. Set the EUT Work on the top, the Middle and the bottom operation frequency individually.
- 4. Set the Span = wide enough to capture the peak level of the in-band emission and all spurious emissions from the lowest frequency generated in the EUT up through the 10th harmonic.
 - RBW = 100 kHz; VBW ≥ RBW; Sweep = auto; Detector function = peak.
- 5. Set SPA Trace 1 Max hold, then View.

9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 8.2

9.3. MEASUREMENT EQUIPMENT USED


The same as described in section 6


9.4. LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT								
Angliaghla Limite	Measurement Result							
Applicable Limits	Test Data	Criteria						
In any 100 KHz Bandwidth Outside the	At least -20dBc than the limit							
frequency band in which the spread spectrum	Specified on the BOTTOM	PASS						
intentional radiator is operating, the radio frequency	Channel							
power that is produce by the intentional radiator								
shall be at least 20 dB below that in 100KHz								
bandwidth within the band that contains the highest								
level of the desired power.	At least -20dBc than the limit	DACC						
In addition, radiation emissions which fall in the	Specified on the TOP Channel	PASS						
restricted bands, as defined in §15.205(a), must also								
comply with the radiated emission limits specified								
in§15.209(a))								


Report No.: AGC00529130604 FE03 Page 18 of 51


TEST PLOT OF OUT OF BAND EMISSIONS WITH THE WORST CASE OF GFSK MODULATION IN LOW CHANNEL







TEST PLOT OF OUT OF BAND EMISSIONS OF GFSK MODULATION IN MIDDLE CHANNEL





TEST PLOT OF OUT OF BAND EMISSIONS OF GFSK MODULATION IN HIGH CHANNEL





Page 21 of 51

10. RADIATED EMISSION

10.1. MEASUREMENT PROCEDURE

- 1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

Report No.: AGC00529130604 FE03 Page 22 of 51

The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/1MHz for Peak, 1MHz/10Hz for Average

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP


Page 23 of 51

10.2. TEST SETUP


RADIATED EMISSION TEST SETUP BELOW 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz




Page 24 of 51

10.3. TEST RESULT

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ-Horizontal



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation Power: Humidity: 60 %

EUT: Pizazz Mobile Phone Distance: 3m

M/N: D100


Mode: Normal Hopping

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	•	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		81.7333	8.89	11.82	20.71	40.00	-19.29	peak			
2		207.8333	14.39	7.89	22.28	43.50	-21.22	peak			
3		311.3000	10.72	18.55	29.27	46.00	-16.73	peak			
4		416.3833	13.65	19.40	33.05	46.00	-12.95	peak			
5	*	623.3167	10.45	25.86	36.31	46.00	-9.69	peak			
6		843.1833	0.25	32.28	32.53	46.00	-13.47	peak			

Page 25 of 51

RADIATED EMISSION BELOW 1GHZ-Vertical



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation Power: Humidity: 60 %

EUT: Pizazz Mobile Phone Distance: 3m

M/N: D100


Mode: Normal Hopping

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	49.3998	28.58	4.82	33.40	40.00	-6.60	peak			
2		73.6500	22.57	5.48	28.05	40.00	-11.95	peak			
3		207.8333	19.42	7.32	26.74	43.50	-16.76	peak			
4		299.9832	6.41	17.70	24.11	46.00	-21.89	peak			
5		416.3833	6.57	20.76	27.33	46.00	-18.67	peak			
6		649.1833	10.74	25.65	36.39	46.00	-9.61	peak			

Page 26 of 51

RADIATED EMISSION ABOVE 1GHZ (1-10th Harmonics) –Horizontal



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Pizazz Mobile Phone Distance: 3m

M/N: D100


Mode: Normal Hopping

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
	•	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2106.667	41.75	-9.57	32.18	74.00	-41.82	peak			
2	Х	2402.000	83.71	-8.39	75.32	74.00	1.32	peak			
3	*	2480.000	83.89	-8.08	75.81	74.00	1.81	peak			
4		4420.000	38.42	-4.88	33.54	74.00	-40.46	peak			

Page 27 of 51

RADIATED EMISSION ABOVE 1GHZ (1-10th Harmonics) -Vertical



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Pizazz Mobile Phone Distance: 3m

M/N: D100

Mode: Normal Hopping

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1660.000	43.53	-10.33	33.20	74.00	-40.80	peak			
2	*	2402.000	83.71	-8.39	75.32	74.00	1.32	peak			
3	Х	2480.000	83.39	-8.08	75.31	74.00	1.31	peak			
4		2986.667	41.59	-8.73	32.86	74.00	-41.14	peak			

RESULT: PASS

Note: 5~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor+ Cable loss-Amplifier gain, Margin=Measurement-Limit.

Page 28 of 51

11. BAND EDGE EMISSION

11.1. MEASUREMENT PROCEDURE

- 1. Set the EUT Work on the top, the bottom operation frequency individually.
- 2. Set SPA Start or Stop Frequency = Operation Frequency, RBW>=1%span, VBW>=RBW
- 3. The band edges was measured and recorded.


11.2. TEST SET-UP

Radiated same as 10.2

Page 29 of 51

11.3. TEST RESULT

TEST PLOT OF BAND EDGE FOR LOW CHANNEL (1Mbps)-Horizontal



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Pizazz Mobile Phone Distance: 3m

M/N: D100


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	11 1 14 B	Comment
	-	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2390.000	36.68	-8.44	28.24	74.00	-45.76	peak			
2		2398.125	41.26	-8.41	32.85	74.00	-41.15	peak			
3	*	2402.071	82.71	-8.39	74.32	74.00	0.32	peak			

Page 30 of 51

TEST PLOT OF BAND EDGE FOR LOW CHANNEL (1Mbps)-Vertical



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Pizazz Mobile Phone Distance: 3m

M/N: D100


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	•	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2390.000	38.99	-8.44	30.55	74.00	-43.45	peak			
2		2395.167	38.76	-8.42	30.34	74.00	-43.66	peak			
3	*	2402.055	82.44	-8.39	74.05	74.00	0.05	peak			

Page 31 of 51

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL (1Mbps)-Horizontal



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Pizazz Mobile Phone Distance: 3m

M/N: D100


Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.096	82.33	-8.08	74.25	74.00	0.25	peak			
2		2483.500	36.24	-8.07	28.17	74.00	-45.83	peak			
3		2494.647	43.57	-8.02	35.55	74.00	-38.45	peak			

Page 32 of 51

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL (1Mbps)-Vertical



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Pizazz Mobile Phone Distance: 3m

M/N: D100

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	•	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.056	82.12	-8.08	74.04	74.00	0.04	peak			
2		2483.500	38.11	-8.07	30.04	74.00	-43.96	peak			
3		2490.430	41.16	-8.04	33.12	74.00	-40.88	peak			
4		2494.573	42.07	-8.02	34.05	74.00	-39.95	peak			

Page 33 of 51

12. NUMBER OF HOPPING FREQUENCY

12.1. MEASUREMENT PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer Start = 2.4GHz Stop = 2.4835GHz
- 4. Set the Spectrum Analyzer as RBW>=1%span, VBW>=RBW.

12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2


12.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6

12.4. LIMITS AND MEASUREMENT RESULT

TOTAL NO. OF HOPPING CHANNEL	LIMIT (NO. OF CH)	MEASUREMENT (NO. OF CH)	RESULT
	>=15	79	PASS

TEST PLOT FOR NO. OF TOTAL CHANNELS



Page 34 of 51

13. TIME OF OCCUPANCY (DWELL TIME)

13.1. MEASUREMENT PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode
- 2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer.
- 3. Set Span = zero span, centered on a hoping channel
- 4. Set the spectrum analyzer as RBW=1MHz, VBW>=RBW, Span = 0 Hz

13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2

13.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6

13.4. LIMITS AND MEASUREMENT RESULT


The Worst Case (3Mbps)

	\ 1 /				
Channel	Time of Pulse for DH5 (ms)	Period Time (s)	Sweep Time (ms)	Limit (ms)	
Low	2.912	31.6	310.61	400	
Middle	2.912	31.6	310.61	400	
High	2.912	31.6	310.61	400	


Low Channel Time 2.912*(1600/6)/79*31.6=310.61ms Middle Channel Time 2.912*(1600/6)/79*31.6=310.61ms High Channel Time 2.912*(1600/6)/79*31.6=310.61ms

Report No.: AGC00529130604 FE03 Page 35 of 51

TEST PLOT OF LOW CHANNEL




TEST PLOT OF MIDDLE CHANNEL



Page 36 of 51

TEST PLOT OF HIGH CHANNEL



Page 37 of 51

14. FREQUENCY SEPARATION

14.1. MEASUREMENT PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode
- 2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer
- Set Span = wide enough to capture the peaks of two adjacent channels Resolution (or IF) Bandwidth
 (RBW) ≥ 1% of the span Video (or Average) Bandwidth (VBW) ≥ RBW; Sweep = auto; Detector function =
 peak; Trace = max hold

14.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 6.2


14.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.3

14.4. LIMITS AND MEASUREMENT RESULT

CHANNEL	CHANNEL SEPARATION	LIMIT	RESULT			
	KHz	KHz	Door			
CH00-CH01	1000	>=25 KHz or 2/3 20 dB BW	Pass			

TEST PLOT FOR FREQUENCY SEPARATION (3Mbps)



Page 38 of 51

15. FCC LINE CONDUCTED EMISSION TEST


15.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Francisco	Maximum RF Line Voltage								
Frequency	Q.P.(dBuV)	Average(dBuV)							
150kHz~500kHz	66-56	56-46							
500kHz~5MHz	56	46							
5MHz~30MHz	60	50							

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

15.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



Page 39 of 51

15.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.

- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. All support equipments received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received power by adapter which received 120V/60Hzpower by a LISN..
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

15.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST


- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

Humidity: 60 %

Page 40 of 51

15.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

Line Conducted Emission Test Line 1-L



Site: Conduction

Limit: FCC Class B Conduction(QP)

EUT: Pizazz Mobile Phone

M/N: D100

Mode: Normal Hopping


Note:

No. Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment	
	Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	Q.	AVG			
1	0.1539	27.47		13.34	10.16	37.63		23.50	65.78	55.78	-28.15	-32.28	Р	
2	0.3498	33.57		10.78	10.31	43.88		21.09	58.97	48.97	-15.09	-27.88	Р	
3	1.3060	26.90		8.28	10.38	37.28		18.66	56.00	46.00	-18.72	-27.34	Р	
4	7.0739	27.12		-1.19	10.36	37.48		9.17	60.00	50.00	-22.52	-40.83	Р	
5	14.3178	23.51		19.37	10.12	33.63		29.49	60.00	50.00	-26.37	-20.51	Р	
6	18.0977	20.98		4.20	10.12	31.10		14.32	60.00	50.00	-28.90	-35.68	Р	

Power:

Page 41 of 51

Line Conducted Emission Test Line 2-N



Site: Conduction Phase: N Temperature: 26
Limit: FCC Class B Conduction(QP) Power: Humidity: 60 %

EUT: Pizazz Mobile Phone

M/N: D100

Mode: Normal Hopping

Note:

No. Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment	
	Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG			
1	0.3379	31.59		10.52	10.30	41.89		20.82	59.25	49.25	-17.36	-28.43	Р	
2	0.5340	31.17		10.10	10.37	41.54		20.47	56.00	46.00	-14.46	-25.53	Р	
3	1.3899	26.47		6.66	10.38	36.85		17.04	56.00	46.00	-19.15	-28.96	Р	
4	2.3380	21.30		2.99	10.36	31.66		13.35	56.00	46.00	-24.34	-32.65	Р	
5	14.3178	22.55		19.54	10.12	32.67		29.66	60.00	50.00	-27.33	-20.34	Р	
6	17.9378	21.64		10.93	10.12	31.76		21.05	60.00	50.00	-28.24	-28.95	Р	


Page 42 of 51

APPENDIX A: PHOTOGRAPHS OF TEST SETUP

FCC LINE CONDUCTED EMISSION TEST SETUP



FCC RADIATED EMISSION TEST SETUP



Page 43 of 51

APPENDIX B: PHOTOGRAPHS OF EUT

TOTAL VIEW OF EUT





Page 44 of 51





BOTTOM VIEW OF EUT




Report No.: AGC00529130604 FE03 Page 45 of 51

FRONT VIEW OF EUT



BACK VIEW OF EUT



Report No.: AGC00529130604 FE03 Page 46 of 51

LEFT VIEW OF EUT



RIGHT VIEW OF EUT



Report No.: AGC00529130604 FE03 Page 47 of 51

OPEN VIEW OF EUT-1



OPEN VIEW OF EUT-2




Report No.: AGC00529130604 FE03 Page 48 of 51

OPEN VIEW OF EUT-3




OPEN VIEW OF EUT-4




Report No.: AGC00529130604 FE03 Page 49 of 51

OPEN VIEW OF EUT-5




INTERNAL VIEW OF EUT-1




Report No.: AGC00529130604 FE03 Page 50 of 51

INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3




Report No.: AGC00529130604 FE03 Page 51 of 51

INTERNAL VIEW OF EUT-4



INTERNAL VIEW OF EUT-5



----END OF REPORT----