

IC: 9576A-SC14S
 Request for Single Modular Approval for DECT Module

**3.2.2 of RSS-Gen.
 Modular Approval Checklist;**

Modular approval requirement	YES	NO*
(a) The radio elements must have the radio frequency circuitry must be shielded. Physical/discrete and tuning capacitors may be located external to the shield, but must be on the module assembly		
(b) The module shall have buffered modulation/data input(s) (if such inputs are provided) to ensure that the module will comply with the requirements set out in the applicable RSS standard under conditions of excessive data rates or over-modulation.		
(c) The module shall have its own power supply regulation on the module. This is to ensure that the module will comply with the requirements set out in the applicable standard regardless of the design of the power supplying circuitry in the host device which houses the module.		
(d) The module shall comply with the provisions for external power amplifiers and antennas detailed in this standard. The equipment certification submission shall contain a detailed description of the configuration of all antennas that will be used with the module.		
(e) The module shall be tested for compliance with the applicable standard in a stand-alone configuration, i.e. the module must not be inside another device during testing.		
(f) The module shall comply with the Category I equipment labelling requirements.		
(g) The module shall comply with applicable RSS-102 exposure requirements, which are based on the intended use/configurations.		
(h) Is the modular device for an Industry Canada licensed exempt service?		

Signature


 Name: Frank van den Dungen
 Title: program manager DECT ULE
 Company Name: Dialog Semiconductor b.v.
 Date August 20th 2013