

Test report No. Page Issued date

: 10835051H-A-R1 : 1 of 29 : July 27, 2015

Revised date : September 17, 2015 FCC ID : Y8PFJ16-1

RADIO TEST REPORT

Test Report No.: 10835051H-A-R1

Applicant

: FUJI HEAVY INDUSTRIES LTD.

Type of Equipment

Keyless Access with Push-Button Start System

Model No.

: FJ16-1

FCC ID

Y8PFJ16-1

Test regulation

FCC Part 15 Subpart C: 2015

Test Result

Complied

- 1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
- 2. The results in this report apply only to the sample tested.
- 3. This sample tested is in compliance with above regulation.

:

- 4. The test results in this report are traceable to the national or international standards.
- 5. This test report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.
- 6. This test report covers Radio technical requirements. It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
- 7. This report is a revised version of 10835051H-A. 10835051H-A is replaced with this report.

Date of test:

June 18 to July 23, 2015

Representative test engineer:

Shinya Watanabe

Engineer Consumer Technology Division

Approved by:

Motoya Imura Engineer

Consumer Technology Division



This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation. *As for the range of Accreditation in NVLAP, you may refer to the WEB address,

http://japan.ul.com/resources/emc accredited/

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone Facsimile : +81 596 24 8999

: +81 596 24 8124

13-EM-F0429

Test report No. : 10835051H-A-R1
Page : 2 of 29
Issued date : July 27, 2015
Revised date : September 17, 2015
FCC ID : Y8PFJ16-1

REVISION HISTORY

Original Test Report No.: 10835051H-A

Revision	Test report No.	Date	Page revised	Contents
- (Original)	10835051H-A	July 27, 2015	-	-
1	10835051H-A-R1	September 17, 2015	P.5	Update to FCC version
1	10835051H-A-R1	September 17, 2015	P.5	Correction of FCC Part 15.31 (e)
1	10835051H-A-R1	September 17, 2015	P.9	Correction of notes for antenna ports
1	10835051H-A-R1	September 17, 2015	P.13	Correction of description in Section 6 and 7

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Test report No. Page **Issued date**

: 10835051H-A-R1 : 3 of 29 : July 27, 2015 : September 17, 2015 : Y8PFJ16-1

Revised date FCC ID

CONTENTS	PAGE
SECTION 1: Customer information	4
SECTION 2: Equipment under test (E.U.T.)	
SECTION 3: Test specification, procedures & results	
SECTION 4: Operation of E.U.T. during testing	9
SECTION 5: Radiated emission (Fundamental and Spurious Emission)	11
SECTION 6: -26dB Bandwidth	13
SECTION 7: 99% Occupied Bandwidth	13
APPENDIX 1: Data of EMI test	14
Radiated Emission below 30MHz (Fundamental and Spurious Emission)	14
Duty Cycle	17
Radiated Emission above 30MHz (Spurious Emission)	18
-26dB Bandwidth and 99% Occupied Bandwidth	21
APPENDIX 2: Test instruments	24
APPENDIX 3: Photographs of test setup	25
Radiated Emission	
Worst Casa Pacition	28

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN Telephone : +81 596 24 8999 Facsimile : +81 596 24 8124

Test report No. : 10835051H-A-R1
Page : 4 of 29
Issued date : July 27, 2015
Revised date : September 17, 2015
FCC ID : Y8PFJ16-1

SECTION 1: Customer information

Company Name : FUJI HEAVY INDUSTRIES LTD.

Address : 1-1, Subaru-cho, ota-shi, Gunma-ken, 373-8555, Japan

Telephone Number : +81-276-26-3064 Facsimile Number : +81-276-26-3069 Contact Person : Yuji Kobayashi

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment : Keyless Access with Push-Button Start System

Model No. : FJ16-1

Serial No. : Refer to Section 4, Clause 4.2

Rating : DC12.0 V Receipt Date of Sample : June 11, 2015

Country of Mass-production : United States of America and Japan

Condition of EUT : Production prototype

(Not for Sale: This sample is equivalent to mass-produced items.)

Modification of EUT : No Modification by the test lab

2.2 Product description

Model No: FJ16-1 (referred to as the EUT in this report) is the Smart system.

General Specification

Clock frequencies in the system : 4.000 MHz (CPU)

Radio Specification

[Transmitter]

Radio Type : Transmitter
Frequency of Operation : 134.2 kHz
Oscillator Frequency : 4.2944 MHz
Type of Modulation : OOK (A1D)
Oscillation circuit : Crystal
Power Supply : DC 12.0 V

Antenna : Antenna (TYPE 1) (*1) (*3) / (TYPE 2) (*2)

*1: Maximum number of this antenna is 2. *2: Maximum number of this antenna is 4.

Antenna Specification : Ferrite antenna coil

[Receiver] *4)

Radio Type : Receiver Frequency of Operation : 433.92 MHz

Oscillator frequency : 52.9025 MHz (Crystal)

Type of Modulation : FSK

Type of receiving system : Super-heterodyne

Power Supply : DC 5.0 V

Antenna Type : Internal antenna (Inverted F antenna)

The difference of these variations is only the outer shell, and the test was performed with the representative model 1.

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

^{*3)} The Antenna (TYPE 1) of this system has variations of model 1 and model 2.

^{*4)} The test of receiver part was performed separately from this test report, and the conformability is confirmed.

Test report No. : 10835051H-A-R1
Page : 5 of 29
Issued date : July 27, 2015
Revised date : September 17, 2015
FCC ID : Y8PFJ16-1

SECTION 3: Test specification, procedures & results

3.1 Test Specification

Test Specification : FCC Part 15 Subpart C: 2015, final revised on September 8, 2015

Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators

Section 15.207 Conducted Emission

Section 15.209 Radiated emission limits, general requirements

FCC Part 15.31 (e)

The test was performed with the New Battery (DC 12.0 V) and the EUT constantly provides the stable voltage to RF part through the regulator regardless of input voltage from New Battery. Therefore, this EUT complies with the requirement.

FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the vehicle. Therefore, the equipment complies with the antenna requirement of Section 15.203.

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

^{*} The revision on September 8, 2015 does not affect the test specification applied to the EUT.

Test report No. : 10835051H-A-R1
Page : 6 of 29
Issued date : July 27, 2015
Revised date : September 17, 2015
FCC ID : Y8PFJ16-1

3.2 Procedures and results

No.	Item	Test Procedure	Specification	Remarks	Deviation	Worst margin	Results
1	Conducted Emission	<fcc> ANSI C63.4:2009 7. AC powerline conducted emission measurements <ic> RSS-Gen 8.8</ic></fcc>	<fcc> Section 15.207 <ic> RSS-Gen 8.8</ic></fcc>	-	N/A *1)	N/A	N/A
2	Electric Field Strength of Fundamental Emission	<fcc> ANSI C63.4:2009 13. Measurement of intentional radiators <ic> RSS-Gen 6.4, 6.12</ic></fcc>	<fcc> Section 15.209 <ic> RSS-210 2.5.1 RSS-Gen 8.9</ic></fcc>	Radiated	N/A	6.1 dB 0.13420 kHz PK (PK with Duty factor) (Antenna Type 2 OUTSIDE)	Complied
3	Electric Field Strength of Spurious Emission	<fcc> ANSI C63.4:2009 13. Measurement of intentional radiators <ic> RSS-Gen 6.4, 6.13</ic></fcc>	<fcc> Section 15.209 <ic> RSS-210 2.5.1 RSS-Gen 8.9</ic></fcc>	Radiated	N/A	11.8 dB 35.952 MHz, Vertical, QP (Antenna Type 2 OUTSIDE)	Complied
4	-26dB Bandwidth	<fcc> ANSI C63.4:2009 13. Measurement of intentional radiators <ic> -</ic></fcc>	<fcc> Reference data <ic> -</ic></fcc>	Radiated	N/A	N/A	N/A

Note: UL Japan, Inc.'s EMI Work Procedures No. 13-EM-W0420 and 13-EM-W0422.

*1) The test is not applicable since the EUT is not the device that is designed to be connected to the public utility (AC) power line.

3.3 Addition to standard

No	. Item	Test Procedure	Specification	Remarks	Deviation	Worst margin	Results
1	99 % Occupied	RSS-Gen 6.6	-	Radiated	N/A	N/A	N/A
	Band Width						

Other than above, no addition, exclusion nor deviation has been made from the standard.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Test report No. : 10835051H-A-R1

 Page
 : 7 of 29

 Issued date
 : July 27, 2015

 Revised date
 : September 17, 2015

 FCC ID
 : Y8PFJ16-1

3.4 Uncertainty

EMI

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor k = 2.

Test room	Radiated emission							
(semi-		(3 m*)	(<u>+</u> dB)		(1 m [*]	*)(<u>+</u> dB)	$(0.5 \text{ m}^*)(\underline{+}dB)$	
anechoic chamber)	9 kHz	30 MHz	300 MHz	1 GHz	10 GHz	18 GHz	26.5 GHz	
	- 30 MHz	- 300 MHz	- 1 GHz	- 10 GHz	- 18 GHz	- 26.5 GHz	- 40 GHz	
No.1	4.3 dB	5.5 dB	6.3 dB	5.5 dB	5.8 dB	5.8 dB	4.3 dB	
No.2	4.2 dB	5.4 dB	6.3 dB	5.4 dB	5.7 dB	5.9 dB	5.6 dB	
No.3	4.4 dB	5.4 dB	6.4 dB	5.2 dB	5.5 dB	5.8 dB	5.5 dB	
No.4	4.7 dB	5.6 dB	6.4 dB	5.3 dB	5.7 dB	5.9 dB	5.5 dB	

^{*3} m / 1 m / 0.5 m = Measurement distance

Radiated emission test(3 m)

The data listed in this test report has enough margin, more than the site margin.

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Test report No. : 10835051H-A-R1
Page : 8 of 29
Issued date : July 27, 2015
Revised date : September 17, 2015
FCC ID : Y8PFJ16-1

3.5 Test Location

UL Japan, Inc. Ise EMC Lab. *NVLAP Lab. code: 200572-0 4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8999 Facsimile: +81 596 24 8124

	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms
No.1 semi-anechoic chamber	2973C-1	19.2 x 11.2 x 7.7m	7.0 x 6.0m	No.1 Power source room
No.2 semi-anechoic chamber	2973C-2	7.5 x 5.8 x 5.2m	4.0 x 4.0m	-
No.3 semi-anechoic chamber	2973C-3	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.3 Preparation room
No.3 shielded room	-	4.0 x 6.0 x 2.7m	N/A	-
No.4 semi-anechoic chamber	2973C-4	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.4 Preparation room
No.4 shielded room	-	4.0 x 6.0 x 2.7m	N/A	-
No.5 semi-anechoic chamber	-	6.0 x 6.0 x 3.9m	6.0 x 6.0m	-
No.6 shielded room	-	4.0 x 4.5 x 2.7m	4.0 x 4.5 m	-
No.6 measurement room	-	4.75 x 5.4 x 3.0m	4.75 x 4.15 m	-
No.7 shielded room	-	4.7 x 7.5 x 2.7m	4.7 x 7.5m	-
No.8 measurement room	-	3.1 x 5.0 x 2.7m	N/A	-
No.9 measurement room	-	8.0 x 4.6 x 2.8m	2.4 x 2.4m	-
No.11 measurement room	-	6.2 x 4.7 x 3.0m	4.8 x 4.6m	-

^{*} Size of vertical conducting plane (for Conducted Emission test): 2.0 x 2.0m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

3.6 Test data, Test instruments, and Test set up

Refer to APPENDIX.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Test report No. : 10835051H-A-R1
Page : 9 of 29
Issued date : July 27, 2015
Revised date : September 17, 2015
FCC ID : Y8PFJ16-1


SECTION 4: Operation of E.U.T. during testing

4.1 Operating Modes

The mode is used: Transmitting mode (Tx) 134.2kHz

Justification : The system was configured in typical fashion (as a customer would normally use it) for testing.

4.2 Configuration and peripherals



^{*} Cabling and setup were taken into consideration and test data was taken under worse case conditions.

- *This system has three kinds of antenna ports.
- Two ports where Antenna (TYPE 1) are connected
- Three ports where Antenna (TYPE 2) are connected (TYPE 2, INSIDE)
- One port where Antenna (TYPE 2) is connected (TYPE 2, OUTSIDE)
- The difference between INSIDE Antenna and OUTSIDE Antenna is output power only.

The test was performed with each representative one of above three kinds of antenna ports.

* Antenna (Type 1) and Antenna (Type 2) were evaluated with the worst duty respectively. Worst duty does not change due to the difference in number of connected antenna.

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

^{*}During testing, transmitting antenna was fixed to one of six antennas.

 Test report No.
 : 10835051H-A-R1

 Page
 : 10 of 29

 Issued date
 : July 27, 2015

 Revised date
 : September 17, 2015

 FCC ID
 : Y8PFJ16-1

Description of EUT and Support equipment

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	Smart ECU	-	001	-	EUT
В	Antenna (TYPE 1)	-	001	-	EUT
C	Antenna (TYPE 1)	-	001	-	EUT
D	Antenna (TYPE 2 INSIDE)	-	001	-	EUT
Е	Antenna (TYPE 2 INSIDE)	-	001	-	EUT
F	Antenna (TYPE 2 INSIDE)	-	001	-	EUT
G	Antenna (TYPE 2 OUTSIDE)	-	001	-	EUT
Н	Jig	_	-	-	-

List of cables used

No.	Name	Length (m)	Shie	eld	Remarks
			Cable	Connector	
1	Antenna (TYPE 1) Cable	3.0	Unshielded	Unshielded	-
2	Antenna (TYPE 1) Cable	3.0	Unshielded	Unshielded	-
3	Antenna (TYPE 2 INSIDE) Cable	3.0	Unshielded	Unshielded	-
4	Antenna (TYPE 2 INSIDE) Cable	3.0	Unshielded	Unshielded	-
5	Antenna (TYPE 2 INSIDE) Cable	3.0	Unshielded	Unshielded	-
6	Antenna (TYPE 2 OUTSIDE) Cable	3.0	Unshielded	Unshielded	-
7	Signal Cable	3.0	Unshielded	Unshielded	-
8	DC Cable	3.0	Unshielded	Unshielded	-
9	DC Cable	3.0	Unshielded	Unshielded	-

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Test report No. : 10835051H-A-R1
Page : 11 of 29
Issued date : July 27, 2015
Revised date : September 17, 2015
FCC ID : Y8PFJ16-1

SECTION 5: Radiated emission (Fundamental and Spurious Emission)

Test Procedure

EUT was placed on a urethane platform of nominal size, 0.5 m by 1.0 m, raised 0.8m above the conducting ground plane.

The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

Frequency: From 9 kHz to 30 MHz

The EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for vertical polarization (antenna angle: 0 deg., 45 deg., 90 deg., 135 deg., and 180 deg.) and horizontal polarization.

*Refer to Figure 1 about Direction of the Loop Antenna.

Frequency: From 30 MHz to 1 GHz

The measuring antenna height varied between 1 and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization.

The test was made with the detector (RBW / VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

Test Antennas are used as below;

Frequency	Below 30 MHz	30 MHz to 300 MHz	300 MHz to 1 GHz
Antenna Type	Loop	Biconical	Logperiodic

Frequency	From 9 kHz to 90 kHz and From 110 kHz to 150 kHz	From 90 kHz to 110 kHz	From 150 kHz to 490 kHz	From 490 kHz to 30 MHz	From 30 MHz to 1 GHz
Instrument used			Test Receiver		
Detector	PK / AV	QP	PK / AV	QP	QP
IF Bandwidth	200 Hz	200 Hz	9 kHz	9 kHz	120 kHz
Test Distance	3 m *1)	3 m *1)	3 m *1)	3 m *2)	3 m

^{*1)} Distance Factor: $40 \times \log (3 \text{ m} / 300 \text{ m}) = -80 \text{ dB}$

Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open field test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 937606.

These tests were performed in semi anechoic chamber. Therefore the measured level of emissions may be higher than if measurements were made without a ground plane.

However test results were confirmed to pass against standard limit.

- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Measurement range : 9 kHz - 1 GHz Test data : APPENDIX 1

Test result : Pass

Date: June 18 and 20, 2015 Test engineer: Kenshi Shimomura

July 23, 2015 Yuta Moriya

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

^{*2)} Distance Factor: $40 \times \log (3 \text{ m} / 30 \text{ m}) = -40 \text{ dB}$

Test report No. : 10835051H-A-R1
Page : 12 of 29
Issued date : July 27, 2015
Revised date : September 17, 2015
FCC ID : Y8PFJ16-1

Figure 1: Direction of the Loop Antenna


Side View (Vertical)

EUT

The state of the

.....


Top View (Horizontal)



Antenna was not rotated.

.....

Top View (Vertical)



Front side: 0 deg.

Forward direction: clockwise

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Test report No. : 10835051H-A-R1
Page : 13 of 29
Issued date : July 27, 2015
Revised date : September 17, 2015
FCC ID : Y8PFJ16-1

SECTION 6: -26dB Bandwidth

Test Procedure

The test was measured with a spectrum analyzer using a test fixture.

Test	Span	RBW	VBW	Sweep	Detector	Trace	Instrument used
-26 dB Bandwidth	100 kHz	1 kHz	3 kHz	Auto	Peak	Max Hold	Spectrum Analyzer

Test data : APPENDIX 1

Test result : Pass

SECTION 7: 99% Occupied Bandwidth

Test Procedure

The test was measured with a spectrum analyzer using a test fixture.

Test	Span	RBW	VBW	Sweep	Detector	Trace	Instrument used
99 % Occupied Bandwidth	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak *1)	Max Hold *1)	Spectrum Analyzer
/	nent was performed with Pe	,	x Hold since th	e duty cycle was not	100 %.		

Test data : APPENDIX 1

Test result : Pass

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Test report No. : 10835051H-A-R1
Page : 14 of 29
Issued date : July 27, 2015
Revised date : September 17, 2015
FCC ID : Y8PFJ16-1

APPENDIX 1: Data of EMI test

Radiated Emission below 30MHz (Fundamental and Spurious Emission)

Antenna (TYPE 1)

Test place Ise EMC Lab. No.2 Semi Anechoic Chamber

Order No. 10835051H
Date 06/18/2015
Temperature/ Humidity 25 deg. C / 40% RH
Engineer Kenshi Shimomura

Mode Tx 134.2kHz, Antenna (TYPE 1)

PK or OP

I K UI QI											
Ant Deg [deg]	Frequency	Detector	Reading	Ant	Loss	Gain	Duty	Result	Limit	Margin	Remark
or				Factor			Factor				
Polarity [Hori/Vert]	[MHz]		[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
0	0.13420	PK	69.4	19.6	-74.0	0.0	-	15.0	45.0	30.0	Fundamental
0	0.26840	PK	61.4	19.6	-74.0	32.1	-	-25.1	39.0	64.1	
0	0.40260	PK	76.1	19.6	-73.9	32.1	-	-10.3	35.5	45.8	
0	0.53680	QP	42.0	19.5	-33.9	32.1	-	-4.5	33.0	37.5	
0	0.67100	QP	63.8	19.5	-33.8	32.1	-	17.4	31.1	13.7	
0	0.80520	QP	40.3	19.5	-33.8	32.1	-	-6.1	29.5	35.6	
0	0.93940	QP	53.4	19.5	-33.8	32.1	-	7.0	28.1	21.1	
0	1.07360	QP	39.9	19.5	-33.8	32.1	-	-6.5	26.9	33.4	
0	1.20780	QP	45.9	19.5	-33.8	32.1	-	-0.5	25.9	26.4	
0	1.34200	QP	39.9	19.5	-33.7	32.1	-	-6.4	25.0	31.4	
0	1.47620	QP	43.6	19.6	-33.7	32.1	-	-2.6	24.2	26.8	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter) - Gain(Amprifier)

PK with Duty factor

Γ	Ant Deg [deg]	Frequency	Detector	Reading	Ant	Loss	Gain	Duty	Result	Limit	Margin	Remark
					Factor			Factor				
L		[MHz]		[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
Г	0	0.13420	PK	69.4	19.6	-74.0	0.0	0.0	15.0	25.0	10.0	Fundamental
Г	0	0.26840	PK	61.4	19.6	-74.0	32.1	0.0	-25.1	19.0	44.1	
	0	0.40260	PK	76.1	19.6	-73.9	32.1	0.0	-10.3	15.5	25.8	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter) - Gain(Amprifier) + Duty factor *

Result of the fundamental emission at 3m without Distance factor

PK or QP

- 1	•											
	Ant Deg [deg]	Frequency	Detector	Reading	Ant	Loss	Gain	Duty	Result	Limit	Margin	Remark
					Factor			Factor				
		[MHz]		[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
	0	0.13420	PK	69.4	19.6	6.0	0.0	-	95.0	-	-	Fundamental

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter) - Gain(Amprifier)

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

^{*} Gain 0.0 dB shows that the pre amplifier was not used to avoid the influence of carrier power.

^{*} Since the peak emission result satisfied the average limit, duty factor was omitted.

^{*} All spurious emissions lower than this result.

^{*}The test result is rounded off to one or two decimal

Test report No. : 10835051H-A-R1
Page : 15 of 29
Issued date : July 27, 2015
Revised date : September 17, 2015
FCC ID : Y8PFJ16-1

Radiated Emission below 30MHz (Fundamental and Spurious Emission)

Antenna (TYPE 2 INSIDE)

Test place Ise EMC Lab. No.2 Semi Anechoic Chamber

Order No. 10835051H
Date 06/18/2015
Temperature/ Humidity 25 deg. C / 40% RH
Engineer Kenshi Shimomura

Mode Tx 134.2kHz, Antenna (TYPE 2 INSIDE)

PK or QP

I K UI QI											
Ant Deg [deg]	Frequency	Detector	Reading	Ant	Loss	Gain	Duty	Result	Limit	Margin	Remark
or				Factor			Factor				
Polarity [Hori/Vert]	[MHz]		[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
0	0.13420	PK	55.5	19.6	-74.0	0.0	-	1.1	45.0	43.9	Fundamental
0	0.26840	PK	66.3	19.6	-74.0	32.1	-	-20.2	39.0	59.2	
0	0.40260	PK	57.2	19.6	-73.9	32.1	-	-29.2	35.5	64.7	
0	0.53680	QP	43.5	19.5	-33.9	32.1	-	-3.0	33.0	36.0	
0	0.67100	QP	41.3	19.5	-33.8	32.1		-5.1	31.1	36.2	
0	0.80520	QP	41.5	19.5	-33.8	32.1	-	-4.9	29.5	34.4	
0	0.93940	QP	40.1	19.5	-33.8	32.1	-	-6.3	28.1	34.4	
0	1.07360	QP	40.4	19.5	-33.8	32.1		-6.0	26.9	32.9	
0	1.20780	QP	40.0	19.5	-33.8	32.1		-6.4	25.9	32.3	
0	1.34200	QP	40.0	19.5	-33.7	32.1	-	-6.3	25.0	31.3	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter) - Gain(Amprifier)

PK with Duty factor

Γ	Ant Deg [deg]	Frequency	Detector	Reading	Ant	Loss	Gain	Duty	Result	Limit	Margin	Remark
ı					Factor			Factor				
L		[MHz]		[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
	0	0.13420	PK	55.5	19.6	-74.0	0.0	0.0	1.1	25.0	23.9	Fundamental
L	0	0.26840	PK	66.3	19.6	-74.0	32.1	0.0	-20.2	19.0	39.2	
	0	0.40260	PK	57.2	19.6	-73.9	32.1	0.0	-29.2	15.5	44.7	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter) - Gain(Amprifier) + Duty factor *

Result of the fundamental emission at 3m without Distance factor

PK or QP

Ant Deg [deg]	Frequency	Detector	Reading	Ant	Loss	Gain	Duty	Result	Limit	Margin	Remark
				Factor			Factor				
	[MHz]		[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
0	0.13420	PK	55.5	19.6	6.0	0.0	-	81.1			Fundamental

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter) - Gain(Amprifier)

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

^{*} Gain 0.0 dB shows that the pre amplifier was not used to avoid the influence of carrier power.

^{*} Since the peak emission result satisfied the average limit, duty factor was omitted.

^{*} All spurious emissions lower than this result.

^{*}The test result is rounded off to one or two decimal

Test report No. : 10835051H-A-R1
Page : 16 of 29
Issued date : July 27, 2015
Revised date : September 17, 2015
FCC ID : Y8PFJ16-1

Radiated Emission below 30MHz (Fundamental and Spurious Emission)

Antenna (TYPE 2 OUTSIDE)

Test place Ise EMC Lab. No.1 Semi Anechoic Chamber

Order No. 10835051H

Date 07/23/2015

Temperature/ Humidity 22 deg. C / 60% RH

Engineer Yuta Moriya Mode Tx 134.2kHz, Antenna (TYPE 2 OUTSIDE)

PK or QF

I K 01 Q1											
Ant Deg [deg]	Frequency	Detector	Reading	Ant	Loss	Gain	Duty	Result	Limit	Margin	Remark
or				Factor			Factor				
Polarity [Hori/Vert]	[MHz]		[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
0	0.13420	PK	79.6	19.6	-74.0	0.0	-	25.2	45.0	19.8	Fundamental
0	0.26840	PK	76.4	19.6	-73.9	32.4	-	-10.3	39.0	49.3	
0	0.40260	PK	61.4	19.6	-73.9	32.3	-	-25.2	35.5	60.7	
0	0.53680	QP	39.9	19.5	-33.9	32.3	-	-6.8	33.0	39.8	
0	0.67100	QP	53.9	19.5	-33.8	32.3	-	7.3	31.1	23.8	
0	0.80520	QP	31.9	19.5	-33.8	32.3	-	-14.7	29.5	44.2	
0	0.93940	QP	51.1	19.5	-33.8	32.3	-	4.5	28.1	23.6	
0	1.07360	QP	40.6	19.5	-33.8	32.3	-	-6.0	26.9	32.9	
0	1.20780	QP	48.3	19.5	-33.7	32.3	-	1.8	25.9	24.1	
0	1.34200	QP	30.7	19.5	-33.7	32.3	-	-15.8	25.0	40.8	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter) - Gain(Amprifier)

PK with Duty factor

Ant Deg [deg]	Frequency	Detector	Reading	Ant	Loss	Gain	Duty	Result	Limit	Margin	Remark
				Factor			Factor				
	[MHz]		[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
(0.13420	PK	79.6	19.6	-74.0	0.0	-6.3	18.9	25.0	6.1	Fundamental
	0.26840	PK	76.4	19.6	-73.9	32.4	-6.3	-16.6	19.0	35.6	
	0.20010	1 12	70.1	17.0	15.7	52.1	0.5	10.0	17.0	35.0	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter) - Gain(Amprifier) + Duty factor (Refer to Duty factor data sheet)

Result of the fundamental emission at 3m without Distance factor

PK or QP

Ant Deg [deg]	Frequency	Detector	Reading	Ant	Loss	Gain	Duty	Result	Limit	Margin	Remark
				Factor			Factor				
	[MHz]		[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
0	0.13420	PK	79.6	19.6	6.0	0.0	-	105.2	-	-	Fundamental

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter) - Gain(Amprifier)

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

^{*} Gain 0.0 dB shows that the pre amplifier was not used to avoid the influence of carrier power.

^{*} All spurious emissions lower than this result.

^{*}The test result is rounded off to one or two decimal

Test report No. : 10835051H-A-R1
Page : 17 of 29
Issued date : July 27, 2015
Revised date : September 17, 2015
FCC ID : Y8PFJ16-1

△ Mkr2 5.931 ms

108.03 %

Span 0 Hz

Sweep 32.8 ms (1201 pts)

Amplitude 416.52 μU 96.66 % 396.63 μU 108.03 %

<u>Duty Cycle</u> Antenna (TYPE 2, OUTSIDE)


Test place Ise EMC Lab. No.1 Semi Anechoic Chamber

Order No. 10835051H
Date 07/23/2015
Temperature/ Humidity 22 deg. C / 60% RH
Engineer Yuta Moriya

Mode Tx 134.2kHz, Antenna (TYPE 2, OUTSIDE)

ON time	Cycle	Duty	Duty
[ms]	[ms]	(On time/Cycle)	[dB]
48.25	100.00	0.48	-6.3

ON time[ms]=40.75+(0.575*2)+(0.8*2)+(0.275*10)+(0.5*4) =48.25 Duty[dB]=20log(On time/Cycle)



UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

: 10835051H-A-R1 Test report No. Page : 18 of 29 **Issued date** : July 27, 2015 Revised date : September 17, 2015 : Y8PFJ16-1 FCC ID

Radiated Emission above 30MHz (Spurious Emission)

Antenna (TYPE 1)


DATA OF RADIATED EMISSION TEST

Ise EMC Lab. No.1 Semi Anechoic Chamber Date: 2015/06/20

Report No. : 10835051H

Temp./Humi. Engineer : 20deg.C / 60% RH : Kenshi Shimomura

Mode / Remarks : Tx 134.2kHz, Antenna (Type 1) (Ant X, ECU X)



Frequency	Reading	DET	Antenna Factor	Loss& Gain	Level	Angle	Height	Polar.	Limit	Margin	Comment
[MHz]	[dBuV]	DEI	[dB/m]	[dB]	[dBuV/m]	[Deg]	[cm]	Total.	[dBuV/m]	[dB]	OOMMOTTE
52. 612	47. 6	QP	9. 7	-31.1	26. 2	163		Vert.	40.0	13. 8	
52. 605	33. 9	QP	9. 7	-31.1	12. 5	66	290	Hori.	40.0	27. 5	
57. 161	32. 1	QP	8. 2	-31.0	9. 3	359	338	Hori.	40.0	30. 7	
83. 744	42. 4	QP	7.4	-30.6	19. 2	105	100	Vert.	40.0	20.8	
122. 395	32. 2	QP	12. 8	-30. 1	14. 9	149	246	Hori.	43. 5	28. 6	
133. 122	31.9	QP	13. 7	-29.9	15. 7	359	249	Hori.	43. 5	27. 8	
133. 126	35. 2	QP	13. 7	-29.9	19. 0	265	100	Vert.	43. 5	24. 5	
171. 778	35. 0	QP	15. 7	-29.6	21. 1	0	100	Vert.	43. 5	22. 4	
405. 000	27. 9	QP	17. 5	-27. 4	18. 0	359	100	Vert.	46. 0	28. 0	
405. 000	27. 9	QP	17. 5	-27. 4	18. 0	359	100	Hori.	46. 0	28. 0	
610.000	26. 6	QP	19. 6	-25. 6	20. 6	359	100	Vert.	46. 0	25. 4	
610.000	27. 7	QP	19. 6	-25. 6	21. 7	359	100	Hori.	46. 0	24. 3	
965. 000	27. 3	QP	22. 7	-23. 1	26. 9	359	100	Hori.	53. 9	27. 0	
965. 000	27. 2	QP	22. 7	-23. 1	26. 8	359	100	Vert.	53. 9	27. 1	

CHART:WITH FACTOR ANT TYPE: -30MHz:LOOP, 30-300MHz:BICONICAL, 300MHz-1000MHz:LOGPERIODIC, 1000MHz-:HORN CALCULATION:RESULT = READING + ANT FACTOR + LOSS(CABLE - GAIN(AMP))

*The test result is rounded off to one or two decimal places, so some differences might be observed.

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

: +81 596 24 8999 Telephone Facsimile : +81 596 24 8124

: 10835051H-A-R1 Test report No. Page : 19 of 29 **Issued date** : July 27, 2015 Revised date : September 17, 2015 : Y8PFJ16-1 FCC ID

Radiated Emission above 30MHz (Spurious Emission)

Antenna (TYPE 2 INSIDE)


DATA OF RADIATED EMISSION TEST

Ise EMC Lab. No.1 Semi Anechoic Chamber Date: 2015/06/20

Report No. : 10835051H

Temp./Humi. Engineer : 20deg.C / 60% RH : Kenshi Shimomura

 $\label{eq:mode_mode_for_mode} \mbox{Mode / Remarks : Tx 134.2kHz, Antenna (TYPE 2 INSIDE) (ANT Y, ECU: X)}$



Frequency	Reading	DET	Antenna Factor	Loss& Gain	Level	Angle	Height	Polar.	Limit	Margin	Comment
[MHz]	[dBuV]	521	[dB/m]	[dB]	[dBuV/m]	[Deg]	[cm]	. o.u	[dBuV/m]	[dB]	00111110110
55. 829	40. 4	QP	8.6	-31.0	18. 0	163	100	Vert.	40. 0	22. 0	
55. 829	31.9	QP	8. 6	-31.0	9. 5	216	343	Hori.	40. 0	30. 5	
85. 884	37. 7	QP	7. 7	-30.6	14. 8	344	340	Hori.	40. 0	25. 2	
81. 592	40. 2	QP	7.0	-30.6	16. 6	135	100	Vert.	40. 0	23. 4	
120. 239	32. 2	QP	12. 6	-30. 1	14. 7	153	272	Hori.	43. 5	28. 8	
161. 738	29. 0	QP	15. 5	-29.6	14. 9	359	249	Hori.	43. 5	28. 6	
91. 613	38. 7	QP	8.6	-30.5	16.8	78	100	Vert.	43. 5	26. 7	
176. 074	32. 9	QP	15. 9	-29.6	19. 2	336	100	Vert.	43. 5	24. 3	
405. 000	27. 8	QP	17. 5	-27. 4	17. 9	359	100	Vert.	46. 0	28. 1	
405. 000	27. 8	QP	17. 5	-27. 4	17. 9	359	100	Hori.	46. 0	28. 1	
610.000	26. 6	QP	19. 6	-25. 6	20. 6	359	100	Vert.	46. 0	25. 4	
610.000	27. 7	QP	19. 6	-25. 6	21. 7	359	100	Hori.	46. 0	24. 3	
965. 000	27. 4	QP	22. 7	-23. 1	27. 0	359	100	Hori.	53. 9	26. 9	
965. 000	27. 3	QP	22. 7	-23. 1	26. 9	359	100	Vert.	53. 9	27. 0	
			1 1								
			1 1								
			1 1								
			1 1								
			1 1								
			1 1								

CHART:WITH FACTOR ANT TYPE: -30MHz:LOOP, 30-300MHz:BICONICAL, 300MHz-1000MHz:LOGPERIODIC, 1000MHz-:HORN CALCULATION:RESULT = READING + ANT FACTOR + LOSS(CABLE - GAIN(AMP))

*The test result is rounded off to one or two decimal places, so some differences might be observed.

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

: +81 596 24 8999 Telephone Facsimile : +81 596 24 8124

: 10835051H-A-R1 Test report No. Page : 20 of 29 **Issued date** : July 27, 2015 Revised date : September 17, 2015 : Y8PFJ16-1 FCC ID

Radiated Emission above 30MHz (Spurious Emission)

Antenna (TYPE 2 OUTSIDE)

DATA OF RADIATED EMISSION TEST


UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber Date : 2015/07/23

: 10835051H Report No.

: 22deg. C / 66% RH : Yuta Moriya Temp./Humi.

Mode / Remarks : Tx 134.2kHz, Antenna (Type 2 OUTSIDE), (Ant Y, ECU X)

LIMIT : FCC15.209 3m, below 1GHz:QP, above 1GHz:PK
All other spurious emissions were less than 20dB for the limit.



			Antenna	Loss&							
Frequency	Reading	DET	Factor	Gain	Level	Angle	Height	Polar.	Limit	Margin	Comment
[MHz]	[dBuV]	DLI	[dB/m]	[dB]	[dBuV/m]	[Deg]	[cm]	ruiai.	[dBuV/m]	[dB]	Collinett
35. 952	42.1	QP	15. 5	-31.4	26. 2	182		Hori.	40.0		
35. 952	44. 1	QP	15.5	-31.4	28. 2	0		Vert.	40. 0		
59. 218		QP	7. 5	-31.0	28. 1	359		Hori.	40. 0		
59. 218	50. 9	QP	7. 5	-31.0	27. 4	73		Vert.	40. 0		
68. 417	38. 0	QP	6. 3	-30. 8	13. 5	8		Hori.	40. 0		
68. 707	44. 1	QP	6. 3	-30. 8	19. 6	134		Vert.	40. 0		
89. 109	47. 9	QP	8. 2	-30. 5	25. 6	351	339	Hori.	43. 5		
88. 978	45. 8	QP	8. 2	-30. 5	23. 5	276		Vert.	43. 5		
120. 240	39. 2	QP	12. 6	-30. 1	21. 7	169	261	Hori.	43. 5		
120, 361	37. 5	QP	12.6	-30. 1	20. 0	290	112	Vert.	43. 5		
141. 928	33. 7	QP	14. 4	-29. 8	18. 3	0		Hori.	43. 5		
144, 928	31.5	QP	14. 6	-29. 8	16.3	276			43. 5		
										i i	
										i i	

CHART: WITH FACTOR ANT TYPE: -30MHz:LOOP, 30-300MHz:BICONICAL, 300MHz-1000MHz:LOGPERIODIC, 1000MHz-:HORN CALCULATION: RESULT = READING + ANT FACTOR + LOSS (CABLE + ATTEN - GAIN (AMP))

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

: +81 596 24 8999 Telephone Facsimile : +81 596 24 8124

^{*}The test result is rounded off to one or two decimal places, so some differences might be observed.

Test report No. : 10835051H-A-R1
Page : 21 of 29
Issued date : July 27, 2015
Revised date : September 17, 2015
FCC ID : Y8PFJ16-1

-26dB Bandwidth and 99% Occupied Bandwidth

Antenna (TYPE 1)

Report No. 10835051H Test place Ise EMC Lab. Semi Anechoic Chamber No.1

Date No.1

Object No.1


Object No.1


Object No.1

Temperature / Humidity
Engineer
Mode

24 deg. C / 60 % RH
Yuta Moriya
Tx 134.2 kHz (TYPE 1)

-26 dB Bandwidth
[kHz]
21.685





4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Test report No. : 10835051H-A-R1
Page : 22 of 29
Issued date : July 27, 2015
Revised date : September 17, 2015
FCC ID : Y8PFJ16-1

-26dB Bandwidth and 99% Occupied Bandwidth

Antenna (TYPE 2 INSIDE)

Report No. 10835051H Test place Ise EMC Lab. Semi Anechoic Chamber No.1


Date No.1


Od/23/2015

Temperature / Humidity 24 deg. C / 60 % RH Engineer Yuta Moriya

Mode Tx 134.2 kHz (TYPE 2 INSIDE)

-26 dB Bandwidth
[kHz]
26.160





4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Test report No. : 10835051H-A-R1
Page : 23 of 29
Issued date : July 27, 2015
Revised date : September 17, 2015
FCC ID : Y8PFJ16-1

-26dB Bandwidth and 99% Occupied Bandwidth

Antenna (TYPE 2 OUTSIDE)


Report No. 10835051H
Test place Ise EMC Lab.
Semi Anechoic Chamber No.1


Date 07/23/2015 Temperature / Humidity 20 deg, C / 60 % RH

Engineer Yuta Moriya

Mode Tx 134.2 kHz (TYPE 2 OUTSIDE)

-26 dB Bandwidth
[kHz]
26.166





4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Test report No. : 10835051H-A-R1
Page : 24 of 29
Issued date : July 27, 2015
Revised date : September 17, 2015
FCC ID : Y8PFJ16-1

APPENDIX 2: Test instruments

EMI test equipment

Control No.	Instrument	Manufacturer	Model No	Serial No	Test Item	Calibration Date * Interval(month)	
MAEC-02	Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 3m	DA-06902	RE	2014/06/25 * 12 *1)	
MOS-22	Thermo-Hygrometer	Custom	CTH-201	0003	RE	2015/01/13 * 12	
MJM-14	Measure	KOMELON	KMC-36	-	RE	-	
COTS-MEMI	EMI measurement program	TSJ	TEPTO-DV	-	RE	-	
MSA-14	Spectrum Analyzer	Agilent	E4440A	MY48250080	RE	2014/10/17 * 12	
MTR-03	Test Receiver	Rohde & Schwarz	ESCI	100300	RE	2015/06/08 * 12	
MLPA-01	Loop Antenna	Rohde & Schwarz	HFH2-Z2	100017	RE	2014/10/04 * 12	
MCC-13	Coaxial Cable	Fujikura 3D-2W(12m)/ 5D-2W(5m)/ 5D-2W(0.8m)/ 5D-2W(1m)		-	RE	2015/02/06 * 12	
MCC-143	Coaxial Cable	UL Japan	-	-	RE	2015/06/24 * 12	
MPA-14	Pre Amplifier	SONOMA INSTRUMENT	310	260833	RE	2015/03/09 * 12	
MAT-07	Attenuator(6dB)	Weinschel Corp	2	BK7970	RE	2014/11/11 * 12	
MLPA-07	Loop Antenna	UL Japan	-	-	RE	Pre Check	
MAEC-01	Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 10m	DA-06881	RE	2014/09/01 * 12	
MOS-27	Thermo-Hygrometer	CUSTOM	CTH-201	A08Q26	RE	2015/01/13 * 12	
MJM-21	Measure	KOMELON	KMC-36	-	RE	-	
MTR-09	EMI Test Receiver	Rohde & Schwarz	ESU26	100412	RE	2014/06/06 * 12 *1)	
KBA-05	Biconical Antenna	Schwarzbeck	BBA9106	2513	RE	2014/11/22 * 12	
KLA-04	Logperiodic Antenna	Schwarzbeck	USLP9143	361	RE	2014/11/22 * 12	
MAT-08	Attenuator(6dB)	Weinschel Corp	2	BK7971	RE	2014/11/20 * 12	
MCC-02	Coaxial Cable	Suhner/storm/Agilent /TSJ	-	-	RE	2014/09/12 * 12	
MPA-19	Pre Amplifier	MITEQ	MLA-10K01-B01-35	1237616	RE	2015/02/03 * 12	
MCC-03	Coaxial Cable	Fujikura/Suhner/TSJ	5D-2W(20m)/3D- 2W(7.5m)/RG400u(1 .5m)/RFM- E421(Switcher)	-/01068 (Switcher)	RE	2014/09/12 * 12	
MPA-13	Pre Amplifier	SONOMA INSTRUMENT	310	260834	RE	2015/03/10 * 12	
MSA-10	Spectrum Analyzer	Agilent	E4448A	MY46180655	RE	2015/02/26 * 12	

^{*1)} This test equipment was used for the tests before the expiration date of the calibration.

The expiration date of the calibration is the end of the expired month.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

Test Item:

RE: Spurious emission

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN