

Report on the Radio Testing

For

Dairymaster

on

MooMonitor+

Report no. TRA-027458-47-07B

24th January 2017

RF922 3.0

Report Number: TRA-027458-47-07B
Issue: A

REPORT ON THE RADIO TESTING OF A
Dairymaster
MooMonitor+
WITH RESPECT TO SPECIFICATION
FCC 47CFR 15.249 & IC RSS-210 Annex 2.9

TEST DATE: 09-05-2016 to 13-05-2016

Written by: D Winstanley

D Winstanley
Senior Radio Test Engineer

Approved by:

Date: 24th January 2017

J Charters
Department Manager -Radio

Disclaimers:

- [1] THIS DOCUMENT MAY BE REPRODUCED ONLY IN ITS ENTIRETY AND WITHOUT CHANGE
- [2] THE RESULTS CONTAINED IN THIS DOCUMENT RELATE ONLY TO THE ITEM(S) TESTED

RF922 3.0

1 Revision Record

<i>Issue Number</i>	<i>Issue Date</i>	<i>Revision History</i>
A	9 th January 2017	Original
B	24 th January 2017	Update typo's

2 Summary

TEST REPORT NUMBER:	TRA-027458-47-07B
WORKS ORDER NUMBER	TRA-027458-05
PURPOSE OF TEST:	<p>USA: Testing of radio frequency equipment per the relevant authorization procedure of chapter 47 of CFR (code of federal regulations) Part 2, subpart J.</p> <p>Canada: Testing of radio apparatus for TAC (technical acceptance certificate) per subsections 4(2) of the Radio communication Act and 21(1) of the Radio communication Regulations.</p>
TEST SPECIFICATION(S):	47CFR15.249 & RSS-210 Annex 2.9
EQUIPMENT UNDER TEST (EUT):	MooMonitor+
FCC IDENTIFIER:	Y9GTAG2-1
EUT SERIAL NUMBER:	not applicable
MANUFACTURER/AGENT:	Dairymaster
ADDRESS:	<p>Causeway Tralee Co. Kerry V92 NWK0 Ireland</p>
CLIENT CONTACT:	<p>Edmond Harty  +353(0)66 7131124  eharty@dairymaster.com</p>
ORDER NUMBER:	N/A
TEST DATE:	09-05-2016 to 13-05-2016
TESTED BY:	<p>D Winstanley Element</p>

2.1 Test Summary

Test Method and Description	Requirement Clause		Applicable to this equipment	Result / Note
	RSS	47CFR15		
Radiated spurious emissions	210, A2.9(b)	15.249(d)	<input checked="" type="checkbox"/>	Pass
AC power line conducted emissions	Gen, 8.8	15.207	<input type="checkbox"/>	
Occupied bandwidth	Gen, 6.6	15.215(c)	<input checked="" type="checkbox"/>	Pass
Field strength of fundamental	210, A2.9(a)	15.249(a)	<input checked="" type="checkbox"/>	Pass
Calculation of duty correction ¹	-	15.35(c)	<input type="checkbox"/>	

Notes:

The results contained in this report relate only to the items tested, in the condition at time of test, and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

The apparatus was set up and exercised using the configurations, modes of operation and arrangements defined in this report only. Any modifications made are identified in Section 8 of this report.

Particular operating modes, apparatus monitoring methods and performance criteria required by the standards tested to have been performed except where identified in Section 5.2 of this test report (Deviations from Test Standards).

3 Contents

1	Revision Record.....	3
2	Summary.....	4
2.1	Test Summary.....	5
3	Contents.....	6
4	Introduction	7
5	Test Specifications	8
5.1	Normative References	8
5.2	Deviations from Test Standards	8
6	Glossary of Terms.....	9
7	Equipment Under Test	10
7.1	EUT Identification.....	10
7.2	System Equipment.....	10
7.3	EUT Mode of Operation	10
7.3.1	Transmission.....	10
7.4	EUT Radio Parameters	11
7.4.1	General	11
7.5	EUT Description.....	11
8	Modifications	12
9	EUT Test Setup.....	12
9.1	Block Diagram.....	12
9.2	General Set-up Photograph	13
10	General Technical Parameters.....	14
10.1	Normal Conditions.....	14
10.2	Varying Test Conditions	14
11	Radiated emissions.....	15
11.1	Definitions	15
11.2	Test Parameters.....	15
11.3	Test Limit	15
11.4	Test Method	16
11.5	Test Set-up Photograph	17
11.6	Test Equipment.....	17
11.7	Test Results	18
12	Occupied Bandwidth	21
12.1	Definitions	21
12.2	Test Parameters.....	21
12.3	Test Limit	21
12.4	Test Method	22
12.5	Test Equipment.....	22
12.6	Test Results	23
13	Transmitter output power (fundamental radiated emission)	25
13.1	Definition	25
13.2	Test Parameters.....	25
13.3	Test Limit	25
13.4	Test Method	26
13.5	Test Equipment.....	26
13.6	Test Results	26
14	Measurement Uncertainty	27

4 Introduction

This report TRA-027458-47-07B presents the results of the Radio testing on a Dairymaster, MooMonitor+ to specification 47CFR15 Radio Frequency Devices and RSS-210 Licence-exempt Radio Apparatus (All Frequency Bands): Category I Equipment.

The testing was carried out for Dairymaster by Element, at the address(es) detailed below.

<input type="checkbox"/> Element Hull Unit E South Orbital Trading Park Hedon Road Hull HU9 1NJ UK	<input checked="" type="checkbox"/> Element North West Unit 1 Pendle Place Skemersdale West Lancashire WN8 9PN UK
--	---

This report details the configuration of the equipment, the test methods used and any relevant modifications where appropriate.

All test and measurement equipment under the control of the laboratory and requiring calibration is subject to an established programme and procedures to control and maintain measurement standards. The quality management system meets the principles of ISO 9001, and has quality control procedures for monitoring the validity of tests undertaken. Records and sufficient detail are retained to establish an audit trail of calibration records relating to its test results for a defined period. Under control of the established calibration programme, key quantities or values of the test & measurement instrumentation are within specification and comply with the relevant traceable internationally recognised and appropriate standard specifications, which are UKAS calibrated as such where these properties have a significant effect on results. Participation in inter-laboratory comparisons and proficiency testing ensures satisfactory correlation of results conform to Elements own procedures, as well as statistical techniques for analysis of test data providing the appropriate confidence in measurements.

Throughout this report EUT denotes equipment under test.

FCC Site Listing:

Element is accredited for the above sites under the US-EU MRA, Designation number UK0009.

IC Registration Number(s):

Element North West 3930B

The test site requirements of ANSI C63.4-2014 are met up to 1 GHz.

The test site SVSWR requirements of CISPR 16-1-4:2010 are met over the frequency range 1 GHz to 18 GHz.

5 Test Specifications

5.1 *Normative References*

- FCC 47 CFR Ch. I – Part 15 – Radio Frequency Devices.
- ANSI C63.10-2013 – American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.
- ANSI C63.4-2014 – American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.
- Industry Canada RSS-210, Issue 8, December 2010 – Licence-exempt Radio Apparatus (All Frequency Bands): Category I Equipment.
- Industry Canada RSS-Gen, Issue 4, November 2014 – General Requirements for Compliance of Radio Apparatus.

5.2 *Deviations from Test Standards*

There were no deviations from the test standard.

6 Glossary of Terms

§	denotes a section reference from the standard, not this document
AC	Alternating Current
ANSI	American National Standards Institute
BW	bandwidth
C	Celsius
CFR	Code of Federal Regulations
CW	Continuous Wave
dB	decibel
dBm	dB relative to 1 milliwatt
DC	Direct Current
DSSS	Direct Sequence Spread Spectrum
EIRP	Equivalent Isotropically Radiated Power
ERP	Effective Radiated Power
EUT	Equipment Under Test
FCC	Federal Communications Commission
FHSS	Frequency Hopping Spread Spectrum
Hz	hertz
IC	Industry Canada
ITU	International Telecommunication Union
LBT	Listen Before Talk
m	metre
max	maximum
MIMO	Multiple Input and Multiple Output
min	minimum
MRA	Mutual Recognition Agreement
N/A	Not Applicable
PCB	Printed Circuit Board
PDF	Portable Document Format
Pt-mpt	Point-to-multipoint
Pt-pt	Point-to-point
RF	Radio Frequency
RH	Relative Humidity
RMS	Root Mean Square
Rx	receiver
s	second
SVSWR	Site Voltage Standing Wave Ratio
Tx	transmitter
UKAS	United Kingdom Accreditation Service
V	volt
W	watt
Ω	ohm

7 Equipment Under Test

7.1 EUT Identification

- Name: MooMonitor+
- Serial Number: not applicable
- Model Number: TAG2-1
- Software Revision: Not Applicable
- Build Level / Revision Number: Not Applicable

7.2 System Equipment

Equipment listed below forms part of the overall test setup and is required for equipment functionality and/or monitoring during testing. The compliance levels achieved in this report relate only to the EUT and not items given in the following list.

Not Applicable – No support/monitoring equipment required.

7.3 EUT Mode of Operation

7.3.1 Transmission

The mode of operation for Tx tests was as follows: the unit was constantly transmitting on a fixed frequency pre-selected manually with a test software.

7.4 EUT Radio Parameters

7.4.1 General

Frequency of operation:	915.1 MHz to 927.9 MHz
Modulation type(s):	FSK
Occupied channel bandwidth(s):	70 kHz
Channel spacing:	100 kHz
ITU emission designator(s):	50K F1D
Declared output power(s):	3dBm
Nominal Supply Voltage:	3Vdc
Location of notice for license exempt use:	Label / user manual / both.
Duty cycle:	0.002%

7.5 EUT Description

The EUT is a battery powered Tag transmitting in 902MHz to 928 MHz band.


8 Modifications

No modifications were performed during this assessment.

9 EUT Test Setup


9.1 *Block Diagram*

The following diagram shows basic EUT interconnections with cable type and cable lengths identified:



9.2 General Set-up Photograph

The following photograph shows basic EUT set-up:



10 General Technical Parameters

10.1 Normal Conditions

The E U T was tested under the normal environmental conditions of the test laboratory, except where otherwise stated. The normal power source applied was approx. 3 V dc from alkaline batteries .

10.2 Varying Test Conditions

There are no specific frequency stability requirements for the type of device. The results contained in this report demonstrate that the occupied bandwidth is contained within the authorised band and the manufacturer has declared sufficient frequency stability (refer to section 7.4).

Variation of supply voltage is required to ensure stability of the declared output power. During carrier power testing the following variations were made:

	Category	Nominal	Variation
<input type="checkbox"/>	Mains	110 V ac +/-2 %	85 % and 115 %
<input checked="" type="checkbox"/>	Battery	New battery	N/A

11 Radiated emissions

11.1 Definitions

Out-of-band emissions

Emissions on a frequency or frequencies immediately outside the necessary bandwidth which result from the modulation process, but exclude spurious emissions.

Spurious emissions

Emissions on a frequency or frequencies which are outside the necessary bandwidth and the level of which may be reduced without affecting the corresponding transmission of information. Spurious emissions include harmonic emissions, parasitic emissions, intermodulation products and frequency conversion products, but exclude out-of-band emissions.

Restricted bands

A frequency band in which intentional radiators are permitted to radiate only spurious emissions but not fundamental signals.

11.2 Test Parameters

Test Location:	Element Skelmersdale
Test Standard and Clause:	ANSI C63.10-2013, Clause 6.5 and 6.6
EUT Channels / Frequencies Measured:	915.1 MHz / 921.5 MHz / 927.9 MHz
Deviations From Standard:	None
Measurement BW:	30 MHz to 1 GHz: 120 kHz Above 1 GHz: 1 MHz
Measurement Detector:	Up to 1 GHz: quasi-peak Above 1 GHz: RMS average and Peak

Environmental Conditions (Normal Environment)

Temperature: 24 °C	+15 °C to +35 °C (as declared)
Humidity: 35 % RH	20 % RH to 75 % RH (as declared)
Supply: 3 V dc	3 V dc ±10 % (as declared)

11.3 Test Limit

Except for harmonics, out-of-band emissions shall be attenuated by at least 50 dB below the level of the fundamental or to the general field strength limits listed in FCC 47CFR15.209 / RSS-Gen {see table below}, whichever is less stringent.

Harmonics shall be limited to a maximum level of 0.5 mV/m measured at 3 metres.

General Field Strength Limits for License-Exempt Transmitters at Frequencies above 30 MHz

Frequency (MHz)	Field Strength (µV/m at 3 m)
30 to 88	100
88 to 216	150
216 to 960	200
Above 960	500

n.b. per FCC 47CFR15.35(b) / RSS-Gen 8.1, peak limit is 20 dB above average.

11.4 Test Method

With the EUT setup as per section 9 of this report and connected as per Figure i, the emissions from the EUT were measured on a spectrum analyzer / EMI receiver.

Radiated electromagnetic emissions from the EUT are checked first by preview scans. Preview scans for all spectrum and modulation characteristics are checked, using a peak detector and where applicable worst-case determined for function, operation, orientation, etc. for both vertical and horizontal polarisations. Pre-scan plots are shown with a peak detector and 100 kHz RBW.

If the EUT connects to auxiliary equipment and is table or floor standing, the configurations prescribed in ANSI C63.10 are followed. Alternatively, a layout closest to normal use (as declared by the provider) is employed, (see EUT setup photographs for more detail).

Emissions between 30 MHz and 1 GHz are measured using calibrated broadband antennas. Emissions above 1 GHz are characterized using standard gain horn antennas. Pre-amplifiers and filters are used where required. Care is taken to ensure that test receiver resolution bandwidth, video bandwidth and detector type(s) meet the regulatory requirements.

For both horizontal and vertical polarizations, the EUT is then rotated through 360 degrees in azimuth until the highest emission is detected. At the previously determined azimuth the test antenna is raised and lowered from 1 to 4 m in height until a maximum emission level is detected, this maximum value is recorded.

Power values measured on the test receiver / analyzer are converted to field strength, FS, in dB μ V/m at the regulatory distance, using:

$$FS = PR + CL + AF - PA + DC - CF$$

Where,

PR is the power recorded on the receiver / spectrum analyzer in dB μ V;

CL is the cable loss in dB;

AF is the test antenna factor in dB/m;


PA is the pre-amplifier gain in dB (where used);

DC is the duty correction factor in dB (where used, e.g. harmonics of pulsed fundamental);


CF is the distance factor in dB (where measurement distance different to limit distance);

This field strength value is then compared with the regulatory limit.

Figure i Test Setup




11.5 Test Set-up Photograph




11.6 Test Equipment

Type of Equipment	Maker/Supplier	Model Number	Element Number	Calibration Due Date	Calibration Interval
Bilog	Chase	CBL611/A	UH191	26/02/2017	24
ESVS10	R&S	ESVS10	L352	07/08/2016	12
Spectrum analyser	R&S	FSU50	U544	16/03/2017	12
Horn Antenna	EMCO	3115	TRL139	25/09/2017	24
Pre-Amplifier	Agilent	8449B	TRL572	16/02/2017	12


11.7 Test Results



1 – Bottom Channel (30 MHz to 1 GHz).




2 – Bottom Channel (1 GHz to 5 GHz).




3 – Bottom Channel (5 GHz to 10 GHz).


High Power; Channel: 915.1 MHz										
Detector	Freq. (MHz)	Meas'd Emission (dBµV)	Cable Loss (dB)	Antenna Factor (dB/m)	Pre-amp Gain (dB)	Duty Cycle Corr'n (dB)	Distance Extrapol'n Factor (dB)	Field Strength (dBµV/m)	Field Strength (µV/m)	Limit (µV/m)
Pk	1830.13	59.92	3.00	27.10	36.08	0.00	0.00	53.94	497.74	5012
Av	1830.13	57.71	3.00	27.10	36.08	0.00	0.00	51.73	385.92	500
Pk	3660.36	53.45	3.70	31.70	35.71	0.00	0.00	53.14	453.94	5012
Av	3660.36	48.36	3.70	31.70	35.71	0.00	0.00	48.05	252.64	500



1 – Middle Channel (30 MHz to 1 GHz).




2 – Middle Channel (1 GHz to 5 GHz).




Date: 10.MAY.2016 10:52:38

3 – Middle Channel (5 GHz to 10 GHz).


High Power; Channel: 921.5 MHz										
Detector	Freq. (MHz)	Meas'd Emission (dBμV)	Cable Loss (dB)	Antenna Factor (dB/m)	Pre-amp Gain (dB)	Duty Cycle Corr'n (dB)	Distance Extrap'n Factor (dB)	Field Strength (dBμV/m)	Field Strength (μV/m)	Limit (μV/m)
Pk	1843.00	58.37	2.70	27.20	36.08	0.00	0.00	52.19	406.91	5012
Av	1843.00	55.54	2.70	27.20	36.08	0.00	0.00	49.36	293.76	500
Pk	3685.99	52.33	3.70	31.70	35.70	0.00	0.00	52.03	399.48	5012
Av	3685.99	47.25	3.70	31.70	35.70	0.00	0.00	46.95	222.59	500



1 – Top Channel (30 MHz to 1 GHz).



2 – Top Channel (1 GHz to 5 GHz).



Date: 10.MAY.2016 10:40:29

3 – Top Channel(5 GHz to 10 GHz).

High Power; Channel: 927.9 MHz										
Detector	Freq. (MHz)	Meas'd Emission (dBμV)	Cable Loss (dB)	Antenna Factor (dB/m)	Pre-amp Gain (dB)	Duty Cycle Corr'n (dB)	Distance Extrap'n Factor (dB)	Field Strength (dBμV/m)	Field Strength (μV/m)	Limit (μV/m)
Pk	1855.75	57.34	3.50	27.20	36.08	0.00	0.00	51.96	396.28	5012
Av	1855.75	54.10	3.50	27.20	36.08	0.00	0.00	48.72	272.90	500
Pk	3711.55	52.24	4.30	31.80	35.69	0.00	0.00	52.65	429.04	5012
Av	3711.55	45.64	4.30	31.80	35.69	0.00	0.00	46.05	200.68	500

12 Occupied Bandwidth

12.1 Definitions

Occupied bandwidth

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to 0.5 % of the emitted power. This is also known as the 99 % *emission bandwidth*. For transmitters in which there are multiple carriers, contiguous or non-contiguous in frequency, the occupied bandwidth is to be the sum of the occupied bandwidths of the individual carriers.

20 dB bandwidth

The emission bandwidth (x dB) is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated x dB below the maximum in-band spectral density of the modulated signal.

12.2 Test Parameters

Test Location:	Element Skelmersdale
Test Chamber:	Radio Chamber
Test Standard and Clause:	ANSI C63.10-2013, Clause 6.9
EUT Channels / Frequencies Measured:	915.1 MHz / 921.5 MHz / 927.9 MHz
EUT Channel Bandwidths:	50 kHz
Deviations From Standard:	None
Measurement BW: (requirement: 1 % to 5 % OBW)	1 kHz
Spectrum Analyzer Video BW: (requirement at least 3x RBW)	300 kHz
Measurement Span: (requirement 2 to 5 times OBW)	150KHz
Measurement Detector:	Peak

Environmental Conditions (Normal Environment)

Temperature: 23 °C	+15 °C to +35 °C (as declared)
Humidity: 35 % RH	20 % RH to 75 % RH (as declared)
Supply: 3 V dc	3 V dc ±10 % (as declared)

12.3 Test Limit

Industry Canada:

If the frequency stability of the license-exempt radio apparatus is not specified in the applicable standard (RSS), measurement of the frequency stability is not required provided that the occupied bandwidth of the license-exempt radio apparatus lies entirely outside the restricted bands and the prohibited TV bands of 54 to 72 MHz, 76 to 88 MHz, 174 to 216 MHz, 470 to 608 MHz and 614 to 806 MHz.

Federal Communications Commission:


Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

12.4 Test Method

With the EUT setup as per section 9 of this report and connected as per Figure iii, the bandwidth of the EUT was measured on a spectrum analyser.

The measurements were performed with EUT set at its maximum duty. All modulation schemes, data rates and power settings were used to observe the worst-case configuration in each bandwidth.

Figure iii Test Setup



12.5 Test Equipment


Type of Equipment	Maker/Supplier	Model Number	Element Number	Calibration Due Date	Calibration Interval
Bilog	Chase	CBL611/A	UH191	26/02/2017	24
Spectrum analyser	R&S	FSU50	U544	16/03/2017	12
Pre-Amplifier	Agilent	8449B	TRL572	16/02/2017	12

12.6 Test Results


RSS-210. Power setting: 3 dBm max.				
Channel Frequency (MHz)	F_L (MHz)	F_H (MHz)	99% Bandwidth (kHz)	Result
915.1	915.0594067	915.1405933	81.186685962	PASS
921.5	921.4591896	921.5408104	81.620839363	PASS
927.9	927.8591896	927.9408104	81.620839363	PASS



1 – Bottom Channel (915.1 MHz).




2 – Middle Channel (921.5 MHz to 1 GHz).




3 – Top Channel (927.9 MHz to 1 GHz).


FCC 15.249. Power setting: 3 dBm				
Channel Frequency (MHz)	F_L (MHz)	F_H (MHz)	20dB Bandwidth (kHz)	Result
915.1	915.06179	915.13321	71.42	PASS
921.5	921.46179	921.53343	71.64	PASS
927.9	927.86179	927.93321	71.42	PASS



1 – Bottom Channel (915.1 MHz).



2 – Middle Channel (921.5 MHz to 1 GHz).



3 – Top Channel (927.9 MHz to 1 GHz).

13 Transmitter output power (fundamental radiated emission)

13.1 Definition

The RF power dissipated in the standard output termination when operating under the rated duty cycle selected by the applicant for approval.

13.2 Test Parameters

Test Location:	Element Skelmersdale
Test Chamber:	Radio Chamber
Test Standard and Clause:	ANSI C63.10-2013, Clause 6.5 / 6.6
EUT Channels / Frequencies Measured:	915.1 MHz / 921.5 MHz / 927.9 MHz
Deviations From Standard:	None
Measurement BW:	120kHz
Spectrum Analyzer Video BW: (requirement at least 3x RBW)	N/A
Measurement Detector:	Up to 1 GHz: Quasi-peak Above 1 GHz: Average RMS and Peak
Voltage Extreme Environment Test Range:	Mains Power = 85 % and 115 % of Nominal (FCC only requirement); Battery Power = new battery.

Environmental Conditions (Normal Environment)

Temperature: 24 °C	+15 °C to +35 °C (as declared)
Humidity: 37 % RH	20 % RH to 75 % RH (as declared)

13.3 Test Limit

The field strength measured at 3 meters shall not exceed the limits in the following table:

Field Strength Limits for License-Exempt Transmitters for Any Application

<i>Fundamental frequency (MHz)</i>	<i>Field strength (mV/m at 3 m)</i>	<i>Detector</i>
902 to 928	50	Quasi-Peak
2400 to 2483.5	50	Average RMS
5725 to 5875	50	Average RMS


n.b. per FCC 47CFR15.249(e) / RSS-Gen 8.1, peak limit is 20 dB above average.

13.4 Test Method

With the EUT setup as per section 9 of this report and connected as per Figure iv, the resolution bandwidth of the spectrum analyser was increased above the EUT occupied bandwidth and the peak emission data noted.

The measurements were performed with EUT set at its maximum duty. All modulation schemes, data rates and power settings were used to observe the worst-case configuration in each bandwidth.

Figure iv Test Setup



13.5 Test Equipment

Type of Equipment	Maker/Supplier	Model Number	Element Number	Calibration Due Date	Calibration Interval
Bilog	Chase	CBL611/A	UH191	26/02/2017	24
ESVS10	R&S	ESVS10	L352	07/08/2016	12
Horn Antenna	EMCO	3115	TRL139	25/09/2017	24

13.6 Test Results

Power setting: 3 dBm							
Channel Frequency (MHz)	Meas'd Emission (dB μ V)	Cable Loss (dB)	Antenna Factor (dB/m)	Pre-amp Gain (dB)	Field Strength (dB μ V/m)	Distance Extrap'n Factor (dB)	Field Strength (μ V/m)
915.08	62.50	4.10	23.45	N/A	90.05	0.00	31805.34
921.50	62.10	4.10	23.68	N/A	89.88	0.00	31188.90
927.90	62.30	4.10	23.80	N/A	90.20	0.00	32359.37

14 Measurement Uncertainty

Calculated Measurement Uncertainties

All statements of uncertainty are expanded standard uncertainty using a coverage factor of 1.96 to give a 95 % confidence:

[1] Carrier power

Uncertainty in test result (Power Meter) = **1.08 dB**

Uncertainty in test result (Spectrum Analyser) = **2.48 dB**

[2] Spurious emissions

Uncertainty in test result (30 MHz to 1 GHz) = **4.6 dB**

Uncertainty in test result (1 GHz to 18 GHz) = **4.7 dB**

[3] AC power line conducted emissions

Uncertainty in test result = **3.4 dB**

[4] Occupied bandwidth

Uncertainty in test result = **15.5 %**

[5] Maximum frequency error

Uncertainty in test result (Power Meter) = **0.113 ppm**

Uncertainty in test result (Spectrum Analyser) = **0.265 ppm**

[6] Duty cycle

Uncertainty in test result = **7.98 %**