

Test Report of FCC Part 15 C for FCC Certificate

On Behalf of

IPW China Limited

Product description: Remote control

Model No.: Pebble-01

FCC ID: Y9P-PEBBLE-01

Prepared for: IPW China Limited

5/F, Block B3, Xujingchang Industrial Park, Donghaoye Road, Fuyuanyi Road, Xinhe Shequ, Fuyong, Bao'an District, Shenzhen, P.R China

Prepared by: Bontek Compliance Laboratory Ltd

1/F, Block East H-3, OCT Eastern Ind. Zone, Qiaocheng East Road, Nanshan, Shenzhen, China

Tel: 86-755-86337020


Fax: 86-755-86337028

Report No.: BCT10LR-2255E

Issue Date: February 24, 2011


Test Date: February 10~14, 2011

Test by:



Kendy Wang

Reviewed By:



Tony Wu

TABLE OF CONTENTS

1 - GENERAL INFORMATION	4
1.1 Product Description for Equipment Under Test (EUT)	4
1.2 Test Standards.....	4
1.3 Test Summary.....	5
1.4 Test Methodology	5
1.5 Test Facility.....	5
1.6 Test Equipment List and Details	6
2 - SYSTEM TEST CONFIGURATION.....	8
2.1 Justification	8
2.2 EUT Exercise Software.....	8
2.3 Equipment Modifications.....	8
2.4 Basic Test Setup Block Diagram	8
3 – DISTURBANCE VOLTAGE AT THE MAINS TERMINALS	10
3.1 Measurement Uncertainty	10
3.2 Applicable Standard.....	10
3.3 Test Description	10
4- RADIATED DISTURBANCES.....	11
4.1 Measurement Uncertainty	11
4.2 Limit of Radiated Disturbances	11
4.3 EUT Setup	11
4.4 Test Receiver Setup	12
4.5 Test Procedure	12
4.6 Corrected Amplitude & Margin Calculation	13
4.7 Radiated Emissions Test Result	13
5- 20DB BANDWIDTH	15
5.1 Measurement Uncertainty	15
5.2 Limit of 20dB Bandwidth	15
5.3 EUT Setup	15
5.4 Test Procedure	15
5.5 Emissions within Band Edges Test Result.....	16
6- DUTY CYCLE.....	17
6.1 Measurement Uncertainty	17
6.2 EUT Setup	17
6.3 Test Procedure	17
6.4 Measurement Result.....	17
7- TRANSMISSION TIME.....	22
7.1 Measurement Uncertainty	22
7.2 EUT Setup	22

7.3 Test Procedure	22
7.4 Limit of Transmission time	22
7.5 Transmission Time Test Result	22
8- ANTENNA REQUIREMENT.....	24
8.1 Standard Applicable.....	24
8.2 Antenna Connected Construction.....	24

1 - GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: IPW China Limited

Address of applicant: 5/F, Block B3, Xujingchang Industrial Park, Donghaoye Road, Fuyuanyi Road, Xinhe Shequ, Fuyong, Bao'an District, Shenzhen, P.R China

Manufacturer: OSSOU Metal&Plastic Manu Facturong(Shenzhen)CO.,Ltd

Address of manufacturer: 5/F, Block B3, Xujingchang Industrial Park, Donghaoye Road, Fuyuanyi Road, Xinhe Shequ, Fuyong, Bao'an District, Shenzhen, P.R China

General Description of E.U.T

Items	Description
EUT Description:	Remote control
Trade Name:	Smart&Green
Model No.:	Pebble-01
Rated Voltage	DC 3V from Battery
Frequency range	433.92MHz
Number of channels	1
Antenna Type:	Built-in Antenna
Channel Separation	None
Product Class:	Low Power Communication Device Transmitter

* The test data gathered are from the production sample provided by the manufacturer.

1.2 Test Standards

The following Declaration of Conformity report of EUT is prepared in accordance with

FCC Rules and Regulations Part 15 Subpart C Section 15.231

The objective of the manufacturer is to demonstrate compliance with the described above standards.

1.3 Test Summary

For the EUT described above. The standards used were FCC Part 15 Subpart C Section 15.231 for Emissions

Tests Carried Out Under FCC Part 15 Subpart C

Standard	Test Items	Status	Application
Part 15 Subpart C Section 15.231	Disturbance Voltage at The Mains Terminals	x	N/A, without AC power supply
	Radiation Emission	√	
	20dB Bandwidth	√	
	Duty Cycle	√	
	Transmission time	√	
	Antennal requirement	√	

√ Indicates that the test is applicable

✗ Indicates that the test is not applicable

1.4 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the Operating Instructions.

The maximum emission levels emanating from the device are compared to the Part 15 Subpart C Section 15.231 limits for radiation emissions and the measurement results contained in this test report show that EUT is to be technically compliant with FCC requirements.

All measurement required was performed at Bontek Compliance Testing Laboratory Ltd at 1/F, Block East H-3, OCT Eastern Ind. Zone, Qiaocheng East Road, Nanshan, Shenzhen, China

1.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC – Registration No.: 338263

Bontek Compliance Testing Laboratory Ltd, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 338263, March, 2008.

IC Registration No.: 7631A

The 3m alternate test site of Bontek Compliance Testing Laboratory Ltd EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 7631A on August 2009.

1.6 Test Equipment List and Details

No.	Instrument no.	Equipment	Manufacturer	Model No.	S/N	Calibration Date	Calibration Due Date
1	BCT-EMC001	EMI Test Receiver	R&S	ESCI	100687	2010-4-14	2011-4-13
2	BCT-EMC002	EMI Test Receiver	R&S	ESPI	100097	2010-4-14	2011-4-13
3	BCT-EMC003	Amplifier	HP	8447D	1937A02492	2010-4-14	2011-4-13
4	BCT-EMC004	Single Power Conductor Module	FCC	FCC-LISN-5-50-1-01-CISPR25	7101	2010-4-14	2011-4-13
5	BCT-EMC005	Single Power Conductor Module	FCC	FCC-LISN-5-50-1-01-CISPR25	7102	2010-4-14	2011-4-13
6	BCT-EMC006	Power Clamp	SCHWARZBECK	MDS-21	3812	2010-4-14	2011-4-13
7	BCT-EMC007	Positioning Controller	C&C	CC-C-1F	MF7802113	N/A	N/A
8	BCT-EMC008	Electrostatic Discharge Simulator	TESEQ	NSG437	125	2010-4-14	2011-4-13
9	BCT-EMC009	Fast Transient Burst Generator	SCHAFFNER	MODULA6150	34572	2010-4-14	2011-4-13
10	BCT-EMC010	Fast Transient Noise Simulator	Noiseken	FNS-105AX	31485	2010-4-14	2011-4-13
11	BCT-EMC011	Color TV Pattern Generator	PHILIPS	PM5418	TM209947	N/A	N/A
12	BCT-EMC012	Power Frequency Magnetic Field Generator	EVERFINE	EMS61000-8K	608002	2010-4-14	2011-4-13
13	BCT-EMC013	N/A	N/A	N/A	N/A	N/A	N/A
14	BCT-EMC014	Capacitive Coupling Clamp	TESEQ	CDN8014	25096	2010-4-14	2011-4-13
15	BCT-EMC015	High Field Biconical Antenna	ELECTRO-METRICS	EM-6913	166	2010-4-14	2012-4-13
16	BCT-EMC016	Log Periodic Antenna	ELECTRO-METRICS	EM-6950	811	2010-4-14	2012-4-13
17	BCT-EMC017	Remote Active Vertical Antenna	ELECTRO-METRICS	EM-6892	304	2010-4-14	2012-4-13
18	BCT-EMC018	TRILOG Broadband Test-Antenna	SCHWARZBECK	VULB9163	9163-324	2010-4-14	2012-4-13
19	BCT-EMC019	Horn Antenna	SCHWARZBECK	BBHA9120A	B08000991-0001	2010-4-14	2012-4-13
20	BCT-EMC020	Teo Line Single Phase Module	SCHWARZBECK	NSLK8128	D-69250	2010-4-14	2011-4-13
21	BCT-EMC021	10dB attenuator	SCHWARZBECK	MTAIMP-136	R65.90.0001#06	2010-4-14	2011-4-13
22	BCT-EMC022	Electric bridge	Zentech	100 LCR METER	803024	N/A	N/A
23	BCT-EMC023	RF Current Probe	FCC	F-33-4	80	2010-4-14	2011-4-13

24	BCT-EMC024	SIGNAL GENERATOR	HP	8647A	3349A02296	2010-4-14	2011-4-13
25	BCT-EMC025	MICROWAVE AMPLIFIER	HP	8349B	2627A00994	2010-4-14	2011-4-13
26	BCT-EMC026	Triple-Loop Antenna	EVERFINE	LLA-2	607004	2010-4-14	2011-4-13
27	BCT-EMC027	CDN	FRANKONIA	M2+M3	A3027019	2010-10-20	2011-10-19
28	BCT-EMC028	6dB Attenuator	FRANKONIA	75-A-FFN-06	1001698	2010-10-20	2011-10-19
29	BCT-EMC029	EMV-Mess-Systeme GMBH	FRANKONIA	FLL-75	1020A1109	2010-10-20	2011-10-19
30	BCT-EMC030	EM Injection Clamp	FCC	F-203I-13mm	91536	2010-10-20	2011-10-19
31	BCT-EMC031	9KHz-2.4GHz Signal generator	MARCONI INSTRUMENTS	2024	112260/042	2010-10-20	2011-10-19

2 - SYSTEM TEST CONFIGURATION

2.1 Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

2.2 EUT Exercise Software

The EUT exercising program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The software offered by manufacturer, can let the EUT being normal operation.

2.3 Equipment Modifications

The EUT tested was not modified by Bontek.

2.4 Basic Test Setup Block Diagram




Figure 1 : Frequencies measured below 1 GHz configuration




Figure 2 : Frequencies measured above 1 GHz configuration

3 – DISTURBANCE VOLTAGE AT THE MAINS TERMINALS

3.1 Measurement Uncertainty

All test results complied with Section 15.207 requirements. Measurement Uncertainty is 2.4 dB.

3.2 Applicable Standard

Section 15.207: For a Low-power Radio-frequency Device is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency Range (MHz)	Limits (dBuV)	
	Quasi-Peak	Average
0.150~0.500	66~56	56~46
0.500~5.000	56	46
5.000~30.00	60	50

3.3 Test Description

The EUT is excused from investigation of Disturbance Voltage at The Mains Terminals, for it is powered by a DC 3V battery. According to the Section 15.207(d), measurement to demonstrate compliance with the limits of Disturbance Voltage at The Mains Terminals are not required to the devices which only employed battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

4- RADIATED DISTURBANCES

4.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ±4.0 dB.

4.2 Limit of Radiated Disturbances

According to 15.231(b), the field strength of emissions from Intentional Radiators operated under this section shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental		Field Strength of Spurious	
	(dBuV/m)	(uV/m)	(dBuV/m)	(uV/m)
40.66 - 40.70	67.04	2,250	47.04	225
70 - 130	61.94	1,250	41.94	125
130 - 174	* 61.94 - 71.48	* 1,250 - 3,750	* 41.94 - 51.48	* 125 - 375
174 - 260	71.48	3,750	51.48	375
260 - 470	* 71.48 - 81.94	* 3,750 - 12,500	* 51.48 - 61.94	* 375 - 1,250
above 470	81.94	12,500	61.94	1,250

** linear interpolations

Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, uV/m at 3 meters = $56.81818(F) - 6136.3636$; for band 260-470 MHz, uV/m at 3 meters = $41.6667(F) - 7083.3333$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]

4.3 EUT Setup

The radiated emission tests were performed in the in the 3-meter Semi-Anechoic Chamber, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC Part 15 Subpart B limits.

The EUT was placed on the center of the test table. In the frequency range below 1 GHz, Ultra-Broadband Antenna horn-antenna is used. In the frequency range above 1 GHz horn-antenna is used. Test setup refer to **Section 2.5 Basic Test Setup Block Diagram** of this report.

Maximum emission emitted from EUT was determined by manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation and the levels in the final result of the test were recorded with the EUT running in the operating mode that maximum emission was emitted.

4.4 Test Receiver Setup

According to FCC Part 15 rule, the frequency was investigated from 30 to 4000 MHz. During the radiated emission test, the test receiver was set with the following configurations:

Test Receiver Setting for frequency range below 1000MHz:

Detector.....Peak & Quasi-Peak
IF Band Width.....100KHz
Frequency Range.....30MHz to 1000MHz
Turntable Rotated.....0 to 360 degrees

Test Receiver Setting for frequency range above 1000MHz:

Detector.....Peak
IF Band Width.....1MHz
Frequency Range.....1000MHz to 4000MHz
Turntable Rotated.....0 to 360 degrees

Antenna Position:

Height.....1m to 4m
Polarity.....Horizontal and Vertical

4.5 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

- 1). Configure the EUT according to ANSI C63.4:2003.
- 2). The EUT was placed on the top of the turntable 0.8 meter above ground.
- 3). The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 4). Power on the EUT and all the supporting units.
- 5). The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 6). The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emission field strength of both horizontal and vertical polarization.
- 7). For each suspected emission, the antenna tower was scanned (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 8). Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode. Then all data was recorded in the peak detection mode. Quasi-peak readings performed only when an emission was found to be marginal (within -10 dB μ V of specification limits), and are distinguished with a "QP" in the data plots.

4.6 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude Indicated reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Transd.}$$

$$\text{Transd.} = \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of $-7\text{dB}\mu\text{V}$ means the emission is $7\text{dB}\mu\text{V}$ below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

4.7 Radiated Emissions Test Result

Temperature (°C) : 22~23	EUT: Remote control
Humidity (%RH) : 50~54	M/N: Pebble-01
Barometric Pressure (mbar) : 950~1000	Operation Condition: Manually activate

Note: In this testing, the EUT was respectively tested in three different orientations. That is:

- (1) EUT was lie vertically, and then its Antenna oriented upward
- (2) EUT was lie vertically, and then its Antenna oriented downward
- (3) EUT was lie flatwise, and then its Antenna oriented to the receiving antenna

The worst test data see following pages

When the EUT was lie flatwise, and its Antenna oriented to the receiving antenna, the worst test data was got as following table.

433.84 MHz Tx in operation							
Maximum Frequency (MHz)	Emission Position and Level				Limit	Margin	
	Polarity	m	Deg°	Transd			
49.231	V	1.50	121.0	20.8	24.61	40.00	15.39
53.732	V	1.85	79.0	21.5	20.56	40.00	19.44
96.456	V	1.20	72.0	23.2	23.45	41.94	18.49
433.84	V	1.25	72.0	23.1	56.23	80.14	23.91
867.78	V	1.00	125.0	23.5	35.67	61.94	26.27
1301.62	V	1.40	74.0	24.1	31.12	61.94	29.70
1735.36	V	1.30	92.0	23.3	32.02	61.94	29.92
2169.28	V	1.24	83.0	23.4	28.42	61.94	33.52
2603.07	V	1.00	125.0	23.6	36.67	61.94	25.27
3036.91	V	1.40	74.0	24.1	34.33	61.94	27.61
3470.75	V	1.35	134.0	23.5	32.13	61.94	29.81
3904.56	V	1.24	56.0	24.8	30.80	61.94	31.14
4338.45	V	1.25	47.0	24.3	34.85	61.94	27.09
Maximum Frequency (MHz)	Emission Position and Level				Limit	Margin	
	Polarity	m	Deg°	Transd			
49.231	H	1.25	135.0	20.8	22.31	40.00	17.69
53.732	H	1.45	129.0	21.5	18.45	40.00	21.55
96.456	H	1.32	96.0	23.2	22.44	41.94	19.50
433.84	H	1.25	32.0	23.1	57.32	80.14	22.42
867.78	H	1.00	125.0	23.5	35.57	61.94	26.37
1301.62	H	1.43	87.0	24.1	31.76	61.94	29.06
1735.36	H	1.65	28.0	24.1	30.33	61.94	30.49
2169.28	H	1.00	125.0	23.6	36.87	61.94	25.07
2603.07	H	1.30	24.0	24.1	33.91	61.94	28.03
3036.99	H	1.00	82.0	24.1	30.42	61.94	31.52
3470.72	H	1.40	63.0	23.7	31.21	61.94	30.73
3904.56	H	1.25	79.0	22.4	30.78	61.94	31.16
4338.45	H	1.57	98.0	23.4	31.51	61.94	30.43

5- 20dB BANDWIDTH

5.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ±4.0 dB.

5.2 Limit of 20dB Bandwidth

In accordance with Part15.231(c), the fundamental frequency bandwidth was kept within 0.25% of the center frequency for devices operating >70MHz and <900MHz.

Fundamental Frequency (MHz)	Limit of 20dB Bandwidth (kHz)
433.84	$433840 \times 0.0025 = 1084.6$

5.3 EUT Setup

The radiated emission tests were performed in the in the 3-meter Semi-Anechoic Chamber, using the setup accordance with the ANSI C63.4-2003.

The EUT was placed on the center of the nonmetal table which is 0.8 meter above a grounded turntable. The turntable can rotate 360 degrees to determine the azimuth of the maximum emission level.

Maximum emission emitted from EUT was determined by manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation and the levels in the final result of the test were recorded with the EUT running in the operating mode that maximum emission was emitted.

5.4 Test Procedure

- 1) Turn on the transmitter, and set it to transmit the pulse train continuously.
- 2) Set Test Receiver into spectrum analyzer mode, Tune the spectrum analyzer to the transmitter carrier frequency, and set the spectrum analyzer resolution bandwidth(RBW) to 100kHz and video bandwidth(VBW) to 100kHz, then select Peak function to scan the channel frequency.
- 3) The 20dB bandwidth was measured and recorded.


Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

5.5 Emissions within Band Edges Test Result

Temperature (°C) : 22~23	EUT: Remote control
Humidity (%RH) : 50~54	M/N: Pebble-01
Barometric Pressure (mbar) : 950~1000	Operation Condition: Manually activate

Test plots see following pages

Fundamental Frequency (MHz)	20dB Bandwidth (kHz)	Maximum Limit (kHz)	Pass/Fail
433.84	50	1084.6	Pass



Date: 11.FEB.2011 18:15:13

6- Duty Cycle

6.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ± 4.0 dB.

6.2 EUT Setup

The radiated emission tests were performed in the in the 3-meter Semi-Anechoic Chamber, using the setup accordance with the ANSI C63.4-2003.

The EUT was placed on the center of the nonmetal table which is 0.8 meter above a grounded turntable. The turntable can rotate 360 degrees to determine the azimuth of the maximum emission level.

6.3 Test Procedure

- 1) The EUT was placed on a turntable which is 0.8m above ground plane.
- 2) Set EUT operating in continuous transmitting mode
- 3) Set Test Receiver into spectrum analyzer mode, Tune the spectrum analyzer to the transmitter carrier frequency, and set the spectrum analyzer resolution bandwidth(RBW) to 1000kHz and video bandwidth(VBW) to 1000kHz, Span was set to 0Hz.
- 4) The Duty Cycle was measured and recorded.


6.4 Measurement Result

Temperature (°C) : 22~23	EUT: Remote control
Humidity (%RH): 50~54	M/N: Pebble-01
Barometric Pressure (mbar): 950~1000	Operation Condition: Normal operating


Test plots see following pages

Total Pulse Time of Transmitter = $5.5 \text{ msec} \times 9 + 0.5 \text{ msec} \times 2 + 32.5 \text{ msec} \times 5 = 213 \text{ msec}$


The Duty Cycle = $213/271.5 = 78.45\%$




Date: 14.FEB.2011 10:07:03



Date: 14.FEB.2011 10:09:47



Date: 14.FEB.2011 10:08:28



Date: 14.FEB.2011 10:09:08

7- Transmission Time

7.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ±4.0 dB.

7.2 EUT Setup

The radiated emission tests were performed in the in the 3-meter Semi-Anechoic Chamber, using the setup accordance with the ANSI C63.4-2003.

The EUT was placed on the center of the nonmetal table which is 0.8 meter above a grounded turntable. The turntable can rotate 360 degrees to determine the azimuth of the maximum emission level.

7.3 Test Procedure

- 3) The EUT was placed on a turntable which is 0.8m above ground plane.
- 4) Set EUT operating in continuous transmitting mode
- 3) Set Test Receiver into spectrum analyzer mode, Tune the spectrum analyzer to the transmitter carrier frequency, and set the spectrum analyzer resolution bandwidth(RBW) to 1000kHz and video bandwidth(VBW) to 1000kHz, Span was set to 0Hz.
- 5) The Transmission time was measured and recorded.

7.4 Limit of Transmission time

In accordance with Part15.231(a)(2), A transmitter activated automatically shall cease transmission within 5 seconds after activation


Fundamental Frequency (MHz)	Limit of Transmission (S)
433.84	5

7.5 Transmission Time Test Result

Temperature (°C) : 22~23	EUT: Remote control
Humidity (%RH): 50~54	M/N: Pebble-01
Barometric Pressure (mbar): 950~1000	Operation Condition: Normal

Test plots see following pages

Fundamental Frequency (MHz)	Transmission time (S)	Maximum Limit (S)	Pass/Fail
433.84	0.670	5	Pass



8- ANTENNA REQUIREMENT

8.1 Standard Applicable

Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

8.2 Antenna Connected Construction

The antenna connector is designed with permanent attachment and no consideration of replacement.