

Champion Power Equipment, Inc.

MPE ASSESSMENT REPORT

Report Type:

FCC Part §2.1091, §2.1093 and §1.1307(b) assessment report

Model:

CPEWIFI02

REPORT NUMBER:

230700097SHA-002

ISSUE DATE:

February 25, 2025

DOCUMENT CONTROL NUMBER:

TTRFFCCMPE-01_V1 © 2018 Intertek



Applicant: Champion Power Equipment, Inc.
6370 S Pioneer Way, Unit 101. Las Vegas, NV 89113

Manufacturer: Chongqing Guangxun iControl Technology Co., Ltd
Building 12, 126 Yunan Avenue, Banan District, Chongqing

Product Name: WiFi Module

Type/Model: CPEWIFI02

FCC ID: YA3-CPEWIFI02

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06
FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

PREPARED BY:

Justin Wu

Project Engineer
Justin Wu

REVIEWED BY:

Wakeyou

Reviewer
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Revision History

Report No.	Version	Description	Issued Date
230700097SHA-002	Rev. 01	Initial issue of report	February 25, 2025

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	WiFi Module
Type/Model:	CPEWIFI02
Description of EUT:	The EUT is a WiFi Module which supports 802.11 b/g/n mode, it has only one model.
Rating:	DC 3.3V
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Product Marketing Name:	CPEWIFI02
HVIN:	CPEWIFI02
Software Version:	/
Hardware Version:	/
Serial numbers:	0230705-55-001(for radiation sample), 0230705-55-002(for conduction sample)
Sample received date:	July 5, 2023
Date of test:	July 25, 2023 ~ September 12, 2023

1.2 Technical Specification

Frequency Band:	2400MHz ~ 2483.5MHz
Support Standards:	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n(HT20)
Type of Modulation:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n(HT20): OFDM (64-QAM, 16-QAM, QPSK, BPSK)
Operating Frequency:	2412MHz to 2462MHz for IEEE 802.11b/g/n(HT20)
Channel Number:	11 Channels for 802.11b, 802.11g ,802.11n(HT20)
Channel Separation:	5 MHz
Antenna Information:	5.57dBi

TEST REPORT

1.3 Description of Test Facility

Name:	Intertek Testing Services (Shanghai FTZ) Co.,Ltd.
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L21189
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

TEST REPORT

2 MPE Assessment

Test result: Pass

2.1 MPE Assessment Limit

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=Frequency in MHz; *Plane-wave equivalent power density

Mobile device exposure for simultaneous transmission operations: **the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0**

2.2 Assessment Results

Power density (S) is calculated according to the formula:

$$S = PG / (4\pi R^2)$$

Where S = power density in mW/cm²

P = Radiated transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

As we can see from the test report 230700097SHA-001:

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

Working Mode	Frequency band	Power		Antenna Gain	R	S	Limits
	(MHz)	dBm	mW	dBi	(cm)	(mW/cm ²)	(mW/cm ²)
2.4G WIFI	2412-2462	20.65	116.145	5.57	20	0.1288	1

Note: 1 mW/cm² from 1.310 Table 1.

Conclusion: therefore, the maximum calculations of the above simultaneous are less the limit.

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.

*****END*****