



Neutron Engineering Inc.

# FCC Radio Test Report

FCC ID: YAE-MX168

This report concerns (check one) :  Original Grant  Class II Change

Issued Date : Nov. 15, 2010  
Project No. : 0906C066C  
Equipment : Dongle  
Model Name : MX-168

Applicant : Ergowerx International LLC  
Address : 39 Park Place Suite 201, Englewood, NJ 07631 USA  
Manufacturer : Shenzhen Fuyeda Industry Development Corp.,Ltd.  
Address : NO.1, NEWMEN ROAD, TONGSHENG VILLAGE,  
DALANG STREET, BAO'AN, SHENZHEN, CHINA


**Tested by:**


Neutron Engineering Inc. EMC Laboratory


**Date of Receipt:** Nov. 08, 2010

**Date of Test:**

Nov. 08, 2010 ~ Nov. 14, 2010

Testing Engineer :   
(Ivan Cao)

Technical Manager :   
(Leo Hung)

Authorized Signatory :   
(Steven Lu)

Neutron Engineering Inc.

No.3, Jinshagang 1st Road, ShiXia, Dalang  
Town, Dong Guan, China.  
TEL : (0769) 8318-3000 FAX : (0769) 8319-6000



## Declaration

**Neutron** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C.**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

**Neutron**'s reports apply only to the specific samples tested under conditions. It is manufacturer's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

**Neutron**'s reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron**'s authorized written approval.

**Neutron**'s laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

## Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.



Table of Contents	Page
<b>1 . CERTIFICATION</b>	<b>6</b>
<b>2 . SUMMARY OF TEST RESULTS</b>	<b>7</b>
<b>2.1 TEST FACILITY</b>	<b>8</b>
<b>2.2 MEASUREMENT UNCERTAINTY</b>	<b>8</b>
<b>3 . GENERAL INFORMATION</b>	<b>9</b>
<b>3.1 GENERAL DESCRIPTION OF EUT</b>	<b>9</b>
<b>3.2 DESCRIPTION OF TEST MODES</b>	<b>11</b>
<b>3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING</b>	<b>11</b>
<b>3.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED</b>	<b>12</b>
<b>3.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)</b>	<b>13</b>
<b>4 . EMC EMISSION TEST</b>	<b>14</b>
<b>4.1 CONDUCTED EMISSION MEASUREMENT</b>	<b>14</b>
<b>4.1.1 POWER LINE CONDUCTED EMISSION LIMITS</b>	<b>14</b>
<b>4.1.2 MEASUREMENT INSTRUMENTS LIST AND SETTING</b>	<b>14</b>
<b>4.1.3 TEST PROCEDURE</b>	<b>14</b>
<b>4.1.4 DEVIATION FROM TEST STANDARD</b>	<b>15</b>
<b>4.1.5 TEST SETUP</b>	<b>15</b>
<b>4.1.6 EUT OPERATING CONDITIONS</b>	<b>15</b>
<b>4.1.7 TEST RESULTS</b>	<b>16</b>
<b>4.2 RADIATED EMISSION MEASUREMENT</b>	<b>18</b>
<b>4.2.1 RADIATED EMISSION LIMITS</b>	<b>18</b>
<b>4.2.2 MEASUREMENT INSTRUMENTS LIST ANS SETTING</b>	<b>19</b>
<b>4.2.3 TEST PROCEDURE</b>	<b>21</b>
<b>4.2.4 DEVIATION FROM TEST STANDARD</b>	<b>21</b>
<b>4.2.5 TEST SETUP</b>	<b>22</b>
<b>4.2.6 EUT OPERATING CONDITIONS</b>	<b>22</b>
<b>4.2.7 TEST RESULTS (BETWEEN30 – 1000 MHZ)</b>	<b>23</b>
<b>4.2.8 TEST RESULTS (ABOVE 1000 MHZ)</b>	<b>25</b>
<b>5 . NUMBER OF HOPPING CHANNEL</b>	<b>37</b>
<b>5.1 APPLIED PROCEDURES / LIMIT</b>	<b>37</b>
<b>5.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING</b>	<b>37</b>
<b>5.1.2 TEST PROCEDURE</b>	<b>37</b>
<b>5.1.3 DEVIATION FROM STANDARD</b>	<b>37</b>
<b>5.1.4 TEST SETUP</b>	<b>37</b>
<b>5.1.5 EUT OPERATION CONDITIONS</b>	<b>37</b>
<b>5.1.6 TEST RESULTS</b>	<b>38</b>



Table of Contents	Page
<b>6 . AVERAGE TIME OF OCCUPANCY</b>	<b>39</b>
<b>6.1 APPLIED PROCEDURES / LIMIT</b>	<b>39</b>
<b>6.1.1 MEASUREMENT INSTRUMENTS LIST</b>	<b>39</b>
<b>6.1.2. TEST PROCEDURES</b>	<b>39</b>
<b>6.1.3. TEST SETUP LAYOUT</b>	<b>39</b>
<b>6.1.4. TEST DEVIATION</b>	<b>39</b>
<b>6.1.5. EUT OPERATION DURING TEST</b>	<b>39</b>
<b>6.1.6. TEST RESULTS</b>	<b>40</b>
<b>7 . HOPPING CHANNEL SEPARATION MEASUREMENT</b>	<b>41</b>
<b>7.1 APPLIED PROCEDURES / LIMIT</b>	<b>41</b>
<b>7.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING</b>	<b>41</b>
<b>7.1.2 TEST PROCEDURE</b>	<b>41</b>
<b>7.1.3 DEVIATION FROM STANDARD</b>	<b>41</b>
<b>7.1.4 TEST SETUP</b>	<b>41</b>
<b>7.1.5 EUT OPERATION CONDITIONS</b>	<b>41</b>
<b>7.1.6 TEST RESULTS</b>	<b>42</b>
<b>8 . BANDWIDTH TEST</b>	<b>44</b>
<b>8.1 APPLIED PROCEDURES / LIMIT</b>	<b>44</b>
<b>8.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING</b>	<b>44</b>
<b>8.1.2 TEST PROCEDURE</b>	<b>44</b>
<b>8.1.3 DEVIATION FROM STANDARD</b>	<b>44</b>
<b>8.1.4 TEST SETUP</b>	<b>44</b>
<b>8.1.5 EUT OPERATION CONDITIONS</b>	<b>44</b>
<b>8.1.6 TEST RESULTS</b>	<b>45</b>
<b>9 . PEAK OUTPUT POWER TEST</b>	<b>47</b>
<b>9.1 APPLIED PROCEDURES / LIMIT</b>	<b>47</b>
<b>9.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING</b>	<b>47</b>
<b>9.1.2 TEST PROCEDURE</b>	<b>47</b>
<b>9.1.3 DEVIATION FROM STANDARD</b>	<b>47</b>
<b>9.1.4 TEST SETUP</b>	<b>47</b>
<b>9.1.5 EUT OPERATION CONDITIONS</b>	<b>47</b>
<b>9.1.6 TEST RESULTS</b>	<b>48</b>
<b>10 . ANTENNA CONDUCTED SPURIOUS EMISSION</b>	<b>50</b>
<b>10.1 APPLIED PROCEDURES / LIMIT</b>	<b>50</b>
<b>10.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING</b>	<b>50</b>
<b>10.1.2 TEST PROCEDURE</b>	<b>50</b>
<b>10.1.3 DEVIATION FROM STANDARD</b>	<b>50</b>
<b>10.1.4 TEST SETUP</b>	<b>51</b>
<b>10.1.5 EUT OPERATION CONDITIONS</b>	<b>51</b>



Table of Contents	Page
<b>10.1.6 TEST RESULTS</b>	<b>52</b>
<b>11 . EUT TEST PHOTO</b>	<b>58</b>



## **1. CERTIFICATION**

Equipment : Dongle

Brand Name : Smartfish

Model Name : MX-168

Applicant: Ergowerx International LLC

Factory: Shenzhen Fuyeda Industry Development Corp.,Ltd.

Address: NO.1,NEWMEN ROAD,TONGSHENG VILLAGE,DALANG STREET,BAO'AN, SHENZHEN, CHINA

Date of Test : Nov. 08, 2010 ~ Nov. 14, 2010

Test Item: ENGINEERING SAMPLE

Standards: FCC Part15, Subpart C(15.247) / ANSI C63.4 : 2003

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-1-0906C066C) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of NVLAP and TAF according to the ISO-17025 quality assessment standard and technical standard(s).



## 2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

<b>FCC Part15 (15.247) , Subpart C</b>			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247(d)	Antenna conducted Spurious Emission	PASS	
15.247 (a)(1)	Hopping Channel Separation	PASS	
15.247 (b)(1)	Peak Output Power	PASS	
15.247(d) 15.209	Radiated Spurious Emission	PASS	
15.247 (a)(1)(iii)	Number of Hopping Frequency	PASS	
15.247 (a)(1)(iii)	Dwell Time	PASS	
15.205	Restricted Bands	PASS	
15.203	Antenna Requirement	PASS	
1.1307 1.1310 2.1091 2.1093	RF Exposure Compliance	PASS	

**NOTE:**

(1)" N/A" denotes test is not applicable in this Test Report



## 2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-C02/CB03** at the location of No.3,Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.523792  
Neutron's test firm number is 319330

## 2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**, providing a level of confidence of approximately **95 %** .

### A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U , (dB)	NOTE
DG-C02	CISPR	150 KHz ~ 30MHz	1.94	

### B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U , (dB)	NOTE
CB03	CISPR	30MHz ~ 200MHz	V	3.82	
		30MHz ~ 200MHz	H	3.60	
		200MHz ~ 1,000MHz	V	3.86	
		200MHz ~ 1,000MHz	H	3.94	



### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

Equipment	Dongle												
Trade Name	Smartfish												
Model Name	MX-168												
OEM Brand/Model Name	N/A												
Model Difference	N/A												
Product Description	<p>The EUT is a Dongle</p> <table border="1"><tr><td>Operation Frequency:</td><td>2405~2476 MHz</td></tr><tr><td>Modulation Type:</td><td>GFSK</td></tr><tr><td>Number Of Channel</td><td>64CH .Please see Note 2.</td></tr><tr><td>Antenna Designation:</td><td>Please see Note 3.</td></tr><tr><td>Antenna Gain(Peak)</td><td>Please see Note 3.</td></tr><tr><td>Output Power:</td><td>-2.68 dBm</td></tr></table> <p>Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.</p>	Operation Frequency:	2405~2476 MHz	Modulation Type:	GFSK	Number Of Channel	64CH .Please see Note 2.	Antenna Designation:	Please see Note 3.	Antenna Gain(Peak)	Please see Note 3.	Output Power:	-2.68 dBm
Operation Frequency:	2405~2476 MHz												
Modulation Type:	GFSK												
Number Of Channel	64CH .Please see Note 2.												
Antenna Designation:	Please see Note 3.												
Antenna Gain(Peak)	Please see Note 3.												
Output Power:	-2.68 dBm												
Channel List	Please refer to the Note 2.												
Power Source	DC Voltage supplied from Host system												
Power Rating	I/P 120V/60Hz O/P DC 5V												
Connecting I/O Port(s)	Please refer to the User's Manual												
Products Covered	N/A												
EUT Modification(s)	N/A												

**Note:**

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2405	28	2435	55	2467
02	2406	29	2436	56	2468
03	2407	30	2437	57	2469
04	2408	31	2438	58	2470
05	2409	32	2439	59	2471
06	2410	33	2442	60	2472
07	2411	34	2443	61	2473
08	2412	35	2444	62	2474
09	2413	36	2446	63	2475
10	2414	37	2447	64	2476
11	2415	38	2448		
12	2416	39	2449		
13	2417	40	2451		
14	2418	41	2452		
15	2419	42	2453		
16	2420	43	2455		
17	2421	44	2456		
18	2422	45	2457		
19	2423	46	2458		
20	2425	47	2459		
21	2427	48	2460		
22	2428	49	2461		
23	2429	50	2462		
24	2430	51	2463		
25	2431	52	2464		
26	2432	53	2465		
27	2434	54	2466		

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Printed Antenna	N/A	1.86



## 3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH Lower - 2405MHz
Mode 2	CH Middle - 2439MHz
Mode 3	CH Highest -2476MHz
Mode 4	Normal Link with Mouse; but Mouse Sample is not requested by application

For Conducted Emission	
Final Test Mode	Description
Mode 4	Normal Link with Mouse; but Mouse Sample is not requested by application

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH Lower - 2405MHz
Mode 2	CH Middle - 2439MHz
Mode 3	CH Highest -2476MHz

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.


## 3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test software Version	Test program: Hardware control		
Frequency	2405 MHz	2439MHz	2476MHz
Parameters(1Mbps)	N/A	N/A	N/A



**3.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED**



**3.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	Dongle	Smartfish	MX-168	YAE-MX168	N/A	EUT
E-2	NOTEBOOK	DELL	1420	DOC	N/A	

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



## 4. EMC EMISSION TEST

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

### 4.1.2 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	EMCO	3816/2	00052765	May.26.2011
2	LISN	Rolf Heine	NNB-2-16Z	99044	May.26.2011
3	50Ω Terminator	SHX	TF2-3G-A	08122901	May.26.2011
4	Transient Limiter	Agilent	11947A	3107A03668	May.26.2011
5	Test Cable	N/A	C-06_C03	N/A	Nov.16.2010
6	EMI TEST RECEIVER	R&S	ESCS30	8333641017	May.26.2011

Remark: " N/A" denotes No Model No. , Serial No. or No Calibration specified.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

### 4.1.3 TEST PROCEDURE



## Neutron Engineering Inc.


The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation

### 4.1.5 TEST SETUP



**Note:** 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

### 4.1.6 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


**4.1.7 TEST RESULTS**

EUT :	Dongle	Model Name :	MX-168
Temperature :	23 °C	Relative Humidity :	44 %
Pressure :	1010 hPa	Test Power :	AC 120V/60Hz
Test Mode :	Normal Link		

Freq. (MHz)	Terminal L/N	Measured(dBuV)		Limits(dBuV)		Margin (dB)	Note
		QP-Mode	AV-Mode	QP-Mode	AV-Mode		
0.19	Line	43.60	*	64.02	54.02	-20.42	(QP)
0.25	Line	38.77	*	61.60	51.60	-22.83	(QP)
0.39	Line	35.56	*	58.15	48.15	-22.59	(QP)
0.70	Line	35.49	*	56.00	46.00	-20.51	(QP)
1.41	Line	36.66	*	56.00	46.00	-19.34	(QP)
14.65	Line	38.06	*	60.00	50.00	-21.94	(QP)

**Remark**

- (1) All readings are QP Mode value unless otherwise stated AVG in column of『Note』. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform. In this case, a “\*” marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.






EUT :	Dongle	Model Name :	MX-168
Temperature :	23 °C	Relative Humidity :	44 %
Pressure :	1010 hPa	Test Power :	AC 120V/60Hz
Test Mode :	Normal Link		

Freq. (MHz)	Terminal L/N	Measured(dBuV)		Limits(dBuV)		Margin (dB)	Note
		QP-Mode	AV-Mode	QP-Mode	AV-Mode		
0.19	Neutral	42.67	*	64.04	54.04	-21.37	(QP)
0.25	Neutral	39.20	*	61.63	51.63	-22.43	(QP)
0.40	Neutral	33.34	*	57.90	47.90	-24.56	(QP)
0.97	Neutral	33.35	*	56.00	46.00	-22.65	(QP)
4.29	Neutral	36.11	*	56.00	46.00	-19.89	(QP)
19.12	Neutral	38.05	*	60.00	50.00	-21.95	(QP)

**Remark**

- (1) All readings are QP Mode value unless otherwise stated AVG in column of "Note". If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform. In this case, a " \* " marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.





## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

### FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 <sup>th</sup> harmonic of the highest frequency or 40 GHz, whichever is lower

**4.2.2 MEASUREMENT INSTRUMENTS LIST AND SETTING**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	ETS	3115	00075789	May.12.2011
2	Amplifier	Agilent	8449B	3008A02274	May.26.2011
3	Spectrum	Agilent	E4408B	US39240143	Nov.16.2010
4	Test Cable	HUBER+SUHNER	CB03 High Fre	N/A	May.03.2011
5	Antenna	Schwarbeck	VULB9160	9160-3232	May.26.2011
6	Amplifier	HP	8447D	2944A09673	May.26.2011
7	Test Receiver	R&S	ESCI	100895	May.26.2011
8	Test Cable	N/A	C-01_CB03	N/A	May.26.2011
9	Controller	CT	SC100	N/A	N/A

Remark: " N/A " denotes No Model Name / Serial No. and No Calibration specified.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, Average=PK-dycty cycle

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



DUTY CYCLE : TX 2405MHz (1Mbps)

Dwell time=ON/ON+OFF


ON:0.40msec

ON+OFF:(total time):8.80msec

Dwell time:4.5%

AV=PK+20 log(Dwell time)

AV=PK-26.85





#### **4.2.3 TEST PROCEDURE**


- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### **4.2.4 DEVIATION FROM TEST STANDARD**


No deviation

#### 4.2.5 TEST SETUP

##### (A) Radiated Emission Test Set-Up Frequency Below 1 GHz



##### (B) Radiated Emission Test Set-Up Frequency Above 1 GHz



#### 4.2.6 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.


**4.2.7 TEST RESULTS (BETWEEN30 – 1000 MHZ)**

EUT :	Dongle	Model Name :	MX-168
Temperature :	23 °C	Relative Humidity :	44 %
Pressure :	1010 hPa	Test Power :	AC 120V/60Hz
Test Mode :	TX Mode 2439MHz		

Freq. (MHz)	Ant. H/V	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
114.90	V	38.87	-20.24	18.63	43.50	- 24.87	
190.10	V	39.70	-18.20	21.50	43.50	- 22.00	
296.80	V	39.91	-13.86	26.05	46.00	- 19.95	
408.30	V	31.22	-10.60	20.62	46.00	- 25.38	
490.80	V	31.06	-8.93	22.13	46.00	- 23.87	
590.20	V	31.19	-6.43	24.76	46.00	- 21.24	

Remark :

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz .
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (3) Measuring frequency range from 30MHz to 1000MHz .
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table .






EUT :	Dongle	Model Name :	MX-168
Temperature :	23 °C	Relative Humidity :	44 %
Pressure :	1010 hPa	Test Power :	AC 120V/60Hz
Test Mode :	T TX Mode 2439MHz		

Freq. (MHz)	Ant. H/V	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
119.70	H	31.21	-20.53	10.68	43.50	- 32.82	
216.70	H	39.52	-17.01	22.51	46.00	- 23.49	
328.30	H	30.33	-12.55	17.78	46.00	- 28.22	
442.30	H	30.29	-10.14	20.15	46.00	- 25.85	
524.70	H	30.80	-7.93	22.87	46.00	- 23.13	
626.60	H	27.27	-4.95	22.32	46.00	- 23.68	

**Remark :**

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz.
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (3) Measuring frequency range from 30MHz to 1000MHz.
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table.



**4.2.8 TEST RESULTS (ABOVE 1000 MHZ)**

EUT :	Dongle	Model Name :	MX-168
Temperature :	23 °C	Relative Humidity :	44 %
Pressure :	1010 hPa	Test Power :	AC 120V/60Hz
Test Mode :	TX 2405MHz		



Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2390.00	V	16.25	-10.60	32.32	48.57	21.72	74.00	54.00	X/E
<b>2405.00</b>	<b>V</b>	<b>53.89</b>	<b>27.04</b>	<b>32.36</b>	<b>86.25</b>	<b>59.40</b>	<b>114.00</b>	<b>94.00</b>	<b>X/F</b>
4811.03	V	49.32	22.47	4.47	53.79	26.84	74.00	54.00	X/H

**Remark :**

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis :  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The average value of fundamental frequency is:  
Average = Peak value + 20log(Duty cycle) , Final AV=PK-26.85



**TX CH01(Above 1000 MHz, Vertical)**





EUT :	Dongle	Model Name :	MX-168
Temperature :	23 °C	Relative Humidity :	44 %
Pressure :	1010 hPa	Test Power :	AC 120V/60Hz
Test Mode :	TX 2405MHz		



Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2390.00	H	16.75	-10.10	32.32	49.07	22.22	74.00	54.00	X/E
<b>2405.30</b>	<b>H</b>	<b>55.55</b>	<b>28.70</b>	<b>32.36</b>	<b>87.91</b>	<b>61.06</b>	<b>114.00</b>	<b>94.00</b>	<b>X/F</b>
4810.58	H	50.81	23.96	4.46	55.27	28.42	74.00	54.00	X/H

#### Remark :

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis :  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The average value of fundamental frequency is:  
Average = Peak value + 20log(Duty cycle) , Final AV=PK-26.85



**TX CH01(Above 1000 MHz, Horizontal)**





EUT :	Dongle	Model Name :	MX-168
Temperature :	23 °C	Relative Humidity :	44 %
Pressure :	1010 hPa	Test Power :	AC 120V/60Hz
Test Mode :	TX 2439MHz		



Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2439.40	V	52.00	25.15	32.49	84.49	57.64	114.00	94.00	X/F
4879.52	V	51.38	24.53	4.69	56.07	29.22	74.00	54.00	X/H

**Remark :**

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis :  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The average value of fundamental frequency is:  
Average = Peak value + 20log(Duty cycle) , Final AV=PK-26.85



**TX CH32 (Above 1000 MHz, Vertical)**





EUT :	Dongle	Model Name :	MX-168
Temperature :	23 °C	Relative Humidity :	44 %
Pressure :	1010 hPa	Test Power :	AC 120V/60Hz
Test Mode :	TX 2439MHz		



Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2439.40	H	52.46	25.61	32.49	84.95	58.10	114.00	94.00	X/F
4879.36	H	51.04	24.19	4.69	55.73	28.88	74.00	54.00	X/H

**Remark :**

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis :  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The average value of fundamental frequency is:  
Average = Peak value + 20log(Duty cycle) , Final AV=PK-26.85



**TX CH32 (Above 1000 MHz, Horizontal)**





EUT :	Dongle	Model Name :	MX-168
Temperature :	23 °C	Relative Humidity :	44 %
Pressure :	1010 hPa	Test Power :	AC 120V/60Hz
Test Mode :	TX 2476MHz		



Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
<b>2476.40</b>	<b>V</b>	<b>52.71</b>	<b>25.86</b>	<b>32.61</b>	<b>85.32</b>	<b>58.47</b>	<b>114.00</b>	<b>94.00</b>	X/F
2483.50	V	34.38	7.53	32.63	67.01	40.16	74.00	54.00	X/E
4953.51	V	53.37	26.52	4.93	58.30	31.45	74.00	54.00	X/H

**Remark :**

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis :  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The average value of fundamental frequency is:  
Average = Peak value + 20log(Duty cycle) , Final AV=PK-26.85



**TX CH64 (Above 1000 MHz, Vertical)**






EUT :	Dongle	Model Name :	MX-168
Temperature :	23 °C	Relative Humidity :	44 %
Pressure :	1010 hPa	Test Power :	AC 120V/60Hz
Test Mode :	TX 2476MHz		

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2476.00	H	54.91	28.06	32.61	87.52	60.67	114.00	94.00	X/F
2483.50	H	38.18	11.33	32.63	70.81	43.96	74.00	54.00	X/E
4953.79	H	50.41	23.56	4.93	55.34	28.49	74.00	54.00	X/H

**Remark :**

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " \* " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis :  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The average value of fundamental frequency is:  
Average = Peak value + 20log(Duty cycle) → Final AV=PK-26.85





## 5. NUMBER OF HOPPING CHANNEL

### 5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Number of Hopping Channel	2400-2483.5	PASS

#### 5.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.27.2010

Remark: " N/A" denotes No Model Name , Serial No. or No Calibration specified.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

#### 5.1.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

#### 5.1.3 DEVIATION FROM STANDARD

No deviation.

#### 5.1.4 TEST SETUP



#### 5.1.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.



## 5.1.6 TEST RESULTS

EUT :	Dongle	Model Name :	MX-168
Temperature :	23 °C	Relative Humidity :	44 %
Pressure :	1010 hPa	Test Power :	AC 120V/60Hz
Test Mode :	Hopping Mode		

Number of Hopping Channel	64
---------------------------	----





## 6. AVERAGE TIME OF OCCUPANCY

### 6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

#### 6.1.1 MEASUREMENT INSTRUMENTS LIST


Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.27.2010

Remark: " N/A" denotes No Model Name , Serial No. or No Calibration specified.

#### 6.1.2. TEST PROCEDURES

- a. The transmitter output (antenna port) was connected to the spectrum analyzer
- b. Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- d. Sweep Time is more than once pulse time.
- e. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- f. Measure the maximum time duration of one single pulse.
- g. Set the EUT for packet transmitting.
- h. Measure the maximum time duration of one single pulse.
- i. Dwell time = [spreading rate/64] x duty-cycle x 0.4 seconds

#### 6.1.3. TEST SETUP LAYOUT



#### 6.1.4. TEST DEVIATION

There is no deviation with the original standard.

#### 6.1.5. EUT OPERATION DURING TEST

The EUT was programmed to be in continuously transmitting/Hopping mode.




## 6.1.6. TEST RESULTS

EUT :	Dongle	Model Name :	MX-168
Temperature :	23 °C	Relative Humidity :	44 %
Pressure :	1010 hPa	Test Power :	AC 120V/60Hz
Test Mode :	Hopping Mode		

Data Packet	90% OBW (MHz)	Duty cycle (%)	Dwell Time (s)	Limits (s)
Hooping	62.275	0.0455	0.0177	0.4000

NOTE: For the test plots please refer to the below pages.





## 7. HOPPING CHANNEL SEPARATION MEASUREMENT

### 7.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

#### 7.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.27.2010

Remark: " N/A" denotes No Model Name , Serial No. or No Calibration specified.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	10 kHz (20dB Bandwidth) / 30 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


#### 7.1.2 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for 20 dB bandwidth measurement.
- The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for channel separation measurement.

#### 7.1.3 DEVIATION FROM STANDARD

No deviation.

#### 7.1.4 TEST SETUP



#### 7.1.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.






### 7.1.6 TEST RESULTS

EUT :	Dongle	Model Name :	MX-168
Temperature :	23 °C	Relative Humidity :	44 %
Pressure :	1010 hPa	Test Power :	AC 120V/60Hz
Test Mode :	CH01 / CH32/ CH64		

Frequency	Ch. Separation (MHz)	20dB Bandwidth (MHz)	Result
2405 MHz	1	0.673	Complies
2439 MHz	1	0.673	Complies
2476 MHz	1	0.480	Complies

Ch. Separation Limits: >20dB bandwidth or >2/3 of 20dB bandwidth







## 8. BANDWIDTH TEST

### 8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(2)	Bandwidth	<= 1 MHz (20dB bandwidth)	2400-2483.5	PASS

#### 8.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.27.2010

Remark: " N/A" denotes No Model Name , Serial No. or No Calibration specified.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	10 kHz (20dB Bandwidth) / 30 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

#### 8.1.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 10KHz, VBW=100KHz, Sweep time = Auto.

#### 8.1.3 DEVIATION FROM STANDARD

No deviation.

#### 8.1.4 TEST SETUP



#### 8.1.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.





## 8.1.6 TEST RESULTS

EUT :	Dongle	Model Name :	MX-168
Temperature :	23 °C	Relative Humidity :	44 %
Pressure :	1010 hPa	Test Power :	AC 120V/60Hz
Test Mode :	CH01 / CH32 /CH64		

Frequency	20dB Bandwidth (MHz)	Channel Separation (MHz)	Result
2405 MHz	0.673	<= 1MHz	PASS
2439 MHz	0.673	<= 1MHz	PASS
2476 MHz	0.480	<= 1MHz	PASS







## 9. PEAK OUTPUT POWER TEST

### 9.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (b)(1)	Peak Output Power	0.125 watt or 21dBm	2400-2483.5	PASS

#### 9.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.27.2010

Remark: " N/A " denotes No Model Name , Serial No. or No Calibration specified.

#### 9.1.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 1MHz, VBW= 1MHz, Sweep time = Auto.

#### 9.1.3 DEVIATION FROM STANDARD

No deviation.

#### 9.1.4 TEST SETUP



#### 9.1.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.





### 9.1.6 TEST RESULTS

EUT :	Dongle	Model Name :	MX-168
Temperature :	23 °C	Relative Humidity :	44 %
Pressure :	1010 hPa	Test Power :	AC 120V/60Hz
Test Mode :	CH01/ CH32 /CH64		

Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH01	2405	-2.90	21	0.125
CH32	2439	-2.68	21	0.125
CH64	2476	-2.90	21	0.125







## 10. ANTENNA CONDUCTED SPURIOUS EMISSION

### 10.1 APPLIED PROCEDURES / LIMIT

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### 10.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.27.2010

Remark: " N/A" denotes No Model Name , Serial No. or No Calibration specified.

The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (other emission)	100 KHz /100 KHz for Peak

#### 10.1.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

#### 10.1.3 DEVIATION FROM STANDARD

No deviation.



#### **10.1.4 TEST SETUP**





#### **10.1.5 EUT OPERATION CONDITIONS**


The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.



**10.1.6 TEST RESULTS**



EUT :	Dongle	Model Name :	MX-168
Temperature :	23 °C	Relative Humidity :	44 %
Pressure :	1010 hPa	Test Power :	AC 120V/60Hz
Test Mode :	CH01 / CH32 / CH64 & Hopping Mode		



The max. radio frequency power in any 100kHz bandwidth outside the frequency band		The max. radio frequency power in any 100 kHz bandwidth within the frequency band.	
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)
2348.71	-47.63	2483.50	-48.87
Result			
In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.			













**11. EUT TEST PHOTO**

**CONDUCTED MEASUREMENT PHOTOS**





**Radiated Measurement Photos**

