

## RF Test Report

Applicant : InnoComm Mobile Technology Corporation  
Product Type : Wireless Audio Module  
Trade Name : InnoComm  
Model Number : WB15  
Applicable Standard : FCC 47 CFR PART 15 SUBPART C  
ANSI C63.10:2013  
Received Date : Jul. 08, 2020  
Test Period : Jul. 21~ Oct. 21, 2020  
Issued Date : Oct. 30, 2020

### Issued by

A Test Lab Techno Corp.  
No. 140-1, Changan Street, Bade District,  
Taoyuan City 33465, Taiwan (R.O.C.)  
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330  
Frequency Range : 9 kHz to 40 GHz  
Test Firm MRA designation number: TW0010

#### Note:

- 1.The test results are valid only for samples provided by customers and under the test conditions described in this report.
- 2.This report shall not be reproduced except in full, without the written approval of A Test Lab Technology Corporation.
- 3.The relevant information is provided by customers in this test report. According to the correctness, appropriateness or completeness of the information provided by the customer, if there is any doubt or error in the information which affects the validity of the test results, the laboratory does not take the responsibility.

### Revision History

Rev.	Issued Date	Revisions	Revised By
00	Oct. 30, 2020	Initial Issue	Yu Chiang

## Verification of Compliance

Applicant : InnoComm Mobile Technology Corporation  
Product Type : Wireless Audio Module  
Trade Name : InnoComm  
Model Number : WB15  
FCC ID : YAIWB15  
EUT Rated Voltage : DC 5.0 V  
Test Voltage : 120 Vac / 60 Hz  
Applicable Standard : FCC 47 CFR PART 15 SUBPART C  
ANSI C63.10:2013  
Test Result : Complied  
Performing Lab. : A Test Lab Techno Corp.  
No. 140-1, Changan Street, Bade District,  
Taoyuan City 33465, Taiwan (R.O.C.)  
Tel : +886-3-2710188 / Fax : +886-3-2710190  
Taiwan Accreditation Foundation accreditation number: 1330  
<http://www.atl-lab.com.tw/e-index.htm>



A Test Lab Techno Corp. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by A Test Lab Techno Corp. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Approved By :   
(Manager) ( Jeremy Lin )

## TABLE OF CONTENTS

<b>1</b>	<b>General Information.....</b>	<b>5</b>
1.1.	Summary of Test Result.....	5
1.2.	Measurement Uncertainty.....	6
<b>2</b>	<b>EUT Description.....</b>	<b>7</b>
<b>3</b>	<b>Test Methodology .....</b>	<b>8</b>
3.1.	Mode of Operation.....	8
3.2.	EUT Test Step.....	8
3.3.	Configuration of Test System Details .....	9
3.4.	Test Instruments .....	11
3.5.	Test Site Environment.....	12
<b>4</b>	<b>Measurement Procedure .....</b>	<b>13</b>
4.1.	Maximum Conducted Output Power Measurement .....	13
4.2.	AC Power Line Conducted Emission Measurement .....	14
4.3.	Radiated Emission Measurement.....	16
4.4.	20 dB RF Bandwidth Measurement .....	19
4.5.	Carrier Frequency Separation Measurement.....	20
4.6.	Number of Hopping Measurement.....	21
4.7.	Time of Occupancy (Dwell Time) Measurement .....	22
4.8.	Out of Band Conducted Emissions Measurement .....	23
4.9.	Antenna Measurement .....	23
<b>5</b>	<b>Test Results .....</b>	<b>24</b>
	Annex A. Conducted Emission.....	24
	Annex B. Conducted Test Results.....	26
	Annex C. Radiated Emission Measurement .....	44

## 1 General Information

### 1.1. Summary of Test Result

Standard	Item	Result	Remark
15.207	AC Power Conducted Emission	PASS	-----
15.203	Antenna Requirement	PASS	-----
15.247(b)(1)	Max. Output Power	PASS	-----
15.247(d)	Transmitter Radiated Emissions	PASS	-----
15.247(a)(1)	20 dB RF Bandwidth	PASS	-----
15.247(a)(1)	Carrier Frequency Separation	PASS	-----
15.247(a)(1)(iii)	Number of Hopping	PASS	-----
15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	PASS	-----
15.247(d)	Out of Band Conducted Spurious Emission	PASS	-----

Standard	Description
CFR47, Part 15, Subpart C	Intentional Radiators
ANSI C63. 10: 2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
KDB 558074	Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems

#### Decision Rule

- Uncertainty is not included.
- Uncertainty is included.

## 1.2. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty (dB)
Conducted Emission	150 kHz ~ 30 MHz	2.68
Radiated Emission	9 kHz ~ 30 MHz	2.14
	30 MHz ~ 1000 MHz	4.99
	1000 MHz ~ 18000 MHz	4.99
	18000 MHz ~ 26500 MHz	4.23
	26500 MHz ~ 40000 MHz	4.39
Conducted Output Power	0.92 dB	
RF Bandwidth	4.79 %	
Power Spectral Density	0.92 dB	

## 2 EUT Description

Applicant	InnoComm Mobile Technology Corporation 3F, No. 6, Hsin Ann Rd., Hsinchu Science Park, Hsinchu, Taiwan, R.O.C.		
Manufacturer	InnoComm Mobile Technology Corporation 3F, No. 6, Hsin Ann Rd., Hsinchu Science Park, Hsinchu, Taiwan, R.O.C.		
Product	Wireless Audio Module		
Trade Name	InnoComm		
Model Number	WB15		
FCC ID	YAIWB15		
Difference description of Hardware Version	<p>Mozart_R004 version difference than Mozart_R003 is fine-tunes the DDR trace spacing according to the vendor's recommendations to improve its performance. The appearance and all components are same.</p> <p>After evaluation, the verification of Mozart_R003 and Mozart_R004, The result is the worst case of Mozart_R003, Therefore, only the complete test data of Mozart_R003 is displayed.</p>		
Frequency Range	2402 ~ 2480 MHz		
Modulation Type	GFSK for 1 Mbps		
	$\pi/4$ -DQPSK for 2 Mbps		
	8DPSK for 3 Mbps		
Operate Temp. Range	0 ~ +55 °C		
Antenna information	ANT	Model Number	Type
	ANT-0	WA-F-LA-01-015	FPCB Antenna
	ANT-1	N14-0808-R0A	PCB Antenna
Max. RF Output Power	GFSK for 1 Mbps	0.01189	W
	$\pi/4$ -DQPSK for 2 Mbps	0.00923	W
	8DPSK for 3 Mbps	0.00953	W

Note: Model Number: WA-F-LA-01-015 is worst.

### 3 Test Methodology

#### 3.1. Mode of Operation

Decision of Test ATL has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Pre-Test Mode
Mode 1: Transmit mode
Mode 2: GFSK Continuous TX mode
Mode 3: $\pi/4$ -DQPSK Continuous TX mode
Mode 4: 8DPSK Continuous TX mode

After verification, all tests were carried out with the worst case test modes.

By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "X axis" position was the worst, then the final test was executed the worst condition and test data were recorded in this report.

Final-Test Mode
Mode 1: Transmit mode
Mode 2: GFSK Continuous TX mode
Mode 4: 8DPSK Continuous TX mode

#### Description of Test Modes

Preliminary tests were performed in different modulation to find the worst case. The modulation has shown the worst-case in section 4.5. Investigation has been done on all the possible configurations for searching the worst cases.


#### 3.2. EUT Test Step

1	Setup the EUT shown on "Configuration of Test System Details."
2	Turn on the power of all equipment.
3	Turn on TX function
4	EUT run test program.


Measurement Software			
No.	Description	Software	Version
1	Conducted Emission	EZ EMC	1.1.4.3
2	Radiated Emission	EZ EMC	1.1.4.4

### 3.3. Configuration of Test System Details

#### Conducted Emission



#### Radiated Emissions



Devices Description					
Product		Manufacturer	Model Number	Serial Number	Remark
(1)	Notebook	DELL	LATITUDE E6440	48GBD72	---
(2)	AC Adapter	DELL	HA65NM130	---	INPUT : 100-240 VAC, 50Hz / 60 Hz, 1.7 A OUTPUT : 19.5 VDC, 3.34 A Non-Shielded, 0.8 m
(3)	USB Cable	LG	EAD62377902	---	STD-A →Micro-B Shielded, 0.8 m
(4)	AC Power Cord	I-SHENG	ATL_001	---	14 AWG, 15 A 3 P 125 V Non-Shielded, 1.6 m

### 3.4. Test Instruments

For Conducted Emission

Test Period: Jul. 28, 2020 ~ Sep. 09, 2020

Testing Engineer: Louis Shen, Andy Lu

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
Test Receiver	R&S	ESCI	100367	05/25/2020	1 year
LISN	R&S	ENV216	101040	03/23/2020	1 year
LISN	R&S	ENV216	101041	04/06/2020	1 year
RF Cable	Woken	00100D1380194M	TE-02-03	05/26/2020	1 year
Power Supply	KEITHLEY	2303	4045290	02/11/2020	1 year

For Radiated Emissions

Test Period: Jul. 21, 2020 ~ Oct. 21, 2020

Testing Engineer: JS Liao, Marc Yeh

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
Spectrum Analyzer (10 Hz~44 GHz)	Keysight	N9010A	MY52221312	01/13/2020	1 year
Pre Amplifier (1~26.5 GHz)	EMCI	EMC012645SE	980289	01/15/2020	1 year
Pre Amplifier (100 kHz~1.3 GHz)	Agilent	8447D	2944A11119	01/15/2020	1 year
Broadband Antenna	Schwarzbeck	VULB9168	416	10/23/2019	1 year
Horn Antenna (1~18 GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	9120D-550	08/22/2019 08/16/2020	1 year
Loop Antenna	COM-POWER CORPORATION	AL-130	121014	03/27/2020	1 year
RF Cable	EMCI	EMC104-N-N-6000	TE01-1	02/20/2020	1 year
Microwave Cable	EMCI	EMC104-SM-SM-1 3000	170814	10/29/2019	1 year
Microwave Cable	EMCI	EMC102-KM-KM-1 4000	151001	02/20/2020	1 year
Bluetooth Tester	R & S	CBT	100350	03/27/2019	2 years
Power Supply	KEITHLEY	2303	4045290	02/17/2020	1 year

Note: N.C.R. = No Calibration Request.

For Conducted

Test Period: Jul. 27, 2020 ~ Oct. 14, 2020

Testing Engineer: Peter Shui, Louis Shen

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
Power Sensor	Anritsu	MA2411B	1126022	09/02/2019 09/01/2020	1 year
Power Meter	Anritsu	ML2495A	1135009	09/02/2019 09/01/2020	1 year
Spectrum Analyzer (20 Hz~26.5 GHz)	Agilent	N9020A	US47520902	09/18/2019 09/24/2020	1 year
Bluetooth Tester	R&S	CBT	100350	03/27/2019	2 years
Power Supply	KEITHLEY	2303	4045290	02/11/2020	1 year

Note: N.C.R. = No Calibration Request.

### 3.5. Test Site Environment

Items	Required (IEC 60068-1)	Actual
Temperature (°C)	15-35	20-30
Humidity (%RH)	25-75	45-75


## 4 Measurement Procedure

### 4.1. Maximum Conducted Output Power Measurement

#### ■ Limit

For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels < 0.125 watt.

#### ■ Test Setup



#### ■ Test Procedure

Testing must be done according to this procedure, FCC Public Notice DA 00-705 - Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems. This is the only method recognized by the FCC. The tests below are run with the EUT's transmitter set at high power in TX mode. The EUT is needed to force selection of output power level and channel number. While testing, EUT was set to transmit continuously. Remove the Subjective device's antenna and connect the RF output port to power sensor. The maximum peak output power shall not exceed 1 watt.

Use a direct connection between the antenna port of transmitter and the power sensor, for prevent the power sensor input attenuation 40-50 dB. Set the RBW Bandwidth of the emission or use a channel power meter mode.


For antennas with gains of 6 dBi or less, maximum allowed transmitter output is 1 watt (+30 dBm). For antennas with gains greater than 6 dBi, transmitter output level must be decreased by an amount equal to  $(GAIN - 6)/3$  dBm. The antenna port of the EUT was connected to the input of a power sensor. Power was read directly and cable loss correction was added to the reading to obtain power at the EUT antenna terminals.

## 4.2. AC Power Line Conducted Emission Measurement

### ■ Limit

Frequency (MHz)	Quasi-peak	Average
0.15 - 0.5	66 to 56	56 to 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

### ■ Test Setup



### ■ Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a  $50 \Omega$  //  $50 \mu\text{H}$  coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a  $50 \Omega$  //  $50 \mu\text{H}$  coupling impedance with  $50 \Omega$  termination.

Tabletop device shall be placed on a non-conducting platform, of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The wall of screened room shall be located 40 cm to the rear of the EUT. Other surfaces of tabletop or floor standing EUT shall be at least 80 cm from any other ground conducting surface including one or more LISNs. For floor-standing device shall be placed under the EUT with a 12 mm insulating material.

Conducted emissions were investigated over the frequency range from 0.15 MHz to 30 MHz using a resolution bandwidth of 9 kHz. The equipment under test (EUT) shall be meet the limits in section 4.1, as applicable, including the average limit and the quasi-peak limit when using respectively, an average detector and quasi-peak detector measured in accordance with the methods described of related standard. When all of peak value were complied with quasi-peak and average limit from 150 kHz to 30 MHz then quasi-peak and average measurement was unnecessary.

The AMN shall be placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for AMNs mounted on top of the ground reference plane. This distance is between the closest points of the AMN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8 m from the AMN. If the mains power cable is longer than 1 m then the cable shall be folded back and forth at the centre of the lead to form a bundle no longer than 0.4 m. All of interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long. All of EUT and AE shall be separate place more than 0.1 m. All  $50 \Omega$  ports of the LISN shall be resistively terminated into  $50 \Omega$  loads when not connected to the measuring instrument.

If the reading of the measuring receiver shows fluctuations close to the limit, the reading shall be observed for at least 15 s at each measurement frequency; the higher reading shall be recorded with the exception of any brief isolated high reading which shall be ignored.

### 4.3. Radiated Emission Measurement

#### ■ Limit


According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu$ V/m at meter)	Measurement Distance (meters)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3


\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

#### ■ Setup


9 kHz ~ 30 MHz



Below 1 GHz



Above 1 GHz



### ■ Test Procedure

Final radiation measurements were made on a three-meter, Semi Anechoic Chamber. The EUT system was placed on a nonconductive turntable which is 0.8 or 1.5 meters height, top surface 1.0 x 1.5 meter. The spectrum was examined from 250 MHz to 2.5 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously & Measurements spectrum range from 9 kHz to 26.5 GHz is investigated.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 3 MHz for peak measurements and 10 Hz for average measurements when Duty cycle >98 % / 1/T for average measurements when Duty cycle <98 %. A nonconductive material surrounded the EUT to supporting the EUT for standing on tree orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

SCHWARZBECK MESS-ELEKTRONIK Biconilog Antenna at 3 Meter and the SCHWARZBECK Double Ridged Guide Antenna was used in frequencies 1 – 26.5 GHz at a distance of 1 meter. All test results were extrapolated to equivalent signal at 3 meters utilizing an inverse linear distance extrapolation Factor (20 dB/decade).

For testing above 1 GHz, the emission level of the EUT in peak mode was 20 dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test.

The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The following procedures were used to convert the emission levels measured in decibels referenced to 1 microvolt (dBuV) into field intensity in micro volts pre meter (uV/m).

The actual field intensity in decibels referenced to 1 microvolt in to field intensity in micro colts per meter (dBuV/m).

The actual field is intensity in referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

$$(1) \text{ Amplitude (dBuV/m)} = \text{FI (dBuV)} + \text{AF (dBuV)} + \text{CL (dBuV)} - \text{Gain (dB)}$$

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

P.S Amplitude is auto calculate in spectrum analyzer.

$$(2) \text{ Actual Amplitude (dBuV/m)} = \text{Amplitude (dBuV)} - \text{Dis(dB)}$$

The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:

(a) For fundamental frequency : Transmitter Output < +30 dBm

(b) For spurious frequency : Spurious emission limits = fundamental emission limit /10


Data of measurement within this frequency range without mark in the table above means the reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.

#### 4.4. 20 dB RF Bandwidth Measurement

##### ■ Limit

N/A

##### ■ Test Setup



##### ■ Test Procedure

Testing must be done according to this procedure, FCC Public Notice DA 00-705 - Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems. This is the only method recognized by the FCC. The RF output port of the Equipment-Under-Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 10 dB passive attenuator. A fully charged battery was used for the supply voltage. The Bluetooth frequency hopping function of the EUT was enabled. The spectrum analyzer used the following settings:

1. Span = approx. 2 to 3 times the 20 dB bandwidth, centered on a hopping frequency
2. RBW  $\geq$  1 % of the 20 dB span
3. VBW  $\geq$  RBW
4. Sweep = auto
5. Detector function = peak
6. Trace = max hold


The trace was allowed to stabilize. The EUT was transmitting at its maximum data rate. The marker-to-peak function was used to set the marker to the peak of the emission. The marker-delta function was used to measure 20 dB down one side of the emission. The marker-delta function and marker was moved to the other side of the emission until it was even with the reference marker. The marker-delta reading at this point was the 20 dB bandwidth of the emission.

## 4.5. Carrier Frequency Separation Measurement

### ■ Limit

Title 47 of the CFR, Part 15 Subpart (c) 15.247(a)(1) requires the measurement of the bandwidth of the transmission between the -20 dB points on the transmitted spectrum. The results of this test determine the limits for channel spacing. The channel spacing shall be a minimum of 25 kHz or the 20 dB bandwidth, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel.

### ■ Test Setup



### ■ Test Procedure

Testing must be done according to this procedure, FCC Public Notice DA 00-705 - Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems. This is the only method recognized by the FCC. The RF output port of the Equipment-Under-Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 10 dB passive attenuator. A fully charged battery was used for the supply voltage. The Bluetooth frequency hopping function of the EUT was enabled. The following spectrum analyzer settings were used:

1. Span = wide enough to capture the peaks of two adjacent channels
2. Resolution (or IF) Bandwidth (RBW)  $\geq 1\%$  of the span
3. Video (or Average) Bandwidth (VBW)  $\geq$  RBW
4. Sweep = auto
5. Detector function = peak
6. Trace = max hold


The trace was allowed to stabilize. The marker-delta function was used to determine the separation between the peaks of the adjacent channels.

## 4.6. Number of Hopping Measurement

### ■ Limit

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

### ■ Test Setup



### ■ Test Procedure

Testing must be done according to this procedure, FCC Public Notice DA 00-705 - Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems. This is the only method recognized by the FCC. The RF output port of the Equipment-Under-Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 10 dB passive attenuator. A fully charged battery was used for the supply voltage. The Bluetooth frequency hopping function of the EUT was enabled. The spectrum analyzer used the following settings:

1. Span = the frequency band of operation
2. RBW  $\geq$  1 % of the span
3. VBW  $\geq$  RBW
4. Sweep = auto
5. Detector function = peak
6. Trace = max hold


The trace was allowed to stabilize.

## 4.7. Time of Occupancy (Dwell Time) Measurement

### ■ Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### ■ Test Setup



### ■ Test Procedure

Testing must be done according to this procedure, FCC Public Notice DA 00-705 - Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems. This is the only method recognized by the FCC. The RF output port of the Equipment-Under-Test is directly coupled to the input of the spectrum through a specialized RF connector and a 10 dB passive attenuator. A fully charged battery was used for the supply voltage. The Bluetooth hopping function of the EUT was enabled. The following spectrum analyzer settings were used:

1. Span = zero span, centered on a hopping channel
2. RBW = 1 MHz
3. VBW  $\geq$  RBW
4. Sweep = as necessary to capture the entire dwell time per hopping channel
5. Detector function = peak
6. Trace = max hold


The marker-delta function was used to determine the dwell time.

## 4.8. Out of Band Conducted Emissions Measurement

### ■ Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

### ■ Test Setup



### ■ Test Procedure

Testing must be done according to this procedure, FCC Public Notice DA 00-705 - Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems. This is the only method recognized by the FCC. In any 100 kHz bandwidth outside the EUT pass band, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function. All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the pass band. The test was performed at 3 channels (Channel 0, 39, 78)

## 4.9. Antenna Measurement

### ■ Limit

For intentional device, according to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And According to 15.247 (b)(4), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


### ■ Antenna Connector Construction

See section 2 – antenna information.

## 5 Test Results

### Annex A. Conducted Emission

Standard:	FCC Part 15.247	Line:	L1
Test item:	Conducted Emission	Power:	AC 120 V/60 Hz
Mode:	Mode 1	Temp.(°C)/Hum.(%RH):	26(°C)/60 %RH
Description:			




No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1860	39.19	36.87	9.70	48.89	46.57	64.21	54.21	-15.32	-7.64	Pass
2	9.2300	22.41	20.04	9.87	32.28	29.91	60.00	50.00	-27.72	-20.09	Pass
3	10.9060	25.42	24.36	9.89	35.31	34.25	60.00	50.00	-24.69	-15.75	Pass
4	13.8420	25.38	24.34	9.95	35.33	34.29	60.00	50.00	-24.67	-15.71	Pass
5	14.6820	28.09	26.97	9.97	38.06	36.94	60.00	50.00	-21.94	-13.06	Pass
6	15.9380	25.43	24.71	9.99	35.42	34.70	60.00	50.00	-24.58	-15.30	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

Standard:	FCC Part 15.247	Line:	N
Test item:	Conducted Emission	Power:	AC 120 V/60 Hz
Mode:	Mode 1	Temp.(°C)/Hum.(%RH):	26(°C)/60 %RH
Description:			



No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1860	39.43	36.91	9.69	49.12	46.60	64.21	54.21	-15.09	-7.61	Pass
2	10.0700	21.10	19.21	9.88	30.98	29.09	60.00	50.00	-29.02	-20.91	Pass
3	10.9060	24.57	23.43	9.90	34.47	33.33	60.00	50.00	-25.53	-16.67	Pass
4	13.8420	25.28	24.57	9.96	35.24	34.53	60.00	50.00	-24.76	-15.47	Pass
5	14.6820	26.99	26.23	9.98	36.97	36.21	60.00	50.00	-23.03	-13.79	Pass
6	15.5180	23.87	22.80	9.99	33.86	32.79	60.00	50.00	-26.14	-17.21	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

## Annex B. Conducted Test Results

### Maximum Conducted Output Power Measurement

Test Mode	Frequency (MHz)	Packet Type	Average Power		Peak Power		Limit (W)
			(dBm)	(W)	(dBm)	(W)	
Mode 2	2402	DH1	10.49	0.01119	10.51	0.01125	≤ 0.125
		DH3	10.50	0.01122	10.53	0.01130	≤ 0.125
		DH5	10.53	0.01130	10.55	0.01135	≤ 0.125
	2441	DH1	10.64	0.01159	10.69	0.01172	≤ 0.125
		DH3	10.67	0.01167	10.72	0.01180	≤ 0.125
		DH5	10.70	0.01175	10.75	0.01189	≤ 0.125
	2480	DH1	10.45	0.01109	10.50	0.01122	≤ 0.125
		DH3	10.47	0.01114	10.53	0.01130	≤ 0.125
		DH5	10.49	0.01119	10.55	0.01135	≤ 0.125
Mode 3	2402	2DH1	6.92	0.00492	9.14	0.00820	≤ 0.125
		2DH3	6.95	0.00495	9.16	0.00824	≤ 0.125
		2DH5	6.98	0.00499	9.20	0.00832	≤ 0.125
	2441	2DH1	7.53	0.00566	9.60	0.00912	≤ 0.125
		2DH3	7.55	0.00569	9.62	0.00916	≤ 0.125
		2DH5	7.57	0.00571	9.65	0.00923	≤ 0.125
	2480	2DH1	7.03	0.00505	9.29	0.00849	≤ 0.125
		2DH3	7.04	0.00506	9.33	0.00857	≤ 0.125
		2DH5	7.08	0.00511	9.36	0.00863	≤ 0.125
Mode 4	2402	3DH1	6.99	0.00500	9.25	0.00841	≤ 0.125
		3DH3	7.00	0.00501	9.28	0.00847	≤ 0.125
		3DH5	7.04	0.00506	9.30	0.00851	≤ 0.125
	2441	3DH1	7.56	0.00570	9.75	0.00944	≤ 0.125
		3DH3	7.59	0.00574	9.76	0.00946	≤ 0.125
		3DH5	7.61	0.00577	9.79	0.00953	≤ 0.125
	2480	3DH1	7.10	0.00513	9.49	0.00889	≤ 0.125
		3DH3	7.12	0.00515	9.50	0.00891	≤ 0.125
		3DH5	7.14	0.00518	9.53	0.00897	≤ 0.125


Note: The relevant measured result has the offset with cable loss already.

### 20 dB RF Bandwidth Measurement


Test Mode	Frequency (MHz)	Measurement Results (MHz)
Mode 2	2402	1.039
	2441	1.032
	2480	1.017
Mode 4	2402	1.346
	2441	1.340
	2480	1.316

## ■ Test Graphs

Mode 2: GFSK Continuous TX mode



## Mode 4: 8DPSK Continuous TX mode


2402 MHz	 <p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq: 2.40200000 GHz</p> <p>Ref Offset 0.8 dB</p> <p>Ref 20.00 dBm</p> <p>CF Step 300.000 kHz</p> <p>Frequency</p> <p>Center Freq 2.40200000 GHz</p> <p>CF Step 300.000 kHz</p> <p>Man</p> <p>Span 3 MHz</p> <p>Sweep 3.2 ms</p> <p>Auto</p> <p>Freq Offset 0 Hz</p> <p>Occupied Bandwidth 1.2379 MHz</p> <p>Total Power 15.6 dBm</p> <p>Transmit Freq Error 94 Hz</p> <p>OBW Power 99.00 %</p> <p>x dB Bandwidth 1.346 MHz</p> <p>x dB -20.00 dB</p> <p>File &lt;BBB.png&gt; saved</p> <p>STATUS</p>
2441 MHz	 <p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq: 2.44100000 GHz</p> <p>Ref Offset 0.8 dB</p> <p>Ref 20.00 dBm</p> <p>CF Step 300.000 kHz</p> <p>Frequency</p> <p>Center Freq 2.44100000 GHz</p> <p>CF Step 300.000 kHz</p> <p>Man</p> <p>Span 3 MHz</p> <p>Sweep 3.2 ms</p> <p>Auto</p> <p>Freq Offset 0 Hz</p> <p>Occupied Bandwidth 1.2296 MHz</p> <p>Total Power 15.8 dBm</p> <p>Transmit Freq Error 3.399 kHz</p> <p>OBW Power 99.00 %</p> <p>x dB Bandwidth 1.340 MHz</p> <p>x dB -20.00 dB</p> <p>File &lt;BBB.png&gt; saved</p> <p>STATUS</p>
2480 MHz	 <p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq: 2.48000000 GHz</p> <p>Ref Offset 0.8 dB</p> <p>Ref 20.00 dBm</p> <p>CF Step 300.000 kHz</p> <p>Frequency</p> <p>Center Freq 2.48000000 GHz</p> <p>CF Step 300.000 kHz</p> <p>Man</p> <p>Span 3 MHz</p> <p>Sweep 3.2 ms</p> <p>Auto</p> <p>Freq Offset 0 Hz</p> <p>Occupied Bandwidth 1.2143 MHz</p> <p>Total Power 15.5 dBm</p> <p>Transmit Freq Error 6.417 kHz</p> <p>OBW Power 99.00 %</p> <p>x dB Bandwidth 1.316 MHz</p> <p>x dB -20.00 dB</p> <p>File &lt;BBB.png&gt; saved</p> <p>STATUS</p>

### Carrier Frequency Separation Measurement

Test Mode	Frequency (MHz)	Measurement Results (MHz)	Limit (MHz)
Mode 2	2402	1.000	≥ 0.693
	2441	1.000	≥ 0.688
	2480	1.000	≥ 0.678
Mode 4	2402	1.000	≥ 0.897
	2441	1.000	≥ 0.893
	2480	1.000	≥ 0.877

## ■ Test Graphs

Mode 2: GFSK Continuous TX mode




## Mode 4: 8DPSK Continuous TX mode

2402 MHz



2441 MHz



2480 MHz




**Number of Hopping Measurement**

Test Mode	Frequency Range (MHz)	Measurement Results (Ch)	Limit (ch)
Mode 2	2402 - 2480	79	$\geq 15$
Mode 3	2402 - 2480	79	$\geq 15$
Mode 4	2402 - 2480	79	$\geq 15$

## ■ Test Graphs

Mode 2: GFSK Continuous TX mode



## Mode 4: 8DPSK Continuous TX mode

CH0~CH39



CH39~CH78




**Time of Occupancy (Dwell Time) Measurement**

Mode 2: GFSK Continuous TX mode	
DH1	
Cycle Calculate	79CH * 0.4 = 31.6 (sec)
The EUT Hopping Number per Sec	1600 times/sec
Each Channel Dwell Times per Sec	800/79CH = 10.13(times/sec)
Each Channel Dwell Times on Cycle(1)	31.6 * 10.13 = 320.108(times)
Each Channel Dwell Times (2)	0.440 ms (sec)
Dwell Times on Cycle (1) * (2)	140.848 ms (sec)
LIMIT(msec)	< = 400
DH3	
Cycle Calculate	79CH * 0.4 = 31.6 (sec)
The EUT Hopping Number per Sec	1600 times/sec
Each Channel Dwell Times per Sec	400/79CH = 5.1(times/sec)
Each Channel Dwell Times on Cycle(1)	31.6 * 5.1 = 161.16(times)
Each Channel Dwell Times (2)	1.700 ms (sec)
Dwell Times on Cycle (1) * (2)	271.823 ms (sec)
LIMIT(msec)	< = 400
DH5	
Cycle Calculate	79CH * 0.4 = 31.6 (sec)
The EUT Hopping Number per Sec	1600 times/sec
Each Channel Dwell Times per Sec	266.7/79CH = 3.37(times/sec)
Each Channel Dwell Times on Cycle(1)	31.6 * 3.37 = 106.492(times)
Each Channel Dwell Times (2)	2.950 ms (sec)
Dwell Times on Cycle (1) * (2)	315.084 ms (sec)
LIMIT(msec)	< = 400


Mode 4: 8DPSK Continuous TX mode	
3DH1	
Cycle Calculate	$79CH * 0.4 = 31.6$ (sec)
The EUT Hopping Number per Sec	1600 times/sec
Each Channel Dwell Times per Sec	$800/79CH = 10.13$ (times/sec)
Each Channel Dwell Times on Cycle(1)	$31.6 * 10.13 = 320.108$ (times)
Each Channel Dwell Times (2)	0.450 ms (sec)
Dwell Times on Cycle (1) * (2)	144.049 ms (sec)
LIMIT(msec)	< = 400
3DH3	
Cycle Calculate	$79CH * 0.4 = 31.6$ (sec)
The EUT Hopping Number per Sec	1600 times/sec
Each Channel Dwell Times per Sec	$400/79CH = 5.1$ (times/sec)
Each Channel Dwell Times on Cycle(1)	$31.6 * 5.1 = 161.16$ (times)
Each Channel Dwell Times (2)	1.700 ms (sec)
Dwell Times on Cycle (1) * (2)	271.823 ms (sec)
LIMIT(msec)	< = 400
3DH5	
Cycle Calculate	$79CH * 0.4 = 31.6$ (sec)
The EUT Hopping Number per Sec	1600 times/sec
Each Channel Dwell Times per Sec	$266.7/79CH = 3.37$ (times/sec)
Each Channel Dwell Times on Cycle(1)	$31.6 * 3.37 = 106.492$ (times)
Each Channel Dwell Times (2)	2.950 ms (sec)
Dwell Times on Cycle (1) * (2)	315.084 ms (sec)
LIMIT(msec)	< = 400

## ■ Test Graphs

Mode 2: GFSK Continuous TX mode




## Mode 4: 8DPSK Continuous TX mode



## Out of Band Conducted Emissions Measurement


### ■ Test Graphs

Mode 2: GFSK Continuous TX mode




## Mode 4: 8DPSK Continuous TX mode


2402 MHz




2441 MHz




2480 MHz




## Mode 2: GFSK Continuous TX mode \_ Un-hopping




## Mode 2: GFSK Continuous TX mode \_ Hopping



## Mode 4: 8DPSK Continuous TX mode \_ Un-hopping




## Mode 4: 8DPSK Continuous TX mode \_ Hopping



## Annex C. Radiated Emission Measurement

Below 1 GHz

Standard:	FCC Part 15.247	Test Distance:	3m
Frequency:	2480 MHz		
Mode:	Mode 2		
Ant.Polar.:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	185.2000	43.86	-7.07	36.79	43.50	-6.71	QP
2	242.4300	44.76	-6.12	38.64	46.00	-7.36	QP
3	298.6900	42.79	-4.23	38.56	46.00	-7.44	QP
4	452.9200	38.18	-0.67	37.51	46.00	-8.49	QP
5	600.3600	34.78	2.49	37.27	46.00	-8.73	QP
6	773.0200	32.42	5.48	37.90	46.00	-8.10	QP


Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

Example:  $36.79 = -7.07 + 43.86$

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Frequency:	2480 MHz		
Mode:	Mode 2		
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	200.7200	43.39	-7.80	35.59	43.50	-7.91	QP
2	267.6500	43.62	-5.23	38.39	46.00	-7.61	QP
3	486.8700	40.04	-0.28	39.76	46.00	-6.24	QP
4	600.3600	37.13	2.49	39.62	46.00	-6.38	QP
5	755.5600	34.50	5.28	39.78	46.00	-6.22	QP
6	821.5200	32.56	6.18	38.74	46.00	-7.26	QP

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

Example:  $35.59 = -7.80 + 43.39$


2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

## Harmonic

Above 1 GHz

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	
Frequency:	2402 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 2		
Ant.Polar.:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4804.000	52.13	-8.66	43.47	74.00	-30.53	peak
2	7206.000	50.19	-1.20	48.99	74.00	-25.01	peak


Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

Example:  $43.47 = -8.66 + 52.13$

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	
Frequency:	2402 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 2		
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4804.000	51.22	-8.66	42.56	74.00	-31.44	peak
2	7206.000	49.23	-1.20	48.03	74.00	-25.97	peak


Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

Example:  $42.56 = -8.66 + 51.22$

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	
Frequency:	2441 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 2		
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4882.000	50.20	-8.45	41.75	74.00	-32.25	peak
2	7323.000	48.69	-0.66	48.03	74.00	-25.97	peak

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	
Frequency:	2441 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 2		
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4882.000	50.35	-8.45	41.90	74.00	-32.10	peak
2	7323.000	49.04	-0.66	48.38	74.00	-25.62	peak

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	
Frequency:	2480 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 2		
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4960.000	50.21	-8.26	41.95	74.00	-32.05	peak
2	7440.000	47.24	-0.14	47.10	74.00	-26.90	peak

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	
Frequency:	2480 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 2		
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4960.000	50.62	-8.26	42.36	74.00	-31.64	peak
2	7440.000	47.93	-0.14	47.79	74.00	-26.21	peak

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	
Frequency:	2402 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 4		
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4804.000	50.16	-8.66	41.50	74.00	-32.50	peak
2	7206.000	48.56	-1.20	47.36	74.00	-26.64	peak

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	
Frequency:	2402 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 4		
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4804.000	50.33	-8.66	41.67	74.00	-32.33	peak
2	7206.000	48.52	-1.20	47.32	74.00	-26.68	peak

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	
Frequency:	2441 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 4		
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4882.000	50.11	-8.45	41.66	74.00	-32.34	peak
2	7323.000	50.06	-0.66	49.40	74.00	-24.60	peak

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	
Frequency:	2441 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 4		
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4882.000	50.22	-8.45	41.77	74.00	-32.23	peak
2	7323.000	48.51	-0.66	47.85	74.00	-26.15	peak

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	
Frequency:	2480 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 4		
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4960.000	50.25	-8.26	41.99	74.00	-32.01	peak
2	7440.000	48.36	-0.14	48.22	74.00	-25.78	peak

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	
Frequency:	2480 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 4		
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4960.000	50.78	-8.26	42.52	74.00	-31.48	peak
2	7440.000	48.07	-0.14	47.93	74.00	-26.07	peak

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Simultaneous Transmitting		
Mode:	BT + 2.4 G		
Ant.Polar.:	Horizontal		
Description:			




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2751.000	51.30	-13.22	38.08	74.00	-35.92	peak
2	4366.000	51.69	-9.65	42.04	74.00	-31.96	peak
3	6185.000	49.77	-4.88	44.89	74.00	-29.11	peak

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Simultaneous Transmitting		
Mode:	BT + 2.4 G		
Ant.Polar.:	Vertical		
Description:			




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2751.000	52.57	-13.22	39.35	74.00	-34.65	peak
2	4417.000	52.53	-9.57	42.96	74.00	-31.04	peak
3	6134.000	48.98	-5.05	43.93	74.00	-30.07	peak

Note: 1. Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2. Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Simultaneous Transmitting		
Mode:	BT + 5 G		
Ant.Polar.:	Horizontal		
Description:			




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2819.000	54.02	-13.02	41.00	74.00	-33.00	peak
2	3686.000	54.75	-11.17	43.58	74.00	-30.42	peak
3	5097.000	51.48	-7.85	43.63	74.00	-30.37	peak

Note: 1. Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2. Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Simultaneous Transmitting		
Mode:	BT + 5 G		
Ant.Polar.:	Vertical		
Description:			



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2802.000	54.20	-13.07	41.13	74.00	-32.87	peak
2	4043.000	52.60	-10.17	42.43	74.00	-31.57	peak
3	4961.000	53.07	-8.26	44.81	74.00	-29.19	peak


Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

**Band Edge**

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	
Frequency:	2402 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 2		
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2339.370	58.71	-14.65	44.06	74.00	-29.94	peak
2	2390.000	56.67	-14.38	42.29	74.00	-31.71	peak
3	2401.850	117.61	-14.32	103.29	--	--	peak

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	
Frequency:	2402 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 2		
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2360.930	58.71	-14.53	44.18	74.00	-29.82	peak
2	2390.000	57.19	-14.38	42.81	74.00	-31.19	peak
3	2401.850	114.65	-14.32	100.33	--	--	peak

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	
Frequency:	2480 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 2		
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2480.140	117.46	-13.92	103.54	--	--	peak
2	2483.500	59.46	-13.91	45.55	74.00	-28.45	peak
3	2483.800	63.43	-13.91	49.52	74.00	-24.48	peak

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	
Frequency:	2480 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 2		
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2480.100	112.72	-13.92	98.80	--	--	peak
2	2483.500	58.01	-13.91	44.10	74.00	-29.90	peak
3	2496.060	59.18	-13.84	45.34	74.00	-28.66	peak

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	
Frequency:	2402 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 4		
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2384.690	59.13	-14.41	44.72	74.00	-29.28	peak
2	2390.000	58.69	-14.38	44.31	74.00	-29.69	peak
3	2401.740	116.72	-14.32	102.40	--	--	peak

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	
Frequency:	2402 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 4		
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2340.910	59.57	-14.63	44.94	74.00	-29.06	peak
2	2390.000	56.74	-14.38	42.36	74.00	-31.64	peak
3	2401.850	113.66	-14.32	99.34	--	--	peak

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	
Frequency:	2480 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 4		
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2480.020	116.58	-13.92	102.66	--	--	peak
2	2483.500	66.63	-13.91	52.72	74.00	-21.28	peak
3	2483.500	53.12	-13.91	39.21	54.00	-14.79	AVG
4	2483.640	65.73	-13.91	51.82	74.00	-22.18	peak

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	
Frequency:	2480 MHz	Temp.(°C)/Hum.(%RH):	
Mode:	Mode 4		
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2480.060	111.88	-13.92	97.96	--	--	peak
2	2483.500	57.48	-13.91	43.57	74.00	-30.43	peak
3	2483.700	59.86	-13.91	45.95	74.00	-28.05	peak

Note: 1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correct factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

--- END---