

www.tuv.com Appendix 10

Prüfbericht - Nr.:	19660105 001	Seite 1 von 2
Test Report No.		Page 1 of 2

RF Exposure Report

RF Exposure Measurement

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an overprediction for near field power density. It is taken as worst case to specify the safety range.

RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range	Electric Field	Magnetic Field	Power Density					
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm²)					
Limits for Occupational / controlled Exposures								
300 - 1500			F/300					
1500 – 100000			5.0					
Limits for General population / Uncontrolled Exposure								
300 - 1500		F/1500						
1500 – 100000			1.0					

F= Frequency in MHz



www.tuv.com Appendix 10

 Prüfbericht - Nr.:
 19660105 001
 Seite 2 von 2

 Test Report No.
 Page 2 of 2

Friss Formula

Friss Transmission Formula: $Pd = (Pout * G) / (4*pi*r^2)$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.

EUT Operation condition

EUT was enabled to transmit and receive at lowest, middle and highest channels.

Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Portable device.

Test Results

Gain (G) = dBi

Protocol	Data Rate (Mbps)	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm²)	Limit (mW/cm²)
Bluetooth	3	2402	0.814	0.0005670	1.000
10.5GHz	-	10.525	8	0.001592	1.000