



Shenzhen Huatongwei International Inspection Co., Ltd.

Keji S,12th , Road, Hi-tech Industrial Park, Shenzhen, Guangdong, China

Phone:86-755-26748099

Fax:86-755-26748089

http://www.szhtw.com.cn



FCC PART 90 TEST REPORT

FCC Part 90

Report Reference No......: **TRE1112009301**

FCC ID.....: **YAMMD78XG-U2**

Compiled by

(position+printed name+signature)..: File administrators Eric Zhang

Supervised by

(position+printed name+signature)..: Test Engineer Wenliang Li

Approved by

(position+printed name+signature)..: Manager Wenliang Li

Date of issue.....: Dec 27, 2011

Testing Laboratory Name: **Shenzhen Huatongwei International Inspection Co., Ltd**

Address: Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China

Applicant's name.....: **Hytera Communications Corporation Ltd.**

Address: HYT Tower,Hi-Tech Industrial Park North,Nanshan District,Shenzhen China.518057

Test specification:

Standard: **FCC Part 90: PRIVATE LAND MOBILE RADIO SERVICES**

TRF Originator.....: Shenzhen Huatongwei International Inspection CO., Ltd

Master TRF: Dated 2006-06

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Digital Mobile Radio

Trade Mark



Manufacturer: **Hytera Communications Corporation Ltd.**

Model/Type reference.....: MD782G U(2)/ MD785G U(2)/ MD786G U(2)/ MD788G U(2)

Listed Models: /

Modulation: FM&4FSK

Channel Separation.....: 12.5KHz

Rated Power: 45 Watts(46.53 dBm)/5 Watts(36.99 dBm)

Operation Frequency.....: From 450 MHz to 520 MHz

Ratings: DC 13.60 V

Result.....: **Positive**

TEST REPORT

| | | |
|--------------------------|----------------------|---------------|
| Test Report No. : | TRE1112009301 | Dec 27, 2011 |
| | | Date of issue |

Equipment under Test : Digital Mobile Radio

Model /Type : MD782G U(2)/ MD785G U(2)/ MD786G U(2)/ MD788G U(2)

Listed Models : /

Applicant : **Hytera Communications Corporation Ltd.**

Address : HYT Tower,Hi-Tech Industrial Park North,Nanshan District,Shenzhen China.518057

Manufacturer : **Hytera Communications Corporation Ltd.**

Address : HYT Tower,Hi-Tech Industrial Park North,Nanshan District,Shenzhen China.518057

| | |
|---|-----------------|
| Test Result according to the standards on page 10: | Positive |
|---|-----------------|

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

| | | |
|-----------|---|-----------|
| 1. | <u>TEST STANDARDS</u> | 4 |
| 2. | <u>SUMMARY</u> | 5 |
| 2.1. | General Remarks | 5 |
| 2.2. | Product Description | 5 |
| 2.3. | Equipment under Test | 5 |
| 2.4. | Short description of the Equipment under Test (EUT) | 6 |
| 2.5. | EUT Configuration | 6 |
| 2.6. | EUT operation mode | 6 |
| 2.7. | EUT configuration | 6 |
| 2.8. | Related Submittal(s) / Grant (s) | 6 |
| 2.9. | Modifications | 7 |
| 2.10. | Note | 7 |
| 3. | <u>TEST ENVIRONMENT</u> | 8 |
| 3.1. | Address of the test laboratory | 8 |
| 3.2. | Test Facility | 8 |
| 3.3. | Environmental conditions | 9 |
| 3.4. | Configuration of Tested System | 9 |
| 3.5. | Discription of Tested Modes | 9 |
| 3.6. | Statement of the measurement uncertainty | 9 |
| 3.7. | Test Description | 10 |
| 3.8. | Equipments Used during the Test | 10 |
| 4. | <u>TEST CONDITIONS AND RESULTS</u> | 12 |
| 4.1. | Conducted Emissions Test | 12 |
| 4.2. | Occupied Bandwidth and Emission Mask Test | 17 |
| 4.3. | Transmitter Radiated Spurious Emssion | 29 |
| 4.4. | Spurious Emssion on Antenna Port | 34 |
| 4.5. | Modulation Charcateristics | 54 |
| 4.6. | Frequency Stability Test | 57 |
| 4.7. | Maximum Transmitter Power | 59 |
| 4.8. | Transmitter Frequency Behavior | 66 |
| 4.9. | Receiver Radiated Spurious Emssion | 69 |
| 4.10. | Receiver Conducted Spurious Emssion | 79 |
| 4.11. | RF Exposure Evaluation | 83 |
| 5. | <u>TEST SETUP PHOTOS OF THE EUT</u> | 85 |
| 6. | <u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u> | 89 |

1. TEST STANDARDS

The tests were performed according to following standards:

FCC Rules Part 90: PRIVATE LAND MOBILE RADIO SERVICES.

TIA/EIA 603: Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

ANSI C63.4-2009: American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.

FCC Rules Part 15 Subpart B: RADIO FREQUENCY DEVICES-Unintentional Radiators

2. SUMMARY

2.1. General Remarks

| | | |
|--------------------------------|---|--------------|
| Date of receipt of test sample | : | Dec 24, 2011 |
| | | |
| Testing commenced on | : | Dec 24, 2011 |
| | | |
| Testing concluded on | : | Dec 27, 2011 |

2.2. Product Description

The Hytera Communications Corporation Ltd.'s Model: MD782G U(2)/ MD785G U(2)/ MD786G U(2)/ MD788G U(2) or the "EUT" as referred to in this report; more general information as follows, for more details, refer to the user's manual of the EUT.

| | | |
|---------------------------|--|---|
| Name of EUT | Digital Mobile Radio | |
| Model Number | MD782G U(2)/ MD785G U(2)/ MD786G U(2)/ MD788G U(2) | |
| FCC ID | YAMMD78XG-U2 | |
| Rated Output Power | 45 Watts(46.53 dBm)/5 Watts(36.99 dBm) | |
| Support data rate | 9.6kbps | |
| Modulation Type | FM for Analog Voice | |
| | 4FSK for Digital Voice/Digital Data | |
| | 4FSK for Digital Data | |
| | Analog | 11K0F3E for 12.5KHz Channel Separation |
| Digital | 7K60FXD for Digital Data only | |
| | 7K60FXW for Digital Data & Digital Voice | |
| Channel Separation | Analog Voice | 12.5KHz |
| | Digital Voice/Data | 12.5KHz |
| | Digital Data | 12.5KHz |
| Antenna Type | External | |
| Frequency Range | From 450 MHz to 520 MHz | |
| Maximum Transmitter Power | Analog | 47.75 W for 12.5 KHz Channel Separation |
| | Digital | 47.53 W for 12.5 KHz Channel Separation |

Note: The product has the same digital working characters when operating in both two digitized voice/data mode (7K60FXD and 7K60FXW). So only one set of test results for digital modulation modes are provided in this test report.

2.3. Equipment under Test

Power supply system utilised

| | | | |
|----------------------|---|---|-----------------------------------|
| Power supply voltage | : | <input type="radio"/> 120V / 60 Hz | <input type="radio"/> 115V / 60Hz |
| | | <input type="radio"/> 12 V DC | <input type="radio"/> 24 V DC |
| | | <input checked="" type="radio"/> Other (specified in blank below) | |

DC 13.60 V

Test frequency list

| Modulation Type | Test Channel | Test Frequency |
|-----------------|----------------|----------------|
| Analog/FM | Low Channel | 450.5000 MHz |
| | Middle Channel | 485.0000 MHz |
| | High Channel | 519.5000 MHz |
| Digital/4FSK | Low Channel | 450.5000 MHz |
| | Middle Channel | 485.0000 MHz |
| | High Channel | 519.5000 MHz |

2.4. Short description of the Equipment under Test (EUT)

450-520 MHz U frequency band Digital Mobile Radio with GPS function (MD782G U(2)/ MD785G U(2)/ MD786G U(2)/ MD788G U(2)).

For more details, refer to the user’s manual of the EUT.

Serial number: Prototype

2.5. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission’s requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.6. EUT operation mode

The EUT has been tested under typical operating condition and The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.7. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- supplied by the manufacturer
- supplied by the lab

| | | | |
|----------------------------------|-------------|----------------|------------|
| <input checked="" type="radio"/> | Power Cable | Length (m) : | 3 |
| | | Shield : | Unshield |
| | | Detachable : | Detachable |
| <input type="radio"/> | Multimeter | Manufacturer : | / |
| | | Model No. : | / |

2.8. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: **YAMMD78GX-U2** filing to comply with FCC Part 90 Rules

2.9. Modifications

No modifications were implemented to meet testing criteria.

2.10. Note

1. The EUT is a U frequency band (450-520 MHz) Digital Mobile Radio with GPS function, The functions of the EUT listed as below:

| | Test Standards | Reference Report |
|--------|----------------|------------------|
| Radio | FCC Part 90 | TRE1112009301 |
| Health | Oet 65 | TRE1112009302 |

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen Huatongwei International Inspection Co., Ltd
Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China
Phone: 86-755-26715686 Fax: 86-755-26748089

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2009) and CISPR Publication 22.

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories, Date of Registration: August 02, 2007. Valid time is until March 29, 2012.

A2LA-Lab Cert. No. 2243.01

Shenzhen Huatongwei International Inspection Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing. Valid time to Sep 30, 2013.

FCC-Registration No.: 662850

Shenzhen Huatongwei International Inspection Co., Ltd, EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 662850, Renewal date July 01, 2009.

IC-Registration No.: 5377

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377 on February 24th, 2011.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd, EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

NEMKO-Aut. No.: ELA125

Shenzhen Huatongwei International Inspection Co., Ltd has been assessed the quality assurance system, the testing facilities, qualifications and testing practices of the relevant parts of the organization. The quality assurance system of the Laboratory has been validated against ISO/IEC 17025:2005 or equivalent. The laboratory also fulfils the conditions described in Nemko Document NLA-10; the Authorization is valid through July 07, 2013.

VCCI

The 3m Semi-anechoic chamber (12.2m×7.95m×6.7m) and Shielded Room (8m×4m×3m) of Shenzhen Huatongwei International Inspection Co., Ltd has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2484. Date of Registration: December 20, 2009. Valid time is until December 19, 2012.

Main Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-2726. Date of Registration: December 20, 2009. Valid time is until December 19, 2012.

DNV

Shenzhen Huatongwei International Inspection Co Ltd has been found to comply with the requirements of DNV towards subcontractor of EMC and safety testing services in conjunction with the EMC and Low voltage Directives and in the voluntary field. The acceptance is based on a formal quality Audit and follow-ups according to relevant parts of ISO/IEC Guide 17025(2005), in accordance with the requirements of the DNV Laboratory Quality Manual towards subcontractors. Valid time is until 24 August, 2013.


3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

| | |
|-----------------------|--------------|
| Temperature: | 15-35 ° C |
| Humidity: | 30-60 % |
| Atmospheric pressure: | 950-1050mbar |

3.4. Configuration of Tested System

Fig. 2-1 Configuration of Tested System



3.5. Discription of Tested Modes

The EUT (Digital Mobile Radio) has been tested under normal operating condition. Three channels (the high, the middle and the low) are chosen for testing at each channel separation (12.5 KHz).

3.6. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

| Test Items | Measurement Uncertainty | Notes |
|--|-------------------------|-------|
| Frequency stability | 150 Hz | (1) |
| Transmitter power conducted | 0.30 dB | (1) |
| Transmitter power Radiated | 2.20 dB | (1) |
| Conducted spurious emission 9KHz-12.75 GHz | 1.60 dB | (1) |
| Radiated spurious emission 9KHz-12.75 GHz | 2.20 dB | (1) |
| Conducted Emission 9KHz-30MHz | 3.39 dB | (1) |
| Radiated Emission 30~1000MHz | 4.24 dB | (1) |
| Radiated Emissio 1~18GHz | 5.16 dB | (1) |
| Radiated Emissio 18-40GHz | 5.54 dB | (1) |
| Occupied Bandwidth | ----- | (1) |
| Emission Mask | ----- | (1) |
| Modulation Characteristic | ----- | (1) |
| Transmitter Frequency Behavior | ----- | (1) |

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

3.7. Test Description

| FCC Rules | Description of Test | Test Result |
|-----------|---------------------------------------|-------------|
| § 15.107 | Conducted Emission | Complies |
| § 15.109 | Receiver Radiated Spurious Emssion | Complies |
| § 15.109 | Receiver Conducted Spurious Emssion | Complies |
| § 90.205 | Maximum Transmitter Power | Complies |
| § 90.207 | Modulation Characteristic | Complies |
| § 90.209 | Occupied Bandwidth | Complies |
| § 90.210 | Emission Mask | Complies |
| § 90.213 | Frequency Stability | Complies |
| § 90.214 | Transmitter Frequency Behavior | Complies |
| § 90.210 | Transmitter Radiated Spurious Emssion | Complies |
| § 90.210 | Spurious Emssion On Antenna Port | Complies |
| § 2.1091 | RF Exposure Evaluation | Complies |

3.8. Equipments Used during the Test

| DC Power Conducted Emission | | | | |
|-----------------------------|---------------|-------------|---------------|-----------------|
| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
| Artificial Mains | Rohde&Schwarz | ESH2-Z6 | 100210 | 23/10/2012 |
| Artificial Mains | Rohde&Schwarz | ESH2-Z6 | 100211 | 23/10/2012 |
| EMI Test Receiver | Rohde&Schwarz | ESCS 30 | 100038 | 23/10/2012 |
| Pulse Limiter | Rohde&Schwarz | ESHSZ2 | 100044 | 23/10/2012 |
| EMI Test Software | Rohde&Schwarz | ES-K1 V1.71 | N/A | 23/10/2012 |

| Modulation Characteristic | | | | |
|---------------------------|---------------|-------|---------------|-----------------|
| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
| Signal Generator | Rohde&Schwarz | SMT03 | 100059 | 23/10/2012 |
| RF COMMUNICATION TEST SET | HP | 8920A | 3813A10206 | 23/10/2012 |

| Transient Frequency Behavior | | | | |
|------------------------------|---------------|----------|---------------|-----------------|
| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
| Signal Generator | Rohde&Schwarz | SMT03 | 100059 | 23/10/2012 |
| Storage Oscilloscope | Tektronix | TDS3054B | B033027 | 23/10/2012 |
| RF COMMUNICATION TEST SET | HP | 8920A | 3813A10206 | 23/10/2012 |

| Transmitter Radiated Spurious Emssion & Occupied Bandwidth & Emission Mask & Receiver Radiated Spurious Emssion | | | | |
|---|---------------|-------------|---------------|-----------------|
| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
| Ultra-Broadband Antenna | Rohde&Schwarz | HL562 | 100015 | 23/10/2012 |
| EMI Test Receiver | Rohde&Schwarz | ESI 26 | 100009 | 23/10/2012 |
| RF Test Panel | Rohde&Schwarz | TS / RSP | 335015/ 0017 | N/A |
| HORN ANTENNA | Rohde&Schwarz | HF906 | 100039 | 23/10/2012 |
| Turntable | ETS | 2088 | 2149 | N/A |
| Antenna Mast | ETS | 2075 | 2346 | N/A |
| High-Pass Filter | Anritsu | MP526B | 6220875256 | 23/10/2012 |
| High-Pass Filter | Anritsu | MP526D | 6220878392 | 23/10/2012 |
| EMI Test Software | Rohde&Schwarz | ES-K1 V1.71 | N/A | 23/10/2012 |
| RF COMMUNICATION TEST SET | HP | 8920A | 3813A10206 | 23/10/2012 |
| Spectrum Analyzer | Aglient | E4407B | MY44210775 | 23/10/2012 |

| Frequency Stability | | | | |
|------------------------|---------------|---------|---------------|-----------------|
| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
| Communication Test Set | HP | HP8920B | US35010135 | 23/10/2012 |
| Signal Generator | Rohde&Schwarz | SMT03 | 100059 | 23/10/2012 |
| Climate Chamber | ESPEC | EL-10KA | 05107008 | 23/10/2012 |

| Maximum Transmitter Power & Spurious Emssion On Antenna Port | | | | |
|--|---------------|---------|---------------|-----------------|
| Name of Equipment | Manufacturer | Model | Serial Number | Calibration Due |
| Receiver | Rohde&Schwarz | ESI 26 | 100009 | 23/10/2012 |
| Attenuator | R&S | ESH3-22 | 100449 | 23/10/2012 |
| RF COMMUNICATION TEST SET | HP | 8920A | 3813A10206 | 23/10/2012 |
| High-Pass Filter | Anritsu | MP526B | 6220875256 | 23/10/2012 |
| High-Pass Filter | Anritsu | MP526D | 6220878392 | 23/10/2012 |


4. TEST CONDITIONS AND RESULTS

4.1. Conducted Emissions Test

TEST APPLICABLE

The EUT was tested according to ANSI C63.4 - 2009. The frequency spectrum from 0.15 MHz to 30 MHz was investigated. The LISN used was 50 ohm / 50 u Henry as specified by section 5.1 of ANSI C63.4 - 2009. Cables and peripherals were moved to find the maximum emission levels for each frequency.

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4-2009.
- 2 Support equipment, if needed, was placed as per ANSI C63.4-2009.
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4-2009.
- 4 If a EUT received DC power from the adapter, the adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

Conducted Power Line Emission Limit

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following :

| Frequency (MHz) | Maximum RF Line Voltage (dBµV) | | | |
|-----------------|--------------------------------|------|---------|--------|
| | CLASS A | | CLASS B | |
| | Q.P. | Ave. | Q.P. | Ave. |
| 0.15 - 0.50 | 79 | 66 | 66-56* | 56-46* |
| 0.50 - 5.00 | 73 | 60 | 56 | 46 |
| 5.00 - 30.0 | 73 | 60 | 60 | 50 |

* Decreasing linearly with the logarithm of the frequency


For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

TEST RESULTS

For FM Modulation @ 12.5 KHz TX Mode

SCAN TABLE: "Voltage (9K-30M) FIN"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "HTW1226385_fin"

12/26/2011 6:33PM

| Frequency MHz | Level dBµV | Transd dB | Limit dBµV | Margin dB | Detector | Line | PE |
|---------------|------------|-----------|------------|-----------|----------|------|-----|
| 0.397500 | 22.50 | 10.1 | 58 | 35.4 | QP | + | GND |
| 0.847500 | 26.60 | 10.1 | 56 | 29.4 | QP | + | GND |
| 0.865500 | 26.60 | 10.1 | 56 | 29.4 | QP | + | GND |
| 2.323500 | 14.00 | 10.2 | 56 | 42.0 | QP | + | GND |
| 7.615500 | 0.50 | 10.3 | 60 | 59.5 | QP | + | GND |
| 25.201500 | 10.20 | 10.7 | 60 | 49.8 | QP | + | GND |


MEASUREMENT RESULT: "HTW1226385_fin2"

12/26/2011 6:33PM

| Frequency MHz | Level dBµV | Transd dB | Limit dBµV | Margin dB | Detector | Line | PE |
|---------------|------------|-----------|------------|-----------|----------|------|-----|
| 0.226500 | 8.60 | 10.1 | 53 | 44.0 | AV | + | GND |
| 0.438000 | 24.60 | 10.1 | 47 | 22.5 | AV | + | GND |
| 0.874500 | 11.10 | 10.1 | 46 | 34.9 | AV | + | GND |
| 2.355000 | -3.00 | 10.2 | 46 | 49.0 | AV | + | GND |
| 7.548000 | -4.30 | 10.3 | 50 | 54.3 | AV | + | GND |
| 25.201500 | 8.90 | 10.7 | 50 | 41.1 | AV | + | GND |

SCAN TABLE: "Voltage (9K-30M) FIN"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "HTW1226386_fin"

12/26/2011 6:37PM

| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.393000 | 19.70 | 10.1 | 58 | 38.3 | QP | - | GND |
| 0.888000 | 25.00 | 10.1 | 56 | 31.0 | QP | - | GND |
| 0.897000 | 25.00 | 10.1 | 56 | 31.0 | QP | - | GND |
| 2.391000 | 16.40 | 10.2 | 56 | 39.6 | QP | - | GND |
| 5.140500 | 0.60 | 10.2 | 60 | 59.4 | QP | - | GND |
| 25.201500 | 9.50 | 10.7 | 60 | 50.5 | QP | - | GND |

MEASUREMENT RESULT: "HTW1226386_fin2"


12/26/2011 6:37PM

| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.226500 | 17.80 | 10.1 | 53 | 34.8 | AV | - | GND |
| 0.438000 | 23.60 | 10.1 | 47 | 23.5 | AV | - | GND |
| 1.077000 | 9.10 | 10.2 | 46 | 36.9 | AV | - | GND |
| 2.310000 | -2.80 | 10.2 | 46 | 48.8 | AV | - | GND |
| 7.710000 | -4.20 | 10.3 | 50 | 54.2 | AV | - | GND |
| 25.201500 | 8.10 | 10.7 | 50 | 41.9 | AV | - | GND |

For 4FSK Modulation @ 12.5 KHz TX Mode

SCAN TABLE: "Voltage (9K-30M) FIN"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "HTW1226387_fin"

12/26/2011 6:41PM

| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.361500 | 17.40 | 10.1 | 59 | 41.3 | QP | - | GND |
| 0.879000 | 23.70 | 10.1 | 56 | 32.3 | QP | - | GND |
| 0.924000 | 22.90 | 10.1 | 56 | 33.1 | QP | - | GND |
| 2.292000 | 7.60 | 10.2 | 56 | 48.4 | QP | - | GND |
| 12.057000 | -0.80 | 10.4 | 60 | 60.8 | QP | - | GND |
| 22.335000 | 1.60 | 10.5 | 60 | 58.4 | QP | - | GND |


MEASUREMENT RESULT: "HTW1226387_fin2"

12/26/2011 6:41PM

| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.226500 | 19.70 | 10.1 | 53 | 32.9 | AV | - | GND |
| 0.438000 | 22.80 | 10.1 | 47 | 24.3 | AV | - | GND |
| 1.077000 | 10.60 | 10.2 | 46 | 35.4 | AV | - | GND |
| 2.152500 | -2.40 | 10.2 | 46 | 48.4 | AV | - | GND |
| 11.994000 | -2.80 | 10.4 | 50 | 52.8 | AV | - | GND |
| 27.420000 | -2.70 | 10.8 | 50 | 52.7 | AV | - | GND |

SCAN TABLE: "Voltage (9K-30M) FIN"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "HTW1226388_fin"

12/26/2011 6:45PM

| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.384000 | 16.60 | 10.1 | 58 | 41.6 | QP | + | GND |
| 0.865500 | 21.60 | 10.1 | 56 | 34.4 | QP | + | GND |
| 0.897000 | 20.90 | 10.1 | 56 | 35.1 | QP | + | GND |
| 2.287500 | 0.60 | 10.2 | 56 | 55.4 | QP | + | GND |
| 22.281000 | 34.90 | 10.5 | 60 | 25.1 | QP | + | GND |
| 24.004500 | 34.10 | 10.7 | 60 | 25.9 | QP | + | GND |

MEASUREMENT RESULT: "HTW1226388_fin2"

12/26/2011 6:45PM


| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.177000 | 7.60 | 10.1 | 55 | 47.0 | AV | + | GND |
| 0.438000 | 22.80 | 10.1 | 47 | 24.3 | AV | + | GND |
| 0.874500 | 9.40 | 10.1 | 46 | 36.6 | AV | + | GND |
| 10.293000 | -3.40 | 10.5 | 50 | 53.4 | AV | + | GND |
| 22.303500 | -1.90 | 10.5 | 50 | 51.9 | AV | + | GND |
| 23.955000 | -3.00 | 10.7 | 50 | 53.0 | AV | + | GND |

4.2. Occupied Bandwidth and Emission Mask Test

TEST APPLICABLE

- (a). Occupied Bandwidth: The EUT was connected to the audio signal generator and the spectrum analyzer via the main RF connector, and through an appropriate attenuator. The EUT was controlled to transmit its maximum power. Then the bandwidth of 99% power can be measured by the spectrum analyzer.
- (b). Emission Mask B: For transmitters that are equipped with an audio low-pass filter pursuant to §90.211(a), the power of any emission must be below the unmodulated carrier power (P) as follows:
- (1) On any frequency removed from the assigned frequency by more than 50 percent, but not more than 100 percent of the authorized bandwidth: At least 25 dB.
 - (2) On any frequency removed from the assigned frequency by more than 100 percent, but not more than 250 percent of the authorized bandwidth: At least 35 dB.
 - (3) On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least $43 + 10 \log (P)$ dB.
- (c). Emission Mask D, 12.5 kHz channel bandwidth equipment: For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:
- (1) On any frequency from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 : Zero dB.
 - (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least $7.27(f_d - 2.88 \text{ kHz})$ dB.
 - (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz: At least $50 + 10 \log (P)$ dB or 70 dB, whichever is the lesser attenuation.

TEST CONFIGURATION



TEST PROCEDURE

- 1 The EUT was placed on a turn table which is 0.8m above ground plane.
- 2 The EUT was modulated by 2.5 KHz Sine wave audio signal; the level of the audio signal employed is 16 dB greater than that necessary to produce 50% of rated system deviation. Rated system deviation is 2.5 kHz (12.5 kHz channel spacing) and 5 kHz (25 kHz channel spacing).
- 3 Set EUT as normal operation.
- 4 Set SPA Center Frequency = fundamental frequency, RBW=300Hz, VBW= 3 KHz, span =50 KHz.
- 5 Set SPA Max hold. Mark peak, Set 99% Occupied Bandwidth and 26dB Occupied Bandwidth.
- 6 Set SPA Center Frequency=fundamental frequency, RBW=300Hz, VBW=3 KHz span=50 KHz for 25 KHz channel spacing, while RBW=100Hz, VBW=1 KHz, span=50 KHz for 12.5 channel spacing.


TEST RESULTS

4.2.1 Occupied Bandwidth


| Modulation Type | Channel Separation | Test Channel | Test Frequency | 99% Occupied Bandwidth | 26dB Occupied Band width |
|-----------------|--------------------|---|----------------|------------------------|--------------------------|
| FM | 12.5KHz | Low | 450.5000 MHz | 5.61 KHz | 10.32 KHz |
| | | Middle | 485.0000 MHz | 5.41 KHz | 10.02 KHz |
| | | High | 519.5000 MHz | 5.51 KHz | 10.02 KHz |
| 4FSK | 12.5KHz | Low | 450.5000 MHz | 7.81 KHz | 10.02 KHz |
| | | Middle | 485.0000 MHz | 7.52 KHz | 9.82 KHz |
| | | High | 519.5000 MHz | 7.62 KHz | 9.42 KHz |
| Limit | | 11.25KHz for 12.5KHz Channel Separation | | | |
| Test Results | | Compliance | | | |

Plots of 99% and 26dB Bandwidth Measurement

| Modulation Type | Channel Separation | Freq.(MHz) | 99% Bandwidth (KHz) | 26dB Bandwidth (KHz) | FCC Limit (KHz) | Results |
|-----------------|--------------------|------------|---------------------|----------------------|-----------------|------------|
| FM | 12.5 KHz | 450.5000 | 5.61 | 10.32 | 11.25 | Compliance |




| Modulation Type | Channel Separation | Freq.(MHz) | 99% Bandwidth (KHz) | 26dB Bandwidth (KHz) | FCC Limit (KHz) | Results |
|-----------------|--------------------|------------|---------------------|----------------------|-----------------|------------|
| FM | 12.5 KHz | 485.0000 | 5.41 | 10.02 | 11.25 | Compliance |




Date: 27.DEC.2011 00:12:07

| Modulation Type | Channel Separation | Freq.(MHz) | 99% Bandwidth (KHz) | 26dB Bandwidth (KHz) | FCC Limit (KHz) | Results |
|-----------------|--------------------|------------|---------------------|----------------------|-----------------|------------|
| FM | 12.5 KHz | 519.5000 | 5.51 | 10.02 | 11.25 | Compliance |




Date: 27.DEC.2011 00:13:25

| Modulation Type | Channel Separation | Freq.(MHz) | 99% Bandwidth (KHz) | 26dB Bandwidth (KHz) | FCC Limit (KHz) | Results |
|-----------------|--------------------|------------|---------------------|----------------------|-----------------|------------|
| 4FSK | 12.5 KHz | 450.5000 | 7.81 | 10.02 | 11.25 | Compliance |




Date: 27.DEC.2011 00:15:23

| Modulation Type | Channel Separation | Freq.(MHz) | 99% Bandwidth (KHz) | 26dB Bandwidth (KHz) | FCC Limit (KHz) | Results |
|-----------------|--------------------|------------|---------------------|----------------------|-----------------|------------|
| 4FSK | 12.5 KHz | 485.0000 | 7.52 | 9.82 | 11.25 | Compliance |



Date: 27.DEC.2011 00:17:25

| Modulation Type | Channel Separation | Freq.(MHz) | 99% Bandwidth (KHz) | 26dB Bandwidth (KHz) | FCC Limit (KHz) | Results |
|-----------------|--------------------|------------|---------------------|----------------------|-----------------|------------|
| 4FSK | 12.5 KHz | 519.5000 | 7.62 | 9.42 | 11.25 | Compliance |



Date: 27.DEC.2011 00:19:00

4.2.2 Emission Mask

| Modulation Type | Channel Separation | Test Channel | Test Frequency | FCC Applicable Mask | RBW |
|-----------------|--------------------|--------------|----------------|---------------------|--------|
| FM | 12.5KHz | Low | 450.5000 MHz | D | 100 Hz |
| | | Middle | 485.0000 MHz | D | 100 Hz |
| | | High | 519.5000 MHz | D | 100 Hz |
| 4FSK | 12.5KHz | Low | 450.5000 MHz | D | 100 Hz |
| | | Middle | 485.0000 MHz | D | 100 Hz |
| | | High | 519.5000 MHz | D | 100 Hz |
| Test Results | | Compliance | | | |

Plots of Emission Mask Measurement

Referred as the attached plot hereinafter


Note: The yellow curve represents unmodulated signal.

The green curve represents modulated signal.

| Modulation Type | Channel Separation | Freq.(MHz) | FCC Applicable Mask | RBW | Audio Freq. (KHz) | Results |
|-----------------|--------------------|------------|---------------------|-------|-------------------|------------|
| FM | 12.5 KHz | 450.5000 | D | 100Hz | 2.5 | Compliance |



Delta 2 [T2] RBW 100 Hz RF Att 20 dB
 Ref Lvl -84.96 dB VBW 1 kHz
 50 dBm 12.50000000 kHz SWT 25 s Unit dBm




Date: 27.DEC.2011 00:32:03

12.5 kHz Channel Spacing, 450.5000 MHz, 2500 Hz Audio Modulation Only

| Modulation Type | Channel Separation | Freq.(MHz) | FCC Applicable Mask | RBW | Audio Freq. (KHz) | Results |
|-----------------|--------------------|------------|---------------------|-------|-------------------|------------|
| FM | 12.5 KHz | 485.0000 | D | 100Hz | 2.5 | Compliance |



Delta 2 [T2] RBW 100 Hz RF Att 20 dB
Ref Lvl -87.38 dB VBW 1 kHz
50 dBm 12.50000000 kHz SWT 25 s Unit dBm




Date: 27.DEC.2011 00:27:47

12.5 kHz Channel Spacing, 485.0000 MHz, 2500 Hz Audio Modulation Only

| Modulation Type | Channel Separation | Freq.(MHz) | FCC Applicable Mask | RBW | Audio Freq. (KHz) | Results |
|-----------------|--------------------|------------|---------------------|-------|-------------------|------------|
| FM | 12.5 KHz | 519.5000 | D | 100Hz | 2.5 | Compliance |



Delta 2 [T2] RBW 100 Hz RF Att 20 dB
 Ref Lvl -86.95 dB VBW 1 kHz
 50 dBm 12.50000000 kHz SWT 25 s Unit dBm




Date: 27.DEC.2011 00:22:56

12.5 kHz Channel Spacing, 519.5000 MHz, 2500 Hz Audio Modulation Only

| Modulation Type | Channel Separation | Freq.(MHz) | FCC Applicable Mask | RBW | Audio Freq. (KHz) | Results |
|-----------------|--------------------|------------|---------------------|-------|-------------------|------------|
| 4FSK | 12.5 KHz | 450.5000 | D | 100Hz | / | Compliance |



Delta 2 [T2] RBW 100 Hz RF Att 20 dB
 Ref Lvl -85.43 dB VBW 1 kHz
 50 dBm 12.50000000 kHz SWT 25 s Unit dBm




Date: 27.DEC.2011 00:33:15

12.5 kHz Channel Spacing, 450.5000 MHz, 4FSK Modulation Only

| Modulation Type | Channel Separation | Freq.(MHz) | FCC Applicable Mask | RBW | Audio Freq. (KHz) | Results |
|-----------------|--------------------|------------|---------------------|-------|-------------------|------------|
| 4FSK | 12.5 KHz | 485.0000 | D | 100Hz | / | Compliance |



Delta 2 [T2] RBW 100 Hz RF Att 20 dB
Ref Lvl -86.63 dB VBW 1 kHz
50 dBm 12.50000000 kHz SWT 25 s Unit dBm




Date: 27.DEC.2011 00:28:54

12.5 kHz Channel Spacing, 485.0000 MHz, 4FSK Modulation Only

| Modulation Type | Channel Separation | Freq.(MHz) | FCC Applicable Mask | RBW | Audio Freq. (KHz) | Results |
|-----------------|--------------------|------------|---------------------|-------|-------------------|------------|
| 4FSK | 12.5 KHz | 519.5000 | D | 100Hz | / | Compliance |



Delta 2 [T2] RBW 100 Hz RF Att 20 dB
Ref Lvl -85.09 dB VBW 1 kHz
50 dBm 12.50000000 kHz SWT 25 s Unit dBm



Date: 27.DEC.2011 00:24:43

12.5 kHz Channel Spacing, 519.5000 MHz, 4FSK Modulation Only

4.3. Transmitter Radiated Spurious Emission

TEST APPLICABLE



According to the TIA/EIA 603 test method, and according to Section 90.210, the power of each unwanted emission shall be less than Transmitted Power as specified below for transmitters designed to operate with 12.5 KHz channel bandwidth:

- 1 On any frequency removed from the center of the authorized bandwidth f_0 to 5.625 KHz removed from f_0 : Zero dB
 - 2 On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in KHz) f_0 of more than 5.625 KHz but no more than 12.5 KHz: At least 7.27dB
 - 3 On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in KHz) f_0 of more than 12.5 KHz: At least $50 + 10 \log(P)$ dB or 70 dB, which ever is lesser attenuation.
- For transmitters designed to transmit with 25 KHz channel separation and equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as following:



- 1 On any frequency removed from the assigned frequency by more than 50 percent, but no more than 100 percent of the authorized bandwidth: At least 25 dB.
- 2 On any frequency removed from the assigned frequency by more than 100 percent, but no more than 250 percent of the authorized bandwidth: At least 35 dB.
- 3 On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least $43 + 10 \log(P)$ dB.

TEST CONFIGURATION

Below 1GHz



Above 1GHz

**TEST PROCEDURE**

- 1 Set the EMI Receiver (for measuring E-Field) and Receiver (for measuring EIRP) as follows:
Center Frequency: equal to the signal source
Resolution BW: 100 KHz
Video BW: VBW > RBW
Detector Mode: positive
Average: off
Span: 3 x the signal bandwidth
- 2 Load an appropriate correction factors file in EMI Receiver for correcting the field strength reading level
Total Correction Factor recorded in the EMI Receiver = Cable Loss + Antenna Factor + Amplifier Gain
 $E \text{ (dBuV/m)} = \text{Reading (dBuV)} + \text{Total Correction Factor (dB)}$
- 3 The transmitter under test was placed at the specified height on a non-conducting turntable (80 cm height)
- 4 Substitute the EUT by a signal generator and one of the following transmitting antenna (substitution antenna):
DIPOLE antenna for frequency from 30-1000 MHz or
HORN antenna for frequency above 1 GHz}.
- 5 Mount the transmitting antenna at 1.0 meter high from the ground plane.
- 6 Use one of the following antenna as a receiving antenna:
DIPOLE antenna for frequency from 30-1000 MHz or
HORN antenna for frequency above 1 GHz}.
- 7 If the DIPOLE antenna is used, tune it's elements to the frequency as specified in the calibration manual.
- 8 Adjust both transmitting and receiving antenna in a VERTICAL polarization.
- 9 Tune the EMI Receivers to the test frequency.
- 10 Lower or raise the test antenna from 1 to 4 meters until the maximum signal level was detected.

- 11 The transmitter was rotated through 360o about a vertical axis until a higher maximum signal was received.
 - 12 Lower or raise the test antenna from 1 to 4 meters until the maximum signal level was detected.
 - 13 Adjust input signal to the substitution antenna until an equal or a known related level to that detected from the transmitter was obtained in the test receiver.
 - 14 Record the power level read from the Average Power Meter and calculate the ERP/EIRP as follows:

$$P = P_1 - L_1 = (P_2 + L_2) - L_1 = P_3 + A + L_2 - L_1$$

$$\text{EIRP} = P + G_1 = P_3 + L_2 - L_1 + A + G_1$$

$$\text{ERP} = \text{EIRP} - 2.15 \text{ dB}$$

$$\text{Total Correction factor in EMI Receiver} = L_2 - L_1 + G_1$$
- Where:
- P: Actual RF Power fed into the substitution antenna port after corrected.
 - P₁: Power output from the signal generator
 - P₂: Power measured at attenuator A input
 - P₃: Power reading on the Average Power Meter
 - EIRP: EIRP after correction
 - ERP: ERP after correction
- 15 Adjust both transmitting and receiving antenna in a Horizontal polarization, then repeat step (11) to (14).
 - 16 Repeat step (4) to (16) for different test frequency
 - 17 Repeat steps (3) to (12) with the substitution antenna oriented in horizontal polarization.
 - 18 Actual gain of the EUT's antenna is the difference of the measured EIRP and measured RF power at the RF port. Correct the antenna gain if necessary.

TEST RESULTS

The Transmitter Radiated Spurious Emssion was performed to the Rated high power (45Watt) and Rated low power (5Watt) the datum that reported below is the worst case (Rated high power) of the two rated power conditions.

Modulation Type: FM

FCC Part 22.359, 74.462, 80.211 and 90.210 and RSS Gen, RSS 119 Issue 11 (12.5 kHz bandwidth only): On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f d in kHz) of more than 12.5 kHz at least:

Low: $50 + 10 \log (\text{Pwatts}) = 50 + 10 \log (46.88) = 66.71 \text{ dB}$

High: $50 + 10 \log (\text{Pwatts}) = 50 + 10 \log (47.75) = 66.79 \text{ dB}$

Note: In general, the worse case attenuation requirement shown above was applied.

Calculation: Limit (dBm) = EL-50-10log10 (TP)

Notes: EL is the emission level of the Output Power expressed in dBm,
 In this application, the EL is 46.53 dBm.
 Limit (dBm) = 46.53-50-10log10 (47.75) = -20 dBm

Modulation Type: 4FSK

FCC Part 22.359, 74.462, 80.211 and 90.210 and RSS Gen, RSS 119 Issue 11 (12.5 kHz Bandwidth only): On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f d in kHz) of more than 12.5 kHz at least:

Low: $50 + 10 \log (\text{Pwatts}) = 50 + 10 \log (47.10) = 66.73 \text{ dB}$

High: $50 + 10 \log (\text{Pwatts}) = 50 + 10 \log (47.53) = 66.77 \text{ dB}$

Note: In general, the worse case attenuation requirement shown above was applied.

Calculation: Limit (dBm) = EL-50-10log10 (TP)

Notes: EL is the emission level of the Output Power expressed in dBm,
 In this application, the EL is 46.53 dBm.
 Limit (dBm) = 46.53-50-10log10 (47.53) = -20 dBm

Note: 1. In general, the worse case attenuation requirement shown above was applied.

2. The measurement frequency range from 30 MHz to 6 GHz.

3. *** means that the emission level is too low to be measured or at least 20 dB down than the limit.

| Modulation | | FM | | Channel Separation | | 12.5KHz | | |
|-----------------|------------------------|------------------------|----------------------|---------------------|----------------------|---|-------------|-------------|
| Test Channel | | Low Channel | | Test Frequency | | 450.5000 MHz | | |
| Frequency (MHz) | E-Field Level (dBuV/m) | EMI Detector (Peak/QP) | Antenna Polarization | Antenna Height (cm) | Table Angle (Degree) | ERP measured by Substitution Method (dBm) | Limit (dBm) | Margin (dB) |
| 901.00 | 55.56 | Peak | H | 300 | 245 | -41.21 | -20 | 21.21 |
| 1351.50 | 49.45 | Peak | H | 221 | 200 | -46.59 | -20 | 26.59 |
| 1802.00 | 49.56 | Peak | H | 109 | 56 | -47.32 | -20 | 27.32 |
| ... | ... | | H | | | | | |
| 901.00 | 51.77 | Peak | V | 108 | 335 | -45.23 | -20 | 25.23 |
| 1351.50 | 49.56 | Peak | V | 100 | 28 | -47.00 | -20 | 27.00 |
| 1802.00 | 48.68 | Peak | V | 100 | 110 | -47.67 | -20 | 27.67 |
| ... | ... | | V | | | | | |

| Modulation | | FM | | Channel Separation | | 12.5KHz | | |
|-----------------|------------------------|------------------------|----------------------|---------------------|----------------------|---|-------------|-------------|
| Test Channel | | Middle Channel | | Test Frequency | | 485.0000 MHz | | |
| Frequency (MHz) | E-Field Level (dBuV/m) | EMI Detector (Peak/QP) | Antenna Polarization | Antenna Height (cm) | Table Angle (Degree) | ERP measured by Substitution Method (dBm) | Limit (dBm) | Margin (dB) |
| 970.00 | 54.55 | Peak | H | 305 | 300 | -42.34 | -20 | 22.34 |
| 1455.00 | 52.00 | Peak | H | 267 | 97 | -44.96 | -20 | 24.96 |
| 2425.00 | 49.83 | Peak | H | 100 | 111 | -46.65 | -20 | 26.65 |
| ... | ... | | H | | | | | |
| 970.00 | 53.21 | Peak | V | 108 | 56 | -43.55 | -20 | 23.55 |
| 1455.00 | 49.97 | Peak | V | 100 | 108 | -46.11 | -20 | 26.11 |
| 2425.00 | 49.52 | Peak | V | 124 | 179 | -47.55 | -20 | 27.55 |
| ... | ... | | V | | | | | |

| Modulation | | FM | | Channel Separation | | 12.5KHz | | |
|-----------------|------------------------|------------------------|----------------------|---------------------|----------------------|---|-------------|-------------|
| Test Channel | | High Channel | | Test Frequency | | 519.5000 MHz | | |
| Frequency (MHz) | E-Field Level (dBuV/m) | EMI Detector (Peak/QP) | Antenna Polarization | Antenna Height (cm) | Table Angle (Degree) | ERP measured by Substitution Method (dBm) | Limit (dBm) | Margin (dB) |
| 1039.00 | 54.43 | Peak | H | 400 | 255 | -42.11 | -20 | 22.11 |
| 1558.50 | 50.31 | Peak | H | 209 | 200 | -46.55 | -20 | 26.55 |
| 2078.00 | 50.69 | Peak | H | 155 | 255 | -45.76 | -20 | 25.76 |
| ... | ... | | H | | | | | |
| 1039.00 | 56.02 | Peak | V | 156 | 341 | -40.53 | -20 | 20.53 |
| 1558.50 | 53.77 | Peak | V | 100 | 31 | -43.33 | -20 | 23.33 |
| 2078.00 | 49.76 | Peak | V | 105 | 134 | -46.68 | -20 | 26.68 |
| ... | ... | | V | | | | | |

| Modulation | | 4FSK | | Channel Separation | | 12.5KHz | | |
|-----------------|------------------------|------------------------|----------------------|---------------------|----------------------|---|-------------|-------------|
| Test Channel | | Low Channel | | Test Frequency | | 450.5000 MHz | | |
| Frequency (MHz) | E-Field Level (dBuV/m) | EMI Detector (Peak/QP) | Antenna Polarization | Antenna Height (cm) | Table Angle (Degree) | ERP measured by Substitution Method (dBm) | Limit (dBm) | Margin (dB) |
| 901.00 | 55.51 | Peak | H | 200 | 123 | -41.04 | -20 | 21.04 |
| 1351.50 | 52.11 | Peak | H | 159 | 320 | -44.66 | -20 | 24.66 |
| 1802.00 | 49.32 | Peak | H | 345 | 122 | -47.45 | -20 | 27.45 |
| ... | ... | | H | | | | | |
| 901.00 | 54.64 | Peak | V | 100 | 275 | -42.23 | -20 | 22.23 |
| 1351.50 | 51.53 | Peak | V | 124 | 345 | -45.02 | -20 | 25.02 |
| 1802.00 | 45.05 | Peak | V | 100 | 264 | -47.00 | -20 | 27.00 |
| ... | ... | | V | | | | | |

| Modulation | | 4FSK | | Channel Separation | | 12.5KHz | | |
|-----------------|------------------------|------------------------|----------------------|---------------------|----------------------|---|-------------|-------------|
| Test Channel | | Middle Channel | | Test Frequency | | 485.0000 MHz | | |
| Frequency (MHz) | E-Field Level (dBuV/m) | EMI Detector (Peak/QP) | Antenna Polarization | Antenna Height (cm) | Table Angle (Degree) | ERP measured by Substitution Method (dBm) | Limit (dBm) | Margin (dB) |
| 970.00 | 56.32 | Peak | H | 350 | 289 | -40.33 | -20 | 20.33 |
| 1455.00 | 50.78 | Peak | H | 145 | 312 | -45.51 | -20 | 25.51 |
| 2425.00 | 49.87 | Peak | H | 100 | 100 | -46.44 | -20 | 26.44 |
| ... | ... | | H | | | | | |
| 970.00 | 54.56 | Peak | V | 128 | 277 | -42.04 | -20 | 22.04 |
| 1455.00 | 50.94 | Peak | V | 104 | 184 | -45.95 | -20 | 25.95 |
| 2425.00 | 49.94 | Peak | V | 100 | 0 | -47.00 | -20 | 27.00 |
| ... | ... | | V | | | | | |

| Modulation | | 4FSK | | Channel Separation | | 12.5KHz | | |
|-----------------|------------------------|------------------------|----------------------|---------------------|----------------------|---|-------------|-------------|
| Test Channel | | High Channel | | Test Frequency | | 519.5000 MHz | | |
| Frequency (MHz) | E-Field Level (dBuV/m) | EMI Detector (Peak/QP) | Antenna Polarization | Antenna Height (cm) | Table Angle (Degree) | ERP measured by Substitution Method (dBm) | Limit (dBm) | Margin (dB) |
| 1039.00 | 54.44 | Peak | H | 231 | 222 | -42.22 | -20 | 22.22 |
| 1588.50 | 51.38 | Peak | H | 300 | 101 | -45.66 | -20 | 25.66 |
| 2078.00 | 96.11 | Peak | H | 100 | 304 | -47.44 | -20 | 27.44 |
| ... | ... | | H | | | | | |
| 1039.00 | 50.78 | Peak | V | 100 | 155 | -45.55 | -20 | 25.55 |
| 1588.50 | 51.63 | Peak | V | 100 | 294 | -44.71 | -20 | 24.71 |
| 2078.00 | 49.51 | Peak | V | 100 | 67 | -47.04 | -20 | 27.04 |
| ... | ... | | V | | | | | |

4.4. Spurious Emission on Antenna Port

TEST APPLICABLE


The same as Section 4.3

TEST PROCEDURE

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set to 100 kHz. Sufficient scans were taken to show any out of band emission up to 10th. Harmonic for the lower and the highest frequency range. Set RBW 100 kHz, VBW 300 kHz in the frequency band 30MHz to 1GHz, while set RBW=1MHz. VBW=3MHz from the 1GHz to 10th Harmonic.

The audio input was set to 0 to get the unmodulated carrier, the resulting picture is print out for each channel separation.

TEST CONFIGURATION



TEST RESULTS

Modulation Type: FM

FCC Part 22.359, 74.462, 80.211 and 90.210 and RSS Gen, RSS 119 Issue 11 (12.5 kHz bandwidth only): On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f d in kHz) of more than 12.5 kHz at least:

Low: $50 + 10 \log (P_{\text{watts}}) = 50 + 10 \log (46.88) = 66.71 \text{ dB}$

High: $50 + 10 \log (P_{\text{watts}}) = 50 + 10 \log (47.75) = 66.79 \text{ dB}$

Note: In general, the worse case attenuation requirement shown above was applied.

Calculation: Limit (dBm) = $EL - 50 - 10 \log_{10} (TP)$

Notes: EL is the emission level of the Output Power expressed in dBm, In this application, the EL is 46.53 dBm.

Limit (dBm) = $46.53 - 50 - 10 \log_{10} (47.75) = -20 \text{ dBm}$

Modulation Type: 4FSK

FCC Part 22.359, 74.462, 80.211 and 90.210 and RSS Gen, RSS 119 Issue 11 (12.5 kHz Bandwidth only):
 On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f d in kHz) of more than 12.5 kHz at least:

Low: $50 + 10 \log(P_{\text{watts}}) = 50 + 10 \log(47.10) = 66.73 \text{ dB}$

High: $50 + 10 \log(P_{\text{watts}}) = 50 + 10 \log(47.53) = 66.77 \text{ dB}$

Note: In general, the worse case attenuation requirement shown above was applied.

Calculation: $\text{Limit (dBm)} = \text{EL} - 50 - 10 \log_{10}(\text{TP})$

Notes: EL is the emission level of the Output Power expressed in dBm,

In this application, the EL is 46.53 dBm.

$\text{Limit (dBm)} = 46.53 - 50 - 10 \log_{10}(47.53) = -20 \text{ dBm}$

Note: 1. In general, the worse case attenuation requirement shown above was applied.

2. The measurement frequency range from 30 MHz to 6 GHz.

For Rated High Power (45Watt)

| Modulation Type | Channel Separation | Test Channel | Test Frequency (MHz) | Maximum Conducted Spurious Emissions Below 1GHz | | Maximum Conducted Spurious Emissions Above 1GHz | |
|-----------------|--------------------|---------------------------------------|----------------------|---|-------------|---|-------------|
| | | | | Frequency (MHz) | Datum (dBm) | Frequency (MHz) | Datum (dBm) |
| FM | 12.5KHz | Low | 450.5000 | 906.16 | -25.27 | 5859.72 | -27.19 |
| | | Middle | 485.0000 | 968.32 | -25.24 | 5729.46 | -27.04 |
| | | High | 519.5000 | 853.25 | -25.09 | 5939.88 | -26.90 |
| 4FSK | 12.5KHz | Low | 450.5000 | 891.73 | -23.24 | 5829.66 | -27.83 |
| | | Middle | 485.0000 | 463.77 | -25.40 | 5619.24 | -27.08 |
| | | High | 519.5000 | 967.60 | -25.24 | 5979.96 | -26.36 |
| Limit | | -20dBm for 12.5KHz Channel Separation | | | | | |
| Test Results | | Compliance | | | | | |


For Rated Low Power (5Watt)

| Modulation Type | Channel Separation | Test Channel | Test Frequency (MHz) | Maximum Conducted Spurious Emissions Below 1GHz | | Maximum Conducted Spurious Emissions Above 1GHz | |
|-----------------|--------------------|---------------------------------------|----------------------|---|-------------|---|-------------|
| | | | | Frequency (MHz) | Datum (dBm) | Frequency (MHz) | Datum (dBm) |
| FM | 12.5KHz | Low | 450.5000 | 900.86 | -24.67 | 5799.60 | -27.27 |
| | | Middle | 485.0000 | 970.84 | -25.10 | 5709.42 | -27.23 |
| | | High | 519.5000 | 955.29 | -35.44 | 1040.08 | -24.10 |
| 4FSK | 12.5KHz | Low | 450.5000 | 900.86 | -30.09 | 5118.24 | -27.36 |
| | | Middle | 485.0000 | 970.84 | -24.96 | 5929.86 | -27.43 |
| | | High | 519.5000 | 982.51 | -35.73 | 1040.08 | -24.06 |
| Limit | | -20dBm for 12.5KHz Channel Separation | | | | | |
| Test Results | | Compliance | | | | | |


Plots of Spurious Emission on Antenna Port Measurement

For Rated High Power (45Watt)


| Modulation Type | Channel Separation | Test Channel | Test Frequency (MHz) | Maximum Conducted Spurious Emissions Below 1GHz | | Maximum Conducted Spurious Emissions Above 1GHz | | FCC Limit |
|-----------------|--------------------|--------------|----------------------|---|-------------|---|-------------|-----------|
| | | | | Frequency (MHz) | Datum (dBm) | Frequency (MHz) | Datum (dBm) | |
| FM | 12.5KHz | Low | 450.5000 | 906.16 | -25.27 | 5859.72 | -27.19 | -20dBm |
| Test Results | | | | Compliance | | | | |




Date: 27.DEC.2011 09:39:52



Date: 27.DEC.2011 09:41:28




Date: 27.DEC.2011 09:42:59




Date: 27.DEC.2011 09:44:41


| Modulation Type | Channel SpARATION | Test Channel | Test Frequency (MHz) | Maximum Conducted Spurious Emissions Below 1GHz | | Maximum Conducted Spurious Emissions Above 1GHz | | FCC Limit |
|-----------------|-------------------|--------------|----------------------|---|-------------|---|-------------|-----------|
| | | | | Frequency (MHz) | Datum (dBm) | Frequency (MHz) | Datum (dBm) | |
| FM | 12.5KHz | Middle | 485.0000 | 968.32 | -25.24 | 5729.46 | -27.04 | -20dBm |
| Test Results | | | | Compliance | | | | |




Date: 27.DEC.2011 09:55:43



Date: 27.DEC.2011 09:58:40




Date: 27.DEC.2011 10:00:03




Date: 27.DEC.2011 09:45:17


| Modulation Type | Channel SpARATION | Test Channel | Test Frequency (MHz) | Maximum Conducted Spurious Emissions Below 1GHz | | Maximum Conducted Spurious Emissions Above 1GHz | | FCC Limit |
|-----------------|-------------------|--------------|----------------------|---|-------------|---|-------------|-----------|
| | | | | Frequency (MHz) | Datum (dBm) | Frequency (MHz) | Datum (dBm) | |
| FM | 12.5KHz | High | 519.5000 | 853.25 | -25.09 | 5939.88 | -26.90 | -20dBm |
| Test Results | | | | Compliance | | | | |




Date: 27.DEC.2011 09:54:46



Date: 27.DEC.2011 09:51:45




Date: 27.DEC.2011 09:49:43




Date: 27.DEC.2011 09:46:01


| Modulation Type | Channel Separation | Test Channel | Test Frequency (MHz) | Maximum Conducted Spurious Emissions Below 1GHz | | Maximum Conducted Spurious Emissions Above 1GHz | | FCC Limit |
|-----------------|--------------------|--------------|----------------------|---|-------------|---|-------------|-----------|
| | | | | Frequency (MHz) | Datum (dBm) | Frequency (MHz) | Datum (dBm) | |
| 4FSK | 12.5KHz | Low | 450.50000 | 891.73 | -23.24 | 5829.66 | -27.83 | -20dBm |
| Test Results | | | | Compliance | | | | |




Date: 27.DEC.2011 10:05:18



Date: 27.DEC.2011 10:04:25




Date: 27.DEC.2011 10:01:34




Date: 27.DEC.2011 09:46:30


| Modulation Type | Channel SpARATION | Test Channel | Test Frequency (MHz) | Maximum Conducted Spurious Emissions Below 1GHz | | Maximum Conducted Spurious Emissions Above 1GHz | | FCC Limit |
|-----------------|-------------------|--------------|----------------------|---|-------------|---|-------------|-----------|
| | | | | Frequency (MHz) | Datum (dBm) | Frequency (MHz) | Datum (dBm) | |
| 4FSK | 12.5KHz | Middle | 485.0000 | 463.77 | -25.40 | 5619.24 | -27.08 | -20dBm |
| Test Results | | | | Compliance | | | | |




Date: 27.DEC.2011 09:56:17



Date: 27.DEC.2011 09:57:39




Date: 27.DEC.2011 10:00:48




Date: 27.DEC.2011 09:46:58



| Modulation Type | Channel Separation | Test Channel | Test Frequency (MHz) | Maximum Conducted Spurious Emissions Below 1GHz | | Maximum Conducted Spurious Emissions Above 1GHz | | FCC Limit |
|-----------------|--------------------|--------------|----------------------|---|-------------|---|-------------|-----------|
| | | | | Frequency (MHz) | Datum (dBm) | Frequency (MHz) | Datum (dBm) | |
| 4FSK | 12.5KHz | High | 519.5000 | 967.60 | -25.24 | 5979.96 | -26.36 | -20dBm |
| Test Results | | | | Compliance | | | | |



Date: 27.DEC.2011 09:54:00




Date: 27.DEC.2011 09:52:46




For Rated Low Power (5Watt)

| Modulation Type | Channel Separation | Test Channel | Test Frequency (MHz) | Maximum Conducted Spurious Emissions Below 1GHz | | Maximum Conducted Spurious Emissions Above 1GHz | | FCC Limit |
|-----------------|--------------------|--------------|----------------------|---|-------------|---|-------------|-----------|
| | | | | Frequency (MHz) | Datum (dBm) | Frequency (MHz) | Datum (dBm) | |
| FM | 12.5KHz | Low | 450.5000 | 900.86 | -24.67 | 5799.60 | -27.27 | -20dBm |
| Test Results | | | | Compliance | | | | |




Date: 27.DEC.2011 10:07:23




Date: 27.DEC.2011 10:13:15

| Modulation Type | Channel Separation | Test Channel | Test Frequency (MHz) | Maximum Conducted Spurious Emissions Below 1GHz | | Maximum Conducted Spurious Emissions Above 1GHz | | FCC Limit |
|-----------------|--------------------|--------------|----------------------|---|-------------|---|-------------|-----------|
| | | | | Frequency (MHz) | Datum (dBm) | Frequency (MHz) | Datum (dBm) | |
| FM | 12.5KHz | Middle | 485.0000 | 970.84 | -25.10 | 5709.42 | -27.23 | -20dBm |
| Test Results | | | | Compliance | | | | |




Date: 27.DEC.2011 10:09:05




Date: 27.DEC.2011 10:12:47

| Modulation Type | Channel Sparation | Test Channel | Test Frequency (MHz) | Maximum Conducted Spurious Emissions Below 1GHz | | Maximum Conducted Spurious Emissions Above 1GHz | | FCC Limit |
|-----------------|-------------------|--------------|----------------------|---|-------------|---|-------------|-----------|
| | | | | Frequency (MHz) | Datum (dBm) | Frequency (MHz) | Datum (dBm) | |
| FM | 12.5KHz | High | 519.5000 | 955.29 | -35.44 | 1040.08 | -24.10 | -20dBm |
| Test Results | | | | Compliance | | | | |




Date: 27.DEC.2011 10:09:32




Date: 27.DEC.2011 10:12:12

| Modulation Type | Channel Separation | Test Channel | Test Frequency (MHz) | Maximum Conducted Spurious Emissions Below 1GHz | | Maximum Conducted Spurious Emissions Above 1GHz | | FCC Limit |
|-----------------|--------------------|--------------|----------------------|---|-------------|---|-------------|-----------|
| | | | | Frequency (MHz) | Datum (dBm) | Frequency (MHz) | Datum (dBm) | |
| 4FSK | 12.5KHz | Low | 450.5000 | 900.86 | -30.09 | 5118.24 | -27.36 | -20dBm |
| Test Results | | | | | | | | |




Date: 27.DEC.2011 10:07:55




Date: 27.DEC.2011 10:11:39

| Modulation Type | Channel Separation | Test Channel | Test Frequency (MHz) | Maximum Conducted Spurious Emissions Below 1GHz | | Maximum Conducted Spurious Emissions Above 1GHz | | FCC Limit |
|-----------------|--------------------|--------------|----------------------|---|-------------|---|-------------|-----------|
| | | | | Frequency (MHz) | Datum (dBm) | Frequency (MHz) | Datum (dBm) | |
| 4FSK | 12.5KHz | Middle | 485.0000 | 970.84 | -24.96 | 5929.86 | -27.43 | -20dBm |
| Test Results | | | | Compliance | | | | |




Date: 27.DEC.2011 10:08:27




Date: 27.DEC.2011 10:11:17

| Modulation Type | Channel Separation | Test Channel | Test Frequency (MHz) | Maximum Conducted Spurious Emissions Below 1GHz | | Maximum Conducted Spurious Emissions Above 1GHz | | FCC Limit |
|-----------------|--------------------|--------------|----------------------|---|-------------|---|-------------|-----------|
| | | | | Frequency (MHz) | Datum (dBm) | Frequency (MHz) | Datum (dBm) | |
| 4FSK | 12.5KHz | High | 519.5000 | 982.51 | -35.73 | 1040.08 | -24.06 | -20dBm |
| Test Results | | | | Compliance | | | | |



Date: 27.DEC.2011 10:09:58



Date: 27.DEC.2011 10:10:44

4.5. Modulation Characteristics

TEST APPLICABLE

According to CFR47 section 2.1047(a), for Voice Modulation Communication Equipment, the frequency response of the audio modulation circuit over a range of 100 to 5000Hz shall be measured.

TEST PROCEDURE


Modulation Limit

- 1 Configure the EUT as shown in figure 1, adjust the audio input for 60% of rated system deviation at 1 KHz using this level as a reference (0dB) and vary the input level from -20 to +20dB. Record the frequency deviation obtained as a function of the input level.
- 2 Repeat step 1 with input frequency changing to 300, 1004, 1500 and 2500Hz in sequence.

Audio Frequency Response

- 1 Configure the EUT as shown in figure 1.
- 2 Adjust the audio input for 20% of rated system deviation at 1 KHz using this level as a reference (0dB).
- 3 Vary the Audio frequency from 100 Hz to 3 KHz and record the frequency deviation.
- 4 Audio Frequency Response = $20 \log_{10} (\text{Deviation of test frequency} / \text{Deviation of 1 KHz reference})$.

TEST CONFIGURATION




TEST RESULTS

Modulation Type: FM

12.5 KHz Channel Separation

| Modulation Level(dB) | Peak Freq. Deviation At 300 Hz(KHz) | Peak Freq. Deviation At 1004 H(KHz) | Peak Freq. Deviation At 1500 Hz(KHz) | Peak Freq. Deviation At 2500 Hz(KHz) |
|----------------------|-------------------------------------|-------------------------------------|--------------------------------------|--------------------------------------|
| -20 | 0.08 | 0.19 | 0.25 | 0.42 |
| -15 | 0.11 | 0.28 | 0.41 | 0.69 |
| -10 | 0.16 | 0.51 | 0.72 | 1.23 |
| -5 | 0.26 | 0.86 | 1.25 | 2.14 |
| 0 | 0.44 | 1.57 | 2.21 | 2.30 |
| +5 | 0.73 | 2.26 | 2.21 | 2.30 |
| +10 | 1.28 | 2.26 | 2.21 | 2.30 |
| +15 | 2.24 | 2.26 | 2.21 | 2.30 |
| +20 | 2.36 | 2.26 | 2.21 | 2.30 |



Modulation type: 4FSK

Channel bandwidth: 12.5 kHz

It is not applicable for devices which operate with the digitized voice/data modulation type.

b). Audio Frequency Response:

Rule Part No.: Part 2.1407(a) (b)

Method of Measurement:

The audio frequency response was measured in accordance with TIA/EIA Specification 603 with no exception. A curve or equivalent data showing the frequency response of the audio modulating circuit over a range of 300-3000Hz shall be submitted and Audio Post Limiter Low Pass Filter Response from 3.0 KHz to 50KHz. However, the audio frequency response should test from 100Hz to 5.0 KHz according to FCC Part 90.

Modulation Type: FM

The audio frequency response curve is show below.and


Test Audio Level (1 KHz and 20% maximum deviation) for 12.5 KHz channel separation is 23 mv.

Note:

- 1 Not applicable to new standard. However, tests are conducted under FCC's recommendation.
- 2 The Audio Frequency Response is identical for 12.5 KHz channel separation

12.5 KHz Channel Separation

| Frequency (KHz) | Frequency Deviation (KHz) | 1KHz Reference Deviation (KHz) | Audio Frequency Response (dB) |
|-----------------|---------------------------|--------------------------------|-------------------------------|
| 0.1 | 0.04 | 0.50 | -21.94 |
| 0.2 | 0.04 | 0.50 | -21.94 |
| 0.3 | 0.15 | 0.50 | -10.46 |
| 0.4 | 0.21 | 0.50 | -7.54 |
| 0.5 | 0.26 | 0.50 | -5.68 |
| 0.6 | 0.32 | 0.50 | -3.88 |
| 0.7 | 0.37 | 0.50 | -2.62 |
| 0.8 | 0.40 | 0.50 | -1.94 |
| 0.9 | 0.45 | 0.50 | -0.92 |
| 1.0 | 0.50 | 0.50 | 0.00 |
| 1.2 | 0.56 | 0.50 | 0.98 |
| 1.4 | 0.68 | 0.50 | 2.67 |
| 1.6 | 0.75 | 0.50 | 3.52 |
| 1.8 | 0.89 | 0.50 | 5.00 |
| 2.0 | 0.97 | 0.50 | 5.75 |
| 2.2 | 1.11 | 0.50 | 6.92 |
| 2.4 | 1.16 | 0.50 | 7.30 |
| 2.6 | 1.28 | 0.50 | 8.16 |
| 2.7 | 1.30 | 0.50 | 8.29 |
| 2.8 | 1.30 | 0.50 | 8.29 |
| 3.0 | 1.34 | 0.50 | 8.56 |
| 3.5 | 0.04 | 0.50 | -21.94 |
| 4.0 | 0.04 | 0.50 | -21.94 |
| 4.5 | 0.04 | 0.50 | -21.94 |
| 5.0 | 0.04 | 0.50 | -21.94 |



Modulation type: 4FSK

Channel bandwidth: 12.5 kHz

It is not applicable for devices which operate with the digitized voice/data modulation type.

4.6. Frequency Stability Test


TEST APPLICABLE

- 1 According to FCC Part 2 Section 2.1055 (a)(1), the frequency stability shall be measured with variation of ambient temperature from -30°C to +60°C centigrade.
- 2 According to FCC Part 2 Section 2.1055 (a) (2), for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacture.
- 3 Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.
- 4 According to §90.213, the frequency stability limit is 2.5 ppm for 12.5 KHz channel separation.

TEST PROCEDURE

The EUT was set in the climate chamber and connected to an external DC power supply. The RF output was directly connected to Spectrum Analyzer ESI 26. The coupling loss of the additional cables was recorded and taken in account for all the measurements. After temperature stabilization (approx. 20 min for each stage), the frequency for the lower, the middle and the highest frequency range was recorded. For Frequency stability Vs. Voltage the EUT was connected to a DC power supply and the voltage was adjusted in the required ranges. The result was recorded.

TEST CONFIGURATION



TEST LIMITS

According to 90.213, Transmitters used must have minimum frequency stability as specified in the following table.

| Frequency Range (MHz) | Channel Bandwidth (KHz) | Frequency Tolerance (ppm) | | |
|-----------------------|-------------------------|---------------------------|-----------------|-------|
| | | Fixed and Base Stations | Mobile Stations | |
| | | | > 2 W | ≤ 2 W |
| 150-174 MHz | 6.25 | 1.0 | 2.0 | 2.0 |
| | 12.5 | 2.5 | 5.0 | 5.0 |
| | 25 | 5.0 | 5.0 | 50.0* |
| 421-512 MHz | 6.25 | 0.5 | 1.0 | 1.0 |
| | 12.5 | 1.5 | 2.5 | 2.5 |
| | 25 | 2.5 | 5.0 | 5.0 |

- Stations operating in the 154.45 to 154.49 MHz or the 173.2 to 173.4 MHz bands must have a frequency stability of 5 ppm.
- Paging transmitters operating on paging-only frequencies must operate with frequency stability of 5 ppm in the 150-174 MHz band and 2.5 ppm in the 421-512 MHz band.

TEST RESULTS

| Modulation Type | Channel Separation | Test conditions | | Frequency error (ppm) | | |
|-------------------|--------------------|------------------|----------|-----------------------|----------------|--------------|
| | | Voltage(V) | Temp(°C) | Low Channel | Middle Channel | High Channel |
| Analog/FM | 12.5KHz | 13.60 | -30 | 1.41 | 1.38 | 1.35 |
| | | | -20 | 1.22 | 1.20 | 1.02 |
| | | | -10 | 0.99 | 0.97 | 0.95 |
| | | | 0 | 0.81 | 0.89 | 0.88 |
| | | | 10 | 0.58 | 0.75 | 0.69 |
| | | | 20 | 0.58 | 0.69 | 0.69 |
| | | | 30 | 0.58 | 0.69 | 0.69 |
| | | | 40 | 0.88 | 0.79 | 0.88 |
| | | | 50 | 1.02 | 0.91 | 1.02 |
| | | 11.0 (85% Rated) | 20 | 0.71 | 0.74 | 0.78 |
| 15.6 (115% Rated) | 20 | 0.81 | 0.74 | 0.78 | | |
| Limit | | | 2.5 ppm | | | |
| Conclusion | | | Complies | | | |

| Modulation Type | Channel Separation | Test conditions | | Frequency error (ppm) | | |
|-------------------|--------------------|------------------|----------|-----------------------|----------------|--------------|
| | | Voltage(V) | Temp(°C) | Low Channel | Middle Channel | High Channel |
| Digital/4FSK | 12.5KHz | 13.60 | -30 | 1.41 | 1.37 | 1.35 |
| | | | -20 | 1.25 | 1.25 | 1.10 |
| | | | -10 | 1.00 | 1.02 | 0.99 |
| | | | 0 | 0.81 | 0.89 | 0.90 |
| | | | 10 | 0.81 | 0.80 | 0.69 |
| | | | 20 | 0.61 | 0.69 | 0.69 |
| | | | 30 | 0.58 | 0.69 | 0.69 |
| | | | 40 | 0.82 | 0.82 | 0.90 |
| | | | 50 | 1.05 | 0.99 | 1.02 |
| | | 11.0 (85% Rated) | 20 | 0.71 | 0.78 | 0.78 |
| 15.6 (115% Rated) | 20 | 0.81 | 0.74 | 0.78 | | |
| Limit | | | 2.5. ppm | | | |
| Conclusion | | | Complies | | | |

4.7. Maximum Transmitter Power

TEST APPLICABLE

Per FCC «2.1046 and «90.205: Maximum ERP is dependent upon the station’s antenna HAAT and required service area.

TEST PROCEDURE

Measurements shall be made to establish the radio frequency power delivered by the transmitter the standard output termination. The power output shall be monitored and recorded and no adjustment shall be made to the transmitter after the test has begun, except as noted bellow:

If the power output is adjustable, measurements shall be made for the highest and lowest power levels.

The EUT connect to the Receiver through 40 dB attenuator.

Measurement with Spectrum Analyzer ESI 26 conducted, external power supply with 13.60 V stabilized supply voltage.

TEST CONFIGURATION

| | | | | |
|-----|--|------------|--|----------------------------|
| EUT | | Attenuator | | Spectrum Analyzer/Receiver |
|-----|--|------------|--|----------------------------|


The EUT was directly connected to a RF Communication Test set by a 40 dB attenuator

TEST RESULTS


| Modulation Type | Channel Separation | Test Channel | Test Frequency | Maximum Transmitter Power at Rated High Power Level(dBm) | Maximum Transmitter Power at Rated Low Power Level(dBm) |
|-----------------|--------------------|---|----------------|--|---|
| Analog/FM | 12.5KHz | Low Channel | 450.5000 MHz | 46.79 | 36.76 |
| | | Middle Channel | 485.0000 MHz | 46.74 | 37.90 |
| | | High Channel | 519.5000 MHz | 46.71 | 37.86 |
| Digital/4FSK | 12.5KHz | Low Channel | 450.5000 MHz | 46.73 | 37.62 |
| | | Middle Channel | 485.0000 MHz | 46.74 | 37.82 |
| | | High Channel | 519.5000 MHz | 46.77 | 37.87 |
| Limit | | The limit is dependent upon the station’s antenna HAAT and required service area. | | | |
| Test Results | | Complicance | | | |

Plots of Maximum Transmitter Power Measurement


| Modulation Type | Channel Separation | Freq.(MHz) | Rated Power (Watt) | Measurement (dBm) | FCC Limit | Results |
|-----------------|--------------------|------------|--------------------|-------------------|-----------|-------------|
| FM | 12.5 KHz | 450.5000 | 45 | 46.79 | Varies | Complicance |




| Modulation Type | Channel Separation | Freq.(MHz) | Rated Power (Watt) | Measurement (dBm) | FCC Limit | Results |
|-----------------|--------------------|------------|--------------------|-------------------|-----------|-------------|
| FM | 12.5 KHz | 485.0000 | 45 | 46.74 | Varies | Complicance |




| Modulation Type | Channel Separation | Freq.(MHz) | Rated Power (Watt) | Measurement (dBm) | FCC Limit | Results |
|-----------------|--------------------|------------|--------------------|-------------------|-----------|-------------|
| FM | 12.5 KHz | 519.5000 | 45 | 46.71 | Varies | Complicance |




| Modulation Type | Channel Separation | Freq.(MHz) | Rated Power (Watt) | Measurement (dBm) | FCC Limit | Results |
|-----------------|--------------------|------------|--------------------|-------------------|-----------|-------------|
| 4FSK | 12.5 KHz | 450.5000 | 45 | 46.73 | Varies | Complicance |




| Modulation Type | Channel Separation | Freq.(MHz) | Rated Power (Watt) | Measurement (dBm) | FCC Limit | Results |
|-----------------|--------------------|------------|--------------------|-------------------|-----------|------------|
| 4FSK | 12.5 KHz | 485.0000 | 45 | 46.74 | Varies | Compliance |




| Modulation Type | Channel Separation | Freq.(MHz) | Rated Power (Watt) | Measurement (dBm) | FCC Limit | Results |
|-----------------|--------------------|------------|--------------------|-------------------|-----------|------------|
| 4FSK | 12.5 KHz | 519.5000 | 45 | 46.77 | Varies | Compliance |




| Modulation Type | Channel Separation | Freq.(MHz) | Rated Power (Watt) | Measurement (dBm) | FCC Limit | Results |
|-----------------|--------------------|------------|--------------------|-------------------|-----------|------------|
| FM | 12.5 KHz | 450.5000 | 5 | 37.76 | Varies | Compliance |




| Modulation Type | Channel Separation | Freq.(MHz) | Rated Power (Watt) | Measurement (dBm) | FCC Limit | Results |
|-----------------|--------------------|------------|--------------------|-------------------|-----------|------------|
| FM | 12.5 KHz | 485.0000 | 5 | 37.90 | Varies | Compliance |




| Modulation Type | Channel Separation | Freq.(MHz) | Rated Power (Watt) | Measurement (dBm) | FCC Limit | Results |
|-----------------|--------------------|------------|--------------------|-------------------|-----------|-------------|
| FM | 12.5 KHz | 519.5000 | 5 | 37.86 | Varies | Complicance |




| Modulation Type | Channel Separation | Freq.(MHz) | Rated Power (Watt) | Measurement (dBm) | FCC Limit | Results |
|-----------------|--------------------|------------|--------------------|-------------------|-----------|-------------|
| 4FSK | 12.5 KHz | 450.5000 | 5 | 37.62 | Varies | Complicance |



| Modulation Type | Channel Separation | Freq.(MHz) | Rated Power (Watt) | Measurement (dBm) | FCC Limit | Results |
|-----------------|--------------------|------------|--------------------|-------------------|-----------|-------------|
| 4FSK | 12.5 KHz | 485.0000 | 5 | 37.82 | Varies | Complicance |



| Modulation Type | Channel Separation | Freq.(MHz) | Rated Power (Watt) | Measurement (dBm) | FCC Limit | Results |
|-----------------|--------------------|------------|--------------------|-------------------|-----------|-------------|
| 4FSK | 12.5 KHz | 519.5000 | 5 | 37.87 | Varies | Complicance |



4.8. Transmitter Frequency Behavior

TEST APPLICABLE

Section 90.214

Transient frequencies must be within the maximum frequency difference limits during the time intervals indicated:


| Time intervals ^{1, 2} | Maximum frequency difference ³ | All equipment | |
|---|---|----------------|---------------|
| | | 150 to 174 MHz | 421 to 512MHz |
| Transient Frequency Behavior for Equipment Designed to Operate on 25 KHz Channels | | | |
| t ₁ ⁴ | ± 25.0 KHz | 5.0 ms | 10.0 ms |
| t ₂ ⁴ | ± 12.5 KHz | 20.0 ms | 25.0 ms |
| t ₃ ⁴ | ± 25.0 KHz | 5.0 ms | 10.0 ms |
| Transient Frequency Behavior for Equipment Designed to Operate on 12.5 KHz Channels | | | |
| t ₁ ⁴ | ± 12.5 KHz | 5.0 ms | 10.0 ms |
| t ₂ ⁴ | ± 6.25 KHz | 20.0 ms | 25.0 ms |
| t ₃ ⁴ | ± 12.5 KHz | 5.0 ms | 10.0 ms |
| Transient Frequency Behavior for Equipment Designed to Operate on 6.25 KHz Channels | | | |
| t ₁ ⁴ | ±6.25 KHz | 5.0 ms | 10.0 ms |
| t ₂ ⁴ | ±3.125 KHz | 20.0 ms | 25.0 ms |
| t ₃ ⁴ | ±6.25 KHz | 5.0 ms | 10.0 ms |

- t_{on} is the instant when a 1 KHz test signal is completely suppressed, including any capture time due to phasing.
 t₁ is the time period immediately following t_{on}.
 t₂ is the time period immediately following t₁.
 t₃ is the time period from the instant when the transmitter is turned off until t_{off}.
 t_{off} is the instant when the 1 KHz test signal starts to rise.
- During the time from the end of t₂ to the beginning of t₃, the frequency difference must not exceed the limits specified in § 90.213.
- Difference between the actual transmitter frequency and the assigned transmitter frequency.
- If the transmitter carrier output power rating is 6 watts or less, the frequency difference during this time period may exceed the maximum frequency difference for this time period.

TEST PROCEDURE

TIA/EIA-603 2.2.19



TEST CONFIGURATION



TEST RESULTS


Please refer to the following plots.

Modulation Type: FM




Modulation Type: 4FSK

Transmitter Frequency Behaviour @ 12.5 KHz Channel Separation-----Off – On



Transmitter Frequency Behaviour @ 12.5 KHz Channel Separation-----On - Off



4.9. Receiver Radiated Spurious Emission

TEST APPLICABLE


The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$


| | |
|---------------------------|--|
| Where FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
| RA = Reading Amplitude | AG = Amplifier Gain |
| AF = Antenna Factor | |

TEST CONFIGURATION

(A) Radiated Emission Test Set-Up, Frequency below 1000MHz



(B) Radiated Emission Test Set-Up, Frequency above 1000MHz



TEST PROCEDURE

- 1 The EUT was placed on a turn table which is 0.8m above ground plane.
- 2 Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
- 3 And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 4 Repeat above procedures until all frequency measurements have been completed.

RECEIVER RADIATED SPOUIOUS LIMIT

For unintentional device, according to § 15.109(a) and RSS-Gen, except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

| Frequency (MHz) | Distance (Meters) | Radiated (dB μ V/m) | Radiated (μ V/m) |
|--------------------|----------------------|----------------------------|--------------------------|
| 30-88 | 3 | 40.0 | 100 |
| 88-216 | 3 | 43.5 | 150 |
| 216-960 | 3 | 46.0 | 200 |
| Above 960 | 3 | 54.0 | 500 |

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.


TEST RESULTS

The Radiated Measurement are performed to the three channels (the high channel, the middle channel and the low channel), the datum recorded below is the worst case for each channel separation; and the EUT shall be scanned from 30 MHz to the 5th harmonic of the highest oscillator frequency in the digital devices or 1 GHz whichever is higher.

| Modulation Type | Channel Separation | Test Frequency (MHz) | Polar. | Maximum Radiated Emissions | | FCC Limit (dBuV/m) |
|-----------------|--------------------|----------------------|------------|----------------------------|----------------|--------------------|
| | | | | Frequency (MHz) | Datum (dBuV/m) | |
| FM | 12.5 KHz | 469.5000 | H | 990.28 | 22.40 | 46.00 |
| | | | V | 984.45 | 22.70 | 46.00 |
| Test Results | | | Compliance | | | |

SWEEP TABLE: "test (30M-1G)"

Short Description: Field Strength
 Start Stop Detector Meas. IF Transducer
 Frequency Frequency Time Bandw.
 30.0 MHz 1.0 GHz MaxPeak Coupled 100 kHz HL562 2011




MEASUREMENT RESULT: "HTW1226454_red"

12/26/2011 9:25AM

| Frequency MHz | Level dBμV/m | Transd dB | Limit dBμV/m | Margin dB | Det. | Height cm | Azimuth deg | Polarization |
|---------------|--------------|-----------|--------------|-----------|------|-----------|-------------|--------------|
| 30.000000 | 14.80 | -22.2 | 40.0 | 25.2 | Peak | 300.0 | 96.00 | HORIZONTAL |
| 96.092184 | 7.70 | -30.9 | 43.5 | 35.8 | Peak | 300.0 | 146.00 | HORIZONTAL |
| 117.474950 | 9.00 | -30.5 | 43.5 | 34.5 | Peak | 100.0 | 232.00 | HORIZONTAL |
| 224.388778 | 8.60 | -31.4 | 46.0 | 37.4 | Peak | 300.0 | 360.00 | HORIZONTAL |
| 395.450902 | 15.60 | -26.3 | 46.0 | 30.4 | Peak | 100.0 | 114.00 | HORIZONTAL |
| 990.280561 | 22.40 | -17.3 | 54.0 | 31.6 | Peak | 300.0 | 27.00 | HORIZONTAL |

SWEEP TABLE: "test (30M-1G)"

| | | | | | |
|--------------------|-----------|----------------|---------|---------|------------|
| Short Description: | | Field Strength | | | |
| Start | Stop | Detector | Meas. | IF | Transducer |
| Frequency | Frequency | | Time | Bandw. | |
| 30.0 MHz | 1.0 GHz | MaxPeak | Coupled | 100 kHz | HL562 2011 |



MEASUREMENT RESULT: "HTW1226453_red"


12/26/2011 9:24AM

| Frequency MHz | Level dBµV/m | Transd dB | Limit dBµV/m | Margin dB | Det. | Height cm | Azimuth deg | Polarization |
|------------------|-----------------|--------------|-----------------|--------------|------|--------------|----------------|--------------|
| 30.000000 | 14.30 | -22.2 | 40.0 | 25.7 | Peak | 100.0 | 278.00 | VERTICAL |
| 96.092184 | 9.00 | -30.9 | 43.5 | 34.5 | Peak | 100.0 | 328.00 | VERTICAL |
| 107.755511 | 8.90 | -30.6 | 43.5 | 34.6 | Peak | 100.0 | 62.00 | VERTICAL |
| 220.501002 | 8.30 | -31.5 | 46.0 | 37.7 | Peak | 100.0 | 296.00 | VERTICAL |
| 523.747495 | 15.30 | -23.9 | 46.0 | 30.7 | Peak | 100.0 | 29.00 | VERTICAL |
| 984.448898 | 22.70 | -17.3 | 54.0 | 31.3 | Peak | 100.0 | 263.00 | VERTICAL |

| Modulation Type | Channel Separation | Test Frequency (MHz) | Polar. | Maximum Radiated Emissions | | FCC Limit (dBuV/m) |
|-----------------|--------------------|----------------------|------------|----------------------------|----------------|--------------------|
| | | | | Frequency (MHz) | Datum (dBuV/m) | |
| FM | 12.5 KHz | 469.5000 | H | 5629.26 | 46.60 | 54.00 |
| | | | V | 5699.40 | 46.60 | 54.00 |
| Test Results | | | Compliance | | | |

SWEEP TABLE: "test (1G-18G) P"

Short Description: EN 55022 Field Strength
 Start Stop Detector Meas. IF Transducer
 Frequency Frequency Time Bandw.
 1.0 GHz 18.0 GHz MaxPeak Coupled 1 MHz HF906 2011




MEASUREMENT RESULT: "HTW1226481_red"

12/26/2011 4:26AM

| Frequency MHz | Level dBuV/m | Transd dB | Limit dBuV/m | Margin dB | Det. | Height cm | Azimuth deg | Polarization |
|------------------|-----------------|--------------|-----------------|--------------|------|--------------|----------------|--------------|
| 1260.521042 | 33.10 | -7.6 | 54.0 | 20.9 | Peak | 100.0 | 299.00 | HORIZONTAL |
| 1801.603206 | 37.20 | -3.0 | 54.0 | 16.8 | Peak | 100.0 | 311.00 | HORIZONTAL |
| 2442.885772 | 41.70 | 0.6 | 54.0 | 12.3 | Peak | 100.0 | 27.00 | HORIZONTAL |
| 2883.767535 | 43.00 | 1.8 | 54.0 | 11.0 | Peak | 100.0 | 215.00 | HORIZONTAL |
| 4146.292585 | 44.70 | 3.5 | 54.0 | 9.3 | Peak | 100.0 | 114.00 | HORIZONTAL |
| 5629.258517 | 46.60 | 6.8 | 54.0 | 7.4 | Peak | 100.0 | 79.00 | HORIZONTAL |

SWEEP TABLE: "test (1G-18G) P"

Short Description: EN 55022 Field Strength
 Start Stop Detector Meas. IF Transducer
 Frequency Frequency Time Bandw.
 1.0 GHz 18.0 GHz MaxPeak Coupled 1 MHz HF906 2011



MEASUREMENT RESULT: "HTW1226480_red"


12/26/2011 4:24AM

| Frequency MHz | Level dBµV/m | Transd dB | Limit dBµV/m | Margin dB | Det. | Height cm | Azimuth deg | Polarization |
|------------------|-----------------|--------------|-----------------|--------------|------|--------------|----------------|--------------|
| 1320.641283 | 31.80 | -7.2 | 54.0 | 22.2 | Peak | 100.0 | 3.00 | VERTICAL |
| 1641.282565 | 36.20 | -4.5 | 54.0 | 17.8 | Peak | 100.0 | 18.00 | VERTICAL |
| 2442.885772 | 40.50 | 0.6 | 54.0 | 13.5 | Peak | 100.0 | 84.00 | VERTICAL |
| 3084.168337 | 42.80 | 2.2 | 54.0 | 11.2 | Peak | 100.0 | 241.00 | VERTICAL |
| 4126.252505 | 43.50 | 3.6 | 54.0 | 10.5 | Peak | 100.0 | 12.00 | VERTICAL |
| 5699.398798 | 46.60 | 6.9 | 54.0 | 7.4 | Peak | 100.0 | 84.00 | VERTICAL |

| Modulation Type | Channel Separation | Test Frequency (MHz) | Polar. | Maximum Radiated Emissions | | FCC Limit (dBuV/m) |
|-----------------|--------------------|----------------------|------------|----------------------------|----------------|--------------------|
| | | | | Frequency (MHz) | Datum (dBuV/m) | |
| 4FSK | 12.5 KHz | 469.5000 | H | 980.56 | 23.00 | 54.00 |
| | | | V | 994.17 | 23.00 | 54.00 |
| Test Results | | | Compliance | | | |

SWEEP TABLE: "test (30M-1G)"

Short Description: Field Strength
 Start Stop Detector Meas. IF Transducer
 Frequency Frequency Time Bandw.
 30.0 MHz 1.0 GHz MaxPeak Coupled 100 kHz HL562 2011




MEASUREMENT RESULT: "HTW1226455_red"

12/26/2011 9:26AM

| Frequency MHz | Level dBμV/m | Transd dB | Limit dBμV/m | Margin dB | Det. | Height cm | Azimuth deg | Polarization |
|---------------|--------------|-----------|--------------|-----------|------|-----------|-------------|--------------|
| 30.000000 | 14.70 | -22.2 | 40.0 | 25.3 | Peak | 300.0 | 298.00 | HORIZONTAL |
| 96.092184 | 8.40 | -30.9 | 43.5 | 35.1 | Peak | 300.0 | 360.00 | HORIZONTAL |
| 117.474950 | 9.50 | -30.5 | 43.5 | 34.0 | Peak | 100.0 | 181.00 | HORIZONTAL |
| 222.444890 | 8.80 | -31.4 | 46.0 | 37.2 | Peak | 100.0 | 332.00 | HORIZONTAL |
| 508.196393 | 15.40 | -24.2 | 46.0 | 30.6 | Peak | 300.0 | 315.00 | HORIZONTAL |
| 980.561122 | 23.00 | -17.4 | 54.0 | 31.0 | Peak | 100.0 | 29.00 | HORIZONTAL |

SWEEP TABLE: "test (30M-1G)"

| | | | | | |
|--------------------|-----------|----------------|---------|---------|------------|
| Short Description: | | Field Strength | | | |
| Start | Stop | Detector | Meas. | IF | Transducer |
| Frequency | Frequency | | Time | Bandw. | |
| 30.0 MHz | 1.0 GHz | MaxPeak | Coupled | 100 kHz | HL562 2011 |



MEASUREMENT RESULT: "HTW1226456_red"


12/26/2011 9:27AM

| Frequency MHz | Level dBμV/m | Transd dB | Limit dBμV/m | Margin dB | Det. | Height cm | Azimuth deg | Polarization |
|------------------|-----------------|--------------|-----------------|--------------|------|--------------|----------------|--------------|
| 31.943888 | 15.20 | -23.2 | 40.0 | 24.8 | Peak | 100.0 | 113.00 | VERTICAL |
| 92.204409 | 8.00 | -31.1 | 43.5 | 35.5 | Peak | 100.0 | 300.00 | VERTICAL |
| 123.306613 | 9.00 | -30.6 | 43.5 | 34.5 | Peak | 100.0 | 264.00 | VERTICAL |
| 212.725451 | 7.80 | -31.9 | 43.5 | 35.5 | Peak | 100.0 | 149.00 | VERTICAL |
| 554.849699 | 15.80 | -24.6 | 46.0 | 30.2 | Peak | 100.0 | 282.00 | VERTICAL |
| 994.168337 | 23.00 | -17.2 | 54.0 | 31.0 | Peak | 100.0 | 62.00 | VERTICAL |

| Modulation Type | Channel Separation | Test Frequency (MHz) | Polar. | Maximum Radiated Emissions | | FCC Limit (dBuV/m) |
|-----------------|--------------------|----------------------|------------|----------------------------|----------------|--------------------|
| | | | | Frequency (MHz) | Datum (dBuV/m) | |
| 4FSK | 12.5 KHz | 469.5000 | H | 5468.94 | 46.10 | 54.00 |
| | | | V | 5659.32 | 46.50 | 54.00 |
| Test Results | | | Compliance | | | |

SWEEP TABLE: "test (1G-18G) P"

Short Description: EN 55022 Field Strength
 Start Stop Detector Meas. IF Transducer
 Frequency Frequency Time Bandw.
 1.0 GHz 18.0 GHz MaxPeak Coupled 1 MHz HF906 2011




MEASUREMENT RESULT: "HTW1226477_red"

12/26/2011 4:18AM

| Frequency MHz | Level dBμV/m | Transd dB | Limit dBμV/m | Margin dB | Det. | Height cm | Azimuth deg | Polarization |
|---------------|--------------|-----------|--------------|-----------|------|-----------|-------------|--------------|
| 1340.681363 | 32.30 | -7.0 | 54.0 | 21.7 | Peak | 100.0 | 314.00 | HORIZONTAL |
| 1661.322645 | 36.70 | -4.3 | 54.0 | 17.3 | Peak | 100.0 | 297.00 | HORIZONTAL |
| 2422.845691 | 41.10 | 0.6 | 54.0 | 12.9 | Peak | 100.0 | 62.00 | HORIZONTAL |
| 3114.228457 | 42.20 | 2.2 | 54.0 | 11.8 | Peak | 100.0 | 309.00 | HORIZONTAL |
| 3775.551102 | 43.40 | 3.2 | 54.0 | 10.6 | Peak | 100.0 | 33.00 | HORIZONTAL |
| 5468.937876 | 46.10 | 6.5 | 54.0 | 7.9 | Peak | 100.0 | 74.00 | HORIZONTAL |

SWEEP TABLE: "test (1G-18G) P"

Short Description: EN 55022 Field Strength
 Start Stop Detector Meas. IF Transducer
 Frequency Frequency Time Bandw.
 1.0 GHz 18.0 GHz MaxPeak Coupled 1 MHz HF906 2011



MEASUREMENT RESULT: "HTW1226476_red"

12/26/2011 4:16AM

| Frequency MHz | Level dBµV/m | Transd dB | Limit dBµV/m | Margin dB | Det. | Height cm | Azimuth deg | Polarization |
|------------------|-----------------|--------------|-----------------|--------------|------|--------------|----------------|--------------|
| 1320.641283 | 32.00 | -7.2 | 54.0 | 22.0 | Peak | 100.0 | 287.00 | VERTICAL |
| 1791.583166 | 36.90 | -3.1 | 54.0 | 17.1 | Peak | 100.0 | 57.00 | VERTICAL |
| 2332.665331 | 40.50 | 0.2 | 54.0 | 13.5 | Peak | 100.0 | 299.00 | VERTICAL |
| 2983.967936 | 43.10 | 2.1 | 54.0 | 10.9 | Peak | 100.0 | 228.00 | VERTICAL |
| 4076.152305 | 44.00 | 3.6 | 54.0 | 10.0 | Peak | 100.0 | 222.00 | VERTICAL |
| 5659.318637 | 46.50 | 6.8 | 54.0 | 7.5 | Peak | 100.0 | 12.00 | VERTICAL |

4.10. Receiver Conducted Spurious Emssion


TEST APPLICABLE

The same as Section 4.3

TEST PROCEDURE

The spectrum analyzer was connected to the RF output power of the EUT, the EUT was setup in receiving mode; The RBW of the spectrum analyzer was set to 100 kHz and the VBW set to 300 KHz below the test frequency 1GHz. While the RBW of the spectrum analyzer was set to the 1MHz and VBW set to the 3MHz from 1GHz to the 10th harmonic.

TEST CONFIGURATION




LIMIT

The power at the antenna terminal shall not exceed 2.0 nanowatts (-57dBm).


TEST RESULTS

The Receiver Conducted Spurious Emssions Measurement is performed to the three channels (the high channel, the middle channel and the low channel), the datums recorded below were for the three channels; and the EUT shall be scanned from 30 MHz to the 6 GHz.


The Low Channel for 12.5 KHz Channel Separation@Horizontal@FM Modulation




The Middle Channel for 12.5 KHz Channel Separation@Horizontal@FM Modulation




The High Channel for 12.5 KHz Channel Separation@Horizontal@FM Modulation




The Low Channel for 12.5 KHz Channel Separation@Horizontal@4FSK Modulation



The Middle Channel for 12.5 KHz Channel Separation@Horizontal@4FSK Modulation



The High Channel for 12.5 KHz Channel Separation@Horizontal@4FSK Modulation



4.11. RF Exposure Evaluation

Applicable Standard

According to §1.1307(b)(1) and RSS-102, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

According to §1.1310 and §2.1091 and RSS-102 RF exposure is calculated.

LIMIT

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

| Frequency Range(MHz) | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density (mW/cm ²) | Averaging Time (minute) |
|---|------------------------------|------------------------------|-------------------------------------|-------------------------|
| Limits for Occupational/Controlled Exposure | | | | |
| 0.3 – 3.0 | 614 | 1.63 | (100) * | 6 |
| 3.0 – 30 | 1842/f | 4.89/f | (900/f)* | 6 |
| 30 – 300 | 61.4 | 0.163 | 1.0 | 6 |
| 300 – 1500 | / | / | f/300 | 6 |
| 1500 – 100,000 | / | / | 5 | 6 |

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

| Frequency Range(MHz) | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density (mW/cm ²) | Averaging Time (minute) |
|---|------------------------------|------------------------------|-------------------------------------|-------------------------|
| Limits for Occupational/Controlled Exposure | | | | |
| 0.3 – 3.0 | 614 | 1.63 | (100) * | 30 |
| 3.0 – 30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30 – 300 | 27.5 | 0.073 | 0.2 | 30 |
| 300 – 1500 | / | / | f/1500 | 30 |
| 1500 – 100,000 | / | / | 1.0 | 30 |

F=frequency in MHz

*=Plane-wave equivalent power density

MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

As declared by the Applicant, the EUT transmits with the maximum soure-baed Duty Cycle of 50%-see the User manual, and the EUT is a wireless device used in a mobile application, at least 100cm from any body part of the user or nearby persons; from the peak EUT RF output power, the minimum mobile separation distance, R=100cm, as well as the gain of the used antenna is 5.5 dBi, the RF power density can be obtained.

TEST RESULTS

For FM Modulation @ 12.5 KHz Channel Spacing@Maximum Output Power

| Frequency (MHz) | Minimum Separation Distance (cm) | Output Power (dBm) | Output Power (mW) | Antenna Gain (Nemeric) | Power Density Limit (mW/cm ²) | Power Density At 100 cm (mW/cm ²) | Test Results |
|-----------------|----------------------------------|--------------------|-------------------|------------------------|---|---|--------------|
| 450.5000 | 100.00 | 46.79 | 47752.90 | 3.5481 | 1.5017 | 1.3483 | Compliance |
| 485.0000 | 100.00 | 46.74 | 47206.30 | 3.5481 | 1.6167 | 1.3329 | Compliance |
| 519.5000 | 100.00 | 46.71 | 46881.30 | 3.5481 | 1.7317 | 1.3237 | Compliance |

For 4FSK Modulation @ 12.5 KHz Channel Spacing@Maximum Output Power

| Frequency (MHz) | Minimum Separation Distance (cm) | Output Power (dBm) | Output Power (mW) | Antenna Gain (Nemeric) | Power Density Limit (mW/cm ²) | Power Density At 100 cm (mW/cm ²) | Test Results |
|-----------------|----------------------------------|--------------------|-------------------|------------------------|---|---|--------------|
| 450.5000 | 100.00 | 46.73 | 47097.70 | 3.5481 | 1.5017 | 1.3298 | Compliance |
| 485.0000 | 100.00 | 46.74 | 47206.30 | 3.5481 | 1.6167 | 1.3329 | Compliance |
| 519.5000 | 100.00 | 46.77 | 47533.50 | 3.5481 | 1.7317 | 1.3421 | Compliance |



For FM Modulation @ 12.5 KHz Channel Spacing@Minimum Output Power




| Frequency (MHz) | Minimum Separation Distance (cm) | Output Power (dBm) | Output Power (mW) | Antenna Gain (Nemeric) | Power Density Limit (mW/cm ²) | Power Density At 100 cm (mW/cm ²) | Test Results |
|-----------------|----------------------------------|--------------------|-------------------|------------------------|---|---|--------------|
| 450.5000 | 100.00 | 36.76 | 4742.40 | 3.5481 | 1.5017 | 0.1339 | Compliance |
| 485.0000 | 100.00 | 37.90 | 6166.00 | 3.5481 | 1.6167 | 0.1741 | Compliance |
| 519.5000 | 100.00 | 37.86 | 6109.40 | 3.5481 | 1.7317 | 0.1725 | Compliance |




For 4FSK Modulation @ 12.5 KHz Channel Spacing@Minimum Output Power


| Frequency (MHz) | Minimum Separation Distance (cm) | Output Power (dBm) | Output Power (mW) | Antenna Gain (Nemeric) | Power Density Limit (mW/cm ²) | Power Density At 100 cm (mW/cm ²) | Test Results |
|-----------------|----------------------------------|--------------------|-------------------|------------------------|---|---|--------------|
| 450.5000 | 100.00 | 37.62 | 5781.00 | 3.5481 | 1.5017 | 0.1632 | Compliance |
| 485.0000 | 100.00 | 37.82 | 6053.40 | 3.5481 | 1.6167 | 0.1709 | Compliance |
| 519.5000 | 100.00 | 37.87 | 6123.50 | 3.5481 | 1.7317 | 0.1729 | Compliance |

5. Test Setup Photos of the EUT









6. External and Internal Photos of the EUT



External Photos















Internal Photos





















.....End of Report.....