

FCC PART 15.247

TEST REPORT

For

Hytera Communications Corporation Limited

Hytera Tower, Hi-Tech Industrial Park North, 9108# Beihuan Road, Nanshan District, Shenzhen, 518057 China

FCC ID: YAMPD98XVHF

Report Type: Product Type:

Original Report Digital Portable Radio

Report Number: RDG161115001-00D

Report Date: 2016-12-29

Oscar Ye

Reviewed By: Engineer

Prepared By: Bay Area Compliance Laboratories Corp. (Kunshan)

No.248 Chenghu Road, Kunshan, Jiangsu province,

Gscar. Ye

China

Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
TEST FACILITY	
SYSTEM TEST CONFIGURATION	
DESCRIPTION OF TEST CONFIGURATION	
DUTY CYCLE	
EXTERNAL I/O CABLE	
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	
TEST EQUIPMENT LIST	10
FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE	11
APPLICABLE STANDARD	
FCC §15.203 - ANTENNA REQUIREMENT	
APPLICABLE STANDARD	
ANTENNA CONNECTOR CONSTRUCTION	
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	
APPLICABLE STANDARD	
EUT SETUP	
EMI TEST RECEIVER SETUP.	
TEST PROCEDURE	
CORRECTED FACTOR & MARGIN CALCULATION	
TEST RESULTS SUMMARY	
TEST DATA	
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	
APPLICABLE STANDARD	17
EUT SETUP	
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	
TEST PROCEDURE	
TEST RESULTS SUMMARY	
TEST DATA	
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH	
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST DATA	
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER	
APPLICABLE STANDARD	
1 LOT 1 ROCLDURE	23

Report No.: RDG161115001-00D

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Hytera Communications Corporation Limited*'s product, model number: *PD982 VHF (FCC ID: YAMPD98XVHF)* or the "EUT" in this report was a *Digital Portable Radio*, which was measured approximately: 142mm (L) x63mm (W) x38mm (H), rated input voltage: DC 7.2V rechargeable Li-ion battery or DC 12.0V charging from adapter.

Report No.: RDG161115001-00D

Adapter Information: Model: HKA01212010-XQ

Input: AC 100-240V, 50/60 Hz, 0.5A

Output: DC 12V, 1.0A

Note: The series product, model PD982 VHF, PD986 VHF, PD988 VHF and PD985 VHF, they have the same appearance, PCB, Material to the testing product's model, and only named differently. PD982 VHF was selected for fully testing, which was explained in the attached product similarity declaration letter.

* All measurement and test data in this report was gathered from production sample serial number: 161115001 (Assigned by BACL, Kunshan). The EUT supplied by the applicant was received on 2016-11-15.

Objective

This report is prepared on behalf of *Hytera Communications Corporation Limited* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS and Part 22&90 TNF submissions with FCC ID: YAMPD98XVHF.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

FCC Part 15.247 Page 4 of 30

Measurement Uncertainty

Item		Uncertainty	
AC Power Line	s Conducted Emissions	±3.26 dB	
RF conducted test with spectrum		±0.9dB	
RF Output Power with Power meter		±0.5dB	
D. F. t. L indian	30MHz~1GHz	±5.91dB	
Radiated emission	Above 1G	±4.92dB	
Occupi	ied Bandwidth	±0.5kHz	
Temperature		±1.0℃	
H	Iumidity	±6%	

Report No.: RDG161115001-00D

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.10-2013.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15.247 Page 5 of 30

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineer mode.

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

Report No.: RDG161115001-00D

EUT was tested with Channel 0, 19 and 39.

Special Accessories

No special accessory.

Equipment Modifications


No modification was made to the EUT tested.

FCC Part 15.247 Page 6 of 30

Duty cycle

BLE Mode

Report No.: RDG161115001-00D



Band	Duty Cycle (%) T(us)		1/T(kHz)	VBW Setting	10log(1/x)
BLE	BLE 68.7		2.23	3kHz	1.63

Support Equipment List and Details

Manufacturer	nufacturer Description Model		Serial Number	
/	/	/	/	


External I/O Cable

Cable Description	Length (m)	From Port	То
Un-shielding Un-detachable DC Power Cable	1.5	EUT	Adapter

FCC Part 15.247 Page 7 of 30

Block Diagram of Test Setup

For Conducted Emissions:



Report No.: RDG161115001-00D

FCC Part 15.247 Page 8 of 30

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

Report No.: RDG161115001-00D

FCC Part 15.247 Page 9 of 30

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date			
AC Line Conducted test								
Rohde & Schwarz	EMI Test Receiver	ESCS30	834115/007	2016-11-25	2017-11-25			
Rohde & Schwarz	LISN	ESH3-Z5	862770/011	2016-10-10	2017-10-10			
Rohde & Schwarz	Pulse limiter	ESH3-Z2	879940/0058	2016-06-19	2017-06-18			
MICRO-COAX	Coaxial line	UFB-293B-1- 0480-50X50	97F0173	2016-09-08	2017-09-08			
Rohde & Schwarz	CE Test software	EMC 32	V 09.10.0	NCR	NCR			
	R	adiation test						
Sonoma Instrunent	Amplifier	330	171377	2016-12-12	2017-12-12			
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2016-11-25	2017-11-2			
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2016-01-09	2019-01-0			
Narda	Pre-amplifier	AFS42- 00101800	2001270	2016-09-08	2017-09-0			
EMCO	Horn Antenna	3116	9510-2384	2015-11-07	2018-11-0			
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2016-11-25	2017-11-2			
ETS	Horn Antenna	3115	9311-4159	2016-01-11	2019-01-1			
R&S	Auto test Software	EMC32	V 09.10.0	NCR	NCR			
haojintech	Coaxial Cable	Cable-1	001	2016-12-12	2017-12-1			
haojintech	Coaxial Cable	Cable-2	002	2016-12-12	2017-12-1			
haojintech	Coaxial Cable	Cable-3	003	2016-12-12	2017-12-1			
MICRO-COAX	Coaxial Cable	Cable-4	004	2016-12-12	2017-12-1			
MICRO-COAX	Coaxial Cable	Cable-5 005		2016-12-12	2017-12-1			
	RF	Conducted test						
BACL	TS 8997 Cable-01	T-KS-EMC086	T-KS-EMC086	2015-12-10	2016-12-0			
BACL	RF cable	KS-LAB-012	KS-LAB-012	2015-12-16	2016-12-1			
WEINSCHEL	10dB Attenuator	5328	N/A	2016-06-18	2017-06-1			
Rohde & Schwarz	OSP120 BASE UNIT	OSP120	101247	2016-07-04	2017-07-0			
Agilent	Power Meter	N1912A	MY5000492	2016-11-17	2017-11-1			
Agilent	Power Sensor	N1921A	MY54210024	2016-11-17	2017-11-1			
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2016-09-21	2017-09-2			

Report No.: RDG161115001-00D

FCC Part 15.247 Page 10 of 30

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Report No.: RDG161115001-00D

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]

 $[\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- 1. f(GHz) is the RF channel transmit frequency in GHz.
- 2. Power and distance are rounded to the nearest mW and mm before calculation.
- 3. The result is rounded to one decimal place for comparison.
- 4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Measurement Result

For worst case:

Mode	Frequency (MHz)	Max Tune-up Conducted Power (dBm)	Max Tune-up Conducted Power (mW)	Calculated Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
BLE	2480	7.0	5.01	5	1.6	3.0	Yes

Result: No SAR test is required

FCC Part 15.247 Page 11 of 30

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

Report No.: RDG161115001-00D

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 3 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.


FCC Part 15.247 Page 12 of 30

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Report No.: RDG161115001-00D

Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

FCC Part 15.247 Page 13 of 30

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Report No.: RDG161115001-00D

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions


Temperature:	26 ℃		
Relative Humidity:	51 %		
ATM Pressure:	101.0 kPa		

The testing was performed by Layne Li on 2016-12-19.

EUT operation mode: Transmitting

FCC Part 15.247 Page 14 of 30

AC 120V/60 Hz, Line:




Report No.: RDG161115001-00D

Frequency (MHz)	QuasiPeak (dBµV)	Average (dB \mu V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.160000		36.19	9.000	L1	10.3	19.27	55.46	Compliance
0.160000	48.06		9.000	L1	10.3	17.40	65.46	Compliance
0.195000		37.79	9.000	L1	10.3	16.03	53.82	Compliance
0.195000	49.16		9.000	L1	10.3	14.66	63.82	Compliance
0.240000		34.12	9.000	L1	10.3	17.98	52.10	Compliance
0.240000	44.85		9.000	L1	10.3	17.25	62.10	Compliance
0.260000		32.27	9.000	L1	10.3	19.16	51.43	Compliance
0.260000	42.37		9.000	L1	10.3	19.06	61.43	Compliance
0.775000		40.08	9.000	L1	10.3	5.92	46.00	Compliance
0.775000	44.51		9.000	L1	10.3	11.49	56.00	Compliance
7.850000		36.96	9.000	L1	10.5	13.04	50.00	Compliance
7.850000	42.08		9.000	L1	10.5	17.92	60.00	Compliance

FCC Part 15.247 Page 15 of 30

AC 120V/60 Hz, Neutral:



Report No.: RDG161115001-00D

Frequency (MHz)	QuasiPeak (dBµV)	Average (dB µ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.180000		35.38	9.000	N	10.3	19.11	54.49	Compliance
0.180000	49.81		9.000	N	10.3	14.68	64.49	Compliance
0.190000		39.72	9.000	N	10.3	14.32	54.04	Compliance
0.190000	52.14		9.000	N	10.3	11.90	64.04	Compliance
0.230000		34.24	9.000	N	10.3	18.21	52.45	Compliance
0.230000	47.30		9.000	N	10.3	15.15	62.45	Compliance
0.270000		30.30	9.000	N	10.3	20.82	51.12	Compliance
0.270000	41.63		9.000	N	10.3	19.49	61.12	Compliance
0.785000		39.47	9.000	N	10.3	6.53	46.00	Compliance
0.785000	44.44		9.000	N	10.3	11.56	56.00	Compliance
7.940000		38.15	9.000	N	10.5	11.85	50.00	Compliance
7.940000	42.96		9.000	N	10.5	17.04	60.00	Compliance

Note:

- 1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
 3) Margin = Limit Corrected Amplitude

FCC Part 15.247 Page 16 of 30


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;


EUT Setup

Below 1 GHz:



Report No.: RDG161115001-00D

Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

FCC Part 15.247 Page 17 of 30

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
	1MHz	3 MHz	/	PK
Above 1 GHz	1MHz	10 Hz Note 1	/	Ave.
	1MHz	>1/T Note 2	/	Ave.

Report No.: RDG161115001-00D

Note 1: when duty cycle is no less than 98% Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.</u>

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

FCC Part 15.247 Page 18 of 30

Test Data

Environmental Conditions

Temperature:	26 ℃	
Relative Humidity:	51 %	
ATM Pressure:	101.0 kPa	

Report No.: RDG161115001-00D

The testing was performed by Layne Li on 2016-12-19.

EUT operation mode: Transmitting

FCC Part 15.247 Page 19 of 30

30 MHz-25 GHz:

Frequency	ency Turntable			Corrected	_	C Part 7/205/209			
(MHz)	Reading (dBµV)	Detector (PK/QP/Ave.)	Degree	Height (m)	Polar (H/V)	Factor (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
			Low Ch	nannel (2	2402 M	Hz)			
850.02	32.72	QP	203	1.2	Н	-1.23	31.49	46	14.51
2402.00	103.47	PK	100	2.2	Н	-6.19	97.28	/	/
2402.00	98.03	Ave.	100	2.2	Н	-6.19	91.84	/	/
2402.00	102.94	PK	39	2	V	-6.19	96.75	/	/
2402.00	97.09	Ave.	39	2	V	-6.19	90.90	/	/
2385.67	66.22	PK	162	1.0	Н	-6.19	60.03	74	13.97
2385.67	51.32	Ave.	162	1.0	Н	-6.19	45.13	54	8.87
2388.07	64.84	PK	94	1.6	Н	-6.19	58.65	74	15.35
2388.07	51.32	Ave.	94	1.6	Н	-6.19	45.13	54	8.87
2485.41	64.74	PK	314	1.2	V	-5.97	58.77	74	15.23
2485.41	51.66	Ave.	314	1.2	V	-5.97	45.69	54	8.31
4804.00	54.83	PK	90	1.2	Н	1.6	56.43	74	17.57
4804.00	42.03	Ave.	90	1.2	Н	1.6	43.63	54	10.37
			Middle C	Channel	(2440 N	MHz)		'	
850.02	32.47	QP	67	1.2	Н	-1.23	31.24	46	14.76
2440.00	103.38	PK	149	1.5	Н	-6.19	97.19	/	/
2440.00	98.6	Ave.	149	1.5	Н	-6.19	92.41	/	/
2440.00	101.56	PK	215	1.4	V	-6.19	95.37	/	/
2440.00	96.65	Ave.	215	1.4	V	-6.19	90.46	/	/
2383.74	64.43	PK	13	2.3	V	-6.19	58.24	74	15.76
2383.74	51.38	Ave.	13	2.3	V	-6.19	45.19	54	8.81
2387.43	65.49	PK	225	1.7	Н	-6.19	59.30	74	14.70
2387.43	51.38	Ave.	225	1.7	Н	-6.19	45.19	54	8.81
2484.62	65.88	PK	113	2.2	Н	-5.97	59.91	74	14.09
2484.62	51.66	Ave.	113	2.2	Н	-5.97	45.69	54	8.31
4880.00	52.54	PK	278	1.6	Н	1.83	54.37	74	19.63
4880.00	40.89	Ave.	278	1.6	Н	1.83	42.72	54	11.28

Report No.: RDG161115001-00D

FCC Part 15.247 Page 20 of 30

Frequency	Re	Receiver		Turntable		15.247	C Part //205/209		
(MHz)	Reading (dBµV)	Detector (PK/QP/Ave.)	Degree Height Polar	Factor (dB)	Amplitude (dBμV/m)		Margin (dB)		
			High Cl	nannel (2	2480 M	Hz)			
850.02	32.61	QP	194	1.1	Н	-1.23	31.38	46	14.62
2480.00	104.84	PK	336	1.7	Н	-5.97	98.87	/	/
2480.00	98.74	Ave.	336	1.7	Н	-5.97	92.77	/	/
2480.00	101.24	PK	190	1.1	V	-5.97	95.27	/	/
2480.00	95.30	Ave.	190	1.1	V	-5.97	89.33	/	/
2384.38	64.88	PK	71	2.1	V	-6.19	58.69	74	15.31
2384.38	51.32	Ave.	71	2.1	V	-6.19	45.13	54	8.87
2484.06	64.65	PK	91	1.6	Н	-5.97	58.68	74	15.32
2484.06	51.61	Ave.	91	1.6	Н	-5.97	45.64	54	8.36
2485.31	64.79	PK	72	1.3	Н	-5.97	58.82	74	15.18
2485.31	51.66	Ave.	72	1.3	Н	-5.97	45.69	54	8.31
4960.00	54.07	PK	183	1.5	Н	2.06	56.13	74	17.87
4960.00	39.78	Ave.	183	1.5	Н	2.06	41.84	54	12.16

Report No.: RDG161115001-00D

Note

 $\label{eq:corrected_factor} \begin{aligned} & \text{Corrected Factor} = \text{Antenna factor} \ (RX) + \text{Cable Loss} - \text{Amplifier Factor} \\ & \text{Corrected Amplitude} = \text{Corrected Factor} + \text{Reading} \end{aligned}$

Margin = Limit - Corrected. Amplitude

The other spurious emission which is 20dB below the limit was not recorded.

FCC Part 15.247 Page 21 of 30

FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Report No.: RDG161115001-00D

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	23 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Nefertari Xu on 2016-12-08.

Test Result: Pass.

Please refer to the following table and plots.


FCC Part 15.247 Page 22 of 30

EUT operation mode: Transmitting

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (kHz)
Low	2402	0.737	≥500
Middle	2440	0.733	≥500
High	2480	0.729	≥500

Report No.: RDG161115001-00D


BLE Low Channel




FCC Part 15.247 Page 23 of 30

BLE Middle Channel

Report No.: RDG161115001-00D



BLE High Channel



FCC Part 15.247 Page 24 of 30

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Report No.: RDG161115001-00D

Test Procedure

- 1. Place the EUT on a bench and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
- 3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	23 ℃	
Relative Humidity:	52 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Nefertari Xu on 2016-12-08.

EUT operation mode: Transmitting

BLE mode

Channel	Frequency (MHz)	Max Peak Output Power (dBm)	Limit (dBm)	Result
Low	2402	4.05	30	Pass
Middle	2440	6.04	30	Pass
High	2480	6.80	30	Pass

FCC Part 15.247 Page 25 of 30

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE


Report No.: RDG161115001-00D

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	23 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Nefertari Xu on 2016-12-08

EUT operation mode: Transmitting


Test Result: Compliance

Please refer to the following plots.


FCC Part 15.247 Page 26 of 30

BLE: Band Edge, Left Side

Report No.: RDG161115001-00D



BLE: Band Edge, Right Side



FCC Part 15.247 Page 27 of 30

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard


For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Report No.: RDG161115001-00D

Test Procedure

According to KDB558074 D01 DTS Meas Guidance v03r05 sub-clause 10.2

- 1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- 2. Set the RBW to: $3kHz \le RBW \le 100 kHz$.
- 3. Set the VBW \geq 3×RBW.
- 4. Set the span to 1.5 times the DTS bandwidth.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	23 ℃	
Relative Humidity:	52 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Nefertari Xu on 2016-12-08.

EUT operation mode: Transmitting


FCC Part 15.247 Page 28 of 30

Test Result: Pass

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)			
BLE mode						
Low	2402	-11.88	≤8			
Middle	2440	-10.13	≤8			
High	2480	-8.79	≤8			

Report No.: RDG161115001-00D


Power Spectral Density, BLE Low Channel




FCC Part 15.247 Page 29 of 30

Power Spectral Density, BLE Middle Channel

Report No.: RDG161115001-00D



Power Spectral Density, BLE High Channel



***** END OF REPORT *****

FCC Part 15.247 Page 30 of 30