BACL
Bay Area Compliance Labs Corp.

FCC PART 22H, PART 24E,PART 27, PART 90 MEASUREMENT AND TEST REPORT

For

Hytera Communications Corporation Limited

Hytera Tower, Hi-Tech Industrial Park North, 9108# Beihuan Road, Nanshan District, Shenzhen, 518057 China

FCC ID:YAMPNC380B9

Report Type:	Product Type:
Original Report	PoC Radio

Report Number:	RDG200109003-00E
Report Date:	2020-03-30
Reviewed By:	Ivan Cao Assistant manager
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:		PoC Radio
EUT Model:		PNC380
Rated Input Voltage:		DC 3.85V from battery or DC 5V from adapter
Adapter Information	**Model:**	S010WV0500200
	Input:	100-240V~50/60Hz 0.4A
	Output:	DC5V; 2000mA
Serial Number:		RDG200109003-RF-S3
EUT Received Date:		2020.01.09

Objective

This report is prepared on behalf of *Hytera Communications Corporation Limited* in accordance with:
Part 2-Subpart J, Part 22-Subpart H, Part 24-Subpart E, Part 27, Part 90 of the Federal Communication Commissions rules.

Related Submittal(s)/Grant(s)

FCC Part 15C DSS submissions with FCC ID: YAMPNC380B9.
FCC Part 15C DTS submissions with FCC ID: YAMPNC380B9.
FCC Part 15C DXX submissions with FCC ID: YAMPNC380B9.
FCC Part 15E NII submissions with FCC ID: YAMPNC380B9.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services
Part 24 Subpart E - Personal Communication Services
Part 27 - Miscellaneous wireless communications services
Part 90 - PRIVATE LAND MOBILE RADIO SERVICES

TIA/EIA 603-D-2010.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp.(Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Unwanted Emissions, radiated	30MHz ~ 1GHz:5.85 dB 1G~26.5GHz: 5.23 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1℃
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier : CN0022.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol "△ ". Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the U.S. Government.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk "★".

SYSTEM TEST CONFIGURATION

Justification

The EUT was configured for testing according to TIA/EIA-603-D 2010.

The test items were performed with the EUT operating at testing mode. The device operates on GSM Band 850/1900MHz,WCDMA Band 2/4/5, and LTE band 2/4/5/7/13/17/26/38/41, test was performed with channels as below table:

Frequency Bands	Bandwidth (MHz)	Test Frequency(MHz)		
		Low	Middle	High
GSM/EDGE 850	0.25	824.2	836.6	848.8
GSM/EDGE1900	0.25	1850.2	1880	1909.8
WCDMA Band 2	4.2	1852.4	1880	1907.6
WCDMA Band 4	4.2	1712.4	1732.6	1752.6
WCDMA Band 5	4.2	826.4	836.6	846.6
LTE Band 2	1.4	1850.7	1880	1909.3
	3	1851.5	1880	1908.5
	5	1852.5	1880	1907.5
	10	1855	1880	1905
	15	1857.5	1880	1902.5
	20	1860	1880	1900
LTE Band 4	1.4	1710.7	1732.5	1754.3
	3	1711.5	1732.5	1753.5
	5	1712.5	1732.5	1752.5
	10	1715	1732.5	1750
	15	1717.5	1732.5	1747.5
	20	1720	1732.5	1745
LTE Band 5	1.4	824.7	836.5	848.3
	3	825.5	836.5	847.5
	5	826.5	836.5	846.5
	10	829	836.5	844
LTE Band 7	5	2502.5	2535	2567.5
	10	2505	2535	2565
	15	2507.5	2535	2562.5
	20	2510	2535	2560
LTE Band 12	1.4	699.7	707.5	715.3
	3	700.5	707.5	714.5
	5	701.5	707.5	713.5
	10	704	707.5	711
LTE Band 13	5	779.5	782	784.5
	10	/	782	/
LTE Band 17	5	706.5	710	713.5
	10	709	710	711

Frequency Bands	Bandwidth (MHz)	Test Frequency(MHz)		
		Low	Middle	High
LTE Band 26	1.4	814.7	831.5	848.3
	3	815.5	831.5	847.5
	5	816.5	831.5	846.5
	10	819	831.5	844
	15	821.5	831.5	841.5
LTE Band 38	5	2572.5	2595	2617.5
	10	2575	2595	2615
	15	2577.5	2595	2612.5
	20	2580	2595	2610
LTE Band 41	5	2498.5	2593	2687.5
	10	2501	2593	2685
	15	2503.5	2593	2682.5
	20	2506	2593	2680

Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
R&S	Universal Radio Communication Tester	CMU200	106 891
R&S	Wideband Radio Communication Tester	CMW500	147473
Unknown	ANTENNA	Unknown	/

Configuration of Test Setup

Block Diagram of Test Setup

CMW500/CMU200

EUT

Antenna

1.0 Meter

Non-Conductive Table
150 cm above Ground Plane

1.5 Meter

SUMMARY OF TEST RESULTS

Rules	Description of Test	Result
FCC§1.1310, §2.1093;	RF Exposure	Compliance
FCC§2.1046;§ 22.913 (a); § 24.232 (c);§27.50; §90.635	RF Output Power	Compliance
FCC§ 2.1047	Modulation Characteristics	Not Applicable
FCC§ 2.1049; § 22.905; § 22.917; § 24.238; §27.53; §90.209	Occupied Bandwidth	Compliance
FCC§ 2.1051, § 22.917 (a); § 24.238 (a); §27.53; §90.691	Spurious Emissions at Antenna Terminal	Compliance
FCC§ 2.1053 § 22.917 (a); § 24.238 (a); §27.53; §90.691	Spurious Radiation Emissions	Compliance
FCC§ 22.917 (a); § 24.238 (a); §27.53; §90.691	Out of band emission, Band Edge	Compliance
FCC§ 2.1055;§ 22.355; § 24.235; §27.54; §90.213	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

FCC §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

FCC§1.1310 and §2.1093

Test Result

Compliant, please refer to the SAR report: RDG200109003-SAA.

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E, Part 27,Part 90 there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FCC § 2.1046, § 22.913 (a) & § 24.232 (c) & § 27.50&§ 90.635 - RF OUTPUT POWER

Applicable Standard

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

According to §24.232 (d) Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

According to §27.50

(a) The following power limits and related requirements apply to stations transmitting in the 2305-2320 MHz band or the 2345-2360 MHz band.

(3) Mobile and portable stations. (i) For mobile and portable stations transmitting in the 2305-2315 MHz band or the 2350-2360 MHz band, the average EIRP must not exceed 50 milliwatts within any 1 megahertz of authorized bandwidth, except that for mobile and portable stations compliant with 3GPP LTE standards or another advanced mobile broadband protocol that avoids concentrating energy at the edge of the operating band the average EIRP must not exceed 250 milliwatts within any 5 megahertz of authorized bandwidth but may exceed 50 milliwatts within any 1 megahertz of authorized bandwidth. For mobile and portable stations using time division duplexing (TDD) technology, the duty cycle must not exceed 38 percent in the 2305-2315 MHz and 2350-2360 MHz bands. Mobile and portable stations using FDD technology are restricted to transmitting in the 2305-2315 MHz band. Power averaging shall not include intervals in which the transmitter is off.

(ii) Mobile and portable stations are not permitted to transmit in the 2315-2320 MHz and 2345-2350 MHz bands.

(iii) Automatic transmit power control. Mobile and portable stations transmitting in the 2305-2315 MHz band or in the 2350-2360 MHz band must employ automatic transmit power control when operating so the stations operate with the minimum power necessary for successful communications.

(iv) Prohibition on external vehicle-mounted antennas. The use of external vehicle-mounted antennas for mobile and portable stations transmitting in the 2305-2315 MHz band or the 2350-2360 MHz band is prohibited.

(b)(10) Portable stations (hand-held devices) transmitting in the 746-757 MHz, 776-788 MHz, and 805-806 MHz bands are limited to 3 watts ERP.

(c) (10) Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

(d), (4) Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP. Fixed stations operating in the 1710-1755 MHz band are limited to a maximum antenna height of 10 meters above ground. Mobile and portable stations operating in these bands must employ a means for limiting power to the minimum necessary for successful communications.

(h),(2) Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

According to §90.635

(b) The maximum output power of the transmitter for mobile stations is 100 watts (20 dBw).

Test Procedure

GSM/GPRS/EGPRS

Function: Menu select > GSM Mobile Station > GSM 850/1900
Press Connection control to choose the different menus
Press RESET > choose all the reset all settings
Connection   Press Signal Off to turn off the signal and change settings
Network Support > GSM + GPRS or GSM + EGSM
Main Service > Packet Data
Service selection > Test Mode A – Auto Slot Config. off
MS Signal   Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting
          > Slot configuration   > Uplink/Gamma
          > 33 dBm for GPRS 850
          > 30 dBm for GPRS 1900
          > 27 dBm for EGPRS 850
          > 26 dBm for EGPRS 1900
BS Signal   Enter the same channel number for TCH channel (test channel) and BCCH channel
Frequency Offset >   + 0 Hz
Mode >   BCCH and TCH
BCCH Level >   -85 dBm (May need to adjust if link is not stable)
BCCH Channel >   choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]

Channel Type >   Off
P0 >   4 dB
Slot Config >   Unchanged (if already set under MS signal)
TCH >   choose desired test channel
Hopping >   Off
Main Timeslot >   3
Network   Coding Scheme >   CS4 (GPRS) and MCS5 (EGPRS)

 Bit Stream >   2E9-1 PSR Bit Stream
AF/RF   Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input
Connection   Press Signal on to turn on the signal and change settings

WCDMA-Release 99

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification. The EUT has a nominal maximum output power of 24dBm (+1.7/-3.7).

WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	βc / βd	8/15

WCDMA HSDPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

		HSDPA	HSDPA	HSDPA	HSDPA
	Mode				
	Subset	1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm2			
	βc	2/15	12/15	15/15	15/15
	βd	15/15	15/15	8/15	4/15
	βd (SF)	64			
	βc/ βd	2/15	12/15	15/8	15/4
	βhs	4/15	24/15	30/15	30/15
	MPR(dB)	0	0	0.5	0.5
HSDPA Specific Settings	DACK	8			
	DNAK	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback	4ms			
	CQI Repetition Factor	2			
	Ahs=βhs/ βc	30/15			

WCDMA HSUPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subset	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	βc	11/15	6/15	15/15	2/15	15/15
	βd	15/15	15/15	9/15	15/15	0
	βec	209/225	12/15	30/15	2/15	5/15
	$\beta c/ \beta d$	11/15	6/15	15/9	2/15	-
	βhs	22/15	12/15	30/15	4/15	5/15
	CM(dB)	1.0	3.0	2.0	3.0	1.0
	MPR(dB)	0	2	1	2	0
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback	4ms				
	CQI Repetition Factor	2				
	Ahs=$\beta hs/ \beta c$	30/15				
HSUPA Specific Settings	DE-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E_FCls		E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E-TFCI PO4 E-TFCI 92 E-TFCI PO 18	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	

HSPA+

The following tests were conducted according to the test requirements in Table C.11.1.4 of 3GPP TS 34.121-1

Sub-test	β_c (Note3)	β_d	β_{HS} (Note1)	β_{ec}	β_{ed} (2xSF2) (Note 4)	β_{ed} (2xSF4) (Note 4)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 4)	E-TFCI (Note 5)	E-TFCI (boost)
1	1	0	30/15	30/15	β_{ed}1: 30/15 β_{ed}2: 30/15	β_{ed}3: 24/15 β_{ed}4: 24/15	3.5	2.5	14	105	105

Note 1:	Δ_{ACK}, Δ_{NACK} and Δ_{CQI} = 30/15 with β_{hs} = 30/15 * β_c.
Note 2:	CM = 3.5 and the MPR is based on the relative CM difference, MPR = MAX(CM-1,0).
Note 3:	DPDCH is not configured, therefore the β_c is set to 1 and β_d = 0 by default.
Note 4:	β_{ed} can not be set directly; it is set by Absolute Grant Value.
Note 5:	All the sub-tests require the UE to transmit 2SF2+2SF4 16QAM EDCH and they apply for UE using E-DPDCH category 7. E-DCH TTI is set to 2ms TTI and E-DCH table index = 2. To support these E-DCH configurations DPDCH is not allocated. The UE is signalled to use the extrapolation algorithm.

DC-HSDPA

The following tests were conducted according to the test requirements in Table C.8.1.12 of 3GPP TS 34.121-1

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1:	The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.	
Note 2:	Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.	

LTE (FDD):

The following tests were conducted according to the test requirements in 3GPP TS36.101

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4.-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signaling Value of "NS_01".

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4,10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10,15,20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3 6.6.3.3.2	13	10	Table 6.2.4-2	Table 6.2.4-2
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23¹	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
..					
NS_32	·	·	·	·	·

Note 1:   Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.

LTE(TDD):

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$			$7680 \cdot T_s$		
1	$19760 \cdot T_s$			$20480 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
2	$21952 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$			$7680 \cdot T_s$		
5	$6592 \cdot T_s$			$20480 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-	-	-
9	$13168 \cdot T_s$			-	-	-

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Calculated Duty Cycle

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-point Periodicity	Subframe Number										Calculated Duty Cycle (%)
		0	1	2	3	4	5	6	7	8	9	
0	5 ms	D	S	U	U	U	D	S	U	U	U	63.33
1	5 ms	D	S	U	U	D	D	S	U	U	D	43.33
2	5 ms	D	S	U	D	D	D	S	U	D	D	23.33
3	10 ms	D	S	U	U	U	D	D	D	D	D	31.67
4	10 ms	D	S	U	U	D	D	D	D	D	D	21.67
5	10 ms	D	S	U	D	D	D	D	D	D	D	11.67
6	5 ms	D	S	U	U	U	D	S	U	U	D	53.33

Calculated Duty Cycle = Extended cyclic prefix in uplink x (T_s) x # of S + # of U

Example for Calculated Duty Cycle for Uplink-Downlink Configuration 0:
Calculated Duty Cycle = 5120 x [1/(15000 x 2048)] x 2 + 6 ms = 63.33%
where
T_s = 1/(15000 x 2048) seconds

Radiated method:

ANSI/TIA-603-D section 2.2.17

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESR3	102453	2019-06-26	2020-06-26
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2019-05-06	2020-05-06
Agilent	Spectrum Analyzer	E4440A	SG43360054	2019-05-09	2020-05-09
TDK RF	Horn Antenna	HRN-0118	130 084	2018-10-12	2021-10-12
ETS-Lindgren	Horn Antenna	3115	000 527 35	2018-10-12	2021-10-12
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-02	2019-09-05	2020-09-05
R&S	Universal Radio Communication Tester	CMU200	106 891	2019-12-14	2020-12-14
Agilent	Signal Generator	E8247C	MY43321350	2019-12-10	2020-12-10
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Test Items:	Radiation Below 1GHz	Radiation Above 1GHz	Conducted Output Power
Temperature:	25.3°C	23°C	23.4 °C
Relative Humidity:	55%	45%	46 %
ATM Pressure:	101.8 kPa	101.8 kPa	101.7 kPa
Tester:	Vern Shen	Felir Wang	Fay Hu
Test Date:	2020-02-27	2020-02-27	2020-02-25

Conducted Output Power

Cellular Band & PCS Band

Band	Channel No.	Conducted Peak Output Power (dBm)								
		GSM	GPRS 1 TX Slot	GPRS 2 TX Slots	GPRS 3 TX Slots	GPRS 4 TX Slots	EGPRS 1 uplink slot	EGPRS 2 uplink slots	EGPRS 3 uplink slots	EGPRS 4 uplink slots
Cellular	128	32.17	32.07	29.21	27.37	26.22	26.13	23.79	22.31	21.07
	190	32.13	32.08	29.28	27.42	26.14	26.17	23.81	22.49	21.04
	251	32.12	32.07	29.29	27.35	26.14	26.22	23.86	22.56	21.22
PCS	512	30.33	30.25	27.55	25.73	24.47	26.12	23.77	22.04	24.50
	661	30.37	30.31	27.49	25.68	24.39	26.09	23.71	22.02	20.71
	810	30.23	30.21	27.46	25.71	24.39	26.23	23.83	22.02	20.68

WCDMA Band II

Mode	3GPP Sub Test	Low Channel		Middle Channel		High Channel	
		Ave. Power (dBm)	PAR (dB)	Ave. Power (dBm)	PAR (dB)	Ave. Power (dBm)	PAR (dB)
Rel 99	1	22.94	2.43	22.83	2.75	23.00	2.72
HSDPA	1	22.03	3.30	21.86	3.57	21.97	3.74
	2	21.19	3.15	21.37	3.50	21.51	3.89
	3	20.45	3.14	20.20	3.56	21.06	4.09
	4	20.05	3.08	20.33	3.61	20.53	3.75
HSUPA	1	22.01	3.57	21.83	3.65	21.98	3.86
	2	21.64	3.67	21.23	3.02	21.28	3.33
	3	20.78	3.51	21.01	3.80	20.44	3.50
	4	20.35	3.46	20.51	3.04	19.77	3.26
	5	20.01	3.58	20.25	3.58	19.40	3.92
DC-HSDPA	1	21.99	3.34	20.76	3.55	22.86	3.79
	2	21.57	3.47	22.38	3.07	21.70	3.49
	3	20.68	3.62	22.67	3.35	20.07	3.59
	4	20.04	3.21	21.92	2.93	19.99	3.21
HSPA+ (16QAM)	1	22.04	3.45	21.04	3.77	20.62	3.49

WCDMA Band IV

Mode	3GPP Sub Test	Low Channel		Middle Channel		High Channel	
		Ave. Power (dBm)	PAR (dB)	Ave. Power (dBm)	PAR (dB)	Ave. Power (dBm)	PAR (dB)
Rel 99	1	22.40	2.46	22.87	2.55	22.91	2.46
HSDPA	1	21.42	3.71	21.83	3.42	21.95	3.42
	2	21.09	3.27	21.34	3.20	21.96	3.85
	3	20.86	3.66	20.93	2.88	20.44	3.37
	4	19.95	3.53	20.73	4.18	20.27	3.45
HSUPA	1	21.37	3.36	21.81	3.65	21.93	3.59
	2	21.02	4.07	21.56	3.97	21.56	4.20
	3	20.85	3.59	21.11	4.20	20.91	3.75
	4	20.12	3.72	20.62	4.28	20.22	3.92
	5	19.58	3.55	19.80	3.57	19.16	2.88
DC-HSDPA	1	21.32	4.01	21.21	3.12	20.33	3.23
	2	21.12	3.42	20.12	3.27	21.25	3.32
	3	20.32	3.03	19.32	3.23	19.21	3.23
	4	19.26	2.31	19.12	3.32	18.28	3.11
HSPA+ (16QAM)	1	21.12	3.00	21.35	3.01	21.87	3.62

WCDMA Band V

Mode	3GPP Sub Test	Low Channel		Middle Channel		High Channel	
		Ave. Power (dBm)	PAR (dB)	Ave. Power (dBm)	PAR (dB)	Ave. Power (dBm)	PAR (dB)
Rel 99	1	23.49	3.01	23.43	2.78	23.35	2.81
HSDPA	1	22.43	3.62	22.41	3.62	22.30	3.71
	2	22.56	3.09	21.90	3.56	21.36	3.76
	3	20.78	3.27	20.44	3.51	20.94	3.04
	4	20.26	4.35	20.20	3.42	19.35	3.72
HSUPA	1	22.37	3.59	22.36	3.48	22.23	3.42
	2	22.11	3.98	21.77	3.88	22.07	3.96
	3	21.45	4.02	20.62	4.37	20.33	4.36
	4	20.56	3.80	20.23	3.97	19.96	3.74
	5	20.44	3.71	19.96	3.32	19.46	3.97
DC-HSDPA	1	21.82	4.06	21.07	3.62	20.96	3.43
	2	21.57	3.44	20.68	3.17	21.05	3.50
	3	20.66	3.08	19.19	3.06	19.15	3.86
	4	19.66	2.91	19.05	3.02	18.98	3.43
HSPA+ (16QAM)	1	21.81	4.32	21.45	3.55	21.72	3.46

LTE Band 2

Channel Bandwidth	Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4MHz	QPSK	RB1#0	22.06	22.20	21.84
		RB1#3	22.15	22.28	21.66
		RB1#5	22.19	22.25	21.51
		RB3#0	22.12	22.17	21.70
		RB3#3	22.16	22.11	21.50
		RB6#0	21.06	21.11	21.24
	16QAM	RB1#0	20.55	21.29	21.00
		RB1#3	20.66	21.40	20.89
		RB1#5	20.65	21.24	20.74
		RB3#0	20.77	21.32	20.80
		RB3#3	20.96	21.14	20.64
		RB6#0	20.16	20.11	20.12
3MHz	QPSK	RB1#0	22.14	22.14	21.91
		RB1#8	21.97	22.25	21.87
		RB1#14	21.92	22.41	21.58
		RB6#0	21.05	21.06	21.08
		RB6#9	21.08	21.08	21.04
		RB15#0	21.05	21.04	21.15
	16QAM	RB1#0	21.25	21.17	20.91
		RB1#8	21.11	21.11	20.60
		RB1#14	21.19	21.12	20.61
		RB6#0	20.09	20.13	20.24
		RB6#9	20.03	20.32	20.04
		RB15#0	20.20	20.03	19.93
5MHz	QPSK	RB1#0	21.90	22.06	21.95
		RB1#13	21.99	21.97	21.77
		RB1#24	21.87	22.12	21.74
		RB15#0	21.07	21.11	21.09
		RB15#10	21.09	21.11	21.03
		RB25#0	20.98	21.08	21.10
	16QAM	RB1#0	20.94	21.29	21.26
		RB1#13	20.13	21.25	21.02
		RB1#24	20.40	21.18	20.54
		RB15#0	20.16	19.99	20.20
		RB15#10	20.23	19.99	19.99
		RB25#0	20.08	20.08	20.15

10MHz	QPSK	RB1#0	22.21	22.25	22.08
		RB1#25	22.22	22.18	22.30
		RB1#49	22.14	22.03	21.23
		RB25#0	21.10	21.15	21.13
		RB25#25	21.11	21.07	21.07
		RB50#0	21.06	21.12	21.09
	16QAM	RB1#0	21.57	21.15	20.45
		RB1#25	21.55	21.04	20.69
		RB1#49	21.22	20.90	20.36
		RB25#0	20.04	20.16	20.21
		RB25#25	20.02	20.19	20.17
		RB50#0	20.06	20.03	20.00
15MHz	QPSK	RB1#0	22.03	22.23	22.17
		RB1#38	21.93	22.22	22.26
		RB1#74	22.06	22.09	21.72
		RB36#0	21.09	21.12	21.17
		RB36#39	21.14	21.10	21.08
		RB75#0	21.17	21.12	21.16
	16QAM	RB1#0	21.16	21.16	21.50
		RB1#38	21.18	21.14	21.35
		RB1#74	21.25	21.43	21.04
		RB36#0	20.11	20.14	20.23
		RB36#39	20.14	20.03	20.07
		RB75#0	20.11	20.14	20.16
20MHz	QPSK	RB1#0	22.14	22.18	22.20
		RB1#50	22.57	22.46	22.24
		RB1#99	22.44	22.23	21.49
		RB50#0	21.22	21.17	21.32
		RB50#50	21.19	21.11	21.19
		RB100#0	21.09	21.15	21.19
	16QAM	RB1#0	20.90	21.32	21.69
		RB1#50	20.79	21.64	21.65
		RB1#99	20.73	21.59	21.15
		RB50#0	20.23	20.17	20.37
		RB50#50	20.28	20.16	20.13
		RB100#0	20.19	20.07	20.30

LTE Band 4

Channel Bandwidth	Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4MHz	QPSK	RB1#0	22.55	22.98	22.99
		RB1#3	22.79	23.16	23.06
		RB1#5	22.66	22.96	23.03
		RB3#0	22.66	22.96	23.12
		RB3#3	22.78	23.02	23.10
		RB6#0	21.81	22.06	22.18
	16QAM	RB1#0	21.32	22.01	22.26
		RB1#3	21.30	22.12	22.29
		RB1#5	21.59	22.32	22.25
		RB3#0	21.73	22.13	22.18
		RB3#3	21.70	21.85	22.01
		RB6#0	20.90	20.80	20.99
3MHz	QPSK	RB1#0	22.73	23.11	23.02
		RB1#8	22.63	22.94	23.08
		RB1#14	22.63	22.99	23.10
		RB6#0	21.83	22.02	22.06
		RB6#9	21.90	22.10	22.12
		RB15#0	21.92	22.11	22.06
	16QAM	RB1#0	22.06	22.21	22.29
		RB1#8	21.99	22.25	22.22
		RB1#14	22.03	22.36	22.26
		RB6#0	20.95	20.97	21.17
		RB6#9	20.71	21.20	21.15
		RB15#0	20.72	21.04	21.15
5MHz	QPSK	RB1#0	22.66	22.89	22.98
		RB1#13	22.59	22.92	22.89
		RB1#24	22.63	22.85	22.78
		RB15#0	21.73	22.04	22.09
		RB15#10	21.77	22.02	22.02
		RB25#0	21.80	22.02	22.05
	16QAM	RB1#0	21.93	21.54	22.07
		RB1#13	21.68	21.93	21.95
		RB1#24	21.57	21.83	21.41
		RB15#0	20.53	21.01	21.00
		RB15#10	20.68	20.89	20.91
		RB25#0	20.74	21.00	21.08

10MHz	QPSK	RB1#0	22.83	23.05	23.07
		RB1#25	22.97	23.13	23.17
		RB1#49	22.75	22.91	23.02
		RB25#0	21.82	21.96	22.09
		RB25#25	21.75	21.99	22.09
		RB50#0	21.92	21.97	22.12
	16QAM	RB1#0	22.09	22.19	21.75
		RB1#25	21.91	22.32	22.05
		RB1#49	21.78	21.90	21.72
		RB25#0	20.67	21.12	21.42
		RB25#25	20.68	21.02	21.08
		RB50#0	20.93	20.98	21.16
15MHz	QPSK	RB1#0	22.89	23.12	23.07
		RB1#38	22.61	23.08	23.12
		RB1#74	22.91	23.24	23.19
		RB36#0	21.85	22.09	22.24
		RB36#39	21.91	22.05	22.08
		RB75#0	21.93	22.11	22.21
	16QAM	RB1#0	22.42	22.30	22.46
		RB1#38	22.28	22.26	22.44
		RB1#74	22.41	22.38	22.50
		RB36#0	21.02	21.00	21.19
		RB36#39	21.03	21.09	21.12
		RB75#0	20.83	21.04	21.10
20MHz	QPSK	RB1#0	23.25	22.92	23.09
		RB1#50	22.92	23.34	22.94
		RB1#99	22.84	23.31	22.87
		RB50#0	21.95	21.99	22.27
		RB50#50	21.98	22.16	22.02
		RB100#0	22.01	22.03	22.15
	16QAM	RB1#0	22.40	21.88	22.39
		RB1#50	22.41	22.36	22.42
		RB1#99	22.41	21.97	22.16
		RB50#0	20.87	21.11	21.24
		RB50#50	20.80	21.09	21.10
		RB100#0	20.94	21.01	21.22

LTE Band 5

Channel Bandwidth	Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4MHz	QPSK	RB1#0	23.36	23.83	23.44
		RB1#3	23.32	23.89	23.25
		RB1#5	23.26	23.87	23.12
		RB3#0	23.20	23.94	23.32
		RB3#3	23.22	23.90	23.12
		RB6#0	23.01	22.95	22.96
	16QAM	RB1#0	22.32	23.12	22.63
		RB1#3	22.21	23.28	22.49
		RB1#5	22.22	23.09	22.34
		RB3#0	22.36	23.09	22.39
		RB3#3	22.35	23.10	22.21
		RB6#0	22.12	22.06	22.10
3MHz	QPSK	RB1#0	23.62	24.00	23.94
		RB1#8	23.53	23.94	23.53
		RB1#14	23.65	24.01	23.24
		RB6#0	23.00	23.01	22.99
		RB6#9	22.95	22.90	22.85
		RB15#0	22.99	22.90	23.03
	16QAM	RB1#0	22.48	23.24	23.23
		RB1#8	22.55	22.97	22.80
		RB1#14	22.58	23.00	22.46
		RB6#0	22.00	21.88	21.92
		RB6#9	21.97	21.75	21.91
		RB15#0	22.09	21.97	21.80
5MHz	QPSK	RB1#0	23.76	23.86	23.83
		RB1#13	23.55	23.92	23.88
		RB1#24	24.06	23.96	23.36
		RB15#0	23.05	23.04	22.94
		RB15#10	22.97	22.99	22.84
		RB25#0	22.94	23.03	22.97
	16QAM	RB1#0	22.65	22.85	22.93
		RB1#13	22.65	22.11	22.45
		RB1#24	23.16	22.21	22.54
		RB15#0	21.96	21.78	21.66
		RB15#10	22.00	21.73	21.56
		RB25#0	21.86	21.99	21.77
10MHz	QPSK	RB1#0	23.34	23.94	23.78
		RB1#25	24.12	23.94	24.16
		RB1#49	23.83	23.20	22.69
		RB25#0	23.03	23.03	22.99
		RB25#25	22.99	22.96	22.89
		RB50#0	22.89	22.97	23.03
	16QAM	RB1#0	22.36	23.04	22.96
		RB1#25	22.94	23.41	23.15
		RB1#49	22.02	22.82	21.92
		RB25#0	22.16	21.87	21.91
		RB25#25	21.91	21.89	21.70
		RB50#0	21.79	21.90	21.78

LTE Band 7

Channel Bandwidth	Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5MHz	QPSK	RB1#0	21.83	21.63	21.90
		RB1#13	21.73	21.55	22.12
		RB1#24	21.88	21.73	22.07
		RB15#0	21.09	21.06	20.99
		RB15#10	21.09	20.95	20.94
		RB25#0	21.00	21.00	21.02
	16QAM	RB1#0	21.00	20.87	21.26
		RB1#13	20.97	20.06	20.74
		RB1#24	21.14	20.01	20.58
		RB15#0	20.10	19.81	19.88
		RB15#10	20.11	20.07	19.76
		RB25#0	20.12	20.04	19.84
10MHz	QPSK	RB1#0	22.03	22.05	22.00
		RB1#25	22.18	22.17	21.97
		RB1#49	22.24	21.91	21.98
		RB25#0	21.03	21.09	21.17
		RB25#25	21.24	21.08	21.05
		RB50#0	21.11	21.06	21.25
	16QAM	RB1#0	21.24	21.19	20.94
		RB1#25	21.44	21.32	20.59
		RB1#49	21.98	21.19	20.62
		RB25#0	20.08	20.22	20.22
		RB25#25	20.38	20.28	20.24
		RB50#0	20.11	20.24	20.19
15MHz	QPSK	RB1#0	22.33	22.03	22.24
		RB1#38	21.88	21.69	21.96
		RB1#74	22.07	21.93	21.75
		RB36#0	21.12	20.95	21.21
		RB36#39	21.20	21.07	20.89
		RB75#0	21.03	21.10	21.14
	16QAM	RB1#0	21.40	21.49	21.59
		RB1#38	21.15	20.98	21.26
		RB1#74	21.10	21.25	20.93
		RB36#0	20.07	19.90	20.25
		RB36#39	20.26	19.87	19.95
		RB75#0	20.05	20.07	20.15
20MHz	QPSK	RB1#0	22.37	22.23	22.27
		RB1#50	22.47	22.12	22.31
		RB1#99	22.16	22.24	21.83
		RB50#0	21.23	21.13	21.29
		RB50#50	21.15	21.12	21.05
		RB100#0	21.09	21.11	21.19
	16QAM	RB1#0	21.48	21.55	22.04
		RB1#50	21.40	21.52	21.87
		RB1#99	20.94	21.50	21.39
		RB50#0	20.26	20.26	20.26
		RB50#50	20.15	20.15	20.02
		RB100#0	20.17	20.07	20.25

LTE Band 12

Channel Bandwidth	Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4MHz	QPSK	RB1#0	22.57	22.87	22.78
		RB1#3	22.75	22.86	23.02
		RB1#5	22.77	22.90	22.88
		RB3#0	22.85	22.89	22.77
		RB3#3	22.85	22.85	22.83
		RB6#0	21.86	21.88	21.83
	16QAM	RB1#0	21.27	21.93	21.94
		RB1#3	21.70	21.82	22.02
		RB1#5	21.34	21.87	22.43
		RB3#0	21.82	21.60	21.91
		RB3#3	21.85	21.49	22.07
		RB6#0	20.73	20.65	21.04
3MHz	QPSK	RB1#0	22.59	22.94	22.86
		RB1#8	22.66	22.81	22.64
		RB1#14	22.64	22.84	22.85
		RB6#0	21.78	21.87	21.83
		RB6#9	21.90	21.87	21.89
		RB15#0	21.88	21.87	21.90
	16QAM	RB1#0	22.15	22.21	21.30
		RB1#8	21.87	22.42	21.29
		RB1#14	21.89	22.58	21.39
		RB6#0	20.88	20.93	20.76
		RB6#9	20.82	21.16	20.91
		RB15#0	20.92	21.09	21.17
5MHz	QPSK	RB1#0	22.44	22.81	22.60
		RB1#13	22.68	22.88	22.55
		RB1#24	22.60	22.79	23.07
		RB15#0	21.91	21.82	21.84
		RB15#10	21.83	21.88	21.85
		RB25#0	21.82	21.88	21.76
	16QAM	RB1#0	20.82	22.01	21.12
		RB1#13	20.86	21.92	21.49
		RB1#24	20.76	21.93	21.40
		RB15#0	20.68	20.55	20.79
		RB15#10	20.71	20.62	20.86
		RB25#0	20.92	20.74	20.87
10MHz	QPSK	RB1#0	22.83	22.88	22.79
		RB1#25	22.90	22.94	22.78
		RB1#49	22.75	22.70	22.99
		RB25#0	21.77	21.78	21.86
		RB25#25	21.91	21.73	21.85
		RB50#0	21.84	21.86	21.88
	16QAM	RB1#0	22.25	22.07	21.83
		RB1#25	22.32	22.11	21.84
		RB1#49	22.25	22.27	21.55
		RB25#0	20.74	20.87	20.99
		RB25#25	20.89	20.71	21.01
		RB50#0	20.88	20.83	20.77

LTE Band 13

Channel Bandwidth	Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5MHz	QPSK	RB1#0	23.61	23.50	23.82
		RB1#13	23.52	23.54	23.91
		RB1#24	23.49	23.55	24.17
		RB15#0	22.91	22.95	22.97
		RB15#10	22.90	22.85	23.01
		RB25#0	22.91	22.90	22.98
	16QAM	RB1#0	22.72	22.26	23.00
		RB1#13	22.90	21.95	22.61
		RB1#24	22.90	22.01	22.63
		RB15#0	22.03	21.92	21.94
		RB15#10	21.94	21.87	21.73
		RB25#0	22.06	21.92	21.88
10MHz	QPSK	RB1#0	/	23.67	/
		RB1#25	/	23.80	/
		RB1#49	/	23.63	/
		RB25#0	/	23.02	/
		RB25#25	/	22.92	/
		RB50#0	/	23.02	/
	16QAM	RB1#0	/	23.04	/
		RB1#25	/	23.11	/
		RB1#49	/	23.25	/
		RB25#0	/	22.01	/
		RB25#25	/	21.93	/
		RB50#0	/	21.97	/

LTE Band 17

Channel Bandwidth	Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5MHz	QPSK	RB1#0	23.75	23.56	23.58
		RB1#13	23.60	23.49	23.42
		RB1#24	23.55	23.45	23.91
		RB15#0	22.73	22.79	22.82
		RB15#10	22.67	22.79	22.74
		RB25#0	22.68	22.82	22.75
	16QAM	RB1#0	22.30	21.71	22.83
		RB1#13	22.15	21.84	22.28
		RB1#24	22.11	21.93	22.43
		RB15#0	21.60	21.63	21.61
		RB15#10	21.49	21.89	21.58
		RB25#0	21.52	21.66	21.71
10MHz	QPSK	RB1#0	23.67	23.81	23.87
		RB1#25	23.96	23.86	24.00
		RB1#49	23.62	23.65	23.65
		RB25#0	22.75	22.91	22.90
		RB25#25	22.74	22.75	22.73
		RB50#0	22.77	22.87	22.75
	16QAM	RB1#0	22.75	22.99	23.05
		RB1#25	22.78	23.27	23.04
		RB1#49	22.07	22.97	22.99
		RB25#0	22.05	21.79	21.87
		RB25#25	21.67	21.76	21.89
		RB50#0	21.65	21.74	21.81

LTE Band 26

Channel Bandwidth	Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4MHz	QPSK	RB1#0	22.55	22.86	22.56
		RB1#3	22.56	22.91	22.54
		RB1#5	22.53	22.74	22.56
		RB3#0	22.53	22.93	22.69
		RB3#3	22.68	22.87	22.57
		RB6#0	21.72	21.84	21.52
	16QAM	RB1#0	21.45	22.41	21.68
		RB1#3	21.26	22.57	21.78
		RB1#5	21.19	22.02	21.70
		RB3#0	21.71	21.60	21.70
		RB3#3	21.56	21.79	21.34
		RB6#0	20.63	20.87	20.68
3MHz	QPSK	RB1#0	22.59	22.74	22.46
		RB1#8	22.61	22.70	22.40
		RB1#14	22.64	22.77	22.42
		RB6#0	21.64	21.79	21.76
		RB6#9	21.70	21.85	21.55
		RB15#0	21.73	21.78	21.71
	16QAM	RB1#0	21.81	22.03	21.76
		RB1#8	21.60	22.28	21.26
		RB1#14	21.55	22.00	21.11
		RB6#0	20.58	20.83	20.73
		RB6#9	20.91	21.00	20.62
		RB15#0	20.94	20.97	20.86
5MHz	QPSK	RB1#0	22.52	22.81	22.57
		RB1#13	22.52	22.64	22.56
		RB1#24	22.51	22.85	22.44
		RB15#0	21.85	21.81	21.74
		RB15#10	21.70	21.79	21.72
		RB25#0	21.72	21.73	21.79
	16QAM	RB1#0	20.88	21.85	21.01
		RB1#13	20.66	21.62	20.99
		RB1#24	20.74	21.76	20.68
		RB15#0	20.75	20.46	20.82
		RB15#10	20.61	20.64	20.53
		RB25#0	20.65	20.77	20.83
10MHz	QPSK	RB1#0	22.73	22.76	22.67
		RB1#25	22.69	23.06	22.73
		RB1#49	22.63	22.73	22.60
		RB25#0	21.79	21.95	21.75
		RB25#25	21.80	21.92	21.76
		RB50#0	21.78	21.94	21.77
	16QAM	RB1#0	22.18	21.86	21.82
		RB1#25	21.90	22.27	21.76
		RB1#49	21.76	21.87	21.34
		RB25#0	20.82	21.08	20.88
		RB25#25	20.75	20.93	20.75
		RB50#0	20.79	20.94	20.80

Channel Bandwidth	Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15MHz	QPSK	RB1#0	22.59	22.38	22.52
		RB1#38	22.22	22.48	22.35
		RB1#74	22.64	22.55	22.26
		RB36#0	21.58	21.66	21.47
		RB36#39	21.49	21.59	21.40
		RB75#0	21.48	21.57	21.53
	16QAM	RB1#0	21.91	21.95	21.80
		RB1#38	21.31	21.78	21.45
		RB1#74	21.53	21.59	21.63
		RB36#0	20.64	20.67	20.68
		RB36#39	20.56	20.59	20.46
		RB75#0	20.45	20.60	20.54

LTE Band 38

Channel Bandwidth	Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5MHz	QPSK	RB1#0	23.02	23.05	22.90
		RB1#13	22.91	23.03	22.72
		RB1#24	23.05	23.07	22.93
		RB15#0	22.24	22.03	21.95
		RB15#10	22.15	22.09	21.88
		RB25#0	22.04	22.10	21.94
	16QAM	RB1#0	21.56	22.18	22.44
		RB1#13	21.28	22.19	22.12
		RB1#24	21.47	22.23	22.37
		RB15#0	20.77	20.95	20.83
		RB15#10	21.02	21.00	20.73
		RB25#0	21.21	20.96	20.93
10MHz	QPSK	RB1#0	23.14	23.02	23.09
		RB1#25	23.07	22.87	23.07
		RB1#49	23.00	22.97	23.04
		RB25#0	22.04	22.13	21.99
		RB25#25	22.05	22.02	21.93
		RB50#0	22.05	22.09	21.98
	16QAM	RB1#0	21.83	22.16	22.04
		RB1#25	22.19	22.09	22.13
		RB1#49	21.78	21.89	22.09
		RB25#0	21.02	21.05	21.03
		RB25#25	21.02	21.00	20.99
		RB50#0	21.06	21.11	20.94
15MHz	QPSK	RB1#0	22.97	23.29	23.09
		RB1#38	22.80	23.10	22.82
		RB1#74	22.92	23.04	22.73
		RB36#0	22.02	22.31	22.02
		RB36#39	22.05	22.11	21.91
		RB75#0	22.02	22.13	22.02
	16QAM	RB1#0	22.37	22.44	22.40
		RB1#38	22.14	22.07	22.03
		RB1#74	22.23	22.35	22.07
		RB36#0	21.01	21.31	21.22
		RB36#39	20.89	21.13	21.11
		RB75#0	21.10	21.15	20.95
20MHz	QPSK	RB1#0	23.01	23.29	23.28
		RB1#50	23.01	23.21	23.12
		RB1#99	22.79	23.07	23.08
		RB50#0	22.10	22.25	22.24
		RB50#50	22.01	22.02	21.95
		RB100#0	22.12	22.15	21.99
	16QAM	RB1#0	22.15	22.12	22.85
		RB1#50	22.19	22.24	22.22
		RB1#99	22.06	21.90	22.21
		RB50#0	21.11	21.33	21.26
		RB50#50	21.04	21.09	21.08
		RB100#0	21.15	21.20	21.05

LTE Band 41

Channel Bandwidth	Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5MHz	QPSK	RB1#0	22.01	21.82	21.72
		RB1#13	22.02	21.80	21.67
		RB1#24	21.79	21.82	21.87
		RB15#0	20.85	20.82	20.86
		RB15#10	20.87	20.76	20.77
		RB25#0	20.74	20.78	20.84
	16QAM	RB1#0	20.54	20.95	21.11
		RB1#13	20.52	20.75	21.32
		RB1#24	20.21	20.73	21.37
		RB15#0	19.81	19.77	20.14
		RB15#10	19.74	19.74	19.57
		RB25#0	19.97	19.89	19.58
10MHz	QPSK	RB1#0	21.75	22.18	21.98
		RB1#25	21.81	22.26	21.90
		RB1#49	21.90	22.06	21.96
		RB25#0	20.90	20.76	20.85
		RB25#25	20.79	20.79	20.87
		RB50#0	20.76	20.83	20.81
	16QAM	RB1#0	20.85	20.96	20.93
		RB1#25	20.60	21.04	20.96
		RB1#49	20.55	20.96	20.65
		RB25#0	19.98	19.94	19.81
		RB25#25	19.66	19.69	19.76
		RB50#0	19.88	19.89	19.78
15MHz	QPSK	RB1#0	21.94	22.23	21.89
		RB1#38	21.56	22.01	21.72
		RB1#74	21.73	22.12	21.65
		RB36#0	20.85	20.90	20.91
		RB36#39	20.73	20.76	20.85
		RB75#0	20.66	20.84	20.82
	16QAM	RB1#0	20.85	21.19	21.01
		RB1#38	20.68	20.86	20.85
		RB1#74	20.73	21.17	20.99
		RB36#0	20.00	20.04	19.83
		RB36#39	19.68	19.89	19.74
		RB75#0	19.94	19.88	19.73

20MHz	QPSK	RB1#0	22.04	22.35	22.16
		RB1#50	22.04	22.59	21.89
		RB1#99	21.94	22.13	22.00
		RB50#0	20.81	20.90	20.86
		RB50#50	20.92	20.80	20.75
		RB100#0	20.83	20.84	20.82
	16QAM	RB1#0	20.98	21.53	21.24
		RB1#50	21.05	21.41	21.25
		RB1#99	20.79	20.92	21.18
		RB50#0	20.05	20.11	20.03
		RB50#50	19.82	20.00	19.92
		RB100#0	19.91	19.92	19.88

PAR, Band 2

Test Modulation		Channel Bandwidth	Low Channel PAR (dB)	Middle Channel PAR (dB)	High Channel PAR (dB)	Limit (dB)
QPSK	1 RB	20 MHz	4.20	4.32	4.43	13
	100 RB		4.90	4.84	4.87	13
16QAM	1 RB	20 MHz	5.30	5.36	5.42	13
	100 RB		5.86	5.77	5.83	13

PAR, Band 4

Test Modulation		Channel Bandwidth	Low Channel PAR (dB)	Middle Channel PAR (dB)	High Channel PAR (dB)	Limit (dB)
QPSK	1 RB	20 MHz	3.74	4.03	3.77	13
	100 RB		4.32	4.35	4.38	13
16QAM	1 RB	20 MHz	4.61	5.01	4.75	13
	100 RB		5.28	5.45	5.33	13

PAR, Band 5

Test Modulation		Channel Bandwidth	Low Channel PAR (dB)	Middle Channel PAR (dB)	High Channel PAR (dB)	Limit (dB)
QPSK	1 RB	10 MHz	4.70	4.29	4.29	13
	50 RB		5.04	4.81	4.72	13
16QAM	1 RB	10 MHz	5.65	5.33	5.30	13
	50 RB		6.06	5.88	5.88	13

PAR, Band 7

Test Modulation		Channel Bandwidth	Low Channel PAR (dB)	Middle Channel PAR (dB)	High Channel PAR (dB)	Limit (dB)
QPSK	1 RB	20 MHz	3.19	3.57	3.59	13
	100 RB		4.09	4.26	4.17	13
16QAM	1 RB	20 MHz	3.94	4.55	4.38	13
	100 RB		5.10	5.25	5.22	13

PAR, LTE Band 12

Test Modulation		Channel Bandwidth	Low Channel PAR (dB)	Middle Channel PAR (dB)	High Channel PAR (dB)	Limit (dB)
QPSK	1 RB	10 MHz	4.46	4.46	4.64	13
	50 RB		5.22	5.10	4.99	13
16QAM	1 RB	10 MHz	5.45	5.68	5.65	13
	50 RB		6.17	6.17	6.00	13

PAR, LTE Band 13

Test Modulation		Channel Bandwidth	Middle Channel PAR (dB)	Limit (dB)
QPSK	1 RB	10 MHz	3.10	13
	50 RB		4.03	13
16QAM	1 RB	10 MHz	4.20	13
	50 RB		5.10	13

PAR, LTE Band 17

Test Modulation		Channel Bandwidth	Low Channel PAR (dB)	Middle Channel PAR (dB)	High Channel PAR (dB)	Limit (dB)
QPSK	1 RB	10 MHz	4.17	4.17	4.32	13
	50 RB		4.81	4.78	4.75	13
16QAM	1 RB	10 MHz	5.16	5.30	5.30	13
	50 RB		5.91	5.77	5.83	13

PAR, LTE Band 26

Test Modulation		Channel Bandwidth	Low Channel PAR (dB)	Middle Channel PAR (dB)	High Channel PAR (dB)	Limit (dB)
QPSK	1 RB	10 MHz	4.38	4.70	4.52	13
	50 RB		4.90	4.87	4.93	13
16QAM	1 RB	10 MHz	5.36	5.74	5.51	13
	50RB		5.86	5.94	5.97	13

PAR, Band 38

Test Modulation		Channel Bandwidth	Low Channel PAR (dB)	Middle Channel PAR (dB)	High Channel PAR (dB)	Limit (dB)
QPSK	1 RB	20 MHz	4.55	3.57	4.14	13
	100 RB		5.47	5.16	5.27	13
16QAM	1 RB	20 MHz	5.21	4.66	5.49	13
	100 RB		6.77	6.17	6.84	13

PAR, Band 41

Test Modulation		Channel Bandwidth	Low Channel PAR (dB)	Middle Channel PAR (dB)	High Channel PAR (dB)	Limit (dB)
QPSK	1 RB	20 MHz	4.58	3.48	4.34	13
	100 RB		5.77	5.56	5.81	13
16QAM	1 RB	20 MHz	5.53	4.34	5.93	13
	100 RB		6.54	5.57	6.32	13

Note: peak-to-average ratio (PAR) <13 dB.

ERP & EIRP

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM 850 Middle Channel								
836.60	H	93.23	18.31	0.00	0.97	17.34	38.45	21.11
836.60	V	104.45	32.66	0.00	0.97	31.69	38.45	6.76
EDGE 850 Middle Channel								
836.60	H	89.98	15.06	0.00	0.97	14.09	38.45	24.36
836.60	V	100.56	28.77	0.00	0.97	27.80	38.45	10.65
WCDMA Band V Middle Channel								
836.60	H	85.79	10.87	0.00	0.97	9.90	38.45	28.55
836.60	V	92.20	20.41	0.00	0.97	19.44	38.45	19.01
GSM 1900 Middle Channel								
1880.00	H	89.67	17.06	11.66	2.66	26.06	33.00	6.94
1880.00	V	92.10	19.63	11.66	2.66	28.63	33.00	4.37
EDGE 1900 Middle Channel								
1880.00	H	85.36	12.75	11.66	2.66	21.75	33.00	11.25
1880.00	V	89.01	16.54	11.66	2.66	25.54	33.00	7.46
WCDMA Band II Middle Channel								
1880.00	H	81.87	9.26	11.66	2.66	18.26	33.00	14.74
1880.00	V	84.89	12.42	11.66	2.66	21.42	33.00	11.58
WCDMA Band IV Middle Channel								
1732.60	H	80.96	6.91	10.90	2.51	15.30	30.00	14.70
1732.60	V	86.92	12.55	10.90	2.51	20.94	30.00	9.06

Note:
   1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
   2) Absolute Level = Substituted Level - Cable loss + Antenna Gain
   3) Margin = Limit-Absolute Level

LTE Band 2

Frequency (MHz)	BW (MHz)	Modulation	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
					Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1880.00	1.40	QPSK	H	82.76	10.15	11.66	2.66	19.15	33.00	13.85
1880.00			V	84.27	11.80	11.66	2.66	20.80	33.00	12.20
1880.00	3.00		H	82.79	10.18	11.66	2.66	19.18	33.00	13.82
1880.00			V	84.12	11.65	11.66	2.66	20.65	33.00	12.35
1880.00	5.00		H	82.48	9.87	11.66	2.66	18.87	33.00	14.13
1880.00			V	83.96	11.49	11.66	2.66	20.49	33.00	12.51
1880.00	10.00		H	82.71	10.10	11.66	2.66	19.10	33.00	13.90
1880.00			V	83.90	11.43	11.66	2.66	20.43	33.00	12.57
1880.00	15.00		H	82.77	10.16	11.66	2.66	19.16	33.00	13.84
1880.00			V	83.73	11.26	11.66	2.66	20.26	33.00	12.74
1880.00	20.00		H	82.89	10.28	11.66	2.66	19.28	33.00	13.72
1880.00			V	83.72	11.25	11.66	2.66	20.25	33.00	12.75
1880.00	1.40	16QAM	H	81.82	9.21	11.66	2.66	18.21	33.00	14.79
1880.00			V	83.28	10.81	11.66	2.66	19.81	33.00	13.19
1880.00	3.00		H	83.03	10.42	11.66	2.66	19.42	33.00	13.58
1880.00			V	83.64	11.17	11.66	2.66	20.17	33.00	12.83
1880.00	5.00		H	81.36	8.75	11.66	2.66	17.75	33.00	15.25
1880.00			V	83.57	11.10	11.66	2.66	20.10	33.00	12.90
1880.00	10.00		H	81.42	8.81	11.66	2.66	17.81	33.00	15.19
1880.00			V	82.45	9.98	11.66	2.66	18.98	33.00	14.02
1880.00	15.00		H	81.40	8.79	11.66	2.66	17.79	33.00	15.21
1880.00			V	82.46	9.99	11.66	2.66	18.99	33.00	14.01
1880.00	20.00		H	81.72	9.11	11.66	2.66	18.11	33.00	14.89
1880.00			V	82.79	10.32	11.66	2.66	19.32	33.00	13.68

LTE Band 4

Frequency (MHz)	BW (MHz)	Modulation	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
					Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1732.50	1.40	QPSK	H	80.32	6.27	10.90	2.51	14.66	30.00	15.34
1732.50			V	84.99	10.62	10.90	2.51	19.01	30.00	10.99
1732.50	3.00		H	79.97	5.92	10.90	2.51	14.31	30.00	15.69
1732.50			V	84.77	10.40	10.90	2.51	18.79	30.00	11.21
1732.50	5.00		H	79.88	5.83	10.90	2.51	14.22	30.00	15.78
1732.50			V	84.82	10.45	10.90	2.51	18.84	30.00	11.16
1732.50	10.00		H	79.94	5.89	10.90	2.51	14.28	30.00	15.72
1732.50			V	84.86	10.49	10.90	2.51	18.88	30.00	11.12
1732.50	15.00		H	79.79	5.74	10.90	2.51	14.13	30.00	15.87
1732.50			V	84.89	10.52	10.90	2.51	18.91	30.00	11.09
1732.50	20.00		H	79.54	5.49	10.90	2.51	13.88	30.00	16.12
1732.50			V	85.65	11.28	10.90	2.51	19.67	30.00	10.33
1732.50	1.40	16QAM	H	79.35	5.30	10.90	2.51	13.69	30.00	16.31
1732.50			V	83.97	9.60	10.90	2.51	17.99	30.00	12.01
1732.50	3.00		H	78.92	4.87	10.90	2.51	13.26	30.00	16.74
1732.50			V	83.53	9.16	10.90	2.51	17.55	30.00	12.45
1732.50	5.00		H	78.81	4.76	10.90	2.51	13.15	30.00	16.85
1732.50			V	83.71	9.34	10.90	2.51	17.73	30.00	12.27
1732.50	10.00		H	78.63	4.58	10.90	2.51	12.97	30.00	17.03
1732.50			V	83.47	9.10	10.90	2.51	17.49	30.00	12.51
1732.50	15.00		H	78.63	4.58	10.90	2.51	12.97	30.00	17.03
1732.50			V	83.94	9.57	10.90	2.51	17.96	30.00	12.04
1732.50	20.00		H	78.48	4.43	10.90	2.51	12.82	30.00	17.18
1732.50			V	84.47	10.10	10.90	2.51	18.49	30.00	11.51

LTE Band 5

Frequency (MHz)	BW (MHz)	Modulation	Polar (H/V)	Receiver Reading (dBμV)	Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
836.50	1.40	QPSK	H	86.07	11.14	0.00	0.97	10.17	38.45	28.28
836.50	1.40	QPSK	V	96.42	24.63	0.00	0.97	23.66	38.45	14.79
836.50	3.00	QPSK	H	85.41	10.48	0.00	0.97	9.51	38.45	28.94
836.50	3.00	QPSK	V	95.40	23.61	0.00	0.97	22.64	38.45	15.81
836.50	5.00	QPSK	H	84.80	9.87	0.00	0.97	8.90	38.45	29.55
836.50	5.00	QPSK	V	94.57	22.78	0.00	0.97	21.81	38.45	16.64
836.50	10.00	QPSK	H	83.75	8.82	0.00	0.97	7.85	38.45	30.60
836.50	10.00	QPSK	V	93.58	21.79	0.00	0.97	20.82	38.45	17.63
836.50	1.40	16QAM	H	86.27	11.34	0.00	0.97	10.37	38.45	28.08
836.50	1.40	16QAM	V	96.98	25.19	0.00	0.97	24.22	38.45	14.23
836.50	3.00	16QAM	H	85.47	10.54	0.00	0.97	9.57	38.45	28.88
836.50	3.00	16QAM	V	95.55	23.76	0.00	0.97	22.79	38.45	15.66
836.50	5.00	16QAM	H	84.87	9.94	0.00	0.97	8.97	38.45	29.48
836.50	5.00	16QAM	V	94.87	23.08	0.00	0.97	22.11	38.45	16.34
836.50	10.00	16QAM	H	83.88	8.95	0.00	0.97	7.98	38.45	30.47
836.50	10.00	16QAM	V	93.65	21.86	0.00	0.97	20.89	38.45	17.56

LTE Band 7

Frequency (MHz)	BW (MHz)	Modulation	Polar (H/V)	Receiver Reading (dBμV)	Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
2535.00	5.00	QPSK	H	83.49	10.88	13.14	3.10	20.92	33.00	12.08
2535.00	5.00	QPSK	V	83.65	12.50	13.14	3.10	22.54	33.00	10.46
2535.00	10.00	QPSK	H	83.61	11.00	13.14	3.10	21.04	33.00	11.96
2535.00	10.00	QPSK	V	83.77	12.62	13.14	3.10	22.66	33.00	10.34
2535.00	15.00	QPSK	H	83.43	10.82	13.14	3.10	20.86	33.00	12.14
2535.00	15.00	QPSK	V	83.76	12.61	13.14	3.10	22.65	33.00	10.35
2535.00	20.00	QPSK	H	82.48	9.87	13.14	3.10	19.91	33.00	13.09
2535.00	20.00	QPSK	V	83.94	12.79	13.14	3.10	22.83	33.00	10.17
2535.00	5.00	16QAM	H	82.27	9.66	13.14	3.10	19.70	33.00	13.30
2535.00	5.00	16QAM	V	82.48	11.33	13.14	3.10	21.37	33.00	11.63
2535.00	10.00	16QAM	H	82.13	9.52	13.14	3.10	19.56	33.00	13.44
2535.00	10.00	16QAM	V	82.42	11.27	13.14	3.10	21.31	33.00	11.69
2535.00	15.00	16QAM	H	82.21	9.60	13.14	3.10	19.64	33.00	13.36
2535.00	15.00	16QAM	V	82.66	11.51	13.14	3.10	21.55	33.00	11.45
2535.00	20.00	16QAM	H	82.41	9.80	13.14	3.10	19.84	33.00	13.16
2535.00	20.00	16QAM	V	82.87	11.72	13.14	3.10	21.76	33.00	11.24

LTE Band 12

Frequency (MHz)	BW (MHz)	Modulation	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
					Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
707.50	1.40	QPSK	H	86.17	9.31	0.00	0.94	8.37	34.77	26.40
707.50			V	97.00	22.58	0.00	0.94	21.64	34.77	13.13
707.50	3.00		H	85.71	8.85	0.00	0.94	7.91	34.77	26.86
707.50			V	96.37	21.95	0.00	0.94	21.01	34.77	13.76
707.50	5.00		H	84.57	7.71	0.00	0.94	6.77	34.77	28.00
707.50			V	95.87	21.45	0.00	0.94	20.51	34.77	14.26
707.50	10.00		H	81.96	5.10	0.00	0.94	4.16	34.77	30.61
707.50			V	94.04	19.62	0.00	0.94	18.68	34.77	16.09
707.50	1.40	16QAM	H	86.25	9.39	0.00	0.94	8.45	34.77	26.32
707.50			V	97.86	23.44	0.00	0.94	22.50	34.77	12.27
707.50	3.00		H	86.87	10.01	0.00	0.94	9.07	34.77	25.70
707.50			V	97.01	22.59	0.00	0.94	21.65	34.77	13.12
707.50	5.00		H	84.64	7.78	0.00	0.94	6.84	34.77	27.93
707.50			V	95.97	21.55	0.00	0.94	20.61	34.77	14.16
707.50	10.00		H	82.50	5.64	0.00	0.94	4.70	34.77	30.07
707.50			V	95.04	20.62	0.00	0.94	19.68	34.77	15.09

LTE Band 13

Frequency (MHz)	BW (MHz)	Modulation	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
					Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
782.00	5.00	QPSK	H	83.42	7.89	0.00	0.93	6.96	34.77	27.81
782.00			V	94.15	21.54	0.00	0.93	20.61	34.77	14.16
782.00	10.00		H	82.68	7.15	0.00	0.93	6.22	34.77	28.55
782.00			V	93.87	21.26	0.00	0.93	20.33	34.77	14.44
782.00	5.00	16QAM	H	83.57	8.04	0.00	0.93	7.11	34.77	27.66
782.00			V	94.86	22.25	0.00	0.93	21.32	34.77	13.45
782.00	10.00		H	93.41	17.88	0.00	0.93	16.95	34.77	17.82
782.00			V	94.00	21.39	0.00	0.93	20.46	34.77	14.31

LTE Band 17

Frequency (MHz)	BW (MHz)	Modulation	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
					Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
710.00	5.00	QPSK	H	95.87	19.06	0.00	0.94	18.12	34.77	16.65
710.00			V	96.07	21.71	0.00	0.94	20.77	34.77	14.00
710.00	10.00		H	84.20	7.39	0.00	0.94	6.45	34.77	28.32
710.00			V	95.03	20.67	0.00	0.94	19.73	34.77	15.04
710.00	5.00	16QAM	H	96.40	19.59	0.00	0.94	18.65	34.77	16.12
710.00			V	97.25	22.89	0.00	0.94	21.95	34.77	12.82
710.00	10.00		H	84.71	7.90	0.00	0.94	6.96	34.77	27.81
710.00			V	95.77	21.41	0.00	0.94	20.47	34.77	14.30

LTE Band 26

Frequency (MHz)	BW (MHz)	Modulation	Polar (H/V)	Receiver Reading (dBµV)	Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
831.50	1.40		H	85.45	10.49	0.00	0.97	9.52	38.45	28.93
831.50			V	96.31	24.46	0.00	0.97	23.49	38.45	14.96
831.50	3.00		H	85.38	10.42	0.00	0.97	9.45	38.45	29.00
831.50			V	96.15	24.30	0.00	0.97	23.33	38.45	15.12
831.50	5.00	QPSK	H	84.57	9.61	0.00	0.97	8.64	38.45	29.81
831.50			V	95.87	24.02	0.00	0.97	23.05	38.45	15.40
831.50	10.00		H	82.58	7.62	0.00	0.97	6.65	38.45	31.80
831.50			V	93.37	21.52	0.00	0.97	20.55	38.45	17.90
831.50	15.00		H	82.41	7.45	0.00	0.97	6.48	38.45	31.97
831.50			V	93.10	21.25	0.00	0.97	20.28	38.45	18.17
831.50	1.40		H	85.75	10.79	0.00	0.97	9.82	38.45	28.63
831.50			V	96.45	24.60	0.00	0.97	23.63	38.45	14.82
831.50	3.00		H	85.61	10.65	0.00	0.97	9.68	38.45	28.77
831.50			V	96.37	24.52	0.00	0.97	23.55	38.45	14.90
831.50	5.00	16QAM	H	82.74	7.78	0.00	0.97	6.81	38.45	31.64
831.50			V	95.97	24.12	0.00	0.97	23.15	38.45	15.30
831.50	10.00		H	82.67	7.71	0.00	0.97	6.74	38.45	31.71
831.50			V	93.74	21.89	0.00	0.97	20.92	38.45	17.53
831.50	15.00		H	82.61	7.65	0.00	0.97	6.68	38.45	31.77
831.50			V	93.40	21.55	0.00	0.97	20.58	38.45	17.87

LTE Band 38

Frequency (MHz)	BW (MHz)	Modulation	Polar (H/V)	Receiver Reading (dBµV)	Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
2595.00	5.00		H	81.85	9.62	13.20	3.10	19.72	33.00	13.28
2595.00			V	83.53	13.16	13.20	3.10	23.26	33.00	9.74
2595.00	10.00		H	82.74	10.51	13.20	3.10	20.61	33.00	12.39
2595.00			V	83.26	12.89	13.20	3.10	22.99	33.00	10.01
2595.00	15.00	QPSK	H	80.98	8.75	13.20	3.10	18.85	33.00	14.15
2595.00			V	83.16	12.79	13.20	3.10	22.89	33.00	10.11
2595.00	20.00		H	81.28	9.05	13.20	3.10	19.15	33.00	13.85
2595.00			V	83.41	13.04	13.20	3.10	23.14	33.00	9.86
2595.00	5.00		H	79.64	7.41	13.20	3.10	17.51	33.00	15.49
2595.00			V	82.35	11.98	13.20	3.10	22.08	33.00	10.92
2595.00	10.00		H	79.73	7.50	13.20	3.10	17.60	33.00	15.40
2595.00		16QAM	V	82.06	11.69	13.20	3.10	21.79	33.00	11.21
2595.00	15.00		H	80.05	7.82	13.20	3.10	17.92	33.00	15.08
2595.00			V	81.26	10.89	13.20	3.10	20.99	33.00	12.01
2595.00	20.00		H	80.19	7.96	13.20	3.10	18.06	33.00	14.94
2595.00			V	82.39	12.02	13.20	3.10	22.12	33.00	10.88

LTE Band 41

Frequency (MHz)	BW (MHz)	Modulation	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
					Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
2593.00	5.00	QPSK	H	79.60	7.36	13.19	3.10	17.45	33.00	15.55
2593.00			V	83.60	13.21	13.19	3.10	23.30	33.00	9.70
2593.00	10.00		H	79.73	7.49	13.19	3.10	17.58	33.00	15.42
2593.00			V	83.61	13.22	13.19	3.10	23.31	33.00	9.69
2593.00	15.00		H	79.81	7.57	13.19	3.10	17.66	33.00	15.34
2593.00			V	83.48	13.09	13.19	3.10	23.18	33.00	9.82
2593.00	20.00		H	79.69	7.45	13.19	3.10	17.54	33.00	15.46
2593.00			V	83.60	13.21	13.19	3.10	23.30	33.00	9.70
2593.00	5.00	16QAM	H	78.48	6.24	13.19	3.10	16.33	33.00	16.67
2593.00			V	82.33	11.94	13.19	3.10	22.03	33.00	10.97
2593.00	10.00		H	78.51	6.27	13.19	3.10	16.36	33.00	16.64
2593.00			V	82.45	12.06	13.19	3.10	22.15	33.00	10.85
2593.00	15.00		H	78.81	6.57	13.19	3.10	16.66	33.00	16.34
2593.00			V	82.60	12.21	13.19	3.10	22.30	33.00	10.70
2593.00	20.00		H	78.81	6.57	13.19	3.10	16.66	33.00	16.34
2593.00			V	82.62	12.23	13.19	3.10	22.32	33.00	10.68

Note:
1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
2) Absolute Level = Substituted Level - Cable loss + Antenna Gain
3) Margin = Limit-Absolute Level

FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53&§90.209- OCCUPIED BANDWIDTH

Applicable Standard

FCC §2.1049, §22.917, §22.905, §24.238, §27.53, and§90.209

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The 26 dB & 99% bandwidth was recorded.

```
┌─────────┐      ┌──────────┐      ┌────────────────────┐
│   EUT   │──────│ Splitter │──────│ Spectrum Analyzer  │
└─────────┘      └──────────┘      └────────────────────┘
                      │
                 ┌──────────┐
                 │ Universal Radio │
                 │ Communication   │
                 │ Tester          │
                 └──────────┘
```

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2020-01-09	2021-01-09
yzjingcheng	Coaxial Cable	KTRFBU-141-50	41005011	Each Time	/
E-Microwave	Two-way Spliter	ODP-1-6-2S	OE0120142	Each Time	/
E-Microwave	Coaxial Attenuators	EMCA10-5RN-6	OE01203239	Each Time	/

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data
Environmental Conditions

Temperature:	19.1~22.9°C
Relative Humidity:	35~75 %
ATM Pressure:	101.6~102.6 kPa
Tester:	Fay Hu
Test Date:	2020-02-13~2020-02-20

Test Mode: Transmitting
Test Result: Compliant. Please refer to the following table and plots.

Band	Test Channel	Mode	99% Occupied Bandwidth (MHz)	26 dB Occupied Bandwidth (MHz)
Cellular	M	GSM	0.246	0.318
		EDGE	0.247	0.313
PCS		GSM	0.246	0.317
		EDGE	0.246	0.316
WCDMA Band II		Rel 99	4.153	4.761
		HSDPA	4.168	4.761
		HSUPA	4.153	4.761
WCDMA Band IV		Rel 99	4.168	4.776
		HSDPA	4.182	4.790
		HSUPA	4.182	4.776
WCDMA Band V		Rel 99	4.124	4.761
		HSDPA	4.139	4.747
		HSUPA	4.124	4.761

Band	Bandwidth	Modulation	99% occupied bandwidth (MHz)	26 dB bandwidth (MHz)
LTE Band 2	1.4 MHz	QPSK	1.102	1.296
		16QAM	1.102	1.314
	3 MHz	QPSK	2.695	2.952
		16QAM	2.695	2.976
	5 MHz	QPSK	4.531	5.040
		16QAM	4.511	5.040
	10 MHz	QPSK	8.942	9.800
		16QAM	8.942	9.680
	15 MHz	QPSK	13.533	14.940
		16QAM	13.533	14.880
	20 MHz	QPSK	17.884	19.360
		16QAM	17.964	19.440
LTE Band 4	1.4 MHz	QPSK	1.102	1.308
		16QAM	1.108	1.326
	3 MHz	QPSK	2.695	2.964
		16QAM	2.695	2.964
	5 MHz	QPSK	4.531	5.040
		16QAM	4.511	5.040
	10 MHz	QPSK	8.942	9.720
		16QAM	8.942	9.720
	15 MHz	QPSK	13.593	14.940
		16QAM	13.473	14.820
	20 MHz	QPSK	17.964	19.360
		16QAM	17.964	19.520
LTE Band 5	1.4 MHz	QPSK	1.108	1.296
		16QAM	1.102	1.320
	3 MHz	QPSK	2.695	2.940
		16QAM	2.683	2.976
	5 MHz	QPSK	4.531	5.040
		16QAM	4.531	5.060
	10 MHz	QPSK	8.942	9.760
		16QAM	8.942	9.680

Band	Bandwidth	Modulation	99% occupied bandwidth (MHz)	26 dB bandwidth (MHz)
LTE Band 7	5 MHz	QPSK	4.511	5.080
		16QAM	4.551	5.080
	10 MHz	QPSK	8.981	9.880
		16QAM	8.942	9.720
	15 MHz	QPSK	13.533	15.000
		16QAM	13.533	14.880
	20 MHz	QPSK	17.964	19.440
		16QAM	17.964	19.600
LTE Band 12	1.4 MHz	QPSK	1.108	1.290
		16QAM	1.102	1.302
	3 MHz	QPSK	2.695	2.940
		16QAM	2.695	2.976
	5 MHz	QPSK	4.531	5.060
		16QAM	4.511	5.040
	10 MHz	QPSK	8.982	9.800
		16QAM	8.982	9.680
LTE Band 13	5 MHz	QPSK	4.511	5.020
		16QAM	4.551	5.040
	10 MHz	QPSK	8.982	9.840
		16QAM	8.942	9.720
LTE Band 17	5 MHz	QPSK	4.531	5.040
		16QAM	4.511	5.040
	10 MHz	QPSK	8.942	9.840
		16QAM	8.942	9.680
LTE Band 26	1.4 MHz	QPSK	1.102	1.326
		16QAM	1.108	1.326
	3 MHz	QPSK	2.695	2.952
		16QAM	2.695	2.976
	5 MHz	QPSK	4.531	5.060
		16QAM	4.511	5.060
	10 MHz	QPSK	8.942	9.800
		16QAM	8.942	9.640
	15 MHz	QPSK	13.473	14.880
		16QAM	13.473	14.820
LTE Band 38	5 MHz	QPSK	4.511	5.050
		16QAM	4.511	5.020
	10 MHz	QPSK	8.942	9.760
		16QAM	8.942	9.680
	15 MHz	QPSK	13.593	16.080
		16QAM	13.533	15.600
	20 MHz	QPSK	17.964	19.360
		16QAM	17.884	19.760

LTE Band 41	5 MHz	QPSK	4.511	5.040
		16QAM	4.511	5.020
	10 MHz	QPSK	8.942	9.760
		16QAM	8.942	9.640
	15 MHz	QPSK	13.593	15.900
		16QAM	13.533	15.720
	20 MHz	QPSK	18.044	19.360
		16QAM	17.884	19.760

GSM 850 Cellular Band

Date: 13.FEB.2020   13:36:30

GSM PCS1900 Cellular Band

Date: 13.FEB.2020 14:15:48

EDGE 850 Cellular Band

Date: 13.FEB.2020 14:39:33

EDGE PCS1900 Cellular Band

Date: 13.FEB.2020 14:31:57

WCDMA Band II, Rel 99

Date: 13.FEB.2020 17:13:00

WCDMA Band II, HSDPA

Date: 13.FEB.2020 18:11:44

WCDMA Band II, HSUPA

Date: 13.FEB.2020 19:03:40

WCDMA Band IV, Rel 99

Date: 13.FEB.2020 17:10:54

WCDMA Band IV, HSDPA

Date: 13.FEB.2020 18:52:28

WCDMA Band IV, HSUPA

Date: 13.FEB.2020 19:05:42

WCDMA Band V, Rel 99

Date: 13.FEB.2020 17:15:21

WCDMA Band V, HSDPA

Date: 13.FEB.2020 18:54:42

WCDMA Band V, HSUPA

Date: 13.FEB.2020 19:07:23

LTE Band 2

QPSK_1.4 MHz

Date: 20.FEB.2020 13:34:19

QPSK_3 MHz

Date: 20.FEB.2020 12:09:49

QPSK_5 MHz

Date: 20.FEB.2020   12:10:36

QPSK_10 MHz

Date: 20.FEB.2020   12:11:41

QPSK_15 MHz

Date: 20.FEB.2020   12:12:43

QPSK_20 MHz

Date: 20.FEB.2020   12:13:41

16QAM_1.4 MHz

Date: 20.FEB.2020   12:09:23

16QAM_3 MHz

Date: 20.FEB.2020   12:10:11

16QAM_5 MHz

Date: 20.FEB.2020 12:11:08

16QAM_10 MHz

Date: 20.FEB.2020 12:12:11

16QAM_15 MHz

Date: 20.FEB.2020 12:13:09

16QAM_20 MHz

Date: 20.FEB.2020 12:14:10

LTE Band 4

QPSK_1.4 MHz

Date: 20.FEB.2020　12:14:48

QPSK_3 MHz

Date: 20.FEB.2020　12:15:46

QPSK_5 MHz

Date: 20.FEB.2020 12:16:43

QPSK_10 MHz

Date: 20.FEB.2020 15:23:09

QPSK_15 MHz

Date: 20.FEB.2020 12:18:59

QPSK_20 MHz

Date: 20.FEB.2020 12:19:57

16QAM_1.4 MHz

Date: 20.FEB.2020 12:15:14

16QAM_3 MHz

Date: 20.FEB.2020 12:16:12

16QAM_5 MHz

Date: 20.FEB.2020 12:17:18

16QAM_10 MHz

Date: 20.FEB.2020 12:18:27

16QAM_15 MHz

Date: 20.FEB.2020 12:19:25

16QAM_20 MHz

Date: 20.FEB.2020 12:20:26

LTE Band 5:

QPSK_1.4 MHz

Date: 20.FEB.2020 12:21:06

QPSK_3 MHz

Date: 20.FEB.2020 12:21:51

QPSK_5 MHz

Date: 20.FEB.2020 12:22:35

QPSK_10 MHz

Date: 20.FEB.2020 12:23:36

16QAM_1.4 MHz

Date: 20.FEB.2020 12:21:25

16QAM_3 MHz

Date: 20.FEB.2020 12:22:10

16QAM_5 MHz

Date: 20.FEB.2020 12:23:04

16QAM_10 MHz

Date: 20.FEB.2020 12:24:03

LTE Band 7:

QPSK_5 MHz

Date: 20.FEB.2020 13:27:19

QPSK_10 MHz

Date: 20.FEB.2020 13:43:14

QPSK_15 MHz

Date: 20.FEB.2020 13:44:10

QPSK_20 MHz

Date: 20.FEB.2020 13:45:12

16QAM_5 MHz

Date: 20.FEB.2020 13:42:34

16QAM_10 MHz

Date: 20.FEB.2020 13:43:41

16QAM_15 MHz

Date: 20.FEB.2020 13:44:39

16QAM_20 MHz

Date: 20.FEB.2020 13:45:44

LTE Band 12:

QPSK_1.4 MHz

Date: 20.FEB.2020 13:46:29

QPSK_3 MHz

Date: 20.FEB.2020 13:47:23

QPSK_5 MHz

Date: 20.FEB.2020   13:48:23

QPSK_10 MHz

Date: 20.FEB.2020   13:49:31

16QAM_1.4 MHz

Date: 20.FEB.2020 13:46:58

16QAM_3 MHz

Date: 20.FEB.2020 13:47:49

16QAM_5 MHz

Date: 20.FEB.2020 13:48:52

16QAM_10 MHz

Date: 20.FEB.2020 13:50:01

LTE Band 13:

QPSK_5 MHz

Date: 20.FEB.2020 13:50:55

QPSK_10 MHz

Date: 20.FEB.2020 13:51:50

16QAM_5 MHz

Date: 20.FEB.2020 13:51:17

16QAM_10MHz

Date: 20.FEB.2020 13:52:23

LTE Band 17:

QPSK_5 MHz

Date: 20.FEB.2020 13:56:56

QPSK_10 MHz

Date: 20.FEB.2020 13:58:01

16QAM_5 MHz

Date: 20.FEB.2020 13:57:28

16QAM_10MHz

Date: 20.FEB.2020 13:58:34

LTE Band 26:

QPSK_1.4 MHz

Date: 20.FEB.2020 14:00:30

QPSK_3 MHz

Date: 20.FEB.2020 14:01:11

QPSK_5 MHz

Date: 20.FEB.2020 14:02:02

QPSK_10 MHz

Date: 20.FEB.2020 14:03:13

QPSK_15 MHz

Date: 20.FEB.2020 14:04:24

16QAM_1.4 MHz

Date: 20.FEB.2020 14:00:49

16QAM_3 MHz

Date: 20.FEB.2020 14:01:30

16QAM_5 MHz

Date: 20.FEB.2020 14:02:31

16QAM_10 MHz

Date: 20.FEB.2020 14:03:49

16QAM_15 MHz

Date: 20.FEB.2020 14:04:53

LTE Band 38:

QPSK_5 MHz

Date: 25.FEB.2020 11:13:42

QPSK_10 MHz

Date: 20.FEB.2020 14:24:46

QPSK_15 MHz

Date: 20.FEB.2020 14:25:58

QPSK_20 MHz

Date: 20.FEB.2020 14:27:16

16QAM_5 MHz


Date: 20.FEB.2020 14:24:07

16QAM_10 MHz

Date: 20.FEB.2020 14:25:16