



NVLAP LAB CODE 200707-0



FCC PART 22H & 24E

MEASUREMENT AND TEST REPORT

For

Zonda Corporation, S.A. de C.V

Schiller 329 Street, Chapultepec Morales, Zip code 11560,
Mexico City, Mexico

FCC ID: YAUZMCK740

| | |
|--|--|
| Report Type: Original Report | Product Type: GSM Mobile Phone |
| Test Engineer: <u>Tim Zhang</u> <i>tim.zhang</i> | |
| Report Number: <u>RB10091452-22H&24E</u> | |
| Report Date: <u>2010-09-26</u> | |
| Reviewed By: <u>Merry Zhao</u> <i>Merry Zhao</i> | |
| Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 | |

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, NIST, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "*" (Rev.2)

TABLE OF CONTENTS

| | |
|---|-----------|
| GENERAL INFORMATION..... | 4 |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | 4 |
| OBJECTIVE | 4 |
| RELATED SUBMITTAL(S)/GRANT(S)..... | 4 |
| TEST METHODOLOGY | 4 |
| TEST FACILITY | 5 |
| SYSTEM TEST CONFIGURATION..... | 6 |
| JUSTIFICATION | 6 |
| EQUIPMENT MODIFICATIONS | 6 |
| CONFIGURATION OF TEST SETUP | 6 |
| BLOCK DIAGRAM OF TEST SETUP | 6 |
| SUMMARY OF TEST RESULTS..... | 7 |
| FCC §1.1307 & §2.1093 - RF EXPOSURE..... | 8 |
| APPLICABLE STANDARDS..... | 8 |
| TEST RESULT | 8 |
| FCC §2.1047 - MODULATION CHARACTERISTIC | 9 |
| FCC § 2.1046, § 22.913 (A) & § 24.232 (C) - RF OUTPUT POWER..... | 10 |
| APPLICABLE STANDARDS..... | 10 |
| TEST PROCEDURE | 10 |
| TEST EQUIPMENT LIST AND DETAILS..... | 10 |
| TEST DATA | 11 |
| FCC §2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH..... | 13 |
| APPLICABLE STANDARDS..... | 13 |
| TEST PROCEDURE | 13 |
| TEST EQUIPMENT LIST AND DETAILS..... | 13 |
| TEST DATA | 13 |
| FCC §2.1051, §22.917(A) & §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS | 17 |
| APPLICABLE STANDARDS..... | 17 |
| TEST PROCEDURE | 17 |
| TEST EQUIPMENT LIST AND DETAILS..... | 17 |
| TEST DATA | 17 |
| FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS | 21 |
| APPLICABLE STANDARDS..... | 21 |
| TEST PROCEDURE | 21 |
| TEST EQUIPMENT LIST AND DETAILS..... | 21 |
| TEST DATA | 22 |
| FCC §22.917(A) & §24.238(A) - BAND EDGES..... | 23 |
| APPLICABLE STANDARDS..... | 23 |
| TEST PROCEDURE | 23 |
| TEST EQUIPMENT LIST AND DETAILS..... | 23 |
| TEST DATA | 23 |

| | |
|---|-----------|
| FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY | 27 |
| APPLICABLE STANDARDS..... | 27 |
| TEST PROCEDURE | 27 |
| TEST EQUIPMENT LIST AND DETAILS..... | 28 |
| TEST DATA | 28 |

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Zonda Corporation, S.A. de C.V*'s product, model number: *ZMCK740 (FCC ID: YAUZMCK740)* or the "EUT" as referred to in this report is a *GSM Mobile Phone*, which measures approximately: 10.8 cm (L) x 6.0 cm (W) x 1.3 cm (H), rated input voltage: DC 3.7 V battery.

Adapter information:

Model: ETPCA-050050UYU7;
Input: AC 100-240 V 50/60 Hz 0.2 A;
Output: DC 5.0 V 500 mA.

All measurement and test data in this report was gathered from production sample serial number: 1009025 (Assigned by BACL, Shenzhen). The EUT was received on 2010-09-14.

Objective

This type approval report is prepared on behalf of *Zonda Corporation, S.A. de C.V* in accordance with Part 2, Subpart J, Part 22 Subpart H, and Part 24 Subpart E of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability, band edge and radiated margin.

Related Submittal(s)/Grant(s)

FCC Part 15.247 submission with FCC ID: YAUZMCK740.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services
Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-C, ANSI C63.4-2003.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

The uncertainty of any RF tests which use conducted method measurement is ± 0.56 dB.

The uncertainty of any radiation emissions measurement is ± 4.0 dB.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp.(Shenzhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 21, 2007. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Justification

The EUT was configured for testing according to TIA/EIA-603-C.


The GSM/PCS item test was performed with the EUT operating at normal mode.

The GPRS item test was performed with the EUT operating at engineering mode.


Equipment Modifications

No modifications were made to the EUT.

Configuration of Test Setup



Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

| FCC Rules | Description of Test | Result |
|--|--|-------------|
| §1.1307, §2.1093 | RF Exposure (SAR) | Compliance* |
| §2.1046; § 22.913 (a); § 24.232 (c) | RF Output Power | Compliance |
| § 2.1047 | Modulation Characteristics | N/A |
| § 2.1049; § 22.905 § 22.917; § 24.238 | 99% & -26 dB Occupied Bandwidth | Compliance |
| § 2.1051, § 22.917 (a); § 24.238 (a) | Spurious Emissions at Antenna Terminal | Compliance |
| § 2.1053 § 22.917 (a); § 24.238 (a) | Field Strength of Spurious Radiation | Compliance |
| § 22.917 (a); § 24.238 (a) | Out of band emission, Band Edge | Compliance |
| § 2.1055 § 22.355; § 24.235 | Frequency stability vs. temperature Frequency stability vs. voltage | Compliance |

Note: * SAR report released by BACL, Report Number: RBJ10091452-SAR

FCC §1.1307 & §2.1093 - RF EXPOSURE

Applicable Standards

§1.1307 and §2.1093.

Test Result

Compliance

The EUT is a portable device, thus requires SAR evaluation; please refer to BACL SAR
Report: RBJ10091452-SAR

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FCC § 2.1046, § 22.913 (a) & § 24.232 (c) - RF OUTPUT POWER

Applicable Standards


According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (c), in no case may the peak output power of a base station transmitter exceed 2 watt EIRP.

Test Procedure

Conducted method:

The RF output of the transmitter was connected to the wireless test set and the spectrum analyzer through sufficient attenuation.



Radiated method:

TIA 603-C section 2.2.17

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|--------------------------------------|-------------|---------------|------------------|----------------------|
| Sunol Sciences | Horn Antenna | DRH-118 | A052604 | 2010-05-05 | 2011-05-04 |
| Rohde & Schwarz | Spectrum Analyzer | FSEM30 | 849720/019 | 2010-07-08 | 2011-07-07 |
| Sunol Sciences | Broadband Antenna | JB1 | A040904-1 | 2010-03-11 | 2011-03-11 |
| HP | Amplifier | 2VA-213+ | T-E27H | 2010-03-08 | 2011-03-07 |
| HP | Signal Generator | HP8657A | 2849U00982 | 2009-10-28 | 2010-10-27 |
| HP | Amplifier | HP8447D | 2944A09795 | 2010-08-02 | 2011-08-02 |
| HP | Synthesized Sweeper | 8341B | 2624A00116 | 2009-11-07 | 2010-11-06 |
| COM POWER | Dipole Antenna | AD-100 | 041000 | 2009-09-25 | 2010-09-25 |
| A.H. System | Horn Antenna | SAS-200/571 | 135 | 2010-05-17 | 2011-05-17 |
| Rohde & Schwarz | Universal Radio Communication Tester | CMU200 | 109038 | 2010-06-11 | 2011-06-10 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

| | |
|---------------------------|----------|
| Temperature: | 25 °C |
| Relative Humidity: | 56 % |
| ATM Pressure: | 100.0kPa |

The testing was performed by Tim Zhang on 2010-09-25.

Conducted Power

Cellular Band (Part 22H)

| Mode | Channel | Frequency (MHz) | Output Power (dBm) | Limit (dBm) |
|------|---------|-----------------|--------------------|-------------|
| GSM | 128 | 824.2 | 32.01 | 38.45 |
| | 190 | 836.6 | 31.94 | 38.45 |
| | 251 | 848.8 | 31.98 | 38.45 |

| Mode | Channel | Frequency (MHz) | Output Power (dBm) | | | | Limit (dBm) |
|------|---------|-----------------|--------------------|---------|---------|---------|-------------|
| | | | 1 slot | 2 slots | 3 slots | 4 slots | |
| GPRS | 128 | 824.2 | 31.56 | 30.93 | 29.47 | 28.59 | 38.45 |
| | 190 | 836.6 | 31.61 | 31.03 | 29.57 | 28.68 | 38.45 |
| | 251 | 848.8 | 31.71 | 31.18 | 29.77 | 28.94 | 38.45 |

PCS Band (Part 24E)

| Mode | Channel | Frequency (MHz) | Output Power (dBm) | Limit (dBm) |
|------|---------|-----------------|--------------------|-------------|
| GSM | 512 | 1850.2 | 30.00 | 33 |
| | 661 | 1880.0 | 29.84 | 33 |
| | 810 | 1909.8 | 29.83 | 33 |

| Mode | Channel | Frequency (MHz) | Output Power (dBm) | | | | Limit (dBm) |
|------|---------|-----------------|--------------------|---------|---------|---------|-------------|
| | | | 1 slot | 2 slots | 3 slots | 4 slots | |
| GPRS | 512 | 1850.2 | 30.11 | 29.15 | 27.28 | 26.24 | 33 |
| | 661 | 1880.0 | 30.03 | 29.09 | 27.28 | 26.25 | 33 |
| | 810 | 1909.8 | 29.98 | 29.20 | 27.42 | 26.44 | 33 |

ERP & EIRP**ERP for Cellular Band (Part 22H)**

| Indicated | | Table Angle Degree | Test Antenna | | Substituted | | | Antenna Gain Correction (dBd) | Cable Loss (dB) | Absolute Level (dBm) | Part 22H |
|-----------------|---------------------------|--------------------|--------------|-------------|-----------------|------------------|------------------|-------------------------------|-----------------|----------------------|----------|
| Frequency (MHz) | S.A. Reading (dB μ V) | | Height (m) | Polar (H/V) | Frequency (MHz) | S.G. Level (dBm) | Ant. Polar (H/V) | | | | |
| Low Channel | | | | | | | | | | | |
| 824.2 | 116.02 | 170 | 2.0 | H | 824.2 | 29.0 | H | 0 | 0.9 | 28.1 | 38.45 |
| 824.2 | 115.16 | 20 | 1.2 | V | 824.2 | 28.6 | V | 0 | 0.9 | 27.7 | 38.45 |

EIRP for PCS Band (Part 24E)

| Indicated | | Table Angle Degree | Test Antenna | | Substituted | | | Antenna Gain Correction (dBi) | Cable Loss (dB) | Absolute Level (dBm) | Part 24E |
|-----------------|---------------------------|--------------------|--------------|-------------|-----------------|------------------|------------------|-------------------------------|-----------------|----------------------|----------|
| Frequency (MHz) | S.A. Reading (dB μ V) | | Height (m) | Polar (H/V) | Frequency (MHz) | S.G. Level (dBm) | Ant. Polar (H/V) | | | | |
| Low Channel | | | | | | | | | | | |
| 1850.2 | 96.06 | 0 | 2.0 | H | 1850.2 | 20.9 | H | 6.2 | 1.09 | 26.01 | 33 |
| 1850.2 | 97.48 | 148 | 1.2 | V | 1850.2 | 21.7 | V | 6.2 | 1.09 | 26.81 | 33 |


FCC §2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH**Applicable Standards**

FCC §2.1049, §22.917, §22.905 and §24.238.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 30 kHz (Cellular /PCS) and the 26 dB & 99% bandwidth was recorded.

**Test Equipment List and Details**

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|--------------------------------------|--------|---------------|------------------|----------------------|
| Rohde & Schwarz | EMI Test Receiver | ESCI | 100224 | 2009-11-24 | 2010-11-23 |
| Rohde & Schwarz | Universal Radio Communication Tester | CMU200 | 109038 | 2010-06-11 | 2011-06-10 |

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data**Environmental Conditions**

| | |
|--------------------|----------|
| Temperature: | 25 °C |
| Relative Humidity: | 56% |
| ATM Pressure: | 100.0kPa |

The testing was performed by Tim Zhang on 2010-09-17.

GMSK:

Cellular Band (Part 22H)

| Channel | Frequency (MHz) | 99% Occupied Bandwidth (kHz) | 26 dB Bandwidth (kHz) |
|---------|-----------------|------------------------------|-----------------------|
| 190 | 836.6 | 250.0 | 336.0 |


PCS Band (Part 24E)

| Channel | Frequency (MHz) | 99% Occupied Bandwidth (kHz) | 26 dB Bandwidth (kHz) |
|---------|-----------------|------------------------------|-----------------------|
| 661 | 1880.0 | 248.0 | 332.0 |

Please refer to the following plots.


Cellular Band (Part 22H)

99% Occupied Bandwidth




Date: 17.SEP.2010 07:55:18

26 dB Bandwidth




Date: 17.SEP.2010 07:56:43

PCS Band (Part 24E)

99% Occupied Bandwidth

Date: 17.SEP.2010 08:00:26

26 dB Bandwidth

Date: 17.SEP.2010 07:58:18

FCC §2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standards

FCC §2.1051, §22.917(a) and §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|--------------------------------------|--------|---------------|------------------|----------------------|
| Rohde & Schwarz | Spectrum Analyzer | FSEM30 | 849720/019 | 2010-07-08 | 2011-07-07 |
| Rohde & Schwarz | Universal Radio Communication Tester | CMU200 | 109038 | 2010-06-11 | 2011-06-10 |
| Rohde & Schwarz | EMI Test Receiver | ESCI | 100224 | 2009-11-24 | 2010-11-23 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.



Test Data

Environmental Conditions

| | |
|--------------------|----------|
| Temperature: | 25 °C |
| Relative Humidity: | 56 % |
| ATM Pressure: | 100.0kPa |


The testing was performed by Tim Zhang on 2010-09-20 and 2010-09-24.

Please refer to the following plots.


Cellular Band (Part 22H)**30 – 1000 MHz - Middle Channel****1 – 10 GHz - Middle Channel**

PCS Band (Part24E)


30 – 1000 MHz - Middle Channel



1 - 2 GHz - Middle Channel



2 – 20 GHz - Middle Channel



FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS**Applicable Standards**

FCC § 2.1053, §22.917 and § 24.238.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg (\text{TXpwr in Watts}/0.001)$ – the absolute level

Spurious attenuation limit in dB = $43 + 10 \log_{10} (\text{power out in Watts})$

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|--------------------------------------|-------------|---------------|------------------|----------------------|
| Sunol Sciences | Horn Antenna | DRH-118 | A052604 | 2010-05-05 | 2011-05-04 |
| Sunol Sciences | Broadband Antenna | JB1 | A040904-1 | 2010-03-11 | 2011-03-11 |
| Rohde & Schwarz | Spectrum Analyzer | FSEM30 | 849720/019 | 2010-07-08 | 2011-07-07 |
| HP | Amplifier | 2VA-213+ | T-E27H | 2010-03-08 | 2011-03-07 |
| HP | Signal Generator | HP8657A | 2849U00982 | 2009-10-28 | 2010-10-27 |
| HP | Amplifier | HP8447D | 2944A09795 | 2010-08-02 | 2011-08-02 |
| HP | Synthesized Sweeper | 8341B | 2624A00116 | 2009-11-07 | 2010-11-06 |
| COM POWER | Dipole Antenna | AD-100 | 041000 | 2009-09-25 | 2010-09-25 |
| A.H. System | Horn Antenna | SAS-200/571 | 135 | 2010-05-17 | 2011-05-17 |
| Rohde & Schwarz | Universal Radio Communication Tester | CMU200 | 109038 | 2010-06-11 | 2011-06-10 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

| | |
|--------------------|----------|
| Temperature: | 25 °C |
| Relative Humidity: | 56 % |
| ATM Pressure: | 100.0kPa |

The testing was performed by Tim Zhang on 2010-09-18.

Test mode: Transmitting

Cellular Band (Part 22H)

| Indicated | | Table Angle Degree | Test Antenna | | Substituted | | | | Absolute Level (dBm) | Limit (dBm) | Margin (dB) |
|----------------------------|---------------------------|--------------------|--------------|-------------|-----------------|-------------|-----------------|-----------------|----------------------|-------------|-------------|
| Frequency (MHz) | S.A. Reading (dB μ V) | | Height (m) | Polar (H/V) | Frequency (MHz) | Level (dBm) | Ant. Gain (dBi) | Cable Loss (dB) | | | |
| Middle Channel, Below 1GHz | | | | | | | | | | | |
| 992.24 | 43.12 | 150 | 1.5 | H | 992.24 | -53.7 | 0 | 0.80 | -54.5 | -13 | 41.50 |
| 540.22 | 39.41 | 242 | 1.2 | V | 540.22 | -56.7 | 0 | 0.65 | -57.35 | -13 | 44.35 |
| 720.64 | 38.52 | 70 | 1.5 | V | 720.64 | -58.5 | 0 | 0.76 | -59.26 | -13 | 46.26 |
| 631.4 | 35.64 | 210 | 1.0 | H | 631.4 | -61.8 | 0 | 0.77 | -62.57 | -13 | 49.57 |
| Middle Channel, Above 1GHz | | | | | | | | | | | |
| 2509.8 | 58.12 | 210 | 1.8 | H | 2509.8 | -37.1 | 7.3 | 1.19 | -30.99 | -13 | 17.99 |
| 2509.8 | 53.25 | 130 | 1.5 | V | 2509.8 | -43.5 | 7.3 | 1.19 | -37.39 | -13 | 24.39 |
| 1673.0 | 54.74 | 100 | 1.9 | H | 1673.0 | -44 | 6.2 | 0.94 | -38.74 | -13 | 25.74 |
| 1673.0 | 47.92 | 220 | 1.0 | V | 1673.0 | -51.3 | 6.2 | 0.94 | -46.04 | -13 | 33.04 |
| 3346.6 | 43.56 | 130 | 1.6 | H | 3346.6 | -60.3 | 6.7 | 1.38 | -54.98 | -13 | 41.98 |
| 3346.6 | 40.47 | 150 | 1.4 | V | 3346.6 | -63.1 | 6.7 | 1.38 | -57.78 | -13 | 44.78 |

PCS Band (Part 24E)

| Indicated | | Table Angle Degree | Test Antenna | | Substituted | | | | Absolute Level (dBm) | Limit (dBm) | Margin (dB) |
|----------------------------|---------------------------|--------------------|--------------|-------------|-----------------|-------------|-----------------|-----------------|----------------------|-------------|-------------|
| Frequency (MHz) | S.A. Reading (dB μ V) | | Height (m) | Polar (H/V) | Frequency (MHz) | Level (dBm) | Ant. Gain (dBi) | Cable Loss (dB) | | | |
| Middle Channel, Below 1GHz | | | | | | | | | | | |
| 540.22 | 40.91 | 150 | 1.5 | H | 540.22 | -55.7 | 0 | 0.65 | -56.35 | -13 | 43.35 |
| 906.88 | 37.42 | 242 | 1.2 | V | 906.88 | -57 | 0 | 0.76 | -57.76 | -13 | 44.76 |
| 720.64 | 40.12 | 210 | 1.0 | H | 720.64 | -57.9 | 0 | 0.74 | -58.64 | -13 | 45.64 |
| 992.24 | 36.85 | 70 | 1.5 | V | 992.24 | -59.9 | 0 | 0.80 | -60.7 | -13 | 47.70 |
| Middle Channel, Above 1GHz | | | | | | | | | | | |
| 3760 | 61.08 | 200 | 1.6 | V | 3760 | -35.3 | 6.9 | 1.47 | -29.87 | -13 | 16.87 |
| 3760 | 54.69 | 190 | 1.9 | H | 3760 | -42.6 | 6.9 | 1.47 | -37.17 | -13 | 24.17 |
| 5640 | 50.63 | 170 | 1.6 | H | 5640 | -48.5 | 8.3 | 1.76 | -41.96 | -13 | 28.96 |
| 5640 | 48.43 | 80 | 1.5 | V | 5640 | -50.5 | 8.3 | 1.76 | -43.96 | -13 | 30.96 |
| 7520 | 45.62 | 180 | 1.5 | H | 7520 | -54.3 | 7.6 | 2.09 | -48.79 | -13 | 35.79 |
| 7520 | 44.87 | 110 | 1.5 | V | 7520 | -55.1 | 7.6 | 2.09 | -49.59 | -13 | 36.59 |

FCC §22.917(a) & §24.238(a) - BAND EDGES

Applicable Standards


According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency, RBW set to 10 kHz.



Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|--------------------------------------|--------|---------------|------------------|----------------------|
| Rohde & Schwarz | EMI Test Receiver | ESCI | 100224 | 2009-11-24 | 2010-11-23 |
| Rohde & Schwarz | Universal Radio Communication Tester | CMU200 | 109038 | 2010-06-11 | 2011-06-10 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

| | |
|--------------------|----------|
| Temperature: | 25 °C |
| Relative Humidity: | 56 % |
| ATM Pressure: | 100.0kPa |

The testing was performed by Tim Zhang on 2010-09-17.

Please refer to the following tables and plots.


Cellular Band (Part 22H)

| Frequency (MHz) | Emission (dBm) | Limit (dBm) |
|--------------------|-------------------|----------------|
| 823.996 | -14.44 | -13 |
| 849.016 | -14.46 | -13 |

PCS Band (Part 24E)


| Frequency (MHz) | Emission (dBm) | Limit (dBm) |
|--------------------|-------------------|----------------|
| 1849.996 | -15.85 | -13 |
| 1910.024 | -17.42 | -13 |

Cellular Band, Lowest Channel




Date: 17.SEP.2010 08:10:53

Cellular Band, Highest Channel




Date: 17.SEP.2010 08:09:26

PCS Band, Lowest Channel



Date: 17.SEP.2010 08:04:19

PCS Band, Highest Channel



Date: 17.SEP.2010 08:06:01

FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY

Applicable Standards

CFR47 § 2.1055 (a), § 2.1055 (d), §22.355, §24.235

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

| Frequency Range (MHz) | Base, fixed (ppm) | Mobile \leq 3 watts (ppm) | Mobile \leq 3 watts (ppm) |
|-----------------------|-------------------|-----------------------------|-----------------------------|
| 25 to 50 | 20.0 | 20.0 | 50.0 |
| 50 to 450 | 5.0 | 5.0 | 50.0 |
| 450 to 512 | 2.5 | 5.0 | 5.0 |
| 821 to 896 | 1.5 | 2.5 | 2.5 |
| 928 to 929. | 5.0 | N/A | N/A |
| 929 to 960. | 1.5 | N/A | N/A |
| 2110 to 2220 | 10.0 | N/A | N/A |


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: An external variable DC power supply was connected to the battery terminals of the equipment under test. The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.



Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|--------------------------------------|--------|---------------|------------------|----------------------|
| WUHUAN | Temperature & Humidity Chamber | HTP205 | 20021115 | 2010-06-04 | 2011-06-03 |
| Rohde & Schwarz | Universal Radio Communication Tester | CMU200 | 109038 | 2010-06-11 | 2011-06-10 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

| | |
|--------------------|----------|
| Temperature: | 25 °C |
| Relative Humidity: | 56 % |
| ATM Pressure: | 100.0kPa |

The testing was performed by Tim Zhang on 2010-09-18.

Cellular Band (Part 22H)

| Middle Channel, $f_0 = 836.6$ MHz | | | | |
|-----------------------------------|-----------------------------------|----------------------|-----------------------|-------------|
| Temperature (°C) | Power Supplied (V _{DC}) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 0 | 3.7 | -18 | -0.0215 | 2.5 |
| 10 | | -19 | -0.0227 | 2.5 |
| 20 | | -15 | -0.0179 | 2.5 |
| 30 | | -16 | -0.0191 | 2.5 |
| 40 | | -13 | -0.0155 | 2.5 |
| 25 | 4.2 | -13 | -0.0155 | 2.5 |
| | 3.7 | -15 | -0.0179 | 2.5 |
| | 3.5 | -12 | -0.0143 | 2.5 |

PCS Band (Part 24E)

| Middle Channel, $f_0 = 1880$ MHz | | | | |
|----------------------------------|-----------------------------------|----------------------|-----------------------|-------------|
| Temperature (°C) | Power Supplied (V _{DC}) | Frequency Error (Hz) | Frequency Error (ppm) | Limit (ppm) |
| 0 | 3.7 | -15 | -0.0080 | Compliance |
| 10 | | -11 | -0.0059 | Compliance |
| 20 | | -26 | -0.0138 | Compliance |
| 30 | | -17 | -0.0090 | Compliance |
| 40 | | -19 | -0.0101 | Compliance |
| 25 | 4.2 | -16 | -0.0085 | Compliance |
| | 3.7 | -11 | -0.0059 | Compliance |
| | 3.5 | -19 | -0.0101 | Compliance |

***** END OF REPORT *****