

TEST REPORT

	1=0111				
То:	MAC DUE INTERNATIONAL LTD.		To:	-	
Attn:	Linda Lei		Attn:	-	
Address:	Unit 2102, Greenfield Tower, Concordia Plaza, No.1 Science Museum Rd, TST East, KLN.		Address:	-	
Fax:	86317106		Fax:	-	
E-mail:	linda@innovation-hk.com		E-mail:	-	
Folder No.:	BVC	CK10A	P317HTHS-B		
Factory name:					
Location:					
Product:			GGY (49MHz) L: KD0701		
			Sample No:	(5210)111-0531	
			Test date:	May 1, 2010 To May 4, 2010	
			Test Requested:	FCC Part 15 - 2008	
			Test Method:	ANSI C63.4 - 2003	
			FCC ID:	YB91-1049MHZ	
The results given in this report are related to the tested specimen of the described electrical apparatus.					
CONCLUSION: The submitted sample was found to COMPLY with requirement of FCC Part 15 Subpart C.					
	Authorized	Signat	ure:		
(1) ^				
	by h		Ar (h.	au	
Reviewed by: I	Keith Yeung	Appro	ved by: Steven T	sang	
Date: May 18, 2010 Date: May 18, 2010					

BUREAU VERITAS HONG KONG LIMITED – Kowloon Bay Office 1/F Pacific Trade Centre, 2 Kai Hing Road, Kowloon Bay, Kowloon,HONG KONG Tel: +852 2331 0888 Fax: +852 2331 0889 www.cps.bureauveritas.com This report is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. Our report is limited to the test samples identified herein. The results set forth in this report are not necessarily indicative or representative of the statistical quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof. You shall have thirty days from receipt of this report to request additional testing of the samples or to notify us of any errors or omissions relating to our report, provided, however, such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



Location of the test laboratory

Radiated and Conducted emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 - 2003. An Open Area Test Site and Full Anechoic Chamber (FCC Listed Site, Registration No. 642151) are set up for investigation and located at:

BUREAU VERITAS HONG KONG LIMITED, EMC CENTRE

No. 2106-2107, 21/F., Westin Centre, 26 Hung To Road, Kwun Tong, Kowloon, Hong Kong

List of measuring equipment

Radiated Emission

EQUIPMENT	MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATION DUE
EMI TEST RECEIVER	R&S	ESCI	100379	24-AUG-2010
BILOG ANTENNA	SCHAFFNER	CBL6112D	25229	31-MAY-2010
OPEN AREA TEST SITE	BVCPS	N/A	N/A	03-JULY-2010
ANECHOIC CHAMBER	ALBATROSS	M-CDC	80374004499B	07-JULY-2010
COAXIAL CABLE	SUHNER	N/A	N/A	11-MAY-2010
SPECTRUM ANALYZER	ADVANTEST	R3127	111000909	17-DEC-2010

Remarks:-

N/A: Not Applicable or Not Available

The measurement instrumentation uncertainty would be taking into consideration on each of the test result



Equipment Under Test [EUT]

Description of Sample:

Model Name: 1:10 BUGGY
Model Number: KD0701

Trade Name: Fast lane RC / Motorma RC

Additional Model 1:8 NEW BUGGY / 1:8 F1 / 1:10 CYCLONE / 1:10 TRUGGY /

Name: 1:8 Hot Rod

Additional Model KD0702B / KD0702C-G, KD0702C-0 / KD0714M, KD0714A, MDI1045 /

Number: MDI1049 / MDI1050 / MDI1051 / MDI1052 / MDI1053 / MDI1054 /

MDI1050 / MDI1056 / MDI1057 / KD0702 / 493379

Additional Model Declare the Circuit, PCB layout and Electrical parts of the products are identical to the basic model. Except the shape and decoration of shell is

different.

Rating: 9Vd.c ("6F22" size battery x 1)

Description of EUT Operation:

The Equipment Under Test (EUT) is a Mac Due International Ltd. of Radio Control toy. It is a 1 wheel, 1 trigger and 1 switch transmitter and operating at 49.8602MHz. The EUT continues to transmit buttons is being pressed, Modulation by IC, and type is pulse modulation.

The transmitter has different control:

- 1. Wheel control left and right
- 2. Trigger- control forward and backward
- 3. On/off switch switch on / off

Antenna Requirement (Section 15.203)

The EUT is use of a permanently antenna. The antenna consists of 43.0cm long metal antenna. It is soldered on the PCB. The antenna is not replaceable or user serviceable. The requirements of S15.203 are met. There are no deviations or exceptions to the specifications.





BUREAU VERITAS HONG KONG LIMITED – Kowloon Bay Office 1/F Pacific Trade Centre, 2 Kai Hing Road, Kowloon Bay, Kowloon,HONG KONG Tel: +852 2331 0888

Fax: +852 2331 0889 www.cps.bureauveritas.com This report is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. Our report is limited to the test samples identified herein. The results set forth in this report are not necessarily indicative or representative of the statistical quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof. You shall have thirty days from receipt of this report to request additional testing of the samples or to notify us of any errors or omissions relating to our report, provided, however, such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



Radiated Emissions (Fundamental)

Test Requirement: FCC Part 15 Section 15.235

Test Method: ANSI C63.4

Test Date(s): 2010-05-04

Temperature: 26.0 °C

Humidity: 62.0 %

Mode of Operation: Transmission mode

Tested Voltage: 9Vd.c. ("6F22" size battery x 1)

101.1 kPa

Test Procedure:

Atmospheric Pressure:


Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 - 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using new battery. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.

Location: The Roof, Westin Centre, 26 Hung To Road, Kwun Tong, Kowloon, Hong Kong

Test Setup: Open Area Test Site



BUREAU VERITAS HONG KONG LIMITED – Kowloon Bay Office 1/F Pacific Trade Centre, 2 Kai Hing Road, Kowloon Bay, Kowloon,HONG KONG Tel: +852 2331 0888 Fax: +852 2331 0889

www.cps.bureauveritas.com

This report is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. Our report is limited to the test samples identified herein. The results set forth in this report are not necessarily indicative or representative of the statistical quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof. You shall have thirty days from receipt of this report to request additional testing of the samples or to notify us of any errors or omissions relating to our report, provided, however, such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



Limits for Field Strength of Fundamental Emissions (FCC 47CFR 15.235):

- 6	The state of the s						
	Frequency Range of	Field Strength of	Field Strength of				
Fundamental		Fundamental Emission	Fundamental Emission				
		[Peak]	[Average]				
	[MHz]	[μV/m]	[μV/m]				
ı	49.82 – 49.90	100,000 (100 dBμV/m)	10,000 (80 dBμV/m)				

Measurement Data

Test Result of (Transmission mode): PASS

Detection mode: Peak

Frequency (MHz)	Polarity (H/V) and degree	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBµV/m)	Limit at 3m (dBμV/m)	Margin (dB)
49.86	V/0°	9.7	70.2	100	-29.8

Detection mode: # Average

Frequency (MHz)	Polarity (H/V) and degree	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBµV/m)	Limit at 3m (dBμV/m)	Margin (dB)
49.86	V/0°	9.7	**66.0	80	-14.0

For pulse modulated devices and using measuring equipment employing a peak detection mode, properly adjusted for such factor as pulse desensitisation.

**Duty Cycle Correction = 20Log(0.618) =-4.2dB

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting: RBW = 100KHz

VBW = 300KHz



Radiated Emissions (9kHz – 1GHz)

Test Requirement: FCC Part 15 Section 15.209

Test Method:

ANSI C63.4

Test Date(s):

2010-05-04

Temperature:

26.0 °C

Humidity:

4tmospheric Pressure:

101.1 kPa

Mode of Operation: Transmission mode

Tested Voltage: 9Vd.c. ("6F22" size battery x 1)

Limits for Radiated Emissions [FCC 47 CFR 15.209]:

Frequency Range	Quasi-Peak Limits
[MHz]	[μV/m]
1.705-30	300
30-88	100
88-216	150
216-960	200
Above960	500

Measurement Data

Test Result of (Transmission mode): PASS

Detection mode: Quasi-Peak

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBµV/m)	Limit at 3m (dB _µ V/m)	Margin (dB)
99.72	Н	10.7	23.4	43.5	-20.1
149.58	Н	10.9	22.6	43.5	-20.9
199.44	Н	11.6	22.0	43.5	-21.5
249.30	Н	13.8	23.7	46.0	-22.3
299.16	Н	15.0	25.8	46.0	-20.2
349.12	Н	16.8	26.3	46.0	-19.7
398.88	Н	18.1	27.8	46.0	-18.2
448.74	Н	19.0	27.8	46.0	-18.2
498.60	V	19.9	31.5	46.0	-14.5
548.46	Н	20.9	32.1	46.0	-13.9

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting: RBW = 120KHz VBW = 120KHz

Kowloon,HONG KONG Tel: +852 2331 0888 Fax: +852 2331 0889 www.cps.bureauveritas.com



26dB Bandwidth of Fundamental Emission

Test Requirement: FCC 47 CFR 15.235

Test Method: ANSI C63.4:2003 (Section 13.1.7)

Test Date(s): 2010-05-01 Temperature: 26.0 °C Humidity: 62.0 % Atmospheric Pressure: 101.1 kPa

Mode of Operation: Transmission mode

Tested Voltage: 9Vd.c. ("6F22" size battery x 1)

Test Method:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.


Limits for 26dB Bandwidth of Fundamental Emission:

Frequency	26dB Bandwidth	Limits				
[MHz]	[KHz]	[MHz]				
49.8602	82.8	within 49.82-49.90				



Measurement Data:

Test Result of 26dB Bandwidth of Fundamental Emission: PASS



Date: 1.MAY.2010 14:33:27



Duty Cycle Correction During 100msec:


Each function key sends a different series of characters, but each packet period (20.7msec) never exceeds a series of 4 long (1.7msec) and 10 short (0.6msec) pulses. Assuming any combination of short or long pulses may be obtained due to encoding the worst case transmit duty cycle would be considered (4x1.7msec) + (10x0.6msec) per 20.7msec=61.8% duty cycle. Figure A and C show the characteristics of the pulse train for one of these functions.

Remarks:


Duty Cycle Correction = 20Log(0.618) =-4.2dB

The following figures [Figure A to Figure C] show the characteristics of the pulse train for one of these functions.





Date: 1.MAY.2010 14:39:18




Date: 1.MAY.2010 14:39:45

BUREAU VERITAS HONG KONG LIMITED -Kowloon Bay Office
1/F Pacific Trade Centre,
2 Kai Hing Road, Kowloon Bay, Kowloon,HONG KONG Tel: +852 2331 0888 Fax: +852 2331 0889

www.cps.bureauveritas.com

This report is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. Our report is limited to the test samples identified herein. The results set forth in this report are not necessarily indicative or representative of the statistical quality or characteristics of nerein. The results set forth if this report are not necessarily indicative or representative of the statistical quanty or characteristics on the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof. You shall have thirty days from receipt of this report to request additional testing of the samples or to notify us of any errors or omissions relating to our report, provided, however, such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.





Date: 1.MAY.2010 14:40:22



Photographs of EUT


Front View of the product



Rear View of the product



Inner Circuit Top View



Inner Circuit Bottom View





Battery compartment



Battery Cover



Front View of the product (Internal)



Rear View of the product (Internal)



Antenna



BUREAU VERITAS HONG KONG LIMITED – Kowloon Bay Office 1/F Pacific Trade Centre, 2 Kai Hing Road, Kowloon Bay, Kowloon,HONG KONG Tel: +852 2331 0888 Fax: +852 2331 0889

www.cps.bureauveritas.com

This report is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. Our report is limited to the test samples identified herein. The results set forth in this report are not necessarily indicative or representative of the statistical quality or characteristics of nerein. The results set forth if this report are not necessarily indicative or representative of the statistical quanty or characteristics on the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof. You shall have thirty days from receipt of this report to request additional testing of the samples or to notify us of any errors or omissions relating to our report, provided, however, such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.





***** End of Report *****