


 Dates of Tests : June 14~21, 2010  
 Test Report S/N: LR500191006C  
 Test Site : LTA CO., LTD

## CERTIFICATION OF COMPLIANCE

FCC ID.

**YBICOMPACTPLUS**

APPLICANT

**SmartPayTech INC.**

<b>Equipment Class</b>	:	<b>Part 15 Spread Spectrum Transmitter (DSS)</b>
<b>Manufacturing Description</b>	:	<b>Industrial PDA</b>
<b>Manufacturer</b>	:	<b>SmartPayTech INC.</b>
<b>Model name</b>	:	<b>SmartCompact Plus</b>
<b>Test Device Serial No.:</b>	:	<b>Identical prototype</b>
<b>Rule Part(s)</b>	:	<b>FCC Part 15.247 Subpart C; ANSI C-63.4-2003</b>
<b>Frequency Range</b>	:	<b>2402 ~ 2480MHz</b>
<b>RF power</b>	:	<b>Max 3.25dBm - Conducted</b>
<b>Data of issue</b>	:	<b>June 21, 2010</b>

This test report is issued under the authority of:

Kyung-Taek LEE, Technical Manager

The test was supervised by:

Hyun-Chae You, Test Engineer

**This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. This report must not be used by the applicant to claim product endorsement by any agency.**

NVLAP LAB Code.: 200723-0

## **TABLE OF CONTENTS**

1. GENERAL INFORMATION'S -----	3
2. INFORMATION'S ABOUT TEST ITEM -----	4
3. TEST REPORT -----	5
3.1 SUMMARY OF TESTS -----	5
3.2 TECHNICAL CHARACTERISTICS TEST -----	6
3.2.1 CARRIER FREQUENCY SEPARATION -----	6
3.2.2 NUMBER OF HOPPING FREQUENCIES -----	8
3.2.3 20 dB BANDWIDTH -----	10
3.2.4 TIME OF OCCUPANCY (Dwell Time) -----	17
3.2.5 TTANSMITTER OUTPUT POWER -----	22
3.2.6 BAND – EDGE & SPURIOUS -----	26
3.2.7 FIELD STRENGTH OF HARMONICS -----	32
3.2.8 AC CONDUCTED EMISSIONS -----	36
 <b>APPENDIX</b>	
APPENDIX TEST EQUIPMENT USED FOR TESTS -----	41

## 1. General information's

### **1-1 Test Performed**

Company name : LTA Co., Ltd.  
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822  
 Web site : <http://www.ltalab.com>  
 E-mail : [chahn@ltalab.com](mailto:chahn@ltalab.com)  
 Telephone : +82-31-323-6008  
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

### **1-2 Accredited agencies**

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2010-09-30	ECT accredited Lab.
RRL	KOREA	KR0049	2011-06-20	EMC accredited Lab.
FCC	U.S.A	610755	2011-04-22	FCC filing
VCCI	JAPAN	R2133, C2307	2011-06-21	VCCI registration
IC	CANADA	IC5799	2012-05-14	IC filing

## 2. Information's about test item

## **2-1 Client & Manufacturer**

Company name : SmartPayTech INC.  
Address : 496 Woncheon-dong youngtongu Suwon, kyung ki-do, 442-824, Korea  
Tel / Fax : Tel. : +82. 31. 211.5596~7/ Fax : 82. 31.217. 8254

## **2-2 Equipment Under Test (EUT)**

### **2-3 Tested frequency**

	<b>LOW</b>	<b>MID</b>	<b>HIGH</b>
<b>Frequency (MHz)</b>	2402	2441	2480

## **2-4 Ancillary Equipment**

Equipment	Model No.	Serial No.	Manufacturer
PC	HP Compaq dx7400	CNG8330J95	HP
MONITOR	HPL1710	CNC816QHF2	HP
Keyboard	SK-8115	68A-04Q6	DELL
Mouse	MO56UOA	F0J00NOL	DELL
PRINTER	STYLUS C65	N/A	EPSON
EARPHONE	N/A	N/A	N/A

### 3. Test Report

#### 3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	> 25 kHz	Conducted	C
15.247(a)	Number of Hopping Frequencies	> 15 hops		C
15.247(a)	20 dB Bandwidth 99% Bandwidth	> 1.5 MHz		C
15.247	Dwell Time	< 0.4 seconds		C
15.247(b)	Transmitter Output Power	< 250 mWatt		C
15.247(d)	Conducted Spurious emission	> 20 dBc		C
15.247(d)	Band Edge	> 20 dBc		C
15.249 / 15.209	Field Strength of Harmonics	< 54 dBuV (at 3m)	Radiated	C
15.109	Field Strength	-		C
15.207 /15.107	AC Conducted Emissions	EN 55022	Line Conducted	C
15.203	Antenna requirement	-	-	C

Note 1: C=Complies    NC=Not Complies    NT=Not Tested    NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

#### → Antenna Requirement

The SmartPayTech INC. FCC ID: YBICOMPACTPLUS unit complies with the requirement of §15.203. The antenna is connected to inside of EUT. And type is PCB antenna.

The sample was tested according to the following specification:

FCC Parts 15.247; ANSI C-63.4-2003

## 3.2 Transmitter requirements

### 3.2.1 Carrier Frequency Separation

#### Procedure:

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

#### The spectrum analyzer is set to:

Span = 3 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 10 kHz (1% of the span or more)      Sweep = auto

VBW = 10 kHz      Detector function = peak

Trace = max hold

#### Measurement Data:

Test Results	
Carrier Frequency Separation (MHz)	Result
1.003	Complies

- See next pages for actual measured spectrum plots.

#### Minimum Standard:

The EUT shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of 20dB bandwidth of the hopping channel, whichever is greater.

#### Measurement Setup





Figure 1: Measurement setup for the carrier frequency separation

### Carrier Frequency Separation



### 3.2.2 Number of Hopping Frequencies

#### Procedure:

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, four frequency ranges within the 2400 ~ 2483.5 MHz FH band were examined.

The spectrum analyzer is set to:

Frequency range 1: Start = 2400.0MHz, Stop = 2441.5 MHz

2: Start = 2441.5MHz, Stop = 2483.5 MHz

RBW = 100 kHz (1% of the span or more) Sweep = auto

VBW = 100 kHz (VBW  $\geq$  RBW) Detector function = peak

Trace = max hold Span > 40MHz

**Measurement Data: Complies**

<b>Total number of Hopping Channels</b>	79
---	----

- See next pages for actual measured spectrum plots.



**Minimum Standard:**

At least 15 hopes

**Measurement Setup**

Same as the Chapter 3.2.1 (Figure 1)

## Number of Hopping Frequencies



### 3.2.3 20 dB Bandwidth

#### Procedure:

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is ( as close as possible to ) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

#### The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 3 MHz (approximately 2 or 3 times of the 20 dB bandwidth)

RBW = 30 kHz

Sweep = auto

VBW = 30 kHz (VBW  $\geq$  RBW)

Detector function = peak

Trace = max hold

dB/Div = 5dB

#### Measurement Data:

Frequency (MHz)	Channel No.	Test Results(MHz)	
		20dB Bandwidth	99% Bandwidth
2402	0	0.82	0.88
2441	39	0.82	0.88
2480	78	0.82	0.87

- See next pages for actual measured spectrum plots.

#### Minimum Standard:

N/A

#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

**Channel 1**  
**20 dB Bandwidth**




**99% Bandwidth**



## Channel 2


### 20 dB Bandwidth




### 99% Bandwidth



**Channel 3**  
**20 dB Bandwidth**



**99% Bandwidth**



### 3.2.4 Time of Occupancy (Dwell Time)

#### Procedure:

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

Center frequency = 2441 MHz

Span = zero

RBW = 1 MHz

VBW = 1 MHz (VBW  $\geq$  RBW)

Trace = max hold

Detector function = peak

#### Measurement Data:

Mode	Number of transmission in a 31.6s ( 79Hopping*0.4)	Length of Transmission Time (msec)	Result (msec)	Limit (msec)
DH1	32(Times /3.16sec) *10.533 = 337.06	0.525	176.96	400
DH3	16(Times /3.16sec) *10.533 = 168.53	1.759	296.44	400
DH5	11(Times /3.16sec) *10.533 = 115.86	3.042	352.46	400



- See next pages for actual measured spectrum plots.
- dwell time = {(number of hopping per second / number of slot ) x duration time per channel} x 0.4 ms


#### Minimum Standard:



0.4 seconds within a 30 second period per any frequency

#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

DH1 mode

**DH3 mode**

DH5 mode

### 3.2.5 Transmitter Output Power

#### Procedure:

The peak output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

#### The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 20 MHz (approximately 5 times of the 20 dB bandwidth)

RBW = 3 MHz (greater than the 20dB bandwidth of the emission being measured)

VBW = 3 MHz (VBW  $\geq$  RBW)      Detector function = peak

Trace = max hold      Sweep = auto

#### Measurement Data:



Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	0	<b>3.19</b>	<b>2.08</b>	Complies
2441	39	<b>3.25</b>	<b>2.11</b>	Complies
2480	78	<b>2.64</b>	<b>1.84</b>	Complies


- See next pages for actual measured spectrum plots.

<b>Minimum Standard:</b>	< 250 mW
--------------------------	----------

#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Channel 1Channel 2

**Channel 3**

### 3.2.6 Band Edge

## Procedure:

The bandwidth at 20dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 10 MHz      Detector function = peak

Trace = max hold      Sweep = auto

**Measurement Data: Complies**

- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.


---

<b>Minimum Standard:</b>	> 20 dBc
--------------------------	----------

---

## Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Band – edgeLower edgeUpper edge

**Band-edges in the restricted band 2310-2390 MHz measurement**


Frequency [MHz]	Reading [dBuV/m] AV / Peak	Pol.	Correction Factor			Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
			Antenna	Amp. Gain	Cable	AV / Peak	AV / Peak	AV / Peak	AV / Peak	AV / Peak	AV / Peak
2390	42.15 55.18	H	26.0	36.0	8.2	54.0 74.0	40.3 53.4	13.7 20.6			

**Band-edges in the restricted band 2483.5-2500 MHz measurement**


Frequency [MHz]	Reading [dBuV/m] AV / Peak	Pol.	Correction Factor			Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
			Antenna	Amp. Gain	Cable	AV / Peak	AV / Peak	AV / Peak	AV / Peak	AV / Peak	AV / Peak
2483.5	50.02 64.34	H	26.0	36.0	8.2	54.0 74.0	48.2 62.5	5.8 11.5			

**Note : This EUT was tested in 3 orthogonal positions and the worst-case data was presented.**


Unwanted Emission – Low channel  
Frequency Range = 30 MHz ~ 26.5 GHz



**Unwanted Emission – Middle channel**  
**Frequency Range = 30 MHz ~ 26.5 GHz**



Unwanted Emission – High channel  
Frequency Range = 30 MHz ~ 26.5 GHz



### 3.2.7 Field Strength of Harmonics

#### Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.

RBW = 100 kHz ( 30MHz ~ 1 GHz)

Peak:VBW ≥ RBW

= 1 MHz (1 GHz ~ 10<sup>th</sup> harmonic )

Average:VBW=10Hz

Span = 100 MHz

Detector function = Peak and Average

Trace = max hold

Sweep = auto

#### Measurement Data: Complies

- Refer to the next page.
- No other emissions were detected at a level greater than 10dB below limit.
- The three antennas were used with this EUT during the Testing.

#### Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

\*\* Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

**Measurement Data:**

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor			Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
	AV	Peak		Antenna	Amp.Gain	Cable	AV	Peak	AV	Peak	AV	Peak
4804	26.8	30.9	H	31.4	36	8.7	54.0	74.0	30.9	35.0	23.1	39.0
Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor			Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
	AV	Peak		Antenna	Amp.Gain	Cable	AV	Peak	AV	Peak	AV	Peak
4882	30.5	33.2	H	31.4	36	8.7	54.0	74.0	34.6	37.3	19.4	36.7
Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor			Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
	AV	Peak		Antenna	Amp.Gain	Cable	AV	Peak	AV	Peak	AV	Peak
4960	24.3	27.8	H	31.4	36	8.7	54.0	74.0	28.4	31.9	25.6	42.1


No other emissions were detected at a level greater than 20dB below limit.

Radiated Emissions – PC+CAM+SCAN Mode

243 Jibug-ni, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel: +82-31-3236008,9  
Fax: +82-31-3236010

EUT/Model No.: SmartCompact Plus TEST MODE: PC+CAM+SCAN mode

Temp Humi : 9 / 53 Tested by: LEE.K.H



Freq MHz	Reading dBuV/m	C.F dB/m	Result dBuV/m	Limit QP		Margin dB	Height cm	Angle deg	Polarity
				dBuV/m	dBuV/m				
1 72.57	50.20	-16.19	34.01	39.00	4.99	100	28	VERTICAL	
2 95.88	52.00	-16.46	35.54	43.50	7.96	100	165	VERTICAL	
3 177.90	45.10	-11.80	33.30	43.50	10.20	400	32	HORIZONTAL	
4 297.90	50.10	-8.58	41.52	46.40	4.88	400	206	HORIZONTAL	
5 317.38	47.50	-8.16	39.34	46.40	7.06	400	265	HORIZONTAL	
6 537.17	40.10	-4.25	35.85	46.40	10.55	100	23	VERTICAL	

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions – BT Mode


243 Jubug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel :+82-31-3236008,9  
Fax :+82-31-3236010

EUT/Model No.: SmartCompact Plus

TEST MODE: BT mode

Temp Humi : 9 / 53

Tested by: LEE.K.H



Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

### 3.2.8 AC Conducted Emissions

#### Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

#### Measurement Data: Complies

- See next pages for actual measured spectrum plots.
- No emissions were detected at a level greater than 10dB below limit.

#### Minimum Standard: FCC Part 15.207(a)/EN 55022


Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

\* Decreases with the logarithm of the frequency

AC Conducted Emissions – PC+CAM+SCAN– Line

243 Jubug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel :+82-31-3236008,9  
Fax :+82-31-3236010

EUT / Model No. : SmartCompact Plus Phase : LINE  
-----  
Test Mode : PC+CAM+SCAN mode Test Power : 120 / 60  
Temp./Humi. : 17 / 24 Test Engineer : PARK H W  
-----




Freq MHz	RD QP dBuV		RD AV dBuV		C. F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB
	QP	AV	QP	AV							
0.200	46.89	33.49	9.65	56.54	56.54	43.14	79.00	66.00	22.46	22.86	
0.397	31.16	28.56	9.67	40.83	40.83	38.23	79.00	66.00	38.17	27.77	
0.464	29.75	23.65	9.67	39.42	39.42	33.32	79.00	66.00	39.58	32.68	
0.796	28.14	28.04	9.78	37.92	37.92	37.82	73.00	60.00	35.08	22.18	
4.465	27.14	22.14	9.91	37.05	37.05	32.05	73.00	60.00	35.95	27.95	
8.860	27.88	22.28	10.08	37.96	37.96	32.36	73.00	60.00	35.04	27.64	

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

AC Conducted Emissions – PC+CAM+SCAN – Neutral

243 Jibug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel. +82-31-3236008,9  
Fax. +82-31-3236010

EUT / Model No. : SmartCompact Plus Phase : NEUTRAL  
 Test Mode : PC+CAM+SCAN mode Test Power : 120 / 60  
 Temp./Humi. : 17 / 24 Test Engineer : PARK H W




Freq MHz	RD QP dBuV	RD AV dBuV	C. F dB	Result		Limit		Margin	
				QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dB	AV dB
0.198	41.79	29.09	9.66	51.45	38.75	79.00	66.00	27.55	27.25
0.331	32.17	28.67	9.66	41.83	38.33	79.00	66.00	37.17	27.67
0.463	31.95	30.95	9.66	41.61	40.61	79.00	66.00	37.39	25.39
0.663	29.84	28.64	9.75	39.59	38.39	73.00	60.00	33.41	21.61
1.664	28.85	26.85	9.81	38.66	36.66	73.00	60.00	34.34	23.34
2.000	27.35	25.05	9.82	37.17	34.87	73.00	60.00	35.83	25.13

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

AC Conducted Emissions – BT – Line

243 Jibug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel. +82-31-3236008,9  
Fax. +82-31-3236010

EUT / Model No. : SmartCompact Plus Phase : LINE  
 Test Mode : BT mode Test Power : 120 / 60  
 Temp./Humi. : 17 / 24 Test Engineer : PARK H W




Freq MHz	RD QP	RD AV	C. F dB	Result QP	Result AV	Limit QP	Limit AV	Margin QP	Margin AV
	dBuV	dBuV		dBuV	dBuV	dBuV	dBuV	dB	dB
0.201	44.29	30.69	9.65	53.94	40.34	79.00	66.00	25.06	25.66
0.262	35.58	25.08	9.66	45.23	34.73	79.00	66.00	33.77	31.27
0.398	30.16	27.06	9.67	39.83	36.73	79.00	66.00	39.17	29.27
0.794	25.34	23.64	9.78	35.12	33.42	73.00	60.00	37.88	26.58
1.464	24.95	22.15	9.80	34.75	31.95	73.00	60.00	38.25	28.05
11.847	34.79	24.59	10.25	45.04	34.84	73.00	60.00	27.96	25.16

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

AC Conducted Emissions – BT – Neutral

243 Jibug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel. +82-31-3236008,9  
Fax. +82-31-3236010

EUT / Model No. : SmartCompact Plus Phase : NEUTRAL  
 Test Mode : BT mode Test Power : 120 / 60  
 Temp./Humi. : 17 / 24 Test Engineer : PARK H W



Freq MHz	RD QP dBuV	RD AV dBuV	C. F dB	Result		Limit		Margin	
				QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dB	AV dB
0.197	39.49	26.19	9.65	49.14	35.84	79.00	66.00	29.86	30.16
0.329	32.37	29.27	9.66	42.02	38.92	79.00	66.00	36.98	27.08
0.462	31.95	30.85	9.67	41.62	40.52	79.00	66.00	37.38	25.48
0.529	31.15	29.65	9.69	40.83	39.33	73.00	60.00	32.17	20.67
0.662	30.14	28.94	9.75	39.89	38.69	73.00	60.00	33.11	21.31
0.728	30.64	29.44	9.77	40.41	39.21	73.00	60.00	32.59	20.79

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

## APPENDIX

### TEST EQUIPMENT USED FOR TESTS

	Description	Model No.	Serial No.	Manufacturer	Next Cal. Date
1	Spectrum Analyzer	FSV-30	100757	R&S	Feb-11
2	Spectrum Analyzer	8563E	3425A02505	HP	Mar-11
3	Spectrum Analyzer	8594E	3710A04074	HP	Oct-10
4	Signal Generator	8648C	3623A02597	HP	Mar-11
5	Signal Generator	83711B	US34490456	HP	Mar-11
6	Attenuator (3dB)	8491A	37822	HP	Oct-10
7	Attenuator (10dB)	8491A	63196	HP	Oct-10
8	Attenuator (30dB)	8498A	1801A06689	HP	Oct-10
9	EMI Test Receiver	ESVD	843748/001	R&S	Mar-11
10	Horn Antenna(18 ~ 40GHz)	SAS-574	154	Schwarzbeck	Nov-10
11	Horn Antenna(18 ~ 40GHz)	SAS-574	155	Schwarzbeck	Nov-10
12	RF Amplifier	8447D	2949A02670	HP	Oct-10
13	RF Amplifier	8449B	3008A02126	HP	Mar-11
14	Test Receiver	ESHS10	828404/009	R&S	Mar-11
15	TRILOG Antenna	VULB 9160	9160-3212	SCHWARZBECK	Apr-11
16	Log.-Per. Antenna	VULP 9118	9118 A 401	SCHWARZBECK	Apr-11
17	Biconical Antenna	BBA 9106	VHA 9103-2315	SCHWARZBECK	Apr-11
18	Horn Antenna	3115	00055005	ETS LINDGREN	Mar-11
19	Horn Antenna	BBHA 9120D	9120D122	SCHWARZBECK	Dec-11
20	Dipole Antenna	VHA9103	2116	SCHWARZBECK	Nov-10
21	Dipole Antenna	VHA9103	2117	SCHWARZBECK	Nov-10
22	Dipole Antenna	VHA9105	2261	SCHWARZBECK	Nov-10
23	Dipole Antenna	VHA9105	2262	SCHWARZBECK	Nov-10
24	Hygro-Thermograph	THB-36	0041557-01	ISUZU	Mar-11
25	Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-
26	RF Switch	MP59B	6200414971	ANRITSU	-
27	Power Divider	11636A	6243	HP	Oct-10
28	DC Power Supply	6622A	3448A03079	HP	Oct-10
29	Frequency Counter	5342A	2826A12411	HP	Mar-11
30	Power Meter	EPM-441A	GB32481702	HP	Mar-11
31	Power Sensor	8481A	2702A64048	HP	Mar-11
32	Audio Analyzer	8903B	3729A18901	HP	Oct-10
33	Modulation Analyzer	8901B	3749A05878	HP	Oct-10
34	TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	Jin Young Tech	Oct-10
35	LOOP-ANTENNA	FMZB 1516	151602/94	SCHWARZBECK	Mar-11
36	Stop Watch	HS-3	601Q09R	CASIO	Mar-11
37	LISN	ENV216	100408	R&S	Oct-10
38	UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	106243	R&S	May-12