

Page 1 of 34

APPLICATION CERTIFICATION FCC Part 15C On Behalf of China Industries Ltd T/A Wow! Stuff

Sonar Copter Model No.: TX-1014

FCC ID: YCR-TX-1014H

Prepared for : China Industries Ltd T/A Wow! Stuff

Address : Creative Industries Centre, Wolverhampton Science

Park, Wolverhampton, WV10 9TG UK

Prepared by : ACCURATE TECHNOLOGY CO., LTD

Address : F1, Bldg. A, Chan Yuan New Material Port, Keyuan

Rd. Science & Industry Park, Nan Shan, Shenzhen,

Guangdong P.R. China

Tel: (0755) 26503290 Fax: (0755) 26503396

Report Number : ATE20151295
Date of Test : Jun 15-27, 2015
Date of Report : Jun 29, 2015






TABLE OF CONTENTS

Descri	Page	
Test R	Leport Certification	
1. G	ENERAL INFORMATION	4
1.1.	Description of Device (EUT)	
1.1.	Special Accessory and Auxiliary Equipment	
1.3.	Description of Test Facility	
1.4.	Measurement Uncertainty	
2. M	EASURING DEVICE AND TEST EQUIPMENT	6
	PERATION OF EUT DURING TESTING	
3.1.	Operating Mode	
3.2.	Configuration and peripherals	
	EST PROCEDURES AND RESULTS	
	DB BANDWIDTH MEASUREMENT	
5.1. 5.2.	Block Diagram of Test Setup The Requirement For Section 15.215(c)	
5.2. 5.3.	Operating Condition of EUT	
5.4.	Test Procedure	
5.5.	Test Result	
6. B	AND EDGE COMPLIANCE TEST	12
6.1.	Block Diagram of Test Setup	
6.2.	The Requirement For Section 15.249	
6.3.	EUT Configuration on Measurement	
6.4.	Operating Condition of EUT	
6.5.	Test Procedure	
6.6.	Test Result	
7. R	ADIATED SPURIOUS EMISSION TEST	
7.1.	Block Diagram of Test Setup	18
7.2.	The Limit For Section 15.249	
7.3.	Restricted bands of operation	
7.4.	Configuration of EUT on Measurement	
7.5.	Operating Condition of EUT	
7.6. 7.7.	Test Procedure The Field Strength of Radiation Emission Measurement Results	
8. Al	NTENNA REQUIREMENT	

8.1.

8.2.



Page 3 of 34

Test Report Certification

Applicant : China Industries Ltd T/A Wow! Stuff

Address : Creative Industries Centre, Wolverhampton Science Park,

Wolverhampton, WV10 9TG UK

Manufacturer: China Industries Ltd T/A Wow! Stuff

Address : Creative Industries Centre, Wolverhampton Science Park,

Wolverhampton, WV10 9TG UK

Product : Sonar Copter

Model No. : TX-1014

Trade Name: Wow! Stuff

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.249 ANSI C63.10: 2013

The EUT was tested according to FCC 47CFR 15.249 for compliance to FCC 47CFR 15.249 requirements

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.249 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test :	Jun 15-27, 2015
Date of Report:	Jun 29, 2015
Prepared by :	(Eric Zhang, Engineer)
Approved & Authorized Signer :	Lemil
	(Sean Liu. Manager)



Page 4 of 34

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT : Sonar Copter

Model Number : TX-1014

Power Supply : 6V DC (batteries $4 \times$)

Operate Frequency : 2407-2473MHz

Antenna Gain : 0dBi

Antenna type : Wire Antenna

Applicant : China Industries Ltd T/A Wow! Stuff

Address : Creative Industries Centre, Wolverhampton Science Park,

Wolverhampton, WV10 9TG UK

Manufacturer : China Industries Ltd T/A Wow! Stuff

Address : Creative Industries Centre, Wolverhampton Science Park,

Wolverhampton, WV10 9TG UK

Date of sample received: Jun 15, 2015

Date of Test : Jun 15-27, 2015

1.2. Special Accessory and Auxiliary Equipment

N/A



Page 5 of 34

1.3.Description of Test Facility

EMC Lab : Accredited by TUV Rheinland Shenzhen

Listed by FCC

The Registration Number is 752051

Listed by Industry Canada

The Registration Number is 5077A-2

Accredited by China National Accreditation Committee

for Laboratories

The Certificate Registration Number is L3193

Name of Firm : ACCURATE TECHNOLOGY CO. LTD

Site Location : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.

Science & Industry Park, Nanshan, Shenzhen, Guangdong

P.R. China

1.4. Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty = 3.08dB, k=2

(9kHz-30MHz)

Radiated emission expanded uncertainty = 4.42dB, k=2

(30MHz-1000MHz)

Radiated emission expanded uncertainty = 4.06dB, k=2

(Above 1GHz)



Report No.: ATE20151295 Page 6 of 34

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Туре	S/N	Calibrated dates	Cal. Interval
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 11, 2015	One Year
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 11, 2015	One Year
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 11, 2015	One Year
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 11, 2015	One Year
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 15, 2015	One Year
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 15, 2015	One Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 15, 2015	One Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1067	Jan. 15, 2015	One Year
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 11, 2015	One Year
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 11, 2015	One Year
Highpass Filter	Wainwright Instruments	WHKX3.6/18 G-10SS	N/A	Jan. 11, 2015	One Year
Band Reject Filter	Wainwright Instruments	WRCG2400/2 485-2375/2510 -60/11SS	N/A	Jan. 11, 2015	One Year





Page 7 of 34

3. OPERATION OF EUT DURING TESTING

3.1. Operating Mode


The mode is used: **Transmitting mode**

Low Channel: 2407MHz Middle Channel: 2440MHz High Channel: 2473MHz

3.2. Configuration and peripherals

EUT

Figure 1 Setup: Transmitting mode





4. TEST PROCEDURES AND RESULTS


FCC Rules	Description of Test	Result		
Section 15.215(c)	20dB Bandwidth	Compliant		
Section 15.249(d)	Band Edge Compliance Test	Compliant		
Section 15.205(a), Section 15.209(a), Section 15.249, Section 15.35	Radiated Spurious Emission Test	Compliant		
Section 15.207	AC Power Line Conducted Emission Test	N/A		
Section 15.203	Antenna Requirement	Compliant		





5. 20DB BANDWIDTH MEASUREMENT

5.1.Block Diagram of Test Setup



5.2. The Requirement For Section 15.215(c)

The bandwidth of a frequency hopping channel is the 20 dB emission bandwidth, measured with the hopping stopped. The system RF bandwidth is equal to the channel bandwidth multiplied by the number of channels in the hopset. The hopset shall be such that the near-term distribution of frequencies appears random, with sequential hops randomly distributed in both direction and magnitude of change in the hopset while the long-term distribution appears evenly distributed.

5.3. Operating Condition of EUT

- 5.3.1. Setup the EUT and simulator as shown as Section 5.1.
- 5.3.2. Turn on the power of all equipment.
- 5.3.3.Let the EUT work in TX modes measure it. The transmit frequency are 2402, 2433, 2475 MHz.

5.4. Test Procedure

- 5.4.1. Place the EUT on the table and set it in transmitting mode.
- 5.4.2.Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 5.4.3.Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz, Detector function=peak, Trace=max hold, Sweep=auto.
- 5.4.4.Set the measured low, middle and high frequency and test 20dB bandwidth with spectrum analyzer.




5.5.Test Result

Channel	Frequency(MHz)	20 dB Bandwidth(MHz)
Low	2407	1.216
Middle	2440	1.548
High	2473	1.838

The spectrum analyzer plots are attached as below.


Low channel



Date: 24.JUN.2015 10:31:56




Middle channel



Date: 24.JUN.2015 10:22:46

High channel



Date: 24.JUN.2015 10:45:23


Page 12 of 34



6. BAND EDGE COMPLIANCE TEST

6.1.Block Diagram of Test Setup

ANTENNA ELEVATION VARIES FROM 1 TO 4 METERS



6.2. The Requirement For Section 15.249

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph A8.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

6.3.EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.



Page 13 of 34

6.4. Operating Condition of EUT

- 6.4.1. Setup the EUT and simulator as shown as Section 6.1.
- 6.4.2. Turn on the power of all equipment.
- 6.4.3.Let the EUT work in TX modes measure it. The transmit frequency are 2402, 2475 MHz..

6.5. Test Procedure

Radiate Band Edge:

- 6.5.1. The EUT is placed on a turntable, which is 1.5m above the ground plane and worked at highest radiated power.
- 6.5.2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
- 6.5.3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
- 6.5.4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:

RBW=1MHz, VBW=1MHz

6.5.5. The band edges was measured and recorded.

6.6.Test Result





F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park,Nanshan Shenzhen,P.R.China Site: 1# Chamber Tel:+86-0755-26503290

Fax:+86-0755-26503396

Report No.: ATE20151295

Page 14 of 34

Job No.: STAR2015 #1035 Polarization: Horizontal Standard: FCC PK Power Source: DC 6V

Test item: Radiation Test Date: 15/06/27/
Temp.(C)/Hum.(%) 25 C / 55 %

Time: 8/41/28


EUT: Sonar Copter Engineer Signature:

Mode: TX 2407MHz Distance: 3m

Model: TX-1014

Manufacturer: Industries

Note: Report No.:ATE20151295



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	50.43	-8.00	42.43	74.00	-31.57	peak			
2	2390.000	39.14	-8.00	31.14	54.00	-22.86	AVG			
3	2400.000	52.22	-7.97	44.25	74.00	-29.75	peak			
4	2400.000	41.86	-7.97	33.89	54.00	-20.11	AVG			



F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park,Nanshan Shenzhen,P.R.China Site: 1# Chamber Tel:+86-0755-26503290 Fax:+86-0755-26503396

Report No.: ATE20151295

Page 15 of 34

Job No.: STAR2015 #1036

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Sonar Copter

Mode: TX 2407MHz

Model: TX-1014

Manufacturer: Industries


Note: Report No.:ATE20151295

Polarization: Vertical

Power Source: DC 6V

Date: 15/06/27/ Time: 8/42/24

Engineer Signature: Distance: 3m



3.0									And the state of t				
No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark			
1	2390.000	49.42	-8.00	41.42	74.00	-32.58	peak						
2	2390.000	38.16	-8.00	30.16	54.00	-23.84	AVG		×.				
3	2400.000	60.50	-7.97	52.53	74.00	-21.47	peak						
4	2400.000	48.67	-7.97	40.70	54.00	-13.30	AVG						



F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park,Nanshan Shenzhen,P.R.China Page 16 of 34

Site: 1# Chamber
Tel:+86-0755-26503290

Fax:+86-0755-26503396

Report No.: ATE20151295

Job No.: STAR2015 #1037 Polarization: Vertical Standard: FCC PK Power Source: DC 6V

Test item: Radiation Test Date: 15/06/27/
Temp.(C)/Hum.(%) 25 C / 55 %
Time: 8/44/45

Temp.(C)/Hum.(%) 25 C / 55 % Time: 8/44/45


EUT: Sonar Copter Engineer Signature:

Mode: TX 2473MHz Distance: 3m

Model: TX-1014

Note: Report No.:ATE20151295

Manufacturer: Industries



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	48.84	-7.76	41.08	74.00	-32.92	peak			
2	2483.500	37.66	-7.76	29.90	54.00	-24.10	AVG		1	
3	2500.000	41.77	-7.71	34.06	74.00	-39.94	peak		1	
4	2500.000	30.20	-7.71	22.49	54.00	-31.51	AVG		-	



F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park,Nanshan Shenzhen,P.R.China Site: 1# Chamber Tel:+86-0755-26503290 Fax:+86-0755-26503396

Report No.: ATE20151295

Page 17 of 34

Job No.: STAR2015 #1038 Polarization: Horizontal Standard: FCC PK Power Source: DC 6V

Test item: Radiation Test Power Source: DC 07

Date: 15/06/27/

Temp.(C)/Hum.(%) 25 C / 55 % Time: 8/46/44

EUT: Sonar Copter Engineer Signature:

Mode: TX 2473MHz Distance: 3m

Mode: TX 2473MHz

Model: TX-1014

Manufacturer: Industries

Note: Report No.:ATE20151295

No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	48.46	-7.76	40.70	74.00	-33.30	peak			
2	2483.500	37.64	-7.76	29.88	54.00	-24.12	AVG			
3	2500.000	43.34	-7.71	35.63	74.00	-38.37	peak			
4	2500.000	32.07	-7.71	24.36	54.00	-29.64	AVG			

Note:

- 1. Emissions attenuated more than 20 dB below the permissible value are not reported.
- 2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

- 3. Display the measurement of peak values.
- 4. The average measurement was not performed when peak measured data under the limit of average detection.



7. RADIATED SPURIOUS EMISSION TEST

7.1.Block Diagram of Test Setup


7.1.1.Block diagram of connection between the EUT and peripherals



Setup: Transmitting mode

(EUT: TX-1014)

7.1.2.Semi-Anechoic Chamber Test Setup Diagram



Cable CROUND PLANE

GROUND PLANE



Report No.: ATE20151295 Page 19 of 34

7.2. The Limit For Section 15.249

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph A8.4(4), the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

7.3. Restricted bands of operation

7.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

perii	permitted in any of the frequency bands listed below:											
MHz	MHz	MHz	GHz									
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15									
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46									
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75									
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5									
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2									
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5									
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7									
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4									
6.31175-6.31225	123-138	2200-2300	14.47-14.5									
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2									
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4									
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12									
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0									
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8									
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5									
12.57675-12.57725	322-335.4	3600-4400	$\binom{2}{}$									
13.36-13.41												

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section

²Above 38.6



15.35 apply to these measurements.

Report No.: ATE20151295 Page 20 of 34

7.4. Configuration of EUT on Measurement

The equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.5. Operating Condition of EUT

- 7.5.1. Setup the EUT and simulator as shown as Section 7.1.
- 7.5.2. Turn on the power of all equipment.
- 7.5.3.Let the EUT work in TX modes measure it. The transmit frequency are 2402, 2433, 2475MHz.

7.6.Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter(Below 1GHz) and 1.5m(above 1GHz) high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10: 2013 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The bandwidth of test receiver is set at 9 kHz in below 30MHz. and set at 120 kHz in 30-1000MHz, and 1MHz in above 1000MHz.

The frequency range from 9 kHz to 25GHz is checked.

The final measurement in band 9-90 kHz, 110-490 kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

RBW (120 kHz), VBW (300 kHz) for QP detector below 1GHz

Peak detector above 1GHz

RBW (1 MHz), VBW (3MHz) for Peak measurement

RBW (1 MHz), VBW (10Hz) for AV measurement

The field strength is calculated by adding the antenna factor, and cable loss, and subtracting the amplifier gain from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

Where Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain



Page 21 of 34

7.7. The Field Strength of Radiation Emission Measurement Results **PASS.**

Fundamental Radiated Emissions

Frequency	Reading(dBμV/m)	Factor(dB)	Result(dBµV/m)		Limit(dBµV/m)		Margin(dB)		Polarization
(MHz)	AV	PEAK	Corr.	AV	PEAK	AV	PEAK	AV	PEAK	
2407.00	78.69	86.62	-7.96	70.73	78.66	94.00	114.00	-23.27	-35.34	Vertical
2407.00	80.11	87.16	-7.96	72.15	79.20	94.00	114.00	-21.85	-34.80	Horizontal
2440.00	82.62	90.06	-7.87	74.75	82.19	94.00	114.00	-19.25	-31.81	Vertical
2440.00	81.37	89.87	-7.87	73.50	82.00	94.00	114.00	-20.50	-32.00	Horizontal
2473.00	78.66	86.73	-7.78	70.88	78.95	94.00	114.00	-23.12	-35.05	Vertical
2473.00	81.22	88.17	-7.78	73.44	80.39	94.00	114.00	-20.56	-33.61	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.

- 2. *: Denotes restricted band of operation.
- 3. The EUT is tested radiation emission in three axes. The worst emissions are reported in all channels.
- 4. The radiation emissions from 18-25GHz are not reported, because the test values lower than the limits of 20dB.
- 5. The average measurement was not performed when peak measured data under the limit of average detection.
- 6. The 18-25GHz emissions are not reported, because the levels are too low against the limit





F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park,Nanshan Shenzhen,P.R.China Site: 1# Chamber Tel:+86-0755-26503290 Fax:+86-0755-26503396

Report No.: ATE20151295

Page 22 of 34

Job No.: STAR2015 #923

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Sonar Copter
Mode: TX 2407MHz
Model: TX-1014
Manufacturer: Industries


Polarization: Vertical

Power Source: DC 6V

Date: 2015/06/24 Time: 19:44:37 Engineer Signature:

Distance: 3m

Note: Report No.:ATE20151295





F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park, Nanshan Shenzhen, P.R. China Report No.: ATE20151295 Page 23 of 34 Site: 1# Chamber

Tel:+86-0755-26503290 Fax:+86-0755-26503396

Job No.: STAR2015 #924 Polarization: Horizontal Standard: FCC Class B 3M Radiated Power Source: DC 6V

Date: 2015/06/24 Time: 19:45:17 Engineer Signature: Distance: 3m


EUT: Sonar Copter Mode: TX 2407MHz Model: TX-1014

Test item: Radiation Test

Manufacturer: Industries

Note: Report No.:ATE20151295

Temp.(C)/Hum.(%) 25 C / 55 %



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	39.3203	37.14	-18.88	18.26	40.00	-21.74	QP			



F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park, Nanshan Shenzhen, P.R. China

Page 24 of 34 Site: 1# Chamber

Tel:+86-0755-26503290 Fax:+86-0755-26503396

Report No.: ATE20151295

Job No.: STAR2015 #925 Polarization: Standard: FCC Class B 3M Radiated


Test item: Radiation Test Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Sonar Copter Mode: TX 2440MHz Model: TX-1014 Manufacturer: Industries

Note: Report No.:ATE20151295

Horizontal Power Source: DC 6V Date: 2015/06/24

Time: 19:45:52 Engineer Signature: Distance: 3m







F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park,Nanshan Shenzhen,P.R.China Site: 1# Chamber Tel:+86-0755-26503290 Fax:+86-0755-26503396

Report No.: ATE20151295

Page 25 of 34

Job No.: STAR2015 #926 Polarization
Standard: FCC Class B 3M Radiated Power Soul

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

Mode: TX 2440MHz

Model: TX-1014


Manufacturer: Industries

EUT: Sonar Copter

Note: Report No.:ATE20151295

Polarization: Vertical Power Source: DC 6V

Date: 2015/06/24 Time: 19:46:23 Engineer Signature: Distance: 3m







F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park, Nanshan Shenzhen, P.R. China

Site: 1# Chamber Tel:+86-0755-26503290 Fax:+86-0755-26503396

Report No.: ATE20151295

Page 26 of 34

Job No.: STAR2015 #927 Polarization: Standard: FCC Class B 3M Radiated

Test item: Radiation Test


Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Sonar Copter Mode: TX 2473MHz Model: TX-1014 Manufacturer: Industries

Vertical Power Source: DC 6V

Date: 2015/06/24 Time: 19:47:02 Engineer Signature: Distance: 3m

Note: Report No.:ATE20151295





F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park, Nanshan Shenzhen, P.R. China

Site: 1# Chamber Tel:+86-0755-26503290 Fax:+86-0755-26503396

Report No.: ATE20151295


Page 27 of 34

Job No.: STAR2015 #928 Polarization: Horizontal Standard: FCC Class B 3M Radiated Power Source: DC 6V

Test item: Radiation Test Date: 2015/06/24 Temp.(C)/Hum.(%) 25 C / 55 % Time: 19:47:30 EUT: Sonar Copter Engineer Signature: Distance: 3m

Mode: TX 2473MHz Model: TX-1014 Manufacturer: Industries

Note: Report No.:ATE20151295







F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park,Nanshan Shenzhen,P.R.China Site: 1# Chamber Tel:+86-0755-26503290 Fax:+86-0755-26503396

Report No.: ATE20151295

Page 28 of 34

Job No.: STAR2015 #989 Polarization: Vertical Standard: FCC Class B 3M Radiated Power Source: DC 6V


Date: 2015/06/24
Time: 21:11:45
Engineer Signature:
Distance: 3m

EUT: Sonar Copter
Mode: TX 2407MHz
Model: TX-1014
Manufacturer: Industries

Test item: Radiation Test

Note: Report No.:ATE20151295

Temp.(C)/Hum.(%) 25 C / 55 %



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark	
1	2407.000	85.33	-7.96	77.37	114.00	36.63	peak				
2	2407.000	78.63	-7.96	70.67	94.00	23.33	AVG				



Page 29 of 34 Site: 1# Chamber

Report No.: ATE20151295

F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park, Nanshan Shenzhen, P.R. China Tel:+86-0755-26503290 Fax:+86-0755-26503396

Job No.: STAR2015 #990

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %


EUT: Sonar Copter Mode: TX 2407MHz Model: TX-1014

Note: Report No.:ATE20151295

Manufacturer: Industries

Horizontal Polarization: Power Source: DC 6V

Date: 2015/06/24 Time: 21:12:48 Engineer Signature: Distance: 3m



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2407.000	87.99	-7.96	80.03	114.00	33.97	peak			
2	2407.000	80.22	-7.96	72.26	94.00	21.74	AVG			





F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park,Nanshan Shenzhen,P.R.China Site: 1# Chamber Tel:+86-0755-26503290 Fax:+86-0755-26503396

Report No.: ATE20151295

Page 30 of 34

Job No.: STAR2015 #991 Polarization: Horizontal Standard: FCC Class B 3M Radiated Power Source: DC 6V Test item: Radiation Test Date: 2015/06/24

Date: 2015/06/24
Time: 21:14:40
Engineer Signature:
Distance: 3m

EUT: Sonar Copter


Mode: TX 2440MHz

Model: TX-1014

Manufacturer: Industries

Note: Report No.:ATE20151295

Temp.(C)/Hum.(%) 25 C / 55 %



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2440.000	85.16	-7.87	77.29	114.00	36.71	peak			
2	2440.000	77.44	-7.87	69.57	94.00	24.43	AVG			





F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park,Nanshan Shenzhen,P.R.China Site: 1# Chamber Tel:+86-0755-26503290 Fax:+86-0755-26503396

Report No.: ATE20151295

Page 31 of 34

Job No.: STAR2015 #992

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %


EUT: Sonar Copter
Mode: TX 2440MHz
Model: TX-1014
Manufacturer: Industries

viariaractarer. Iridastries

Note: Report No.:ATE20151295

Polarization: Vertical Power Source: DC 6V

Date: 2015/06/24 Time: 21:15:30 Engineer Signature: Distance: 3m



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2440.000	88.83	-7.87	80.96	114.00	33.04	peak			
2	2440.000	80.75	-7.87	72.88	94.00	21.12	AVG			





F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park,Nanshan Shenzhen,P.R.China Site: 1# Chamber Tel:+86-0755-26503290 Fax:+86-0755-26503396

Report No.: ATE20151295

Page 32 of 34

Job No.: STAR2015 #993 Polarization: Vertical Standard: FCC Class B 3M Radiated Power Source: DC 6V

Test item: Radiation Test

Date: 2015/06/24

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Sonar Copter

Mode: TX 2473MHz

Date: 2015/06/24

Time: 21:17:01

Engineer Signature:


Distance: 3m

Mode: TX 2473MHz

Model: TX-1014

Manufacturer: Industries

Note: Report No.:ATE20151295



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2473.000	89.90	-7.78	82.12	114.00	31.88	peak			
2	2473.000	81.58	-7.78	73.80	94.00	20.20	AVG			



F1,Bldg,A,Changyuan New Material Port Keyuan Rd, Science & Industry Park,Nanshan Shenzhen,P.R.China Site: 1# Chamber Tel:+86-0755-26503290 Fax:+86-0755-26503396

Horizontal

Report No.: ATE20151295

Page 33 of 34

Job No.: STAR2015 #994 Polarization:
Standard: FCC Class B 3M Radiated Power Source

Standard: FCC Class B 3M Radiated Power Source: DC 6V
Test item: Radiation Test Date: 2015/06/24

Temp.(C)/Hum.(%) 25 C / 55 %


EUT: Sonar Copter Engineer Signature:

Mode: TX 2473MHz

Distance: 3m

Model: TX-1014
Manufacturer: Industries

Note: Report No.:ATE20151295



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2473.000	92.21	-7.78	84.43	114.00	29.57	peak			
2	2473.000	85.69	-7.78	77.91	94.00	16.09	AVG			




8. ANTENNA REQUIREMENT

8.1. The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2. Antenna Construction

Device is equipped with unique antenna, which isn't displaced by other antenna. Therefore, the equipment complies with the antenna requirement of Section 15.203.



Antenna