

Certification Exhibit

FCC ID: YCW-6098 IC: 8950A-6098

FCC Rule Part: 15.247
IC Radio Standards Specification: RSS-210

ACS Report Number: 10-0163.W06.11.A

Manufacturer: Crane Merchandising Systems Inc

Model: CR0006098

RF Exposure

Model: CR0006098 FCC ID: YCW-6098 IC: 8950A-6098

General Information:

Applicant: Crane Merchandising Systems Inc.

ACS Project: 10-0163
Device Category: Mobile

Environment: General Population/Uncontrolled Exposure

Technical Information:

Antenna Type: 1/4 wave monopole

Antenna Gain: 2 dBi

Maximum Transmitter Conducted Power: 20.80 Maximum System EIRP: 22.80 dBm, 190.5 mW Exposure Conditions: Greater than 20 centimeters

MPE Calculation

The Power Density (mW/cm²) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

MPE Calculator for Mobile Equipment							
Limits for General Population/Uncontrolled Exposure*							
Transmit Frequency	Radio Power	Power Density Limit	Radio Power	Antenna Gain	Antenna Gain	Distance	Power Density
(MHz)	(dBm)	(mW/Cm2)	(mW)	(dBi)	(mW eq.)	(cm)	(mW/cm^2)
2405	20.8	1.00	120.23	2	1.585	20	0.038

Installation Guidelines

The installation manual should contain text similar to the following advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

RF Exposure

In accordance with FCC requirements of human exposure to radio frequency fields, the radiating element shall be installed such that a minimum separation distance of 20 centimeters will be maintained.

Conclusion

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure and the general population.