

Co-location Report

1 TEST RESULT

1.1 Radiated Emissions Measurement

1.1.1 Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

1.1.2 Measuring Instruments and Setting

Please refer to section 2 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

1.1.3 Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

1.1.4 Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

1.1.5 Test Deviation

There is no deviation with the original standard.

1.1.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

1.1.7 Results of Radiated Emissions (9kHz~30MHz)

Final Test Date	May 19, 2010	Test Site No.	03CH03-HY
Temperature	27.9	Humidity	56%
Test Engineer	Eddie		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:


The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.


1.1.8 Results of Radiated Emissions (30MHz~1GHz)

Final Test Date	May 31, 2010	Test Site No.	03CH03-HY
Temperature	27.9	Humidity	56%
Test Engineer	Eddie	Configuration	WLAN 2.4G & Bluetooth

Horizontal

Freq	Level	Over Limit		Read Line	Antenna Factor	Cable Loss	Preamp Factor	Table Pos	Table Pos	Remark
		MHz	dBuV/m	dB	dBuV/m					
1	137.670	26.14	-17.36	43.50	40.24	11.64	2.02	27.76	---	--- Peak
2	272.500	28.43	-17.57	46.00	40.24	13.40	2.89	28.10	---	--- Peak
3	326.820	31.31	-14.69	46.00	41.87	14.49	3.19	28.23	---	--- Peak
4	382.110	35.34	-10.66	46.00	44.85	15.85	3.39	28.75	---	--- Peak
5	625.580	35.10	-10.90	46.00	40.58	19.47	4.60	29.55	---	--- Peak
6	800.180	33.00	-13.00	46.00	36.64	20.75	5.08	29.47	---	--- Peak

Vertical



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table		
		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	Pos	Pos
1 3	30.000	35.53	-4.47	40.00	44.74	18.48	0.73	28.42	---	---	Peak
2	125.060	29.41	-14.09	43.50	42.70	12.49	1.93	27.72	---	---	Peak
3 3	382.110	36.96	-9.04	46.00	46.47	15.85	3.39	28.75	---	---	Peak
4 3	490.750	38.69	-7.31	46.00	45.79	18.02	3.87	28.99	---	---	Peak
5 3	625.580	40.46	-5.54	46.00	45.94	19.47	4.60	29.55	---	---	Peak
6	762.350	35.27	-10.73	46.00	39.49	20.73	4.95	29.89	---	---	Peak


Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Final Test Date	May 31, 2010	Test Site No.	03CH03-HY
Temperature	27.9	Humidity	56%
Test Engineer	Eddie	Configuration	WLAN 5G & Bluetooth

Horizontal

Freq	Level	Over Limit	Limit Line	Read		Ant	Table			
				Antenna Factor	Cable Loss			Pos	Pos	Remark
107.600	21.74	-21.76	43.50	35.50	12.16	1.75	27.66	---	---	Peak
137.670	25.89	-17.61	43.50	39.99	11.64	2.02	27.76	---	---	Peak
272.500	31.36	-14.64	46.00	43.17	13.40	2.89	28.10	---	---	Peak
381.140	32.91	-13.09	46.00	42.43	15.81	3.39	28.72	---	---	Peak
625.580	35.94	-10.06	46.00	41.42	19.47	4.60	29.55	---	---	Peak
824.430	33.19	-12.81	46.00	36.48	20.79	5.20	29.29	---	---	Peak

Vertical



Freq	Level	Over Limit	Limit Line	Read	Antenna	Cable	Preamp	Ant	Table		
									Pos	Pos	Remark
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg		
1 @	30.000	35.43	-4.57	40.00	44.64	18.48	0.73	28.42	---	---	Peak
2	125.060	28.59	-14.91	43.50	41.88	12.49	1.93	27.72	---	---	Peak
3	382.110	35.01	-10.99	46.00	44.52	15.85	3.39	28.75	---	---	Peak
4 @	489.780	39.77	-6.23	46.00	46.87	18.02	3.86	28.98	---	---	Peak
5 @	625.580	40.28	-5.72	46.00	45.76	19.47	4.60	29.55	---	---	Peak
6	800.180	33.20	-12.80	46.00	36.84	20.75	5.08	29.47	---	---	Peak

Note:


The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

1.1.9 Results for Radiated Emissions (1GHz~10th Harmonic)


Final Test Date	May 31, 2010	Test Site No.	03CH03-HY
Temperature	27.9	Humidity	56%
Test Engineer	Eddie	Configuration	WLAN 2.4G & Bluetooth

Horizontal

Freq	Level	Over Limit		Read		Ant	Table		
		Line	Limit	Antenna	Factor			Pos	Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	3216.000	45.53		44.49	30.51	2.91	32.37	---	--- PEAK
2	4804.000	46.79	-7.21	54.00	43.32	33.02	2.70	32.25	--- PK
3	4824.000	46.43	-7.57	54.00	42.96	33.06	2.70	32.28	--- PK
4	6432.000	53.80		47.38	34.19	4.15	31.91	---	--- PEAK
5	7202.000	48.30		41.07	35.46	4.50	32.73	---	--- PEAK
6	7236.000	59.87		52.40	35.53	4.55	32.61	---	--- PEAK
7	9612.000	54.12		42.75	38.34	5.29	32.27	---	--- PEAK
8	9648.000	54.73		43.28	38.41	5.32	32.28	---	--- PEAK

Note: Items 1 and 4~8 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.

Vertical



Freq	Level	Over Limit		ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark	
		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	3216.000	48.67			47.62	30.51	2.91	32.37	---	---	PEAK
2 @	4804.000	46.86	-7.14	54.00	43.40	33.02	2.70	32.25	---	---	PK
3	4824.000	52.53	-21.47	74.00	49.05	33.06	2.70	32.28	---	---	PEAK
4	4824.000	42.45	-11.55	54.00	38.98	33.06	2.70	32.28	---	---	Average
5	6432.000	49.11			42.68	34.19	4.15	31.91	---	---	PEAK
6	7202.000	49.25			42.03	35.46	4.50	32.73	---	---	PEAK
7	7232.000	60.52			53.11	35.53	4.55	32.67	---	---	PEAK
8	9604.000	54.08			42.74	38.31	5.29	32.26	---	---	PEAK
9	9648.000	54.66			43.21	38.41	5.32	32.28	---	---	PEAK


Note: Items 1 and 5~9 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


Final Test Date	May 31, 2010	Test Site No.	03CH03-HY
Temperature	27.9	Humidity	56%
Test Engineer	Eddie	Configuration	WLAN 5G & Bluetooth

Horizontal

Freq	Level	Over Limit		Read Line	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
		MHz	dBuV/m	dB	dBuV/m					
1	4804.000	48.34	-15.20	63.54	44.13	33.77	2.70	32.25	---	--- PK
2	7202.000	50.42			42.17	36.47	4.50	32.73	---	--- PEAK
3	8504.000	54.00			42.46	38.20	5.37	32.03	---	--- PEAK
4	9610.000	54.16			42.31	38.83	5.29	32.27	---	--- PEAK
5	11008.000	61.81	-21.73	83.54	48.41	39.22	6.23	32.05	---	--- PEAK
6	11008.000	48.78	-14.76	63.54	35.37	39.22	6.23	32.05	---	--- Average
7	16502.000	60.66			45.79	38.50	7.60	31.23	---	--- PEAK

Note: Items 2, 3, 4 and 7 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.

Vertical



Spectrum	Measurement Parameters										Ant	Table
	Freq	Level	Over Limit	Line	Read	Antenna	Cable	Preamp	Ant	Table		
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg		
1	4804.000	48.83	-14.71	63.54	44.62	33.77	2.70	32.25	---	---	PK	
2	7202.000	49.71			41.46	36.47	4.50	32.73	---	---	PEAK	
3	8300.000	53.10	-24.74	77.84	41.92	37.95	5.34	32.11	---	---	PK	
4	9608.000	54.44			42.60	38.83	5.29	32.27	---	---	PEAK	
5	11000.000	59.83	-3.71	63.54	46.45	39.20	6.23	32.05	---	---	PK	
6	16500.000	60.17			45.30	38.50	7.60	31.23	---	---	PEAK	

Note: Items 2, 4 and 6 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

2 LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 07, 2009	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan. 24, 2010	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	Jul. 21, 2009	Radiation (03CH01-HY)
Spectrum Analyzer	R&S	FSP40	100004	9 kHz - 40 GHz	Oct. 03, 2009	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz - 1 GHz	Sep. 26, 2009	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	May. 20, 2010	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jan. 11, 2010	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Jan. 05, 2010	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Jan. 05, 2010	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 - 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	Jul. 28, 2008*	Radiation (03CH03-HY)

Note: Calibration Interval of instruments listed above is one year.

3 TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085