

# Approval Sheet

Customer : 美商定誼

Project Name : DT302RP\_V2\_Trimble

Customer P/N : 27-302-720007

P/N : AJ6F1J-W0001

Product Description : Wifi Aux antenna  
MHF-4 / RF1.13\_260mm\_White

Issue Date : 2023 / 10 / 06

Reversion : A

| Customer<br>Approved | Anjie<br>Approved |
|----------------------|-------------------|
|                      |                   |

Taiwan Anjie Electronics Co.,Ltd  
Address : 1F, No.236,Sec 3, Huan-Bei Rd., Ju-Bei City  
Hsin-Chu Country, 30265, Taiwan  
Tel : +886-3-5543399 Fax : +886-3-5533062

台灣安潔電子股份有限公司  
地址：新竹縣竹北市環北路三段236號1樓  
電話：+886-3-5543399 傳真：+886-3-5543062  
Website: www.anjietw.com

# Content

1. Specification
2. S Parameter Test
  - 2.1 S.W.R. Test Data
3. Antenna Gain Test
  - 3.1 Antenna Radiation Pattern
  - 3.2 Gain and Efficiency Test Data
4. Mechanical Drawing / Dimension / Layout

## 1. Specification

- . Product Number: AJ6F1J-W0001
- . Version : 1.0
- . Model Name : DT302RP\_V2\_Trimble

## Electrical Characteristics

- . Frequency (MHz) : 2400-2500MHz / 5150-7125MHz
- . S.W.R. :  $\leq$  2.0 / 3.0
- . Efficiency (dB): > -6/ -5
- . Peak Gain : 0.8 / 2.5 dBi
- . Impedance : 50 ohm
- . Polarization : Linear

## Mechanical Characteristics

- . Material : FPC
- . Cable : RF 1.13
- . Connector : MHF-4
- . Color : White
- . Material : RoHS 2011/65/EU

with IEC 62321:2008 Method

## Environmental Condition







- . Operation Temperature : -30 ~ +60 °C
- . Storage Temperature : -40 ~ +85 °C

## 2.1 S Parameter Test S.W.R. Test Data



### 3. Antenna Gain Test

#### 3.1 Antenna Radiation Pattern



### 3. Antenna Gain Test

#### 3.2 Gain and Efficiency Test Data

| Frequency Band<br>(MHz) |      | Efficiency (dB) | Peak Gain (dBi) |
|-------------------------|------|-----------------|-----------------|
|                         |      |                 |                 |
| 802.11b/g/n             | 2400 | -5.9            | -0.9            |
|                         | 2450 | -5.8            | -0.8            |
|                         | 2500 | -5.7            | -0.8            |
|                         |      |                 |                 |
| WiFi 6<br>802.11a/ac/ax | 5150 | -4.6            | 1.2             |
|                         | 5250 | -4.4            | 1.8             |
|                         | 5350 | -4.9            | 1.2             |
|                         | 5470 | -5.0            | 1.2             |
|                         | 5600 | -4.7            | 1.0             |
|                         | 5725 | -3.8            | 2.3             |
|                         | 5785 | -3.8            | 2.4             |
|                         | 5800 | -3.9            | 2.5             |
|                         | 5850 | -4.1            | 2.4             |
|                         |      |                 |                 |
| WiFi 6E<br>802.11ac/ax  | 5925 | -4.3            | 2.3             |
|                         | 6175 | -5.0            | 1.6             |
|                         | 6425 | -4.8            | 0.3             |
|                         | 6525 | -4.4            | 0.5             |
|                         | 6700 | -4.8            | 0.4             |
|                         | 6875 | -4.5            | 0.6             |
|                         | 7000 | -4.5            | 0.7             |
|                         | 7125 | -4.8            | 0.5             |

# 4. Mechanical Drawing / Dimension / Layout

