



# DYNAMIC FREQUENCY SELECTION

## DFS Test Report

**APPLICANT** : DT Research Inc.  
**EQUIPMENT** : WLAN Module  
**BRAND NAME** : DT Research Inc.  
**MODEL NAME** : 600B  
**FCC ID** : YE3600B  
**STANDARD** : FCC Part 15 Subpart E  
**CLASSIFICATION** : (NII) Unlicensed National Information Infrastructure

The product was received on Dec. 15, 2012 and completely tested on Dec. 25, 2012. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

Jones Tsai / Manager



**SPORTON INTERNATIONAL INC.**  
No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



## TABLE OF CONTENTS

<b>REVISION HISTORY.....</b>	<b>3</b>
<b>SUMMARY OF DYNAMIC FREQUENCY SELECTION TEST.....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION.....</b>	<b>5</b>
1.1    Applicant .....	5
1.2    Manufacturer.....	5
1.3    Feature of Equipment Under Test .....	5
1.4    Product Specification of Equipment Under Test.....	6
1.5    Testing Site .....	8
1.6    Applied Standards .....	8
1.7    Support Unit used in test configuration and system .....	8
<b>2 REQUIREMENTS AND PARAMETERS FOR DFS TEST.....</b>	<b>9</b>
2.1    Applicability of DFS Requirements .....	9
2.2    Interference Threshold values, Master or Client incorporating In-Service Monitoring .....	10
2.3    DFS Response requirement values.....	11
2.4    Short Pulse Radar Test Waveforms .....	12
<b>3 CALIBRATION SETUP AND DFS TEST RESULTS.....</b>	<b>13</b>
3.1    Calibration of Radar Waveform .....	13
3.2    In-Service Monitoring: Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period.....	16
<b>4 LIST OF MEASURING EQUIPMENT.....</b>	<b>25</b>
<b>APPENDIX A. PHOTOGRAPHS OF EUT</b>	
<b>APPENDIX B. SETUP PHOTOGRAPHS</b>	



## REVISION HISTORY



## SUMMARY OF DYNAMIC FREQUENCY SELECTION TEST

UNII	Bandwidth and Channel	Description	Measured	Limit	Result
UNII Band 2 5250-5350MHz	20MHz (CH60) 5300MHz	Channel Move Time	1.23 sec	10 sec	Pass
		Channel Closing Transmission time	<200ms + 40.8 ms (aggregate)	200 ms + aggregate of 60 ms over remaining 10 s period	Pass
		Non-Occupancy Period and Client Beacon Test	No transmission or Beacons occurred	30 minutes	Pass
	40MHz (CH62) 5310MHz	Channel Move Time	0.42 sec	10 sec	Pass
		Channel Closing Transmission time	<200ms + 31.2 ms (aggregate)	200 ms + aggregate of 60 ms over remaining 10 s period	Pass
		Non-Occupancy Period and Client Beacon Test	No transmission or Beacons occurred	30 minutes	Pass
UNII Band 3 5470-5725MHz	20MHz (CH100) 5500MHz	Channel Move Time	1.58 sec	10 sec	Pass
		Channel Closing Transmission time	<200ms + 44.4 ms (aggregate)	200 ms + aggregate of 60 ms over remaining 10 s period	Pass
		Non-Occupancy Period and Client Beacon Test	No transmission or Beacons occurred	30 minutes	Pass
	40MHz (CH110) 5550MHz	Channel Move Time	1.11 sec	10 sec	Pass
		Channel Closing Transmission time	<200ms + 44.4 ms (aggregate)	200 ms + aggregate of 60 ms over remaining 10 s period	Pass
		Non-Occupancy Period and Client Beacon Test	No transmission or Beacons occurred	30 minutes	Pass

Note: Since the product is client without radar detection function, only Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period Test are required to be performed according to KDB 848637.



## 1 General Description

### 1.1 Applicant

**DT Research Inc.**

6F, NO .1, NingPo E. St., Taipei, 100 Taiwan, R.O.C.

### 1.2 Manufacturer

**DT Research Inc.**

6F, NO .1, NingPo E. St., Taipei, 100 Taiwan, R.O.C.

### 1.3 Feature of Equipment Under Test

<b>Product Feature</b>	
<b>Equipment</b>	WLAN Module
<b>Brand Name</b>	DT Research Inc.
<b>Model Name</b>	600B
<b>FCC ID</b>	YE3600B
<b>Installed into Mobile POS Tablet</b>	Brand Name: DT Research Inc. Model Name: DT395 FCC ID: YE3800A
<b>EUT supports Radios application</b>	CDMA WLAN 11abgn / Bluetooth 2.1/3.0/4.0
<b>EUT Stage</b>	Production Unit

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



## 1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
<b>DFS Function</b>	Client without radar detection function
<b>Tx/Rx Channel Frequency Range</b>	5260 MHz ~ 5320 MHz 5500 MHz ~ 5700 MHz
<b>Maximum Output Power</b>	<b>&lt;5260 MHz ~ 5320 MHz&gt;</b> 802.11a : 16.30 dBm / 0.0427 W <for Ant 1> 802.11a : 15.90 dBm / 0.0389 W <for Ant 2> 802.11n HT20 : 16.57 dBm / 0.0454 W <for Ant 1> 802.11n HT20 : 15.65 dBm / 0.0367 W <for Ant 2> 802.11n HT20 : 15.97 dBm / 0.0395 W <for Ant 1+2> 802.11n HT40 : 16.02 dBm / 0.0400 W <for Ant 1> 802.11n HT40 : 15.16 dBm / 0.0328 W <for Ant 2> 802.11n HT40 : 15.51 dBm / 0.0356 W <for Ant 1+2> <b>&lt;5500 MHz ~ 5700 MHz &gt;</b> 802.11a : 16.46 dBm / 0.0443 W <for Ant 1> 802.11a : 15.67 dBm / 0.0369 W <for Ant 2> 802.11n HT20 : 16.50 dBm / 0.0447 W <for Ant 1> 802.11n HT20 : 15.69 dBm / 0.0371 W <for Ant 2> 802.11n HT20 : 15.92 dBm / 0.0391 W <for Ant 1+2> 802.11n HT40 : 16.47 dBm / 0.0444 W <for Ant 1> 802.11n HT40 : 15.78 dBm / 0.0378 W <for Ant 2> 802.11n HT40 : 16.19 dBm / 0.0416 W <for Ant 1+2>
<b>EUT support WLAN function</b>	<b>&lt;5260 MHz ~ 5320 MHz&gt;</b> 802.11a 802.11n HT20 802.11n HT40 <b>&lt;5500 MHz ~ 5700 MHz &gt;</b> 802.11a 802.11n HT20 802.11n HT40
<b>Type of Modulation</b>	OFDM (BPSK / QPSK / 16QAM / 64QAM)



<b>Product Specification subjective to this standard</b>														
<b>Antenna Type</b>	<b>&lt;5260 MHz ~ 5320 MHz&gt;</b> <b>Main Antenna</b> : PIFA_L Antenna with gain 2.24 dBi <b>Aux. Antenna</b> : PIFA_R Antenna with gain 0.86 dBi <b>&lt;5500 MHz ~ 5700 MHz &gt;</b> <b>Main Antenna</b> : PIFA_L Antenna with gain 2.15 dBi <b>Aux. Antenna</b> : PIFA_R Antenna with gain -0.34 dBi													
	<table border="1"><thead><tr><th></th><th>Ant 1.</th><th>Ant 2.</th></tr></thead><tbody><tr><td>802.11 a</td><td>V</td><td>V</td></tr><tr><td>802.11 n SISO</td><td>V</td><td>V</td></tr><tr><td>802.11 n MIMO</td><td>V</td><td>V</td></tr></tbody></table>			Ant 1.	Ant 2.	802.11 a	V	V	802.11 n SISO	V	V	802.11 n MIMO	V	V
	Ant 1.	Ant 2.												
802.11 a	V	V												
802.11 n SISO	V	V												
802.11 n MIMO	V	V												
<b>Antenna Function Description</b>	Note: MIMO mode is completely uncorrelated. Ant 1 and Ant 2 could not transmit simultaneously under 802.11 a/n SISO mode													



## 1.5 Testing Site

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978
Test Site No.	<b>Sporton Site No.</b> TH04-HY

## 1.6 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart E
- FCC OET Order 06-96A (2006)
- FCC KDB 905462
- FCC KDB 848637 (client device without radar detection capability)

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.

## 1.7 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	HW / FW Version	Power Cord
1.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	HW: Ver.A2 FW: Ver.1.23WW	Unshielded, 1.8 m
2.	Notebook	Lenovo	AR5B95	PPD-AR5B95	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m



## 2 Requirements and Parameters for DFS Test

### 2.1 Applicability of DFS Requirements

EUT is a slave device and operates in client without radar detection function.

**Table 1: Applicability of DFS Requirements Prior to Use of a Channel**

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
Non-Occupancy Period	Yes	Not required	Yes
DFS Detection Threshold	Yes	Not required	Yes
Channel Availability Check Time	Yes	Not required	Not required
Uniform Spreading	Yes	Not required	Not required
U-NII Detection Bandwidth	Yes	Not required	Yes

**Table 2: Applicability of DFS requirements during normal operation**

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
DFS Detection Threshold	Yes	Not required	Yes
Channel Closing Transmission Time	Yes	Yes	Yes
Channel Move Time	Yes	Yes	Yes
U-NII Detection Bandwidth	Yes	Not required	Yes
Client Beacon Test	Yes	Yes	Yes



## 2.2 Interference Threshold values, Master or Client incorporating In-Service Monitoring

Maximum Transmit Power	Value (see notes 1 and 2)
$\geq 200$ milliwatt	-64 dBm
$< 200$ milliwatt	-62 dBm

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.

Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.

The radar *Detection Threshold*, lowest antenna gain is the parameter of Interference *radar DFS detection threshold*, The Interference *Detection Threshold* is the ( -64dBm) + (0) [dBi]+ 1 dB= -63 dBm.



## 2.3 DFS Response requirement values

Parameter	Value
<i>Non-occupancy period</i>	Minimum 30 minutes
<i>Channel Availability Check Time</i>	60 seconds
<i>Channel Move Time</i>	10 seconds See Note 1.
<i>Channel Closing Transmission Time</i>	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
<i>U-NII Detection Bandwidth</i>	Minimum 80% of the 99% power bandwidth See Note 3.

Note 1: The instant that the *Channel Move Time* and the *Channel Closing Transmission Time* begins is as follows:

- For the Short pulse radar Test Signals this instant is the end of the *Burst*.
- For the Frequency Hopping radar Test Signal, this instant is the end of the last radar *Burst* generated.
- For the Long Pulse radar Test Signal this instant is the end of the 12 second period defining the radar transmission.

Note 2: The *Channel Closing Transmission Time* is comprised of 200 milliseconds starting at the beginning of the *Channel Move Time* plus any additional intermittent control signals required to facilitate *Channel* changes (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the *U-NII Detection Bandwidth* detection test, radar type 1 is used and for each frequency step the minimum percentage of detection is 90%. Measurements are performed with no data traffic.



## 2.4 Short Pulse Radar Test Waveforms

As the EUT is a Client Device with no Radar Detection, only one type radar pulse is required for the testing. Radar Pulse type 1 was used in the evaluation of the Client device for the purpose of measuring the Channel Move Time and the Channel Closing Transmission Time.

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Trials
1	1	1428	18	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120

A minimum of 30 unique waveforms are required for each of the short pulse radar types 2 through 4. For short pulse radar type 1, the same waveform is used a minimum of 30 times. If more than 30 waveforms are used for short pulse radar types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms. The aggregate is the average of the percentage of successful detections of short pulse radar types 1-4.


### 3 Calibration Setup and DFS Test Results

#### 3.1 Calibration of Radar Waveform

##### 3.1.1 Radar Waveform Calibration Procedure

The Interference Radar Detection Threshold Level is  $(-64\text{dBm}) + (0) [\text{dB}] + 1 \text{ dB} = -63\text{dBm}$  that had been taken into account the output power range and antenna gain. The following equipment setup was used to calibrate the radiated Radar Waveform. A vector signal generator was utilized to establish the test signal level for radar type 1. During this process there were no transmissions by either the Master or Client Device. The spectrum analyzer was switched to the zero span (Time Domain) at the frequency of the Radar Waveform generator. Peak detection was used. The spectrum analyzer resolution bandwidth (RBW) and video bandwidth (VBW) were set to 3 MHz to measure the type 1 radar waveform. The spectrum analyzer had offset -7.1dB to compensate receiving horn antenna gain 9.3dBi and RF cable loss 2.1dB. The vector signal generator amplitude was set so that the power level measured at the spectrum analyzer was  $(-64\text{dBm}) + (0) [\text{dB}] + 1 \text{ dB} = -63 \text{ dBm}$ . Capture the spectrum analyzer plots on short pulse radar waveform.


##### 3.1.2 Radiated Calibration Setup




##### 3.1.3 Calibration Deviation


There is no deviation with the original standard.

### 3.1.4 Radar Waveform Calibration Result



**<20MHz / 5500 MHz> Radar Type 1**
**Radar / DFS detection threshold level and the burst of pulses on the Channel frequency**


Date: 24.DEC.2012 16:41:43

**<40MHz / 5550 MHz> Radar Type 1**
**Radar / DFS detection threshold level and the burst of pulses on the Channel frequency**


Date: 24.DEC.2012 16:42:25



## **3.2 In-Service Monitoring: Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period**

### **3.2.1 Limit of In-Service Monitoring**

The EUT has In-Service Monitoring function to continuously monitor the radar signals. If radar is detected, it must leave the channel (Shutdown). The Channel Move Time to cease all transmissions on the current Channel upon detection of a Radar Waveform above the DFS Detection Threshold within 10 sec. The total duration of *Channel Closing Transmission Time* is comprised of 200 milliseconds starting at the beginning of the *Channel Move Time* plus any additional intermittent control signals required to facilitate *Channel* changes (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Non-Occupancy Period time is 30 minute during which a Channel will not be utilized after a Radar Waveform is detected on that Channel. The non-associated Client Beacon Test is during the 30 minutes observation time. The EUT should not make any transmissions in the DFS band after EUT power up.




### 3.2.2 Test Procedures

1. The radar pulse generator is setup to provide a pulse at frequency that the Master and Client are operating. A type 1 radar pulse with a 1us pulse width and a 1428 us PRI is used for the testing.
2. The vector signal generator is adjusted to provide the radar burst (18 pulses) at a level of approximately -62dBm at the antenna of the Master device.
3. A trigger is provided from the pulse generator to the DFS monitoring system in order to capture the traffic and the occurrence of the radar pulse.
4. A U-NII device operating as a Client Device will associate with the Master at Channel. The MPEG file "TestFile.mpg" specified by the FCC is streamed from the "file computer" through the Master to the Slave Device and played in full motion video using Media Player Classic Ver. 6.4.8.6 in order to properly load the network for the entire period of the test.
5. When a radar Burst with a level equal to the DFS Detection Threshold + 1dB is generated on the Operating Channel of the U-NII device. At time T0 the Radar Waveform generator sends a Burst of pulse of the radar waveform at Detection Threshold + 1dB.
6. Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel. Measure and record the transmissions from the EUT during the observation time (Channel Move Time). One 12 seconds plot is reported for the Short Pulse Radar Types 1. The plot for the Short Pulse Radar Types start at the end of the radar burst. The Channel Move Time will be calculated based on the zoom in 600ms plot of the Short Pulse Radar Type.
7. Measurement of the aggregate duration of the Channel Closing Transmission Time method. With the spectrum analyzer set to zero span tuned to the center frequency of the EUT operating channel at the radar simulated frequency, peak detection, and max hold, the dwell time per bin is given by: **Dwell (1.2ms)= S (600ms) / B (500)**; where Dwell is the dwell time per spectrum analyzer sampling bin, S is the sweep time and B is the number of spectrum analyzer sampling bins. An upper bound of the aggregate duration of the intermittent control signals of Channel Closing Transmission Time is calculated by: **C (ms)= N X Dwell (1.2 ms)**; where C is the Closing Time, N is the number of spectrum analyzer sampling bins (intermittent control signals) showing a U-NII transmission and Dwell is the dwell time per bin.
8. Measure the EUT for more than 30 minutes following the channel move time to verify that no transmissions or beacons occur on this Channel according to KDB848637.

### 3.2.3 Test Setup

Radiated Test Setup Photo



### 3.2.4 Test Deviation

There is no deviation with the original standard.




### 3.2.5 Result of Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period for Client Beacon Test

Test Mode :	Client without radar detection	Temperature :	27.3°C
Test Engineer :	Kenny Chen	Relative Humidity :	47%

BW / Channel	Test Item	Test Result	Limit	Pass/Fail
20MHz / 5300 MHz	Channel Move Time	1.23 s	< 10s	Pass
	Channel Closing Transmission Time	40.8 ms	< 60ms	Pass
	Non-Occupancy Period	≥30	≥ 30 min	Pass
40MHz / 5310 MHz	Channel Move Time	0.42 s	< 10s	Pass
	Channel Closing Transmission Time	31.2 ms	< 60ms	Pass
	Non-Occupancy Period	≥30	≥ 30 min	Pass
20MHz / 5500 MHz	Channel Move Time	1.58 s	< 10s	Pass
	Channel Closing Transmission Time	44.4 ms	< 60ms	Pass
	Non-Occupancy Period	≥30	≥ 30 min	Pass
40MHz / 5550 MHz	Channel Move Time	1.11 s	< 10s	Pass
	Channel Closing Transmission Time	44.4 ms	< 60ms	Pass
	Non-Occupancy Period	≥30	≥ 30 min	Pass


Note: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 seconds period. The aggregate duration of control signals will not count quiet periods in between transmissions.

### 3.2.6 Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period for Client Beacon Test Plots


**Note:**


**Dwell (1.2 ms)= Sweep Time (600 ms) / Sweep Point Bins (500)**

**Channel Closing Transmission Time (40.8 ms) = Number (34) X Dwell (1.2 ms) < 60ms**


**Note:**


**Dwell (1.2 ms)= Sweep Time (600 ms) / Sweep Point Bins (500)**

**Channel Closing Transmission Time (31.2 ms) = Number (26) X Dwell (1.2 ms) < 60ms**


**Note:**

**Dwell (1.2 ms)= Sweep Time (600 ms) / Sweep Point Bins (500)**



**Channel Closing Transmission Time (44.4 ms) = Number (37) X Dwell (1.2 ms) < 60ms**


**Note:**

**Dwell (1.2 ms)= Sweep Time (600 ms) / Sweep Point Bins (500)**

**Channel Closing Transmission Time (44.4 ms) = Number (37) X Dwell (1.2 ms) < 60ms**

### 3.2.7 Data Traffic and Noise Floor Plots





## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP7	101131	9KHz~7GHz	Jul. 23, 2012	Dec. 24, 2012 ~ Dec. 25 2012	Jul. 22, 2013	DFS (TH04-HY)
Signal Generator	R&S	SMJ100A	101375	9KHz ~ 6GHz	Feb. 20, 2012	Dec. 24, 2012 ~ Dec. 25 2012	Feb. 19, 2013	DFS (TH04-HY)
Horn Antenna	EMCO	AH-118	071025	1GHz ~ 18GHz	Nov. 19, 2012	Dec. 24, 2012 ~ Dec. 25 2012	Nov. 18, 2013	DFS (TH04-HY)
Horn Antenna	EMCO	AHA-118	071030	1GHz ~ 18GHz	Aug. 09, 2012	Dec. 24, 2012 ~ Dec. 25 2012	Aug. 08, 2013	DFS (TH04-HY)



## Appendix A. Photographs of EUT

Please refer to Sporton report number EP2D0508-01 as below.