

**Report No. : FA322535** 

# **FCC SAR Test Report**

APPLICANT : DT Research Inc.

**EQUIPMENT**: WLAN Module

BRAND NAME : DT Research Inc.

MODEL NAME : 600B

FCC ID : YE3600B

**STANDARD** : **FCC 47 CFR Part 2 (2.1093)** 

**ANSI/IEEE C95.1-1992** 

IEEE 1528-2003

FCC OET Bulletin 65 Supplement C (Edition 01-01)

The product was installed into Mobile Tablet (Brand Name: DT Research Inc., Model Name:DT365) during test.

The product was completely tested on Mar. 12, 2013. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Eric Huang / Vice Manager

Approved by: Jones Tsai / Manager

Cole huan

SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 1 of 44

Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01

# **Table of Contents**

1. Statement of Compliance	
2. Administration Data	
2.1 Testing Laboratory	5
2.2 Applicant	5
2.3 Manufacturer	5
2.4 Application Details	
3. General Information	
3.1 Description of Equipment Under Test (EUT)	. 6
3.2 Maximum RF output power among production units	. 7
3.3 Applied Standard	9
3.4 Device Category and SAR Limits	9
3.5 Test Conditions	9
4. Specific Absorption Rate (SAR)	10
4.1 Introduction	
4.2 SAR Definition	
5. SAR Measurement System	
5.1 E-Field Probe	
5.2 Data Acquisition Electronics (DAE)	
5.3 Robot	12
5.4 Measurement Server	
5.5 Phantom	
5.6 Device Holder	
5.7 Data Storage and Evaluation	
5.7 Data Storage and Evaluation	
6. Tissue Simulating Liquids	19
7. SAR System Vernication	21
7.1 Purpose of System Performance check	.21
7.2 System Setup	.21
7.3 SAR System Verification Results	
8. EUT Testing Position	23
9. Measurement Procedures	
9.1 Spatial Peak SAR Evaluation	.23
9.2 Area & Zoom Scan Procedures	
9.3 Volume Scan Procedures	
9.4 SAR Averaged Methods	
9.5 Power Drift Monitoring	
10. Conducted RF Output Power (Unit: dBm)	.26
11. Exposure Positions Consideration	.34
12. SAR Test Results	
12.1 Test Records for Body SAR Test	
12.2 Highest SAR Plot	.38
12.3 Simultaneous Multi-band Transmission Analysis	.40
13. Uncertainty Assessment	
14. References	.44
Appendix A. Plots of System Performance Check	
Appendix B. Plots of SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B



# **Revision History**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA322535	Rev. 01	Initial issue of report	Mar. 25, 2013

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 3 of 44

Report Issued Date : Mar. 25, 2013

Report No.: FA322535

## 1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **DT Research Inc. WLAN Module, DT Research Inc., 600B**, are as follows.

<Highest Reported standalone SAR Summary>

Frequency Band	Exposure Position	Reported 1g-SAR (W/kg)	Equipment Class	Highest Reported 1g-SAR (W/kg)
WLAN 5.2GHz Band	Body (0 cm Gap)	0.31		
WLAN 5.3GHz Band	Body (0 cm Gap)	0.24	NII	0.38
WLAN 5.6GHz Band	Body (0 cm Gap)	0.38		
WLAN 5.8GHz Band	Body (0 cm Gap)	0.86	DTS	0.86
WLAN 2.4GHz Band	Body (0 cm Gap)	0.29	סוס	0.80

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003 and FCC OET Bulletin 65 Supplement C (Edition 01-01).

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 4 of 44
Report Issued Date : Mar. 25, 2013

Report No.: FA322535



## 2. Administration Data

## 2.1 Testing Laboratory

Test Site	SPORTON INTERNATIONAL INC.		
Tost Site Location	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.		
Test Site Location	TEL: +886-3-327-3456 FAX: +886-3-328-4978		

## 2.2 Applicant

Company Name	DT Research Inc.
Address	6F, NO.1, Ning Po E. St., Taipei, 100 Taiwan, R.O.C.

## 2.3 Manufacturer

Company Name	DT Research Inc.
Address	6F, NO.1, Ning Po E. St., Taipei, 100 Taiwan, R.O.C.

## 2.4 Application Details

Date of Start during the Test	Mar. 04, 2013
Date of End during the Test	Mar. 12, 2013

SPORTON INTERNATIONAL INC. TEL: 886-3-327-3456

FAX: 886-3-328-4978 FCC ID: YE3600B

Page Number : 5 of 44 Report Issued Date: Mar. 25, 2013

Report No.: FA322535



## 3. General Information

## 3.1 <u>Description of Equipment Under Test (EUT)</u>

Product Feature & Specification			
EUT	WLAN Module		
Brand Name	DT Research Inc.		
Model Name	600B		
FCC ID	YE3600B		
TX Frequency	WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5700 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz		
Uplink Modulations	802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n: OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth : GFSK Bluetooth EDR : π/4-DQPSK, 8-DPSK Bluetooth 4.0 LE: GFSK		

#### Remark

The product was installed into Mobile Tablet (Brand Name: DT Research Inc., Model Name:DT365) during test.

Product Feature & Specification		
Host	Mobile Tablet	
Brand Name	DT Research Inc.	
Model Name	DT365	
Antenna Type	WLAN: PIFA Antenna Bluetooth: PIFA Antenna	
EUT Stage	Production Unit	

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 6 of 44
Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01

The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

<sup>2. 5600</sup> MHz ~ 5650 MHz is notched.

## 3.2 Maximum RF output power among production units

WLAN2.4GHz	IEEE 802.11 Ant 0 (Main antenna) average power(dBm)		
WLAN2.4GHZ	Ch1	Ch6	Ch11
802.11b	17	17	17
802.11g	13	16	13
802.11n_20M	12	16	12
802.11n_40M	Ch3	Ch6	CH9
	9.5	12.5	8.5

WLAN2.4GHz	IEEE 802.11 Ant 1 (Aux antenna) average power(dBm)		
WLAN2.4GHZ	Ch1	Ch6	Ch11
802.11b	16	14.5	15.5
802.11g	12	15	12
802.11n_20M	11	15.5	11
802.11n_40M	Ch3	Ch6	CH9
	8	11.5	9

WLAN2.4GHz	IEEE 802.11 Ant 0+1 (MIMO antenna) average power(dBm)		
WLAN2.4GHZ	Ch1	Ch6	Ch11
802.11n_20M	14.5	16.5	13.5
802.11n_40M	Ch3	Ch6	CH9
	10	15.5	9.5

	Bluetooth average power (dBm)					
Mode / Band	1Mbps	2Mbps	3Mbps	BT4.0-LE		
	(GFSK)	(π/4-DQPSK)	(8-DPSK)	(GFSK)		
2.4 GHz Bluetooth	6	3	3	4		

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 7 of 44
Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01



WLAN5GHz		IEEE 802.11 Ant 0 (Main antenna) average power(dBm)						
WLANSGHZ	WLAN5.2GHz band		WLAN5.3GHz band		WLAN5.5GHz band		band	WLAN5.8GHz band
802.11a	16	5.5	16.5		16.5			14.5
802.11n_20M	1	7	17			17		14.5
802.11n 40M	Ch38	Ch46	CH54	Ch62	Ch102	Ch110	Ch134	
602.11N_40W	13	16.5	16.5	12	15	16.5	16.5	20

WLAN5GHz		IEEE 802.11 Ant 1 (Aux antenna) average power(dBm)						
WLANSGHZ	WLAN5.2	GHz band	WLAN5.3GHz band		WLAN5.5GHz band	WLAN5.8GHz band		
802.11a	1	6	16		16	16		
802.11n_20M	1	16		6	16	16		
902 44m 40M	Ch38	Ch46	CH54	Ch62				
802.11n_40M	13	16	15.5	12.5	16	20.5		

WLAN5GHz		IEEE 802.11 Ant 0+1 (MIMO antenna) average power(dBm)						
WLANSGHZ	WLAN5.2GHz band		WLAN5.3GHz band	WLAN5.5GHz band	WLAN5.8GHz band			
802.11n_20M	16.5		16.5 16.5 16.5		17			
902 11n 40M	Ch38	Ch46						
802.11n_40M	13.5	16.5	16	16.5	16.5			

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 8 of 44
Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01



## 3.3 Applied Standard

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

**Report No. : FA322535** 

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2003
- FCC OET Bulletin 65 Supplement C (Edition 01-01)
- FCC KDB 447498 D01 v05
- FCC KDB 248227 D01 v01r02
- FCC KDB 616217 D04 v01

### 3.4 Device Category and SAR Limits

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

### 3.5 Test Conditions

#### **Ambient Condition**

Ambient Temperature	20 to 24 $^{\circ}\mathrm{C}$
Humidity	< 60 %

### **Test Configuration**

During WLAN SAR testing EUT is configured with the WLAN continuous TX tool, and the transmission duty factor was monitored on the spectrum analyzer with zero-span setting

Duty factor observed as below:

802.11b, 1Mbps: 100% 802.11a, 6Mbps: 100% 802.11n HT20, MCS8: 100% 802.11n HT40, MCS8: 100%

For WLAN SAR testing, WLAN engineering testing software installed on the EUT can provide continuous transmitting RF signal.

 SPORTON INTERNATIONAL INC.
 Page Number
 : 9 of 44

 TEL: 886-3-327-3456
 Report Issued Date
 : Mar. 25, 2013

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

FCC ID: YE3600B

## 4. Specific Absorption Rate (SAR)

### 4.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

Report No.: FA322535

### 4.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = C\left(\frac{\delta T}{\delta t}\right)$$

Where: C is the specific heat capacity,  $\delta T$  is the temperature rise and  $\delta t$  is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

Page Number

Report Version

: 10 of 44

: Rev. 01

Report Issued Date: Mar. 25, 2013

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B



Report No. : FA322535

## 5. SAR Measurement System




Fig 5.1 SPEAG DASY System Configurations

The DASY system for performance compliance tests is illustrated above graphically. This system consists of the following items:

- A standard high precision 6-axis robot with controller, a teach pendant and software
- A data acquisition electronic (DAE) attached to the robot arm extension
- A dosimetric probe equipped with an optical surface detector system
- > The electro-optical converter (EOC) performs the conversion between optical and electrical signals
- A measurement server performs the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the accuracy of the probe positioning
- A computer operating Windows XP
- DASY software
- > Remove control with teach pendant and additional circuitry for robot safety such as warming lamps, etc.
- The SAM twin phantom
- A device holder
- > Tissue simulating liquid
- Dipole for evaluating the proper functioning of the system

Component details are described in in the following sub-sections.

### 5.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 11 of 44
Report Issued Date : Mar. 25, 2013

## 5.1.1 E-Field Probe Specification

#### <ES3DV3 Probe >

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE)			### ### ### ### ### ### #### #########
Frequency	10 MHz to 3 GHz; Linearity: ± 0.2 dB			
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.4 dB in HSL (rotation normal to probe axis)			
Dynamic Range	10 μW/g to 100 mW/g; Linearity: ± 0.2 dB			
Dimensions	Overall length: 337 mm (Tip: 10 mm) Tip diameter: 4 mm (Body: 10 mm) Distance from probe tip to dipole centers: 3 mm	Fi	g 5.2	Photo of ES3DV3

#### <EX3DV4 Probe>

Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz to 6 GHz; Linearity: ± 0.2 dB	Ť
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	1
Dynamic Range	10 μW/g to 100 mW/g; Linearity: ± 0.2 dB (noise: typically < 1 μW/g)	
Dimensions	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	
		Fig 5.3 Photo of EX3DV4/ES3DV4

#### 5.1.2 E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than  $\pm$  10%. The spherical isotropy shall be evaluated and within  $\pm$  0.25dB. The sensitivity parameters (NormX, NormY, and NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested. The calibration data can be referred to appendix C of this report.

### 5.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



**Report No. : FA322535** 

Fig 5.4 Photo of DAE

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 12 of 44
Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01

# 5.3 <u>Robot</u>

The SPEAG DASY system uses the high precision robots (DASY4: RX90BL; DASY5: TX90XL) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY4: CS7MB; DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- ➤ High precision (repeatability ±0.035 mm)
- > High reliability (industrial design)
- Jerk-free straight movements
- > Low ELF interference (the closed metallic construction shields against motor control fields)



Fig 5.5 Photo of DASY4



**Report No. : FA322535** 

Fig 5.6 Photo of DASY5

### 5.4 Measurement Server

The measurement server is based on a PC/104 CPU board with CPU (DASY4: 166 MHz, Intel Pentium; DASY5: 400 MHz, Intel Celeron), chipdisk (DASY4: 32 MB; DASY5: 128 MB), RAM (DASY4: 64 MB, DASY5: 128 MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all the real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operations.



Fig 5.7 Photo of Server for DASY4



Fig 5.8 Photo of Server for DASY5

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 13 of 44
Report Issued Date : Mar. 25, 2013

### 5.5 Phantom

#### <SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm;				
	Center ear point: 6 ± 0.2 mm				
Filling Volume	Approx. 25 liters				
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet				
Measurement Areas	Left Hand, Right Hand, Flat Phantom	Fig 5.9 Photo of SAM Phantom			

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

#### <ELI4 Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	Fig 5.10 Photo of ELI4 Phantom

The ELI4 phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 14 of 44
Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01



### 5.6 <u>Device Holder</u>

#### <Device Holder for SAM Twin Phantom>

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of  $\pm$  0.5 mm would produce a SAR uncertainty of  $\pm$  20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon$  = 3 and loss tangent  $\delta$  = 0.02. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



Fig 5.11 Device Holder

#### <Laptop Extension Kit>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Fig 5.12 Laptop Extension Kit

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 15 of 44
Report Issued Date : Mar. 25, 2013

**Report No. : FA322535** 



### 5.7 Data Storage and Evaluation

#### 5.7.1 Data Storage

The DASY software stores the assessed data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all the necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files. The post-processing software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of erroneous parameter settings. For example, if a measurement has been performed with an incorrect crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be reevaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type (e.g., [V/m], [A/m], [mW/g]). Some of these units are not available in certain situations or give meaningless results, e.g., a SAR-output in a non-lose media, will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

#### 5.7.2 Data Evaluation

**Device parameters:** 

The DASY post-processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

**Probe parameters**: - Sensitivity Norm<sub>i</sub>, a<sub>i0</sub>, a<sub>i1</sub>, a<sub>i2</sub>

 $\begin{array}{lll} \text{- Conversion factor} & \text{ConvF}_i \\ \text{- Diode compression point} & \text{dcp}_i \\ \text{- Frequency} & \text{f} \\ \text{- Crest factor} & \text{cf} \end{array}$ 

 Media parameters :
 - Conductivity
 σ

 - Density
 ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 16 of 44
Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01



The formula for each channel can be given as :

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with  $V_i$  = compensated signal of channel i, (i = x, y, z)

 $U_i$  = input signal of channel i, (i = x, y, z)

cf = crest factor of exciting field (DASY parameter) dcp<sub>i</sub> = diode compression point (DASY parameter)

From the compensated input signals, the primary field data for each channel can be evaluated:

E-field Probes :  $E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$ 

H-field Probes :  $H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$ 

with  $V_i$  = compensated signal of channel i, (i = x, y, z)

Norm<sub>i</sub> = sensor sensitivity of channel i, (i = x, y, z),  $\mu V/(V/m)^2$  for E-field Probes

ConvF = sensitivity enhancement in solution  $a_{ij}$  = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

 $E_i$  = electric field strength of channel i in V/m  $H_i$  = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with SAR = local specific absorption rate in mW/g

E<sub>tot</sub> = total field strength in V/m

 $\sigma$  = conductivity in [mho/m] or [Siemens/m]

 $\rho$  = equivalent tissue density in g/cm<sup>3</sup>

Note that the density is set to 1, to account for actual head tissue density rather than the density of the tissue simulating liquid.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 17 of 44
Report Issued Date : Mar. 25, 2013

Report No.: FA322535



### 5.8 Test Equipment List

Manufacturer	Name of Equipment	Tyme/Medal	Serial Number	Calibration		
wanuracturer	Name of Equipment	Type/Model	Serial Number	Last Cal.	Due Date	
SPEAG	2450MHz System Validation Kit	D2450V2	736	Jul. 25, 2011	Jul. 24, 2013	
SPEAG	5GHz System Validation Kit	D5GHzV2	1006	Dec. 11, 2012	Dec. 10, 2013	
SPEAG	Data Acquisition Electronics	DAE4	778	Aug. 27, 2012	Aug. 26, 2013	
SPEAG	Data Acquisition Electronics	DAE3	495	Apr. 23, 2012	Apr. 22, 2013	
SPEAG	Data Acquisition Electronics	DAE4	1279	Jan. 28, 2013	Jan. 27, 2014	
SPEAG	Data Acquisition Electronics	DAE4	1338	Jun. 12, 2012	Jun. 11, 2013	
SPEAG	Dosimetric E-Field Probe	EX3DV4	3661	Jan. 5, 2013	Jan. 4, 2014	
SPEAG	Dosimetric E-Field Probe	EX3DV4	3697	Sep. 28, 2012	Sep. 27, 2013	
SPEAG	Dosimetric E-Field Probe	EX3DV4	3792	Jun. 21, 2012	Jun. 20, 2013	
SPEAG	Dosimetric E-Field Probe	ES3DV3	3270	Sep. 28, 2012	Sep. 27, 2013	
Wisewind	Thermometer	ETP-101	TM560	Nov. 13, 2012	Nov. 12, 2013	
Wisewind	Thermometer	ETP-101	TM685	Nov. 13, 2012	Nov. 12, 2013	
Wisewind	Thermometer	HTC-1	TM281	Nov. 13, 2012	Nov. 12, 2013	
H.M.IRIS	Thermometer	TH-08	TM658	Nov. 13, 2012	Nov. 12, 2013	
SPEAG	ELI4 Phantom	QD OVA 002 AA	1173	NCR	NCR	
SPEAG	ELI4 Phantom	QD 0VA 001 BB	1026	NCR	NCR	
SPEAG	ELI4 Phantom	QD 0VA 001 BA	1029	NCR	NCR	
SPEAG	ELI4 Phantom	QD 0VA 002 AA	TP-1131	NCR	NCR	
Agilent	ENA Network Analyzer	E5071C	MY46316648	Feb. 07, 2013	Feb. 06, 2014	
Agilent	ESG Vector Series Signal Generator	E4438C	MY49070755	Oct. 02, 2012	Oct. 01, 2013	
Anritsu	Power Meter	ML2495A	1132003	Aug. 14, 2012	Aug. 13, 2013	
Agilent	Dual Directional Coupler	778D	50422	Not	te 4	
Woken	Attenuator 1	WK0602-XX	N/A	Note 4		
PE	Attenuator 2	PE7005-10	N/A	Note 4		
PE	Attenuator 3	PE7005-3	N/A Note 4		te 4	
Agilent	Dielectric Probe Kit	85070D	US01440205	Note 5		
AR	Power Amplifier	5S1G4M2	328767	Not	te 6	
R&S	Spectrum Analyzer	FSP	101131	Jul. 23, 2012	Jul. 22, 2013	

#### **Table 5.1 Test Equipment List**

#### Note:

- 1. The calibration certificate of DASY can be referred to appendix C of this report.
- 2. Referring to KDB 865664 D01v01, the dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
- 3. The justification data of dipole D2450V2, SN: 736, can be found in appendix C. The return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration.
- 4. The Insertion Loss calibration of Dual Directional Coupler and Attenuator were characterized via the network analyzer and compensated during system check.
- 5. The dielectric probe kit was calibrated via the network analyzer, with the specified procedure (calibrated in pure water) and calibration kit (standard) short circuit, before the dielectric measurement. The specific procedure and calibration kit are provided by Agilent.
- 6. In system check we need to monitor the level on the power meter, and adjust the power amplifier level to have precise power level to the dipole; the measured SAR will be normalized to 1W input power according to the ratio of 1W to the input power to the dipole. For system check, the calibration of the power amplifier is deemed not critically required for correct measurement; the power meter is critical and we do have calibration for it
- Attenuator 1 insertion loss is calibrated by the network Analyzer, which the calibration is valid, before system
  check.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 18 of 44
Report Issued Date : Mar. 25, 2013

**Report No. : FA322535** 



**Report No. : FA322535** 

## 6. Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.2.





Fig 6.1 Photo of Liquid Height for Head SAR

Fig 6.2 Photo of Liquid Height for Body SAR

The following table gives the recipes for tissue simulating liquid.

Frequency	Water	Sugar	Cellulose	Salt	Preventol	DGBE	Conductivity	Permittivity
(MHz)	(%)	(%)	(%)	(%)	(%)	(%)	(σ)	(ε <sub>r</sub> )
	For Body							
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7

**Table 6.1 Recipes of Tissue Simulating Liquid** 

Simulating Liquid for 5G, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

 SPORTON INTERNATIONAL INC.
 Page Number
 : 19 of 44

 TEL: 886-3-327-3456
 Report Issued Date
 : Mar. 25, 2013

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

FCC ID: YE3600B



The dielectric parameters of the liquids were verified prior to the SAR evaluation using an Agilent 85070D Dielectric Probe Kit and an Agilent Network Analyzer.

Report No.: FA322535

The following table shows the measuring results for simulating liquid.

Frequency (MHz)	Liquid Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (εr)	Conductivity Target (σ)	Permittivity Target (εr)	Delta (σ) (%)	Delta (εr) (%)	Limit (%)	Date
2450	Body	21.4	1.963	52.895	1.95	52.7	0.67	0.37	±5	2013/3/4
5200	Body	21.2	5.131	47.488	5.3	49	-3.19	-3.09	±5	2013/3/6
5300	Body	21.2	5.264	47.249	5.30	49.0	-0.68	-3.57	±5	2013/3/6
5600	Body	21.5	5.821	46.733	5.8	48.5	0.36	-3.64	±5	2013/3/7
5600	Body	21.4	5.642	46.786	5.8	48.5	-2.72	-3.53	±5	2013/3/12
5800	Body	21.5	6.179	46.434	6	48.2	2.98	-3.66	±5	2013/3/7
5800	Body	21.5	6.153	46.472	6	48.2	2.55	-3.59	±5	2013/3/12

Table 6.2 Measuring Results for Simulating Liquid

 SPORTON INTERNATIONAL INC.
 Page Number
 : 20 of 44

 TEL: 886-3-327-3456
 Report Issued Date
 : Mar. 25, 2013

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

FCC ID: YE3600B



Report No.: FA322535

## 7. SAR System Verification

Each DASY system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the DASY software, enable the user to conduct the system performance check and system validation. System validation kit includes a dipole, tripod holder to fix it underneath the flat phantom and a corresponding distance holder.

### 7.1 Purpose of System Performance check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure

## 7.2 System Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:




Fig 7.1 System Setup for System Evaluation

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 21 of 44
Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01



- 1. Signal Generator
- 2. Amplifier
- 3. Directional Coupler
- 4. Power Meter
- 5. Calibrated Dipole



Fig 7.2 Photo of Dipole Setup

## 7.3 SAR System Verification Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Table 7.1 shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Liquid Type	Power fed onto reference dipole (mW)	Targeted SAR (W/kg)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Deviation (%)
2013/3/4	2450	Body	250	52.3	12.9	51.6	-1.34
2013/3/6	5200	Body	100	71.4	7.53	75.3	5.46
2013/3/6	5300	Body	100	73.5	7.3	73	-0.68
2013/3/7	5600	Body	100	76.8	7.68	76.8	0.00
2013/3/12	5600	Body	100	76.8	7.58	75.8	-1.30
2013/3/7	5800	Body	100	71.7	6.82	68.2	-4.88
2013/3/12	5800	Body	100	71.7	7.67	76.7	6.97

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 22 of 44
Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01

## 8. EUT Testing Position

This EUT was tested in three different positions. They are bottom-face of tablet PC, Edge3, and Edge4. In these positions, the surface of EUT is touching with phantom 0 cm. Please refer to Appendix D for the test setup photos.

Report No.: FA322535

## 9. Measurement Procedures

The measurement procedures are as follows:

#### <Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

#### <SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

## 9.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values form the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

 SPORTON INTERNATIONAL INC.
 Page Number
 : 23 of 44

 TEL: 886-3-327-3456
 Report Issued Date
 : Mar. 25, 2013

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

FCC ID: YE3600B

### 9.2 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01 quoted below.

For any secondary peaks found in the area scan which are within 2 dB of the maximum peak and are not within this zoom scan, the zoom scan should be repeated

			≤ 3 GHz	> 3 GHz
Maximum distance fron (geometric center of pro			5 ± 1 mm	½-δ·ln(2) ± 0.5 mm
Maximum probe angle to normal at the measurem			30° ± 1°	20° ± 1°
			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
Maximum area scan spa	tial resoluti	on: Δx <sub>Area</sub> , Δy <sub>Area</sub>	When the x or y dimension of t measurement plane orientation measurement resolution must b dimension of the test device wi point on the test device.	, is smaller than the above, the e ≤ the corresponding x or y
Maximum zoom scan sp	oatial resolu	tion: Δx <sub>Zoom</sub> , Δy <sub>Zoom</sub>	≤ 2 GHz: ≤ 8 mm 2 - 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
	uniform g	rid: Δz <sub>Zoom</sub> (n)	≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
Maximum zoom scan spatial resolution, normal to phantom surface	graded	Δz <sub>Zoom</sub> (1): between 1 <sup>st</sup> two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
	grid	Δz <sub>Zoom</sub> (n>1): between subsequent points	≤ 1.5·Δz	z <sub>Zoom</sub> (n-1)
Minimum zoom scan volume	x, y, z	I	≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 24 of 44
Report Issued Date : Mar. 25, 2013

**Report No. : FA322535** 

When zoom scan is required and the <u>reported</u> SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.



#### 9.3 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

## 9.4 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

## 9.5 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 25 of 44
Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01

## 10. Conducted RF Output Power (Unit: dBm)

#### <WLAN 2.4GHz Conducted Power>

#### < SISO mode Antenna 0 Conducted Power>

	WLAN 2.4GHz 802.11b Average Power (dBm)											
	Power vs. Cha	nnel		Power vs. Data Rate								
Channel	Freq.	Data Rate	Channal	Channel Data Rate								
Chamilei	(MHz)	1Mbps	Chamilei	2Mbps	5.5Mbps	11Mbps						
CH 1	2412	15.99										
CH 6	2437	16.75	CH 6	16.48	16.62	16.68						
CH 11	2462	16.33										

	WLAN 2.4GHz 802.11g Average Power (dBm)											
	Power vs. Cha		Power vs. Data Rate									
Channal	Frequency	Data Rate	Channel	Data Rate								
Channel	(MHz)	6Mbps	Chamilei	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps		
CH 1	2412	12.88										
CH 6	2437	15.70	CH 6	15.69	15.64	15.67	15.64	15.68	15.67	15.65		
CH 11	2462	12.75										

	WLAN 2.4GHz 802.11n-HT20 Average Power (dBm)											
	Power vs. Cha		Power vs. Data Rate									
Channal	Frequency	MCS Index	Channel	MCS Index								
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7		
CH 1	2412	11.98										
CH 6	2437	15.40	CH 6	15.36	15.37	15.26	15.29	15.34	15.29	15.38		
CH 11	2462	11.58										

	WLAN 2.4GHz 802.11n-HT40 Average Power (dBm)											
	Power vs. Cha				Power vs.	Data Rate						
Channal	Frequency	MCS Index	Channal	MCS Index								
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7		
CH 3	2422	9.10										
CH 6	2437	12.19	CH 6	12.17	12.16	12.14	12.18	12.17	12.18	12.17		
CH 9	2452	8.45										

#### Note:

- Per KDB 248227 D01 v01r02, choose the highest output power channel to test SAR and determine further SAR exclusion
- 2. For each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 0.25dB higher than those measured at the lowest data rate.
- 3. Per KDB 248227 D01 v01r02, 11g, 11n-HT20 and 11n-HT40 output power is less than 1/4dB higher than 11b mode, thus the SAR can be excluded.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 26 of 44
Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01



#### < SISO mode Antenna 1 Conducted Power>

10.00	Colod mode Alterna i Conducted i Gwely												
		W	LAN 2.4GH	z 802.11b Average Powe	r (dBm)								
	Power vs. Cha	annel		Power vs. Data Rate									
Channel	Freq.	Data Rate (bps)	Channel Data Rate (bps)										
Chamilei	(MHz)	1Mbps	Charmer	2Mbps	5.5Mbps	11Mbps							
CH 1	2412	15.69											
CH 6	2437	13.94	CH 1	15.64	15.66	1.63							
CH 11	2462	14.99											

	WLAN 2.4GHz 802.11g Average Power (dBm)											
	Power vs. Channel				Power vs. Data Rate							
Channel	Frequency	Data Rate	Channel	Data Rate								
Channel	(MHz)	6Mbps	Challie	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps		
CH 1	2412	11.95			15.05	15.09	15.05					
CH 6	2437	15.12	CH 6	15.06				15.06	15.09	15.11		
CH 11	2462	11.99										

	WLAN 2.4GHz 802.11n-HT20 Average Power (dBm)											
	Power vs. Cha	nnel		Power vs. Data Rate								
Channal	Frequency	MCS Index	Channel	MCS Index								
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7		
CH 1	2412	10.64										
CH 6	2437	15.12	CH 6	15.01	15.10	15.11	15.10	15.11	15.09	15.10		
CH 11	2462	10.48										

	WLAN 2.4GHz 802.11n-HT40 Average Power (dBm)											
	Power vs. Cha				Power vs.	Data Rate						
Channal	Frequency	MCS Index	Channal	Channel MCS Index								
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7		
CH 3	2422	7.97										
CH 6	2437	11.35	CH 6	11.33	11.30	11.27	11.32	11.32	11.31	11.32		
CH 9	2452	8.62										

#### Note:

- 1. Per KDB 248227 D01 v01r02, choose the highest output power channel to test SAR and determine further SAR
- 2. For each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 0.25dB higher than those measured at the lowest data rate.
- 3. Per KDB 248227 D01 v01r02, 11g, 11n-HT20 and 11n-HT40 output power is less than 1/4dB higher than 11b mode, thus the SAR can be excluded.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 27 of 44
Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01



#### < MIMO mode Antenna 0+1 Conducted Power>

	WLAN 2.4GHz 802.11n-HT20 Average Power (dBm)												
	Power vs. Cha	nnel		Power vs. Data Rate									
Channal	Frequency	MCS Index	Channel	MCS Index									
Channel	(MHz)	MCS8	Charmer	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15			
CH 1	2412	14.45											
CH 6	2437	16.12	CH 6	16.10	15.92	15.88	15.90	16.09	16.07	16.11			
CH 11	2462	13.33											

		WLA	N 2.4GHz 8	02.11n-HT4	10 Average	Power (di	3m)			
	Power vs. Cha	Power vs. Data Rate								
Channel	Frequency	MCS Index	Channel MCS Index							
Chamilei	(MHz)	MCS0	Chamilei	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 3	2422	9.80								
CH 6	2437	14.98	CH 6	14.94	14.97	14.94	14.95	14.96	14.97	14.92
CH 9	2452	9.13								

#### Note:

- Per KDB 248227 D01 v01r02, choose the highest output power channel to test SAR and determine further SAR exclusion
- 2. For each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 0.25dB higher than those measured at the lowest data rate.
- 3. Per KDB 248227 D01 v01r02, 11n-HT40 output power is less than 1/4dB higher than 11n-HT20 mode, thus the SAR can be excluded.

#### <Bluetooth Conducted Power>

	F	Average power (dBm)							
Channel	Frequency (MHz)	Mode							
	(1411 12)	GFSK	π/4-DQPSK	8-DPSK					
CH 0	2402	5.92	1.97	1.96					
CH 39	2441	5.97	2.21	2.21					
CH 78	2480	5.75	2.30	2.29					

	F	Average power (dBm)
Channel	Channel Frequency (MHz)	Mode
		BT v4.0 LE, GFSK
CH 0	2402	3.55
CH 19	2440	3.62
CH 39	2480	3.82

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 28 of 44
Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01

### <WLAN 5GHz Conducted Power>

### < SISO mode Antenna 0 Conducted Power>

		W	LAN 5GHz 8	02.11a Av	erage Pow	er (dBm)							
	Power vs. Cha	annel				Power vs.	Data Rate						
Channel	Frequency	Data Rate	Channal	Channel Data Rate									
Channel	(MHz)	6Mbps	Channel	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps			
CH 36	5180	16.05											
CH 40	5200	15.99	CH 36	16.00	15.98	15.99	16.01	16.03	16.02	16.04			
CH 44	5220	15.85	CH 36	16.03	15.96	15.99	16.01	16.03	16.02	16.04			
CH 48	5240	15.49	1										
CH 52	5260	15.55											
CH 56	5280	16.22	CH 64	16.23	16.17	46.00	16.21	16.00	16 17	16.16			
CH 60	5300	16.07	CH 64	10.23	16.17	16.22	10.21	16.20	16.17	16.16			
CH 64	5320	16.24	1										
CH 100	5500	16.16											
CH 104	5520	16.31											
CH 108	5540	16.08	1				16.26	16.33	40.04				
CH 112	5560	16.33	011446	40.00	40.04	16.28				40.04			
CH 116	5580	16.37	CH 116	16.36	16.21				16.31	16.34			
CH 132	5660	16.36	1										
CH 136	5680	16.27	1										
CH 140	5700	16.33	1										
CH 149	5745	14.36											
CH 153	5765	14.34	1										
CH 157	5785	14.27	CH 149	14.30	14.28	14.18	14.30	14.24	14.25	14.18			
CH 161	5805	14.25		14.30		14.10							
CH 165	5825	14.05	1										

		WLA	N 5GHz 802	2.11n-HT20	Average	Power (dE	3m)			
	Power vs. Ch	nannel				Power vs.	Data Rate			
Channel	Frequency	MCS Index	Channel				MCS Index	(		
Chamer	(MHz)	MCS0	Chamer	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 36	5180	15.86								
CH 40	5200	16.31	CH 44	16.48	16.48	16.45	16.44	16.46	16.45	16.48
CH 44	5220	16.49	CH 44	11 44 10.46	10.40	10.43	10.44	10.40	10.43	10.40
CH 48	5240	16.31								
CH 52	5260	15.82								
CH 56	5280	16.23	CH 64	16.45	16.44	16.42	16.43	16.44	16.42	16.45
CH 60	5300	16.38	CH 64	CH 64 16.45	10.44	10.42	10.43	10.44	10.42	10.45
CH 64	5320	16.47								
CH 100	5500	16.31								
CH 104	5520	15.95								
CH 108	5540	16.19		16.28		16.30		16.35	16.34	16.32
CH 112	5560	16.18	CH 116		16.30		16.34			
CH 116	5580	16.36	CHIII	10.20	10.30	10.30		10.33	10.34	10.32
CH 132	5660	16.35								
CH 136	5680	16.12								
CH 140	5700	16.21								
CH 149	5745	14.49								
CH 153	5765	14.38								
CH 157	5785	14.35	CH 149	14.35	14.43	14.41	14.38	14.45	14.35	14.46
CH 161	5805	14.32		100						
CH 165	5825	14.30								

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 29 of 44

Report Issued Date : Mar. 25, 2013

Report Version : Rev. 01



		WLA	N 5GHz 802	2.11n-HT40	Average	Power (dE	3m)				
	Power vs. Cha	nnel		Power vs. Data Rate							
Channel	Frequency	MCS Index	Channel				MCS Index				
Chamilei	(MHz)	MCS0	Chamilei	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	
CH 38	5190	12.59	CH 46	16.25	16 DE	16.00	16.21	16.26	16 DE	16.24	
CH 46	5230	16.37	CH 46	16.35	16.35	16.23	16.31	16.36	16.35	16.34	
CH 54	5270	15.95	CH 54	15.04	15.90	1E 0E	15.04	15.04	15.00	15.00	
CH 62	5310	11.37	CH 54	15.94	15.90	15.85	15.94	15.94	15.93	15.93	
CH 102	5510	14.98									
CH 110	5550	16.30	CH 110	16.28	16.29	16.16	16.25	16.27	16.26	16.28	
CH 134	5670	16.16									
CH 151	5755	19.49	CH 151	19.47	19.48	19.42	19.48	19.47	19.45	19.48	
CH 159	5795	19.24	OH 131	19.47	19.46	19.42	19.46	19.47	19.45	19.40	

#### Note:

- Per KDB 248227 D01 v01r02, choose the highest output power channel to test SAR and determine further SAR exclusion
- 2. For each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 0.25dB higher than those measured at the lowest data rate.
- 3. Per KDB 248227 D01 v01r02, 11n-HT20 and 11n-HT40 (Freq: 5180 MHz ~ 5240MHz) power is 1/4dB higher than 802.11a mode, 11n-HT20 and 11n HT40 SAR will be verified at the highest RF exposure position found in 802.11a SAR testing.
- 4. Per KDB 248227 D01 v01r02, 11n-HT40 (Freq: 5745 MHz ~ 5825MHz) power is 1/4dB higher than 802.11a mode, 11n-HT40 SAR will be verified at the highest RF exposure position found in 802.11a SAR testing.
- 5. Per KDB 248227 D01 v01r02, 11n-HT20 and 11n-HT40 (Freq: 5260 MHz ~ 5700MHz) output power is less than 1/4dB higher than 11a mode, thus the SAR can be excluded.

SPORTON INTERNATIONAL INC.

FAX: 886-3-328-4978 FCC ID: YE3600B

TEL: 886-3-327-3456

Page Number : 30 of 44
Report Issued Date : Mar. 25, 2013

**Report No. : FA322535** 



## < SISO mode Antenna 1 Conducted Power>

			802.1 WLA	N 5GHz 1a	Average P	ower (dBm	)			
F	ower vs. Cha	nnel				Power vs. [	Data Rate			
Channel	Frequency	Data Rate	Channel				Data Rate			
Channel	(MHz)	6Mbps	Channel	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
CH 36	5180	15.58								
CH 40	5200	15.57	CH 36	15.56	15.51	15.49	15.50	15.56	15.56	15.54
CH 44	5220	15.47	01130	13.30	13.31	13.49	13.30	13.30	13.30	15.54
CH 48	5240	15.27								
CH 52	5260	15.02								
CH 56	5280	15.16	CH 64	15.83	15.80	15.85	15.81	15.84	15.88	15.84
CH 60	5300	15.08	CH 64	13.63	13.60	13.63	13.61	13.04	13.00	13.64
CH 64	5320	15.89								
CH 100	5500	15.44								
CH 104	5520	15.45								
CH 108	5540	15.47				15.43			15.42	
CH 112	5560	15.35	CH 116	15.47	15.45		15.39	15.43		15.45
CH 116	5580	15.48	CITTIO	13.47	13.43	13.43	13.38	13.43	13.42	15.45
CH 132	5660	15.34								
CH 136	5680	15.14								
CH 140	5700	15.41								
CH 149	5745	15.86								
CH 153	5765	15.81								
CH 157	5785	15.71	CH 149	15.83	15.70	15.81	15.68	15.73	15.84	15.85
CH 161	5805	15.77								
CH 165	5825	15.81								

		WI	LAN 5GHz	802.11n-H	T20 Avera	age Power (	dBm)					
	Power vs. Char						. Data Rate					
Channel	Frequency	MCS Index	Channel	hannel MCS Index								
Channel	(MHz)	MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7		
CH 36	5180	15.91										
CH 40	5200	15.70	CH 36	15.85	15.86	15.78	15.87	15.88	15.88	15.88		
CH 44	5220	15.83	CH 30	13.03	13.00	13.70	13.07	13.00	13.00	13.00		
CH 48	5240	15.79										
CH 52	5260	15.37										
CH 56	5280	15.39	CH 64	15.51	15.55	15.57	15.54	15.52	15.53	15.54		
CH 60	5300	15.09	CH 64	13.31	15.55	15.57	15.54	13.32	15.55	13.34		
CH 64	5320	15.58										
CH 100	5500	15.41										
CH 104	5520	15.31										
CH 108	5540	15.43										
CH 112	5560	15.45	CH 116	15.41	15.48	15.47	15.48	15.48	15.45	15.46		
CH 116	5580	15.49	CITTIO	13.41	13.40	13.47	13.40	13.40	13.43	13.40		
CH 132	5660	15.45										
CH 136	5680	15.39										
CH 140	5700	15.39										
CH 149	5745	15.76										
CH 153	5765	15.58										
CH 157	5785	15.54	CH 149	15.53	15.70	15.69	15.72	15.74	15.70	15.75		
CH 161	5805	15.52										
CH 165	5825	15.49										

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 31 of 44
Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01



		W	LAN 5GHz	802.11n-H	T40 Avera	age Power (	dBm)					
	Power vs. Char	nnel	Power vs. Data Rate									
Channel	Frequency	MCS Index	Channel	MCS Index								
Chamilei	(MHz)	MCS0	Chamilei	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7		
CH 38	5190	12.43	CH 46	15.71	15.73	15.72	15.72	15.74	15.72	15.67		
CH 46	5230	15.76	CH 40	15.71	15.75	13.72	13.72	13.74	13.72	13.67		
CH 54	5270	14.95	CH 54	14.92	14.92	14.93	14.93	14.94	14.92	14.88		
CH 62	5310	12.06	CH 34	14.92	14.92	14.93	14.93	14.94	14.92	14.00		
CH 102	5510	14.60										
CH 110	5550	15.65	CH 110	15.64	15.63	15.62	15.62	15.61	15.60	15.57		
CH 134	5670	15.31										
CH 151	5755	19.67	CH 151	10.57	19.62	19.59	19.63	19.63	19.65	19.65		
CH 159	5795	19.58	CH 131	19.57	19.02	19.59	19.03	19.03	19.00	19.05		

#### Note:

- Per KDB 248227 D01 v01r02, choose the highest output power channel to test SAR and determine further SAR exclusion
- 2. For each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 0.25dB higher than those measured at the lowest data rate.
- 3. Per KDB 248227 D01 v01r02, 11n-HT20 (Freq: 5180 MHz ~ 5240MHz) power is 1/4dB higher than 802.11a mode, 11n-HT20 SAR will be verified at the highest RF exposure position found in 802.11a SAR testing.
- 4. Per KDB 248227 D01 v01r02, 11n-HT40 (Freq: 5745 MHz ~ 5825MHz) power is 1/4dB higher than 802.11a mode, 11n-HT40 SAR will be verified at the highest RF exposure position found in 802.11a SAR testing.
- 5. Per KDB 248227 D01 v01r02, 11n-HT20 and 11n-HT40 (Freq: 5260 MHz ~ 5700MHz) output power is less than 1/4dB higher than 11a mode, thus the SAR can be excluded.

SPORTON INTERNATIONAL INC.

FAX: 886-3-328-4978 FCC ID: YE3600B

TEL: 886-3-327-3456

Page Number : 32 of 44
Report Issued Date : Mar. 25, 2013

**Report No. : FA322535** 



#### < MIMO mode Antenna 0+1 Conducted Power>

		1	<b>NLAN 5GH</b>	lz 802.11n-	HT20 Ave	rage Power	(dBm)			
	Power vs. Cha	nnel				Power vs	. Data Rate			
Channel	Frequency	MCS Index	Channel				MCS Index			
Chamilei	(MHz)	MCS8	Chamer	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
CH 36	5180	15.97								
CH 40	5200	16.02	CH 44	16.06	16.05	16.06	16.04	16.07	16.06	16.06
CH 44	5220	16.08	01144	10.00	10.03	10.00	10.04	10.07	10.00	10.00
CH 48	5240	15.90								
CH 52	5260	15.29								
CH 56	5280	15.46	CH 64	15.77	15.78	15.78	15.74	15.84	15.80	15.78
CH 60	5300	15.49	CH 64	13.77	15.76	13.76	13.74	15.64	15.60	13.76
CH 64	5320	15.85								
CH 100	5500	15.79								
CH 104	5520	15.59								
CH 108	5540	15.89								
CH 112	5560	15.92	CH 116	15.90	15.93	15.91	15.91	15.94	15.93	15.93
CH 116	5580	15.94	CH III	15.90	15.95	15.91	15.91	15.94	15.95	15.95
CH 132	5660	15.56								
CH 136	5680	15.36								
CH 140	5700	15.37								
CH 149	5745	16.54								
CH 153	5765	16.41								
CH 157	5785	16.44	CH 149	16.39	16.35	16.20	16.33	16.12	16.00	16.14
CH 161	5805	16.12		10.00						
CH 165	5825	16.24								

		1	<b>NLAN 5GH</b>	lz 802.11n-	HT40 Ave	rage Power	(dBm)					
	Power vs. Cha	nnel	Power vs. Data Rate									
Channel	Frequency	MCS Index	Channel	MCS Index								
Chamilei	(MHz)	MCS8	Chamilei	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15		
CH 38	5190	13.39	CH 46	16.07	16.06	16.06	16.03	15.92	16.01	16.04		
CH 46	5230	16.08	CH 40	10.07	10.00	10.00	10.03	15.92	10.01	16.04		
CH 54	5270	15.59	CH 54	15.58	15.57	15.58	15.58	15.58	15.49	15.57		
CH 62	5310	15.24	CH 54	10.06	15.57	15.56	15.56	15.56	15.49	15.57		
CH 102	5510	15.74										
CH 110	5550	15.94	CH 110	15.93	15.93	15.93	15.93	15.91	15.91	15.79		
CH 134	5670	15.36										
CH 151	5755	16.47	CH 151	16.46	16.46	16.46	16.45	16.46	16.41	16.45		
CH 159	5795	16.37	CH ISI	10.40	10.40	10.40	16.45	10.40	10.41	16.45		

- Per KDB 248227 D01 v01r02, choose the highest output power channel to test SAR and determine further SAR exclusion
- 2. For each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 0.25dB higher than those measured at the lowest data rate.
- 3. Per KDB 248227 D01 v01r02, 11n-HT40 output power is less than 1/4 dB higher than 802.11n HT20 mode, thus the SAR can be excluded.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 33 of 44
Report Issued Date : Mar. 25, 2013

Report No.: FA322535




Report No. : FA322535

## 11. Exposure Positions Consideration

#### <Tablet PC>

## Edge 1



## Edge 3

### Front View

Antennas	Wireless Interface
WLAN Main Antenna	WLAN 5GHz
Ant 0(Tx/Rx)	WLAN 2.4GHz
WLAN Aux Antenna Ant	WLAN 5GHz
1(Tx/Rx)	WLAN 2.4GHz
I(IX/KX)	Bluetooth 2.4GHz

#### <Transmission configuration>

Wireless Interface	SISO	Mode	MIMO Mode		
Wireless interrace	WLAN Antenna 0 (Tx / Rx)	WLAN Antenna 1 (Tx / Rx)	WLAN Antenna 0+1 (Tx / Rx)		
2.4GHz Bluetooth		yes			
WLAN2.4GHz 802.11b/g	yes	yes			
WLAN2.4GHz 802.11 HT20/HT40	yes	yes	yes		
WLAN5GHz 802.11a	yes	yes			
WLAN5GHz 802.11 HT20/HT40	yes	yes	yes		

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 34 of 44
Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01



#### <WLAN/Bluetooth SAR test exclusion table>

5 5 50	Wireless Interface	802.11b Ant 0	802.11b Ant 1	802.11n Ant 0+1	802.11a Ant 0	802.11a Ant 1	802.11a Ant 0+1	Bluetooth
Exposure Position	Tune-up Maximum power (dBm)	17	16	16.5	20	20	17	6
	Tune-up Maximum rated power (mW)	50.12	39.81	44.67	100.00	100.00	50.12	3.98
	Antenna to user (mm)	5	5	5	5	5	5	5
Bottom Face	SAR exclusion threshold (mW)	10	10	10	6	6	6	10
	SAR testing required?	YES	YES	YES	YES	YES	YES	NO
	Antenna to user (mm)	90.3	90.3	90.3	90.3	90.3	90.3	90.3
Edge 1	SAR exclusion threshold (mW)	499	499	499	465	465	465	172
	SAR testing required?	NO	NO	NO	NO	NO	NO	NO
	Antenna to user (mm)	5	227.96	5	5	227.96	5	227.96
Edge 2	SAR exclusion threshold (mW)	10	1875	10	6	1842	6	434
	SAR testing required?	YES	NO	YES	YES	NO	YES	NO
	Antenna to user (mm)	100.9	100.9	100.9	100.9	100.9	100.9	100.9
Edge 3	SAR exclusion threshold (mW)	605	605	605	571	571	571	192
	SAR testing required?	NO	NO	NO	NO	NO	NO	NO
	Antenna to user (mm)	227.96	5	5	227.96	5	5	5
Edge 4	SAR exclusion threshold (mW)	1875	10	10	1842	6	6	10
	SAR testing required?	NO	YES	YES	NO	YES	YES	NO

**Report No. : FA322535** 

#### Note:

- 1. Maximum power is the source-based time-average power and represents the maximum RF output power among production units
- 2. Per KDB 447498 D01v05, for larger devices, the *test separation distance* is determined by the closest separation between the antenna and the user.
- 3. Per KDB 447498 D01v05, standalone SAR test exclusion threshold is applied; If the distance of the antenna to the user is < 5mm, 5mm is used to determine SAR exclusion threshold
- 4. Per KDB 447498 D01v05, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 5. Per KDB 447498 D01v05, at 100 MHz to 6 GHz and for *test separation distances* > 50 mm, the SAR test exclusion threshold is determined according to the following
  - a) [Threshold at 50 mm in step 1) + (test separation distance 50 mm)·( f(MHz)/150)] mW, at 100 MHz to 1500 MHz
  - b) [Threshold at 50 mm in step 1) + (test separation distance 50 mm)·10] mW at > 1500 MHz and ≤ 6 GHz

 SPORTON INTERNATIONAL INC.
 Page Number
 : 35 of 44

 TEL: 886-3-327-3456
 Report Issued Date
 : Mar. 25, 2013

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

FCC ID: YE3600B

## 12. SAR Test Results

#### Note:

- 1. Per KDB 447498 D01v05, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance. Scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
  - Reported SAR(W/kg)= Measured SAR(W/kg)\* Scaling Factor
- 2. Per KDB 447498 D01v05, for each exposure position, if the highest output channel reported SAR ≤0.8W/kg, other channels SAR testing is not necessary.
- 3. Per KDB 447498 D01v05, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
  - · ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
  - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
  - · ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

### 12.1 Test Records for Body SAR Test

### <WLAN SAR DTS>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ant	Ch.	Freq. (MHz)	Data Rate	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured SAR 1g (W/kg)	Scaled SAR 1g (W/kg)
1	WLAN2.4GHz	802.11b	Bottom Face	0cm	Ant 0	6	2437	1Mbps	16.75	17	1.060	-0.06	0.055	0.058
2	WLAN2.4GHz	802.11b	Edge 2	0cm	Ant 0	6	2437	1Mbps	16.75	17	1.060	0.07	0.208	0.221
3	WLAN2.4GHz	802.11b	Bottom Face	0cm	Ant 1	1	2412	1Mbps	15.69	16	1.075	0.13	0.069	0.074
4	WLAN2.4GHz	802.11b	Edge 4	0cm	Ant 1	1	2412	1Mbps	15.69	16	1.075	0	0.271	0.291
5	WLAN2.4GHz	802.11n-HT20	Bottom Face	0cm	Ant 0+1	6	2437	MCS8	16.12	16.5	1.090	0.06	0.022	0.024
6	WLAN2.4GHz	802.11n-HT20	Edge 2	0cm	Ant 0+1	6	2437	MCS8	16.12	16.5	1.090	0.02	0.073	0.080
7	WLAN2.4GHz	802.11n-HT20	Edge 4	0cm	Ant 0+1	6	2437	MCS8	16.12	16.5	1.090	0.02	0.111	<mark>0.121</mark>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ant	Ch.	Freq. (MHz)	Data Rate	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured SAR 1g (W/kg)	Scaled SAR 1g (W/kg)
32	WLAN5GHz	802.11a	Bottom Face	0cm	Ant 0	149	5745	6Mbps	14.36	14.5	1.032	0.08	0.021	0.022
33	WLAN5GHz	802.11a	Edge 2	0cm	Ant 0	149	5745	6Mbps	14.36	14.5	1.032	0.11	0.189	0.195
34	WLAN5GHz	802.11n-HT40	Edge 2	0cm	Ant 0	151	5755	MCS0	19.49	20	1.123	-0.02	0.762	0.856
38	WLAN5GHz	802.11n-HT40	Edge 2	0cm	Ant 0	159	5795	MCS0	19.24	20	1.190	-0.07	0.717	0.853
35	WLAN5GHz	802.11a	Bottom Face	0cm	Ant 1	149	5745	6Mbps	15.86	16	1.032	-0.01	0.023	0.024
36	WLAN5GHz	802.11a	Edge4	0cm	Ant 1	149	5745	6Mbps	15.86	16	1.032	-0.16	0.194	0.200
37	WLAN5GHz	802.11n-HT40	Edge4	0cm	Ant 1	151	5755	MCS0	19.67	20.5	1.210	-0.18	0.517	<mark>0.626</mark>
38	WLAN5GHz	802.11n-HT20	Bottom Face	0cm	Ant 0+1	149	5745	MCS8	16.54	17	1.113	-0.1	0.119	0.132
39	WLAN5GHz	802.11n-HT20	Edge2	0cm	Ant 0+1	149	5745	MCS8	16.54	17	1.113	0.01	0.124	<mark>0.138</mark>
40	WLAN5GHz	802.11n-HT20	Edge4	0cm	Ant 0+1	149	5745	MCS8	16.54	17	1.113	-0.07	0.114	0.127

SPORTON INTERNATIONAL INC.

FAX: 886-3-328-4978 FCC ID: YE3600B

TEL: 886-3-327-3456

Page Number : 36 of 44
Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01



## <WLAN SAR NII>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ant	Ch.	Freq. (MHz)	Data Rate	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured SAR 1g (W/kg)	Scaled SAR 1g (W/kg)
8	WLAN5GHz	802.11a	Bottom Face	0cm	Ant 0	36	5180	6Mbps	16.05	16.5	1.109	-0.09	0.09	0.100
9	WLAN5GHz	802.11a	Edge2	0cm	Ant 0	36	5180	6Mbps	16.05	16.5	1.109	0.03	0.268	0.297
10	WLAN5GHz	802.11n-HT20	Edge2	0cm	Ant 0	44	5220	MCS0	16.49	17	1.125	-0.06	0.274	0.308
11	WLAN5GHz	802.11n-HT40	Edge2	0cm	Ant 0	46	5230	MCS0	16.37	16.5	1.029	-0.1	0.253	0.260
18	WLAN5GHz	802.11a	Bottom Face	0cm	Ant 0	64	5320	6Mbps	16.24	16.5	1.061	0.12	0.12	0.127
19	WLAN5GHz	802.11a	Edge2	0cm	Ant 0	64	5320	6Mbps	16.24	16.5	1.061	0.05	0.222	0.236
25	WLAN5GHz	802.11a	Bottom Face	0cm	Ant 0	116	5580	6Mbps	16.37	16.5	1.030	-0.17	0.132	0.136
26	WLAN5GHz	802.11a	Edge 2	0cm	Ant 0	116	5580	6Mbps	16.37	16.5	1.030	0.07	0.373	<mark>0.384</mark>
12	WLAN5GHz	802.11a	Bottom Face	0cm	Ant 1	36	5180	6Mbps	15.58	16	1.101	-0.19	0.043	0.047
13	WLAN5GHz	802.11a	Edge4	0cm	Ant 1	36	5180	6Mbps	15.58	16	1.101	-0.08	0.152	<mark>0.167</mark>
14	WLAN5GHz	802.11n-HT20	Edge4	0cm	Ant 1	36	5180	MCS0	15.91	16	1.022	-0.16	0.152	0.155
20	WLAN5GHz	802.11a	Bottom Face	0cm	Ant 1	64	5320	6Mbps	15.89	16	1.025	-0.13	0.077	0.079
21	WLAN5GHz	802.11a	Edge4	0cm	Ant 1	64	5320	6Mbps	15.89	16	1.025	0.09	0.156	<mark>0.160</mark>
27	WLAN5GHz	802.11a	Bottom Face	0cm	Ant 1	116	5580	6Mbps	15.48	16	1.127	0.05	0.038	0.043
28	WLAN5GHz	802.11a	Edge 4	0cm	Ant 1	116	5580	6Mbps	15.48	16	1.127	0	0.224	<mark>0.252</mark>
15	WLAN5GHz	802.11n-HT20	Bottom Face	0cm	Ant 0+1	44	5220	MCS8	16.08	16.5	1.101	0.14	0.082	0.090
16	WLAN5GHz	802.11n-HT20	Edge2	0cm	Ant 0+1	44	5220	MCS8	16.08	16.5	1.101	0.16	0.114	<mark>0.126</mark>
17	WLAN5GHz	802.11n-HT20	Edge4	0cm	Ant 0+1	44	5220	MCS8	16.08	16.5	1.101	0.08	0.088	0.097
22	WLAN5GHz	802.11n-HT20	Bottom Face	0cm	Ant 0+1	64	5320	MCS8	15.85	16.5	1.163	0.14	0.088	0.102
23	WLAN5GHz	802.11n-HT20	Edge2	0cm	Ant 0+1	64	5320	MCS8	15.85	16.5	1.163	0.03	0.066	0.077
24	WLAN5GHz	802.11n-HT20	Edge4	0cm	Ant 0+1	64	5320	MCS8	15.85	16.5	1.163	-0.05	0.089	<mark>0.103</mark>
29	WLAN5GHz	802.11n-HT20	Bottom Face	0cm	Ant 0+1	116	5580	MCS8	15.94	16.5	1.138	0.13	0.103	0.117
30	WLAN5GHz	802.11n-HT20	Edge2	0cm	Ant 0+1	116	5580	MCS8	15.94	16.5	1.138	-0.04	0.158	0.180
31	WLAN5GHz	802.11n-HT20	Edge 4	0cm	Ant 0+1	116	5580	MCS8	15.94	16.5	1.138	0.14	0.118	<mark>0.134</mark>

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B

: 37 of 44 Page Number Report Issued Date: Mar. 25, 2013

Report No.: FA322535

: Rev. 01 Report Version



## 12.2 Highest SAR Plot

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2013/3/4

### #04\_WLAN2.4G\_802.11b\_Edge 4\_0cm\_Ch1;Ant 1

#### **DUT: 322535**

Communication System: 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1 Medium: MSL\_2450\_130304 Medium parameters used: f = 2412 MHz;  $\sigma = 1.913$  mho/m;  $\epsilon_r = 53.018$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4 °C; Liquid Temperature: 21.4 °C

#### DASY5 Configuration:

- Probe: ES3DV3 SN3270; ConvF(4.17, 4.17, 4.17); Calibrated: 2012/9/28;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2012/8/27
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1026
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

# **Configuration/Ch1/Area Scan (71x201x1):** Measurement grid: dx=12mm, dy=12mm Maximum value of SAR (interpolated) = 0.357 mW/g

### Configuration/Ch1/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm,


dz=5mm

Reference Value = 13.868 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 0.556 mW/g

SAR(1 g) = 0.271 mW/g; SAR(10 g) = 0.135 mW/g

Maximum value of SAR (measured) = 0.346 mW/g



TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 38 of 44
Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01



**Report No. : FA322535** 

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2013/3/7

### #34\_WLAN5G\_802.11n-HT40\_Edge 2\_0cm\_Ch151;Ant 0

#### **DUT: 322535**

Communication System: 802.11n; Frequency: 5755 MHz; Duty Cycle: 1:1

Medium: MSL 5G 130307 Medium parameters used: f = 5755 MHz;  $\sigma = 6.138$  mho/m;  $\epsilon_r = 46.626$ ;  $\rho =$ 

 $1000 \, \text{kg/m}^3$ 

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

#### DASY5 Configuration:

- Probe: EX3DV4 SN3661; ConvF(3.97, 3.97, 3.97); Calibrated: 2013/1/15;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2012/4/23
- Phantom: ELI v5.0 Left; Type: QDOVA002AA; Serial: TP:1131
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

#### Configuration/Ch151/Area Scan (71x231x1): Measurement grid: dx=10mm, dy=10mm Maximum value of SAR (interpolated) = 1.66 mW/g


## Configuration/Ch151/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm,

dz=1.4mm

Reference Value = 19.901 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 2.974 mW/g

SAR(1 g) = 0.762 mW/g; SAR(10 g) = 0.292 mW/gMaximum value of SAR (measured) = 1.78 mW/g



0 dB = 1.78 mW/g = 5.01 dB mW/g

SPORTON INTERNATIONAL INC.

FCC ID: YE3600B

Page Number : 39 of 44 TEL: 886-3-327-3456 Report Issued Date: Mar. 25, 2013 FAX: 886-3-328-4978 Report Version : Rev. 01



## 12.3 Simultaneous Multi-band Transmission Analysis

No.	Applicable Simultaneous Transmission Combination
1.	None

#### Note:

- 1. WLAN Main and Bluetooth cannot transmit simultaneously.
- 2. WLAN Aux and Bluetooth share the same antenna, and cannot transmit simultaneously.
- 3. EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, they will not transmit simultaneously.

Test Engineer: Aaron Chen, Ted Sun, Jack Wu, Anglo Chang and San Lin

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 40 of 44
Report Issued Date : Mar. 25, 2013

Report No.: FA322535

## 13. Uncertainty Assessment

The component of uncertainly may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainly by the statistical analysis of a series of observations is termed a Type An evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

Report No.: FA322535

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in Table 12.1

<b>Uncertainty Distributions</b>	Normal	Rectangular	Triangular	U-Shape
Multi-plying Factor <sup>(a)</sup>	1/k <sup>(b)</sup>	1/√3	1/√6	1/√2

- (a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity
- (b)  $\kappa$  is the coverage factor

#### **Table 13.1 Standard Uncertainty for Assumed Distribution**

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

 SPORTON INTERNATIONAL INC.
 Page Number
 : 41 of 44

 TEL: 886-3-327-3456
 Report Issued Date
 : Mar. 25, 2013

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

FCC ID: YE3600B



FCC SAR Test Report No.: FA322535

	Uncertainty	Probability		Ci	Ci	Standard	Standard	
Error Description	Value	Distribution	Divisor	(1g)	(10g)	Uncertainty	Uncertainty	
	(±%)					(1g)	(10g)	
Measurement System								
Probe Calibration	6.0	Normal	1	1	1	± 6.0 %	± 6.0 %	
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	± 1.9 %	± 1.9 %	
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	± 3.9 %	± 3.9 %	
Boundary Effects	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %	
Linearity	4.7	Rectangular	√3	1	1	± 2.7 %	± 2.7 %	
System Detection Limits	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %	
Readout Electronics	0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	
Response Time	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %	
Integration Time	2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %	
RF Ambient Noise	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	
RF Ambient Reflections	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	
Probe Positioner	0.4	Rectangular	√3	1	1	± 0.2 %	± 0.2 %	
Probe Positioning	2.9	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	
Max. SAR Eval.	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %	
Test Sample Related								
Device Positioning	2.9	Normal	1	1	1	± 2.9 %	± 2.9 %	
Device Holder	3.6	Normal	1	1	1	± 3.6 %	± 3.6 %	
Power Drift	5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %	
Phantom and Setup								
Phantom Uncertainty	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %	
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %	
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	0.43	± 1.6 %	± 1.1 %	
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	0.49	± 1.7 %	± 1.4 %	
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	0.49	± 1.5 %	± 1.2 %	
Combined Standard Uncertainty						± 11.0 %	± 10.8 %	
Coverage Factor for 95 %							K=2	
Expanded Uncertainty						± 22.0 %	± 21.5 %	

Table 13.2 Uncertainty Budget for frequency range 300 MHz to 3 GHz according to IEEE 1528-2003

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 42 of 44
Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01



FCC SAR Test Report No.: FA322535

	Uncertainty	Probability		Ci	Ci	Standard	Standard	
Error Description	Value	Distribution	Divisor	(1g)	(10g)	Uncertainty	Uncertainty	
	(±%)					(1g)	(10g)	
Measurement System								
Probe Calibration	6.55	Normal	1	1	1	± 6.55 %	± 6.55 %	
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	± 1.9 %	± 1.9 %	
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	± 3.9 %	± 3.9 %	
Boundary Effects	2.0	Rectangular	√3	1	1	± 1.2 %	± 1.2 %	
Linearity	4.7	Rectangular	√3	1	1	± 2.7 %	± 2.7 %	
System Detection Limits	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %	
Readout Electronics	0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	
Response Time	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %	
Integration Time	2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %	
RF Ambient Noise	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	
RF Ambient Reflections	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	
Probe Positioner	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %	
Probe Positioning	9.9	Rectangular	√3	1	1	± 5.7 %	± 5.7 %	
Max. SAR Eval.	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %	
Test Sample Related								
Device Positioning	2.9	Normal	1	1	1	± 2.9 %	± 2.9 %	
Device Holder	3.6	Normal	1	1	1	± 3.6 %	± 3.6 %	
Power Drift	5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %	
Phantom and Setup								
Phantom Uncertainty	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %	
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %	
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	0.43	± 1.6 %	± 1.1 %	
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	0.49	± 1.7 %	± 1.4 %	
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	0.49	± 1.5 %	± 1.2 %	
Combined Standard Uncertainty	Combined Standard Uncertainty							
Coverage Factor for 95 %							K=2	
Expanded Uncertainty						± 25.6 %	± 25.2 %	

Table 13.3 Uncertainty Budget for frequency range 3 GHz to 6 GHz according to Dasy5 user manual

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : 43 of 44
Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01



## 14. References

[1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"

**Report No. : FA322535** 

: 44 of 44

: Rev. 01

Report Version

- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- IEEE Std. 1528-2003, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- [4] FCC OET Bulletin 65 (Edition 97-01) Supplement C (Edition 01-01), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields", June 2001
- SPEAG DASY System Handbook
- [6] FCC KDB 248227 D01 v01r02, "SAR Measurement Procedures for 802.11 a/b/g Transmitters", May 2007
- [7] FCC KDB 447498 D01 v05, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", October 2012
- FCC KDB 616217 D04 v01, "SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers", October 2012

SPORTON INTERNATIONAL INC. Page Number TEL: 886-3-327-3456 Report Issued Date: Mar. 25, 2013

FAX: 886-3-328-4978 FCC ID: YE3600B



## Appendix A. Plots of System Performance Check

The plots are shown as follows.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B Page Number : A1 of A1
Report Issued Date : Mar. 25, 2013
Report Version : Rev. 01



#### Appendix B. Plots of SAR Measurement

The plots are shown as follows.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B

Page Number : B1 of B1 Report Issued Date: Mar. 25, 2013

**Report No. : FA322535** 



#### Appendix C. **DASY Calibration Certificate**

The DASY calibration certificates are shown as follows.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: YE3600B

Page Number : C1 of C1 Report Issued Date: Mar. 25, 2013

**Report No. : FA322535**