



TEST REPORT

Part 15 Subpart C 15.247

Equipment under test In-vehicle Infotainment System

Model name XSG3CB2

FCC ID YE4XSG3CB2

Applicant Glosys Inc.

Manufacturer Glosys Inc.

Date of test(s) 2020.04.06 ~ 2020.04.17

Date of issue 2020.04.17

Issued to

Glosys Inc.

#510, 40, Omokcheon-ro 152beon-gil, Gwonseon-gu, Suwon-si,
Gyeonggi-do, Korea

Tel: +82-31-291-1450 / Fax : 82-31-291-1451

Issued by

KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,

Gyeonggi-do, 14057, Korea

473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea

Tel: +82-31-425-6200 / Fax: +82-31-424-0450

Test and report completed by :	Report approval by :
Yeong-Jun, Cho Test engineer	Young-Jin, Lee Technical manager

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-20T0078
Page (2) of (48)

Revision history

Revision	Date of issue	Test report No.	Description
-	2020.04.17	KES-RF-20T0078	Initial

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr

TABLE OF CONTENTS

1.	General information.....	4
1.1.	EUT description	4
1.2.	Requirements for Bluetooth transmitter	5
1.3.	Test configuration.....	6
1.4.	Device modifications.....	6
1.5.	Accessory information.....	6
1.6.	Sample calculation	6
1.7.	Measurement Uncertainty	6
1.8.	Frequency/channel operations	7
2.	Summary of tests	8
Note1 : This device is installed only on vehicles and is used with DC power.		8
3.	Test results	9
3.1.	20 dB bandwidth	9
3.2.	Output power.....	12
3.3.	Carrier frequency separation	14
3.4.	Number of hopping frequency.....	16
3.5.	Time of occupancy	18
3.6.	Radiated restricted band and emissions.....	22
3.7.	Conducted band edge and out of band emissions	41
Appendix A.	Measurement equipment	47
Appendix B.	Test setup photo.....	48

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-20T0078
Page (4) of (48)

1. General information

Applicant: Glosys Inc.
Applicant address: #510, 40, Omokcheon-ro 152beon-gil, Gwonseon-gu, Suwon-si,
Gyeonggi-do, Korea
Test site: KES Co., Ltd.
Test site address: 3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,
Gyeonggi-do, 14057, Korea
473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea
Test Facility FCC Accreditation Designation No.: KR0100, Registration No.: 444148
FCC rule part(s): 15.247
FCC ID: YE4XSG3CB2
Test device serial No.: Production Pre-production Engineering

1.1. EUT description

Equipment under test In-vehicle Infortainment System
Frequency range 2 402 MHz ~ 2 480 MHz (BDR / EDR)
Model: XSG3CB2
Modulation technique GFSK, $\pi/4$ DQPSK, 8DPSK
Number of channels 2 402 MHz ~ 2 480 MHz (BDR / EDR) : 79ch
Antenna specification Antenna type : PCB Antenna // Peak gain: -4.54 dBi
Power source DC 12 V
H/W version V 2.2
S/W version V 0.91

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr



1.2. Requirements for Bluetooth transmitter

15.247(a)(1) that the rx input bandwidths shift frequencies in synchronization with the transmitted signals.

Pseudorandom frequency hopping sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The nominal hop rate is 1 600 hops/s.

Equal hopping frequency use

The channels of this system will be used equally over the long-term distribution of the hopsets.

Example of a 79 hopping sequence in data mode:

67 59 57 49 27 77 76 69 20 10 36 66 35 62 15 58 68 41 34 61 45 14 53 70 29 25 18 06 40 33 38 65 24 46 44
12 47 17 71 60 28 43 09 02 75 42 30 04 54 48 37 00 50 03 19 07 01 32 22 64 78 08 26 39 31 13 63 52 51 11
21 05 23 55 16 56 74 72 73 24 04 18 71 22 23 08 10 62 25 65 03 39 47 28 58 53 67 06 64 20 73 70 37 41 61
45 74 12 54 21 76 56 43 16 11 17 30 29 27 15 31 42 52 66 77 40 35 57 32 48 60 49 63 59 05 44 07 72 38 51
26 14 75 01 68 36 46 13 34 69 09 19 33 02 50 78 55 09

System receiver input bandwidth

Each channel bandwidth is 1 MHz.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.

15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection/ hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.



1.3. Test configuration

The **Glosys Inc. // In-vehicle Infortainment System // XSG3CB2 // FCC ID: YE4XSG3CB2** was tested according to the specification of EUT, the EUT must comply with following standards and KDB documents.

FCC Subpart C 15.247

KDB 558074 D01 V05r02

ANSI C63.10-2013

1.4. Device modifications

N/A

1.5. Accessory information

Equipment	Manufacturer	Model	Serial No.	Power source
-	-	-	-	-

1.6. Sample calculation

Where relevant, the following sample calculation is provided

For all conducted test items :

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 0.98 + 10 = 10.98 \text{ (dB)}\end{aligned}$$

For Radiation test :

Field strength level ($\text{dB}\mu\text{V}/\text{m}$) = Measured level ($\text{dB}\mu\text{V}$) + Antenna factor (dB) + Cable loss (dB) – Amplifier gain (dB)

1.7. Measurement Uncertainty

Test Item	Uncertainty	
Uncertainty for Conduction emission test	2.62 dB	
Uncertainty for Radiation emission test (include Fundamental emission)	9kHz - 30MHz	4.54 dB
	30MHz - 1GHz	4.36 dB
	Above 1GHz	5.00 dB

Note. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



1.8. Frequency/channel operations

Ch.	Frequency (MHz)	Rate(Mbps)
00	2402	BDR 1 Mbps, EDR 2 Mbps, EDR 3 Mbps
.	.	.
40	2442	BDR 1 Mbps, EDR 2 Mbps, EDR 3 Mbps
.	.	.
78	2480	BDR 1 Mbps, EDR 2 Mbps, EDR 3 Mbps

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-20T0078
Page (8) of (48)

2. Summary of tests

Reference	Test description	Test results
15.247(a)(1)	20 dB bandwidth	Pass
15.247(b)(1)	Output power	Pass
15.247(a)(1)	Channel separation	Pass
15.247(a)(1)(iii)	Number of channels	Pass
15.247(a)(1)(iii)	Time of occupancy	Pass
15.205, 15.209	Radiated restricted band and emission	Pass
15.247(d)	Conducted band edge and out of band emissions	Pass
15.207(a)	AC conducted emissions	N/A ^{Note1}

Note1 : This device is installed only on vehicles and is used with DC power.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr


3. Test results

3.1. 20 dB bandwidth

Test procedure

ANSI C63.10-2013 clause 6.9.2 and 6.9.3

Test setup



Test setting


1. Span = Set between two times and five times the OBW
2. RBW \geq 1 % to 5 % of the OBW
3. VBW \geq 3 * RBW
4. Sweep = Auto
5. Detector function = Peak
6. Sweep = Auto couple
7. Trace mode = Max hold
8. All the trace to stabilize

Limit

Not applicable

Test results


Frequency(MHz)	Channel no.	Data rate(Mbps)	Measured bandwidth(MHz)	Occupied bandwidth(MHz)
2 402	00	BDR 1 Mbps	0.808	0.876
2 442	40		0.805	0.872
2 480	78		0.806	0.871
2 402	00	EDR 2 Mbps	1.244	1.193
2 442	40		1.248	1.198
2 480	78		1.249	1.198
2 402	00	EDR 3 Mbps	1.206	1.181
2 442	40		1.207	1.187
2 480	78		1.206	1.185



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.


The authenticity of the test report, contact shchoi@kes.co.kr

3.2. Output power

Test procedure

ANSI C63.10-2013 - Section 7.8.5

Test setup



Test setting

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

Limit

According to §15.247(a)(1), Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

According to §15.247(b)(1), For frequency hopping systems operating in the 2 400 ~ 2 483.5 MHz employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5 725 ~ 5 805 MHz band: 1 Watt.

According to §15.247(b)(4), The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.

**Test results**

Frequency(MHz)	Channel no.	Data rate(Mbps)	Peak Power (dBm) ^{Note1}	Average Power (dBm) ^{Note1}	Power Limit (dBm)
2 402	00	BDR 1 Mbps	-0.96	-1.37	20.97
2 442	40		-0.73	-1.13	20.97
2 480	78		-0.61	-1.00	20.97
2 402	00	EDR 2 Mbps	-1.95	-4.19	20.97
2 442	40		-1.44	-3.65	20.97
2 480	78		-1.26	-3.49	20.97
2 402	00	EDR 3 Mbps	-1.65	-4.24	20.97
2 442	40		-1.54	-3.85	20.97
2 480	78		-0.99	-3.34	20.97

Note.


1. The peak power and average power was tested using an power meter, power sensor.

3.3. Carrier frequency separation

Test procedure

ANSI C63.10-2013 - Section 7.8.2

Test setup



Test Setting

1. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
2. Span = wide enough to capture the peaks of two adjacent channels
3. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
4. Video (or Average) Bandwidth (VBW) \geq RBW
5. Sweep = auto
6. Detector function = peak
7. Trace = max hold
8. Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.

Limit


According to 15.247(a)(1), frequency hopping system operating in 2 400 ~ 2 483.5 MHz. Band may have hopping channel carrier frequencies that are separated by 25 kHz or two-third of 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Note:

EUT does not support AFH mode.

Test results

Frequency(MHz)	Channel no.	Data rate(Mbps)	Channel Separation (MHz)	Minimum limit (MHz)
2 442	40	BDR 1 Mbps	1.001	0.536
2 442	40	EDR 3 Mbps	1.009	0.804



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.


The authenticity of the test report, contact shchoi@kes.co.kr

3.4. Number of hopping frequency

Test procedure

ANSI C63.10-2013 - Section 7.8.3

Test setup



Test setting

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings.

1. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
2. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
3. VBW \geq RBW.
4. Sweep = auto
5. Detector function = peak
6. Trace = max hold


All the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Limit

According to 15.247(a)(1)(iii), for frequency hopping system operating in the 2 400 ~ 2 483.5 MHz bands shall use at least 15 hopping frequencies.

Test results

Frequency	Data rate(Mbps)	Number of hopping frequency	Limit
2402 ~ 2480 MHz	BDR 1 Mbps	79	≥ 15
2402 ~ 2480 MHz	EDR 3 Mbps	79	≥ 15



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.


The authenticity of the test report, contact shchoi@kes.co.kr

3.5. Time of occupancy

Test procedure

ANSI C63.10-2013 - Section 7.8.4

Test setup



Test setting

1. The EUT must have its hopping function enabled.
2. Span = zero span, centered on a hopping channel
3. RBW shall be \leq channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected dwell time per channel.
4. Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
5. Detector function = peak
6. Trace = max hold

Limit

According to 15.247(a)(1)(iii), for frequency hopping system operating in the 2 400 ~ 2 483.5 MHz band, the average time of occupancy on any frequency shall not be greater than 0.4 second within a 31.6 second period.

A period time = $0.4(s) \times 79 = 31.6(s)$

Time of occupancy on the TX channel in 31.6 sec

= time domain slot length \times (hop rate \div number of hop per channel) \times 31.6

**Operation mode: GFSK , $\pi/4$ -DQPSK, 8DPSK**

Packet type	Frequency (MHz)	Dwell time (ms)	Time of occupancy on the Tx channel in 31.6 sec (ms)	Limit for time of occupancy on the Tx channel in 31.6 sec (ms)
DH1	2 442	0.420	134.40	400
DH3	2 442	1.774	283.84	400
DH5	2 442	3.026	322.77	400
2-DH1	2 442	0.432	138.24	400
2-DH3	2 442	1.684	269.44	400
2-DH5	2 442	2.935	313.07	400
3-DH1	2 442	0.433	138.56	400
3-DH3	2 442	1.683	269.28	400
3-DH5	2 442	2.936	313.17	400

Note:**Normal Mode**

DH1: Dwell time (ms) \times $[(1600 \div 2) \div 79] \times 31.6(s) = 134.40$ (ms)

DH3: Dwell time (ms) \times $[(1600 \div 4) \div 79] \times 31.6(s) = 283.84$ (ms)

DH5: Dwell time (ms) \times $[(1600 \div 6) \div 79] \times 31.6(s) = 322.77$ (ms)

2-DH1: Dwell time (ms) \times $[(1600 \div 2) \div 79] \times 31.6(s) = 138.24$ (ms)


2-DH3: Dwell time (ms) \times $[(1600 \div 4) \div 79] \times 31.6(s) = 269.44$ (ms)

2-DH5: Dwell time (ms) \times $[(1600 \div 6) \div 79] \times 31.6(s) = 313.07$ (ms)

3-DH1: Dwell time (ms) \times $[(1600 \div 2) \div 79] \times 31.6(s) = 138.56$ (ms)

3-DH3: Dwell time (ms) \times $[(1600 \div 4) \div 79] \times 31.6(s) = 269.28$ (ms)


3-DH5: Dwell time (ms) \times $[(1600 \div 6) \div 79] \times 31.6(s) = 313.17$ (ms)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.


The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr


3.6. Radiated restricted band and emissions

Test setup


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr

**Test procedure**

1. The EUT is placed on a turntable, which is 0.8 m (below 1 GHz) and 1.5 m (above 1 GHz) ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

7. Spectrum analyzer settings for $f < 1$ GHz:

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz

VBW \geq RBW

Sweep = auto

Detector function = quasi peak

Trace = max hold

8. Spectrum analyzer settings for $f \geq 1$ GHz: Peak

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

9. Spectrum analyzer settings for $f \geq 1$ GHz: Average

Average value of pulsed emissions.

Unless otherwise specified, when the radiated emission limits are expressed in terms of the average value of the emission and pulsed operation is employed, the average measurement shall be determined from the peak field strength after correcting for the worst-case duty cycle as described in 7.5 in ANSI 63.10-2013 & Procedure 9(b) in the KDB 558074 v05r02.

Note.

1. The spectrum is measured from 9 kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1 GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20 dB of the respective limits were not reported.
2. The loop antenna was investigated with three polarizations, and horizontal and vertical polarizations were reported as the worst case.
3. According to 15.35 (c), as a "duty cycle correction factor", pulse averaging with $20 \log(\text{duty cycle})$ has to be used.
Duty cycle correction factor = $20 \log(\text{dwell time}/100 \text{ ms})$
4. Emissions below 18 GHz were measured at a 3 meter test distance while emissions above 18 GHz were measured at a 1 meter test distance with the application of a distance correction factor.
5. Average test would be performed if the peak result were greater than the average limit.
6. Field strength(dB_μV/m) = Level(dB_μV) + Correction factors(dB/m) + Cable loss(dB) + or F_d(dB)
7. Correction factors(dB/m) = Antenna factor(dB/m) + Cable loss(dB) + or Amp. gain(dB)
8. Margin(dB) = Limit(dB_μV/m) - Field strength(dB_μV/m)
9. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z, it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.
10. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
11. According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open field test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.
12. $f < 30 \text{ MHz}$, extrapolation factor of 40 dB/decade of distance. $F_d = 40 \log(D_m / D_s)$
 $f \geq 30 \text{ MHz}$, extrapolation factor of 20 dB/decade of distance. $F_d = 20 \log(D_m / D_s)$

Where:

F_d = Distance factor in dB
 D_m = Measurement distance in meters
 D_s = Specification distance in meters

**Limit**

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

Frequency (MHz)	Distance (Meters)	Radiated (μV/m)
0.009 ~ 0.490	300	2400/F(kHz)
0.490 ~ 1.705	30	24000/F(kHz)
1.705 ~ 30.0	30	30
30 ~ 88	3	100**
88 ~ 216	3	150**
216 ~ 960	3	200**
Above 960	3	500


**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 MHz, 76 ~ 88 MHz, 174 ~ 216 MHz or 470 ~ 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

Test results (Below 30 MHz)

Mode: BDR(Worst case)

Distance of measurement: 3 meter

Channel: 78(Worst case)



Note.

1. No spurious emission were detected below 30 MHz.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.


The authenticity of the test report, contact shchoi@kes.co.kr

Test results (Below 1 000 MHz) – Worst case

Mode: BDR(Worst case)

Distance of measurement: 3 meter

Channel: 78(Worst case)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr

Test results (Above 1 000 MHz)


Mode:	BDR
Transfer rate:	1 Mbps
Distance of measurement:	3 meter
Channel:	00

- Spurious

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ N/m)	Limit (dB μ N/m)	Margin (dB)
1 122.29	47.59	Peak	V	-6.13	-	41.46	74.00	32.54
1 934.80	45.07	Peak	H	4.31	-	49.38	74.00	24.62

- Band edge


Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ N/m)	Limit (dB μ N/m)	Margin (dB)
2 373.04	42.89	Peak	V	0.50	-	43.39	74.00	30.61
2 379.43	42.81	Peak	H	0.48	-	43.29	74.00	30.71



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.


Mode: BDR

Transfer rate: 1 Mbps

Distance of measurement: 3 meter

Channel: 40

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 127.89	47.59	Peak	H	-6.11	-	41.48	74.00	32.52
1 627.44	48.14	Peak	V	-0.94	-	47.20	74.00	26.80



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr

Mode: BDR

Transfer rate: 1 Mbps

Distance of measurement: 3 meter


Channel: 78

- Spurious

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ N/m)	Limit (dB μ N/m)	Margin (dB)
1 028.30	47.38	Peak	V	-6.40	-	40.98	74.00	33.02
1 032.50	47.04	Peak	H	-6.39	-	40.65	74.00	33.35

- Band edge


Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ N/m)	Limit (dB μ N/m)	Margin (dB)
2 493.10	42.54	Peak	V	0.14	-	42.68	74.00	31.32
2 493.23	42.22	Peak	H	0.14	-	42.36	74.00	31.64



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

Mode: EDR

Transfer rate: 3 Mbps(Worst case)

Distance of measurement: 3 meter


Channel: 00

- Spurious

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ N/m)	Limit (dB μ N/m)	Margin (dB)
1 247.68	46.01	Peak	V	-5.78	-	40.23	74.00	33.77
1 602.24	46.97	Peak	H	-1.36	-	45.61	74.00	28.39

- Band edge


Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ N/m)	Limit (dB μ N/m)	Margin (dB)
2 359.93	42.43	Peak	V	0.53	-	42.96	74.00	31.04
2 376.10	42.61	Peak	H	0.49	-	43.10	74.00	30.90



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

Mode: EDR


Transfer rate: 3 Mbps(Worst case)

Distance of measurement: 3 meter

Channel: 40

- Spurious

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 081.29	47.70	Peak	V	-6.24	-	41.46	74.00	32.54
1 627.44	47.72	Peak	H	-0.94	-	46.78	74.00	27.22


Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr

Mode: EDR

Transfer rate: 3 Mbps(Worst case)

Distance of measurement: 3 meter


Channel: 78

- Spurious

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ N/m)	Limit (dB μ N/m)	Margin (dB)
1 029.30	47.47	Peak	H	-6.40	-	41.07	74.00	32.93
1 160.88	46.74	Peak	V	-6.02	-	40.72	74.00	33.28

- Band edge


Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ N/m)	Limit (dB μ N/m)	Margin (dB)
2 492.17	42.10	Peak	H	0.15	-	42.25	74.00	31.75
2 494.55	42.17	Peak	V	0.14	-	42.31	74.00	31.69



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr




Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

Test results (18 GHz to 30 GHz) – Worst case

Mode:	BDR
Transfer rate:	1 Mbps
Distance of measurement:	3 meter
Channel:	78(Worst case)



Note.


1. No spurious emission were detected above 18 GHz.

Mode: EDR

Transfer rate: 3 Mbps(Worst case)

Distance of measurement: 3 meter

Channel: 78(Worst case)



Note.

1. No spurious emission were detected above 18 GHz.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.


The authenticity of the test report, contact shchoi@kes.co.kr

3.7. Conducted band edge and out of band emissions

Test procedure

ANSI C63.10-2013 - Section 7.8.6 and 7.8.8

Test setup




Test setting

1. Span = wide enough to capture the peak level of the in-band emission and all spurious emissions(e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.
2. RBW = 100 kHz
3. VBW \geq 300 kHz
4. Detector = Peak
5. Number of sweep points $\geq 2 \times$ Span/RBW
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Limit


According to 15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval , as permitted under paragraph(b)(3) of this section , the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section 15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section 15.205(a), must also comply the radiated emission limits specified in section 15.209(a) (see section 15.205(c))

Test results


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.


The authenticity of the test report, contact shchoi@kes.co.kr



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.


The authenticity of the test report, contact shchoi@kes.co.kr



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



The authenticity of the test report, contact shchoi@kes.co.kr



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-20T0078
Page (47) of (48)

Appendix A. Measurement equipment

Equipment	Manufacturer	Model	Serial No.	Cal. Day to next Cal. day
Spectrum Analyzer	R&S	FSV30	101389	2020.01.15 ~ 2021.01.15
Spectrum Analyzer	R&S	FSV40	101002	2019.06.24 ~ 2020.06.24
8360B Series Swept Signal Generator	HP	83630B	3844A00786	2020.01.15 ~ 2021.01.15
Vector Signal Generator	R&S	SMBV100A	1407.6004K02	2019.06.25 ~ 2020.06.25
Power Meter	Anritsu	ML2495A	1438001	2020.01.14 ~ 2021.01.14
Pulse Power Sensor	Anritsu	MA2411B	1339205	2020.01.14 ~ 2021.01.14
Attenuator	HP	8494B	2630A12857	2020.01.15 ~ 2021.01.15
Attenuator	KEYSIGHT	8493C	82506	2020.01.14 ~ 2021.01.14
Loop Antenna	Schwarzbeck	FMZB1513	225	2020.02.15 ~ 2021.02.15
Trilog-broadband antenna	SCHWARZBECK	VULB 9163	715	2019.09.20 ~ 2020.09.20
Horn Antenna	A.H	SAS-571	414	2020.01.31 ~ 2021.01.31
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA 9170550	2020.01.20 ~ 2021.01.20
Broadband Amplifier	Schwarzbeck	BBV9721	PS9721-003	2020.01.17 ~ 2021.01.17
Preamplifier	AGILENT	8449B	3008A01742	2020.01.02 ~ 2021.01.02
Amplifier	R&S	SCU 01	100603	2019.11.25 ~ 2020.11.25
EMI Test Receiver	R&S	ESU26	100551	2019.04.09 ~ 2020.04.09 2020.04.01 ~ 2021.04.01
DC Power supply	Agilent	6632B	MY43004090	2019.06.25 ~ 2020.06.25
RF Cable 1	Woken	-	#B-1	2020.04.06 (Cal. date)
RF Cable 2	Woken	-	#B-2	2020.04.06 (Cal. date)

* The RF cable cal. is measured every time before the test.

Peripheral devices

Device	Manufacturer	Model No.	Serial No.
Notebook computer	LG Electronics Inc.,	LGS53	306QCZP560949
Test Jig Board	N/A	N/A	N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact shchoi@kes.co.kr