

Report No.:ER/2015/80132 Issue Date: Oct. 16, 2015

Page: 2 of 13

## 1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

# 1.1 Standard Applicable

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Mobile device, the MPE is required.

According to §1.1310 and §2.1093 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

Frequency Range	Electric Field	Magnetic Field	Power Density	Averaging Time
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm <sup>2</sup> )	(minute)
	Limits for Genera	al Population/Uncon	trolled Exposure	
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-15000	/	/	1.0	30

F = frequency in MHz

# Prediction of MPE limit at a given distance Equation from page 18 of OET Bulletin 65, Edition 97-01

 $S=PG/4\pi R^2$ 

*Where:* S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號

<sup>\* =</sup> Plane-wave equipment power density



Report No.:ER/2015/80132 Issue Date: Oct. 16, 2015

Page: 3 of 13

# 802.11a Max. output power

#### 802.11a Main

СН	Frequency (MHz)	TOTAL POWER (dBm)	TOTAL POWER (mW)	ļ	QUIRED LIMIT dBm)		RESULT
36	5180	14.47	27.990		23.98		PASS
44	5220	14.46	27.925		23.98		PASS
48	5240	14.43	27.733	23.98		PASS	
52	5260	14.41	27.606	23.98 or 11+	·10log(B)	24.37	PASS
60	5300	14.48	28.054	23.98 or 11+	·10log(B)	24.34	PASS
64	5320	14.40	27.542	23.98 or 11+	·10log(B)	24.34	PASS
100	5500	14.42	27.669	23.98 or 11+	·10log(B)	24.31	PASS
116	5580	14.43	27.733	23.98 or 11+	·10log(B)	24.33	PASS
140	5700	14.47	27.990	23.98 or 11+	·10log(B)	24.37	PASS
149	5745	14.42	27.669		30		PASS
157	5785	14.39	27.479		30		PASS
165	5825	14.45	27.861		30		PASS

# MPE Prediction (802.11a 5150~5250)

Average output power at antenna input terminal:	14.47	(dBm)
Average output power at antenna input terminal:	27.989813	(mW)
Duty cycle:	95.1	(%)
Maximum Pav :	26.618312	(mW)
Peak Antenna gain (Maximum):	4.61	(dBi)
Peak Antenna gain (linear):	2.8906799	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5180	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)
Power density at predication frequency at 20 (cm)	0.015	(mW/cm^2)
	•	

#### **Measurement Result**

The predicted power density level at 20 cm is 0.015 mW/cm2.

This is below the uncontrolled exposure limit of 1 mW/cm2 at 5180MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留卯天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or approval of this document is unquited and find the prior that the full terms of the low. pearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號



Report No.:ER/2015/80132 Issue Date: Oct. 16, 2015

Page: 4 of 13

## MPE Prediction (802.11a 5250~5350)

Average output power at antenna input terminal:	14.48	(dBm)
Average output power at antenna input terminal:	28.054336	(mW)
Duty cycle:	95.1	(%)
Maximum Pav :	26.679674	(mW)
Peak Antenna gain (Maximum):	4.61	(dBi)
Peak Antenna gain (linear):	2.8906799	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5300	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)
Power density at predication frequency at 20 (cm)	0.015	(mW/cm^2)
Maggurament Pagult	-	

#### Measurement Result

The predicted power density level at 20 cm is 0.015 mW/cm2.

This is below the uncontrolled exposure limit of 1 mW/cm2 at 5300MHz.

# MPE Prediction (802.11a 5470~5725)

Average output power at antenna input terminal:	14.47	(dBm)			
Average output power at antenna input terminal:	27.989813	(mW)			
Duty cycle:	95.1	(%)			
Maximum Pav :	26.618312	(mW)			
Peak Antenna gain (Maximum):	4.45	(dBi)			
Peak Antenna gain (linear):	2.7861212	(numeric)			
Prediction distance:	20	(cm)			
Prediction frequency:	5700	(MHz)			
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)			
Power density at predication frequency at 20 (cm)	0.015	(mW/cm^2)			
Measurement Result					

The predicted power density level at 20 cm is 0.015 mW/cm2.

This is below the uncontrolled exposure limit of 1 mW/cm2 at 5700MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

家非方角就明 - 比較容易未僅對測減之樣必負責 | 阿時此樣必僅体留別之 - 本教者を無率之の音曲部引 - 木可能价模装。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司 t (886-2) 2299-3279



Report No.:ER/2015/80132 Issue Date: Oct. 16, 2015

Page: 5 of 13

# MPE Prediction (802.11a 5725~5850)

Average output power at antenna input terminal:	14.45	(dBm)
Average output power at antenna input terminal:	27.861212	(mW)
Duty cycle:	95.1	(%)
Maximum Pav :	26.496012	(mW)
Peak Antenna gain (Maximum):	3.42	(dBi)
Peak Antenna gain (linear):	2.1978599	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5825	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)
Power density at predication frequency at 20 (cm)	0.012	(mW/cm^2)

#### **Measurement Result**

The predicted power density level at 20 cm is 0.012 mW/cm2.

This is below the uncontrolled exposure limit of 1 mW/cm2 at 5825MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未總本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appropriate in languaged and the propriate of the follows are proposed to the language and the fillest extent of the language. pearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號



Report No.:ER/2015/80132 Issue Date: Oct. 16, 2015

Page: 6 of 13

## 802.11n\_HT20M Max. output power

#### 802.11n\_HT20\_MIMO

СН	Frequency (MHz)		E POWER 3m)	TOTAL POWER	TOTAL POWER	REQUIRED LIMIT (dBm)		RESULT	
	(IVIII <i>Z)</i>	CHAIN 0	CHAIN 1	(dBm)	(mW)				
36	5180	15.51	12.99	17.44	55.470		22.36		PASS
44	5220	15.16	12.98	17.22	52.670	22.36			PASS
48	5240	15.17	12.88	17.18	52.294	22.36		PASS	
52	5260	15.43	13.25	17.49	56.049	22.36	or 11+10log(B)	24.31	PASS
60	5300	15.23	13.4	17.42	55.220	22.36	or 11+10log(B)	24.32	PASS
64	5320	15.24	13.55	17.49	56.066	22.36	or 11+10log(B)	24.36	PASS
100	5500	14.38	14.39	17.40	54.895	22.52	or 11+10log(B)	24.39	PASS
116	5580	13.85	14.49	17.19	52.385	22.52	or 11+10log(B)	24.32	PASS
140	5700	13.82	14.90	17.40	55.002	22.52	or 11+10log(B)	24.40	PASS
149	5745	13.93	14.62	17.30	53.691		29.57		PASS
157	5785	13.86	14.55	17.23	52.832		29.57		PASS
165	5825	13.97	14.53	17.27	53.325		29.57		PASS

# MPE Prediction (802.11n\_HT20 5150~5250)

MIMO gain= G+(10 logN)= 4.61+3.01= 7.62dBm

Average output power at antenna input terminal:	17.44	(dBm)
Average output power at antenna input terminal:	55.462571	(mW)
Duty cycle:	95.2	(%)
Maximum Pav :	52.800368	(mW)
Peak Antenna gain (Maximum):	7.62	(dBi)
Peak Antenna gain (linear):	5.7809605	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5180	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)
Power density at predication frequency at 20 (cm)	0.061	(mW/cm^2)

#### **Measurement Result**

The predicted power density level at 20 cm is 0.061 mW/cm2.

This is below the uncontrolled exposure limit of 1 mW/cm2 at 5180MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or approval of this document is unquited and find the prior that the full terms of the low. pearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號 SGS Taiwan Ltd.



Report No.: ER/2015/80132 Issue Date: Oct. 16, 2015

Page: 7 of 13

## MPE Prediction (802.11n HT20 5250~5350)

MIMO gain= G+(10 logN)= 4.61+3.01= 7.62dBm

Average output power at antenna input terminal:	17.49	(dBm)
Average output power at antenna input terminal:	56.104798	(mW)
Duty cycle:	95.2	(%)
Maximum Pav :	53.411767	(mW)
Peak Antenna gain (Maximum):	7.62	(dBi)
Peak Antenna gain (linear):	5.7809605	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5320	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)
Power density at predication frequency at 20 (cm)	0.061	(mW/cm^2)

#### **Measurement Result**

The predicted power density level at 20 cm is 0.061 mW/cm2.

This is below the uncontrolled exposure limit of 1 mW/cm2 at 5320MHz.

# MPE Prediction (802.11n\_HT20 5470~5725)

#### MIMO gain= G+(10 logN)= 4.45+3.01= 7.46dBm

Average output power at antenna input terminal:	17.40	(dBm)
Average output power at antenna input terminal:	54.954087	(mW)
Duty cycle:	95.2	(%)
Maximum Pav :	52.316291	(mW)
Peak Antenna gain (Maximum):	7.46	(dBi)
Peak Antenna gain (linear):	5.5718575	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5700	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)
Power density at predication frequency at 20 (cm)	0.058	(mW/cm^2)

#### **Measurement Result**

The predicted power density level at 20 cm is 0.058 mW/cm2.

This is below the uncontrolled exposure limit of 1 mW/cm2 at 5700MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

家非方角就明 - 比較容易未僅對測減之樣必負責 | 阿時此樣必僅体留別之 - 本教者を無率之の音曲部引 - 木可能价模装。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號



Report No.:ER/2015/80132 Issue Date: Oct. 16, 2015

Page: 8 of 13

## MPE Prediction (802.11n\_HT20 5725~5850)

MIMO gain= G+(10 logN)= 3.42+3.01= 6.43dBm

Average output power at antenna input terminal:	17.30	(dBm)
Average output power at antenna input terminal:	53.70318	(mW)
Duty cycle:	95.2	(%)
Maximum Pav :	51.125427	(mW)
Peak Antenna gain (Maximum):	6.43	(dBi)
Peak Antenna gain (linear):	4.3954162	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5745	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)
Power density at predication frequency at 20 (cm)	0.045	(mW/cm^2)

#### **Measurement Result**

The predicted power density level at 20 cm is 0.045 mW/cm2.

This is below the uncontrolled exposure limit of 1 mW/cm2 at 5745MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留明天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and dispiration issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appropriate in languaged and the propresent of this document is unauthal and effenders may be prospected to the full lest extent of the language. pearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司 t (886-2) 2299-3279



Report No.:ER/2015/80132 Issue Date: Oct. 16, 2015

Page: 9 of 13

# 802.11n\_HT40M Max. output power

#### 802.11n HT40 MIMO

СН	Frequency	_	E POWER 3m)	TOTAL POWER	TOTAL POWER	` -		RESULT	
	(MHz)	CHAIN 0	CHAIN 1	(dBm)	(mW)				
38	5190	14.89	12.73	16.95	49.582		22.36		PASS
46	5230	15.58	12.99	17.49	56.048		22.36		PASS
54	5270	15.28	13.19	17.37	54.574	22.36	or 11+10log(B)	27.02	PASS
62	5310	15.18	13.07	17.26	53.238	22.36	or 11+10log(B)	27.04	PASS
102	5510	12.15	12.22	15.20	33.078	22.52	or 11+10log(B)	27.05	PASS
110	5550	14.28	14.44	17.37	54.589	22.52	or 11+10log(B)	27.03	PASS
134	5670	14.05	14.77	17.44	55.401	22.52	or 11+10log(B)	27.09	PASS
151	5755	10.47	11.26	13.89	24.509		29.57		PASS
159	5795	13.84	14.43	17.16	51.943		29.57		PASS

# MPE Prediction (802.11n\_HT40 5150~5250)

MIMO gain= G+(10 logN)= 4.61+3.01= 7.62dBm

Average output power at antenna input terminal:	17.49	(dBm)
Average output power at antenna input terminal:	56.104798	(mW)
Duty cycle:	90.4	(%)
Maximum Pav :	50.718737	(mW)
Peak Antenna gain (Maximum):	7.62	(dBi)
Peak Antenna gain (linear):	5.7809605	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5230	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)
Power density at predication frequency at 20 (cm)	0.058	(mW/cm^2)
Macauramant Daguit	•	•

#### **Measurement Result**

The predicted power density level at 20 cm is 0.058 mW/cm2.

This is below the uncontrolled exposure limit of 1 mW/cm2 at 5230MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

除非另有說明,比賴告結果僅對測試之樣品負責,同時此樣品性保留別大。本報告未經本公司者如評可,不可能价模製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號

www.tw.sgs.com



Report No.:ER/2015/80132 Issue Date: Oct. 16, 2015

Page: 10 of 13

## MPE Prediction (802.11n\_HT40 5250~5350)

MIMO gain= G+(10 logN)= 4.61+3.01= 7.62dBm

Average output power at antenna input terminal:	17.37	(dBm)
Average output power at antenna input terminal:	54.575786	(mW)
Duty cycle:	90.4	(%)
Maximum Pav :	49.336511	(mW)
Peak Antenna gain (Maximum):	7.62	(dBi)
Peak Antenna gain (linear):	5.7809605	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5270	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)
Power density at predication frequency at 20 (cm)	0.057	(mW/cm^2)
Measurement Result		

The predicted power density level at 20 cm is 0.057 mW/cm2.

This is below the uncontrolled exposure limit of 1 mW/cm2 at 5270MHz.

# MPE Prediction (802.11n\_HT40 5470~5725)

#### MIMO gain= G+(10 logN)= 4.45+3.01= 7.46dBm

Average output power at antenna input terminal:	17 44	(dDm)
		(dBm)
Average output power at antenna input terminal:	55.462571	(mW)
Duty cycle:		(%)
Maximum Pav :	50.138164	(mW)
Peak Antenna gain (Maximum):	7.46	(dBi)
Peak Antenna gain (linear):	5.5718575	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5670	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)
Power density at predication frequency at 20 (cm)	0.056	(mW/cm <sup>2</sup> )

#### **Measurement Result**

The predicted power density level at 20 cm is 0.056 mW/cm2.

This is below the uncontrolled exposure limit of 1 mW/cm2 at 5670MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

家非方角就明 小礼報告題未僅對測試之樣必負負 "四呼政保の理味噌如不。今報告不經本公司者即計可,不可能的模表。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號



Report No.:ER/2015/80132 Issue Date: Oct. 16, 2015

Page: 11 of 13

# MPE Prediction (802.11n\_HT40 5725~5850)

MIMO gain= G+(10 logN)= 3.42+3.01= 6.43dBm

Average output power at antenna input terminal:	17.16	(dBm)
Average output power at antenna input terminal:	51.9996	(mW)
Duty cycle:	90.4	(%)
Maximum Pav :	47.007638	(mW)
Peak Antenna gain (Maximum):	6.43	(dBi)
Peak Antenna gain (linear):	4.3954162	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5795	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)
Power density at predication frequency at 20 (cm)	0.041	(mW/cm^2)

#### **Measurement Result**

The predicted power density level at 20 cm is 0.041 mW/cm2.

This is below the uncontrolled exposure limit of 1 mW/cm2 at 5795MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留明天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and dispiration issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appropriate in languaged and the propresent of this document is unauthal and effenders may be prospected to the full lest extent of the language. pearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號 SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

t (886-2) 2299-3279



Report No.:ER/2015/80132 Issue Date: Oct. 16, 2015

Page: 12 of 13

## 802.11ac VHT80M Max. output power

#### 802.11ac VHT80 MIMO

<u>002:11:00_11:11:00_11:11:10</u>									
СН	Frequency		E POWER Bm)	TOTAL POWER	TOTAL POWER		REQUIRED LIMIT		RESULT
	(MHz)	CHAIN 0	CHAIN 1	(dBm)	(mW)		(dBm)		
42	5210	13.54	11.36	15.60	36.272		22.36		PASS
58	5290	13.7	10.75	15.48	35.327	22.36	or 11+10log(B)	30.06	PASS
106	5530	8.29	8.5	11.41	13.825	22.52	or 11+10log(B)	30.04	PASS
155	5775	9.54	10.4	13.00	19.960		29.57		PASS

## MPE Prediction (802.11ac\_VHT80 5150~5250)

MIMO gain= G+(10 logN)= 4.61+3.01= 7.62dBm

Average output power at antenna input terminal:	15.60	(dBm)
Average output power at antenna input terminal:	36.307805	(mW)
Duty cycle:	94	(%)
Maximum Pav :	34.129337	(mW)
Peak Antenna gain (Maximum):	7.62	(dBi)
Peak Antenna gain (linear):	5.7809605	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5210	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)
Power density at predication frequency at 20 (cm)	0.039	(mW/cm^2)
	•	•

#### Measurement Result

The predicted power density level at 20 cm is 0.039 mW/cm2.

This is below the uncontrolled exposure limit of 1 mW/cm2 at 5210MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

家非方角就明 - 比較容易未僅對測減之樣必負責 | 阿時此樣必僅体留別之 - 本教者を無率之の音曲部引 - 木可能价模装。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號



Report No.: ER/2015/80132 Issue Date: Oct. 16, 2015

Page: 13 of 13

## MPE Prediction (802.11ac\_VHT80 5250~5350)

MIMO gain= G+(10 logN)= 4.61+3.01= 7.62dBm

Average output power at antenna input terminal:	15.48	(dBm)
Average output power at antenna input terminal:	35.318317	(mW)
Duty cycle:	94	(%)
Maximum Pav :	33.199218	(mW)
Peak Antenna gain (Maximum):	7.62	(dBi)
Peak Antenna gain (linear):	5.7809605	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5290	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)
Power density at predication frequency at 20 (cm)	0.038	(mW/cm^2)
Measurement Result		

The predicted power density level at 20 cm is 0.038 mW/cm2.

This is below the uncontrolled exposure limit of 1 mW/cm2 at 5290MHz.

## MPE Prediction (802.11ac\_VHT80 5470~5725)

MIMO gain= G+(10 logN)= 4.45+3.01= 7.46dBm

Average output power at antenna input terminal:	11.41	(dBm)
Average output power at antenna input terminal:	13.835664	(mW)
Duty cycle:	94	(%)
Maximum Pav :	13.005524	(mW)
Peak Antenna gain (Maximum):	7.46	(dBi)
Peak Antenna gain (linear):	5.5718575	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5530	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)
Power density at predication frequency at 20 (cm)	0.014	(mW/cm^2)

#### **Measurement Result**

The predicted power density level at 20 cm is 0.014 mW/cm2.

This is below the uncontrolled exposure limit of 1 mW/cm2 at 5530MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號

f (886-2) 2298-0488

台灣檢驗科技股份有限公司 t (886-2) 2299-3279

www.tw.sqs.com



Report No.:ER/2015/80132 Issue Date: Oct. 16, 2015

Page: 14 of 13

## MPE Prediction (802.11ac\_VHT80 5725~5850)

MIMO gain= G+(10 logN)= 3.42+3.01= 6.43dBm

Average output power at antenna input terminal:	13.00	(dBm)
Average output power at antenna input terminal:	19.952623	(mW)
Duty cycle:	94	(%)
Maximum Pav :	18.755466	(mW)
Peak Antenna gain (Maximum):	6.43	(dBi)
Peak Antenna gain (linear):	4.3954162	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5775	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)
Power density at predication frequency at 20 (cm)	0.016	(mW/cm^2)

#### Measurement Result

The predicted power density level at 20 cm is 0.016 mW/cm2.

This is below the uncontrolled exposure limit of 1 mW/cm2 at 5775MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留明天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and dispiration issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appropriate in languaged and the propresent of this document is unauthal and effenders may be prospected to the full lest extent of the language. pearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號 SGS Taiwan Ltd.

台灣檢驗科技股份有限公司 t (886-2) 2299-3279