

| Prüfbericht-Nr.:<br>Test report no.: | CN25VS1Z 001  |  | Seite 35 von 36<br>Page 35 of 36 |
|--------------------------------------|---|--|----------------------------------|
| Absatz<br>Clause                     | Anforderungen - Prüfungen /<br>Requirements - Tests | Messergebnisse – Bemerkungen/<br>Measuring results - Remarks | Ergebnis<br>Result               |
|                                      |   |  |                                  |

## Appendix 5

### RF Exposure Information

FCC ID: YFA370410544

IC ID: 12260A-370410544

**Prüfbericht-Nr.:**  
Test report no.:

**CN25VS1Z 001**

Seite 36 von 36  
Page 36 of 36

| Absatz<br>Clause | Anforderungen - Prüfungen /<br>Requirements - Tests | Messergebnisse – Bemerkungen/<br>Measuring results - Remarks | Ergebnis<br>Result |
|------------------|---|--|--------------------|
|------------------|---|--|--------------------|

### Maximum Transmitter Power

| Frequency<br>(MHz) | Maximum peak field strength<br>(dB $\mu$ V/m) | Maximum transmitter power<br>(mW) |
|--------------------|---|-----------------------------------|
| 2446               | 94.4  | 0.8263                            |
| 2458               | 94.2  | 0.7891                            |
| 2474               | 92.4  | 0.5213                            |

Note: The maximum peak field strength was taken from table of “Subclause 15.249(a)/RSS-210 B.10(a) – Field Strength of Fundamental and Harmonics”.

### For FCC

According to KDB 447498 D01:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq$  5 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$   
 $\leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

### **Result:**

$$(0.8263/5) * \sqrt{2.446} = 0.258 < 3.0$$

$$(0.7891/5) * \sqrt{2.458} = 0.247 < 3.0$$

$$(0.5213/5) * \sqrt{2.474} = 0.164 < 3.0$$

**Conclusion:** No SAR is required.

### For ISED

According to table 11 in RSS-102 Issue 6, below exemption limit is applied:

Frequency: 2450 MHz

At separation distance of  $\leq$  5mm

Exemption limits: 3mW

### **Results:**

max. power of channel = 0.8263mW < 3mW

### **Conclusion:**

The maximum peak output power of the transmitter is less than the SAR evaluation exemption threshold and hence it complies with the RSS-102 RF exposure requirement.